

```

1  import components.map.Map;
9
10 /**
11  * {@code Program} represented the obvious way with implementations of primary
12  * methods.
13  *
14  * @convention [$this.name is an IDENTIFIER] and [$this.context is a CONTEXT]
15  *             and [$this.body is a BLOCK statement]
16  * @correspondence this = ($this.name, $this.context, $this.body)
17  *
18  * @author Krish Patel and Chloe Feller
19  *
20  */
21 public class Program2 extends ProgramSecondary {
22
23     /*
24     * Private members -----
25     */
26
27     /**
28     * The program name.
29     */
30     private String name;
31
32     /**
33     * The program context.
34     */
35     private Map<String, Statement> context;
36
37     /**
38     * The program body.
39     */
40     private Statement body;
41
42     /**
43     * Reports whether all the names of instructions in {@code c} are valid
44     * IDENTIFIERS.
45     *
46     * @param c
47     *         the context to check
48     * @return true if all instruction names are identifiers; false otherwise
49     * @ensures <pre>
50     *   allIdentifiers =
51     *     [all the names of instructions in c are valid IDENTIFIERS]
52     * </pre>
53     */
54     private static boolean allIdentifiers(Map<String, Statement> c) {
55         for (Map.Pair<String, Statement> pair : c) {
56             if (!Tokenizer.isIdentifier(pair.key())) {
57                 return false;
58             }
59         }
60         return true;
61     }
62
63     /**
64     * Reports whether no instruction name in {@code c} is the name of a

```

```

65     * primitive instruction.
66     *
67     * @param c
68     *     the context to check
69     * @return true if no instruction name is the name of a primitive
70     *     instruction; false otherwise
71     * @ensures <pre>
72     * noPrimitiveInstructions =
73     * [no instruction name in c is the name of a primitive instruction]
74     * </pre>
75     */
76     private static boolean noPrimitiveInstructions(Map<String, Statement> c) {
77         return !c.containsKey("move") && !c.containsKey("turnleft")
78             && !c.containsKey("turnright") && !c.containsKey("infect")
79             && !c.containsKey("skip");
80     }
81
82     /**
83     * Reports whether all the bodies of instructions in {@code c} are BLOCK
84     * statements.
85     *
86     * @param c
87     *     the context to check
88     * @return true if all instruction bodies are BLOCK statements; false
89     *     otherwise
90     * @ensures <pre>
91     * allBlocks =
92     * [all the bodies of instructions in c are BLOCK statements]
93     * </pre>
94     */
95     private static boolean allBlocks(Map<String, Statement> c) {
96         for (Map.Pair<String, Statement> pair : c) {
97             if (pair.value().kind() != Kind.BLOCK) {
98                 return false;
99             }
100         }
101         return true;
102     }
103
104     /**
105     * Creator of initial representation.
106     */
107     private void createNewRep() {
108
109         this.name = "Unnamed";
110         this.context = new Map1L<String, Statement>();
111         this.body = new Statement1();
112
113         // Make sure to use Statement1 from the library
114         // Use Map1L for the context if you want the asserts below to match
115     }
116
117
118     /**
119     * Constructors -----
120     */
121

```

```
122     /**
123      * No-argument constructor.
124      */
125     public Program2() {
126         this.createNewRep();
127     }
128
129     /**
130      * Standard methods -----
131      */
132
133     @Override
134     public final Program newInstance() {
135         try {
136             return this.getClass().getConstructor().newInstance();
137         } catch (ReflectiveOperationException e) {
138             throw new AssertionError(
139                 "Cannot construct object of type " + this.getClass());
140         }
141     }
142
143     @Override
144     public final void clear() {
145         this.createNewRep();
146     }
147
148     @Override
149     public final void transferFrom(Program source) {
150         assert source != null : "Violation of: source is not null";
151         assert source != this : "Violation of: source is not this";
152         assert source instanceof Program2 : ""
153             + "Violation of: source is of dynamic type Program2";
154         /*
155          * This cast cannot fail since the assert above would have stopped
156          * execution in that case: source must be of dynamic type Program2.
157          */
158         Program2 localSource = (Program2) source;
159         this.name = localSource.name;
160         this.context = localSource.context;
161         this.body = localSource.body;
162         localSource.createNewRep();
163     }
164
165     /**
166      * Kernel methods -----
167      */
168
169     @Override
170     public final void setName(String n) {
171         assert n != null : "Violation of: n is not null";
172         assert Tokenizer.isIdentifier(n) : ""
173             + "Violation of: n is a valid IDENTIFIER";
174
175         this.name = n;
176     }
177 }
178
```

```
179     @Override
180     public final String name() {
181
182         return this.name;
183     }
184
185
186     @Override
187     public final Map<String, Statement> newContext() {
188
189         Map<String, Statement> map = this.context.newInstance();
190
191         // Fix this line to return the result.
192         return map;
193     }
194
195     @Override
196     public final void swapContext(Map<String, Statement> c) {
197         assert c != null : "Violation of: c is not null";
198         assert c instanceof Map1L<?, ?> : "Violation of: c is a Map1L<?, ?>";
199         assert allIdentifiers(
200             c) : "Violation of: names in c are valid IDENTIFIERS";
201         assert noPrimitiveInstructions(c) : ""
202             + "Violation of: names in c do not match the names"
203             + " of primitive instructions in the BL language";
204         assert allBlocks(c) : "Violation of: bodies in c"
205             + " are all BLOCK statements";
206
207         Map<String, Statement> temp = c.newInstance();
208         temp.transferFrom(c);
209         c.transferFrom(this.context);
210         this.context.transferFrom(temp);
211     }
212
213
214     @Override
215     public final Statement newBody() {
216
217         return this.body.newInstance();
218     }
219
220
221     @Override
222     public final void swapBody(Statement b) {
223         assert b != null : "Violation of: b is not null";
224         assert b instanceof Statement1 : "Violation of: b is a Statement1";
225         assert b.kind() == Kind.BLOCK : "Violation of: b is a BLOCK statement";
226
227         Statement fakeBody = this.body.newInstance();
228         fakeBody.transferFrom(this.body);
229
230         this.body.transferFrom(b);
231         b.transferFrom(fakeBody);
232     }
233
234
235 }
```

Program2.java

Wednesday, November 1, 2023, 9:47 PM

236