
NSURLHandleClient Protocol Reference

[Cocoa](#) > [Networking](#)



2006-05-23



Apple Inc.
© 2006 Apple Computer, Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Cocoa, Mac, and Mac OS are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

NSURLHandleClient Protocol Reference 5

Overview 5

Tasks 5

Notification Methods 5

Appendix A Deprecated NSURLHandleClient Methods 7

Deprecated in Mac OS X v10.4 and later 7

URLHandle:resourceDataDidBecomeAvailable: 7

URLHandle:resourceDidFailLoadingWithReason: 7

URLHandleResourceDidBeginLoading: 8

URLHandleResourceDidCancelLoading: 8

URLHandleResourceDidFinishLoading: 8

Document Revision History 9

Index 11

NSURLHandleClient Protocol Reference

Adopted by	NSURL
Framework	/System/Library/Frameworks/Foundation.framework
Availability	Available in Mac OS X v10.0 and later.
Declared in	NSURLHandle.h

`NSURLHandleClient` is deprecated in Mac OS X v10.4 and later. Applications that are intended for deployment on Mac OS X v10.3 or later should use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.

Overview

This protocol defines the interface for clients to `NSURLHandle`.

Tasks

Notification Methods

- `URLHandle:resourceDataDidBecomeAvailable:` (page 7) **Deprecated in Mac OS X v10.4 and later**
Sent periodically by an URL handle when new resource data becomes available. (**Deprecated.** Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)
- `URLHandle:resourceDidFailLoadingWithReason:` (page 7) **Deprecated in Mac OS X v10.4 and later**
Sent when the URL handle failed to load resource data for some reason other than being canceled. (**Deprecated.** Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)
- `URLHandleResourceDidBeginLoading:` (page 8) **Deprecated in Mac OS X v10.4 and later**
Sent when an URL handle begins loading resource data. (**Deprecated.** Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)
- `URLHandleResourceDidCancelLoading:` (page 8) **Deprecated in Mac OS X v10.4 and later**
Sent when an URL handle has canceled loading resource data in response to a programmatic request. (**Deprecated.** Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)
- `URLHandleResourceDidFinishLoading:` (page 8) **Deprecated in Mac OS X v10.4 and later**
Sent when an URL handle finishes loading resource data. (**Deprecated.** Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

Deprecated NSURLHandleClient Methods

A method identified as deprecated has been superseded and may become unsupported in the future.

Deprecated in Mac OS X v10.4 and later

URLHandle:resourceDataDidBecomeAvailable:

Sent periodically by an URL handle when new resource data becomes available. (Deprecated in Mac OS X v10.4 and later. Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

```
- (void)URLHandle:(NSURLHandle *)sender resourceDataDidBecomeAvailable:(NSData *)newBytes
```

Parameters

sender

The URL handle sending the message.

newBytes

The newly available data.

Availability

Deprecated in Mac OS X v10.4 and later.

Declared In

NSURLHandle.h

URLHandle:resourceDidFailLoadingWithReason:

Sent when the URL handle failed to load resource data for some reason other than being canceled. (Deprecated in Mac OS X v10.4 and later. Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

```
- (void)URLHandle:(NSURLHandle *)sender resourceDidFailLoadingWithReason:(NSString *)reason
```

Parameters

sender

The URL handle sending the message.

reason

A human-readable, localized string describing why the load failed.

Availability

Deprecated in Mac OS X v10.4 and later.

Declared In

NSURLHandle.h

URLHandleResourceDidBeginLoading:

Sent when an URL handle begins loading resource data. (Deprecated in Mac OS X v10.4 and later. Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

- (void)URLHandleResourceDidBeginLoading:(NSURLHandle *)sender

Parameters

sender

The URL handle sending the message.

Availability

Deprecated in Mac OS X v10.4 and later.

Declared In

NSURLHandle.h

URLHandleResourceDidCancelLoading:

Sent when an URL handle has canceled loading resource data in response to a programmatic request. (Deprecated in Mac OS X v10.4 and later. Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

- (void)URLHandleResourceDidCancelLoading:(NSURLHandle *)sender

Parameters

sender

The URL handle sending the message.

Availability

Deprecated in Mac OS X v10.4 and later.

Declared In

NSURLHandle.h

URLHandleResourceDidFinishLoading:

Sent when an URL handle finishes loading resource data. (Deprecated in Mac OS X v10.4 and later. Use `NSURLConnection` or `NSURLDownload` instead; see *URL Loading System*.)

- (void)URLHandleResourceDidFinishLoading:(NSURLHandle *)sender

Parameters

sender

The URL handle sending the message.

Availability

Deprecated in Mac OS X v10.4 and later.

Declared In

NSURLHandle.h

Document Revision History

This table describes the changes to *NSURLHandleClient Protocol Reference*.

Date	Notes
2006-05-23	Updated to reflect that this class is deprecated in Mac OS X v10.4 and later.
	First publication of this content as a separate document.

REVISION HISTORY

Document Revision History

Index

U

`URLHandle:resourceDataDidBecomeAvailable:`
 protocol instance method [7](#)
`URLHandle:resourceDidFailLoadingWithReason:`
 protocol instance method [7](#)
`URLHandleResourceDidBeginLoading:` **protocol**
 instance method [8](#)
`URLHandleResourceDidCancelLoading:` **protocol**
 instance method [8](#)
`URLHandleResourceDidFinishLoading:` **protocol**
 instance method [8](#)