
CalAttendee Class Reference

[Cocoa](#) > [Apple Applications](#)



2007-07-08



Apple Inc.
© 2007 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Cocoa, Mac, Mac OS, and Objective-C are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

CalAttendee Class Reference 5

- Overview 5
- Tasks 5
 - Getting Properties 5
- Properties 6
 - address 6
 - commonName 6
 - status 6
- Constants 7
 - CalAttendee Status Strings 7

Document Revision History 9

Index 11

CalAttendee Class Reference

Inherits from	NSObject
Conforms to	NSCopying NSObject (NSObject)
Framework	/System/Library/Frameworks/CalendarStore.framework
Availability	Available in Mac OS X v10.5 and later.
Companion guide	Calendar Store Programming Guide
Declared in	CalAttendee.h

Overview

A `CalAttendee` object represents one attendee of a calendar event.

You do not create `CalAttendee` objects directly. Send attendees to a `CalEvent` object to get an array of `CalAttendee` objects.

Use the [status](#) (page 6) property to get the confirmation status of an attendee. Use the [commonName](#) (page 6) and [address](#) (page 6) properties to get more information about an attendee. You cannot modify the properties of a `CalAttendee` object—they are read-only.

Tasks

Getting Properties

[address](#) (page 6) *property*

An `NSURL` object that can be used to contact the attendee.

[commonName](#) (page 6) *property*

The user-entered name of the attendee.

[status](#) (page 6) *property*

The attendee's confirmation status.

Properties

For more about Objective-C properties, see “Properties” in *The Objective-C 2.0 Programming Language*.

address

An `NSURL` object that can be used to contact the attendee.

```
@property(readonly) NSURL *address;
```

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CalAttendee.h`

commonName

The user-entered name of the attendee.

```
@property(readonly) NSString *commonName;
```

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CalAttendee.h`

status

The attendee’s confirmation status.

```
@property(readonly) NSString *status;
```

Discussion

The value of this property is one of the constants in “[CalAttendee Status Strings](#)” (page 7).

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CalAttendee.h`

Constants

CalAttendee Status Strings

Describe an attendee's confirmation status of an event.

```
extern NSString * const CalAttendeeStatusNeedsAction;
extern NSString * const CalAttendeeStatusAccepted;
extern NSString * const CalAttendeeStatusDeclined;
extern NSString * const CalAttendeeStatusTentative;
```

Constants

`CalAttendeeStatusNeedsAction`

The status is not set for this attendee.

Available in Mac OS X v10.5 and later.

Declared in `CalAttendee.h`.

`CalAttendeeStatusAccepted`

The attendee accepted the invitation.

Available in Mac OS X v10.5 and later.

Declared in `CalAttendee.h`.

`CalAttendeeStatusDeclined`

The attendee declined the invitation.

Available in Mac OS X v10.5 and later.

Declared in `CalAttendee.h`.

`CalAttendeeStatusTentative`

The attendee's status is tentative.

Available in Mac OS X v10.5 and later.

Declared in `CalAttendee.h`.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CalendarStore/CalAttendee.h`

Document Revision History

This table describes the changes to *CalAttendee Class Reference*.

Date	Notes
2007-07-08	New document that describes the the class used to to confirm status and obtain more information about an attendee.

REVISION HISTORY

Document Revision History

Index

A

address **instance property** [6](#)

C

CalAttendee Status Strings [7](#)

CalAttendeeStatusAccepted **constant** [7](#)

CalAttendeeStatusDeclined **constant** [7](#)

CalAttendeeStatusNeedsAction **constant** [7](#)

CalAttendeeStatusTentative **constant** [7](#)

commonName **instance property** [6](#)

S

status **instance property** [6](#)