

---

# WebKit Constants Reference

[Cocoa](#) > [User Experience](#)



2008-10-15



Apple Inc.  
© 2008 Apple Inc.  
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.  
1 Infinite Loop  
Cupertino, CA 95014  
408-996-1010

Apple, the Apple logo, Cocoa, Mac, Mac OS, and Pages are trademarks of Apple Inc., registered in the United States and other countries.

Spotlight is a trademark of Apple Inc.

Java and all Java-based trademarks are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY,

MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

# Contents

## **WebKit Constants Reference 5**

---

Overview 5  
Constants 5  
    Enumerations 5  
    Global Variables 9  
    Notifications 11

## **Document Revision History 13**

---

## **Index 15**

---



# WebKit Constants Reference

---

<b>Framework:</b>	WebKit/WebKit.h
<b>Declared in</b>	WebKitErrors.h

## Overview

This document describes the types and constants found in the WebKit:

## Constants

### Enumerations

---

#### WebEditingDelegate—WebViewInsertAction

```
typedef enum {  
    WebViewInsertActionTyped,  
    WebViewInsertActionPasted,  
    WebViewInsertActionDropped,  
} WebViewInsertAction;
```

##### Discussion

These constants are described in `WebEditingDelegate`.

##### Availability

Available in Mac OS X v10.3.9 and later.

## WebPolicyDelegate—WebNavigationType

```
typedef enum {
    WebNavigationTypeLinkClicked,
    WebNavigationTypeFormSubmitted,
    WebNavigationTypeBackForward,
    WebNavigationTypeReload,
    WebNavigationTypeFormResubmitted,
    WebNavigationTypeOther
} WebNavigationType;
```

### Discussion

These constants are described in `WebPolicyDelegate`.

### Availability

Available in Mac OS X v10.3.9 and later.

## WebUIDelegate—WebDragDestinationAction

```
typedef enum {
    WebDragDestinationActionNone      = 0,
    WebDragDestinationActionDHTML     = 1,
    WebDragDestinationActionEdit      = 2,
    WebDragDestinationActionLoad      = 4,
    WebDragDestinationActionAny       = UINT_MAX
} WebDragDestinationAction;
```

### Discussion

These constants are described in `WebUIDelegate`.

### Availability

Available in Mac OS X v10.3.9 and later.

## WebUIDelegate—WebDragSourceAction

```
typedef enum {
    WebDragSourceActionNone           = 0,
    WebDragSourceActionDHTML          = 1,
    WebDragSourceActionImage          = 2,
    WebDragSourceActionLink           = 4,
    WebDragSourceActionSelection      = 8,
    WebDragSourceActionAny            = UINT_MAX
} WebDragSourceAction;
```

### Discussion

These constants are described in `WebUIDelegate`.

### Availability

Available in Mac OS X v10.3.9 and later.

## WebUIDelegate—WebMenuItemTag

```
enum {
    WebMenuItemTagOpenLinkInNewWindow=1,
    WebMenuItemTagDownloadLinkToDisk,
    WebMenuItemTagCopyLinkToClipboard,
    WebMenuItemTagOpenImageInNewWindow,
    WebMenuItemTagDownloadImageToDisk,
    WebMenuItemTagCopyImageToClipboard,
    WebMenuItemTagOpenFrameInNewWindow,
    WebMenuItemTagCopy,
    WebMenuItemTagGoBack,
    WebMenuItemTagGoForward,
    WebMenuItemTagStop,
    WebMenuItemTagReload,
    WebMenuItemTagCut,
    WebMenuItemTagPaste,
    WebMenuItemTagSpellingGuess,
    WebMenuItemTagNoGuessesFound,
    WebMenuItemTagIgnoreSpelling,
    WebMenuItemTagLearnSpelling,
    WebMenuItemTagOther,
    WebMenuItemTagSearchInSpotlight,
    WebMenuItemTagSearchWeb,
    WebMenuItemTagLookUpInDictionary,
    WebMenuItemTagOpenWithDefaultApplication,
    WebMenuItemPDFActualSize,
    WebMenuItemPDFZoomIn,
    WebMenuItemPDFZoomOut,
    WebMenuItemPDFAutoSize,
    WebMenuItemPDFSinglePage,
    WebMenuItemPDFFacingPages,
    WebMenuItemPDFContinuous,
    WebMenuItemPDFNextPage,
    WebMenuItemPDFPreviousPage,
};
```

### Discussion

These constants are described in `WebUIDelegate`.

### Availability

`WebMenuItemTagGoBack`, `WebMenuItemTagGoForward`, `WebMenuItemTagStop`, and `WebMenuItemTagReload` **available in Mac OS X v10.3.9 and later.**

## WebKit Policy Errors

```
typedef enum {
    WebKitErrorCannotShowMIMETYPE = 100,
    WebKitErrorCannotShowURL = 101,
    WebKitErrorFrameLoadInterruptedByPolicyChange = 102,
};
```

### Constants

**WebKitErrorCannotShowMIMETYPE**  
 Indicates that a MIME type is not supported.  
 Available in Mac OS X v10.2 and later.  
 Declared in `WebKitErrors.h`.

**WebKitErrorCannotShowURL**  
 Indicates a failure in changing a location.  
 Available in Mac OS X v10.2 and later.  
 Declared in `WebKitErrors.h`.

**WebKitErrorFrameLoadInterruptedByPolicyChange**  
 Indicates that a frame load was interrupted by a policy change.  
 Available in Mac OS X v10.2 and later.  
 Declared in `WebKitErrors.h`.

### Discussion

These errors occur when applying policy decisions.

## WebKit Plug-in and Java Errors

```
typedef enum {
    WebKitErrorCannotFindPlugIn = 200,
    WebKitErrorCannotLoadPlugIn = 201,
    WebKitErrorJavaUnavailable = 202,
};
```

### Constants

**WebKitErrorCannotFindPlugIn**  
 Indicates a plug-in could not be found.  
 Available in Mac OS X v10.3 and later.  
 Declared in `WebKitErrors.h`.

**WebKitErrorCannotLoadPlugIn**  
 Indicates a plug-in could not be loaded.  
 Available in Mac OS X v10.3 and later.  
 Declared in `WebKitErrors.h`.

**WebKitErrorJavaUnavailable**  
 Indicates that Java is unavailable.  
 Available in Mac OS X v10.2 and later.  
 Declared in `WebKitErrors.h`.

### Discussion

These errors occur when loading pages containing plug-in or Java content.



## Global Variables

---

### WebArchive—Pasteboard Types

```
extern NSString *WebArchivePboardType;
```

#### Discussion

This constant is described in `WebArchive`.

### WebHistory—User Info Dictionary Key

```
extern NSString *WebHistoryItemsKey;
```

#### Discussion

This constant is described in `WebHistory`.

### WebPlugInViewFactory—Plug-in View Dictionary Keys

```
extern NSString *WebPlugInBaseURLKey;  
extern NSString *WebPlugInAttributesKey;  
extern NSString *WebPlugInContainerKey;  
extern NSString *WebPlugInContainingElementKey;
```

#### Discussion

These constants are defined in `WebPlugInViewFactory`.

### WebPolicyDelegate—Action Dictionary Keys

```
extern NSString *WebActionNavigationTypeKey;  
extern NSString *WebActionElementKey;  
extern NSString *WebActionButtonKey;  
extern NSString *WebActionModifierFlagsKey;  
extern NSString *WebActionOriginalURLKey;
```

#### Discussion

These constants are defined in `WebPolicyDelegate`.

## WebView—Element Dictionary Keys

```
extern NSString *WebElementDOMNodeKey;
extern NSString *WebElementFrameKey;
extern NSString *WebElementImageAltStringKey;
extern NSString *WebElementImageKey;
extern NSString *WebElementImageRectKey;
extern NSString *WebElementImageURLKey;
extern NSString *WebElementIsSelectedKey;
extern NSString *WebElementLinkURLKey;
extern NSString *WebElementLinkTargetFrameKey;
extern NSString *WebElementLinkTitleKey;
extern NSString *WebElementLinkLabelKey;
```

### Discussion

These constants are defined in `WebView`.

## Other WebKit Errors

```
extern NSString *WebKitErrorDomain;
extern NSString * const WebKitErrorMIMETYPEKey;
extern NSString * const WebKitErrorPlugInNameKey;
extern NSString * const WebKitErrorPlugInPageURLStringKey;
```

### Constants

`WebKitErrorDomain`

A string used by `NSError` to indicate that the error was originated by a WebKit class.

Available in Mac OS X v10.2 and later.

Declared in `WebKitErrors.h`.

`WebKitErrorMIMETYPEKey`

A dictionary key whose value is a string of the `TYPE` attribute.

Available in Mac OS X v10.2 and later.

Declared in `WebKitErrors.h`.

`WebKitErrorPlugInNameKey`

A dictionary key whose value is a string containing the plug-in's name.

Available in Mac OS X v10.2 and later.

Declared in `WebKitErrors.h`.

`WebKitErrorPlugInPageURLStringKey`

A dictionary key whose value is a URL string of the `PLUGINSPAGE` attribute.

Available in Mac OS X v10.2 and later.

Declared in `WebKitErrors.h`.

### Discussion

These errors occur while loading content.

## Notifications

---

### WebHistory Notification Names

```
NSString *WebHistoryItemsAddedNotification;  
NSString *WebHistoryItemsRemovedNotification;  
NSString *WebHistoryAllItemsRemovedNotification;  
NSString *WebHistoryLoadedNotification;  
NSString *WebHistorySavedNotification;
```

#### Discussion

These notifications are described in *WebHistory Class Reference*.

### WebPreferences Notification Names

```
NSString *WebPreferencesChangedNotification;
```

#### Discussion

This notification is described in *WebPreferences Class Reference*.

### WebView Notification Names

```
NSString *WebViewDidBeginEditingNotification;  
NSString *WebViewDidChangeNotification;  
NSString *WebViewDidEndEditingNotification;  
NSString *WebViewDidChangeTypingStyleNotification;  
NSString *WebViewDidChangeSelectionNotification;  
NSString *WebViewProgressEstimateChangedNotification;  
NSString *WebViewProgressFinishedNotification;  
NSString *WebViewProgressStartedNotification;
```

#### Discussion

These notifications are described in *WebView Class Reference*.



# Document Revision History

---

This table describes the changes to *WebKit Constants Reference*.

Date	Notes
2008-10-15	Minor edits throughout.
2008-06-19	Updated for Mac OS X v10.5.
2006-05-23	First publication of this content as a separate document.



# Index

---

## O

---

Other WebKit Errors [10](#)

## W

---

WebArchive—Pasteboard Types [9](#)  
WebEditingDelegate—WebViewInsertAction [5](#)  
WebHistory Notification Names [11](#)  
WebHistory—User Info Dictionary Key [9](#)  
WebKit Plug-in and Java Errors [8](#)  
WebKit Policy Errors [8](#)  
WebKitErrorCannotFindPlugIn constant [8](#)  
WebKitErrorCannotLoadPlugIn constant [8](#)  
WebKitErrorCannotShowMimeType constant [8](#)  
WebKitErrorCannotShowURL constant [8](#)  
WebKitErrorDomain constant [10](#)  
WebKitErrorFrameLoadInterruptedByPolicyChange  
constant [8](#)  
WebKitErrorJavaUnavailable constant [8](#)  
WebKitErrorMimeTypeKey constant [10](#)  
WebKitErrorPlugInNameKey constant [10](#)  
WebKitErrorPlugInPageURLStringKey constant [10](#)  
WebPlugInViewFactory—Plug-in View Dictionary Keys [9](#)  
WebPolicyDelegate—Action Dictionary Keys [9](#)  
WebPolicyDelegate—WebNavigationType [6](#)  
WebPreferences Notification Names [11](#)  
WebUIDelegate—WebDragDestinationAction [6](#)  
WebUIDelegate—WebDragSourceAction [6](#)  
WebUIDelegate—WebMenuItemTag [7](#)  
WebView Notification Names [11](#)  
WebView—Element Dictionary Keys [10](#)