NSNibOutletConnector Class Reference

Cocoa > Resource Management

2007-01-31

Apple Inc.
© 2007 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, Cocoa, Mac, and Mac OS are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

NSNibOutletConnector Class Reference 5

Overview 5
Tasks 5
  Establishing a Connection 5
Instance Methods 5
  establishConnection 5

Document Revision History 7

Index 9

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

NSNibOutletConnector Class Reference

Inherits from	NSNibConnector : NSObject
Conforms to	NSCoding (NSNibConnector) NSObject (NSObject)
Framework	/System/Library/Frameworks/AppKit.framework
Availability	Available in Mac OS X v10.0 and later.
Companion guide	Resource Programming Guide
Declared in	NSNibOutletConnector.h

Overview

This class manages an outlet connection in Interface Builder. The label is of the form `"value"`. If the source contains a method of the form `setValue:`, then that method is called with the destination as the argument. Otherwise, if the label is the name of an instance variable in the source, then that instance variable is set to the destination.

Tasks

Establishing a Connection

`- establishConnection` (page 5)
Establishes an outlet connection.

Instance Methods

establishConnection

Establishes an outlet connection.

```
- (void)establishConnection
```


2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

Discussion
If the label is a method name of the form `set`*`Value`*`:` (where *`Value`* can be anything), that method is called on the source object. The parameter passed to that method is the destination object.

If the label contains the name of an outlet, this method sets the value of the outlet to the destination object. The outlet must specify an instance variable in the source object.

Availability
Available in Mac OS X v10.0 and later.

See Also
- `setSource:` (`NSNibConnector`)
- `setDestination:` (`NSNibConnector`)
- `setLabel:` (`NSNibConnector`)

Declared In
`NSNibOutletConnector.h`

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

Document Revision History

This table describes the changes to *NSNibOutletConnector Class Reference*.

Date	Notes
2007-01-31	Added links to NSNibConnector methods. Updated for Mac OS X v10.5.
2006-05-23	First publication of this content as a separate document.

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

Document Revision History

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.

Index

E

establishConnection instance method 5

2007-01-31 | © 2007 Apple Inc. All Rights Reserved.