CONFIDENTIAL

External exposure audit

Example Corp (fictional sample)

Prepared for	Example Corp (fictional sample)
Prepared by	Sample Auditor (placeholder)
Contact	audits@example.org
Date	2026-11-08
Engagement reference	SAMPLE-001
Scope	example.com, example.net
Bundle SHA-256	`8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa`

The interactive technical annex (technical-annex.html) shows every name, finding and record with its evidence.

Contents

1. Authorisation
2. Executive summary
3. Findings and remediation, in priority order
4. Asset inventory
5. What was not tested
6. Methodology
7. Glossary
8. Evidence appendix

Authorisation

This review was carried out under a written authorisation from Example Corp (fictional sample), signed by Sample Signatory (fictional) (CISO (fictional)), in force from 2026-10-01 to 2026-12-31, for the domains listed above and for this purpose: Sample report made from the planted lab fixture; not a real engagement

The authorisation (its SHA-256 02ccc7d8a905c94f0fa87b4c32c06634801ff45b2d0071f6ec58a2cf814706a1) was recorded when this report was made; the scan itself was run before it was recorded, so the signed bundle does not contain it.

Permitted activity: passive collection of public records only.

Executive summary

1. Sample Auditor (placeholder) reviewed the public internet footprint of Example Corp (fictional sample) (example.com, example.net) on 2026-10-20, using public records only: no scanning, no login attempts, no exploitation.
2. The review confirmed 17 internet-facing names under these domains that resolve in public DNS or appear in a recent certificate. (17 records)
3. Third-party lists mention 1 more name that public DNS does not confirm; it is kept as unconfirmed and not counted as findings. (1 record)
4. 23 issues were found: 3 high, 10 medium, 8 low and 2 informational. [R1, R2, R3, R4, R5, R6 …] (64 records)
5. Priority 1: CNAME to a claimable service that no longer exists (shop.example.com, demo.pages.example.org). Delete the CNAME record, or re-create the resource at the service so the name is yours again. [R1] (2 records)
6. Priority 2: Domain registration has expired (example.net). Renew the domain at once, or confirm that it is meant to lapse and remove what depends on it. [R2] (1 record)
7. Priority 3: SPF record authorises every sender (example.com). End the record with -all (or ~all while rolling out) and list only the senders you use. [R3] (1 record)
8. 1 of 14 public sources did not answer in full during the review; what they hold is not reflected here.
9. Every statement about the client's systems cites the records it rests on, sealed in a signed bundle that the client or their auditor can verify offline.

Each numbered statement cites the evidence records it rests on (appendix).

Findings and remediation, in priority order

Priority	Severity	Finding	Affected	Effort (estimate)
R1	High	CNAME to a claimable service that no longer exists	shop.example.com, demo.pages.example.org	Low
R2	High	Domain registration has expired	example.net	Low
R3	High	SPF record authorises every sender	example.com	Low
R4	Medium	Domain registration expires within 30 days	example.com	Low
R5	Medium	More than one SPF record	multi.example.com	Low
R6	Medium	SPF record takes no position on unlisted senders	neutral.example.com	Low
R7	Medium	SPF record has no default result	noall.example.com	Low
R8	Medium	Mail domain without a DMARC record	example.com	Medium
R9	Medium	Mail domain without a DMARC record	oldmail.example.com	Medium
R10	Medium	SPF record needs more than ten DNS lookups	bulk.example.com	Medium
R11	Medium	CNAME to a host that does not exist	legacy.example.com, gone.example.org	Low
R12	Medium	CNAME to a host that no longer exists, at a service known for takeovers	docs.example.com, team.sites.example.org	Low
R13	Medium	A database, remote-administration or file-sharing port is open to the internet	192.0.2.50	Medium
R14	Low	No CAA record at a zone apex	example.net	Low
R15	Low	No CAA record at a zone apex	example.com	Low
R16	Low	DMARC policy is monitoring only	sales.example.com	Medium
R17	Low	SPF record soft-fails unlisted senders	soft.example.com	Medium

Priority	Severity	Finding	Affected	Effort (estimate)
R18	Low	All names depend on one DNS provider	example.com, example.net	High
R19	Low	Several names depend on one CDN or hosting provider	app1.example.com, app2.example.com, app4.example.com, bulk.example.com …	High
R20	Low	Registry and DNS disagree about the name servers	example.com	Low
R21	Low	Name that looks like a forgotten test or staging system	dev.example.com	Medium
R22	Info	A certificate or archive names a host that DNS does not know	ghost.example.com	Low
R23	Info	A gap in a numbered series of names	app1.example.com, app2.example.com, app4.example.com	Low

Effort is the auditor's estimate of the work to fix, not a measurement.

R1 · CNAME to a claimable service that no longer exists High

Affected	shop.example.com, demo.pages.example.org
What the evidence shows	shop.example.com is an alias (CNAME) of demo.pages.example.org, and the address lookup for shop.example.com returned NXDOMAIN, so the target does not exist. demo.pages.example.org matches the takeover fingerprint lab-pages (Example Pages, rated vulnerable, shown by NXDOMAIN).
Remediation	Delete the CNAME record, or re-create the resource at the service so the name is yours again. Check what else (cookies, OAuth redirects, SPF) trusted the name.
Effort (estimate)	Low
Informational mapping	OWASP WSTG-CONF-10; OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)*
Evidence	`c4d48be7276d`, `bcee36275bf0`

R2 · Domain registration has expired High

Affected	example.net
What the evidence shows	RDAP lists the expiration of example.net as 2026-10-15T20:16:36Z; the data was collected 2026-10-20T20:16:37+00:00, after that date.
Remediation	Renew the domain at once, or confirm that it is meant to lapse and remove what depends on it.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.5.30 *(unverified)*
Evidence	`08f6bf5b1661`

R3 · SPF record authorises every sender High

Affected	example.com
What the evidence shows	example.com publishes the SPF record "v=spf1 include:spf.example.org +all", which ends with "+all".
Remediation	End the record with -all (or ~all while rolling out) and list only the senders you use.
Effort (estimate)	Low
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`6389b626d207`

R4 · Domain registration expires within 30 days Medium

Affected	example.com
What the evidence shows	RDAP lists the expiration of example.com as 2026-11-09T20:16:36Z; the data was collected 2026-10-20T20:16:36+00:00, 20 day(s) before it.
Remediation	Renew the domain and enable auto-renewal.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.5.30 *(unverified)*
Evidence	`756a47891001`

R5 · More than one SPF record Medium

Affected	multi.example.com
What the evidence shows	multi.example.com publishes 2 TXT records that start with v=spf1.
Remediation	Merge the records into one.
Effort (estimate)	Low
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`cf9ad5431714`

R6 · SPF record takes no position on unlisted senders Medium

Affected	neutral.example.com
What the evidence shows	neutral.example.com publishes the SPF record "v=spf1 mx ?all", which ends with "?all".
Remediation	End the record with -all (or ~all while rolling out).
Effort (estimate)	Low
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`067fb14624bb`

R7 · SPF record has no default result Medium

Affected	noall.example.com
What the evidence shows	noall.example.com publishes the SPF record "v=spf1 mx", which has no all mechanism and no redirect.
Remediation	End the record with -all (or ~all while rolling out).
Effort (estimate)	Low
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`ec591befd7d6`

R8 · Mail domain without a DMARC record Medium

Affected	example.com
What the evidence shows	example.com has MX records, and the TXT lookup for _dmarc.example.com returned NXDOMAIN.
Remediation	Publish a DMARC record at _dmarc.<domain>, starting with p=none and reporting addresses, then move to quarantine and reject.
Effort (estimate)	Medium
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`f371732585dd`, `80978d4d5f04`

R9 · Mail domain without a DMARC record Medium

Affected	oldmail.example.com
What the evidence shows	oldmail.example.com has MX records, and the TXT lookup for _dmarc.oldmail.example.com returned NXDOMAIN.
Remediation	Publish a DMARC record at _dmarc.<domain>, starting with p=none and reporting addresses, then move to quarantine and reject.
Effort (estimate)	Medium
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`0fdfa5c4feac`, `89ed0ed79d51`

R10 · SPF record needs more than ten DNS lookups Medium

Affected	bulk.example.com
What the evidence shows	bulk.example.com publishes the SPF record "v=spf1 include:s1.example.org include:s2.example.org include:s3.example.org include:s4.example.org include:s5.example.org include:s6.example.org include:s7.example.org include:s8.example.org includ...", whose own terms contain 11 mechanisms that cause a DNS lookup.
Remediation	Remove unused includes, replace includes with ip4/ip6 ranges, or flatten the record.
Effort (estimate)	Medium
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`b26f8720e480`

R11 · CNAME to a host that does not exist Medium

Affected	legacy.example.com, gone.example.org
What the evidence shows	legacy.example.com is an alias (CNAME) of gone.example.org, and the address lookup for legacy.example.com returned NXDOMAIN, so the target does not exist.
Remediation	Delete the CNAME record if the target is no longer used, or restore the target.
Effort (estimate)	Low
Informational mapping	OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)*
Evidence	`8388b89816b7`, `09d37eedacce`

R12 · CNAME to a host that no longer exists, at a service known for takeovers Medium

Affected	docs.example.com, team.sites.example.org
What the evidence shows	docs.example.com is an alias (CNAME) of team.sites.example.org, and the address lookup for docs.example.com returned NXDOMAIN, so the target does not exist. team.sites.example.org matches the takeover fingerprint lab-sites (Example Sites, rated vulnerable, shown by http-fingerprint).
Remediation	Delete the CNAME record or re-create the resource at the service. In an authorised assessment, confirm with an active check.
Effort (estimate)	Low
Informational mapping	OWASP WSTG-CONF-10; OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)*
Evidence	`64cda6f69dad`, `77a939695ea9`

R13 · A database, remote-administration or file-sharing port is open to the internet

Medium

Affected	192.0.2.50
What the evidence shows	Shodan InternetDB lists these open ports on 192.0.2.50: 6379 (Redis). InternetDB reports an earlier scan by Shodan, not a check made now.
Remediation	Confirm with the owner whether the port is open now; if it is, close it at the firewall or restrict it to known addresses, and require authentication.
Effort (estimate)	Medium
How established	Reported earlier by a third party (Shodan InternetDB); not checked now.
Informational mapping	NIS2 Art. 21(2)(e); CIS 4.1; CIS 7.6; CIS 12.1; OWASP A05:2021; KVKK Art. 12(1); ISO 27001 A.8.20 *(unverified)*; ISO 27001 A.8.8 *(unverified)*
Evidence	`22f8bc15441d`

R14 · No CAA record at a zone apex Low

Affected	example.net
What the evidence shows	example.net has name server records and the CAA lookup for example.net returned no record.
Remediation	Publish CAA records naming the certificate authorities you use.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(h); CIS 4.1; ISO 27001 A.8.24 *(unverified)*
Evidence	`fb41a659ee47`, `b343a685a88e`

R15 · No CAA record at a zone apex Low

Affected	example.com
What the evidence shows	example.com has name server records and the CAA lookup for example.com returned no record.
Remediation	Publish CAA records naming the certificate authorities you use.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(h); CIS 4.1; ISO 27001 A.8.24 *(unverified)*
Evidence	`fb32292266be`, `59edc5a1e9ef`

R16 · DMARC policy is monitoring only Low

Affected	sales.example.com
What the evidence shows	_dmarc.sales.example.com publishes "v=DMARC1; p=none; rua=mailto:dmarc@example.com", whose policy is p=none.
Remediation	Move to p=quarantine and then p=reject once the reports show only legitimate senders.
Effort (estimate)	Medium
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`e38fa3477046`

R17 · SPF record soft-fails unlisted senders Low

Affected	soft.example.com
What the evidence shows	soft.example.com publishes the SPF record "v=spf1 mx ~all", which ends with "~all".
Remediation	Move to -all once the sender list is complete, and publish a DMARC policy.
Effort (estimate)	Medium
Informational mapping	CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)*
Evidence	`85cfb2338240`

R18 · All names depend on one DNS provider Low

Affected	example.com, example.net
What the evidence shows	The name servers of example.com, example.net all belong to Example DNS; 22 in-scope name(s) sit in these zones.
Remediation	Consider a secondary DNS provider on a different network, and protect the account with strong authentication.
Effort (estimate)	High
Informational mapping	NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(d); CIS 15.1; ISO 27001 A.5.19 *(unverified)*; ISO 27001 A.5.23 *(unverified)*; ISO 27001 A.5.30 *(unverified)*
Evidence	`59edc5a1e9ef`, `b343a685a88e`

R19 · Several names depend on one CDN or hosting provider Low

Affected	app1.example.com, app2.example.com, app4.example.com, bulk.example.com, dev.example.com, example.com, example.net, mail.example.com, multi.example.com, neutral.example.com
What the evidence shows	17 in-scope names are served through Example Edge (app1.example.com, app2.example.com, app4.example.com, bulk.example.com, dev.example.com, example.com, example.net, mail.example.com, multi.example.com, neutral.example.com).
Remediation	Know the provider's outage and incident process; consider whether critical names need an alternative.
Effort (estimate)	High
Informational mapping	NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(d); CIS 15.1; ISO 27001 A.5.19 *(unverified)*; ISO 27001 A.5.23 *(unverified)*; ISO 27001 A.5.30 *(unverified)*
Evidence	`01e0d9f756c8`, `0ca4114e8c6a`, `0f03aa66fc72`, `1dab89720a1b`, `24d86e32684a`, `31618bb7c7a0`, `4183e499e07d`, `454b918b6e9c` +26

R20 · Registry and DNS disagree about the name servers Low

Affected	example.com
What the evidence shows	For example.com, only RDAP lists ns9.old.example.net and only the zone's NS records list ns2.dns.example.net.
Remediation	Make the registry delegation and the zone's NS records identical.
Effort (estimate)	Low
Informational mapping	CIS 4.1; OWASP A05:2021; ISO 27001 A.8.9 *(unverified)*
Evidence	`756a47891001`, `59edc5a1e9ef`

R21 · Name that looks like a forgotten test or staging system Low

Affected	dev.example.com
What the evidence shows	dev.example.com contains the label "dev" and resolves to 192.0.2.50.
Remediation	Confirm the system is still needed and maintained; otherwise remove the DNS record and the system.
Effort (estimate)	Medium
Informational mapping	NIS2 Art. 21(2)(i); CIS 1.1; CIS 7.6; OWASP A05:2021; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.8.8 *(unverified)*
Evidence	`4af45bdc672e`

R22 · A certificate or archive names a host that DNS does not know Info

Affected	ghost.example.com
What the evidence shows	ghost.example.com is named by crtsh, wayback, and the address lookup for ghost.example.com returned NXDOMAIN.
Remediation	Check whether the name is still referenced (certificates, links, configuration) and whether DNS or the certificate should be cleaned up.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*
Evidence	`2e29c591d4c8`, `c6db47b4d3e2`, `f9b081024eae`

R23 · A gap in a numbered series of names Info

Affected	app1.example.com, app2.example.com, app4.example.com
What the evidence shows	3 names follow the pattern app<number>.example.com (app1.example.com, app2.example.com, app4.example.com); the number(s) 3 are missing, for example app3.example.com.
Remediation	Check whether the missing number is a retired or unlisted system.
Effort (estimate)	Low
Informational mapping	NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*
Evidence	`33272b595e75`, `35f2254265c0`, `eb6969220261`

> The framework references are an informational mapping, not a certification, an audit opinion or a legal conclusion. References marked (unverified), including every ISO/IEC 27001 reference, could not be read at an authoritative public source and must be checked against the framework itself.

Asset inventory

Names that public DNS resolves or that a certificate dated in the last 90 days names (verified). Names that only third-party lists mention are counted below, not listed here.

Name	Addresses	Providers	Networks	Evidence
example.com	192.0.2.1	Example DNS (dns), Example Edge (cdn)		ed67e58c5cf5
example.net	198.51.100.10	Example DNS (dns), Example Edge (cdn)		7eaf7a6e4ce1
app1.example.com	192.0.2.61	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		72cdd8aa0540
app2.example.com	192.0.2.62	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		affd6716b827
app4.example.com	192.0.2.64	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		5936a350f877
bulk.example.com	192.0.2.75	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		45662725b4f3
dev.example.com	192.0.2.50	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		4af45bdc672e
mail.example.com	192.0.2.25	Example DNS (dns), Example Edge (cdn)		b66a08b9fea4
multi.example.com	192.0.2.74	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		ff472dc63ced
neutral.example.com	192.0.2.71	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		ff153d7b83a7
noall.example.com	192.0.2.73	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		8b51c626a4c3
oldmail.example.com	192.0.2.77	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		fc3339d17634
sales.example.com	192.0.2.76	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		0f03aa66fc72
soft.example.com	192.0.2.72	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		8fae92b68fbb
www.example.com	192.0.2.10	Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca)		6cf07b70fe54

Name	Addresses	Providers	Networks	Evidence
ns1.dns.example.net	198.51.100.53	Example DNS (dns), Example Edge (cdn)		7f5ace880243
ns2.dns.example.net	198.51.100.54	Example DNS (dns), Example Edge (cdn)		1dab89720a1b

Unconfirmed names (only lists mention them): 1. Retired names (DNS says they do not exist): 4. Covered only by a wildcard record: 0.

What was not tested

This review is passive. It did not:

- scan ports or services, or send any request to the client's systems other than ordinary DNS lookups of their names;
- test web applications, APIs, logins or authentication;
- attempt to exploit, confirm or reproduce any weakness (a takeover candidate is reported, never claimed);
- look at internal networks, endpoints, cloud accounts or source code;
- look up any person, e-mail address or credential, or use breach data;
- test phishing resistance, physical security or staff awareness.

Public sources asked and how they answered during the review:

Source	Outcome
`asn`	answered
`certspotter`	answered
`commoncrawl`	answered
`crtsh`	answered
`dns`	answered
`hackertarget`	answered
`internetdb`	answered
`mnemonic`	answered
`rdap`	answered
`ripestat`	failed — ModuleError: ripestat returned HTTP 404
`subdomaincenter`	answered
`urlscan`	answered
`wayback`	answered
`wildcard`	answered

> Names that no certificate log, archive or aggregator has ever seen cannot appear in this report. A finding reflects public records at the time they were collected; the client's systems may have changed since.

Methodology

Scrutator asked public sources what they know about the domains in scope: certificate transparency logs, DNS, registration data (RDAP), routing data, web archives and passive-DNS and name aggregators. It did not contact the client's systems except through ordinary DNS lookups.

Every answer was stored unchanged as an evidence record addressed by its SHA-256 hash. Findings and risks are derived from those records by deterministic rules; a risk cannot exist without the records it cites. A name is verified when DNS resolves it or a recent certificate names it, and only claimed when only a list mentions it.

The records, the derived report and a hash-chained log of every lookup were sealed in a proof bundle and signed with an Ed25519 key. The bundle can be checked by anyone, offline, with the commands in the appendix.

Sources used: asn, certspotter, commoncrawl, crtsh, dns, hackertarget, internetdb, mnemonic, rdap, ripestat, subdomaincenter, urlscan, wayback, wildcard.

Tool scrutator 0.7.0; risk rules 5; knowledge packs 44bbd66959eeacfc; scan started 2026-10-20T20:16:36+00:00; report made 2026-11-08T12:39:56+00:00.

Glossary

DNS
The internet's directory: it turns names such as www.example.com into addresses.

CNAME (alias)
A DNS record saying a name is another name. If the target disappears, whoever claims it may control the alias.

Subdomain takeover
Taking control of a name whose alias points at a cloud resource that no longer exists.

SPF
A DNS record listing which servers may send e-mail for a domain.

DMARC
A DNS record telling receivers what to do with mail that fails SPF/DKIM checks, and where to report it.

CAA
A DNS record naming the certificate authorities allowed to issue certificates for a domain.

Certificate transparency
Public logs of every TLS certificate issued; they reveal names a company uses.

RDAP
The modern registration database for domains and IP networks (successor of WHOIS).

Verified / claimed
Verified: DNS or a recent certificate supports the name. Claimed: only a list mentions it.

Evidence record
The unchanged answer of a source, identified by its SHA-256 hash.

Proof bundle
A signed file with the report, every evidence record and the lookup log; any change is detected.

SHA-256
A fingerprint of a file: changing one bit changes it completely.

Ed25519
The signature scheme used to seal the bundle; the key fingerprint identifies the signer.

Evidence appendix

This report was made from the signed proof bundle below. Give the client the bundle with this report; it holds every record this report cites.

Bundle file	`proof.scrutator`
Bundle SHA-256	`8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa`
Signing key fingerprint	`b8dc88a33a0016aea35a4b45d4bf6c944bf2a7293905daaeaf001239d8eea6ca`
Evidence records in the bundle	83

How the client or their auditor verifies this report offline, in three commands

1. Check that the bundle is the one this report names (Windows: certutil -hashfile proof.scrutator SHA256):

   ```
   sha256sum proof.scrutator
   # 8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa
   ```

2. Check the signature, the hash chain of the lookup log and every record, and that the findings follow from the records:

   ```
   scrutator verify proof.scrutator --pin
   b8dc88a33a0016aea35a4b45d4bf6c944bf2a7293905daaeaf001239d8eea6ca
   ```

3. Check that every number, finding and sentence of this report is what the bundle implies:

   ```
   scrutator audit-check audit.html proof.scrutator
   ```

Scrutator is open source (Apache-2.0); install it with pip from the wheel or the project. None of the three commands uses the network.

Records cited by this report

Record	Source	Request	Collected (UTC)
`c4d48be7276d`	dns	`DNS A shop.example.com`	`2026-10-20T20:16:36+00:00`
`bcee36275bf0`	dns	`DNS CNAME shop.example.com`	`2026-10-20T20:16:36+00:00`
`08f6bf5b1661`	rdap	`GET https://rdap.org/domain/example.net`	`2026-10-20T20:16:37+00:00`

Record	Source	Request	Collected (UTC)
6389b626d207	dns	DNS TXT example.com	2026-10-20T20:16:36+00:00
756a47891001	rdap	GET https://rdap.org/domain/example.com	2026-10-20T20:16:36+00:00
cf9ad5431714	dns	DNS TXT multi.example.com	2026-10-20T20:16:36+00:00
067fb14624bb	dns	DNS TXT neutral.example.com	2026-10-20T20:16:36+00:00
ec591befd7d6	dns	DNS TXT noall.example.com	2026-10-20T20:16:36+00:00
f371732585dd	dns	DNS MX example.com	2026-10-20T20:16:36+00:00
80978d4d5f04	dns	DNS TXT _dmarc.example.com	2026-10-20T20:16:36+00:00
0fdfa5c4feac	dns	DNS MX oldmail.example.com	2026-10-20T20:16:36+00:00
89ed0ed79d51	dns	DNS TXT _dmarc.oldmail.example.com	2026-10-20T20:16:36+00:00
b26f8720e480	dns	DNS TXT bulk.example.com	2026-10-20T20:16:36+00:00
8388b89816b7	dns	DNS A legacy.example.com	2026-10-20T20:16:36+00:00
09d37eedacce	dns	DNS CNAME legacy.example.com	2026-10-20T20:16:36+00:00
64cda6f69dad	dns	DNS A docs.example.com	2026-10-20T20:16:36+00:00

Record	Source	Request	Collected (UTC)
77a939695ea9	dns	DNS CNAME docs.example.com	2026-10-20T20:16:36+00:00
22f8bc15441d	internetdb	GET https://internetdb.shodan.io/192.0.2.50	2026-10-20T20:16:37+00:00
fb41a659ee47	dns	DNS CAA example.net	2026-10-20T20:16:37+00:00
b343a685a88e	dns	DNS NS example.net	2026-10-20T20:16:37+00:00
fb32292266be	dns	DNS CAA example.com	2026-10-20T20:16:36+00:00
59edc5a1e9ef	dns	DNS NS example.com	2026-10-20T20:16:36+00:00
e38fa3477046	dns	DNS TXT _dmarc.sales.example.com	2026-10-20T20:16:36+00:00
85cfb2338240	dns	DNS TXT soft.example.com	2026-10-20T20:16:36+00:00
01e0d9f756c8	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.77&sourceapp=scrutator	2026-10-20T20:16:37+00:00
0ca4114e8c6a	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.76&sourceapp=scrutator	2026-10-20T20:16:37+00:00
0f03aa66fc72	dns	DNS A sales.example.com	2026-10-20T20:16:36+00:00
1dab89720a1b	dns	DNS A ns2.dns.example.net	2026-10-20T20:16:37+00:00
24d86e32684a	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.74&sourceapp=scrutator	2026-10-20T20:16:37+00:00

Record	Source	Request	Collected (UTC)
31618bb7c7a0	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.10&sourceapp=scrutator	2026-10-20T20:16:37+00:00
4183e499e07d	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.50&sourceapp=scrutator	2026-10-20T20:16:37+00:00
454b918b6e9c	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.64&sourceapp=scrutator	2026-10-20T20:16:37+00:00
45662725b4f3	dns	DNS A bulk.example.com	2026-10-20T20:16:36+00:00
4adf860db088	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.73&sourceapp=scrutator	2026-10-20T20:16:37+00:00
4af45bdc672e	dns	DNS A dev.example.com	2026-10-20T20:16:36+00:00
5936a350f877	dns	DNS A app4.example.com	2026-10-20T20:16:36+00:00
6cf07b70fe54	dns	DNS A www.example.com	2026-10-20T20:16:36+00:00
723fd57994f3	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.10&sourceapp=scrutator	2026-10-20T20:16:37+00:00
72cdd8aa0540	dns	DNS A app1.example.com	2026-10-20T20:16:36+00:00
7eaf7a6e4ce1	dns	DNS A example.net	2026-10-20T20:16:37+00:00
7f5ace880243	dns	DNS A ns1.dns.example.net	2026-10-20T20:16:36+00:00
8796b00d0d58	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.1&sourceapp=scrutator	2026-10-20T20:16:36+00:00

Record	Source	Request	Collected (UTC)
8b51c626a4c3	dns	DNS A noall.example.com	2026-10-20T20:16:36+00:00
8fae92b68fbb	dns	DNS A soft.example.com	2026-10-20T20:16:36+00:00
928582d58494	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.54&sourceapp=scrutator	2026-10-20T20:16:37+00:00
9ba28d58c36c	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.61&sourceapp=scrutator	2026-10-20T20:16:37+00:00
affd6716b827	dns	DNS A app2.example.com	2026-10-20T20:16:36+00:00
b2cc2a3bf3dd	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.75&sourceapp=scrutator	2026-10-20T20:16:37+00:00
b66a08b9fea4	dns	DNS A mail.example.com	2026-10-20T20:16:37+00:00
b81d938641b2	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.25&sourceapp=scrutator	2026-10-20T20:16:37+00:00
dcda18944133	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.71&sourceapp=scrutator	2026-10-20T20:16:37+00:00
e0ba3bebce56	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.72&sourceapp=scrutator	2026-10-20T20:16:37+00:00
e463807d036c	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.53&sourceapp=scrutator	2026-10-20T20:16:37+00:00
ed67e58c5cf5	dns	DNS A example.com	2026-10-20T20:16:36+00:00
f66c746bc440	asn	GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.62&sourceapp=scrutator	2026-10-20T20:16:37+00:00

Record	Source	Request	Collected (UTC)
fc3339d17634	dns	DNS A oldmail.example.com	2026-10-20T20:16:36+00:00
ff153d7b83a7	dns	DNS A neutral.example.com	2026-10-20T20:16:36+00:00
ff472dc63ced	dns	DNS A multi.example.com	2026-10-20T20:16:36+00:00
2e29c591d4c8	crtsh	GET https://crt.sh/?q=%25.example.com&output=json	2026-10-20T20:16:36+00:00
c6db47b4d3e2	wayback	GET https://web.archive.org/cdx/search/cdx?url=%2A.example.com&output=json&fl=original&collapse=urlkey&limit=500	2026-10-20T20:16:36+00:00
f9b081024eae	dns	DNS A ghost.example.com	2026-10-20T20:16:36+00:00
33272b595e75	crtsh	GET https://crt.sh/?q=%25.example.com&output=json	2026-10-20T20:16:36+00:00
35f2254265c0	crtsh	GET https://crt.sh/?q=%25.example.com&output=json	2026-10-20T20:16:36+00:00
eb6969220261	crtsh	GET https://crt.sh/?q=%25.example.com&output=json	2026-10-20T20:16:36+00:00