CONFIDENTIAL

# External exposure audit

## Example Corp (fictional sample)

| | |
|---|---|
| Prepared for | Example Corp (fictional sample) |
| Prepared by | Sample Auditor (placeholder) |
| Contact | audits@example.org |
| Date | 2026-11-07 |
| Engagement reference | SAMPLE-001 |
| Scope | example.com, example.net |
| Bundle SHA-256 | `8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa` |

The interactive technical annex (technical-annex.html) shows every name, finding and record with its evidence.

# Contents

1. Authorisation
2. Executive summary
3. Findings and remediation, in priority order
4. Asset inventory
5. What was not tested
6. Methodology
7. Glossary
8. Evidence appendix

# Authorisation

This review was carried out under a written authorisation from Example Corp (fictional sample), signed by Sample Signatory (fictional) (CISO (fictional)), in force from 2026-10-01 to 2026-12-31, for the domains listed above and for this purpose: Sample report made from the planted lab fixture; not a real engagement

The authorisation (its SHA-256 02ccc7d8a905c94f0fa87b4c32c06634801ff45b2d0071f6ec58a2cf814706a1) was recorded when this report was made; the scan itself was run before it was recorded, so the signed bundle does not contain it.

Permitted activity: passive collection of public records only.

# Executive summary

1. Sample Auditor (placeholder) reviewed the public internet footprint of Example Corp (fictional sample) (example.com, example.net) on 2026-10-20, using public records only: no scanning, no login attempts, no exploitation.
2. The review confirmed 17 internet-facing names under these domains that resolve in public DNS or appear in a recent certificate. (17 records)
3. Third-party lists mention 1 more name that public DNS does not confirm; it is kept as unconfirmed and not counted as findings. (1 record)
4. 23 issues were found: 3 high, 10 medium, 8 low and 2 informational. [R1, R2, R3, R4, R5, R6 …] (64 records)
5. Priority 1: CNAME to a claimable service that no longer exists (shop.example.com, demo.pages.example.org). Delete the CNAME record, or re-create the resource at the service so the name is yours again. [R1] (2 records)
6. Priority 2: Domain registration has expired (example.net). Renew the domain at once, or confirm that it is meant to lapse and remove what depends on it. [R2] (1 record)
7. Priority 3: SPF record authorises every sender (example.com). End the record with -all (or ~all while rolling out) and list only the senders you use. [R3] (1 record)
8. 1 of 14 public sources did not answer in full during the review; what they hold is not reflected here.
9. Every statement about the client's systems cites the records it rests on, sealed in a signed bundle that the client or their auditor can verify offline.

Each numbered statement cites the evidence records it rests on (appendix).

## Findings and remediation, in priority order

| Priority | Severity | Finding | Affected | Effort (estimate) |
|---|---|---|---|---|
| R1 | High | CNAME to a claimable service that no longer exists | shop.example.com, demo.pages.example.org | Low |
| R2 | High | Domain registration has expired | example.net | Low |
| R3 | High | SPF record authorises every sender | example.com | Low |
| R4 | Medium | Domain registration expires within 30 days | example.com | Low |
| R5 | Medium | More than one SPF record | multi.example.com | Low |
| R6 | Medium | SPF record takes no position on unlisted senders | neutral.example.com | Low |
| R7 | Medium | SPF record has no default result | noall.example.com | Low |
| R8 | Medium | Mail domain without a DMARC record | example.com | Medium |
| R9 | Medium | Mail domain without a DMARC record | oldmail.example.com | Medium |
| R10 | Medium | SPF record needs more than ten DNS lookups | bulk.example.com | Medium |
| R11 | Medium | CNAME to a host that does not exist | legacy.example.com, gone.example.org | Low |
| R12 | Medium | CNAME to a host that no longer exists, at a service known for takeovers | docs.example.com, team.sites.example.org | Low |
| R13 | Medium | A database, remote-administration or file-sharing port is open to the internet | 192.0.2.50 | Medium |
| R14 | Low | No CAA record at a zone apex | example.net | Low |
| R15 | Low | No CAA record at a zone apex | example.com | Low |
| R16 | Low | DMARC policy is monitoring only | sales.example.com | Medium |
| R17 | Low | SPF record soft-fails unlisted senders | soft.example.com | Medium |

| Priority | Severity | Finding | Affected | Effort (estimate) |
|---|---|---|---|---|
| R18 | Low | All names depend on one DNS provider | example.com, example.net | High |
| R19 | Low | Several names depend on one CDN or hosting provider | app1.example.com, app2.example.com, app4.example.com, bulk.example.com … | High |
| R20 | Low | Registry and DNS disagree about the name servers | example.com | Low |
| R21 | Low | Name that looks like a forgotten test or staging system | dev.example.com | Medium |
| R22 | Info | A certificate or archive names a host that DNS does not know | ghost.example.com | Low |
| R23 | Info | A gap in a numbered series of names | app1.example.com, app2.example.com, app4.example.com | Low |

Effort is the auditor's estimate of the work to fix, not a measurement.

### R1 · CNAME to a claimable service that no longer exists High

| | |
|---|---|
| Affected | shop.example.com, demo.pages.example.org |
| What the evidence shows | shop.example.com is an alias (CNAME) of demo.pages.example.org, and the address lookup for shop.example.com returned NXDOMAIN, so the target does not exist. demo.pages.example.org matches the takeover fingerprint lab-pages (Example Pages, rated vulnerable, shown by NXDOMAIN). |
| Remediation | Delete the CNAME record, or re-create the resource at the service so the name is yours again. Check what else (cookies, OAuth redirects, SPF) trusted the name. |
| Effort (estimate) | Low |
| Informational mapping | OWASP WSTG-CONF-10; OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)* |
| Evidence | `c4d48be7276d`, `bcee36275bf0` |

### R2 · Domain registration has expired High

| | |
|---|---|
| Affected | example.net |
| What the evidence shows | RDAP lists the expiration of example.net as 2026-10-15T20:16:36Z; the data was collected 2026-10-20T20:16:37+00:00, after that date. |
| Remediation | Renew the domain at once, or confirm that it is meant to lapse and remove what depends on it. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.5.30 *(unverified)* |
| Evidence | `08f6bf5b1661` |

### R3 · SPF record authorises every sender High

| | |
|---|---|
| Affected | example.com |
| What the evidence shows | example.com publishes the SPF record "v=spf1 include:spf.example.org +all", which ends with "+all". |
| Remediation | End the record with -all (or ~all while rolling out) and list only the senders you use. |
| Effort (estimate) | Low |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `6389b626d207` |

### R4 · Domain registration expires within 30 days Medium

| | |
|---|---|
| Affected | example.com |
| What the evidence shows | RDAP lists the expiration of example.com as 2026-11-09T20:16:36Z; the data was collected 2026-10-20T20:16:36+00:00, 20 day(s) before it. |
| Remediation | Renew the domain and enable auto-renewal. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.5.30 *(unverified)* |
| Evidence | `756a47891001` |

### R5 · More than one SPF record Medium

| | |
|---|---|
| Affected | multi.example.com |
| What the evidence shows | multi.example.com publishes 2 TXT records that start with v=spf1. |
| Remediation | Merge the records into one. |
| Effort (estimate) | Low |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `cf9ad5431714` |

### R6 · SPF record takes no position on unlisted senders Medium

| | |
|---|---|
| Affected | neutral.example.com |
| What the evidence shows | neutral.example.com publishes the SPF record "v=spf1 mx ?all", which ends with "?all". |
| Remediation | End the record with -all (or ~all while rolling out). |
| Effort (estimate) | Low |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `067fb14624bb` |

### R7 · SPF record has no default result Medium

| | |
|---|---|
| Affected | noall.example.com |
| What the evidence shows | noall.example.com publishes the SPF record "v=spf1 mx", which has no all mechanism and no redirect. |
| Remediation | End the record with -all (or ~all while rolling out). |
| Effort (estimate) | Low |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `ec591befd7d6` |

### R8 · Mail domain without a DMARC record Medium

| | |
|---|---|
| Affected | example.com |
| What the evidence shows | example.com has MX records, and the TXT lookup for _dmarc.example.com returned NXDOMAIN. |
| Remediation | Publish a DMARC record at _dmarc.<domain>, starting with p=none and reporting addresses, then move to quarantine and reject. |
| Effort (estimate) | Medium |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `f371732585dd`, `80978d4d5f04` |

### R9 · Mail domain without a DMARC record Medium

| | |
|---|---|
| Affected | oldmail.example.com |
| What the evidence shows | oldmail.example.com has MX records, and the TXT lookup for _dmarc.oldmail.example.com returned NXDOMAIN. |
| Remediation | Publish a DMARC record at _dmarc.<domain>, starting with p=none and reporting addresses, then move to quarantine and reject. |
| Effort (estimate) | Medium |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `0fdfa5c4feac`, `89ed0ed79d51` |

### R10 · SPF record needs more than ten DNS lookups Medium

| | |
|---|---|
| Affected | bulk.example.com |
| What the evidence shows | bulk.example.com publishes the SPF record "v=spf1 include:s1.example.org include:s2.example.org include:s3.example.org include:s4.example.org include:s5.example.org include:s6.example.org include:s7.example.org include:s8.example.org includ...", whose own terms contain 11 mechanisms that cause a DNS lookup. |
| Remediation | Remove unused includes, replace includes with ip4/ip6 ranges, or flatten the record. |
| Effort (estimate) | Medium |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `b26f8720e480` |

### R11 · CNAME to a host that does not exist Medium

| | |
|---|---|
| Affected | legacy.example.com, gone.example.org |
| What the evidence shows | legacy.example.com is an alias (CNAME) of gone.example.org, and the address lookup for legacy.example.com returned NXDOMAIN, so the target does not exist. |
| Remediation | Delete the CNAME record if the target is no longer used, or restore the target. |
| Effort (estimate) | Low |
| Informational mapping | OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)* |
| Evidence | `8388b89816b7`, `09d37eedacce` |

### R12 · CNAME to a host that no longer exists, at a service known for takeovers Medium

| | |
|---|---|
| Affected | docs.example.com, team.sites.example.org |
| What the evidence shows | docs.example.com is an alias (CNAME) of team.sites.example.org, and the address lookup for docs.example.com returned NXDOMAIN, so the target does not exist. team.sites.example.org matches the takeover fingerprint lab-sites (Example Sites, rated vulnerable, shown by http-fingerprint). |
| Remediation | Delete the CNAME record or re-create the resource at the service. In an authorised assessment, confirm with an active check. |
| Effort (estimate) | Low |
| Informational mapping | OWASP WSTG-CONF-10; OWASP A05:2021; NIS2 Art. 21(2)(e); CIS 1.1; CIS 4.1; ISO 27001 A.8.9 *(unverified)*; ISO 27001 A.5.9 *(unverified)* |
| Evidence | `64cda6f69dad`, `77a939695ea9` |

### R13 · A database, remote-administration or file-sharing port is open to the internet

Medium

| | |
|---|---|
| Affected | 192.0.2.50 |
| What the evidence shows | Shodan InternetDB lists these open ports on 192.0.2.50: 6379 (Redis). InternetDB reports an earlier scan by Shodan, not a check made now. |
| Remediation | Confirm with the owner whether the port is open now; if it is, close it at the firewall or restrict it to known addresses, and require authentication. |
| Effort (estimate) | Medium |
| How established | Reported earlier by a third party (Shodan InternetDB); not checked now. |
| Informational mapping | NIS2 Art. 21(2)(e); CIS 4.1; CIS 7.6; CIS 12.1; OWASP A05:2021; KVKK Art. 12(1); ISO 27001 A.8.20 *(unverified)*; ISO 27001 A.8.8 *(unverified)* |
| Evidence | `22f8bc15441d` |

### R14 · No CAA record at a zone apex Low

| | |
|---|---|
| Affected | example.net |
| What the evidence shows | example.net has name server records and the CAA lookup for example.net returned no record. |
| Remediation | Publish CAA records naming the certificate authorities you use. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(h); CIS 4.1; ISO 27001 A.8.24 *(unverified)* |
| Evidence | `fb41a659ee47`, `b343a685a88e` |

### R15 · No CAA record at a zone apex Low

| | |
|---|---|
| Affected | example.com |
| What the evidence shows | example.com has name server records and the CAA lookup for example.com returned no record. |
| Remediation | Publish CAA records naming the certificate authorities you use. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(h); CIS 4.1; ISO 27001 A.8.24 *(unverified)* |
| Evidence | `fb32292266be`, `59edc5a1e9ef` |

### R16 · DMARC policy is monitoring only Low

| | |
|---|---|
| Affected | sales.example.com |
| What the evidence shows | _dmarc.sales.example.com publishes "v=DMARC1; p=none; rua=mailto:dmarc@example.com", whose policy is p=none. |
| Remediation | Move to p=quarantine and then p=reject once the reports show only legitimate senders. |
| Effort (estimate) | Medium |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `e38fa3477046` |

### R17 · SPF record soft-fails unlisted senders Low

| | |
|---|---|
| Affected | soft.example.com |
| What the evidence shows | soft.example.com publishes the SPF record "v=spf1 mx ~all", which ends with "~all". |
| Remediation | Move to -all once the sender list is complete, and publish a DMARC policy. |
| Effort (estimate) | Medium |
| Informational mapping | CIS 9.5; NIS2 Art. 21(2)(g); ISO 27001 A.5.14 *(unverified)*; ISO 27001 A.8.21 *(unverified)* |
| Evidence | `85cfb2338240` |

### R18 · All names depend on one DNS provider Low

| | |
|---|---|
| Affected | example.com, example.net |
| What the evidence shows | The name servers of example.com, example.net all belong to Example DNS; 22 in-scope name(s) sit in these zones. |
| Remediation | Consider a secondary DNS provider on a different network, and protect the account with strong authentication. |
| Effort (estimate) | High |
| Informational mapping | NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(d); CIS 15.1; ISO 27001 A.5.19 *(unverified)*; ISO 27001 A.5.23 *(unverified)*; ISO 27001 A.5.30 *(unverified)* |
| Evidence | `59edc5a1e9ef`, `b343a685a88e` |

### R19 · Several names depend on one CDN or hosting provider Low

| | |
|---|---|
| Affected | app1.example.com, app2.example.com, app4.example.com, bulk.example.com, dev.example.com, example.com, example.net, mail.example.com, multi.example.com, neutral.example.com |
| What the evidence shows | 17 in-scope names are served through Example Edge (app1.example.com, app2.example.com, app4.example.com, bulk.example.com, dev.example.com, example.com, example.net, mail.example.com, multi.example.com, neutral.example.com). |
| Remediation | Know the provider's outage and incident process; consider whether critical names need an alternative. |
| Effort (estimate) | High |
| Informational mapping | NIS2 Art. 21(2)(c); NIS2 Art. 21(2)(d); CIS 15.1; ISO 27001 A.5.19 *(unverified)*; ISO 27001 A.5.23 *(unverified)*; ISO 27001 A.5.30 *(unverified)* |
| Evidence | `01e0d9f756c8`, `0ca4114e8c6a`, `0f03aa66fc72`, `1dab89720a1b`, `24d86e32684a`, `31618bb7c7a0`, `4183e499e07d`, `454b918b6e9c` +26 |

### R20 · Registry and DNS disagree about the name servers Low

| | |
|---|---|
| Affected | example.com |
| What the evidence shows | For example.com, only RDAP lists ns9.old.example.net and only the zone's NS records list ns2.dns.example.net. |
| Remediation | Make the registry delegation and the zone's NS records identical. |
| Effort (estimate) | Low |
| Informational mapping | CIS 4.1; OWASP A05:2021; ISO 27001 A.8.9 *(unverified)* |
| Evidence | `756a47891001`, `59edc5a1e9ef` |

### R21 · Name that looks like a forgotten test or staging system Low

| | |
|---|---|
| Affected | dev.example.com |
| What the evidence shows | dev.example.com contains the label "dev" and resolves to 192.0.2.50. |
| Remediation | Confirm the system is still needed and maintained; otherwise remove the DNS record and the system. |
| Effort (estimate) | Medium |
| Informational mapping | NIS2 Art. 21(2)(i); CIS 1.1; CIS 7.6; OWASP A05:2021; ISO 27001 A.5.9 *(unverified)*; ISO 27001 A.8.8 *(unverified)* |
| Evidence | `4af45bdc672e` |

### R22 · A certificate or archive names a host that DNS does not know Info

| | |
|---|---|
| Affected | ghost.example.com |
| What the evidence shows | ghost.example.com is named by crtsh, wayback, and the address lookup for ghost.example.com returned NXDOMAIN. |
| Remediation | Check whether the name is still referenced (certificates, links, configuration) and whether DNS or the certificate should be cleaned up. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)* |
| Evidence | `2e29c591d4c8`, `c6db47b4d3e2`, `f9b081024eae` |

### R23 · A gap in a numbered series of names Info

| | |
|---|---|
| Affected | app1.example.com, app2.example.com, app4.example.com |
| What the evidence shows | 3 names follow the pattern app<number>.example.com (app1.example.com, app2.example.com, app4.example.com); the number(s) 3 are missing, for example app3.example.com. |
| Remediation | Check whether the missing number is a retired or unlisted system. |
| Effort (estimate) | Low |
| Informational mapping | NIS2 Art. 21(2)(i); CIS 1.1; ISO 27001 A.5.9 *(unverified)* |
| Evidence | `33272b595e75`, `35f2254265c0`, `eb6969220261` |

> The framework references are an informational mapping, not a certification, an audit opinion or a legal conclusion. References marked (unverified), including every ISO/IEC 27001 reference, could not be read at an authoritative public source and must be checked against the framework itself.

## Asset inventory

Names that public DNS resolves or that a certificate dated in the last 90 days names (verified). Names that only third-party lists mention are counted below, not listed here.

| Name | Addresses | Providers | Networks | Evidence |
|---|---|---|---|---|
| example.com | 192.0.2.1 | Example DNS (dns), Example Edge (cdn) | | ed67e58c5cf5 |
| example.net | 198.51.100.10 | Example DNS (dns), Example Edge (cdn) | | 7eaf7a6e4ce1 |
| app1.example.com | 192.0.2.61 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 72cdd8aa0540 |
| app2.example.com | 192.0.2.62 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | affd6716b827 |
| app4.example.com | 192.0.2.64 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 5936a350f877 |
| bulk.example.com | 192.0.2.75 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 45662725b4f3 |
| dev.example.com | 192.0.2.50 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 4af45bdc672e |
| mail.example.com | 192.0.2.25 | Example DNS (dns), Example Edge (cdn) | | b66a08b9fea4 |
| multi.example.com | 192.0.2.74 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | ff472dc63ced |
| neutral.example.com | 192.0.2.71 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | ff153d7b83a7 |
| noall.example.com | 192.0.2.73 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 8b51c626a4c3 |
| oldmail.example.com | 192.0.2.77 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | fc3339d17634 |
| sales.example.com | 192.0.2.76 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 0f03aa66fc72 |
| soft.example.com | 192.0.2.72 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 8fae92b68fbb |
| www.example.com | 192.0.2.10 | Example DNS (dns), Example Edge (cdn), Let's Encrypt (ca) | | 6cf07b70fe54 |

| Name | Addresses | Providers | Networks | Evidence |
| --- | --- | --- | --- | --- |
| ns1.dns.example.net | 198.51.100.53 | Example DNS (dns), Example Edge (cdn) | | 7f5ace880243 |
| ns2.dns.example.net | 198.51.100.54 | Example DNS (dns), Example Edge (cdn) | | 1dab89720a1b |

Unconfirmed names (only lists mention them): 1. Retired names (DNS says they do not exist): 4. Covered only by a wildcard record: 0.

## What was not tested

This review is passive. It did not:

- scan ports or services, or send any request to the client's systems other than ordinary DNS lookups of their names;
- test web applications, APIs, logins or authentication;
- attempt to exploit, confirm or reproduce any weakness (a takeover candidate is reported, never claimed);
- look at internal networks, endpoints, cloud accounts or source code;
- look up any person, e-mail address or credential, or use breach data;
- test phishing resistance, physical security or staff awareness.

### Public sources asked and how they answered during the review:

| Source | Outcome |
|---|---|
| `asn` | answered |
| `certspotter` | answered |
| `commoncrawl` | answered |
| `crtsh` | answered |
| `dns` | answered |
| `hackertarget` | answered |
| `internetdb` | answered |
| `mnemonic` | answered |
| `rdap` | answered |
| `ripestat` | failed — ModuleError: ripestat returned HTTP 404 |
| `subdomaincenter` | answered |
| `urlscan` | answered |
| `wayback` | answered |
| `wildcard` | answered |

> Names that no certificate log, archive or aggregator has ever seen cannot appear in this report. A finding reflects public records at the time they were collected; the client's systems may have changed since.

# Methodology

Scrutator asked public sources what they know about the domains in scope: certificate transparency logs, DNS, registration data (RDAP), routing data, web archives and passive-DNS and name aggregators. It did not contact the client's systems except through ordinary DNS lookups.

Every answer was stored unchanged as an evidence record addressed by its SHA-256 hash. Findings and risks are derived from those records by deterministic rules; a risk cannot exist without the records it cites. A name is verified when DNS resolves it or a recent certificate names it, and only claimed when only a list mentions it.

The records, the derived report and a hash-chained log of every lookup were sealed in a proof bundle and signed with an Ed25519 key. The bundle can be checked by anyone, offline, with the commands in the appendix.

Sources used: asn, certspotter, commoncrawl, crtsh, dns, hackertarget, internetdb, mnemonic, rdap, ripestat, subdomaincenter, urlscan, wayback, wildcard.

Tool scrutator 0.7.0; risk rules 4; knowledge packs 44bbd66959eeacfc; scan started 2026-10-20T20:16:36+00:00; report made 2026-11-07T22:30:47+00:00.

# Glossary

**DNS**
The internet's directory: it turns names such as www.example.com into addresses.

**CNAME (alias)**
A DNS record saying a name is another name. If the target disappears, whoever claims it may control the alias.

**Subdomain takeover**
Taking control of a name whose alias points at a cloud resource that no longer exists.

**SPF**
A DNS record listing which servers may send e-mail for a domain.

**DMARC**
A DNS record telling receivers what to do with mail that fails SPF/DKIM checks, and where to report it.

**CAA**
A DNS record naming the certificate authorities allowed to issue certificates for a domain.

**Certificate transparency**
Public logs of every TLS certificate issued; they reveal names a company uses.

**RDAP**
The modern registration database for domains and IP networks (successor of WHOIS).

**Verified / claimed**
Verified: DNS or a recent certificate supports the name. Claimed: only a list mentions it.

**Evidence record**
The unchanged answer of a source, identified by its SHA-256 hash.

**Proof bundle**
A signed file with the report, every evidence record and the lookup log; any change is detected.

**SHA-256**
A fingerprint of a file: changing one bit changes it completely.

**Ed25519**
The signature scheme used to seal the bundle; the key fingerprint identifies the signer.

# Evidence appendix

This report was made from the signed proof bundle below. Give the client the bundle with this report; it holds every record this report cites.

| | |
|---|---|
| Bundle file | `proof.scrutator` |
| Bundle SHA-256 | `8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa` |
| Signing key fingerprint | `b8dc88a33a0016aea35a4b45d4bf6c944bf2a7293905daaeaf001239d8eea6ca` |
| Evidence records in the bundle | 83 |

### How the client or their auditor verifies this report offline, in three commands

1. Check that the bundle is the one this report names (Windows: certutil -hashfile proof.scrutator SHA256):

   ```
   sha256sum proof.scrutator
   # 8cfcdc95a0128a9a7bb8d3e107a84d8a2928f2ceeb552e7f70a1e0c73a40c9aa
   ```

2. Check the signature, the hash chain of the lookup log and every record, and that the findings follow from the records:

   ```
   scrutator verify proof.scrutator --pin
   b8dc88a33a0016aea35a4b45d4bf6c944bf2a7293905daaeaf001239d8eea6ca
   ```

3. Check that every number, finding and sentence of this report is what the bundle implies:

   ```
   scrutator audit-check audit.html proof.scrutator
   ```

Scrutator is open source (Apache-2.0); install it with pip from the wheel or the project. None of the three commands uses the network.

### Records cited by this report

| Record | Source | Request | Collected (UTC) |
|---|---|---|---|
| `c4d48be7276d` | dns | `DNS A shop.example.com` | `2026-10-20T20:16:36+00:00` |
| `bcee36275bf0` | dns | `DNS CNAME shop.example.com` | `2026-10-20T20:16:36+00:00` |
| `08f6bf5b1661` | rdap | `GET https://rdap.org/domain/example.net` | `2026-10-20T20:16:37+00:00` |

| Record | Source | Request | Collected (UTC) |
| --- | --- | --- | --- |
| 6389b626d207 | dns | DNS TXT example.com | 2026-10-20T20:16:36+00:00 |
| 756a47891001 | rdap | GET https://rdap.org/domain/example.com | 2026-10-20T20:16:36+00:00 |
| cf9ad5431714 | dns | DNS TXT multi.example.com | 2026-10-20T20:16:36+00:00 |
| 067fb14624bb | dns | DNS TXT neutral.example.com | 2026-10-20T20:16:36+00:00 |
| ec591befd7d6 | dns | DNS TXT noall.example.com | 2026-10-20T20:16:36+00:00 |
| f371732585dd | dns | DNS MX example.com | 2026-10-20T20:16:36+00:00 |
| 80978d4d5f04 | dns | DNS TXT _dmarc.example.com | 2026-10-20T20:16:36+00:00 |
| 0fdfa5c4feac | dns | DNS MX oldmail.example.com | 2026-10-20T20:16:36+00:00 |
| 89ed0ed79d51 | dns | DNS TXT _dmarc.oldmail.example.com | 2026-10-20T20:16:36+00:00 |
| b26f8720e480 | dns | DNS TXT bulk.example.com | 2026-10-20T20:16:36+00:00 |
| 8388b89816b7 | dns | DNS A legacy.example.com | 2026-10-20T20:16:36+00:00 |
| 09d37eedacce | dns | DNS CNAME legacy.example.com | 2026-10-20T20:16:36+00:00 |
| 64cda6f69dad | dns | DNS A docs.example.com | 2026-10-20T20:16:36+00:00 |

| Record | Source | Request | Collected (UTC) |
|---|---|---|---|
| 77a939695ea9 | dns | DNS CNAME docs.example.com | 2026-10-20T20:16:36+00:00 |
| 22f8bc15441d | internetdb | GET https://internetdb.shodan.io/192.0.2.50 | 2026-10-20T20:16:37+00:00 |
| fb41a659ee47 | dns | DNS CAA example.net | 2026-10-20T20:16:37+00:00 |
| b343a685a88e | dns | DNS NS example.net | 2026-10-20T20:16:37+00:00 |
| fb32292266be | dns | DNS CAA example.com | 2026-10-20T20:16:36+00:00 |
| 59edc5a1e9ef | dns | DNS NS example.com | 2026-10-20T20:16:36+00:00 |
| e38fa3477046 | dns | DNS TXT _dmarc.sales.example.com | 2026-10-20T20:16:36+00:00 |
| 85cfb2338240 | dns | DNS TXT soft.example.com | 2026-10-20T20:16:36+00:00 |
| 01e0d9f756c8 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.77&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 0ca4114e8c6a | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.76&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 0f03aa66fc72 | dns | DNS A sales.example.com | 2026-10-20T20:16:36+00:00 |
| 1dab89720a1b | dns | DNS A ns2.dns.example.net | 2026-10-20T20:16:37+00:00 |
| 24d86e32684a | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.74&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |

| Record | Source | Request | Collected (UTC) |
| --- | --- | --- | --- |
| 31618bb7c7a0 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.10&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 4183e499e07d | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.50&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 454b918b6e9c | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.64&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 45662725b4f3 | dns | DNS A bulk.example.com | 2026-10-20T20:16:36+00:00 |
| 4adf860db088 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.73&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 4af45bdc672e | dns | DNS A dev.example.com | 2026-10-20T20:16:36+00:00 |
| 5936a350f877 | dns | DNS A app4.example.com | 2026-10-20T20:16:36+00:00 |
| 6cf07b70fe54 | dns | DNS A www.example.com | 2026-10-20T20:16:36+00:00 |
| 723fd57994f3 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.10&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 72cdd8aa0540 | dns | DNS A app1.example.com | 2026-10-20T20:16:36+00:00 |
| 7eaf7a6e4ce1 | dns | DNS A example.net | 2026-10-20T20:16:37+00:00 |
| 7f5ace880243 | dns | DNS A ns1.dns.example.net | 2026-10-20T20:16:36+00:00 |
| 8796b00d0d58 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.1&sourceapp=scrutator | 2026-10-20T20:16:36+00:00 |

| Record | Source | Request | Collected (UTC) |
|---|---|---|---|
| 8b51c626a4c3 | dns | DNS A noall.example.com | 2026-10-20T20:16:36+00:00 |
| 8fae92b68fbb | dns | DNS A soft.example.com | 2026-10-20T20:16:36+00:00 |
| 928582d58494 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.54&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| 9ba28d58c36c | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.61&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| affd6716b827 | dns | DNS A app2.example.com | 2026-10-20T20:16:36+00:00 |
| b2cc2a3bf3dd | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.75&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| b66a08b9fea4 | dns | DNS A mail.example.com | 2026-10-20T20:16:37+00:00 |
| b81d938641b2 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.25&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| dcda18944133 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.71&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| e0ba3bebce56 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.72&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| e463807d036c | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=198.51.100.53&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |
| ed67e58c5cf5 | dns | DNS A example.com | 2026-10-20T20:16:36+00:00 |
| f66c746bc440 | asn | GET https://stat.ripe.net/data/prefix-overview/data.json?resource=192.0.2.62&sourceapp=scrutator | 2026-10-20T20:16:37+00:00 |

| Record | Source | Request | Collected (UTC) |
|---|---|---|---|
| fc3339d17634 | dns | DNS A oldmail.example.com | 2026-10-20T20:16:36+00:00 |
| ff153d7b83a7 | dns | DNS A neutral.example.com | 2026-10-20T20:16:36+00:00 |
| ff472dc63ced | dns | DNS A multi.example.com | 2026-10-20T20:16:36+00:00 |
| 2e29c591d4c8 | crtsh | GET https://crt.sh/?q=%25.example.com&output=json | 2026-10-20T20:16:36+00:00 |
| c6db47b4d3e2 | wayback | GET https://web.archive.org/cdx/search/cdx?url=%2A.example.com&output=json&fl=original&collapse=urlkey&limit=500 | 2026-10-20T20:16:36+00:00 |
| f9b081024eae | dns | DNS A ghost.example.com | 2026-10-20T20:16:36+00:00 |
| 33272b595e75 | crtsh | GET https://crt.sh/?q=%25.example.com&output=json | 2026-10-20T20:16:36+00:00 |
| 35f2254265c0 | crtsh | GET https://crt.sh/?q=%25.example.com&output=json | 2026-10-20T20:16:36+00:00 |
| eb6969220261 | crtsh | GET https://crt.sh/?q=%25.example.com&output=json | 2026-10-20T20:16:36+00:00 |