

Package ‘ROpenLayers’

February 3, 2019

Title Geo-visualization Using OperLayers and ArcGIS

Version 1.0.0

Description

Functions to export geospatial data and analyses to interactive HTML/javascript visualization using the OpenLayers javascript library. The resulting HTML pages replicate some of the functionality in the Leaflet and ggmap packages, but have the advantage of enabling the user to easily leverage the functionality of the OpenLayers javascript library with a variety of public and US Government authenticated map servers. User-supplied ArcGIS map servers are also supported. The output HTML, files, and folders can be viewed on a local machine, hosted as self-contained web pages on a minimal http server, or parsed by the user for inclusion in other applications, web pages, or other server environments (e.g., RShiny).

Depends R (>= 3.3)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports sp, stats, grDevices, graphics, utils, base64enc, png

Suggests rgdal, jpeg, tiff, httr, jsonlite

RoxygenNote 6.1.1

NeedsCompilation no

Author Christopher Marks [aut, cre]

Maintainer Christopher Marks <cemarks@alum.mit.edu>

R topics documented:

+.Ol.Map	2
geocode	3
nga_basemap	4
ol_aes	6
ol_geom_circle	7
ol_geom_heatmap	9
ol_geom_icon	11
ol_geom_line	13
ol_geom_point	16
ol_geom_polygon	18
ol_geom_text	21
ol_map	22

ol_map2HTML	23
ol_map2Strings	25
ol_scale_color_continuous	26
ol_scale_color_discrete	29
ol_scale_fill_continuous	31
ol_scale_fill_discrete	33
ol_scale_iconimage_discrete	35
ol_scale_iconsize_continuous	37
ol_scale_iconsize_discrete	39
ol_scale_lty_discrete	41
ol_scale_lwd_discrete	43
ol_scale_size_continuous	45
ol_scale_size_discrete	47
public_arcgis_basemap	49
public_OSM_basemap	50
ROpenLayers	51
user_arcgis_basemap	53

Index	55
--------------	-----------

+.Ol.Map

+.Ol.Map

Description

Add components to a OpenLayers Map.

Usage

```
## S3 method for class 'Ol.Map'
ol.map.obj + other.obj
```

Arguments

ol.map.obj	S3 object of class Ol.Map.
other.obj	A map layer or scale component.

Details

Similar to the ggplot2 package, + provides functionality to add layers to an existing OpenLayers Map object. Layers are simply appended to the Ol.Map objects layers list. When adding scales, this method searches through map layers in reverse order for scales with matching aesthetics. When a matching scale is found, it is updated according to the parameters of the added scale. In general, continuous scales can be coerced into discrete scales.

Value

Ol.Map object with updated layers or scales.

What can you add?

You can add the following types of objects:

- A layer object generated by one of the `ol_geom_*` layer functions.
- A scale object generated by one of the `ol_scale_*` functions.

See Also

[ol_map](#)

Examples

```
mymap <- ol_map()
base.layer <- lightgray()
mymap <- mymap + base.layer
## Not run:
ol_map2HTML(mymap, "SanDiego.html")
browseURL("SanDiego.html")

## End(Not run)
```

geocode

Geocode an Address

Description

Get Lat/Lon Coordinates for an Address.

Usage

```
geocode(address.string)
```

Arguments

`address.string` character vector of addresses to geocode.

Details

This function uses the `findAddressCandidates` utility at [Arcgis.com](https://www.arcgis.com) to get coordinates for a single address.

Value

A data frame with probable address locations.

See Also

[ol_geom_point](#), [ol_geom_icon](#),

Examples

```

address <- "1600 Pennsylvania Ave NW, Washington, DC 20500"
## Not run:
g <- geocode(address)
point.matrix <- matrix(
  c(
    as.numeric(g$location[1,1]),
    as.numeric(g$location[1,2])
  ),
  nrow=1
)
point.df <- data.frame(
  pt.type="White House"
)
mymap <- ol_map(
  center=c(-77.03196,38.89037),
  zoom=12
) +
  streetmap() +
  ol_geom_point(
    point.matrix,
    name="Points of Interest",
    marker="pin",
    toggle.control=TRUE,
    tooltip=point.df$pt.type
  )

# Output to file and view
ol_map2HTML(mymap, 'map.html')
browseURL('map.html')

## End(Not run)

```

nga_basemap

NGA Basemap Layer

Description

Create a basemap layer linking to an NGA ArcGIS mapserver.

Usage

```

nga_basemap(basemap.identifier = "WSM", name = NULL,
  toggle.control = FALSE)

```

Arguments

basemap.identifier	character indicating which NGA mapserver to use. See 'Available Base Maps'.
name	character layer name.
toggle.control	logical. If TRUE, a checkbox will appear on the map allowing the viewer to toggle its visibility in the browser.

Details

Creates and returns an OpenLayers ArcGIS Tile layer that sources a map server hosted at <https://home.gvs.nga.mil>. These map servers are owned by the US Government and require authentication. If the `basemap.identifier` parameter is unrecognized the function will default to the NGA OpenStreetMap map server.

Value

A `Layer.ArcGIS S3` object.

Available Base Maps

The following `basemap.identifiers` are currently supported by this method.

"ABM"	Analytic Base Map
"LightGray"	Analytic Base Map (Light Gray)
"Light_LightGray"	Analytic Base Map (Light Light Gray)
"LightMidnight"	Analytic Base Map (Light Midnight)
"Light_Slate"	Analytic Base Map (Light Slate)
"Midnight"	Analytic Base Map (Midnight)
"Slate"	Analytic Base Map (Slate)
"CARDG"	Scanned CARDG Maps
"DNC"	Digital Nautical Charts
"Imagery"	Satellite Imagery
"Hillshade"	Hillshade Map
"ShadedRelief"	Shaded Relief Map
"TintedHillshade"	Tinted Hillshade Map
"WorldBoundaries"	World Boundaries (WSM)
"WorldBoundaries_Places"	World Boundaries, Places (WSM)
"WorldPlaceNames"	World Place Names (WSM)
"WorldTransportation"	World Transportation (WSM)
"WorldCities"	Sample World Cities
"WSM"	World Street Map

See Also

[ol_map](#), [+.Ol.Map](#), [public_arcgis_basemap](#), [public_OSM_basemap](#), [user_arcgis_basemap](#)

Examples

```
mymap <- ol_map()
base.layer <- nga_basemap('Midnight')
mymap <- mymap + base.layer
## Not run:
ol_map2HTML(
  mymap,
  "SanDiegoMidnight.html",
  nga.olsource = TRUE ## Not required; can also use public OpenLayers
                      ## javascript source with NGA mapservers.
)
browseURL("SanDiegoMidnight.html")

## End(Not run)
```

ol_aes

Aesthetic Mappings

Description

Map variables to layer aesthetics.

Usage

```
ol_aes(...)
```

Arguments

... comma-separated mappings of the form 'aesthetic=variable'. Available aesthetics for mapping are layer specific and are listed in the documentation for each layer type. Unavailable or unrecognized aesthetics are ignored. Variables must correspond to names in the layer's input data.frame, otherwise an error is thrown.

Details

This function replicates a subset of the functionality of the ggplot2 aes function. It *does not* allow for variable transformations or functions of multiple variables. These operations must be completed a priori by the user.

Value

A list of aesthetic mappings.

See Also

[ol_geom_polygon](#), [ol_geom_line](#), [ol_geom_point](#), [ol_geom_icon](#), [ol_geom_circle](#)

Examples

```

polygon.matrix1 <- matrix(
  c(
    -80.385+c(0,0.05,0.05,0,0),
    25.782618+c(0,0.05,0.05,0,0)
  ),
  ncol=2
)
polygon.matrix2 <- matrix(
  c(
    -80.34+c(0,0.05,0.025,0),
    25.73++c(0,0,0.025*sqrt(3),0)
  ),
  ncol=2
)
polygon.list<-list(polygon.matrix1,polygon.matrix2)
polygon.df <- data.frame(shape=c("rectangle","triangle"),no=c(1,2))
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
)
```

```

    ) +
    streetmap()
  polygon.layer <- ol_geom_polygon(
    polygon.list,
    mapping=ol_aes(
      fill=no,
      lwd=shape
    ),
    df=polygon.df,
    name="Miami Polygons",
    toggle.control=TRUE,
    tooltip=polygon.df$no
  )
  polygon.fill.scale <- ol_scale_fill_discrete(
    c("1"="red", "2"="green"),
    opacity=0.5,
    display=TRUE,
    name="Number"
  )
  polygon.linewidth.scale <- ol_scale_lwd_discrete(
    display=TRUE,
    name="Shape"
  )
  polygons.over.miami <- miami.OSM.basemap +
    polygon.layer +
    polygon.fill.scale +
    polygon.linewidth.scale

  ## Not run:
  ol_map2HTML(
    polygons.over.miami,
    'miami_polygons.html',
    map.heading="Miami Shapes",
    map.note="Note: Mouseover popup values are
      independent of shape size & color."
  )
  browseURL("miami_polygons.html")

  ## End(Not run)

```

ol_geom_circle

OpenLayers Circle Layer

Description

Function to create a circle layer to add to an OpenLayers Map object.

Usage

```

ol_geom_circle(circle.obj, mapping = ol_aes(), name = NULL,
  df = NULL, toggle.control = FALSE, fill = "#00FF0090",
  fill.opacity = 0.5, lwd = 1, ol.lty = list(), color = "#000000",
  label = NULL, label.params = list(), tooltip = NULL,
  tooltip.params = list())

```

Arguments

circle.obj	matrix containing three columns: center longitude, center latitude, and radius respectively. Each row yields a single circle feature in the resulting layer.
mapping	list created by ol_aes.
name	character Layer name.
df	data.frame with same number of rows as circle.obj. Used for aesthetic mapping.
toggle.control	logical indicating whether this layer will have a visibility toggle.
fill	character color string, or vector of color strings. Used only if no fill aesthetic is provided in mapping
fill.opacity	numeric in [0,1]. Controls circle opacity if no opacity provided in fill or fill aesthetic.
lwd	numeric circle border width. Used only if no lwd aesthetic is provided in mapping
ol.lty	(experimental) numeric vector with length > 1, or list of such vectors. Used only if no ol.lty aesthetic is provided in mapping. See OpenLayers ol/style/Stroke Documentation , 'lineDash' property for more information.
color	character border color string, or vector of color strings. Used only if no color aesthetic is provided in mapping
label	character vector of length nrow(circle.obj) of feature labels.
label.params, tooltip.params	named lists (e.g., list(property=value)) of label and tooltip position and format parameters. See ol_geom_polygon documentation.
tooltip	character vector of length nrow(circle.obj) of feature tooltip popups.

Details

This function stores the data required to generate an OpenLayers vector layer with features using circle geometries. See OpenLayers [Circle Documentation](#) for details.

Value

A list object of class `Layer.Circle`.

Aesthetics

- fill
- color
- lwd
- ol.lty (experimental; See OpenLayers [ol/style/Stroke Documentation](#), 'lineDash' property for more information.)

See Also

[ol_aes](#), [ol_map](#), [ol_geom_polygon](#)

Examples

```

miami.circles <- matrix(
  c(
    -80.885+runif(10), #Longitudes
    25.282618+runif(10), #Latitudes
    rnorm(10,2000,500) # Radii in meters
  ),
  ncol=3
)
aesthetic.df <- data.frame(
  type=sample(c("A","B"),10,replace=TRUE),
  value=runif(10)*10
)
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
circle.layer<-ol_geom_circle(
  miami.circles,
  df = aesthetic.df,
  mapping=ol_aes(fill=type),
  lwd=2,
  name="Meaningless Miami Circles",
  toggle.control=TRUE,
  color="#000000FF",
  tooltip=sprintf("%1.2f",aesthetic.df$value)
)
circle.fill <- ol_scale_fill_discrete(
  display=TRUE,
  preserve.opacity=TRUE
)
circles <- miami.OSM.basemap + circle.layer + circle.fill

## Not run:
# Output to file and view
ol_map2HTML(
  circles,
  'miami_circles.html',
  map.heading="Miami Shapes",
  map.note="Note: Mouseover popup values are
    independent of shape size & color."
)
browseURL("miami_circles.html")

## End(Not run)

```

Description

Function to create a Heatmap layer to add to an OpenLayers Map object.

Usage

```
ol_geom_heatmap(point.obj, name = NULL, toggle.control = FALSE,
  gradient = NULL, opacity = 1, radius = 8, blur = 15,
  shadow = 250, weight.values = NULL)
```

Arguments

<code>point.obj</code>	SpatialPointsDataframe, SpatialPoints, or a matrix containing columns of point longitudes and latitudes, respectively.
<code>name</code>	character Layer name.
<code>toggle.control</code>	logical indicating whether this layer will have a visibility toggle.
<code>gradient</code>	character color gradient of heatmap. See OpenLayers Heatmap Documentation Enclose gradient array in single character string.
<code>opacity</code>	numeric Heatmap opacity. See OpenLayers Heatmap Documentation .
<code>radius</code>	numeric Heatmap radius size in pixels. See OpenLayers Heatmap Documentation .
<code>blur</code>	numeric Heatmap blur. See OpenLayers Heatmap Documentation .
<code>shadow</code>	numeric Heatmap shadow. See OpenLayers Heatmap Documentation .
<code>weight.values</code>	numeric vector of weights to be assigned to the points in <code>point.obj</code> . Values should be in [0,1].

Details

This function stores the data required to generate an OpenLayers vector layer with features using Point geometries. See OpenLayers [Heatmap Documentation](#) for details.

Value

A list object of class `Layer.HeatMap`.

Aesthetics

- `fill`
- `size`

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_circle](#), [ol_geom_point](#), [ol_geom_icon](#)

Examples

```
heatmap.pts <- matrix(
  c(
    rnorm(100,-80.385,1), #Miami Longitudes
    rnorm(100,-117.1611,3), #San Diego Longitudes
    rnorm(100,25.782618,1), #Miami Latitudes
    rnorm(100,32.7157,3) # San Diego Latitudes
  ),ncol=2
)
mymap <- ol_map(
  center=c(-98.5,28.5),
```

```

        zoom=4
    ) +
      streetmap() +
      ol_geom_heatmap(
        heatmap.pts,
        name="Random Heatmap",
        toggle.control=TRUE,
        opacity=0.25
      )
## Not run:
# Write to file and view in browser
ol_map2HTML(
  mymap,
  "heatmap.html",
  map.note="Heatmap of random points centered on Miami and San Diego."
)
browseURL("heatmap.html")

## End(Not run)

```

ol_geom_icon

OpenLayers Icon Layer

Description

Function to create a point-icon layer to add to an OpenLayers Map object.

Usage

```

ol_geom_icon(point.obj, src.img = NULL, mapping = ol_aes(),
  name = NULL, df = NULL, toggle.control = FALSE,
  icon.size.scalar = "autoscale", src.img.width = NULL,
  target.icon.width = 30, size.scale.lims = c(0.5, 1.25),
  label = NULL, label.params = list(), tooltip = NULL,
  tooltip.params = list())

```

Arguments

point.obj	SpatialPointsDataframe, SpatialPoints, or a matrix containing columns of point longitudes and latitudes, respectively.
src.img	character vector of image file paths.
mapping	list created by ol_aes. Used for aesthetic mapping.
name	character Layer name.
df	data.frame with same number of rows as point.obj coordinate matrix.
toggle.control	logical indicating whether this layer will have a visibility toggle.
icon.size.scalar	numeric scalar vector or 'autoscale'. The width of the icon on the map will be scaled by this input from the original image width. The default 'autoscale' uses the png, jpeg, or tiff package to scale each image to target.icon.width.

<code>src.img.width</code>	numeric vector of widths of user-supplied images, in pixels. If <code>icon.size.scalar</code> is not supplied and <code>src.img.width</code> is not provided, image widths will be detected using the png, jpeg, or tiff package.
<code>target.icon.width</code>	numeric desired width of icons on map, in pixels. Only used if <code>icon.size.scalar</code> is 'autoscale'.
<code>size.scale.lims</code>	numeric vector containing the minimum and maximum image scaling for size aesthetic mappings. A value of 1 results renders the image at the default size, determined by <code>target.icon.width</code> or <code>icon.size.scalar</code> .
<code>label</code>	character vector of point feature labels.
<code>label.params, tooltip.params</code>	named lists (e.g., <code>list(property=value)</code>) of label and tooltip position and format parameters. See ol_geom_polygon documentation.
<code>tooltip</code>	character vector of point feature tooltip popups.

Details

This function stores the data required to generate an OpenLayers vector layer with features using Point geometries and user-supplied point icons.

Value

A list object of class `Layer.SpatialIcon`.

Aesthetics

- `iconimage`
- `iconsize`

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_circle](#), [ol_geom_line](#), [ol_geom_point](#)

Examples

```
some.r.servers <- matrix(
  c(
    144.964, -37.798,
    -122.920, 49.278,
    121.494, 31.307,
    25.083, 35.307,
    -21.930, 64.149,
    11.877, 45.407,
    -99.200, 19.345,
    5.322, 60.388,
    -8.224, 39.400,
    -8.616, 41.147,
    -73.953, 40.768,
    20.304, 63.821,
    8.548, 47.376,
    33.031, 35.247,
    -78.938, 36.001,
    -123.279, 44.564,
```

```

        -96.797,32.777
    ),
    byrow=TRUE,
    ncol=2
)
r.server.names <- c(
  'School of Mathematics and Statistics, University of Melbourne',
  'Simon Fraser University, Burnaby',
  'Shanghai University',
  'University of Crete',
  'Marine Research Institute',
  'University of Padua',
  'Instituto Tecnologico Autonomo de Mexico',
  'University of Bergen',
  'RadicalDevelop, Lda',
  'University of Porto',
  'Four Dots',
  'Academic Computer Club, Umeå University',
  'ETH Zurich',
  'Middle East Technical University Northern Cyprus Campus, Mersin',
  'Duke University, Durham, NC',
  'Oregon State University',
  'Revolution Analytics, Dallas, TX'
)
r.icon <- "https://www.r-project.org/Rlogo.png"
## If width is not provided image must be local
## and png package must be installed.
r.icon.width <- 200
r.map <- ol_map(
  center=c(-100,30),
  zoom=3
) +
  streetmap()+
  ol_geom_icon(
    some.r.servers,
    r.icon,
    name="R Servers",
    icon.size.scalar='autoscale',
    src.img.width=r.icon.width,
    toggle.control=TRUE,
    tooltip=r.server.names
  )
## Not run:
# Save as HTML and open in browser
ol_map2HTML(r.map, 'R-servers.html')
browseURL("R-servers.html")

## End(Not run)

```

ol_geom_line

OpenLayers Line Layer

Description

Function to create a line layer to add to an OpenLayers Map object.

Usage

```
ol_geom_line(line.obj, mapping = ol_aes(), name = NULL, df = NULL,
  toggle.control = FALSE, lwd = 1, ol.lty = list(),
  color = "#000000", label = NULL, label.params = list(),
  tooltip = NULL, tooltip.params = list())
```

Arguments

line.obj	SpatialLinesDataFrame, SpatialLines, list of lines-like objects, or a two-column matrix of longitude-latitude coordinates to be used as ordered line object coordinates.
mapping	list created by ol_aes.
name	character Layer name.
df	data.frame with same number of lines-like objects as line.obj. Used for aesthetic mapping. Defaults to line.obj@data if class(polygon.obj) == SpatialLinesDataFrame and df is not provided.
toggle.control	logical indicating whether this layer will have a visibility toggle.
lwd	numeric line feature width. Used only if no lwd aesthetic is provided in mapping
ol.lty	(experimental) numeric vector with length > 1, or list of such vectors. Used only if no ol.lty aesthetic is provided in mapping. See OpenLayers ol/style/Stroke Documentation , 'lineDash' property for more information.
color	character line color string, or vector of color strings. Used only if no color aesthetic is provided in mapping
label	character vector of line feature labels.
label.params, tooltip.params	named lists (e.g., list(property=value)) of label and tooltip position and format parameters. See ol_geom_polygon documentation.
tooltip	character vector of line feature tooltip popups.

Details

This function creates a list object containing the data required to generate an OpenLayers vector layer with features using MultiLineString. See Openlayers [MultiLineString Documentation](#) for details.

Value

A list object of class Layer.SpatialLine.

Aesthetics

- color
- lwd
- ol.lty (experimental; See OpenLayers [ol/style/Stroke Documentation](#), 'lineDash' property for more information.)

See Also

[ol_aes](#), [ol_map](#), [ol_geom_point](#), [ol_geom_polygon](#), [ol_geom_circle](#)

Examples

```

line.matrix1 <- matrix(
  c(
    -80.4, -80.4,
    25.78, 25.88
  ),
  ncol=2
)
line.matrix2 <- matrix(
  c(
    -80.25, -80.35,
    25.65, 25.65
  ),
  ncol=2
)
line.list <- list(line.matrix1, line.matrix2)
line.df <- data.frame(
  direction=c("vertical", "horizontal"),
  no=c(1, 2)
)
miami.gray.basemap <- ol_map(
  center=c(-80.385790, 25.782618),
  zoom=9
) +
  lightgray()
line.layer <- ol_geom_line(
  line.list,
  mapping=ol_aes(
    color=no,
    lwd=direction
  ),
  df=line.df,
  name="Miami Lines",
  toggle.control=TRUE,
  tooltip=line.df$direction
)
line.color.scale <- ol_scale_color_continuous(
  name="Number",
  display=TRUE
)
line.width.scale <- ol_scale_lwd_discrete(
  lwd.vector=c(
    horizontal=2,
    vertical=4
  ),
  name="Direction",
  display=TRUE
)
line.map.miami <- miami.gray.basemap +
  line.layer +
  line.color.scale +
  line.width.scale
## Not run:
# Output to file and view
ol_map2HTML(
  line.map.miami,

```

```
'miami_lines.html',
  map.heading="Miami Lines"
)
browseURL("miami_lines.html")

## End(Not run)
```

ol_geom_point

OpenLayers Point Layer

Description

Function to create a points layer to add to an OpenLayers Map object.

Usage

```
ol_geom_point(point.obj, mapping = ol_aes(), name = NULL, df = NULL,
  toggle.control = FALSE, fill = "#00FF00", fill.opacity = 1,
  marker = "pin", size = 0.5, label = NULL, label.params = list(),
  tooltip = NULL, tooltip.params = list())
```

Arguments

point.obj	SpatialPointsDataframe, SpatialPoints, or a matrix containing columns of point longitudes and latitudes, respectively.
mapping	list created by ol_aes. Used for aesthetic mapping.
name	character Layer name.
df	data.frame with same number of rows as point.obj coordinate matrix.
toggle.control	logical indicating whether this layer will have a visibility toggle.
fill	character color string, or vector of color strings. Used only if no fill aesthetic is provided in mapping
fill.opacity	numeric in [0,1]. Controls circle opacity if no opacity provided in fill or fill aesthetic.
marker	character. The 'pin' marker draws map pointers similar to most web map applications. The 'dot' or 'point' markers render as circular points on the map. Other marker types are not supported by this method.
size	numeric point icon size scalar or vector scalars. Used only if no size aesthetic is provided in mapping. A value of 1 translates to an icon width of 40 pixels for "pin" markers, or 20 pixels for "dot" markers.
label	character vector of point feature labels.
label.params, tooltip.params	named lists (e.g., list(property=value)) of label and tooltip position and format parameters. See ol_geom_polygon documentation.
tooltip	character vector of point feature tooltip popups.

Details

This function stores the data required to generate an OpenLayers vector layer with features using Point geometries. See OpenLayers [Point Documentation](#) for details.

Value

A list object of class `Layer.SpatialPoint`.

Aesthetics

- fill
- size

See Also

[ol_aes](#), [ol_map](#), [ol_geom_polygon](#), [ol_geom_circle](#), [ol_geom_line](#), [ol_geom_icon](#)

Examples

```
point.matrix <- matrix(
  c(
    -80.885+runif(10),
    25.282618+runif(10)
  ),
  ncol=2
)
point.df <- data.frame(
  pt.type=sample(c("A","B"),10,replace=TRUE),
  pt.value=runif(10)*10
)
miami.map <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
miami.points <- ol_geom_point(
  point.matrix,
  df=point.df,
  mapping=ol_aes(fill=pt.type,size=pt.value),
  name="Random Points of Interest",
  marker="pin",
  toggle.control=TRUE,
  tooltip=point.df$pt.type
)
size.scale <- ol_scale_size_continuous(
  display=TRUE,
  draw.fill='green'
)
fill.scale <- ol_scale_fill_discrete(
  c(B='red',A='green'),
  display=TRUE
)
miami.points.map <- miami.map +
  miami.points +
  size.scale +
  fill.scale

## Not run:
# Output to file and view
ol_map2HTML(
  miami.points.map,
```

```
'Miami_points.html'
)
browseURL('Miami_points.html')

## End(Not run)
```

ol_geom_polygon

OpenLayers Polygon Layer

Description

Function to create a polygon layer to add to an OpenLayers Map object.

Usage

```
ol_geom_polygon(polygon.obj, mapping = ol_aes(), name = NULL,
  df = NULL, toggle.control = FALSE, fill = "#00FF00",
  fill.opacity = 0.5, lwd = 1, ol.lty = list(), color = "#000000",
  label = NULL, label.params = list(), tooltip = NULL,
  tooltip.params = list())
```

Arguments

polygon.obj	SpatialPolygonsDataFrame, SpatialPolygons, list of polygon-like objects, or a two-column matrix of longitude-latitude coordinates to be used as ordered polygon vertices.
mapping	list created by ol_aes.
name	character Layer name.
df	data.frame with same number of polygon objects as polygon.obj. Used for aesthetic mapping. Defaults to polygon.obj@data if class(polygon.obj)==SpatialPolygonsDataFrame and df is not provided.
toggle.control	logical indicating whether this layer will have a visibility toggle.
fill	character color string, or vector of color strings. Used only if no fill aesthetic is provided in mapping
fill.opacity	numeric in [0,1]. Controls circle opacity if no opacity provided in fill or fill aesthetic.
lwd	numeric polygon border width. Used only if no lwd aesthetic is provided in mapping
ol.lty	(experimental) numeric vector with length > 1, or list of such vectors. Used only if no ol.lty aesthetic is provided in mapping. See OpenLayers ol/style/Stroke Documentation , 'lineDash' property for more information.
color	character border color string, or vector of color strings. Used only if no color aesthetic is provided in mapping
label	character vector of polygon feature labels.
label.params	named list (e.g., list(property=value)) of label position and format parameters. See below.
tooltip	character vector polygon feature tooltip popups.
tooltip.params	named list (e.g., list(property=value)) of tooltip position and format parameters. See below.

Details

This function creates a list object containing the data required to generate an OpenLayers vector layer with features using MultiPolygon. See OpenLayers [MultiPolygon Documentation](#) for details.

Value

A list object of class `Layer.SpatialPolygon`.

Aesthetics

- `fill`
- `color`
- `lwd`
- `ol_lty` (experimental; See OpenLayers [ol/style/Stroke Documentation](#), 'lineDash' property for more information.)

Formatting Labels With `label.params`

The `label.params` parameter provide direct access to OpenLayers feature text styling (see [OpenLayers Documentation](#)). Multiple values for any of these properties is not supported. The following `ol/style/Text` properties are supported:

<code>font</code>	character label font CSS string
<code>offsetX</code>	numeric label x-offset
<code>offsetY</code>	numeric label y-offset
<code>rotation</code>	numeric label rotation
<code>textAlign</code>	character label text horizontal alignment
<code>textBaseline</code>	character label text vertical alignment
<code>stroke_color</code>	character text color
<code>fill_color</code>	character text fill color

Formatting Tooltips With `label.params`

The `tooltip.params` parameter enable the user to control tooltip formats. Unlike the `label.params`, not all `tooltip.params` are embedded in Openlayers javascript objects; some are translated to corresponding CSS properties. The table below provides a list of supported properties and their descriptions. OpenLayers [Overlay Documentation](#) provides additional information about Overlay Properties.

<code>font</code>	character tooltip CSS font
<code>offsetX</code>	numeric OpenLayers Overlay x-offset
<code>offsetY</code>	numeric OpenLayers Overlay y-offset
<code>positioning</code>	character OpenLayers Overlay positioning string
<code>stroke_color</code>	character Tooltip CSS font-color
<code>fill_color</code>	character Tooltip CSS background-color
<code>padding,</code>	character Tooltip CSS padding
<code>border,</code>	character Tooltip CSS border
<code>borderradius</code>	character Tooltip CSS border-radius

See Also

[ol_aes](#), [ol_map](#), [ol_geom_point](#), [ol_geom_line](#), [ol_geom_circle](#)

Examples

```

polygon.matrix1 <- matrix(
  c(
    -80.385+c(0,0.05,0.05,0,0),
    25.782618+c(0,0,0.05,0.05,0)
  ),
  ncol=2
)
polygon.matrix2 <- matrix(
  c(
    -80.34+c(0,0.05,0.025,0),
    25.73++c(0,0,0.025*sqrt(3),0)
  ),
  ncol=2
)
polygon.list<-list(polygon.matrix1,polygon.matrix2)
polygon.df <- data.frame(shape=c("rectangle","triangle"),no=c(1,2))
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
polygon.layer <- ol_geom_polygon(
  polygon.list,
  mapping=ol_aes(
    fill=shape,
  ),
  df=polygon.df,
  lwd=1,
  name="Miami Polygons",
  toggle.control=TRUE,
  tooltip=polygon.df$no
)
polygon.fill.scale <- ol_scale_fill_discrete(display=TRUE)
polygons.over.miami <- miami.OSM.basemap +
  polygon.layer +
  polygon.fill.scale

## Not run:
# Output to file and view
ol_map2HTML(
  polygons.over.miami,
  'miami_polygons.html',
  map.heading="Miami Shapes",
  map.note="Note: Mouseover popup values are
    independent of shape size & color."
)
browseURL("miami_polygons.html")

## End(Not run)

```

ol_geom_text	<i>OpenLayers Text Layer</i>
--------------	------------------------------

Description

Function to create a Text layer to add to an OpenLayers Map object.

Usage

```
ol_geom_text(point.obj, label, name = NULL, toggle.control = FALSE,
  label.params = list(), tooltip = NULL, tooltip.params = list())
```

Arguments

point.obj	SpatialPointsDataframe, SpatialPoints, or a matrix containing columns of point longitudes and latitudes, respectively.
label	character vector of text labels to put at points.
name	character Layer name.
toggle.control	logical indicating whether this layer will have a visibility toggle.
label.params	named list (e.g., list(property=value)) of label position and format parameters. See below.
tooltip	character vector of point feature tooltip popups.
tooltip.params	named list (e.g., list(property=value)) of tooltip position and format parameters. See ol_geom_polygon documentation.

Details

This function stores the data required to generate an OpenLayers vector layer with text features using Point geometries. It does not enable aesthetic mappings to variables.

Value

A list object of class `Layer.Text`.

Formatting Labels With label.params

The `label.params` parameter provide direct access to OpenLayers feature text styling (see [OpenLayers Documentation](#)). Multiple values for any of these properties is not supported. The following `ol/style/Text` properties are supported:

font	character label font CSS string
offsetX	numeric label x-offset
offsetY	numeric label y-offset
rotation	numeric label rotation
textAlign	character label text horizontal alignment
textBaseline	character label text vertical alignment
stroke_color	character text color
fill_color	character text fill color

See Also[ol_map](#), [ol_geom_point](#)**Examples**

```

text.pts <- matrix(
  c(
    -101.5, 39.2,
    -101.1, 54,
    -101.1, 21.4
  ),
  byrow=TRUE,
  ncol=2
)
text.labels <- c("USA", "Canada", "Mexico")
mymap <- ol_map(
  center=c(-100,25),
  zoom=3
) +
  oceanbase() +
  ol_geom_text(
    text.pts,
    text.labels,
    toggle.control=TRUE,
    label.params=list(
      font="16px sans-serif",
      stroke_color="#FF0000",
      fill_color="#FFFFFF00"
    )
  )
## Not run:
# Write to file and view in browser
ol_map2HTML(mymap, "textmap.html")
browseURL("textmap.html")

## End(Not run)

```

ol_map*OpenLayers Map*

Description

Create an OpenLayers Map Object.

Usage

```
ol_map(zoom = 10, center = c(-117.1611, 32.7157))
```

Arguments

zoom	integer map initial zoom level.
center	numeric vector of length 2 containing decimal longitude and latitude coordinates for initial map center.

Details

This function creates a new S3 OpenLayers Map object with no layers. If `ol.source.url` is `NULL` and `nga.olsource` is `FALSE`, OpenLayers Javascript source will be embedded directly into the HTML when `ol_map2HTML` or `ol_map2Strings` is called. Otherwise, the output HTML/Javascript with source the OpenLayers library according to the value of `ol.source.url`, or the NGA hosted OpenLayers library if `nga.olsource` is `TRUE`.

Value

A list object of class `Ol.Map`.

See Also

[ol_map2HTML](#), [ol_map2Strings](#), [public_OSM_basemap](#), [nga_basemap](#), [public_arcgis_basemap](#), [user_arcgis_basemap](#)

Examples

```
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
## Not run:
ol_map2HTML(
  miami.OSM.basemap,
  'miami.html',
  map.heading="Miami, FL"
)
browseURL("miami.html")

## End(Not run)
```

ol_map2HTML

Export OpenLayers Map to file.

Description

Writes `Ol.Map` object to HTML file.

Usage

```
ol_map2HTML(ol.map.obj, file.name, page.name = "ROpenLayers Map",
  width = NULL, height = NULL, ol.source.url = NULL,
  nga.olsource = FALSE, map.heading = NULL, map.note = NULL,
  nice.format = FALSE, IE.compatability.view = TRUE)
```

Arguments

<code>ol.map.obj</code>	Ol.Map object to be exported.
<code>file.name</code>	character output HTML file name.
<code>page.name</code>	character page title to be included in the HTML head section.
<code>width</code>	numeric or character CSS value width of map container.
<code>height</code>	numeric or character CSS value height of map container.
<code>ol.source.url</code>	character string containing the url to the OpenLayers javascript library. Ignored if <code>nga.olsource</code> is TRUE.
<code>nga.olsource</code>	logical. TRUE will use the OpenLayers 3.16.0 javascript library from https://home.gvs.nga.mil (requires authentication); FALSE uses the sources the <code>ol.source.url</code> , if provided, or embeds the OpenLayers 5.3.0 JavaScript code in the HTML head. Only used if <code>ol.source.url</code> is missing or NULL.
<code>map.heading</code>	character heading to be placed over map in html h1 tag.
<code>map.note</code>	character note placed in html paragraph (<p>) tag centered under map container.
<code>nice.format</code>	logical. If TRUE, output file will be formatted with new lines and indentation for human readability.
<code>IE.compatibility.view</code>	logical. If TRUE, the statement <pre><meta http-equiv="X-UA-Compatible" content="IE=edge"/></pre> to the HTML document head. This statement is required for some browsers to render the map.

Details

Ol.Map object is written to HTML file with embedded javascript. The file will include or source the OpenLayers javascript library as specified in the Ol.Map object (see [ol_map](#)). The Javascript will call any REST APIs required for each layer in order to produce an output file with supporting images, if required, that can be placed directly into a directory hosted by a minimal http server.

See Also

[ol_map](#), [ol_map2Strings](#),

Examples

```
mymap <- ol_map()
base.layer <- lightgray()
mymap <- mymap + base.layer
## Not run:
# The following writes HTML and needed images
ol_map2HTML(mymap, "SanDiego.html", nice.format=TRUE)
# Open in browser
browseURL("SanDiego.html")

## End(Not run)
```

ol_map2Strings	<i>OpenLayers Map HTML to List</i>
----------------	------------------------------------

Description

Assigns Ol.Map HTML content to list.

Usage

```
ol_map2Strings(ol.map.obj, width = NULL, height = NULL,
  ol.source.url = NULL, nga.olsource = FALSE, map.heading = NULL,
  map.note = NULL)
```

Arguments

ol.map.obj	Ol.Map object to be exported.
width	numeric or character CSS value width of map container.
height	numeric or character CSS value height of map container.
ol.source.url	character string containing the url to the OpenLayers javascript library. Ignored if nga.olsource is TRUE.
nga.olsource	logical. TRUE will use the OpenLayers 3.16.0 javascript library from https://home.gvs.nga.mil (requires authentication); FALSE uses the sources the ol.source.url, if provided, or embeds the OpenLayers 3.21.1 JavaScript code in the HTML head. Only used if ol.source.url is missing or NULL.
map.heading	character heading to be placed over map in html h1 tag.
map.note	character note placed in html paragraph (<p>) tag centered under map container.

Details

Ol.Map object HTML is exported to a list object that can be deployed in a variety of applications or server environments. See exmaples for a minimal example using RShiny. This method does not currently support adding multiple maps to the same web page, as javascript variable names would be replicated.

Value

list object with the following character elements:

\$head.meta.IE.compatibility	HTML meta tag for IE compatability viewing.
\$head.script	HTML script block including or sourcing the OpenLayers Javascript library (see ol.m
\$style	CSS code for styling the map and legends.
\$body.html	HTML map and legend containers, and associated elements.
\$body.script	Javascript code writing the layer and map objects.

See Also

[ol_map](#), [ol_map2HTML](#),

Examples

```
heatmap.pts <- matrix(
  c(
    rnorm(100,-80.385,1), #Miami Longitudes
    rnorm(100,-117.1611,3), #San Diego Longitudes
    rnorm(100,25.782618,1), #Miami Latitudes
    rnorm(100,32.7157,3) # San Diego Latitudes
  ),ncol=2
)
mymap <- ol_map(
  center=c(-98.5,28.5),
  zoom=4
) +
  streetmap() +
  ol_geom_heatmap(
    heatmap.pts,
    name="Random Heatmap",
    toggle.control=TRUE,
    opacity=0.25
  )
## The following line will create image files
## as needed for point layers and legends.
## None are required in this example.
HTML.strings <- ol_map2Strings(
  mymap,
  nga.olsource=FALSE,
  map.note="Heatmap of random points centered on Miami and San Diego."
)
## Minimal shiny example
## Not run:
library(shiny)
ui <- shinyUI(
  fluidPage(
    #Add OpenLayers Javascript source & CSS to head
    tags$head(
      HTML(HTML.strings[[1]])
      HTML(HTML.strings[[2]]),
      tags$style(HTML(HTML.strings[[3]]))
    ),
    titlePanel("Random Heatmap"),
    mainPanel(
      tags$div(HTML(HTML.strings[[4]]))
    ),
    tags$script(HTML(HTML.strings[[5]]))
  )
)
server <- function(input,output){
}
shinyApp(ui=ui,server)

## End(Not run)
```

ol_scale_color_continuous

Line Color Scale (Continuous)

Description

Specify a line (or border) color mapping scale.

Usage

```
ol_scale_color_continuous(low.val, high.val, low.col = NULL,
  high.col = NULL, rotate.clockwise = TRUE, name = NULL,
  na.col.val = "#FFFFFF00", opacity = 1, preserve.opacity = NULL,
  display = FALSE)
```

Arguments

low.val	numeric the minimum variable value to be mapped to the lowest color.
high.val	numeric the maximum variable value to be mapped to the highest color.
low.col	character the "low" color.
high.col	character the "high" color.
rotate.clockwise	logical. If TRUE, continuous scale will map to colors on a clockwise rotation from low.col to high.col on the hue-saturation-value (HSV) color space. If FALSE, rotation will be counter-clockwise.
name	character the scale name.
na.col.val	character the color assigned to non-numeric or NA values.
opacity	numeric in [0,1]. The fill opacity, if not specified in the low.col and high.col colors.
preserve.opacity	logical indicating whether to draw the legend with the same opacity as the feature fills on the map.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an img tag.

Details

This method maps OpenLayers feature line or border colors to continuous variable values. This scale can be added to an `Ol.Map` S3 object only if the `Ol.Map` object has a layer with a "color" mapping to a numeric variable. If no such layer exists, attempts to add this type of scale will result in a warning. Attempts to apply this scale to a non-numeric variable will throw an error.

Value

list of class `Scale.Color.Continuous`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_line](#)

Examples

```

line.matrix1 <- matrix(
  c(
    -80.4, -80.4,
    25.78, 25.88
  ),
  ncol=2
)
line.matrix2 <- matrix(
  c(
    -80.25, -80.35,
    25.65, 25.65
  ),
  ncol=2
)
line.list <- list(line.matrix1, line.matrix2)
line.df <- data.frame(
  direction=c("vertical", "horizontal"),
  no=runif(2)
)
miami.gray.basemap <- ol_map(
  center=c(-80.385790, 25.782618),
  zoom=9
) +
  lightgray()
line.layer <- ol_geom_line(
  line.list,
  mapping=ol_aes(
    color=no #continuous mapping
  ),
  df=line.df,
  name="Miami Lines",
  toggle.control=TRUE,
  lwd=5,
  tooltip=line.df$no
)
line.color.scale <- ol_scale_color_continuous(
  low.val = 0,
  high.val = 1,
  low.col = 'red',
  high.col = 'green',
  opacity = 1,
  preserve.opacity = TRUE,
  name = "Number",
  display = TRUE
)
line.map.miami <- miami.gray.basemap +
  line.layer +
  line.color.scale

## Not run:
# Output to file and view
ol_map2HTML(
  line.map.miami,
  'miami_lines.html',
  map.heading="Miami Lines"

```

```
)
browseURL("miami_lines.html")

## End(Not run)
```

ol_scale_color_discrete

Line Color Scale (Discrete)

Description

Specify a discrete line color mapping scale.

Usage

```
ol_scale_color_discrete(color.vector = NULL, name = NULL,
  na.col.val = "#FFFFFF00", ordered.values = NULL, opacity = 1,
  preserve.opacity = FALSE, draw.lty = "solid", draw.lwd = 3,
  display = FALSE)
```

Arguments

color.vector	character named vector of the form c(value=color). If NULL, a default color mapping is assigned.
name	character the scale name.
na.col.val	character the color assigned to unrecognized or NA values.
ordered.values	character, numeric, or factor vector containing the ordered unique discrete variable values. This input is used to determine the order of the values appearing in the legend. If not supplied, the order is taken from names(color.vector).
opacity	numeric in [0,1]. The color opacity, if not specified in the color.vector colors.
preserve.opacity	logical indicating whether to draw the legend with the same opacity as the feature fills on the map.
draw.lty	character indicating the line type for the legend only. This will be passed to an R plot command. See par .
draw.lwd	numeric width of lines only used in drawing the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an img tag. If FALSE, the draw.* inputs are ignored.

Details

This method maps OpenLayers feature line colors to discrete variable values. This scale can be added to an Ol.Map S3 object only if the Ol.Map object has a layer with a "color" mapping to a numeric, character, or factor type variable. If no such layer exists, attempts to add this type of scale will result in a warning. The color.vector input enables the user to specify the exact mapping, assigning colors to specific variable values.

Value

list of class `Scale.Color.Discrete`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_line](#)

Examples

```
line.matrix1 <- matrix(
  c(
    -80.4, -80.4,
    25.78, 25.88
  ),
  ncol=2
)
line.matrix2 <- matrix(
  c(
    -80.25, -80.35,
    25.65, 25.65
  ),
  ncol=2
)
line.list <- list(line.matrix1, line.matrix2)
line.df <- data.frame(
  direction=c("vertical", "horizontal"),
  no=runif(2)
)
miami.gray.basemap <- ol_map(
  center=c(-80.385790, 25.782618),
  zoom=9
) +
  lightgray()
line.layer <- ol_geom_line(
  line.list,
  mapping=ol_aes(
    color=direction # discrete mapping
  ),
  df=line.df,
  name="Miami Lines",
  toggle.control=TRUE,
  lwd=5
)
line.color.scale <- ol_scale_color_discrete(
  color.vector=c(
    vertical = 'red',
    horizontal = 'blue'
  ),
  name="Direction",
  display=TRUE
)
line.map.miami <- miami.gray.basemap +
  line.layer +
  line.color.scale
## Not run:
# Output to file and view
```

```

ol_map2HTML(
  line.map.miami,
  'miami_lines.html',
  map.heading="Miami Lines"
)
browseURL("miami_lines.html")

## End(Not run)

```

ol_scale_fill_continuous

Fill Color Scale (Continuous)

Description

Specify a continuous fill color mapping scale.

Usage

```

ol_scale_fill_continuous(low.val, high.val, low.col = NULL,
  high.col = NULL, rotate.clockwise = TRUE, name = NULL,
  na.col.val = "#FFFFFF00", opacity = 1, preserve.opacity = FALSE,
  display = FALSE)

```

Arguments

low.val	numeric the minimum variable value to be mapped to the lowest color.
high.val	numeric the maximum variable value to be mapped to the highest color.
low.col	character the "low" color.
high.col	character the "high" color.
rotate.clockwise	logical. If TRUE, continuous scale will map to colors on a clockwise rotation from low.col to high.col on the hue-saturation-value (HSV) color space. If FALSE, rotation will be counter-clockwise.
name	character the scale name.
na.col.val	character the color assigned to non-numeric or NA values.
opacity	numeric in [0,1]. The fill opacity, if not specified in the low.col and high.col colors.
preserve.opacity	logical indicating whether to draw the legend with the same opacity as the feature fills on the map.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an img tag.

Details

This method maps OpenLayers feature fill colors to continuous variable values. This scale can be added to an Ol.Map S3 object only if the Ol.Map object has a layer with a "fill" mapping to a numeric variable. If no such layer exists, attempts to add this type of scale will result in a warning. Attempts to add this scale to a discrete variable mapping will throw an error.

Value

list of class `Scale.Fill.Continuous`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_circle](#)

Examples

```

polygon.matrix1 <- matrix(
  c(
    -80.385+c(0,0.05,0.05,0,0),
    25.782618+c(0,0.05,0.05,0)
  ),
  ncol=2
)
polygon.matrix2 <- matrix(
  c(
    -80.34+c(0,0.05,0.025,0),
    25.73++c(0,0,0.025*sqrt(3),0)
  ),
  ncol=2
)
polygon.list<-list(polygon.matrix1,polygon.matrix2)
polygon.df <- data.frame(shape=c("rectangle","triangle"),no=runif(2))
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
polygon.layer <- ol_geom_polygon(
  polygon.list,
  mapping=ol_aes(
    fill=no #numeric mapping
  ),
  df=polygon.df,
  lwd=1,
  name="Miami Polygons",
  toggle.control=TRUE,
  tooltip=polygon.df$no
)
polygon.fill.scale <- ol_scale_fill_continuous(
  low.val=0,
  high.val=1,
  low.col='red',
  high.col='green',
  opacity=0.5,
  preserve.opacity=FALSE,
  display=TRUE
)
polygons.over.miami <- miami.OSM.basemap +
  polygon.layer +
  polygon.fill.scale

## Not run:
# Output to file and view

```



```

ol_map2HTML(
  polygons.over.miami,
  'miami_polygons.html',
  map.heading="Miami Shapes",
  map.note="Note: Mouseover popup values are
    independent of shape size & color."
)
browseURL("miami_polygons.html")

## End(Not run)

```

ol_scale_fill_discrete

Fill Color Scale (Discrete)

Description

Specify a discrete fill color mapping scale.

Usage

```

ol_scale_fill_discrete(color.vector = NULL, name = NULL,
  na.col.val = "#FFFFFF00", ordered.values = NULL,
  ordinal.scale = FALSE, opacity = 1, preserve.opacity = FALSE,
  draw.lines = NULL, draw.color = "black", draw.lty = "solid",
  draw.lwd = 1, display = FALSE)

```

Arguments

color.vector	character named vector of the form c(value=color). If NULL, a default color mapping is assigned.
name	character the scale name.
na.col.val	character the color assigned to unrecognized or NA values.
ordered.values	character, numeric, or factor vector containing the ordered unique discrete variable values. This input is used to determine the order of the values appearing in the legend. If not supplied, the order is taken from names(color.vector).
ordinal.scale	logical. If TRUE, the colors in the legend will not have spaces between them.
opacity	numeric in [0,1]. The fill opacity, if not specified in the color.vector colors.
preserve.opacity	logical indicating whether to draw the legend with the same opacity as the feature fills on the map.
draw.lines	logical indicating whether to draw a border around each color in the legend. If NULL, a default is assigned according to the type of layer containing the scale.
draw.color	character color of the border in the legend.
draw.lty	character indicating the border line type for the legend only. This will be passed to an R plot command. See par .
draw.lwd	numeric width of border only used in drawing the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an img tag. If FALSE, the draw.* inputs are ignored.

Details

This method maps OpenLayers feature fill colors to discrete variable values. This scale can be added to an Ol.Map S3 object only if the Ol.Map object has a layer with a "fill" mapping to a numeric, character, or factor type variable. If no such layer exists, attempts to add this type of scale will result in a warning. The `color.vector` input enables the user to specify the exact mapping, assigning colors to specific variable values.

Value

list of class `Scale.Fill.Discrete`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_circle](#)

Examples

```

polygon.matrix1 <- matrix(
  c(
    -80.385+c(0,0.05,0.05,0,0),
    25.782618+c(0,0,0.05,0.05,0)
  ),
  ncol=2
)
polygon.matrix2 <- matrix(
  c(
    -80.34+c(0,0.05,0.025,0),
    25.73++c(0,0,0.025*sqrt(3),0)
  ),
  ncol=2
)
polygon.list<-list(polygon.matrix1,polygon.matrix2)
polygon.df <- data.frame(shape=c("rectangle","triangle"),no=runif(2))
miami.OSM.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  streetmap()
polygon.layer <- ol_geom_polygon(
  polygon.list,
  mapping=ol_aes(
    fill=shape #discrete mapping
  ),
  df=polygon.df,
  lwd=1,
  name="Miami Polygons",
  toggle.control=TRUE
)
polygon.fill.scale <- ol_scale_fill_discrete(
  color.vector=c(
    rectangle = 'red',
    triangle = 'blue'
  ),
  name = "Shape",
  opacity = 0.5,
  preserve.opacity = FALSE,

```

```

    display = TRUE
  )
  polygons.over.miami <- miami.OSM.basemap +
    polygon.layer +
    polygon.fill.scale

## Not run:
# Output to file and view
ol_map2HTML(
  polygons.over.miami,
  'miami_polygons.html',
  map.heading="Miami Shapes",
  map.note="Note: Mouseover popup values are
    independent of shape size & color."
)
browseURL("miami_polygons.html")

## End(Not run)

```

ol_scale_iconimage_discrete

Icon Image Scale

Description

Map icon images to discrete variable values.

Usage

```

ol_scale_iconimage_discrete(icon.img.vector = NULL, name = NULL,
  na.img.src = NULL, ordered.values = NULL, display = FALSE,
  icon.width = NULL)

```

Arguments

icon.img.vector	character named vector of the form <code>c(value=image.path)</code> . If NULL, a default mapping is assigned to the images available in the layer.
name	character the scale name.
na.img.src	character image path assigned to unrecognized or NA values.
ordered.values	character, numeric, or factor vector giving the ordering for the legend display. If NULL, the ordering from <code>icon.img.vector</code> is used.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in one or more <code>img</code> tags.
icon.width	numeric width(s) of icons for the legend display only. Icon widths for the map overlay are defined in ol_geom_icon .

Details

This method maps OpenLayers point (icon) feature images to discrete variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with an "iconimage" mapping to a numeric, character, or factor variable. If no such layer exists, attempts to add this type of scale will result in a warning.

Value

list of class `Scale.IconImage.Discrete`.

See Also

[ol_map](#), [ol_geom_icon](#),

Examples

```
freebsd.icon <- "https://www.freebsd.org/gifs/daemon-phk.png"
freebsd.icon.width <- 191
r.icon <- "https://www.r-project.org/Rlogo.png"
r.icon.width <- 200
loc.df <- data.frame(
  lon=c(
    -73.953,
    -78.938,
    -74.007
  ),
  lat=c(
    40.768,
    36.001,
    40.708
  ),
  type=c(
    "R",
    "R",
    "BSD"
  )
)

icon.map <- ol_map(
  center=c(-75,38),
  zoom=5
) +
  streetmap()+
  ol_geom_icon(
    loc.df[,1:2],
    c(r.icon,freebsd.icon),
    mapping=ol_aes(iconimage=type),
    df = loc.df,
    name="Some Open Source Locations",
    icon.size.scalar='autoscale',
    src.img.width=c(r.icon.width,freebsd.icon.width),
    toggle.control=TRUE
  ) +
  ol_scale_iconimage_discrete(
    c(R=r.icon,BSD=freebsd.icon),
    display=TRUE
  )
## Not run:
# Oave as HTML and open in browser
ol_map2HTML(
  icon.map,
  'servers.html'
)
```

```
browseURL("servers.html")

## End(Not run)
```

```
ol_scale_iconsize_continuous
      Icon Size Scale (Continuous)
```

Description

Specify a continuous size mapping for an icon layer.

Usage

```
ol_scale_iconsize_continuous(low.val, high.val, low.size = 0.33,
  high.size = 0.75, name = NULL, na.size.val = 0.33,
  legend.breaks = NULL, display = FALSE, display.icon.img.src = NULL)
```

Arguments

low.val	numeric the minimum variable value to be mapped to the smallest size.
high.val	numeric the maximum variable value to be mapped to the largest size.
low.size	numeric smallest size scalar.
high.size	numeric largest size scalar.
name	character the scale name.
na.size.val	numeric the size scalar assigned to non-numeric or NA values.
legend.breaks	numeric ordered vector of variable values to display in the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in one or more <code>img</code> tags.
display.icon.img.src	character path to image file to use in size legend. If NULL, the first image supplied to the icon layer will be used.

Details

This method maps OpenLayers point (icon) feature sizes to continuous variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with an "iconsize" mapping to a numeric variable. If no such layer exists, attempts to add this type of scale will result in a warning. Attempt to apply this scale to a non-numeric variable will throw an error.

Size inputs to this method are applied as scalars to the icon widths. A size value of 1 translates to the `target.icon.width` assigned to the layer.

Value

list of class `Scale.IconSize.Continuous`.

See Also

[ol_map](#), [ol_geom_icon](#),

Examples

```

some.r.servers <- matrix(
  c(
    144.964,-37.798,
    -122.920,49.278,
    121.494,31.307,
    25.083,35.307,
    -21.930,64.149,
    11.877,45.407,
    -99.200,19.345,
    5.322,60.388,
    -8.224,39.400,
    -8.616,41.147,
    -73.953,40.768,
    20.304,63.821,
    8.548,47.376,
    33.031,35.247,
    -78.938,36.001,
    -123.279,44.564,
    -96.797,32.777
  ),
  byrow=TRUE,
  ncol=2
)
r.server.df <- data.frame(
  server.name=c(
    'School of Mathematics and Statistics, University of Melbourne',
    'Simon Fraser University, Burnaby',
    'Shanghai University',
    'University of Crete',
    'Marine Research Institute',
    'University of Padua',
    'Instituto Tecnologico Autonomo de Mexico',
    'University of Bergen',
    'RadicalDevelop, Lda',
    'University of Porto',
    'Four Dots',
    'Academic Computer Club, Umeå University',
    'ETH Zurich',
    'Middle East Technical University Northern Cyprus Campus, Mersin',
    'Duke University, Durham, NC',
    'Oregon State University',
    'Revolution Analytics, Dallas, TX'
  ),
  server.value = runif(17)*10,
  stringsAsFactors=FALSE
)
r.icon <- "https://www.r-project.org/Rlogo.png"
## If width is not provided image must be local
## and png package must be installed.
r.icon.width <- 200
r.map <- ol_map(
  center=c(-100,30),
  zoom=3
) +
  streetmap()+

```

```

    ol_geom_icon(
      some.r.servers,
      r.icon,
      mapping=ol_aes(iconsize=server.value),
      df = r.server.df,
      name="R Servers",
      icon.size.scalar='autoscale',
      src.img.width=r.icon.width,
      toggle.control=TRUE,
      tooltip=r.server.df$server.name
    ) +
    ol_scale_iconsize_continuous(
      low.val=0,
      high.val=10,
      legend.breaks=c(0,2.5,5,7.5,10),
      display=TRUE
    )
## Not run:
# Oave as HTML and open in browser
ol_map2HTML(
  r.map,
  'R-servers.html'
)
browseURL("R-servers.html")

## End(Not run)

```

ol_scale_iconsize_discrete

Icon Size Scale (Discrete)

Description

Specify a discrete size mapping for an icon layer.

Usage

```

ol_scale_iconsize_discrete(size.vector = NULL, name = NULL,
  na.size.val = 0.33, legend.breaks = NULL, display = FALSE,
  display.icon.img.src = NULL)

```

Arguments

size.vector	numeric named vector of the form c(value=width). If NULL, a default size mapping is assigned.
name	character the scale name.
na.size.val	numeric the size scalar assigned to non-numeric or NA values.
legend.breaks	numeric ordered vector of variable values to display in the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in one or more img tags.
display.icon.img.src	character path to image file to use in size legend. If NULL, the first image supplied to the icon layer will be used.

Details

This method maps OpenLayers point (icon) feature sizes to discrete variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with a "iconsize" mapping to a numeric, character, or factor variable. If no such layer exists, attempts to add this type of scale will result in a warning.

Size inputs to this method are applied as scalars to the icon widths. A size value of 1 translates to the `target.icon.width` assigned to the layer.

Value

list of class `Scale.IconSize.Discrete`.

See Also

[ol_map](#), [ol_geom_icon](#),

Examples

```
some.r.servers <- matrix(
  c(
    144.964, -37.798,
    -122.920, 49.278,
    121.494, 31.307,
    25.083, 35.307,
    -21.930, 64.149,
    11.877, 45.407,
    -99.200, 19.345,
    5.322, 60.388,
    -8.224, 39.400,
    -8.616, 41.147,
    -73.953, 40.768,
    20.304, 63.821,
    8.548, 47.376,
    33.031, 35.247,
    -78.938, 36.001,
    -123.279, 44.564,
    -96.797, 32.777
  ),
  byrow=TRUE,
  ncol=2
)
r.server.df <- data.frame(
  server.name=c(
    'School of Mathematics and Statistics, University of Melbourne',
    'Simon Fraser University, Burnaby',
    'Shanghai University',
    'University of Crete',
    'Marine Research Institute',
    'University of Padua',
    'Instituto Tecnologico Autonomo de Mexico',
    'University of Bergen',
    'RadicalDevelop, Lda',
    'University of Porto',
    'Four Dots',
    'Academic Computer Club, Umeå University',
```



```

      'ETH Zurich',
      'Middle East Technical University Northern Cyprus Campus, Mersin',
      'Duke University, Durham, NC',
      'Oregon State University',
      'Revolution Analytics, Dallas, TX'
    ),
    server.type = sample(c("A", "B", "C"), 17, replace=TRUE),
    stringsAsFactors=FALSE
  )
  r.icon <- "https://www.r-project.org/Rlogo.png"
  ## If width is not provided image must be local
  ## and png package must be installed.
  r.icon.width <- 200
  r.map <- ol_map(
    center=c(-100,30),
    zoom=3
  ) +
    streetmap()+
    ol_geom_icon(
      some.r.servers,
      r.icon,
      mapping=ol_aes(iconsize=server.type),
      df = r.server.df,
      name="R Servers",
      icon.size.scalar='autoscale',
      src.img.width=r.icon.width,
      toggle.control=TRUE,
      tooltip=r.server.df$server.type
    ) +
    ol_scale_iconsize_discrete(
      display=TRUE
    )
  ## Not run:
  # Oave as HTML and open in browser
  ol_map2HTML(
    r.map,
    'R-servers.html'
  )
  browseURL("R-servers.html")

  ## End(Not run)

```

ol_scale_lty_discrete *Line Type Scale (Experimental)*

Description

Specify a discrete line type mapping scale.

Usage

```

ol_scale_lty_discrete(lty.list = NULL, name = NULL, na.lty.val = NA,
  ordered.values = NULL, opacity = 1, draw.color = "black",
  draw.lwd = 1, display = FALSE)

```

Arguments

lty.list	numeric named list of the form <code>list(value=numeric.vector)</code> . If NULL, a default line type mapping is assigned. The input vectors will be converted to javascript numeric arrays. See the <code>lineDash</code> property in the OpenLayers Stroke Documentation for interpretation of these inputs.
name	character the scale name.
na.lty.val	numeric the <code>lineDash</code> vector assigned to unrecognized or NA values.
ordered.values	character, numeric, or factor vector containing the ordered unique discrete variable values. This input is used to determine the order of the values appearing in the legend. If not supplied, the order is taken from <code>names(lwd.vector)</code> .
opacity	numeric in [0,1]. The line opacity used in the legend only.
draw.color	character color used in the legend lines only.
draw.lwd	numeric indicating the line width for the legend only. This will be passed to an R plot command. See par .
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an <code>img</code> tag. If FALSE, the <code>draw.*</code> inputs are ignored.

Details

This method maps OpenLayers feature line dash types to discrete variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with a "lty" mapping to a numeric, character, or factor type variable. If no such layer exists, attempts to add this type of scale will result in a warning. The `lty.list` input enables the user to specify the exact mapping, assigning line dash types to specific variable values. The `lty` aesthetic does not have a continuous scale.

Note: this method does not result in consistent rendering for different browsers or map zoom levels.

Value

list of class `Scale.Lwd.Discrete`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_line](#)

Examples

```
line.matrix1 <- matrix(
  c(
    -80.4, -80.4,
    25.78, 25.88
  ),
  ncol=2
)
line.matrix2 <- matrix(
  c(
    -80.25, -80.35,
    25.65, 25.65
  ),
  ncol=2
)
```

```

)
line.list <- list(line.matrix1,line.matrix2)
line.df <- data.frame(
  direction=c("vertical","horizontal"),
  no=runif(2)
)
miami.gray.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
  lightgray()
line.layer <- ol_geom_line(
  line.list,
  mapping=ol_aes(
    lty=direction # discrete mapping
  ),
  df=line.df,
  name="Miami Lines",
  toggle.control=TRUE
)
line.type.scale <- ol_scale_lty_discrete(
  lty.list=list(
    vertical = 1,
    horizontal = c(5,5)
  ),
  name="Direction",
  display=TRUE
)
line.map.miami <- miami.gray.basemap +
  line.layer +
  line.type.scale
## Not run:
# Output to file and view
ol_map2HTML(
  line.map.miami,
  'miami_lines.html',
  map.heading="Miami Lines"
)
browseURL("miami_lines.html")

## End(Not run)

```

ol_scale_lwd_discrete *Line Width Scale*

Description

Specify a discrete line width mapping scale.

Usage

```

ol_scale_lwd_discrete(lwd.vector = NULL, name = NULL, na.lwd.val = 1,
  ordered.values = NULL, opacity = 1, draw.color = "black",
  draw.lty = "solid", display = FALSE)

```

Arguments

<code>lwd.vector</code>	numeric named vector of the form <code>c(value=width)</code> . If <code>NULL</code> , a default width mapping is assigned.
<code>name</code>	character the scale name.
<code>na.lwd.val</code>	numeric the width assigned to unrecognized or NA values.
<code>ordered.values</code>	character, numeric, or factor vector containing the ordered unique discrete variable values. This input is used to determine the order of the values appearing in the legend. If not supplied, the order is taken from <code>names(lwd.vector)</code> .
<code>opacity</code>	numeric in <code>[0,1]</code> . The line opacity used in the legend only.
<code>draw.color</code>	character color used in the legend lines only.
<code>draw.lty</code>	character indicating the line type for the legend only. This will be passed to an R plot command. See par .
<code>display</code>	logical indicating whether to draw the scale for output in the HTML. If <code>TRUE</code> , a bitmap will be created and sourced in the HTML in an <code>img</code> tag. If <code>FALSE</code> , the <code>draw.*</code> inputs are ignored.

Details

This method maps OpenLayers feature line widths to discrete variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with a "lwd" mapping to a numeric, character, or factor type variable. If no such layer exists, attempts to add this type of scale will result in a warning. The `lwd.vector` input enables the user to specify the exact mapping, assigning widths to specific variable values. The width aesthetic does not have a continuous scale.

Value

list of class `Scale.Lwd.Discrete`.

See Also

[ol_map](#), [ol_geom_polygon](#), [ol_geom_line](#)

Examples

```
line.matrix1 <- matrix(
  c(
    -80.4, -80.4,
    25.78, 25.88
  ),
  ncol=2
)
line.matrix2 <- matrix(
  c(
    -80.25, -80.35,
    25.65, 25.65
  ),
  ncol=2
)
line.list <- list(line.matrix1, line.matrix2)
line.df <- data.frame(
  direction=c("vertical", "horizontal"),
  no=runif(2)
```

```

)
miami.gray.basemap <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=9
) +
lightgray()
line.layer <- ol_geom_line(
  line.list,
  mapping=ol_aes(
    lwd=direction # discrete mapping
  ),
  df=line.df,
  name="Miami Lines",
  toggle.control=TRUE
)
line.width.scale <- ol_scale_lwd_discrete(
  lwd.vector=c(
    vertical = 2,
    horizontal = 5
  ),
  name="Direction",
  display=TRUE
)
line.map.miami <- miami.gray.basemap +
  line.layer +
  line.width.scale
## Not run:
# Output to file and view
ol_map2HTML(
  line.map.miami,
  'miami_lines.html',
  map.heading="Miami Lines"
)
browseURL("miami_lines.html")

## End(Not run)

```

ol_scale_size_continuous

Point Size Scale (Continuous)

Description

Specify a continuous size mapping for a point layer.

Usage

```

ol_scale_size_continuous(low.val, high.val, low.size = 0.33,
  high.size = 0.75, name = NULL, na.size.val = 0.33,
  draw.fill = NULL, legend.breaks = NULL, display = FALSE)

```

Arguments

low.val numeric the minimum variable value to be mapped to the smallest size.

high.val	numeric the maximum variable value to be mapped to the largest size.
low.size	numeric smallest size scalar.
high.size	numeric largest size scalar.
name	character the scale name.
na.size.val	numeric the size scalar assigned to non-numeric or NA values.
draw.fill	character fill color for drawing points in the legend only.
legend.breaks	numeric ordered vector of variable values to display in the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in an img tag.

Details

This method maps OpenLayers point feature sizes to continuous variable values. This scale can be added to an `Ol.Map` S3 object only if the `Ol.Map` object has a layer with a "size" mapping to a numeric variable. If no such layer exists, attempts to add this type of scale will result in a warning. Attempt to apply this scale to a non-numeric variable will throw an error.

Size inputs to this method are applied as scalars to the icon widths. A size value of 1 translates to an icon width of 40 pixels for "pin" markers, or 20 pixels for "dot" markers.

Value

list of class `Scale.Size.Continuous`.

See Also

[ol_map](#), [ol_geom_point](#),

Examples

```
point.matrix <- matrix(
  c(
    -80.885+runif(10),
    25.223+runif(10)
  ),
  ncol=2
)
point.df <- data.frame(
  pt.type=sample(c("A","B"),10,replace=TRUE),
  pt.numeric=runif(10)*10
)
miami.points.map <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=10
) +
  streetmap()+
  ol_geom_point(
    point.matrix,
    df=point.df,
    mapping=ol_aes(
      size=pt.numeric # continuous mapping
    ),
    name="Point",
    marker="pin",
```

```

        fill='green',
        toggle.control=TRUE,
        tooltip=sprintf("%.2f",point.df$pt.numeric)
    ) +
    ol_scale_size_continuous(
        high.val=10,
        low.val=0,
        high.size=0.66,
        low.size=0.33,
        draw.fill='green',
        legend.breaks=c(0,3.33,6.67,10),
        display=TRUE
    )
## Not run:
# Oave to file and open on browser
ol_map2HTML(
    miami.points.map,
    'pointsizes.html'
)
browseURL('pointsizes.html')

## End(Not run)

```

ol_scale_size_discrete

Point Size Scale (Discrete)

Description

Specify a discrete size mapping for a point layer.

Usage

```
ol_scale_size_discrete(size.vector = NULL, name = NULL,
  na.size.val = 0.33, draw.fill = NULL, legend.breaks = NULL,
  display = FALSE)
```

Arguments

size.vector	numeric named vector of the form c(value=width). If NULL, a default size mapping is assigned.
name	character scale name.
na.size.val	numeric the size scalar assigned to unrecognized or NA values.
draw.fill	character fill color for drawing points in the legend only.
legend.breaks	numeric ordered vector of variable values to display in the legend.
display	logical indicating whether to draw the scale for output in the HTML. If TRUE, a bitmap will be created and sourced in the HTML in one or more img tags.

Details

This method maps OpenLayers point feature sizes to a discrete set of variable values. This scale can be added to an `Ol.Map S3` object only if the `Ol.Map` object has a layer with a "size" mapping to a numeric, character, or factor variable. If no such layer exists, attempts to add this type of scale will result in a warning.

Size inputs to this method are applied as scalars to the icon widths. A size value of 1 translates to an icon width of 40 pixels for "pin" markers, or 20 pixels for "dot" markers.

Value

list of class `Scale.Size.Discrete`.

See Also

[ol_map](#), [ol_geom_point](#),

Examples

```
point.matrix <- matrix(
  c(
    -80.885+runif(10),
    25.223+runif(10)
  ),
  ncol=2
)
point.df <- data.frame(
  pt.type=sample(c("A", "B"),10,replace=TRUE),
  pt.numeric=runif(10)*10
)
miami.points.map <- ol_map(
  center=c(-80.385790,25.782618),
  zoom=10
) +
  streetmap()+
  ol_geom_point(
    point.matrix,
    df=point.df,
    mapping=ol_aes(
      size=pt.type # continuous mapping
    ),
    name="Point",
    marker="pin",
    fill='green',
    toggle.control=TRUE,
    tooltip=point.df$pt.type
  ) +
  ol_scale_size_discrete(
    c(A=1,B=0.5),
    name="Point Type",
    draw.fill='black',
    display=TRUE
  )
## Not run:
# Oave to file and open on browser
ol_map2HTML(
```



```

        miami.points.map,
        'pointsizes.html'
    )
    browseURL('pointsizes.html')

    ## End(Not run)

```

public_arcgis_basemap *Public ArcGIS Basemap Layer*

Description

Create a basemap layer linking to an Public ArcGIS mapserver.

Usage

```

public_arcgis_basemap(basemap.identifier = "DeLorme", name = NULL,
    toggle.control = FALSE)

lightgray(toggle.control = FALSE)

oceanbase(toggle.control = FALSE)

```

Arguments

basemap.identifier	character indicating which Public ArcGIS mapserver to use. See 'Available Base Maps'.
name	character layer name.
toggle.control	logical. If TRUE, a checkbox will appear on the map allowing the viewer to toggle its visibility in the browser.

Details

Creates and returns an OpenLayers ArcGIS Tile layer that sources a map server hosted at <http://server.arcgisonline.com>. If the basemap.identifier parameter is unrecognized the function will default to the **DeLorme** map server.

Value

A Layer.ArcGIS S3 object.

Functions

- lightgray: Call "LightGray" public_arcgis_basemap.
- oceanbase: Call "OceanBase" public_arcgis_basemap.

Available Base Maps

The following basemap.identifiers are currently supported by this method.

"LightGray"	World Light Gray Base
"USAPOP2010"	USA Population Change 2000-2010
"Hillshade"	World Hillshade
"OceanBase"	World Ocean Base
"WorldBoundaries"	World Boundaries and Places
"WorldRefOverlay"	World Reference Overlay
"WorldTrans"	World Transportation
"WorldNav"	World Navigation Charts
"Imagery"	World Imagery
"DeLorme"	World Imagery

See Also

[ol_map](#), [+.Ol.Map](#), [nga_basemap](#), [public_OSM_basemap](#), [user_arcgis_basemap](#)

Examples

```
mymap <- ol_map()
base.layer <- public_arcgis_basemap('LightGray')
mymap <- mymap + base.layer
## Not run:
ol_map2HTML(mymap, "SanDiego.html")
browseURL("SanDiego.html")

## End(Not run)
```

public_OSM_basemap	<i>Public OpenStreetMap Basemap Layer</i>
--------------------	---

Description

Create a basemap layer linking to [OpenStreetMap](#).

Usage

```
public_OSM_basemap(name = NULL, toggle.control = FALSE)

streetmap(toggle.control = FALSE)
```

Arguments

name	character layer name.
toggle.control	logical. If TRUE, a checkbox will appear on the map allowing the viewer to toggle its visibility in the browser.

Details

Creates and returns an OpenLayers OpenStreetMap Tile layer.

Value

A `Layer`.ArcGIS S3 object.

Functions

- `streetmap`: Call `public_OSM_basemap` with default settings.

See Also

[ol_map](#), [+.Ol.Map](#), [nga_basemap](#), [public_arcgis_basemap](#), [user_arcgis_basemap](#)

Examples

```
mymap <- ol_map()
base.layer <- public_OSM_basemap()
mymap <- mymap + base.layer
## Not run:
ol_map2HTML(mymap, "SanDiego_OSM.html")
browseURL("SanDiego_OSM.html")

## End(Not run)
```

ROpenLayers

ROpenLayers: A package for Geo-Visualization

Description

ROpenLayers leverages the power of OpenLayers javascript libraries and web-based Mapservers to enable informative visualization.

What this package does

The purpose of this package is to make it easy for a user to visualize geo-spatial data and analyses using the open source **OpenLayers** javascript library and online map servers. The process for creating a visualization imitates the process of creating a plot in R package **ggplot2**.

1. First, an OpenLayers Map object is created with a call to the [ol_map](#) method.
2. Next, layers and scales are created and added. Layers can reference map servers to provide underlying base maps or vector features (polygons, lines, or points) created or imported in R. These capabilities are described in the following sections.
3. Finally, the updated map object is exported to HTML/javascript for viewing in a browser, hosting on a server, or embedding into another application or format. Export methods are [ol_map2HTML](#) and [ol_map2Strings](#).

OpenLayers

OpenLayers is an open source javascript library that makes it easy to put a dynamic map on any web page. It is licensed under the 2-clause BSD license (see **OpenLayers Licence**). This license will appear commented within OpenLayers CSS code in the HTML exports created by this package. However, this package does not contain any of the OpenLayers javascript source code; rather, it exports HTML code that source these libraries when loaded. Therefore, these products will not render without network access to the OpenLayers javascript library. By default, the products exported by this package source OpenLayers 3.16.0, but the user has the option to set the source URL (see [ol_map](#)).

Public ArcGIS Servers

ESRI ArcGIS hosts several publicly available map servers at arcgisonline.com, which can be accessed via REST APIs and rendered using OpenLayers javascript methods. A subset of these are made available in this package through the [public_arcgis_basemap](#) method. Alternatively, a user can specify any ArcGIS map server using the [user_arcgis_basemap](#) method. Note that while these maps servers are publicly available, they are not necessarily open-licensed. Users must ensure they comply with each map server's license and terms of use.

OpenStreetMap

OpenStreetMap also hosts a public and open license map server that can be imported as a layer using OpenLayers. See [public_OSM_basemap](#).

Other Servers

As stated above, the [user_arcgis_basemap](#) method allows the user to manually specify any available ArcGIS map server. This package also provides access to US National Geospatial-Intelligence Agency servers hosted at [NGA.mil](http://nga.mil) through the [nga_basemap](#) method. Note that these servers require authentication, which will be requested at the time of access (i.e., when the HTML page is opened in a browser).

Vector Layers

This package enables users to rapidly access and write OpenLayers vector layers in javascript. The following methods enable that functionality.

- [ol_geom_polygon](#)
- [ol_geom_line](#)
- [ol_geom_point](#)
- [ol_geom_icon](#)
- [ol_geom_circle](#)
- [ol_geom_heatmap](#)
- [ol_geom_text](#)

Geocode

New in version 1.0.0—geocode addresses using **ArcGIS** geocoding service. See [geocode](#).

Examples

```
data(quakes)
center <- c(mean(quakes$long),mean(quakes$lat))
quakes$long[which(quakes$long>180)]<-quakes$long[which(quakes$long>180)]-360
tooltips <- paste("Depth",quakes$depth,sep=": ")
mymap <- ol_map(
  zoom = 5,
  center = center
)
basemap.layer <- oceanbase()
point.layer <- ol_geom_point(
  quakes[,c("long","lat")],
  mapping = ol_aes(fill=mag),
  df = quakes,
```

```

    name = "Earthquake Points",
    toggle.control=TRUE,
    tooltip = tooltips
  )
  heatmap.layer <- ol_geom_heatmap(
    quakes[,c("long", "lat")],
    name = "Earthquake Heatmap",
    toggle.control=TRUE,
    weight.values = quakes$mag,
    opacity = 0.25
  )
  mymap <- mymap +
    basemap.layer +
    point.layer +
    ol_scale_fill_continuous(name="Magnitude",display=TRUE) +
    heatmap.layer
## Not run:
# Save to file and open in browser
ol_map2HTML(
  mymap,
  "Quakes.html",
  map.heading = "Earthquake Data Visualization"
)
browseURL("Quakes.html")

## End(Not run)

```

user_arcgis_basemap	<i>User ArcGIS Basemap Layer</i>
---------------------	----------------------------------

Description

Create a basemap layer linking to an User-supplied ArcGIS mapserver.

Usage

```

user_arcgis_basemap(url, name = "", attributions = "",
  toggle.control = FALSE)

```

Arguments

url	character url string where the map server is located. Typically these urls end with "/MapServer".
name	character layer name.
attributions	character HTML. This HTML will render as attributional text at the bottom-right corner of the map. At a minimum, this text should include the copyright text provided on the map server.
toggle.control	logical. If TRUE, a checkbox will appear on the map allowing the viewer to toggle its visibility in the browser.

Details

Creates and returns an OpenLayers ArcGIS Tile layer that sources a map server at a user-supplied URL.

Value

A Layer.ArcGIS S3 object.

See Also

[ol_map](#), [+.Ol.Map](#), [nga_basemap](#), [public_OSM_basemap](#), [public_arcgis_basemap](#)

Examples

```
server.url <- "http://server.arcgisonline.com/arcgis/rest/services/NatGeo_World_Map/MapServer"
mymap <- ol_map()
attrib <- paste(
  "Content may not reflect National Geographic's current map policy.",
  "Sources: National Geographic, Esri, Garmin, HERE,",
  "UNEP-WCMC, USGS, NASA, ESA, METI, NRCAN, GEBCO, NOAA, increment P Corp",
  sep=" " # long attribution!
)
base.layer <- user_arcgis_basemap(
  server.url,
  attributions = attrib,
  toggle.control=TRUE
)
mymap <- mymap + base.layer
## Not run:
ol_map2HTML(
  mymap,
  "SanDiego_NatGeo.html",
  map.note = sprintf(
    "I found this at <a href='%s'>arcgisonline.com</a>",
    server.url
  )
)
browseURL("SanDiego_NatGeo.html")

## End(Not run)
```

Index

`+.Ol.Map`, [2](#), [5](#), [50](#), [51](#), [54](#)

`geocode`, [3](#), [52](#)

`lightgray (public_arcgis_basemap)`, [49](#)

`nga_basemap`, [4](#), [23](#), [50–52](#), [54](#)

`oceanbase (public_arcgis_basemap)`, [49](#)

`ol_aes`, [6](#), [8](#), [14](#), [17](#), [20](#)

`ol_geom_circle`, [6](#), [7](#), [10](#), [12](#), [14](#), [17](#), [20](#), [32](#), [34](#), [52](#)

`ol_geom_heatmap`, [9](#), [52](#)

`ol_geom_icon`, [3](#), [6](#), [10](#), [11](#), [17](#), [35–37](#), [40](#), [52](#)

`ol_geom_line`, [6](#), [12](#), [13](#), [17](#), [20](#), [27](#), [30](#), [42](#), [44](#), [52](#)

`ol_geom_point`, [3](#), [6](#), [10](#), [12](#), [14](#), [16](#), [20](#), [22](#), [46](#), [48](#), [52](#)

`ol_geom_polygon`, [6](#), [8](#), [10](#), [12](#), [14](#), [16](#), [17](#), [18](#), [21](#), [27](#), [30](#), [32](#), [34](#), [42](#), [44](#), [52](#)

`ol_geom_text`, [21](#), [52](#)

`ol_map`, [3](#), [5](#), [8](#), [10](#), [12](#), [14](#), [17](#), [20](#), [22](#), [22](#), [24](#), [25](#), [27](#), [30](#), [32](#), [34](#), [36](#), [37](#), [40](#), [42](#), [44](#), [46](#), [48](#), [50](#), [51](#), [54](#)

`ol_map2HTML`, [23](#), [23](#), [25](#), [51](#)

`ol_map2Strings`, [23](#), [24](#), [25](#), [51](#)

`ol_scale_color_continuous`, [26](#)

`ol_scale_color_discrete`, [29](#)

`ol_scale_fill_continuous`, [31](#)

`ol_scale_fill_discrete`, [33](#)

`ol_scale_iconimage_discrete`, [35](#)

`ol_scale_iconsize_continuous`, [37](#)

`ol_scale_iconsize_discrete`, [39](#)

`ol_scale_lty_discrete`, [41](#)

`ol_scale_lwd_discrete`, [43](#)

`ol_scale_size_continuous`, [45](#)

`ol_scale_size_discrete`, [47](#)

`par`, [29](#), [33](#), [42](#), [44](#)

`public_arcgis_basemap`, [5](#), [23](#), [49](#), [51](#), [52](#), [54](#)

`public_OSM_basemap`, [5](#), [23](#), [50](#), [50](#), [52](#), [54](#)

`ROpenLayers`, [51](#)

`ROpenLayers-package (ROpenLayers)`, [51](#)

`streetmap (public_OSM_basemap)`, [50](#)

`user_arcgis_basemap`, [5](#), [23](#), [50–52](#), [53](#)