

# Hitachi Ops Center Administrator

11.0.4

---

## REST API Reference Guide

This guide describes the commands used in the REST API to use with Hitachi Ops Center Administrator.

© 2024, 2025 Hitachi Vantara, Ltd. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including copying and recording, or stored in a database or retrieval system for commercial purposes without the express written permission of Hitachi, Ltd., Hitachi Vantara, Ltd., or Hitachi Vantara Corporation (collectively "Hitachi"). Licensee may make copies of the Materials provided that any such copy is: (i) created as an essential step in utilization of the Software as licensed and is used in no other manner; or (ii) used for archival purposes. Licensee may not make any other copies of the Materials. "Materials" mean text, data, photographs, graphics, audio, video and documents.

Hitachi reserves the right to make changes to this Material at any time without notice and assumes no responsibility for its use. The Materials contain the most current information available at the time of publication.

Some of the features described in the Materials might not be currently available. Refer to the most recent product announcement for information about feature and product availability, or contact Hitachi Vantara LLC at [https://support.hitachivantara.com/en\\_us/contact-us.html](https://support.hitachivantara.com/en_us/contact-us.html).

**Notice:** Hitachi products and services can be ordered only under the terms and conditions of the applicable Hitachi agreements. The use of Hitachi products is governed by the terms of your agreements with Hitachi Vantara LLC.

By using this software, you agree that you are responsible for:

1. Acquiring the relevant consents as may be required under local privacy laws or otherwise from authorized employees and other individuals; and
2. Verifying that your data continues to be held, retrieved, deleted, or otherwise processed in accordance with relevant laws.

**Notice on Export Controls.** The technical data and technology inherent in this Document may be subject to U.S. export control laws, including the U.S. Export Administration Act and its associated regulations, and may be subject to export or import regulations in other countries. Reader agrees to comply strictly with all such regulations and acknowledges that Reader has the responsibility to obtain licenses to export, re-export, or import the Document and any Compliant Products.

Hitachi and Lumada are trademarks or registered trademarks of Hitachi, Ltd., in the United States and other countries.

AlX, DB2, DS6000, DS8000, Enterprise Storage Server, eServer, FICON, FlashCopy, GDPS, HyperSwap, IBM, OS/390, PowerHA, PowerPC, S/390, System z9, System z10, Tivoli, z/OS, z9, z10, z13, z14, z15, z16, z/VM, and z/VSE are registered trademarks or trademarks of International Business Machines Corporation.

Active Directory, ActiveX, Bing, Excel, Hyper-V, Internet Explorer, the Internet Explorer logo, Microsoft, Microsoft Edge, the Microsoft corporate logo, the Microsoft Edge logo, MS-DOS, Outlook, PowerPoint, SharePoint, Silverlight, SmartScreen, SQL Server, Visual Basic, Visual C++, Visual Studio, Windows, the Windows logo, Windows Azure, Windows PowerShell, Windows Server, the Windows start button, and Windows Vista are registered trademarks or trademarks of Microsoft Corporation. Microsoft product screen shots are reprinted with permission from Microsoft Corporation.

All other trademarks, service marks, and company names in this document or website are properties of their respective owners.

Copyright and license information for third-party and open source software used in Hitachi Vantara products can be found in the product documentation, at <https://www.hitachivantara.com/en-us/company/legal.html>.

---

# Contents

<b>Preface.....</b>	<b>10</b>
Product version.....	10
Release notes.....	10
Accessing product documentation.....	10
Getting help.....	10
Comments.....	11
<b>Chapter 1: Using the Ops Center Administrator REST API .....</b>	<b>12</b>
REST architecture .....	12
API functionality and HTTP methods.....	12
Security and authentication.....	14
Privileges and roles.....	15
Identifying a resource.....	15
HTTP response .....	16
Token management resources.....	17
Getting a token.....	18
Creating a token.....	20
Deleting a token.....	23
Sending API requests using cURL .....	24
<b>Chapter 2: Block storage management resources .....</b>	<b>26</b>
Storage system management.....	26
Listing storage systems .....	27
Getting a storage system .....	38
Getting storage systems summary .....	48
Getting storage system license information .....	51
Adding a storage system.....	53
Updating a storage system .....	57
Deleting a storage system .....	60
Switching the access point to GUM .....	62
Refreshing a storage system.....	65
Disk management .....	69
Listing disks .....	69
Getting a disk.....	73
Updating a disk.....	77

Parity group management resources.....	80
Listing parity groups .....	82
Getting a parity group.....	87
Listing parity groups summary .....	91
Listing external parity groups .....	94
Creating external parity groups .....	97
Initializing an external parity group .....	102
Deleting external parity groups .....	105
Getting an external parity group.....	109
Listing external parity groups summary .....	112
Creating a parity group .....	113
Enabling compression on a parity group .....	118
Initializing a parity group .....	121
Deleting a parity group .....	124
Getting parity group template .....	128
Creating parity group template .....	132
Pool management resources.....	137
Listing pools.....	139
Getting a pool.....	152
Getting pool summaries .....	164
Creating a pool .....	167
Updating a pool .....	174
Deleting a pool .....	182
Getting pool templates .....	185
Getting a specific pool template .....	189
Creating pool template .....	193
Updating a pool template .....	200
Volume management resources.....	207
Listing volumes .....	210
Getting a volume.....	226
Getting a volumes summary .....	239
Creating a volume .....	241
Updating a volume .....	247
Deleting a volume .....	251
Deleting volumes .....	255
Detaching volumes .....	259
Creating multiple volumes .....	263
Attaching volumes .....	269
Attaching and protecting volumes .....	278
Creating, attaching, and protecting volumes .....	285
Updating volumes.....	298

Detaching volumes from multiple servers .....	303
Editing volume LUN paths.....	307
Editing namespace paths.....	313
Getting auto-selection paths .....	317
Shredding volumes .....	320
Interrupting volume shredding .....	324
Host group management resources.....	327
Getting host groups.....	329
Getting a host group.....	334
Creating host groups .....	338
Editing a host group.....	344
Adding volumes to host groups.....	348
Removing volumes from host groups.....	352
Adding a mutual CHAP user of a host group .....	355
Updating a mutual CHAP user of a host group .....	359
Deleting a mutual CHAP user of a host group .....	363
Deleting host groups.....	367
NVM subsystem management resources.....	370
Listing NVM subsystems.....	371
Getting an NVM subsystem.....	375
Updating an NVM subsystem.....	378
Port management resources.....	381
Listing ports .....	382
Getting a port .....	391
Updating a port .....	399
Getting port login information.....	406
Tier management resources.....	409
Listing tiers.....	410
Updating a tier .....	413
<b>Chapter 3: Server management resources.....</b>	<b>417</b>
Listing servers .....	419
Getting a server.....	428
Getting servers summary .....	436
Adding servers.....	437
Updating a server.....	445
Deleting a server .....	448
Deleting multiple servers .....	451
Updating world wide port names.....	455
Listing attached volumes .....	460
Updating iSCSI settings.....	475
Updating Host NVMe Qualified Names.....	481

Scanning host groups .....	484
Getting a list of server groups.....	488
Getting a server group.....	491
Listing volumes attached to servers in a server group.....	493
Creating a server group.....	510
Updating a server group.....	514
Adding servers to a server group.....	517
Deleting a server group.....	521
Removing multiple servers from a server group.....	525
Using existing LUN paths.....	529
<b>Chapter 4: Volume Migration resources.....</b>	<b>534</b>
Attaching volumes to storage .....	536
Creating external volumes .....	542
Deleting external volumes .....	550
Discovering external devices .....	553
Listing external devices .....	557
Listing external volumes.....	560
Getting an external volume .....	566
Detaching volumes from storage.....	572
Listing migration tasks .....	575
Getting a migration task .....	578
Creating a migration task .....	580
Interrupting a running migration job .....	586
Updating a migration task .....	588
Deleting a migration task .....	594
Listing migration pairs .....	596
<b>Chapter 5: Fabric switch management resources.....</b>	<b>600</b>
Listing fabric switches.....	600
Getting a fabric switch.....	602
Creating a fabric switch.....	604
Editing a fabric switch.....	608
Deleting a fabric switch.....	611
<b>Chapter 6: Virtual storage machine management resources .....</b>	<b>615</b>
Listing virtual storage machines .....	618
Getting a virtual storage machine.....	621
Getting a physical storage system summary in a virtual storage machine ....	624
Listing volume IDs assigned to a physical storage system in a virtual storage machine .....	627
Listing volume IDs in a virtual storage machine .....	629
Getting a volume ID in a virtual storage machine .....	632

Listing host group IDs in a virtual storage machine.....	634
Getting a host group ID in a virtual storage machine .....	637
Creating a virtual storage machine .....	639
Adding resources to a virtual storage machine.....	645
Getting a virtual storage machine summary .....	651
Moving volumes to a virtual storage machine.....	652
Removing resources from a virtual storage machine .....	656
Removing defined volumes from a virtual storage machine .....	661
Deleting a physical storage system from a virtual storage machine .....	664
Deleting a virtual storage machine .....	667
<b>Chapter 7: Data protection management resources.....</b>	<b>671</b>
Getting a data protection summary for all storage systems .....	676
Getting a data protection summary for a storage system .....	677
Listing replication groups .....	679
Getting a replication group by ID .....	687
Getting a replication group summary .....	692
Creating a replication group .....	694
Adding volumes to a replication group on a storage system.....	700
Removing volumes from a replication group on a storage system .....	704
Restoring volumes on a storage system.....	707
Updating clone replication groups on a storage system.....	710
Updating a snapshot replication group on a storage system .....	714
Updating high availability replication groups on a storage system .....	718
Suspending data replication .....	721
Resuming replication .....	724
Deleting a replication group.....	727
Listing volume pairs .....	730
Viewing volume pairs affected by actions performed on a replication group ..	736
Listing primary volume pairs.....	741
Listing secondary volume pairs.....	745
Listing secondary volumes for a primary volume.....	750
Listing failed volume pairs .....	761
Getting Ops Center Protector information .....	765
Registering/Deleting the Hitachi Ops Center Protector .....	767
Testing the connection to Ops Center Protector .....	772
Importing high availability pairs from Ops Center Protector .....	775
Listing quorum disks.....	778
Listing remote paths.....	781
Getting a high availability setup status summary.....	783
Listing high availability status external volumes.....	788

<b>Chapter 8: Monitoring resources.....</b>	<b>792</b>
Capacity monitoring resources.....	792
Getting the total number of capacity alerts for all storage systems .....	793
Listing capacity alert details for all storage systems.....	794
Getting the total number of capacity alerts for a storage system.....	796
Listing capacity alert details for a storage system.....	797
Getting a summary of data reduction savings and capacity efficiency .....	799
Getting a data reduction savings and capacity efficiency summary for a storage system .....	801
Monitoring hardware resources.....	803
Getting the total number of hardware alerts for all storage systems .....	804
Listing resource-specific hardware alert details for all storage systems ...	806
Getting the total number of hardware alerts for a storage system .....	808
Listing resource-specific hardware alert details for a storage system .....	810
Listing disk alert information for all storage systems .....	812
Listing disk alert information for a storage system.....	815
SNMP resources.....	818
Listing SNMP managers.....	818
Adding SNMP managers .....	820
Updating an SNMP manager .....	824
Deleting an SNMP manager.....	827
<b>Chapter 9: System administration resources.....</b>	<b>831</b>
Account domain resources.....	831
Listing account domains .....	831
Getting an account domain .....	833
Adding an account domain .....	835
Updating an account domain .....	838
Deleting an account domain.....	841
User management resources.....	844
Listing user groups.....	844
Listing group mappings .....	847
Getting a group mapping .....	849
Creating role mappings.....	851
Deleting role mappings .....	854
Listing users .....	856
Getting a user.....	858
Updating a user.....	860
Getting a job .....	863
Listing jobs .....	868
Listing storage system task information.....	874



Getting a storage system task information summary.....	876
<b>Appendix A: Supported REST APIs list for Virtual Storage Platform One SDS Block.....</b>	<b>879</b>
Supported REST APIs list for Virtual Storage Platform One SDS Block.....	879

---

# Preface

Hitachi Ops Center Administrator is an infrastructure management solution that unifies storage management solutions such as storage provisioning, data protection, and storage management; simplifies the management of large-scale data centers by providing smarter software services; and is extensible to provide better programmability and control.

## Product version

This document revision applies to Hitachi Ops Center Administrator version 11.0.4 or later.

## Release notes

Read the release notes before installing and using this product. They may contain requirements or restrictions that are not fully described in this document or updates or corrections to this document.

Release notes are located on Support Connect at <https://knowledge.hitachivantara.com/Documents>.

## Accessing product documentation

Product user documentation is available on: <https://docs.hitachivantara.com>. Check this site for the most current documentation, including important updates that may have been made after the release of the product.

## Getting help

The [Hitachi Vantara Support Website](https://support.hitachivantara.com/en_us/contact-us.html) is the destination for technical support of products and solutions sold by Hitachi Vantara. To contact technical support, log on to the Hitachi Vantara Support Website for contact information: [https://support.hitachivantara.com/en\\_us/contact-us.html](https://support.hitachivantara.com/en_us/contact-us.html).

[Hitachi Vantara Community](https://community.hitachivantara.com) is a global online community for Hitachi Vantara customers, partners, independent software vendors, employees, and prospects. It is the destination to get answers, discover insights, and make connections. **Join the conversation today!** Go to [community.hitachivantara.com](https://community.hitachivantara.com), register, and complete your profile.

## Comments

Please send comments to [doc.feedback@hitachivantara.com](mailto:doc.feedback@hitachivantara.com). Include the document title and number, including the revision level (for example, -07), and refer to specific sections and paragraphs whenever possible. All comments become the property of Hitachi Vantara LLC.

**Thank you!**

---

# Chapter 1: Using the Ops Center Administrator REST API

The Ops Center Administrator API is a REST (representational state transfer) interface for administrative tasks to manage storage resources. Ops Center Administrator is a unified software management tool that reduces the complexity of managing storage systems by simplifying the setup, management, and maintenance of storage resources.

## VSP One Block terminology

In some cases, the VSP One Block storage system terminology differs from other VSP models. However, for the following terms, the Administrator UI, API, and documentation still use the existing terms. So, when you see the following terms for VSP One Block, note the correct term as follows:

Term for VSP storage systems	Term for VSP One Block storage systems
External Parity Groups	External Volume Groups
Storage Advisor Embedded	VSP One Block Administrator
Gateway for Unified Management (GUM)	Embedded Storage Manager (ESM) or Storage Management Controller (SMC)

## REST architecture

REST is a style of software architecture that can be used with many message formats for web services.

REST uses the HTTP protocol along with a uniform resource identifier (URI) to identify a name of a web resource for requests from the client.

Ops Center Administrator REST API has a non-GUI interface to manage storage. It supports JSON requests and responses only.

## API functionality and HTTP methods

### Supported HTTP methods

HTTP defines a set of methods that define the actions that can be performed on a resource.

The API supports the following HTTP methods:

## GET

Retrieves information about an individual resource or retrieves a list of resources of a given type. GET is synchronous, so it returns a response message with information for the given resource.

All GET API calls support filtered queries.

The GET jobs API has a searching and sorting structure: `https://ipAddress/v1/jobs?q=query&sort=sorting` (where everything after the "?" is optional). Here are a few examples:

- GET jobs with a specific username: `https://ipAddress/v1/jobs?q=user:username`
- GET jobs with tags: `https://ipAddress/v1/jobs/tags?q=tag:server)`
- GET jobs with ascending sorting of startDate: `https://ipAddress/v1/jobs?sort=startDate:asc`
- GET calls can be combined: `https://ipAddress/v1/jobs?q=user:username&sort=startDate:asc`. This call searches for jobs with user = username and sorts them in ascending order by startDate
- Filters also can be combined with each other using AND or OR operators, and ranges of numbers can be specified using TO: `https://ipAddress/v1/jobs?q=(status:(IN_PROGRESS OR SUCCESS) AND startDate:[now-1d TO now])`

## POST

Adds (creates) and updates a resource.

You need to provide values for all of the attributes of a resource that do not have default values. To override a default value, include the attribute and provide an override value for that attribute in the request body. POST is asynchronous, so it returns a response message with information about the status and job of the request.

In Ops Center Administrator, a POST is asynchronous except when the response message that is returned has just an HTTP status code.

- Account domain resources
- Role mapping resources
- Token resources
- Fabric switch resources

## PATCH

The PATCH method applies partial modifications to a resource.

## DELETE

Deletes a resource. DELETE is asynchronous, so it returns a response message with information about the status and job of the request.

The exceptions to DELETE being asynchronous in Ops Center Administrator are when the response message that is returned is a response message has just an HTTP status code.

- Account domain resources
- Role mapping resources
- Token resources
- Fabric switch resources

## Security and authentication

A security token is required to call the API. There are two options to generate and specify token.

### X-Auth-Token header for default local user and users in the registered Active Directory:

1. Call the following API with the header to generate tokens.

```
POST v1/security/tokens
```

In the Authorization header of the request header, specify a base64-encoded character string in which the user ID and password are concatenated with a colon (:).

```
Authorization: Basic authentication_information
```

2. Extract X-Auth-Token: `x_auth_token` header from the response.
3. Specify the X-Auth-Token: `x_auth_token` header for the target API.

### Authorization header with bearer token for users in the registered Common Service:

The API also can use bearer token with OpenID connect authentication when it works with the Hitachi Ops Center Common Services.

1. Get bearer token from Common Services. See *Hitachi Ops Center Common Services REST API Reference Guide* for details.
2. Specify `Authorization: Bearer bearer_token` header for the target API.



#### Note:

If you use Authorization header with bearer token, you must synchronize the time on the Common Services server with the time on the Ops Center Administrator server. Use NTP to keep the time synchronized between the servers.



#### Note:

The following API is not supported with `Authorization: Bearer` header:  
Token management resources API

## Privileges and roles

Access to the storage system is restricted by roles. Roles determine which tasks a user can complete on the storage system. The security administrator can grant access to users by assigning users roles with privileges that are associated to those specific roles.

### System administrator

- Addition, administration, and deletion of servers, storage system, and fabric switches, SNMP manager, and tier management.
- Addition, administration, and deletion of parity groups.
- Read-only privileges to monitor everything in Ops Center Administrator.
- Registration of Ops Center Protector in Ops Center Administrator.

### Storage administrator

- Addition, administration, and deletion of pools.
- Addition, administration, and deletion of volumes, including creating, attaching to hosts, and data protection.
- Addition, administration, and deletion of port configurations.
- Read-only privileges to monitor everything in Ops Center Administrator.

### Security administrator

- Addition, administration, and deletion of remote account domains.
- User role assignment to groups.
- Read-only privileges to monitor everything in Ops Center Administrator.

### Monitoring role

Read-only privileges to monitor everything in Ops Center Administrator.

## Identifying a resource

The REST API allows you to manage and configure resources on the storage system including common storage systems, disks, parity groups, pool, volumes, ports, and tiers.

To identify a resource you want to manage, enter a resource domain URL in a web browser. All URLs for Ops Center Administrator API have the following base or root, uniform resource identifier (URI):

```
https://management-server/v1
```

where:

*management-server* is the virtual IP address or resolvable management server name of Ops Center Administrator.

For example, you can use the following URI to display a list of servers and details for each server.

```
https://172.17.35.70/v1/compute/servers
```

Each resource (URI) can only be accessed by users with correct privileges. Privileges are inherited based on the roles that are assigned to users.

## HTTP response

When an HTTP request is sent, the server sends back an HTTP response message. The HTTP response message consists of an HTTP header and optional message body. Within the response header is the HTTP status code. The HTTP status code gives a status of the request. The following table contains a list of returned status codes, descriptions, and the type of HTTP request that can generate the status code.

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
404	Not found	The specified storage system ID is not valid or the storage system does not exist.
409	Conflict	The specified resource type does not match the existing resource type.



Status code	HTTP name	Description
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

## Token management resources

Request	Method	URI	Role
<a href="#">Getting a token (on page 18)</a>	GET	/v1/security/tokens	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a token (on page 20)</a>	POST	/v1/security/tokens	Storage administrator System administrator Security administrator Monitoring
<a href="#">Deleting a token (on page 23)</a>	DELETE	/v1/security/tokens	Storage administrator System administrator

Request	Method	URI	Role
			Security administrator Monitoring

## Getting a token

You can get a security token. If not used, the token expires in 1200 seconds, if it is used for a REST call the expiry timer resets. A new token must be acquired after the current one expires.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/tokens
```

The token is passed back in the header.

### Request structure

Not applicable.

### Response structure

```
{
  "token":{
    "issuedAt":"",
    "expiresAt":"",
    "tenantId":"",
    "user":{
      "name":"",
      "domain":,
      "roles":[
        {
          "name":""
        },
      ],
      "providerId":""
    },
    "_links":{
      "self":{
        "href":""
      }
    }
  }
}
```

Parameter	Type	Description
issuedAt	String	Date the token was issued.
expiresAt	String	Date the token expires.
tenantId	Integer	ID number of the service catalog with services activated for the user. Default is 0 for all services.
name	String	The user name that is being used to access the domain.
domain	String	The name or address of the domain.
roles	String	Roles determine what a user can and cannot do. The security administrator assigns users specific roles.
providerId	Integer	ID of the authentication provider.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Request example

```
GET https://172.17.64.116/v1/security/tokens
```

### Response example

```
{
  "token": {
    "issuedAt": "2018-02-05T20:44:37Z",
    "expiresAt": "2018-02-05T21:06:05Z",
    "tenantId": "0",
    "user": {
      "name": "sysadmin",
      "domain": null,
      "roles": [
        {
          "name": "ROLE_SYSTEM_ADMIN"
        },
        {
          "name": "ROLE_SECURITY_ADMIN"
        },
        {
          "name": "ROLE_STORAGE_ADMIN"
        }
      ],
      "providerId": "57503d78-3294-44c6-8c8a-08edd38a08be"
    },
    "_links": {
      "self": {
        "href": "https://172.17.64.111:80/v1/tokens"
      }
    }
  }
}
```

## Creating a token

You can create a security token. The expiration time for the generated token is 1200 seconds.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/security/tokens
```

The token is generated and passed back in the header.

**Request structure**

Not applicable.

**Response structure**

```
{
  "token": {
    "issuedAt": "",
    "expiresAt": "",
    "tenantId": "",
    "user": {
      "name": "",
      "domain": ,
      "roles": [
        {
          "name": ""
        },
        {
          "name": ""
        },
        {
          "name": ""
        }
      ],
      "providerId": ""
    },
    "_links": {
      "self": {
        "href": ""
      }
    }
  }
}
```

Parameter	Type	Description
issuedAt	String	Date the token was issued.
expiresAt	String	Date the token expires.
tenantId	Integer	ID number of the service catalog with services activated for the user. Default is 0 for all services.

Parameter	Type	Description
name	String	The user name that is being used to access the domain.
domain	String	The name or address of the domain.
roles	String	Roles determine what a user can and cannot do. The security administrator assigns users specific roles.
providerId	Integer	ID of the authentication provider.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Request example**

```
POST https://172.17.64.116/v1/security/tokens
```

**Response example**

```
{
  "token": {
    "issuedAt": "2018-02-05T21:10:46Z",
    "expiresAt": "2018-02-05T21:30:46Z",
    "tenantId": "0",
    "user": {
      "name": "sysadmin",
      "domain": null,
      "roles": [
        {
          "name": "ROLE_SYSTEM_ADMIN"
        },
        {
          "name": "ROLE_SECURITY_ADMIN"
        },
        {
          "name": "ROLE_STORAGE_ADMIN"
        }
      ],
      "providerId": "57503d78-3294-44c6-8c8a-08edd38a08be"
    },
    "_links": {
      "self": {
        "href": "https://172.17.64.111:80/v1/tokens"
      }
    }
  }
}
```

**Deleting a token**

You can delete a security token before it expires.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/security/tokens
```

**Request structure**

Not applicable.

**Response structure**

Not applicable.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server is currently unable to receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator cannot connect to the node.

## Sending API requests using cURL

You can use cURL in the command line with Ops Center Administrator REST APIs.

**Procedure**

1. To connect to the Ops Center Administrator instance, using SSH from a terminal window:
  - a. `ssh root@10.10.20.88`
  - b. Provide the root password when prompted.



2. Run the command: `curl -k -I --Basic https://10.10.20.88/v1/security/tokens -X POST -u sysadmin:<ask your administrator>`

## Result

**Message:** Server: nginx/1.8.1 Date: Fri, 05 Aug 2016 23:06:34 GMT Content-Type: application/hal+json; charset=UTF-8 Transfer-Encoding: chunked Connection: keep-alive X-Content-Type-Options: nosniff X-XSS-Protection: 1; mode=block Cache-Control: no-cache, no-store, max-age=0, must-revalidate Pragma: no-cache Expires: 0 X-Frame-Options: DENY X-Auth-Token: 3a22e682-5023-4a54-9f99-70f264555569 Strict-Transport-Security: max-age=31536000; includeSubdomains

## Values to pass on the command line

- Use -k if the connection is insecure.
- Specify the API URI enclosed in single quotes.
- -X specifies the verb (for example, POST, GET, DELETE, PATCH).
- -d specifies the API payload enclosed in single quotes.
- -H specifies each header:value pair. The X-Auth-Token you saved and Content-Type (application/json) headers are passed here.
- Use 'curl -Help' to get info about additional parameters as needed.

For example:

```
curl -k 'API URI' -X {REST verb} -d 'API payload' -H 'header1:value'
-H 'header2:value'
```

## Sample API calls

Attach volume to a server:

```
'{"storageSystemId": "410395", "hostModeOptions":
[], "intendedImageType": "LINUX", "volumes": [{"volumeId": 649, "lun":
1111}], "ports": [{"serverId": 3, "serverWwns": [], "portIds": ["CL8-
C", "CL6-D"]}], "enableZoning": false, "enableLunUnification": false}'
-H 'Content-Type: application/json' -H 'X-Auth-Token:
3a22e682-5023-4a54-9f99-70f264555569'
```

Delete a volume:

```
curl -k https:// 10.10.20.88/v1/storage-systems/410395/volumes/513 -
X DELETE -H 'Content-Type: application/json' -H 'X-Auth-Token:
3a22e682-5023-4a54-9f99-70f264555569'
```

Get all storage systems:

```
curl -k https:// 10.10.20.88/v1/storage-systems -X GET -H 'X-Auth-
Token: 3a22e682-5023-4a54-9f99-70f264555569'
```

---

## Chapter 2: Block storage management resources

This module describes block storage management.

### Storage system management

Request	Method	URI	Role
<a href="#">Listing storage systems (on page 27)</a>	GET	/v1/storage-systems	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a storage system (on page 38)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting storage systems summary (on page 48)</a>	GET	/v1/storage-systems/summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting storage system license information (on page 51)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /settings/ licenses	Storage administrator System administrator

Request	Method	URI	Role
			Security administrator Monitoring
<a href="#">Adding a storage system (on page 53)</a>	POST	/v1/storage-systems	System administrator
<a href="#">Updating a storage system (on page 57)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i>	System administrator
<a href="#">Deleting a storage system (on page 60)</a>	DELETE	/v1/storage-systems/ <i>storageSystemId</i>	System administrator
<a href="#">Switching the access point to GUM (on page 62)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /switch-access-point	System administrator
<a href="#">Refreshing a storage system (on page 65)</a>	POST	/v1/storage-systems/refresh	Storage administrator System administrator

## Listing storage systems

You can display a list of all storage systems.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems
```

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources": [
    {
      "storageSystemId": "",
      "storageSystemName": "",
      "rmiPortNumber": "",
      "accessible": ,
      "model": "",
      "svpIpAddress": "",
      "svpHttpsPortNumber": "",

```

```

" gum1IpAddress": "",
" gum2IpAddress": "",
" serviceIpAddress": "",
" unified": ,
" firmwareVersion": "",
" horcmVersion": "",
" cacheCapacity": ,
" totalUsableCapacity": ,
" allocatedToPool": ,
" unallocatedToPool": ,
" usedCapacity": ,
" availableCapacity": ,
" subscribedCapacity": ,
" unusedDisks": ,
" unusedDisksCapacity": ,
" statusMessage": ,
" gadSummary": ,
" dataReductionSavingsRate": ,
" capacityEfficiencyRate": ,
" migrationTaskCount": ,
" lastRefreshedTime": ,
" primaryGumNumber": ,
" username": "",
" svpFlashState": "",
" totalEfficiency": {
  "totalEfficiencyRate": {
    "status": "",
    "value":
  },
  "dataReductionEfficiency": {
    "totalDataReductionRate": {
      "status": "",
      "value":
    },
    "softwareSavingEfficiency": {
      "totalSoftwareSavingRate": {
        "status": "",
        "value":
      },
      "compressionRate": {
        "status": "",
        "value":
      },
      "deduplicationRate": {
        "status": "",
        "value":
      },
      "patternMatchingRate": {
        "status": "",
        "value":
      }
    }
  }
}

```

```

    },
    "fmdSavingEfficiency": {
      "totalFmdSavingRate": {
        "status": "",
        "value":
      },
      "compressionRate": {
        "status": "",
        "value":
      },
      "patternMatchingRate": {
        "status": "",
        "value":
      }
    }
  },
  "snapshotEfficiencyRate": {
    "status": "",
    "value":
  },
  "provisioningEfficiencyPercentage": {
    "status": "",
    "value":
  },
  "calculationStartTime": "",
  "calculationEndTime": ""
},
"compressionAcceleration": "",
"sds": ,
"deviceNumber": ""
}
],
...
"total": ,
"nextToken":
}

```

Parameter	Type	Description
storageSystemId	String	The ID of the storage system (serial number) for block storage or storage cluster id(uuid) for software-defined storage.
storageSystemName	String	The name of the storage system.

Parameter	Type	Description
accessible	Boolean	The status of the storage system indicating whether the storage system is available with Ops Center Administrator. If accessible = TRUE, the storage system can be managed with Ops Center Administrator. If accessible = FALSE, the storage system cannot be managed with Ops Center Administrator. This happens when the storage system is first onboarded and the system is initializing the cache details.
model	String	The storage system model.
svplpAddress	String	For block storage, the IP address of the service processor (SVP) of the storage system. For storage systems without an SVP, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
svpHttpsPortNumber	Integer	The HTTPS port number of the SVP web servlet.  For software-defined storage, the value is null.
gum1lpAddress	String	The IP address of the maintenance utility controller 1. For VSP G1x00, F1500 storage systems, the GUM IP address is the IP address of the service processor (SVP).  For VSP One Block, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
gum2lpAddress	String	The IP address of the maintenance utility controller 2.  For VSP One Block, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
serviceIpAddress	String	The service IP address. For storage system other than VSP One Block, the value is null.
unified	Boolean	Not used. Always respond with false.

Parameter	Type	Description
firmwareVersion	String	The firmware version of the storage system.
horcmVersion	String	The HORCM version of the storage system. For software-defined storage, the value is null.
cacheCapacity	Long	The cache capacity in the storage system. For software-defined storage, the value is null.
lastRefreshedTime	Long	The time of last update in Epoch time format.
totalUsableCapacity	Long	The total usable capacity in the storage system. For block storage, this is the sum of all parity group capacities in the system. For software-defined storage, this is the sum of all drive capacities in the system. <b>Note:</b> Drive capacities in software-defined storage are used capacity in the catalog.
allocatedToPool	Long	For block storages, the sum of all the pool capacities in the system. For software-defined storage, the sum of all drive capacities except drive status that is "Offline".
unallocatedToPool	Long	For block storage, the capacity available to create pools in the system. This is the difference between totalUsableCapacity and allocatedToPool. For software-defined storage, the sum of drive with status is "Offline" capacity.
usedCapacity	Long	The sum of all used capacities in all the pools in the system.
availableCapacity	Long	The available capacities in all pools in the system. This is the difference between allocatedToPool and usedCapacity.
subscribedCapacity	Long	This is the overall capacity of all created volumes that are available in the storage pools of the storage system.

Parameter	Type	Description
unusedDisks	Integer	<p>For block storage, the number of disks unused in the storage system, such as disks that are not allocated as hot spare disks and not used for parity group creation.</p> <p>For software-defined storage, the number of drive with status is "Offline".</p>
unusedDisksCapacity	Long	<p>For block storage, the unused disk capacity in the storage system.</p> <p>For software-defined storage, the sum of drive with status is "Offline" capacity.</p>
statusMessage	String	Displays errors that might occur while adding a storage system; null indicates no errors.
gadSummary	String	<p>The status of GAD. Values are:</p> <ol style="list-style-type: none"> <li>1. Incomplete</li> <li>2. Not Available</li> <li>3. Complete</li> </ol> <p>For software-defined storage, the value is Not Available.</p>
dataReductionSavingsRate	Float	<p>The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.</p> <p>For software-defined storage, the value is 0.</p>
capacityEfficiencyRate	Float	<p>The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.</p> <p>If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.</p> <p>If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.</p> <p>If no compression technology is in use, the physical used capacity is the used capacity of the pools.</p>



Parameter	Type	Description
migrationTaskCount	Integer	The number of migration tasks. For software-defined storage, the value is 0.
primaryGumNumber	Integer	DKC controller number for VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900. For VSP G/F350, G/F370, G/F700, G/F900 without SVP, the number is changed by the user if a controller is broken. See <a href="#">Switching the access point to GUM (on page 62)</a> . For VSP One Block, the value is null.
username	String	The user name for the storage system that the user specified during onboarding.
svpFlashState	Enum	A state of SVP setting for Flash, either ENABLED or DISABLED. This parameter is only used by the Ops Center Administrator GUI. For software-defined storage, the value is null.
totalEfficiency	Object	Ratios regarding total efficiency. For the VSP 5000 series, VSP E series, VSP One Block, and the following storage systems, this parameter has all the <code>totalEfficiency</code> values: VSP G/F350, G/F370, G/F700, G/F900 with firmware versions 88-03-0x and later. For all other storage systems, this value is null.
totalEfficiencyRate	Object	The ratio of the total saving effect achieved by accelerated compression, capacity saving (compression and deduplication), snapshot, and Dynamic Provisioning. For software-defined storage, the value is null.
status	String	Status of the calculation process of that particular metric. Values can be CALCULATED, CALCULATION_IN_PROGRESS, and CALCULATED_WITH_EXCEEDED.
value	Float	Ratio of that particular metric.
dataReductionEfficiency	Object	Ratios regarding data reduction efficiency.

Parameter	Type	Description
totalDataReductionRate	Object	Data reduction ratio before and after accelerated compression and capacity saving (compression and deduplication).
softwareSavingEfficiency	Object	Ratios regarding software saving efficiency.
totalSoftwareSavingRate	Object	The capacity reduction ratio before and after capacity saving.
compressionRate	Object	The capacity compression ratio before and after capacity saving.
deduplicationRate	Object	The capacity deduplication ratio before and after capacity saving.
patternMatchingRate	Object	The capacity reduction ratio before and after capacity saving pattern matching.
fmdSavingEfficiency	Object	Ratios regarding accelerated compression saving.
totalFmdSavingRate	Object	The capacity reduction ratio before and after accelerated compression.
compressionRate	Object	The capacity compression ratio before and after accelerated compression.
patternMatchingRate	Object	The capacity reduction ratio before and after accelerated compression pattern matching.
snapshotEfficiencyRate	Object	The efficiency ratio achieved by snapshot.
provisioningEfficiencyPercentage	Object	The efficiency ratio achieved by Dynamic Provisioning.
calculationStartTime	String	The start date and time for the calculation. The date and time are displayed in UTC.
calculationEndTime	String	The end date and time for the calculation. The date and time are displayed in UTC.
total	Integer	Total number of resources.
rmiPortNumber	Integer	The RMI access port number of a storage system with a virtual SVP.  For software-defined storage, the value is null.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in

Parameter	Type	Description
		<p>the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZlRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>
compressionAcceleration	String	<p>Whether the compression accelerator is available or not for a supported storage system.</p> <p>Valid values: AVAILABLE, UNAVAILABLE</p> <p>For software-defined storage, the value is null.</p>
sds	Boolean	Whether the storage system is software-defined storage.
deviceNumber	String	<p>Same as the "S/N" column displayed in the storage system inventory by the Ops Center Administrator GUI.</p> <p>For block storage, serial number of storage system.</p> <p>For software-defined storage, internal ID used by software-defined storage.</p>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Request example**

Request with JSON command:

```
https://172.17.64.118/v1/storage-systems
```

**Response example**

JSON response. For the following storage systems, totalEfficiency is set to null: VSP F1500 and VSP G1000, VSP G1500 and VSP G200, G/F400, G/F600, G/F800, VSP N400, VSP N600 and VSP N800.

```
{
  "resources":
  [
    {
      "storageSystemId": "410031",
      "storageSystemName": "RN-SC-41130-HID_SVOS7.3-Gsd-41.130",
      "accessible": true,
      "model": "VSP F600",
      "svpIpAddress": "172.17.41.130",
      "svpHttpsPortNumber": 443,
      "gum1IpAddress": "172.17.41.131",
      "gum2IpAddress": "172.17.41.132",
      "unified": false,
      "firmwareVersion": "83-05-01-40/00",
      "horcmVersion": "01-44-03/01",
      "cacheCapacity": 220922380288,
      "totalUsableCapacity": 296686246549504,

```

```

"allocatedToPool": 35400431173632,
"unallocatedToPool": 261285815375872,
"usedCapacity": 6475224711168,
"availableCapacity": 28925206462464,
"subscribedCapacity": 459154453954560,
"unusedDisks": 9,
"unusedDisksCapacity": 18755262163776,
"statusMessage": null,
"gadSummary": "NOT_AVAILABLE",
"dataReductionSavingsRate": 1.01,
"capacityEfficiencyRate": 5.2,
"migrationTaskCount": 2,
"lastRefreshedTime": 1564575651404,
"primaryGumNumber": 1,
"username": "maintenance",
"svpFlashState": "ENABLED",
"totalEfficiency": {
  "totalEfficiencyRate": {
    "status": "CALCULATED",
    "value": 2.21
  },
  "dataReductionEfficiency": {
    "totalDataReductionRate": {
      "status": "CALCULATED",
      "value": 99999.99
    },
    "softwareSavingEfficiency": {
      "totalSoftwareSavingRate": {
        "status": "CALCULATED",
        "value": 1.52
      },
      "compressionRate": {
        "status": "CALCULATED",
        "value": 1.15
      },
      "deduplicationRate": {
        "status": "CALCULATED",
        "value": 1.34
      },
      "patternMatchingRate": {
        "status": "CALCULATED",
        "value": 1.08
      }
    },
    "fmdSavingEfficiency": {
      "totalFmdSavingRate": {
        "status": "CALCULATED",
        "value": 2.21
      },
      "compressionRate": {
        "status": "CALCULATED",

```

```

        "value": 2.14
      },
      "patternMatchingRate": {
        "status": "CALCULATION_IN_PROGRESS",
        "value": null
      }
    },
    "snapshotEfficiencyRate": {
      "status": "CALCULATED",
      "value": 10.37
    },
    "provisioningEfficiencyPercentage": {
      "status": "CALCULATED",
      "value": 170
    },
    "calculationStartTime": "2018-05-15T10:05",
    "calculationEndTime": "2018-05-15T10:38"
  },
  "compressionAcceleration": "AVAILABLE",
  "sds": false,
  "deviceNumber": "410031"
}
...
],
"total": 4,
"nextToken": null
}

```

## Getting a storage system

You can display detailed information for a specific storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "storageSystemId": "",
  "storageSystemName": "",
  "rmiPortNumber": "",

```

```

"accessible": ,
"model": "",
"svpIpAddress": "",
"svpHttpsPortNumber": "",
"gum1IpAddress": "",
"gum2IpAddress": "",
"serviceIpAddress": "",
"unified": ,
"firmwareVersion": "",
"horcmVersion": "",
"cacheCapacity": ,
"totalUsableCapacity": ,
"allocatedToPool": ,
"unallocatedToPool": ,
"usedCapacity": ,
"availableCapacity": ,
"subscribedCapacity": ,
"unusedDisks": ,
"unusedDisksCapacity": ,
"statusMessage": ,
"gadSummary": ,
"dataReductionSavingsRate": ,
"capacityEfficiencyRate": ,
"migrationTaskCount": ,
"lastRefreshedTime": ,
"primaryGumNumber": ,
"username": "",
"svpFlashState": "",
"totalEfficiency": {
  "totalEfficiencyRate": {
    "status": "",
    "value":
  },
  "dataReductionEfficiency": {
    "totalDataReductionRate": {
      "status": "",
      "value":
    },
    "softwareSavingEfficiency": {
      "totalSoftwareSavingRate": {
        "status": "",
        "value":
      },
      "compressionRate": {
        "status": "",
        "value":
      },
      "deduplicationRate": {
        "status": "",
        "value":
      },
    },
  },
}

```

```

    "patternMatchingRate": {
      "status": "",
      "value":
    }
  },
  "fmdSavingEfficiency": {
    "totalFmdSavingRate": {
      "status": "",
      "value":
    },
    "compressionRate": {
      "status": "",
      "value":
    },
  },
  "patternMatchingRate": {
    "status": "",
    "value":
  }
}
},
"snapshotEfficiencyRate": {
  "status": "",
  "value":
},
"provisioningEfficiencyPercentage": {
  "status": "",
  "value":
},
"calculationStartTime": "",
"calculationEndTime": ""
},
"compressionAcceleration": "",
"sds": ,
"deviceNumber": ""
}

```

Parameter	Type	Description
storageSystemId	String	The ID of the storage system (serial number) for block storage or storage cluster id(uuid) for software-defined storage.
storageSystemName	String	The name of the storage system.



Parameter	Type	Description
accessible	Boolean	The status of the storage system indicating whether the storage system is available with Ops Center Administrator. If accessible = TRUE, the storage system can be managed with Ops Center Administrator. If accessible = FALSE, storage system cannot be managed with Ops Center Administrator. This happens when the storage system is first onboarded and the system is initializing the cache details.
model	String	The storage system model.
svplpAddress	String	For block storage, the IP address of the service processor (SVP) of the storage system. For storage systems without an SVP, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
svpHttpsPortNumber	Integer	The HTTPS port number of the SVP web servlet.  For software-defined storage, the value is null.
gum1lpAddress	String	The IP address of the maintenance utility controller 1. For VSP G1x00 , F1500 storage systems, the GUM IP address is the IP address of the service processor (SVP).  For VSP One Block, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
gum2lpAddress	String	The IP address of the maintenance utility controller 2.  For VSP One Block, the value is null.  For software-defined storage, the representative IP address of the storage cluster.
serviceIpAddress	String	The service IP address. For storage system other than VSP One Block, the value is null.
unified	Boolean	Not used. Always respond with false.

Parameter	Type	Description
firmwareVersion	String	The firmware version of the storage system.
horcmVersion	String	The HORCM version of the storage system. For software-defined storage, the value is null.
cacheCapacity	Long	The cache capacity in the storage system. For software-defined storage, the value is null.
lastRefreshedTime	Long	The time of last update in Epoch time format.
totalUsableCapacity	Long	The total usable capacity in the storage system. For block storage, this is the sum of all parity group capacities in the system. For software-defined storage, this is the sum of all drive capacities in the system. <b>Note:</b> Drive capacities in software-defined storage are used capacity in the catalog.
allocatedToPool	Long	For block storages, the sum of all the pool capacities in the system. For software-defined storage, the sum of all drive capacities except drive status that is "Offline".
unallocatedToPool	Long	For block storage, the capacity available to create pools in the system. This is the difference between totalUsableCapacity and allocatedToPool. For software-defined storage, the sum of drive with status is "Offline" capacity.
usedCapacity	Long	The sum of all used capacities in all the pools in the system.
availableCapacity	Long	The available capacities in all pools in the system. This is the difference between allocatedToPool and usedCapacity.
subscribedCapacity	Long	This is the overall capacity of all created volumes that are available in the storage pools of the storage system.

Parameter	Type	Description
unusedDisks	Integer	For block storage, the number of disks unused in the storage system, such as disks that are not allocated as hot spare disks and not used for parity group creation.  For software-defined storage, the number of drive with status is "Offline".
unusedDisksCapacity	Long	For block storage, the unused disk capacity in the storage system.  For software-defined storage, the sum of drive with status is "Offline" capacity.
statusMessage	String	The storage system status; null indicates no errors.
gadSummary	String	The status of GAD. Values are:  <ol style="list-style-type: none"> <li>1. Incomplete</li> <li>2. Not Available</li> <li>3. Complete</li> </ol> For software-defined storage, the value is Not Available.
dataReductionSavingsRate	Float	The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.  For software-defined storage, the value is 0.
capacityEfficiencyRate	Float	The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.  If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.  If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.  If no compression technology is in use, the physical used capacity is the used capacity of the pools.

Parameter	Type	Description
migrationTaskCount	Integer	The number of migration tasks. For software-defined storage, the value is 0.
primaryGumNumber	Integer	DKC controller number for VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900. For VSP G/F350, G/F370, G/F700, G/F900 without SVP, the number is changed by the user if a controller is broken. See <a href="#">Switching the access point to GUM (on page 62)</a> . For VSP One Block, the value is null.
username	String	The user name for the storage system that the user specified during onboarding.
svpFlashState	Enum	A state of SVP setting for Flash, either ENABLED or DISABLED. This parameter is only used by the Ops Center Administrator GUI. For software-defined storage, the value is null.
totalEfficiency	Object	Ratios regarding total efficiency. For the VSP 5000 series, VSP E series, VSP One Block, and the following storage systems, this parameter has all the <code>totalEfficiency</code> values: VSP G/F350, G/F370, G/F700, G/F900 with firmware versions 88-03-0x and later. For all other storage systems, this value is null.
totalEfficiencyRate	Object	The ratio of the total saving effect achieved by accelerated compression, capacity saving (compression and deduplication), snapshot, and Dynamic Provisioning. For software-defined storage, the value is null.
status	String	Status of the calculation process of that particular metric. Values can be CALCULATED, CALCULATION_IN_PROGRESS, and CALCULATED_WITH_EXCEEDED.
value	Float	Ratio of that particular metric.
dataReductionEfficiency	Object	Ratios regarding data reduction efficiency.

Parameter	Type	Description
totalDataReductionRate	Object	Data reduction ratio before and after accelerated compression and capacity saving (compression and deduplication).
softwareSavingEfficiency	Object	Ratios regarding software saving efficiency.
totalSoftwareSavingRate	Object	The capacity reduction ratio before and after capacity saving.
compressionRate	Object	The capacity compression ratio before and after capacity saving.
deduplicationRate	Object	The capacity deduplication ratio before and after capacity saving.
patternMatchingRate	Object	The capacity reduction ratio before and after capacity saving pattern matching.
fmdSavingEfficiency	Object	The capacity reduction ratio before and after accelerated compression.
compressionRate	Object	The capacity compression ratio before and after accelerated compression.
patternMatchingRate	Object	The capacity reduction ratio before and after accelerated compression pattern matching.
snapshotEfficiencyRate	Object	The efficiency ratio achieved by snapshot.
provisioningEfficiencyPercentage	Object	The efficiency ratio achieved by Dynamic Provisioning.
calculationStartTime	String	The start date and time for the calculation. The date and time are displayed in UTC.
calculationEndTime	String	The end date and time for the calculation. The date and time are displayed in UTC.
rmiPortNumber	Integer	The RMI access port number of a storage system with a virtual SVP. For software-defined storage, the value is null.
compressionAcceleration	String	Whether the compression accelerator is available or not for a supported storage system. Valid values: AVAILABLE, UNAVAILABLE For software-defined storage, the value is null.

Parameter	Type	Description
sds	Boolean	Whether the storage system is software-defined storage.
deviceNumber	String	Same as the "S/N" column displayed in the storage system inventory by the Ops Center Administrator GUI.  For block storage, serial number of storage system.  For software-defined storage, internal ID used by software-defined storage.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	This is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Request example

```
https://172.17.64.111/v1/storage-systems/410031
```

### Response example

For the following storage systems, totalEfficiency is set to null: VSP F1500 and VSP G1000, VSP G1500 and VSP G200, G/F400, G/F600, G/F800, VSP N400, VSP N600 and VSP N800.

```
{
  "storageSystemId": "410031",
  "storageSystemName": "RN-SC-41130-HID_SVOS7.3-Gsd-41.130",
```

```

"accessible": true,
"model": "VSP F600",
"svpIpAddress": "172.17.41.130",
"svpHttpsPortNumber": 443,
"gum1IpAddress": "172.17.41.131",
"gum2IpAddress": "172.17.41.132",
"unified": false,
"firmwareVersion": "83-05-01-40/00",
"horcmVersion": "01-44-03/01",
"cacheCapacity": 220922380288,
"totalUsableCapacity": 296686246549504,
"allocatedToPool": 35400431173632,
"unallocatedToPool": 261285815375872,
"usedCapacity": 6475224711168,
"availableCapacity": 28925206462464,
"subscribedCapacity": 459154453954560,
"unusedDisks": 9,
"unusedDisksCapacity": 18755262163776,
"statusMessage": null,
"gadSummary": "NOT_AVAILABLE",
"dataReductionSavingsRate": 1.01,
"capacityEfficiencyRate": 5.2,
"migrationTaskCount": 2,
"lastRefreshedTime": 1564575651404,
"primaryGumNumber": 1,
"username": "maintenance",
"svpFlashState": "ENABLED",
"totalEfficiency": {
  "totalEfficiencyRate": {
    "status": "CALCULATED",
    "value": 2.21
  },
  "dataReductionEfficiency": {
    "totalDataReductionRate": {
      "status": "CALCULATED",
      "value": 99999.99
    },
    "softwareSavingEfficiency": {
      "totalSoftwareSavingRate": {
        "status": "CALCULATED",
        "value": 1.52
      },
      "compressionRate": {
        "status": "CALCULATED",
        "value": 1.15
      },
      "deduplicationRate": {
        "status": "CALCULATED",
        "value": 1.34
      },
      "patternMatchingRate": {

```

```

        "status": "CALCULATED",
        "value": 1.08
      },
      "fmdSavingEfficiency": {
        "totalFmdSavingRate": {
          "status": "CALCULATED",
          "value": 2.21
        },
        "compressionRate": {
          "status": "CALCULATED",
          "value": 2.14
        },
        "patternMatchingRate": {
          "status": "CALCULATION_IN_PROGRESS",
          "value": null
        }
      },
      "snapshotEfficiencyRate": {
        "status": "CALCULATED",
        "value": 10.37
      },
      "provisioningEfficiencyPercentage": {
        "status": "CALCULATED",
        "value": 170
      },
      "calculationStartTime": "2018-05-15T10:05",
      "calculationEndTime": "2018-05-15T10:38"
    },
    "compressionAcceleration": "AVAILABLE",
    "sds": false,
    "deviceNumber": "410031"
  }
}

```

## Getting storage systems summary

You can display a report of all storage systems in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/summary
```

### Request structure

Not applicable.



## Response structure

The response body structure is as follows:

```
{
  "totalUsableCapacity": "",
  "allocatedToPool": "",
  "unallocatedToPool": "",
  "usedCapacity": "",
  "availableCapacity": "",
  "subscribedCapacity": "",
  "storageSystemCount":
  "tierSummaryItems":
  [
    {
      "tierName": "",
      "totalCapacity": "",
      "freeCapacity": ""
    },
    ...
  ]
}
```

Parameter	Type	Description
subscribedCapacity	String	This is the overall capacity of all created volumes that are available in the storage pools of the storage system.
totalUsableCapacity	String	The total usable capacity of all storage systems. This is the sum of all parity group capacities in all block storages and all drive capacities in all software-defined storage. <b>Note:</b> Drive capacities in software-defined storage are used capacity in the catalog.
allocatedToPool	String	The sum of all pool capacities in all block storages and all drive capacities except drive status that is "Offline" in software-defined storage.
unallocatedToPool	String	The capacity available to create pools in the block storage and all drive capacities that drive status is "Offline" in software-defined storage.  For block storage, this is the difference between totalUsableCapacity and allocatedToPool.

Parameter	Type	Description
storageSystemCount	Integer	Storage system count.
availableCapacity	String	The available capacities in all pools. This is the difference between allocatedToPool and usedCapacity.
usedCapacity	String	The sum of all used capacity in all the pools across all storage systems.
tierSummaryItems	List	List of the tier items.
tierName	String	The name of the tier.
totalCapacity	String	Total capacity of the specified pool type in the storage system, in bytes.
freeCapacity	String	Capacity available, in bytes.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Request Example

```
https://172.17.64.116/v1/storage-systems/summary
```

### Response Example

```
{
  "totalUsableCapacity": "288965590974464",
  "allocatedToPool": "152762169950208",
  "unallocatedToPool": "136203421024256",
  "usedCapacity": "333428293632",
  "availableCapacity": "152428741656576",
  "subscribedCapacity": "1311474974720",
  "storageSystemCount": 4,
  "tierSummaryItems":
  [
    {
      "tierName": "External",
      "totalCapacity": "9907297124352",
      "freeCapacity": "9907297124352"
    },
    ...
  ]
}
```

## Getting storage system license information

You can display the license keys for the software features that are enabled on the storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/settings/licenses
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "storageSystemId": "",
  "licenseSettings": [
    {
      "productName": "",
      "productId": "",
      "installed": ,
      "licenseCapacity": {
        "permitted": {
          "unlimited": ,
          "value":
```

```

    },
    "usedCapacity": ""
  }
},
...
]
}

```

Parameter	Type	Description
storageSystemId	String	ID of the storage system.
productName	String	Name of the software application.
productId	String	Product ID of the license.
installed	Boolean	Whether a permanent license is installed.
licenseCapacity	Object	License permitted and used capacity.
usedCapacity	String	Sum of used capacity across all pools of the specified type in the storage system, in bytes.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Response example

```
{
  "storageSystemId": "444004",
  "licenseSettings": [
    {
      "productName": "Provisioning",
      "productId": "07",
      "installed": true,
      "licenseCapacity": {
        "permitted": {
          "unlimited": true,
          "value": null
        },
        "usedCapacity": "37396280246272"
      }
    },
    ...
  ]
}
```

## Adding a storage system

You can add a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems
```

### Request structure

The request body structure for storage systems without an SVP is as follows:

```
{
  "password": "",
  "username": "",
  "ipAddress": "",
  "rmiPortNumber":
}
```

Parameter	Required	Type	Description
password	Yes	String	Password.
username	Yes	String	User name.

Parameter	Required	Type	Description
ipAddress	No	String	For block storage, service IP address for VSP One block or IP address of the SVP or GUM for other than VSP One block.  For software-defined storage, the representative IP address of the storage cluster.  Specify either ipAddress or svplpAddress.
svplpAddresses	No	String	IP address of the SVP or GUM. Specify either ipAddress or svplpAddress.  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the ipAddress parameter instead.
rmiPortNumber	No	Integer	The RMI access port number of a storage system with a virtual SVP. If not specified, default port number will be used.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
```

```

        "href": "/v1/jobs/jobId"
    }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the process.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

For storage systems without an SVP:

```
{
  "password": "mainte",
  "username": "mainte",
  "ipAddress": "10.145.24.12"
}
```



## Updating a storage system

You can modify the credentials that are used to manage a storage system in Ops Center Administrator and you can modify the storage system name.



**Note:** When you update the storage system name, the change will be reflected to some views and REST API responses after the next manual refresh. To reflect it, update the storage system data in Ops Center Administrator by refreshing manually.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId
```

Use the storage system ID as the *storageSystemId*.

### Request structure

The request body structure is as follows:

```
{
  "password": "",
  "username": "",
  "storageSystemName": ""
}
```

Parameter	Required	Type	Description
password*	Yes	String	Password of the storage system.
username*	Yes	String	User name of the storage system.
storageSystemName*	Yes	String	The name of the storage system.
* Execution needs the storageSystemName or a password and username, but not all three.			

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  }
}
```

```

    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Deleting a storage system

You can delete a storage system from Ops Center Administrator.

### HTTP request syntax (URI)

```
DELETE https://ipAddress/v1/storage-systems/storageSystemId
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
```

```

    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Switching the access point to GUM

You can switch the connection to the backend API from one DKC controller (GUM1) to another DKC controller (GUM2) to manage storage systems without an SVP in Ops Center Administrator. If one of the controllers fails and Ops Center Administrator cannot manage the storage system any longer, do this using the other controller.

You cannot switch the connection for the storage systems onboarded with the service IP address.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/switch-access-point
```

**Request structure**

The request body structure is as follows:

```
{
  "primaryGumNumber":
}
```

Parameter	Required	Type	Description
primaryGumNumber	Yes	Integer	The primary GUM number.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .



**Return codes**

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
409	Conflict	The GUM number has already been configured.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "primaryGumNumber": 2
}
```

**Refreshing a storage system****HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/refresh
```

**Request structure**

```
{
  "storageSystemIds": []
}
```

Parameter	Required	Type	Description
storageSystemIds	Yes	List	IDs of the manually updated storage systems in String

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      "text": ""
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
{
  "storageSystemIds": ["100542", "200555"]
}
```

**Example Response**

```
{
  "jobId": "d1f5bb45-bce4-42e6-a8f7-86fc7c407d89",
  "title": {
    "text": "Refresh storage systems",
    "messageCode": "RefreshStorageSystemsJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1567797062801,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/d1f5bb45-bce4-42e6-a8f7-86fc7c407d89"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ]
}
```

```

    ],
    "isSystem": false
  }

```

## Disk management

Request	Method	URI	Role
<a href="#">Listing disks (on page 69)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /disks	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a disk (on page 73)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /disks/ <i>diskId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Updating a disk (on page 77)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /disks/ <i>diskId</i>	System administrator

## Listing disks

You can display a list of all disks in the storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/disks
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

## Response structure

The response body structure is as follows:

```
{
  "resources": [
    {
      "diskId": "",
      "storageSystemId": "",
      "serialNumber": "",
      "location": "",
      "model": "",
      "capacityInBytes": ,
      "version": "",
      "speed": ,
      "type": "",
      "purpose": "",
      "parityGroupId": ""
    },
    ...
  ],
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
diskId	String	ID of the disk.
storageSystemId	String	ID of the storage system.
serialNumber	String	Serial number of the disk.
location	String	The location of the disk in the storage system.
model	String	Model of the disk.
capacityInBytes	Long	Drive capacity in bytes.
version	String	For storage systems with an SVP, returns the version of the disk.  For storage systems without an SVP, a NULL value is returned.
speed	Integer	The speed of the disk.

Parameter	Type	Description
type	String	<p>Disk type: one of the following values:</p> <ul style="list-style-type: none"> <li>▪ FMD HDE - Flash Module with compression and encryption support</li> <li>▪ FMD DC2 - Flash Module Drive Data Compression</li> <li>▪ FMD - Flash Module Drive</li> <li>▪ SAS - Serial Attached SCSI</li> <li>▪ SSD - Solid State Drive</li> <li>▪ SSD(RI) - Solid State Drive (Read Intensive)</li> <li>▪ SSD NVMe - Solid State Drive Non-Volatile Memory Express</li> <li>▪ SCM NVMe - Storage Class Memory Non-Volatile Memory Express</li> <li>▪ SSD(QLC) - Solid State Drive (Quad Level Cell)</li> </ul>
purpose	String	<p>Disk utility: one of the following values:</p> <ul style="list-style-type: none"> <li>▪ DATA - disk is used in a parity group.</li> <li>▪ SPARE - hot spare disk.</li> <li>▪ DATA_SWAPPED - data disk which is switched from hot spare.</li> <li>▪ RESERVED - reserved, is not used for parity group creation.</li> <li>▪ FREE - the disk is available for parity group creation.</li> </ul>
parityGroupId	String	ID of the parity group that the disk belongs to.
total	Long	Total number of resources.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/serial/disks?nextToken=</pre>

Parameter	Type	Description
		cXVlcn1BbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUS1jZzswOw==

### Return codes

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

Request with JSON command:

```
https://172.17.64.116/v1/storage-systems/410209/disks
```

### Example response

JSON response:

```
{
  "resources":
  [
    {
      "diskId": "6XN8GGEK0000M533SVKB",
      "storageSystemId": "410209",
      "serialNumber": "6XN8GGEK0000M533SVKB",
    }
  ]
}
```



```

        "location": "HDD02-00",
        "model": "DKS5C-K300SS",
        "capacityInBytes": 288196762112,
        "version": "7F-55",
        "speed": 15000,
        "type": "SAS",
        "purpose": "DATA",
        "parityGroupId": "1-1"
    },
    {
        "diskId": "KWGLDT8F",
        "storageSystemId": "450179",
        "serialNumber": "KWGLDT8F",
        "location": "HDD00-07",
        "model": "XXXXXXXXXXXX",
        "capacityInBytes": 600000000000,
        "version": "XX-XX",
        "speed": 0,
        "type": "SSD(RI)",
        "purpose": "DATA",
        "parityGroupId": "1-2"
    },
    ...
],
"total": 72,
"nextToken": null
}

```

## Getting a disk

You can display details about a specific disk in the storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/disks/diskId
```

Use the storage system number as the *storageSystemId*.

Use the ID of the disk as the *diskId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "diskId": "",
  "storageSystemId": "",

```

```

"serialNumber": "",
"location": "",
"model": "",
"capacityInBytes": ,
"version": "",
"speed": ,
"type": "",
"purpose": "",
"parityGroupId":
}

```

Parameter	Type	Description
storageSystemId	String	ID of the storage system.
speed	Integer	The speed of the disk.
capacityInBytes	String	Drive capacity in bytes.
version	String	For storage systems with an SVP, returns the version of the disk.  For storage systems without an SVP, returns Null.
diskId	String	ID of the disk.
parityGroupId	String	ID of the parity group that the disk belongs to.
purpose	String	Disk utility: one of the following values: <ul style="list-style-type: none"> <li>DATA - disk is used in a parity group.</li> <li>SPARE - hot spare disk.</li> <li>DATA_SWAPPED - data disk which is switched from a hot spare.</li> <li>RESERVED - reserved, is not used for parity group creation.</li> <li>FREE - the disk is available for parity group creation.</li> </ul>
model	String	Model of the disk.
serialNumber	String	Serial number of the disk.
location	String	The location of the disk in the storage system.

Parameter	Type	Description
type	String	<p>Disk type: one of the following values:</p> <ul style="list-style-type: none"> <li>▪ FMD HDE - Flash Module with compression and encryption support</li> <li>▪ FMD DC2 - Flash Module with compression support</li> <li>▪ FMD - Flash Module Drive</li> <li>▪ SAS - Serial Attached SCSI</li> <li>▪ SSD - Solid State Drive</li> <li>▪ SSD(RI) - Solid State Drive (Read Intensive)</li> <li>▪ SSD NVMe - Solid State Drive Non-Volatile Memory Express</li> <li>▪ SCM NVMe - Storage Class Memory Non-Volatile Memory Express</li> <li>▪ SSD(QLC) - Solid State Drive (Quad Level Cell)</li> </ul>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

Request with JSON command:

```
https://172.17.64.116/v1/storage-systems/410209/disks/6XN8GGEK0000M533SVKB
```

**Example response**

```
{
  "diskId": "6XN8GGEK0000M533SVKB",
  "storageSystemId": "410209",
  "serialNumber": "6XN8GGEK0000M533SVKB",
  "location": "HDD02-00",
  "model": "DKS5C-K300SS",
  "capacityInBytes": 288196762112,
  "version": "7F-55",
  "speed": 15000,
  "type": "SAS",
  "purpose": "DATA",
  "parityGroupId": "1-1"
}
```

## Updating a disk

You can update the disks in a storage system to reserve a disk as a hot spare. You cannot update disks for VSP G1000, VSP G1500, and VSP F1500 storage systems or VSP 5000 series storage systems.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/disks/diskId
```

Use the storage system ID as the *storageSystemId*.

Use the ID of the disk as the *diskId*.

### Request structure

The request body structure is as follows:

```
{
  "hotSpare": ""
}
```

Parameter	Required	Type	Description
hotSpare	Yes	String	Whether a disk is reserved as a spare:  Specify <b>Yes</b> to reserve a free data disk as a Hot Spare.  Specify <b>No</b> to set a spare disk as a data disk and make it available for use in parity groups.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      }
    },
  "user": "",
  "status": "",
}
```

```

    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Parity group management resources

The following are parity group and parity group template APIs:

Request	Method	URI	Role
<a href="#">Listing parity groups (on page 82)</a>	GET	<i>/v1/storage-systems/ storageSystemId/parity-groups</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a parity group (on page 87)</a>	GET	<i>/v1/storage-systems/ storageSystemId/parity-groups/parityGroupId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing parity groups summary (on page 91)</a>	GET	<i>/v1/storage-systems/ storageSystemId/parity-groups/summary</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing external parity groups (on page 94)</a>	GET	<i>/v1/storage-systems/ storageSystemId/external-parity-groups</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating external parity groups (on page 97)</a>	POST	<i>/v1/external-parity-group-manager/create</i>	System administrator



Request	Method	URI	Role
<a href="#">Initializing an external parity group (on page 102)</a>	POST	<i>/v1/storage-systems/ storageSystemId/external- parity-groups/ externalParityGroupId/initialize</i>	System administrator
<a href="#">Deleting external parity groups (on page 105)</a>	POST	<i>/v1/external-parity-group- manager/delete</i>	System administrator
<a href="#">Getting an external parity group (on page 109)</a>	GET	<i>/v1/storage-systems/ storageSystemId/external- parity-groups/ externalParityGroupId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing external parity groups summary (on page 112)</a>	GET	<i>/v1/storage-systems/ storageSystemId/external- parity-groups/summary</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a parity group (on page 113)</a>	POST	<i>/v1/storage-systems/ storageSystemId/parity-groups</i>	System administrator
<a href="#">Enabling compression on a parity group (on page 118)</a>	POST	<i>/v1/storage-systems/ storageSystemId/parity- groups/parityGroupId/ compress</i>	System administrator
<a href="#">Initializing a parity group (on page 121)</a>	POST	<i>/v1/storage-systems/ storageSystemId/parity- groups/parityGroupId/initialize</i>	System administrator
<a href="#">Deleting a parity group (on page 124)</a>	DELETE	<i>/v1/storage-systems/ storageSystemId/parity- groups/parityGroupId</i>	System administrator

The following are parity group template APIs:

Request	Method	URI	Role
<a href="#">Getting parity group template (on page 128)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /templates/ parity-group	Storage Administrator System Administrator Security Administrator Monitoring
<a href="#">Creating parity group template (on page 132)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /templates/ parity-group	System Administrator

## Listing parity groups

You can display a list of all parity groups in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/parity-groups
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources":
  [
    {
      "parityGroupId": "",
      "storageSystemId": "",
      "raidLevel": "",
      "raidLayout": "",
      "diskSpec":
      {
        "type": "",
        "speed": ,
        "capacityInBytes":
      },
      "totalCapacityInBytes": ,
      "uninitializedCapacityInBytes": ,
    }
  ]
}
```

```

        "availableCapacityInBytes": ,
        "physicalCapacityInBytes": ,
        "status": "",
        "encryption": ,
        "compression":,
        "nasBoot":,
        "parityGroupType":
    },
    ...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
resources	List	List of parity groups in a storage system.
Id	String	ID of the parity group.
storageSystemId	String	ID of the storage system.
raidLevel	String	RAID level. Valid values: RAID1+0, RAID5, or RAID6.
raidLayout	String	RAID layout. This RAID layout should be of the specified RAID level.
diskSpec	Object	Disk type, speed, and capacity of the disks that are used to create the parity group. If a parity group is created outside of Ops Center Administrator and consists of multiple disk types, only one disk type is output in this field.
type	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
capacityInBytes	Long	Total capacity, in bytes.
totalCapacityInBytes	Long	Total capacity of the parity group.
uninitializedCapacityInBytes	Long	Free capacity that can be initialized.
availableCapacityInBytes	Long	The capacity of unused volumes in the parity group that can be used for the pool.

Parameter	Type	Description
physicalCapacityInBytes	Long	Available physical capacity of a parity group, in bytes.
status	String	<p>Status of the parity group:</p> <ul style="list-style-type: none"> <li>▪ In Use: The parity group is being used by a storage pool.</li> <li>▪ Available: The parity group is not being used for any storage pools. It is available for pool creation.</li> <li>▪ Available_Physical: The parity group is not being used for any storage pools. Compression is enabled on the parity group and physical capacity of the parity group is available for pool creation. Not applicable to parity groups that are not enabled for compression.</li> <li>▪ Uninitialized: The parity group either has no volumes, at least one of the pool volumes is in Blocked status, or one or more partitions is uninitialized and has a size greater than 16,787,456 blocks.</li> <li>▪ Quick_Formatting: The time taken by the service processor to format the pool volumes in the parity groups. To make the formatting process quick, the drive is not fully verified, the files are still there, and the volume can be rebuilt to gain access to the files again.</li> <li>▪ Formatting: The full format takes longer than a quick format because the service processor fully scans the hard drive.</li> <li>▪ Unsupported_Attached: Either one or more volumes has a path to a storage port, or multiple volumes are used for multiple pools.</li> <li>▪ Unsupported_Inaccessible_Resource_Group: The parity group and at least one of its pool volumes are in different resource groups and the user does not have access to one of the resource groups when using HDvM - SN.</li> </ul>
encryption	Boolean	Whether the data is encrypted.

Parameter	Type	Description
compression	Boolean	Whether the data is compressed. accelerated compression is only supported on FMD DC2 drives.
nasBoot	Boolean	Whether a parity group consists of NAS startup volumes. Values are TRUE or FALSE.
parityGroupType	Enum	Type of this parity group. <ul style="list-style-type: none"> <li>RAID: The parity group with Dynamic Drive Protection disabled.</li> <li>DDP: The parity group with Dynamic Drive Protection enabled.</li> </ul>
total	Long	Total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken=", and then the token. Example: <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZlrlhTT UNoSXVYNlFPUS1jZzswOw==</pre>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.109/v1/storage-systems/410209/parity-groups
```

### JSON response:

```
{
  "resources":
  [
    {
      "parityGroupId": "1-1",
      "storageSystemId": "410209",
      "raidLevel": "RAID5",
      "raidLayout": "3D+1P",
      "diskSpec":
      {
        "type": "SAS",
        "speed": 10000,
        "capacityInBytes": 576393524736
      },
      "totalCapacityInBytes": 1729179942912,
      "uninitializedCapacityInBytes": 4718592,
      "availableCapacityInBytes": 1729179942912,
      "physicalCapacityInBytes": 5277649993728,
      "status": "AVAILABLE",
      "encryption": false,
      "compression": false,
      "nasBoot": true,
      "parityGroupType": "RAID"
    },
    {
      "parityGroupId": "1-2",
      "storageSystemId": "410209",
      "raidLevel": "RAID5",
      "raidLayout": "3D+1P",
      "diskSpec": {
        "type": "SSD(RI)",
        "speed": 0,
        "capacityInBytes": 600000000000
      }
    }
  ]
}
```

```

    },
    "totalCapacityInBytes": 1729179942912,
    "uninitializedCapacityInBytes": 0,
    "availableCapacityInBytes": 0,
    "physicalCapacityInBytes": 1729179942912,
    "status": "IN_USE",
    "encryption": false,
    "compression": false,
    "nasBoot": false,
    "parityGroupType": "RAID"
  },
  ...
],
"total": 12,
"nextToken": null
}

```

## Getting a parity group

You can view detailed information about a specific parity group in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/parity-groups/parityGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the parity group ID as the *parityGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "parityGroupId": "",
  "storageSystemId": "",
  "raidLevel": "",
  "raidLayout": "",
  "diskSpec":
  {
    "type": "",
    "speed": ,
    "capacityInBytes":
  },
  "totalCapacityInBytes": ,
  "uninitializedCapacityInBytes": ,
  "availableCapacityInBytes": ,

```

```

    "physicalCapacityInBytes": ,
    "status": "",
    "encryption": ,
    "compression": ,
    "nasBoot":,
    "parityGroupType":
  }

```

Parameter	Type	Description
Id	String	ID of the parity group.
storageSystemId	String	ID of the storage system.
raidLevel	String	RAID level. Valid values: RAID1+0, RAID5, or RAID6.
raidLayout	String	RAID layout. This RAID layout should be of the specified RAID level.
diskSpec	Object	Disk type, speed, and capacity of the disks that are used to create the parity group. If a parity group is created outside of Ops Center Administrator and consists of multiple disk types, only one disk type is output in this field.
type	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
capacityInBytes	Long	Total capacity, in bytes.
totalCapacityInBytes	Long	Total capacity of the parity group.
uninitializedCapacityInBytes	Long	Free capacity that is available to be initialized.
availableCapacityInBytes	Long	The capacity of unused volumes in the parity group that can be used for the pool.
physicalCapacityInBytes	Long	Available physical capacity of a parity group, in bytes.



Parameter	Type	Description
status	String	<p>Status of the parity group:</p> <ul style="list-style-type: none"> <li>▪ In Use: The parity group is being used by a storage pool.</li> <li>▪ Available: The parity group is not being used for any storage pools. It is available for pool creation.</li> <li>▪ Uninitialized: The parity group either has no volumes, at least one of the pool volumes is in Blocked status, or one or more partitions is uninitialized and has a size greater than 16,787,456 blocks.</li> <li>▪ Quick-Formatting: The time taken by the service processor to format the pool volumes in the parity groups. To make the formatting process quick, the drive is not fully verified, the files are still there, and the volume can be rebuilt to gain access to the files again.</li> <li>▪ Formatting: The full format takes longer than a quick format because the service processor fully scans the hard drive.</li> <li>▪ Externalized: The parity groups assigned to the external storage system.</li> <li>▪ Unsupported_Attached: At least one of the volumes has a path to a storage port or volumes are used for multiple pools.</li> <li>▪ Unsupported_Inaccessible_Resource_Group: The parity group and at least one of its pool volumes are in different resource groups and the user does not have access to one of the resource groups when using HDvM - SN.</li> </ul>
encryption	Boolean	Whether the data is encrypted.
compression	Boolean	Whether or not the data is compressed. accelerated compression is only supported on FMD DC2 drives.
nasBoot	Boolean	Whether a parity group consists of NAS startup volumes. Values are TRUE or FALSE.

Parameter	Type	Description
parityGroupType	Enum	Type of this parity group. <ul style="list-style-type: none"> <li>RAID: The parity group with Dynamic Drive Protection disabled.</li> <li>DDP: The parity group with Dynamic Drive Protection enabled.</li> </ul>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.109/v1/storage-systems/410209/parity-groups/1-9
```

### Example response

```
{
  "parityGroupId": "1-9",
  "storageSystemId": "410209",
  "raidLevel": "RAID5",
  "raidLayout": "3D+1P",
  "diskSpec": {
    "type": "SAS",
    "speed": 7200,
    "capacityInBytes": "3916143603200"
  }
}
```

```

    },
    "totalCapacityInBytes": 11748430577664,
    "uninitializedCapacityInBytes": 4718592,
    "availableCapacityInBytes": 0,
    "physicalCapacityInBytes": 5277649993728,
    "status": "IN_USE",
    "encryption": false,
    "compression": false,
    "nasBoot": false,
    "parityGroupType": "RAID"
  }
}

```

## Listing parity groups summary

You can display a summary of parity group items.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/parity-groups/summary
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "parityGroupSummaryItems":
  [
    {
      "diskType": "",
      "speed": "",
      "size": "",
      "tierName": "",
      "numberOfAvailableDisks": ,
      "numberOfExistingHotSpares": ,
      "totalCapacity": ,
      "totalFreeParityGroupCapacity": ,
      "numberOfParityGroups":
    },
    ...
  ]
}

```

Parameter	Type	Description
parityGroupSummaryItems	List	List of parity group items in a storage system.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	String	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
size	Long	Size of the volume, in bytes.
tierName	String	Custom name of the tier, such as Diamond, Platinum, Gold, Silver, Bronze, or External.
numberOfAvailableDisks	Integer	The number of available disks for parity group creation.
numberOfExistingHotSpares	Integer	Based on best practices, the number of existing hot spare disks needed for the disk type.
totalCapacity	Long	Total capacity of all parity groups for the disk type.
totalFreeParityGroupCapacity	Long	Capacity available of all parity groups for the disk type.
numberOfParityGroups	Integer	The number of parity groups for the disk type.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/storage-systems/410209/parity-groups/summary
```

### Example response

```
{
  "parityGroupSummaryItems": [
    {
      "diskType": "SSD(RI)",
      "speed": "0",
      "size": 600000000000,
      "tierName": "Platinum",
      "numberOfAvailableDisks": 0,
      "numberOfExistingHotSpares": 0,
      "totalCapacity": 8645899714560,
      "totalFreeCapacity": 1152786628608,
      "numberOfParityGroups": 5
    },
    {
      "diskType": "SAS",
      "speed": "7200",
      "size": "3916143603200",
      "tierName": "Bronze",
      "numberOfAvailableDisks": 3,
      "numberOfExistingHotSpares": 1,
      "totalCapacity": 11748425859072,
      "totalFreeParityGroupCapacity": 11748425859072,
      "numberOfParityGroups": 5
    },
    ...
  ]
}
```

## Listing external parity groups

External parity groups are parity groups in a storage system that are connected to an onboarded storage system. The ability to view external parity groups helps manage multiple storage systems using a single storage system. You can display a list of external parity groups in a storage system that has been registered with other storage management tools.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-parity-groups
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources": [
    {
      "externalParityGroupId": "",
      "storageSystemId": "",
      "availableCapacity": ,
      "capacity": ,
      "externalStorageSystemId": "",
      "externalStorageVendor": "",
      "externalStorageProduct": ""
    },
    ...
  ]
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
resources	List	List of external parity groups in a storage system.
externalParityGroupId	String	ID of the parity group on external volumes.

Parameter	Type	Description
parityGroupStatus	String	<p>The status of the parity group. The status can be:</p> <ul style="list-style-type: none"> <li>IN_USE: The parity group is being used by a storage pool.</li> <li>AVAILABLE: The parity group is not being used for any storage pools. It is available for pool creation and expansion.</li> <li>UNINITIALIZED: The parity group either has no volumes, at least one of the pool volumes is in Blocked status, or one or more partitions is uninitialized and has a size greater than 16,777,216 blocks.</li> <li>FORMATTING: The volumes in the external parity groups are being formatted.</li> <li>UNSUPPORTED_ATTACHED: At least one of volumes has a path to a storage port or volumes are used for multiple pools.</li> <li>UNSUPPORTED_INACCESSIBLE_RESOURCE_GROUP: The parity group and at least one of its pool volumes are in different resource groups and the user does not have access to one of the resource groups when using Storage Navigator or Hitachi Command Suite.</li> </ul>
uninitializedCapacity	Long	Free capacity that can be initialized in bytes.
ddmEnabled	Boolean	Whether the parity group is of type DDM. Values are true or false.
externalParityGroupId	String	ID of the parity group on external volumes.
storageSystemId	String	ID of the storage system.
availableCapacity	Long	Unused capacity of the resource, in bytes.
capacity	Long	Total capacity of the system drive, in bytes.

Parameter	Type	Description
externalStorageSystemId	String	ID of the external storage system.
externalStorageVendor	String	Name of the external storage system.
externalStorageProduct	String	Model of the external storage system.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/external-parity-groups
```

JSON response:

```
{
  "resources": [
    {
      "externalParityGroupId": "1-1",
      "storageSystemId": "410209",

```



```

    "availableCapacity": 1729179942912,
    "capacity": 1729179942912,
    "externalStorageSystemId": "420007",
    "externalStorageVendor": "EMC",
    "externalStorageProduct": "Symmetrix"
  },
  ...
]
"total": 4,
"nextToken": null
}

```

## Creating external parity groups

External parity groups are parity groups in a storage system that are connected to an onboarded storage system. You can create and initialize external parity groups.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/external-parity-group-manager/create
```

### Request structure

```

{
  "storageSystemId": "",
  "externalDevices": [
    {
      "externalDeviceId": "",
      "externalPaths": [
        {
          "portId": "",
          "externalWwn": "",
          "externalIscsiInformation": {
            "iscsiName": "",
            "ipAddress": ""
          },
          "externalLun": ""
        }
      ]
    }
  ],
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	The storage system ID.

Parameter	Required	Type	Description
externalDevices	Yes	List	The list of the external devices.
externalDeviceId	No	String	The external device ID.
externalPaths	No	List	The list of the external paths. If you do not specify a path, the method automatically selects an available path.
portId	No	String	The storage port ID of the internal storage system. This parameter is required when you specify <code>externalPaths</code> .
externalWwn	No	String	The WWN of the external storage system's storage port. The <code>externalWwn</code> or <code>externalIscsiInformation</code> parameter is required when you specify <code>externalPaths</code> .
externalIscsiInformation	No	Object	iSCSI information for the external storage system's storage port. The <code>externalWwn</code> or <code>externalIscsiInformation</code> parameter is required when you specify <code>externalPaths</code> .
iscsiName	No	String	The iSCSI storage port target name of the external storage system. This parameter is required when you specify <code>externalIscsiInformation</code> .
ipAddress	No	String	The storage port's IP address of the external storage system. This parameter is required when you specify <code>externalIscsiInformation</code> .
externalLun	No	Integer	The LUN ID. This parameter is required when you specify <code>externalPaths</code> .

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
```

```

    "text": "",
    "messageCode": "",
    "parameters":
      {
      },
    },
    "user": "",
    "status": "",
    "createdDate":,
    "scheduledDate":,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
    "tags":
    [
    ],
    "isSystem":
  }

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "storageSystemId": "410209",
  "externalDevices": [
    {
      "externalDeviceId": " XYZ 50405F7702BC",
      "externalPaths": [
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7700",
          "externalIscsiInformation": null,
          "externalLun": 12
        },
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7710",
          "externalIscsiInformation": null,
          "externalLun": 12
        }
      ]
    }
  ]
}
```

### Example response

```
{
  "jobId": "cb01b71a-36f0-41ae-9060-2d82517eb857",
  "title": {
    "text": "Create external parity groups. Storage System: \"410209\"",
    "messageCode": "CreateExternalParityGroupsTitleMessage",
    "parameters": {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1455837568839,
  "endDate": null,
}
```

```

    "parentJobId": null,
    "reports":
    [
    ],
    "links":
    [
    {
        "rel": "_self",
        "href": "/v1/jobs/cb01b71a-36f0-41ae-9060-2d82517eb857"
    }
    ],
    "tags":
    [
    ],
    "isSystem": false
}

```

## Initializing an external parity group

External parity groups are parity groups in a storage system that are connected to an onboarded storage system. You can initialize an external parity group.

### HTTP request syntax (URI)

```

POST https://ipAddress/v1/storage-systems/{storageSystemId}/external-parity-groups/
{externalParityGroupId}/initialize

```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
    "jobId": "",
    "title":
    {
        "text": "",
        "messageCode": "",
        "parameters":
        {
        }
    },
    "user": "",
    "status": "",
    "createdDate":,

```

```

"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example

```
{
  "jobId": "cb01b71a-36f0-41ae-9060-2d82517eb859",
```



```

    "title": {
      "text": "Initialize external parity group",
      "messageCode": "InitializeExternalParityGroupJobTitleMessage",
      "parameters":
        {
        }
    },
    "user": "sysadmin",
    "status": "IN_PROGRESS",
    "startDate": 1455837568839,
    "endDate": null,
    "parentJobId": null,
    "reports":
    [
    ],
    "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/cb01b71a-36f0-41ae-9060-2d82517eb859"
      }
    ],
    "tags":
    [
    ],
    "isSystem": false
  }

```

## Deleting external parity groups

External parity groups are parity groups in a storage system that are connected to an onboarded storage system. You can delete external parity groups.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/external-parity-group-manager/delete
```

### Request structure

```

{
  "storageSystemId": "",
  "externalParityGroupIds": [""],
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	The storage system ID.
externalParityGroupId	Yes	String	The list of the external parity group IDs to be deleted.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      {}
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.

Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "storageSystemId": "410209",
  "externalParityGroupIds": [ "1-45", "1-46" ],
}
```

**Example response**

```
{
  "jobId": "cb01b71a-36f0-41ae-9060-2d82517eb857",
  "title": {
    "text": "Delete external parity groups. Storage System:"410209"",
    "messageCode": "DeleteExternalParityGroupsTitleMessage",
    "parameters": {
      {
    },
    "user": "sysadmin",
    "status": "IN_PROGRESS",
    "startDate": 1455837568839,
    "endDate": null,
    "parentJobId": null,
    "reports": [
    ],
    "links":
```

```
[
  {
    "rel": "_self",
    "href": "/v1/jobs/cb01b71a-36f0-41ae-9060-2d82517eb857"
  },
  ],
  "tags":
  [
  ],
  "isSystem": false
}
```

## Getting an external parity group

You can display detailed information about a specific external parity group in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-parity-groups/externalParityGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the external parity group ID as the *externalParityGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "externalParityGroupId": "",
  "storageSystemId": "",
  "availableCapacity": "",
  "capacity": "",
  "externalStorageSystemId": "",
  "externalStorageVendor": "",
  "externalStorageProduct": ""
}
```

Parameter	Type	Description
externalParityGroupId	String	ID of the parity group on external volumes.

Parameter	Type	Description
parityGroupStatus	String	<p>The status of the parity group. The status can be:</p> <ul style="list-style-type: none"> <li>IN_USE: The parity group is being used by a storage pool.</li> <li>AVAILABLE: The parity group is not being used for any storage pools. It is available for pool creation and expansion.</li> <li>UNINITIALIZED: The parity group either has no volumes, at least one of the pool volumes is in Blocked status, or one or more partitions is uninitialized and has a size greater than 16,777,216 blocks.</li> <li>FORMATTING: The volumes in the external parity groups are being formatted.</li> <li>UNSUPPORTED_ATTACHED: At least one of volumes has a path to a storage port or volumes are used for multiple pools.</li> <li>UNSUPPORTED_INACCESSIBLE_RESOURCE_GROUP: The parity group and at least one of its pool volumes are in different resource groups and the user does not have access to one of the resource groups when using Storage Navigator or Hitachi Command Suite.</li> </ul>
uninitializedCapacity	Long	Free capacity that can be initialized in bytes.
ddmEnabled	Boolean	Whether the parity group is of type DDM. Values are true or false.
storageSystemId	String	ID of the storage system.
availableCapacity	Long	Unused capacity of the resource, in bytes.
capacity	Long	Total capacity of the system drive, in bytes.
externalStorageSystemId	String	ID of the external storage system.

Parameter	Type	Description
externalStorageVendor	String	Name of the external storage system.
externalStorageProduct	String	Model of the external storage system.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/external-parity-groups/1-1
```

JSON response:

```
{
  "externalParityGroupId": "1-1",
  "storageSystemId": "410209",
  "availableCapacity": "1729179942912",
  "capacity": "1729179942912",
  "externalStorageSystemId": "420007",
  "externalStorageVendor": "EMC",
```

```
"externalStorageProduct": "Symmetrix"
}
```

## Listing external parity groups summary

You can display a summary of external parity groups.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-parity-groups/summary
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "totalCapacity": ,
  "totalFreeCapacity": ,
  "numberOfExternalParityGroups":
}
```

Parameter	Type	Description
totalCapacity	Long	Total capacity of all external parity groups available for a storage system.
totalFreeCapacity	Long	Free capacity of all external parity groups available for a storage system.
numberOfExternalParityGroups	Integer	The number of external parity groups.

### Return codes

Status code	HTTP name	Description
200	OK	Success.



Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/external-parity-groups/summary
```

**Example response**

```
{
  "totalCapacity": 2881966571520,
  "totalFreeCapacity": 2881966571520,
  "numberOfExternalParityGroups": 2
}
```

## Creating a parity group

You can create a parity group with the requested RAID configuration by using the specified disks. Additionally, you can also create and format the logical device (LDEV) on the parity group, so that the parity group is ready for pool creation. You cannot create parity groups on VSP G1000, VSP G1500, or VSP F1500 storage systems or on VSP 5000 series storage systems. To set encryption on the parity groups on VSP G1000, VSP G1500, VSP F1500 or VSP 5000 series, set it in Storage Navigator. You cannot create a parity group with Dynamic Drive Protection enabled.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/parity-groups
```

You can only view an external parity group but you are not able to create it using the API.

Use the storage system ID as the *storageSystemId*.

**Request structure**

The request body structure is as follows:

```
{
  "diskIds": [],
  "raidLevel": "",
  "raidLayout": "",
  "encryption": ""
}
```

Parameter	Required	Type	Description
diskIds	Yes	Integer	List of diskIds that are used to create the parity group.
raidLevel	Yes	String	RAID level. Valid values: RAID0, RAID1, RAID1+0, RAID0+1, RAID2, RAID3, RAID4, RAID5, or RAID6.
raidLayout	Yes	String	The RAID layout of the specified RAID level.  For VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900: <ul style="list-style-type: none"> <li>RAID1+0: (2D+2D)</li> <li>RAID5: (3D+1P), (4D+1P), (6D+1P), and (7D+1P)</li> <li>RAID6: (6D+2P), (14D+2P), (12D+2P)</li> </ul>
encryption	No	Boolean	Whether the data is encrypted. To set an encryption on the parity group, set the encryption parameter to true.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
}
```

```

"title":
{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  }
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

The request with JSON command:

```
{
  "diskIds": [ "PVKEAR6B", "PVKB5TLB", "PVK075SB", "SOM1MR870000B422JRR6" ],
  "raidLevel": "RAID5", "raidLayout": "3D+1P", "encryption": true}
}
```

**Example request**

```
https://172.17.64.109/storage-systems/410209/parity-groups
```

**Example response**

```
{
  "jobId": "cb01b71a-36f0-41ae-9060-2d82517eb858",
  "title": {
    {
      "text": "Creating parity group",
      "messageCode": "CreateParityGroupJobTitleMessage",
      "parameters": {
        {
        }
      }
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1455837568839,
  "endDate": null,
  "parentJobId": null,
  "reports": [
    {
    },
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/cb01b71a-36f0-41ae-9060-2d82517eb858"
    }
  ]
}
```

```

    }
  ],
  "tags":
  [
  ],
  "isSystem": false
}

```

## Enabling compression on a parity group

You can enable data compression on FMD DC2 disks to use more virtual capacity in a parity group than the actual usable capacity.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/parity-groups/parityGroupId/compress
```

Use the storage system ID as the *storageSystemId*.

Use the parity group ID as the *parityGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":

```

```
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.

Parameter	Type	Description
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/parity-groups/1-9/compress
```



## Initializing a parity group

You can create and initialize pool volumes on a parity group if the pool volumes have not been created. You can also format any pool volumes that are in the blocked state. You cannot initialize a parity group with Dynamic Drive Protection enabled.

This API is supported only when the parity group status is available or uninitialized.

- The parity group status is `Uninitialized`. This occurs when the parity group has no volumes, at least one of the pool volumes is in Blocked state, or one or more partitions is uninitialized and has a size greater than 16,787,456 blocks.
- The parity group status is `Available` but the available capacity is much less than the total capacity. This occurs when the pool volumes on the parity group do not account for the entire parity group capacity and there are unused partitions on the parity group.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/parity-groups/parityGroupId/initialize
```

Use the storage system ID as the *storageSystemId*.

Use the parity group ID as the *parityGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
```

```

],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.108/v1/storage-systems/410209/parity-groups/1-2/initialize
```

**Example response**

```
{
  "jobId": "a88bd309-fe36-4d68-b3b3-342d1edf20e8",
  "title": {
    "text": "Initialize parity group",
    "messageCode": "InitializeParityGroupSystemJobPreTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1452129643172,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/a88bd309-fe36-4d68-b3b3-342d1edf20e8"
    }
  ],
  "tags": [],
  "isSystem": false
}
```

**Deleting a parity group**

You can delete a parity group from a supported storage system except VSP G1000, VSP G1500, VSP F1500 or VSP 5000 series models. When you delete a parity group, the disks that are in the parity group are no longer in use. You can then remove the storage system or reconfigure the storage system with another RAID configuration. You cannot delete a parity group with Dynamic Drive Protection enabled.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/storage-systems/storageSystemId/parity-groups/parityGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the parity group ID as the *parityGroupId*.

**Request structure**

Not applicable.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/parity-groups/1-9
```

**Example response**

```
{
  "jobId": "c2aba251-b4a5-44d1-a846-54d32c2c33ff",
  "title":
  {
    "text": "Delete parity group",
    "messageCode": "DeleteParityGroupJobTitleMessage",
    "parameters":
    {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1455838105134,
  "endDate": null,
  "parentJobId": null,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/c2aba251-b4a5-44d1-a846-54d32c2c33ff"
    }
  ]
}
```

```

    ],
    "tags":
    [
    ],
    "isSystem": false
  }

```

## Getting parity group template

You can display a list of the possible methods for creating parity groups on the storage system, based on best practices. Use one or more methods from this list to configure parity groups. Alternatively, you can configure parity groups by selecting disks and allocating them to parity groups. You cannot create a parity group with Dynamic Drive Protection enabled from this list. For VSP G1000, VSP G1500, VSP F1500 or VSP 5000 series, you cannot get parity group templates.

For each disk type, this API returns the various RAID options for creating parity groups. For each RAID option, it shows how many parity groups can be created and the available usable capacity. It also identifies the best RAID configuration for every disk type and the number of spare disks that must be assigned based on best practices.

Additionally, this API returns the number of total disks for a given disk type that are available and the number of spare disks that are already allocated.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/templates/parity-group
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "parityGroupTemplateItems":
  [
    {
      "diskType": "",
      "speed": ,
      "size": "",
      "totalNumberOfDisks": ,
      "numberOfAvailableDisks": ,
      "numberOfNewHotSpares": ,
      "numberOfExistingHotSpares": ,
      "raidOptions":
      [

```



```

    {
      "raidLayout": "",
      "raidLevel": "",
      "numberOfDisksForRaidLayout": ,
      "numberOfParityGroups": ,
      "usableCapacity": "",
      "isDefault":,
      "numberOfUnusedDisks":
    },
  ]
}

```

Parameter	Type	Description
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	The speed of the disk.
size	String	Size of the resource, in bytes.
totalNumberOfDisks	Integer	Total number of specific disk type.
numberOfAvailableDisks	Integer	The number of available disks for parity group creation.
numberOfNewHotSpares	Integer	Based on best practices, the number of additional hot spare disks needed for the disk type.
numberOfExistingHotSpares	Integer	The number of existing hot spare disks of the specific disk type.
raidOptions	List	List of RAID option parity group template items.
raidLevel	String	RAID level. Valid values: RAID1+0, RAID5, or RAID6.
raidLayout	String	RAID layout. This RAID layout should be of the specified RAID level. Valid values:

Parameter	Type	Description
		<p>For VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900:</p> <ul style="list-style-type: none"> <li>RAID1+0: (2D+2D)</li> <li>RAID5: (3D+1P), (4D+1P), (6D+1P), and (7D+1P)</li> <li>RAID6: (6D+2P), (14D+2P), (12D+2P)</li> </ul>
numberOfDisksForRaidLayout	Integer	The number of disks that are used to create a parity group with the RAID layout.
numberOfParityGroups	Integer	The maximum number of parity groups that can be created for the RAID layout.
usableCapacity	Long	Usable capacity of the parity group, in bytes.
isDefault	Boolean	True if RAID layout is the best RAID layout for the disk type.
numberOfUnusedDisks	Integer	The number of disks that are left unused after creating parity groups with this RAID layout.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/templates/parity-group
```

**Example response**

```
{
  "parityGroupTemplateItems":
  [
    {
      "diskType": "SSD(RI) ",
      "speed": 0,
      "size": 600000000000,
      "totalNumberOfDisks": 24,
      "numberOfAvailableDisks": 0,
      "numberOfNewHotSpares": 1,
      "numberOfExistingHotSpares": 0,
      "raidOptions": [
        ...
      ]
    },
    {
      "diskType": "SAS",
      "speed": 7200,
      "size": "3916143603200",
      "totalNumberOfDisks": 24,
      "numberOfAvailableDisks": 3,
      "numberOfNewHotSpares": 0,
      "numberOfExistingHotSpares": 1,
      "raidOptions":
      [
        {
          "raidLayout": "6D+1P",
          "raidLevel": "RAID5",
          "numberOfDisksForRaidLayout": 7,
          "numberOfParityGroups": 0,
          "usableCapacity": "0",
          "isDefault": false,
          "numberOfUnusedDisks": 3
        }
      ]
    }
  ]
}
```

## Creating parity group template

You can configure parity groups that are based on best practices when adding new disks to a storage system. You can specify the RAID configuration and the number of parity groups to be created for each disk type in the storage system. For VSP G1000, VSP G1500, VSP F1500 or VSP 5000 series models, you cannot create a parity group template using this API. You cannot create a parity group with Dynamic Drive Protection enabled.

This API does the following:

- Based on the total number of disks of each disk type, it identifies the number of spare disks to be reserved and the number of spare disks to be allocated.
- Creates the required number of parity groups.
- If the RAID level and layout are not specified, Ops Center Administrator creates and formats the pool volumes for each parity group.

Configuring parity groups with this API allows you to use a template that is based on the following best practices:

### Best practice 1: Hot spare disk

Ops Center Administrator determines the ratio of hot spare disks per disk type and the selection of hot spare disks from the following supported types:

- SSD: 1 per 32
- SSD(RI): 1 per 32
- FMD: 1 per 24
- FMD DC2: 1 per 24
- SAS: 1 per 32
- SCM NVMe: 1 per 32
- SSD(QLC): 1 per 32

### Best practice 2: RAID configuration and layout

Ops Center Administrator gives a best-practice RAID configuration and the number of disks per disk type, speed, and model based on the following information:

- SATA, SSD, SSD(RI), FMD, SAS, FMD DC2, SCM NVMe, SSD(QLC): RAID 6: 6D+2
- SAS 15K, SAS 10K: RAID 6: 6D+2
- SAS 7.2K RAID 6: 14D+2

### Best practice 3: Disk selection

Disks are selected to create an individual parity group. The disks should be identical in terms of disk type, speed, and capacity.

### Best practice 4: Logical device (LDEV) creation

Create LDEVs on parity groups that can be used as pool volumes for data protection pools.

The API supports the following workflow for configuring parity groups:

For each disk type:

- Get the disk and identify the total number of disks needed based on best practice 1.
- Calculate the number of hot spare disks needed based on best practice 1.
- Assign the hot spare disks based on best practice 1.

For every different speed for the chosen disk type:

- Determine the RAID type and layout based on best practice 2 or user input, if provided.
- Based on the layout, calculate the number of parity groups to be created and the size of each parity group for this disk type and speed.

For each parity group to be created:

- Select the disk based on best practice 3.
- Create the parity group.
- Create LDEVs on the parity group based on best practice 4.
- Initialize and format LDEVs.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/templates/parity-group
```

Use the storage system ID as the *storageSystemId*.

### Request structure

The request body structure is as shown:

```
{
  "createParityGroupItems":
  [
    {
      "diskType": "",
      "speed": ,
      "size": ,
      "encryption": ,
      "raidLevel": "",
      "raidLayout": "",
      "numberOfParityGroups":
    }
  ]
}
```

Parameter	Required	Type	Description
diskType	Yes	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Yes	Integer	The speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, SCM NVMe, FMD DC2, or SSD(QLC), the speed is 0.
size	Yes	Long	Size of the resource, in bytes.
encryption	No	Boolean	Whether the data is encrypted. To set an encryption on the parity group, set the encryption parameter to true.
raidLevel	Yes	String	RAID level. Valid values: RAID0, RAID1, RAID1+0, RAID0+1, RAID2, RAID3, RAID4, RAID5, or RAID6.
raidLayout	Yes	String	The RAID layout of the specified RAID level. For VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900: <ul style="list-style-type: none"> <li>RAID1+0: (2D+2D)</li> <li>RAID5: (3D+1P), (4D+1P), (6D+1P) and (7D+1P)</li> <li>RAID6: (6D+2P), (14D+2P), (12D+2P)</li> </ul>
numberOfParityGroups	Yes	Integer	The number of parity groups to be created. This should be less than or equal to the maximum number of parity groups that can be created for the RAID layout with the specified disk type.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  }
}
```

```

    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.



Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/templates/parity-group
```

**Example request**

```
{
  "createParityGroupItems":
  [
    {
      "diskType": "SAS",
      "speed": 10000,
      "size": 1729286481408,
      "encryption": false,
      "raidLevel": "RAID6",
      "raidLayout": "6D+2P",
      "numberOfParityGroups": 1
    }
  ]
}
```

## Pool management resources

The following are pool management APIs:

Request	Method	URI	Role
<a href="#">Listing pools (on page 139)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a pool (on page 152)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools/ <i>storagePoolId</i>	Storage administrator

Request	Method	URI	Role
			System administrator Security administrator Monitoring
<a href="#">Getting pool summaries (on page 164)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools/summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a pool (on page 167)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools	Storage administrator
<a href="#">Updating a pool (on page 174)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools/ <i>storagePoolId</i>	Storage administrator
<a href="#">Deleting a pool (on page 182)</a>	DELETE	/v1/storage-systems/ <i>storageSystemId</i> /storage-pools/ <i>storagePoolId</i>	Storage administrator

The following are pool management template APIs:

Request	Method	URI	Role
<a href="#">Getting pool templates (on page 185)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /templates/ pool	Storage Administrator System Administrator Security Administrator Monitoring
<a href="#">Getting a specific pool template (on page 189)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /templates/ pool/ <i>storagePoolId</i>	Storage Administrator System Administrator

Request	Method	URI	Role
			Security Administrator Monitoring
<a href="#">Creating pool template (on page 193)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /templates/ pool	Storage Administrator
<a href="#">Updating a pool template (on page 200)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /templates/ pool/ <i>storagePoolId</i>	Storage Administrator

## Listing pools

You can display a list all the pools in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/storage-pools
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources": [
    {
      "storagePoolId": ,
      "storageSystemId": "",
      "label": "",
      "capacityInBytes": ,
      "usedCapacityInBytes": ,
      "availableCapacityInBytes": ,
      "usedSubscribedCapacityInBytes": ,
      "logicalCapacityInBytes": ,
      "usedLogicalCapacityInBytes": ,
      "availableLogicalCapacityInBytes": ,
      "suspendSnapshot": ,
      "type": "",
      "utilizationThreshold1": ,
      "utilizationThreshold2": ,
    }
  ]
}
```

```

"subscriptionLimit": {
  "unlimited": ,
  "value":
},
"usedSubscription": ,
"availableSubscription": {
  "unlimited": ,
  "value":
},
"status": "",
"parityGroups": [
  {
    "id": "",
    "encryption": ,
    "compression": ,
    "compressionSupported": ,
    "parityGroupType":
  }
],
"externalParityGroupIds": [],
"tiers": [
  {
    "tier": "",
    "capacity": ,
    "usedCapacity": ,
    "usage": {
      "unlimited": ,
      "value":
    },
    "bufferSpace": {
      "newPageAssignment": {
        "unlimited": ,
        "value":
      },
      "tierRelocation": {
        "unlimited": ,
        "value":
      }
    },
    "performanceUtilization": {
      "unlimited": ,
      "value":
    }
  }
],
"tieringMode": "",
"monitoringMode": "",
"monitoringCycle": "",
"monitoringPeriodStart": "",
"monitoringPeriodEnd": "",
"activeFlashEnabled": ,

```

```

"relocationSpeed": ,
"ddmEnabled": ,
"encrypted": "",
"fmcCompressed": "",
"deduplicationEnabled": ,
"compressionDetails": {
    "compressionRate": ,
    "deduplicationRate": ,
    "savingsPercentage":
},
"fmcCompressionDetails": {
    "expansionRate": ,
    "compressionRate": ,
    "savingsPercentage":
},
"deduplicationSystemDataCapacityInBytes": ,
"nasBoot": ,
"dataReductionSavingsRate": ,
"capacityEfficiencyRate": ,
"totalEfficiency": {
    "totalEfficiencyRate": {
        "status": "",
        "value":
    },
    "dataReductionEfficiency": {
        "totalDataReductionRate": {
            "status": "",
            "value":
        },
        "softwareSavingEfficiency": {
            "totalSoftwareSavingRate": {
                "status": "",
                "value":
            },
            "compressionRate": {
                "status": "",
                "value":
            },
            "deduplicationRate": {
                "status": "",
                "value":
            },
            "patternMatchingRate": {
                "status": "",
                "value":
            }
        },
        "fmdSavingEfficiency": {
            "totalFmdSavingRate": {
                "status": "",
                "value":
            }
        }
    }
}

```

```

    },
    "compressionRate": {
      "status": "",
      "value":
    },
    "patternMatchingRate": {
      "status": "",
      "value":
    }
  },
  "snapshotEfficiencyRate": {
    "status": "",
    "value":
  },
  "provisioningEfficiencyPercentage": {
    "status": "",
    "value":
  },
  "calculationStartTime": "",
  "calculationEndTime": ""
}
...
]
"total": ,
"nextToken":
}

```

Parameter	Type	Description
storagePoolId	String	ID of the storage pool.
storageSystemId	String	ID of the storage system.
Label	String	Name of the storage pool.
capacityInBytes	Long	Total pool capacity.
usedCapacityInBytes	Long	Current used capacity in the pool.
availableCapacityInBytes	Long	Unused capacity in the pool.
usedSubscribedCapacityInBytes	Long	Used subscribed capacity for this pool.
logicalCapacityInBytes	Long	Total pool logical capacity.
usedLogicalCapacityInBytes	Long	Used logical capacity for this pool.

Parameter	Type	Description
availableLogicalCapacityInBytes	Long	Unused logical capacity in the pool.
suspendSnapshot	Boolean	Whether the usedCapacity of the pool is greater than <code>utilizationThreshold2</code> . If <code>TRUE</code> , the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If <code>FALSE</code> , you can write to the snapshot. If the pool is TIERED or SNAP, a NULL value is returned. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is <code>TRUE</code> , the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE.
type	String	Pool type: <ul style="list-style-type: none"> <li>THIN</li> <li>TIERED</li> <li>SNAP</li> </ul>
utilizationThreshold1	Integer	Pool utilization thresholds in percentage (Low). "0" is always displayed in Snap Pool.
utilizationThreshold2	Integer	Pool utilization thresholds in percentage (High).
subscriptionLimit	Object	If a subscription limit is set, unlimited is false and value indicates the limit. If a subscription limit is not set, unlimited is true.
unlimited	Boolean	Whether there is a subscription limit. Values are <code>TRUE</code> or <code>FALSE</code> .
value	Integer	The subscription limit value set for a pool. When the subscription limit is set, you cannot configure another DP-VOL if the new DP-VOL capacity will cause the subscription limit to be exceeded.
usedSubscription	Integer	Current subscribed capacity in this pool.
availableSubscription	String	The rate of subscription available for the pool, derived by "subscriptionLimit" - "usedSubscription".
unlimited	Boolean	Whether there is a limit on available capacity. Values are <code>TRUE</code> or <code>FALSE</code> .

Parameter	Type	Description
value	Integer	The rate of subscription available for the pool, derived by "subscriptionLimit" - "usedSubscription". Null if the subscription is unlimited.
status	String	Pool status: Valid values: NORMAL, FULL, SUSPENDED, FAILED.
parityGroups	String	List of parity groups that belong to this pool.
id	String	ID of the parity groups.
encryption	Boolean	Whether the parity group is encrypted. Values are TRUE or FALSE.
compression	Boolean	Whether the parity group is compressed. Values are TRUE or FALSE.
compressionSupported	Boolean	Whether the parity group supports drive-based compression on FMD drives.
parityGroupType	Enum	Type of this parity group. <ul style="list-style-type: none"> <li>RAID: The parity group with Dynamic Drive Protection disabled.</li> <li>DDP: The parity group with Dynamic Drive Protection enabled.</li> </ul>
externalParityGroupIds	List	List of external parity groups that belong to this pool.
tiers	List	List of tiers, with details for each.
tier	String	The tier type. Valid values: Diamond, Platinum, Gold, Silver, Bronze, External.
capacity	String	Capacity of the tier, in bytes.
usedCapacity	String	Tier capacity that is in use.
usage	Object	Tier usage.
unlimited	Boolean	Whether a limit is set.
value	Integer	
bufferSpace	Object	Tier buffer space.
newPageAssignment	Object	The buffer space for new page assignments.



Parameter	Type	Description
unlimited	Boolean	Whether the buffer space for new page assignments is limited. Values are TRUE or FALSE.
value	Integer	
tierRelocation	Object	The buffer space for tier relocation.
unlimited	Boolean	Whether a limit is set.
value	Integer	
performanceUtilization	Object	Tier performance usage percentage.
unlimited	Boolean	Whether the buffer space for new page assignments is limited. Values are TRUE or FALSE.
value	Integer	
tieringMode	String	Tiering mode for a Tiered pool. Values: MANUAL, AUTOMATIC, NONE, UNKNOWN. The value for a non-Tiered pool should be NONE. This value is only available for storage systems with an SVP.
monitoringMode	String	Monitoring mode for a Tiered pool. Values: PERIODICAL, CONTINUOUS, PERIODICAL_WITH_ACTIVE_FLASH, CONTINUOUS_WITH_ACTIVE_FLASH, NONE. The value for a non-Tiered pool is NONE.
monitoringCycle	String	A cycle time during which I/O monitoring is performed on a tiered pool. The value is in the ISO8601 duration format. This value is only available for storage systems with an SVP.
monitoringPeriodStart	String	The instant that monitoring begins in storage system local time, with no adjustment for daylight savings. This value is only available for storage systems with an SVP.
monitoringPeriodEnd	String	The instant that monitoring ends in storage system local time, with no adjustment for daylight savings. This value is only available for storage systems with an SVP.

Parameter	Type	Description
activeFlashEnabled	Boolean	Whether active flash is enabled. To enable active flash, one of the tiers must be Platinum and disk types: FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, FMD HDE, or SSD(QLC). You also need to enable the active flash license.
relocationSpeed	String	Relocation speed for a tiered pool.  This value is only available for storage systems with an SVP.
ddmEnabled	Boolean	Whether the pool is of type DDM. Values are TRUE or FALSE.
encrypted	Boolean	Whether the data is encrypted. Valid values: YES, NO, PARTIAL, or UNKNOWN.
fmcCompressed	String	Whether the data is compressed. accelerated compression is only supported on FMD DC2 drives.
deduplicationEnabled	Boolean	Whether "Deduplication and Compression" capacity saving is available.
compressionDetails	Object	The following attributes are displayed: compressionRate, deduplicationRate, and savingsPercentage.
compressionRate	Float	The ratio of data compression using only controller-based compression.
deduplicationRate	Float	Rate of deduplication. Shows how much the capacity is reduced by deduplication.
savingsPercentage	Integer	Displays the percentage of capacity reduced by capacity saving against the amount before the reduction.
fmcCompressionDetails	Object	Detailed information regarding FMD DC2 compression. If "fmcCompressed" is true, then this parameter is available.
expansionRate	Float	The ratio of the total capacity of FMD pool volumes with respect to the total capacity of FMD pool volumes assured for writing.
compressionRate	Float	The ratio of data compression using only accelerated compression.

Parameter	Type	Description
savingsPercentage	Float	Displays the percentage of the capacity reduced by accelerated compression against the amount before the reduction. This does not display a percentage value until the data is compressed. If the savingsPercentage for a pool is not high enough, you can provision additional pool volumes to the pool from the parity groups using FMD drives.
nasBoot	Boolean	Whether a pool consists of NAS boot volumes. Values are TRUE or FALSE.
deduplicationSystemDataCapacityInBytes	String	System data capacity that is reserved when "deduplicationEnabled" is true. System data capacity is the capacity of the managed area reserved by the storage system when the deduplication function is enabled.
dataReductionSavingsRate	Float	The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.
capacityEfficiencyRate	Float	<p>The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.</p> <p>If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.</p> <p>If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.</p> <p>If no compression technology is in use, the physical used capacity is the used capacity of the pools.</p>
totalEfficiency	Object	Percentages regarding total efficiency. For VSP E series, VSP One Block, and the following storage systems with firmware versions from 88-03-0x or later: VSP G/F350, G/F370, G/F700, G/F900, this parameter has all the totalEfficiency values. For all other storage systems, this value is null.

Parameter	Type	Description
totalEfficiencyRate	Object	The ratio of the total saving effect achieved by accelerated compression, capacity saving (compression and deduplication), snapshot, and Dynamic Provisioning.
status	String	Status of the calculation process of that particular metric. Values can be CALCULATED, CALCULATION_IN_PROGRESS, and CALCULATED_WITH_EXCEEDED.
value	Float	Ratio of that particular metric.
dataReductionEfficiency	Object	Ratios regarding data reduction efficiency.
totalDataReductionRate	Object	Data reduction ratio before and after accelerated compression and capacity saving (compression and deduplication).
softwareSavingEfficiency	Object	Ratios regarding software saving efficiency.
totalSoftwareSavingRate	Object	The capacity reduction ratio before and after capacity saving.
compressionRate	Object	The capacity compression ratio before and after capacity saving.
deduplicationRate	Object	The capacity deduplication ratio before and after capacity saving.
patternMatchingRate	Object	The capacity reduction ratio before and after capacity saving pattern matching.
fmdSavingEfficiency	Object	Ratios regarding accelerated compression saving.
totalFmdSavingRate	Object	The capacity reduction ratio before and after accelerated compression.
compressionRate	Object	The capacity compression ratio before and after accelerated compression.
patternMatchingRate	Object	The capacity reduction ratio before and after accelerated compression pattern matching.
snapshotEfficiencyRate	Object	The efficiency ratio achieved by snapshot.
provisioningEfficiencyPercentage	Object	The efficiency ratio achieved by Dynamic Provisioning.
calculationStartTime	String	The start date and time for the calculation. The date and time are displayed in UTC.

Parameter	Type	Description
calculationEndTime	String	The end date and time for the calculation. The date and time are displayed in UTC.
total	Integer	Total number of resources.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUSl jZzswOw==</pre>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/storage-pools
```

**Example response**

JSON response. For the following storage systems, totalEfficiency is set to null: VSP F1500 and VSP G1000, VSP G1500 and VSP G200, G/F400, G/F600, G/F800, VSP N400, VSP N600 and VSP N800.

```
{
  "resources": [
    {
      "storagePoolId": 3,
      "storageSystemId": "410209",
      "label": "AutoTieredPool-1",
      "capacityInBytes": 3453896097792,
      "usedCapacityInBytes": 0,
      "availableCapacityInBytes": 3453896097792,
      "usedSubscribedCapacityInBytes": 37497077760,
      "logicalCapacityInBytes": 3453896097792,
      "usedLogicalCapacityInBytes": 0,
      "availableLogicalCapacityInBytes": 3453896097792,
      "type": "TIERED",
      "utilizationThreshold1": 20,
      "utilizationThreshold2": 90,
      "subscriptionLimit": {
        "unlimited": false,
        "value": 101
      },
      "usedSubscription": 1,
      "availableSubscription": {
        "unlimited": false,
        "value": 100
      },
      "status": "NORMAL",
      "parityGroups": [
        {
          "id": "1-2",
          "encryption": false,
          "compression": false,
          "compressionSupported": false,
          "parityGroupType": "RAID"
        }
      ],
      "externalParityGroupIds": [],
      "tiers": [
        {
          "tier": "Silver",
          "capacity": 3453896097792,
          "usedCapacity": 0,
          "usage": {
            "unlimited": false,
            "value": 0
          }
        }
      ]
    }
  ]
}
```

```

        "bufferSpace": {
            "newPageAssignment": {
                "unlimited": false,
                "value": 8
            },
            "tierRelocation": {
                "unlimited": false,
                "value": 2
            }
        },
        "performanceUtilization": {
            "unlimited": false,
            "value": 0
        }
    }
},
"tieringMode": "MANUAL",
"monitoringMode": "PERIODICAL",
"activeFlashEnabled": false,
"encrypted": "NO",
"fmcCompressed": "NO",
"deduplicationEnabled": false,
"compressionDetails": null,
"fmcCompressionDetails": null,
"deduplicationSystemDataCapacityInBytes": 0,
"nasBoot": false,
"dataReductionSavingsRate": null,
"capacityEfficiencyRate": null,
"totalEfficiency": {
    "totalEfficiencyRate": {
        "status": "CALCULATED_WITH_EXCEEDED",
        "value": 99999.99
    },
    "dataReductionEfficiency": {
        "totalDataReductionRate": {
            "status": "CALCULATED",
            "value": 99999.99
        },
        "softwareSavingEfficiency": {
            "totalSoftwareSavingRate": {
                "status": "CALCULATED",
                "value": 1.52
            },
            "compressionRate": {
                "status": "CALCULATED",
                "value": 1.15
            },
            "deduplicationRate": {
                "status": "CALCULATED",
                "value": 1.34
            }
        }
    }
},

```

```

        "patternMatchingRate": {
            "status": "CALCULATED",
            "value": 1.08
        },
        "fmdSavingEfficiency": {
            "totalFmdSavingRate": {
                "status": "CALCULATED",
                "value": 2.21
            },
            "compressionRate": {
                "status": "CALCULATED",
                "value": 2.14
            },
            "patternMatchingRate": {
                "status": "CALCULATION_IN_PROGRESS",
                "value": null
            }
        },
        "snapshotEfficiencyRate": {
            "status": "CALCULATED",
            "value": 10.37
        },
        "provisioningEfficiencyPercentage": {
            "status": "CALCULATED",
            "value": 170
        },
        "calculationStartTime": "2018-05-15T10:05",
        "calculationEndTime": "2018-05-15T10:38"
    }
}
]
"total": ,
"nextToken":
}

```

## Getting a pool

You can display detailed information about a specific pool.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/storage-pools/storagePoolId
```

Use the storage system ID as the *storageSystemId*.

Use the storage pool ID as the *storagePoolId*.



**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "storagePoolId": ,
  "storageSystemId": "",
  "label": "",
  "capacityInBytes": ,
  "usedCapacityInBytes": ,
  "availableCapacityInBytes": ,
  "usedSubscribedCapacityInBytes": ,
  "logicalCapacityInBytes": ,
  "usedLogicalCapacityInBytes": ,
  "availableLogicalCapacityInBytes": ,
  "type": "",
  "utilizationThreshold1": ,
  "utilizationThreshold2": ,
  "subscriptionLimit": {
    "unlimited": ,
    "value":
  },
  "usedSubscription": ,
  "availableSubscription": {
    "unlimited": ,
    "value":
  },
  "status": "",
  "parityGroups": [
    {
      "id": "",
      "encryption": ,
      "compression": ,
      "compressionSupported": ,
      "parityGroupType":
    }
  ],
  "externalParityGroupIds": [],
  "tiers": [
    {
      "tier": "",
      "capacity": ,
      "usedCapacity": ,
      "usage": {
        "unlimited": ,
        "value":
      },
      "bufferSpace": {
```

```

        "newPageAssignment": {
            "unlimited": ,
            "value":
        },
        "tierRelocation": {
            "unlimited": ,
            "value":
        }
    },
    "performanceUtilization": {
        "unlimited": ,
        "value":
    }
}
],
"tieringMode": "",
"monitoringMode": "",
"monitoringCycle": "",
"monitoringPeriodStart": "",
"monitoringPeriodEnd": "",
"activeFlashEnabled": ,
"relocationSpeed": "",
"ddmEnabled": ,
"encrypted": "",
"fmcCompressed": "",
"deduplicationEnabled": ,
"compressionDetails": {
    "compressionRate": ,
    "deduplicationRate": ,
    "savingsPercentage":
},
"fmcCompressionDetails": {
    "expansionRate": ,
    "compressionRate": ,
    "savingsPercentage":
},
"deduplicationSystemDataCapacityInBytes": ,
"nasBoot": ,
"dataReductionSavingsRate": ,
"suspendSnapshot": ,
"capacityEfficiencyRate": ,
"totalEfficiency": {
    "totalEfficiencyRate": {
        "status": "",
        "value":
    },
    "dataReductionEfficiency": {
        "totalDataReductionRate": {
            "status": "",
            "value":
        },
    },

```

```

    "softwareSavingEfficiency": {
      "totalSoftwareSavingRate": {
        "status": "",
        "value":
      },
      "compressionRate": {
        "status": "",
        "value":
      },
      "deduplicationRate": {
        "status": "",
        "value":
      },
      "patternMatchingRate": {
        "status": "",
        "value":
      }
    },
    "fmdSavingEfficiency": {
      "totalFmdSavingRate": {
        "status": "",
        "value":
      },
      "compressionRate": {
        "status": "",
        "value":
      },
      "patternMatchingRate": {
        "status": "",
        "value":
      }
    }
  },
  "snapshotEfficiencyRate": {
    "status": "",
    "value":
  },
  "provisioningEfficiencyPercentage": {
    "status": "",
    "value":
  },
  "calculationStartTime": "",
  "calculationEndTime": ""
}

```

Parameter	Type	Description
storagePoolId	String	ID of the storage pool.
storageSystemId	String	ID of the storage system.
label	String	Name of the storage pool.
capacityInBytes	Long	Total capacity, in bytes.
usedCapacityInBytes	Long	Current used capacity in the pool.
availableCapacityInBytes	Long	Unused capacity in the pool.
usedSubscribedCapacityInBytes	Long	Used subscribed capacity for this pool.
logicalCapacityInBytes	Long	Total pool logical capacity.
usedLogicalCapacityInBytes	Long	Used logical capacity for this pool.
availableLogicalCapacityInBytes	Long	Unused logical capacity in the pool.
suspendSnapshot	Boolean	Whether the usedCapacity of the pool is greater than <code>utilizationThreshold2</code> . If <code>TRUE</code> , the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If <code>FALSE</code> , you can write to the snapshot. If the pool is TIERED or SNAP, a NULL value is returned. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is <code>TRUE</code> , the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE.
type	String	Pool type: <ul style="list-style-type: none"> <li>THIN</li> <li>TIERED</li> <li>SNAP</li> </ul>
utilizationThreshold1	Integer	Pool utilization thresholds in percentage (Low). "0" is always displayed in Snap Pool.
utilizationThreshold2	Integer	Pool utilization thresholds in percentage (High).
subscriptionLimit	Object	If a subscription limit is set, unlimited is false and value indicates the limit. If a subscription limit is not set, unlimited is true.

Parameter	Type	Description
unlimited	Boolean	Whether there is a subscription limit. Values are TRUE or FALSE.
usedSubscription	Integer	Current subscribed capacity in this pool.
availableSubscription	String	Available capacity of this pool.
unlimited	Boolean	Whether there is a limit on available capacity. Values are TRUE or FALSE.
status	String	Pool status: Valid values: NORMAL, FULL, SUSPENDED, FAILED.
parityGroups	String	List of parity groups that belong to this pool.
Id	String	ID of the parity group.
encryption	Boolean	Whether the parity group is encrypted. Values are TRUE or FALSE.
compression	Boolean	Whether the parity group is compressed. Values are TRUE or FALSE.
compressionSupported	Boolean	Whether the parity group supports drive-based compression on FMD drives.
parityGroupType	Enum	Type of this parity group. <ul style="list-style-type: none"> <li>RAID: The parity group with Dynamic Drive Protection disabled.</li> <li>DDP: The parity group with Dynamic Drive Protection enabled.</li> </ul>
externalParityGroupIds	List	List of external parity groups that belong to this pool.
tiers	List	List of tiers, with details for each.
tier	String	The tier type. Valid values: Diamond, Platinum, Gold, Silver, Bronze, External.
capacity	String	Capacity of the tier, in bytes.
usedCapacity	String	Tier capacity that is in use.
usage	Object	Percent usage of the tier.
unlimited	Boolean	Whether a limit is set.
bufferSpace	Object	Tier buffer space.
newPageAssignment	Object	The buffer space for new page assignments.

Parameter	Type	Description
unlimited	Boolean	Whether the buffer space for a new page assignment is limited. Values are TRUE or FALSE.
tierRelocation	Object	The buffer space allocated for tier relocation.
unlimited	Boolean	Whether a limit is set.
performanceUtilization	Object	Tier performance usage percentage.
unlimited	Boolean	Whether the buffer space for a new page assignment is limited. Values are TRUE or FALSE.
tieringMode	String	Tiering mode for a Tiered pool. Values: MANUAL, AUTOMATIC, NONE, UNKNOWN. The value for a non-Tiered pool should be NONE. This value is only available for storage systems with an SVP.
activeFlashEnabled	Boolean	Whether active flash is enabled. To enable active flash, one of the tiers must be Platinum and disk types: FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, FMD HDE, or SSD(QLC). You also need to enable the active flash license.
ddmEnabled	Boolean	Whether the pool is of type DDM. Valid values are TRUE or FALSE.
encrypted	Boolean	Whether the data is encrypted. Valid values: YES, NO, PARTIAL, or UNKNOWN.
fmcCompressed	String	Whether the data is compressed. accelerated compression is only supported on FMD DC2 drives.
deduplicationEnabled	Boolean	Whether "Deduplication and Compression" capacity saving is available.
compressionDetails	Object	The following attributes are displayed: compressionRate, deduplicationRate, and savingsPercentage.
compressionRate	Float	The ratio of data compression using only accelerated compression.
deduplicationRate	Float	Rate of deduplication. Shows how much the capacity is reduced by deduplication.

Parameter	Type	Description
savingsPercentage	Integer	Displays the percentage of capacity reduced by capacity saving against the amount before the reduction.
fmcCompressionDetails	Object	Detailed information regarding FMD DC2 compression. If "fmcCompressed" is true, then this parameter is available.
expansionRate	Float	The ratio of the total capacity of FMD pool volumes with respect to the total capacity of FMD pool volumes assured for writing.
compressionRate	Float	The ratio of data compression using only accelerated compression.
savingsPercentage	Float	Displays the percentage of the capacity reduced by accelerated compression against the amount before the reduction. This does not display a percentage value until the data is compressed. If the savingsPercentage for a pool is not high enough, you can provision additional pool volumes to the pool from the parity groups using FMD drives.
deduplicationSystemDataCapacityInBytes	String	System data capacity that is reserved when "deduplicationEnabled" is true. System data capacity is the capacity of the managed area reserved by the storage system when the deduplication function is enabled.
nasBoot	Boolean	Whether a pool consists of NAS boot volumes. Values are TRUE or FALSE.
dataReductionSavingsRate	Float	The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.
capacityEfficiencyRate	Float	<p>The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.</p> <p>If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.</p>

Parameter	Type	Description
		<p>If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.</p> <p>If no compression technology is in use, the physical used capacity is the used capacity of the pools.</p>
totalEfficiency	Object	Percentages regarding total efficiency. For VSP E series, VSP One Block, and the following storage systems with firmware versions from 88-03-0x or later: VSP G/ F350, G/F370, G/F700, G/F900, this parameter has all the totalEfficiency values. For all other storage systems, this value is null.
totalEfficiencyRate	Object	The ratio of the total saving effect achieved by accelerated compression, capacity saving (compression and deduplication), snapshot, and Dynamic Provisioning.
status	String	Status of the calculation process of that particular metric. Values can be CALCULATED, CALCULATION_IN_PROGRESS, and CALCULATED_WITH_EXCEEDED.
value	Float	Ratio of that particular metric.
dataReductionEfficiency	Object	Ratios regarding data reduction efficiency.
totalDataReductionRate	Object	Data reduction ratio before and after accelerated compression and capacity saving (compression and deduplication).
softwareSavingEfficiency	Object	Ratios regarding software saving efficiency.
totalSoftwareSavingRate	Object	The capacity reduction ratio before and after capacity saving.
compressionRate	Object	The capacity compression ratio before and after capacity saving.
deduplicationRate	Object	The capacity deduplication ratio before and after capacity saving.
patternMatchingRate	Object	The capacity reduction ratio before and after capacity saving pattern matching.



Parameter	Type	Description
fmdSavingEfficiency	Object	Ratios regarding accelerated compression saving.
totalFmdSavingRate	Object	The capacity reduction ratio before and after accelerated compression.
compressionRate	Object	The capacity compression ratio before and after accelerated compression.
patternMatchingRate	Object	The capacity reduction ratio before and after accelerated compression pattern matching.
snapshotEfficiencyRate	Object	The efficiency ratio achieved by snapshot.
provisioningEfficiencyPercentage	Object	The efficiency ratio achieved by Dynamic Provisioning.
calculationStartTime	String	The start date and time for the calculation. The date and time are displayed in UTC.
calculationEndTime	String	The end date and time for the calculation. The date and time are displayed in UTC.
relocationSpeed	String	Relocation speed for a tiered pool.  This value is only available for storage systems with an SVP.
monitoringMode	String	Monitoring mode for a Tiered pool. Values: PERIODICAL, CONTINUOUS, PERIODICAL_WITH_ACTIVE_FLASH, CONTINUOUS_WITH_ACTIVE_FLASH, NONE. The value for a non-Tiered pool is NONE.
monitoringCycle	String	A cycle time during which I/O monitoring is performed on a tiered pool. The value is in the ISO8601 duration format. This value is only available for storage systems with an SVP.
monitoringPeriodStart	String	The instant that monitoring begins in storage system local time, with no adjustment for daylight savings. This value is only available for storage systems with an SVP.
monitoringPeriodEnd	String	The instant that monitoring ends in storage system local time, with no adjustment for daylight savings. This value is only available for storage systems with an SVP.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example code**

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/storage-pools/3
```

**Example response**

JSON response. For the following storage systems, totalEfficiency is set to null: VSP F1500 and VSP G1000, VSP G1500 and VSP G200, G/F400, G/F600, G/F800, VSP N400, VSP N600 and VSP N800.

```
{
  "storagePoolId": 0,
  "storageSystemId": "410209",
  "label": "SSD-Pool",
  "capacityInBytes": 19500160253952,
  "usedCapacityInBytes": 0,
  "availableCapacityInBytes": 19500160253952,
  "usedSubscribedCapacityInBytes": 1277165568,
  "logicalCapacityInBytes": 19500160253952,
  "usedLogicalCapacityInBytes": 0,
  "availableLogicalCapacityInBytes": 19500160253952,
  "type": "TIERED",
  "utilizationThreshold1": 70,
  "utilizationThreshold2": 80,
  "subscriptionLimit": {
    "unlimited": true,
```

```

        "value": null
    },
    "usedSubscription": 0,
    "availableSubscription": {
        "unlimited": true,
        "value": null
    },
    "status": "NORMAL",
    "parityGroups": [
        {
            "id": "1-2",
            "encryption": false,
            "compression": false,
            "compressionSupported": false,
            "parityGroupType": "RAID"
        },
        {
            "id": "1-12",
            "encryption": false,
            "compression": false,
            "compressionSupported": false,
            "parityGroupType": "RAID"
        }
    ],
    "externalParityGroupIds": [],
    "tiers": [
        {
            "tierId": 1,
            "tier": "Platinum",
            "capacity": 5666915745792,
            "usedCapacity": 0,
            "usage": {
                "unlimited": false,
                "value": 0
            },
            "bufferSpace": {
                "newPageAssignment": {
                    "unlimited": false,
                    "value": 8
                },
                "tierRelocation": {
                    "unlimited": false,
                    "value": 2
                }
            },
            "performanceUtilization": {
                "unlimited": false,
                "value": 0
            }
        },
        {

```

```

        "tierId": 3,
        "tier": "Silver",
        "capacity": 13833244508160,
        "usedCapacity": 0,
        "usage": {
            "unlimited": false,
            "value": 0
        },
        "bufferSpace": {
            "newPageAssignment": {
                "unlimited": false,
                "value": 8
            },
            "tierRelocation": {
                "unlimited": false,
                "value": 2
            }
        },
        "performanceUtilization": {
            "unlimited": false,
            "value": 0
        }
    }
},
"tieringMode": "AUTOMATIC",
"monitoringMode": "CONTINUOUS",
"monitoringCycle": "PT24H",
"monitoringPeriodStart": "00:00",
"monitoringPeriodEnd": "23:59",
"relocationSpeed": "STANDARD",
"activeFlashEnabled": false,
"ddmEnabled": false,
"encrypted": "NO",
"fmcCompressed": "NO",
"deduplicationEnabled": false,
"compressionDetails": null,
"fmcCompressionDetails": null,
"deduplicationSystemDataCapacityInBytes": 0,
"nasBoot": false,
"dataReductionSavingsRate": 0,
"capacityEfficiencyRate": 0,
"suspendSnapshot": null,
"totalEfficiency": null
}

```

## Getting pool summaries

You can display a summary of pools based on their type: THIN, TIERED, or SNAP.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/storage-pools/summary
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "summariesByType":
  [
    {
      "poolType": "",
      "totalCapacity": ,
      "usedCapacity": ,
      "availableCapacity": ,
      "usedSubscribedCapacity": ,
      "poolCount": ,
    },
    .....
  ]
}
```

Parameter	Type	Description
poolType	String	Pool type can be of the following values or the name of a tier that is available in the storage system. <ul style="list-style-type: none"> <li>THIN</li> <li>TIERED</li> <li>SNAP</li> </ul>
usedCapacity	String	Sum of used capacity across all pools of the specified type in the storage system, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
usedSubscribedCapacity	String	Subscribed used capacity across all the pools of the specified type on that storage system.

Parameter	Type	Description
totalCapacity	String	Total capacity of the specified pool type in the storage system, in bytes.
poolCount	Integer	Number of pools in the pool type that is available on the storage system.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

Request with JSON command:

```
https://172.17.64.109/v1/storage-systems/410209/storage-pools/summary
```

JSON response:

```
{
  "summariesByType":
  [
    {
      "poolType": "THIN",
```

```

        "totalCapacity": "23819314003968",
        "usedCapacity": "3748436901888",
        "availableCapacity": "20070877102080",
        "usedSubscribedCapacity": "167136337068032"
        "poolCount": 4
    },
]
}

```

## Creating a pool

You can create a pool with a list of parity groups. All parity groups must belong to the same storage system and the pool type. You cannot create a pool from parity groups with Dynamic Drive Protection enabled.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/storage-pools
```

Use the storage system ID as the *storageSystemId*.

### Request structure

The request body structure is as follows:

```

{
  "label": " ",
  "type": "",
  "tieringMode": "",
  "monitoringMode": "",
  "monitoringCycle": "",
  "monitoringPeriodStart": "",
  "monitoringPeriodEnd": "",
  "relocationSpeed": "",
  "activeFlashEnabled": ,
  "ddmEnabled": ,
  "utilizationThreshold1": ,
  "utilizationThreshold2": ,
  "subscriptionLimit": {
    "value" : ,
    "unlimited":
  },
  "parityGroupIds":[""],
  "externalParityGroupsIds" [""]
  "suspendSnapshot": ,
  "tiers": [
    {
      "bufferSpace": {
        "newPageAssignment": ,
        "tierRelocation":

```

```

    },
    "bufferSpace": {
      "newPageAssignment": ,
      "tierRelocation":
    },
    "bufferSpace": {
      "newPageAssignment": ,
      "tierRelocation":
    }
  }
]
}

```

Parameter	Required	Type	Description
label	Yes	String	The pool name.
type	Yes	String	The pool type: THIN, TIERED, or SNAP.
activeFlashEnabled	No	Boolean	Whether active flash is enabled. To enable it, one of the tiers must be a Platinum tier and one of the disk type: FMD, SSD, SSD(RI), FMD DC2, FMD HDE, SSD NVMe, or SSD(QLC). You also need to install the active flash license.
bufferSpace	No	Object	The default rates (rate to capacity of a tier) of buffer space used for new page assignments and tier relocation. Can be specified up to 3 times. The first, second, and third bufferSpace object setting will be applied to the first, second, and third tier, respectively.
ddmEnabled	No	Boolean	Whether there is a DDM pool creation request. Valid values are TRUE or FALSE.
tieringMode	No	String	Tiering mode for tiered pools. Values: AUTOMATIC or MANUAL. This is set to AUTOMATIC if no value is specified. Setting this value is only available for storage systems with an SVP.
monitoringMode	No	String	Monitoring mode for a Tiered pool. Values: PERIODICAL or CONTINUOUS. This is set to CONTINUOUS if no value is specified.



Parameter	Required	Type	Description
monitoringCycle	No	String	A cycle time during which I/O monitoring is performed on a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 duration format. Possible values are: "PT24H", "PT8H", "PT4H", "PT2H", "PT1H" or "PT30M" for 24 hours, 8 hours, 4 hours, 2 hours, 1 hour and 30 minutes respectively. If a value is not specified, "PT24H" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodStart	No	String	The instant when monitoring begins in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "00:00" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodEnd	No	String	The instant when monitoring ends in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "23:59" will be set as default value. This value cannot be less than monitoringPeriodStart value. This value is only available for storage systems with an SVP.
newPageAssignment	No	Integer	The percentage of buffer space of a tier assigned to new pages. This value must be between 0 and 50.
tierRelocation	No	Integer	The percentage of buffer space of a tier assigned for relocation. This value must be between 2 and 40. If not specified 2 (%) will be used as a default value for each tier.

Parameter	Required	Type	Description
relocationSpeed	No	String	Relocation speed for a tiered pool. If not specified STANDARD is used as a default value. Possible values are SLOWEST, SLOWER, STANDARD, FASTER or FASTEST. This value is only available for storage systems with an SVP.
utilizationThreshold1	No	Integer	Pool utilization thresholds in percentage (Low). When type is SNAP, this parameter is ignored. The range is between 1 - 100. If the utilizationThreshold1 is not specified, Ops Center Administrator sets it to 70%.
utilizationThreshold2	No	Integer	Pool utilization thresholds in percentage (High). The range is between 1 - 100. The value for utilizationThreshold2 must be greater than the value for utilizationThreshold1. If utilizationThreshold2 is not specified, Ops Center Administrator sets it to 80%.
subscriptionLimit	No	Object	<p>This is the maximum volume capacity subscription that is allowed on a given storage pool. The allowed values are between 1 - 65534.</p> <p>To set an unlimited subscription limit, set unlimited = true.</p> <p>This parameter cannot be set for pools which is deduplication disabled or has volumes with capacity saving enabled for VSP 5000 series storage systems with firmware versions from 90-01-4x or later.</p> <p>If the subscriptionLimit is not specified, Hitachi Ops Center Administrator sets it to unlimited for storage systems VSP 5000 series with firmware versions 90-01-4x or later, and to 100% for others.</p>

Parameter	Required	Type	Description
			This parameter cannot be set for VSP G370, VSP F370, VSP F700, VSP F900 and VSP G350, VSP G370, VSP G700, VSP G900 and VSP One Block.
parityGroupIds	No*	List	The list of parity group IDs that belong to this pool.
externalParityGroupIds	No*	List	The list of external parity group IDs that belong to this pool.
suspendSnapshot	No	Boolean	Whether the usedCapacity of the pool is greater than utilizationThreshold2. If TRUE, the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If FALSE, you can write to the snapshot. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is TRUE, the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE. Set to TRUE by default.
*: You must specify either parityGroupIds or externalParityGroupIds, or you can specify both.			

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
}
```

```

"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/storage-pools
```

**Example request**

```
{
  "label": "ExternalPool",
  "type": "TIERED",
  "tieringMode": "MANUAL" ,
  "monitoringMode": "PERIODICAL" ,
  "monitoringCycle": "PT24H" ,
  "monitoringPeriodStart": "00:00" ,
  "monitoringPeriodEnd": "23:59" ,
  "relocationSpeed": "SLOWER" ,
  "activeFlashEnabled": true,
  "ddmEnabled": false,
  "utilizationThreshold1": 90,
  "utilizationThreshold2": 95,
  "subscriptionLimit": {
    "value" : 100,
    "unlimited": false
  },
  "parityGroupIds": ["5-1"]
  "externalParityGroupIds": ["2-3"],
  "tiers": [
    {
      "tier": "Silver",
      "bufferSpace": {
        "newPageAssignment": {
          "value": 8
        },
        "tierRelocation": {
          "value": 2
        }
      }
    }
  ]
}
```

## Updating a pool

You can update a pool, such as renaming or expanding the pool by adding parity groups, changing the threshold and subscription limits for the pool, and changing the pool type from THIN to TIERED. However, you can not delete or update any parameters on pools created on external parity groups. You cannot update a pool created from parity groups with Dynamic Drive Protection enabled or by adding parity groups with Dynamic Drive Protection enabled.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/storage-pools/storagePoolId
```

Use the storage system ID as the *storageSystemId*.

Use the storage pool ID as the *storagePoolId*.

**Request structure**

The request body structure is shown below:

```
{
  "label": " ",
  "type": "",
  "tieringMode": "",
  "monitoringMode": "",
  "monitoringCycle": "",
  "monitoringPeriodStart": "",
  "monitoringPeriodEnd": "",
  "relocationSpeed": "",
  "activeFlashEnabled": ,
  "ddmEnabled": ,
  "utilizationThreshold1": ,
  "utilizationThreshold2": ,
  "subscriptionLimit": {
    "value" : ,
    "unlimited":
  },
  "parityGroupIds": [""],
  "externalParityGroupsIds" [""],
  "suspendSnapshot": ,
  "tiers": [
    {
      "bufferSpace": {
        "newPageAssignment": ,
        "tierRelocation":
      },
      "bufferSpace": {
        "newPageAssignment": ,
        "tierRelocation":
      },
      "bufferSpace": {
        "newPageAssignment": ,
        "tierRelocation":
      }
    }
  ]
}
```

Parameter	Required	Type	Description
label	Yes	String	The pool name.
poolType	No	String	The pool type: THIN, TIERED, and SNAP.
moveToResourceGroup	No	Boolean	Whether to move parity group LDEVs to the pool's resource group or not.
activeFlashEnabled	No	Boolean	Whether active flash is enabled. To enable it, one of the tiers must be a Platinum tier and one of the disk type: FMD, SSD, SSD(RI), FMD DC2, FMD HDE, SSD NVMe, or SSD(QLC). You also need to install the active flash license.
bufferSpace	No	Object	The default rates (rate to capacity of a tier) of buffer space used for new page assignments and tier relocation. Can be specified up to 3 times. The first, second, and third bufferSpace object setting will be applied to the first, second, and third tier, respectively.
ddmEnabled	No	Boolean	Whether there is a DDM pool creation request. Valid values are TRUE or FALSE.
tieringMode	No	String	Tiering mode for tiered pools. Values: AUTOMATIC or MANUAL. This is set to AUTOMATIC if no value is specified. Setting this value is only available for storage systems with an SVP.
monitoringMode	No	String	Monitoring mode for a Tiered pool. Values: PERIODICAL or CONTINUOUS. This is set to CONTINUOUS if no value is specified.



Parameter	Required	Type	Description
monitoringCycle	No	String	A cycle time during which I/O monitoring is performed on a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 duration format. Possible values are: "PT24H", "PT8H", "PT4H", "PT2H", "PT1H" or "PT30M" for 24 hours, 8 hours, 4 hours, 2 hours, 1 hour and 30 minutes respectively. If a value is not specified, "PT24H" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodStart	No	String	The instant when monitoring begins in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "00:00" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodEnd	No	String	The instant when monitoring ends in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "23:59" will be set as default value. This value cannot be less than monitoringPeriodStart value. This value is only available for storage systems with an SVP.
newPageAssignment	No	Integer	The percentage of buffer space of a tier assigned to new pages. This value must be between 0 and 50.
tierRelocation	No	Integer	The percentage of buffer space of a tier assigned for relocation. This value must be between 2 and 40. If not specified 2 (%) will be used as a default value for each tier.

Parameter	Required	Type	Description
relocationSpeed	No	String	Relocation speed for a tiered pool. If not specified STANDARD is used as a default value. Possible values are SLOWEST, SLOWER, STANDARD, FASTER or FASTEST. This value is only available for storage systems with an SVP.
utilizationThreshold1	No	Integer	Pool utilization thresholds in percentage (Low). When type is SNAP, this parameter is ignored. The range is between 1 - 100. If the utilizationThreshold1 is not specified, Ops Center Administrator sets it to 70%.
utilizationThreshold2	No	Integer	Pool utilization thresholds in percentage (High). The range is between 1 - 100. The value for utilizationThreshold2 must be greater than the value for utilizationThreshold1. If utilizationThreshold2 is not specified, Ops Center Administrator sets it to 80%.
subscriptionLimit	No	Object	<p>This is the maximum volume capacity subscription that is allowed on a given storage pool. The allowed values are between 1 - 65534.</p> <p>To set an unlimited subscription limit, set unlimited = true.</p> <p>This parameter cannot be set for pools which is deduplication disabled or has volumes with capacity saving enabled for VSP 5000 series storage systems with firmware versions from 90-01-4x or later.</p> <p>If the subscriptionLimit is not specified, Hitachi Ops Center Administrator sets it to unlimited for storage systems VSP 5000 series with firmware versions 90-01-4x or later, and to 100% for others.</p>

Parameter	Required	Type	Description
			This parameter cannot be set for VSP G370, VSP F370, VSP F700, VSP F900 and VSP G350, VSP G370, VSP G700, VSP G900 and VSP One Block.
parityGroupIds	No*	List	The list of parity group IDs that belong to this pool.
externalParityGroupIds	No*	List	The list of external parity group IDs that belong to this pool.
suspendSnapshot	No	Boolean	Whether the usedCapacity of the pool is greater than <code>utilizationThreshold2</code> . If <code>TRUE</code> , the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If <code>FALSE</code> , you can write to the snapshot. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is <code>TRUE</code> , the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE. Set to <code>TRUE</code> by default.
*: You must specify either <code>parityGroupIds</code> or <code>externalParityGroupIds</code> , or you can specify both.			

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
}
```

```

"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/storage-systems/410209/storage-pools/14
```

**Example request**

```
{
  "label": "ExternalPool",
  "type": "TIERED",
  "tieringMode": "MANUAL" ,
  "monitoringMode": "PERIODICAL" ,
  "monitoringCycle": "PT24H" ,
  "monitoringPeriodStart": "00:00" ,
  "monitoringPeriodEnd": "23:59" ,
  "relocationSpeed": "SLOWER" ,
  "activeFlashEnabled": true,
  "moveToResourceGroup": false,
  "utilizationThreshold1": 90,
  "utilizationThreshold2": 95,
  "subscriptionLimit": {
    "value" : 100,
    "unlimited": false
  },
  "parityGroupIds": ["5-1"]
  "externalParityGroupIds": ["2-3"],
  "tiers": [
    {
      "tier": "Silver",
      "bufferSpace": {
        "newPageAssignment": {
          "value": 8
        },
        "tierRelocation": {
          "value": 2
        }
      }
    }
  ]
}
```

**Deleting a pool**

You can delete a pool from a storage system. You cannot delete a pool created from parity groups with Dynamic Drive Protection enabled.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/storage-systems/storageSystemId/storage-pools/storagePoolId
```

Use the storage system ID as the *storageSystemId*.

Use the storage pool ID as the *storagePoolId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .



**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Getting pool templates**

You can list all the different pool size options that are available to expand a given pool. You must specify either the tier name or the capacity, diskType, raidLevel, raidLayout, and speed. You cannot create a pool from parity group with Dynamic Drive Protection enabled from this list.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/templates/pool
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The request body structure is as follows:

```
{
  "label": ,
  "utilizationThreshold1": ,
  "utilizationThreshold2": ,
  "subscriptionLimit": {
    "unlimited": ,
    "value":
  },
  "suspendSnapshot": ,
  "tiers": [
    {
      "name": "",
      "tierId": ,
      "templateSubTiers": [
        {
          "description": "",
          "diskType": "",
          "speed": ,
          "capacity": "",
          "raidLevel": "",
          "raidLayout": "",
          "availableSizesInBytes": [
            ""
          ]
        }
      ],
      "priority":
    }
  ]
}
```

Parameter	Type	Description
label	String	Name of the storage pool.

Parameter	Type	Description
utilizationThreshold1	String	Pool utilization thresholds in percentage (Low).
utilizationThreshold2	String	Pool utilization thresholds in percentage (High).
subscriptionLimit	String	Maximum subscription of volume capacity allowed on this pool.  If there is an unlimited subscription limit, unlimited = true.  Always NULL for VSP G/F350, G/F370, G/F700, G/F900.
suspendSnapshot	Boolean	Whether the usedCapacity of the pool is greater than utilizationThreshold2. If TRUE, the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If FALSE, you can write to the snapshot. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is TRUE, the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE.
tiers	String	Tiers that belong in the pool.
name	String	Name of the tier.
tierId	Integer	ID of the tier.
templateSubTiers	List	List of template items that form the sub tier.
description	String	Short description of the pool.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
capacity	Long	Capacity of the tier in bytes.
raidLevel	String	RAID level. Valid values: RAID1+0, RAID5, or RAID6.

Parameter	Type	Description
raidLayout	String	RAID layout. This RAID layout should be of the specified RAID level.
availableSizesInBytes	Long	Available sizes to use for creating and updating the pool.
priority	Integer	Priority of the tier. 1 equals the highest tier priority.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.109/v1/storage-systems/410209/templates/pool
```

### Example response

```
{
  "label": "SSD-Pool",
  "utilizationThreshold1": 70,
  "utilizationThreshold2": 80,
  "subscriptionLimit": null,
  "tiers": [
    {
      "name": "Diamond",
      "tierId": 6,
```

```

    "templateSubTiers": [],
    "priority": 1
  },
  {
    "name": "Platinum",
    "tierId": 1,
    "templateSubTiers": [],
    "priority": 2
  },
  {
    "name": "Gold",
    "tierId": 2,
    "templateSubTiers": [],
    "priority": 3
  },
  {
    "name": "Silver",
    "tierId": 3,
    "templateSubTiers": [],
    "priority": 4
  },
  {
    "name": "Bronze",
    "tierId": 4,
    "templateSubTiers": [],
    "priority": 5
  }
],
"warning": null,
"suspendSnapshot": null
}

```

## Getting a specific pool template

You can list the different pool sizes that can be created for a specific storage pool, based on the available resources and applying best practices. You cannot update a pool from parity group with Dynamic Drive Protection enabled from this list.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/templates/pool/storagePoolId
```

Use the storage system ID as the *storageSystemId*.

Use the storage pool ID as the *storagePoolId*.

### Request structure

Not applicable.

**Response structure**

```

{
  "label": "",
  "utilizationThreshold1": ,
  "utilizationThreshold2": ,
  "subscriptionLimit": {
    "value": ,
    "unlimited":
  },
  "suspendSnapshot": ,
  "tiers": [
    {
      "name": "",
      "tierId": ,
      "templateSubTiers": [
        {
          "availableSizesInBytes": [
            ""
          ],
          "diskType": "",
          "speed": ,
          "capacity": {
            "bytes":
          },
          "raidLevel": "",
          "raidLayout": "",
          "description": ""
        }
      ],
      "priority":
    }
  ]
}

```

Parameter	Type	Description
label	String	Name of the storage pool.
utilizationThreshold1	String	Pool utilization thresholds in percentage (Low).
utilizationThreshold2	String	Pool utilization thresholds in percentage (High).
subscriptionLimit	String	Maximum subscription of volume capacity allowed on this pool.  If there is an unlimited subscription limit, unlimited = true.

Parameter	Type	Description
		Always NULL for VSP G/F350, G/F370, G/F700, G/F900.
suspendSnapshot	Boolean	Whether the usedCapacity of the pool is greater than <code>utilizationThreshold2</code> . If <code>TRUE</code> , the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If <code>FALSE</code> , you can write to the snapshot. If the pool is TIERED or SNAP, a NULL value is returned. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is <code>TRUE</code> , the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE.
tiers	String	Tiers that belong in the pool.
name	String	Name of the tier.
tierId	Integer	ID of the tier.
templateSubTiers	List	List of template items that form the sub tier.
availableSizesInBytes	String	Unused capacity of the volume that is attached to the host.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
capacity	String	Capacity of the tier in bytes.
raidLevel	String	RAID level, such as RAID 5 or RAID 6.
raidLayout	String	RAID layout.
description	String	Short description of the pool.
priority	Integer	Priority of the tier. 1 equals the highest tier priority.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.109/v1/storage-systems/410209/templates/pool/1
```

**Example response**

```
{
  "label": "SSD-Pool",
  "utilizationThreshold1": 70,
  "utilizationThreshold2": 80,
  "subscriptionLimit": null,
  "tiers": [
    {
      "name": "Diamond",
      "tierId": 6,
      "templateSubTiers": [],
      "priority": 1
    },
    {
      "name": "Platinum",
      "tierId": 1,
      "templateSubTiers": [],
      "priority": 2
    },
    {
      "name": "Gold",
      "tierId": 2,
      "templateSubTiers": [],

```



```

        "priority": 3
    },
    {
        "name": "Silver",
        "tierId": 3,
        "templateSubTiers": [],
        "priority": 4
    },
    {
        "name": "Bronze",
        "tierId": 4,
        "templateSubTiers": [],
        "priority": 5
    }
],
"warning": null,
"suspendSnapshot": null
}

```

## Creating pool template

Using best practices, you can create a pool of a specified size and tier. If more than one tier is requested, a tiered pool is created. The tier `name` and the available pool size, `sizeToUseInBytes`, are the required parameters. Other disk parameters, such as, `speed`, `capacity`, `raidLevel`, `raidLayout`, and `diskType` are ignored, if specified. You cannot create a pool from parity groups with Dynamic Drive Protection enabled.

The pool size must be one of the possible sizes returned by the GET pool template API.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/templates/pool
```

Use the storage system ID as the *storageSystemId*.

### Request structure

The request body structure is as follows:

```

{
    "tieringMode": "",
    "monitoringMode": "",
    "monitoringCycle": "",
    "monitoringPeriodStart": "",
    "monitoringPeriodEnd": "",
    "relocationSpeed": "",
    "utilizationThreshold1": ,
    "utilizationThreshold2": ,
    "subscriptionLimit": {
        "unlimited": ,
    }
}

```

```

    "value":
  },
  "htiPool": ,
  "poolTemplateSubTiers": [
    {
      "capacity": {
        "bytes":
      },
      "diskType": "",
      "raidLevel": "",
      "raidLayout": "",
      "speed": ,
      "sizeToUseInBytes": "",
      "name": "",
      "bufferSpace": {
        "newPageAssignment":,
        "tierRelocation":
      }
    }
  ],
  "label": ""
  "suspendSnapshot":
}

```

Parameter	Required	Type	Description
subscriptionLimit	No	Object	<p>This is the maximum volume capacity subscription that is allowed on a given storage pool. The allowed values are between 1 - 65534.</p> <p>To set an unlimited subscription limit, set unlimited = true.</p> <p>This parameter cannot be set for pools which is deduplication disabled or has volumes with capacity saving enabled for VSP 5000 series storage systems with firmware versions from 90-01-4x or later.</p> <p>If the subscriptionLimit is not specified, Hitachi Ops Center Administrator sets it to unlimited for storage systems VSP 5000 series with firmware versions 90-01-4x or later, and to 100% for others.</p> <p>This parameter cannot be set for VSP G370, VSP F370, VSP F700, VSP F900 and VSP G350, VSP G370, VSP G700, VSP G900 and VSP One Block.</p>

Parameter	Required	Type	Description
utilizationThreshold1	No	Integer	Pool utilization thresholds in percentage (Low). The range is between 1 - 100. If the utilizationThreshold1 is not specified, Ops Center Administrator sets it to 70%.
utilizationThreshold2	No	Integer	Pool utilization thresholds in percentage (High). The range is between 1 - 100. The value for utilizationThreshold2 must be greater than the value for utilizationThreshold1. If utilizationThreshold2 is not specified, Ops Center Administrator sets it to 80%.
htiPool	No	Boolean	Determines whether the pool is an HTI pool. Set this to be true when you want the pool to be an HTI pool.
diskType	Yes	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
raidLevel	Yes	String	RAID level. Valid values: RAID0, RAID1, RAID1+0, RAID0+1, RAID2, RAID3, RAID4, RAID5, or RAID6.
raidLayout	Yes	String	<p>The RAID layout of the specified RAID level.</p> <p>For VSP E series, VSP G200, G/F400, G/F600, G/F800 and VSP G/F350, G/F370, G/F700, G/F900:</p> <ul style="list-style-type: none"> <li>RAID1+0: (2D+2D)</li> <li>RAID5: (3D+1P), (4D+1P), (6D+1P), and (7D+1P)</li> <li>RAID6: (6D+2P), (14D+2P), (12D+2P)</li> </ul> <p>For VSP G1000, VSP G1500, VSP F1500, VSP 5000 series:</p> <ul style="list-style-type: none"> <li>RAID5: (3D+1P), (7D+1P)</li> <li>RAID6: (6D+2P), (14D+2P)</li> <li>RAID1+0: (2D+2D), (2D+2D)x2</li> </ul>
speed	Yes	Integer	The speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, SCM NVMe, FMD DC2, or SSD(QLC), the speed is 0.

Parameter	Required	Type	Description
sizeToUseInBytes	Yes	String	The size to be used in creating and updating the pool (Based on all availableSizesInBytes).
name	Yes	String	Name of the tier, such as Diamond, Platinum, Gold, Silver, or Bronze.
label	No	String	Name of the storage pool. This should be a unique name for the storage pool.
tieringMode	No	String	Tiering mode for tiered pools. Values: AUTOMATIC or MANUAL. This is set to AUTOMATIC if no value is specified. Setting this value is only available for storage systems with an SVP.
monitoringMode	No	String	Monitoring mode for a Tiered pool. Values: PERIODICAL or CONTINUOUS. This is set to CONTINUOUS if no value is specified.
monitoringCycle	No	String	A cycle time during which I/O monitoring is performed on a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 duration format. Possible values are: "PT24H", "PT8H", "PT4H", "PT2H", "PT1H" or "PT30M" for 24 hours, 8 hours, 4 hours, 2 hours, 1 hour and 30 minutes respectively. If a value is not specified, "PT24H" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodStart	No	String	The instant when monitoring begins in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "00:00" will be set as default value. This value is only available for storage systems with an SVP.

Parameter	Required	Type	Description
monitoringPeriodEnd	No	String	The instant when monitoring ends in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "23:59" will be set as default value. This value cannot be less than monitoringPeriodStart value. This value is only available for storage systems with an SVP.
newPageAssignment	No	Integer	The percentage of buffer space of a tier assigned to new pages. This value must be between 0 and 50.
tierRelocation	No	Integer	The percentage of buffer space of a tier assigned for relocation. This value must be between 2 and 40. If not specified 2 (%) will be used as a default value for each tier.
relocationSpeed	No	String	Relocation speed for a tiered pool. If not specified STANDARD is used as a default value. Possible values are SLOWEST, SLOWER, STANDARD, FASTER or FASTEST. This value is only available for storage systems with an SVP.
suspendSnapshot	No	Boolean	Whether the usedCapacity of the pool is greater than utilizationThreshold2. If TRUE, the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If FALSE, you can write to the snapshot. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is TRUE, the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE. Set to TRUE by default.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
```

```

"title":
{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  }
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Updating a pool template**

Using best practices, you can update a pool of a specified size and tier. If more than one tier is requested, a tiered pool is created. You must specify either the tier name or the capacity, diskType, raidLevel, raidLayout, and speed. You cannot update a pool created from parity groups with Dynamic Drive Protection enabled or by adding parity groups with Dynamic Drive Protection enabled.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/templates/pool/storagePoolId
```

Use the storage system ID as the *storageSystemId*.

Use the storage pool ID as the *storagePoolId*.

**Request structure**

The request body structure is as follows:

```
{
  "tieringMode": "",
```



```

"monitoringMode": "",
"monitoringCycle": "",
"monitoringPeriodStart": "",
"monitoringPeriodEnd": "",
"relocationSpeed": "",
"utilizationThreshold1": ,
"utilizationThreshold2": ,
"subscriptionLimit": {
  "unlimited": ,
  "value":
},
"htiPool": ,
"poolTemplateSubTiers": [
  {
    "capacity": {
      "bytes":
    },
    "diskType": "",
    "raidLevel": "",
    "raidLayout": "",
    "speed": ,
    "sizeToUseInBytes": "",
    "name": "",
    "bufferSpace": {
      "newPageAssignment":,
      "tierRelocation":
    }
  }
],
"label": ""
"suspendSnapshot":
}

```

Parameter	Required	Type	Description
bufferSpace	No	Object	The default rates (rate to capacity of a tier) of buffer space used for new page assignments and tier relocation.
utilizationThreshold1	No	Integer	Pool utilization thresholds in percentage (Low). The range is between 1 - 100. If the utilizationThreshold1 is not specified, Ops Center Administrator sets it to 70%.

Parameter	Required	Type	Description
utilizationThreshold2	No	Integer	Pool utilization thresholds in percentage (High). The range is between 1 - 100. The value for utilizationThreshold2 must be greater than the value for utilizationThreshold1. If utilizationThreshold2 is not specified, Ops Center Administrator sets it to 80%.
subscriptionLimit	No	Object	<p>This is the maximum volume capacity subscription that is allowed on a given storage pool. The allowed values are between 1 - 65534.</p> <p>To set an unlimited subscription limit, set unlimited = true.</p> <p>This parameter cannot be set for pools which is deduplication disabled or has volumes with capacity saving enabled for VSP 5000 series storage systems with firmware versions from 90-01-4x or later.</p> <p>If the subscriptionLimit is not specified, Hitachi Ops Center Administrator sets it to unlimited for storage systems VSP 5000 series with firmware versions 90-01-4x or later, and to 100% for others.</p> <p>This parameter cannot be set for VSP G370, VSP F370, VSP F700, VSP F900 and VSP G350, VSP G370, VSP G700, VSP G900 and VSP One Block.</p>
htiPool	No	Boolean	Determines whether the pool is a HTI pool. Set this to be true when you want the pool to be an HTI pool.
capacity	No	String	Capacity of the tier in bytes.
diskType	Yes	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
raidLevel	No	String	RAID level, such as RAID 5 or RAID 6.
raidLayout	No	String	RAID layout

Parameter	Required	Type	Description
speed	Yes	Integer	The speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, SCM NVMe, FMD DC2, or SSD(QLC), the speed is 0.
sizeToUseInBytes	Yes	String	The size to be used in creating and updating the pool (Based on all availableSizesInBytes).
name	No	String	Name of the tier.
label	No	String	Name of the storage pool. This should be a unique name for the storage pool.
moveToResourceGroup	No	Boolean	Whether to move parity group ldevs to the pool's resource group or not.
tieringMode	No	String	Tiering mode for tiered pools. Values: AUTOMATIC or MANUAL. This is set to AUTOMATIC if no value is specified. Setting this value is only available for storage systems with an SVP.
monitoringMode	No	String	Monitoring mode for a Tiered pool. Values: PERIODICAL or CONTINUOUS. This is set to CONTINUOUS if no value is specified.
monitoringCycle	No	String	A cycle time during which I/O monitoring is performed on a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 duration format. Possible values are: "PT24H", "PT8H", "PT4H", "PT2H", "PT1H" or "PT30M" for 24 hours, 8 hours, 4 hours, 2 hours, 1 hour and 30 minutes respectively. If a value is not specified, "PT24H" will be set as default value. This value is only available for storage systems with an SVP.
monitoringPeriodStart	No	String	The instant when monitoring begins in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "00:00" will be set as default value. This value is only available for storage systems with an SVP.

Parameter	Required	Type	Description
monitoringPeriodEnd	No	String	The instant when monitoring ends in storage system local time, with no adjustment for daylight savings for a tiered pool when tieringMode is set to "AUTOMATIC". The input value is in the ISO8601 times format. If the value is not specified, "23:59" will be set as default value. This value cannot be less than monitoringPeriodStart value. This value is only available for storage systems with an SVP.
newPageAssignment	No	Integer	The percentage of buffer space of a tier assigned to new pages. This value must be between 0 and 50.
tierRelocation	No	Integer	The percentage of buffer space of a tier assigned for relocation. This value must be between 2 and 40. If not specified 2 (%) will be used as a default value for each tier.
relocationSpeed	No	String	Relocation speed for a tiered pool. If not specified STANDARD is used as a default value. Possible values are SLOWEST, SLOWER, STANDARD, FASTER or FASTEST. This value is only available for storage systems with an SVP.
suspendSnapshot	No	Boolean	Whether the usedCapacity of the pool is greater than utilizationThreshold2. If TRUE, the snapshots inside the pool are suspended. Their status is PSUE and the S-VOL will never accept read/write operations. If FALSE, you can write to the snapshot. Thin Image Advanced that uses DRS-VOLs does not support this parameter. If the threshold is exceeded while this option is TRUE, the Thin Image Advanced pair that uses DRS-VOLs does not change to PSUE. Set to TRUE by default.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.

Status code	HTTP name	Description
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
404	Not found	The specified storage system ID is not valid or the storage system does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

## Volume management resources

Request	Method	URI	Role
<a href="#">Listing volumes (on page 210)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /volumes	Storage administrator

Request	Method	URI	Role
			System administrator Security administrator Monitoring
<a href="#">Getting a volume (on page 226)</a>	GET	<i>/v1/storage-systems/ storageSystemId/volumes/ volumeId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a volumes summary (on page 239)</a>	GET	<i>/v1/storage-systems/ storageSystemId/volumes/ summary</i>	Storage administrator System administrator Security administrator Monitoring



The following requests can be used when you want to create, update, delete, or attach volumes in a pool in the storage system.

Request	Method	URI	Role
<a href="#">Creating a volume (on page 241)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /volumes	Storage administrator
<a href="#">Updating a volume (on page 247)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /volumes/ <i>volumeId</i>	Storage administrator
<a href="#">Deleting a volume (on page 251)</a>	DELETE	/v1/storage-systems/ <i>storageSystemId</i> /volumes/ <i>volumeId</i>	Storage administrator
<a href="#">Deleting volumes (on page 255)</a>	POST	/v1/volume-manager/delete	Storage administrator
<a href="#">Detaching volumes (on page 259)</a>	POST	/v1/volume-manager/detach	Storage administrator
<a href="#">Editing volume LUN paths (on page 307)</a>	POST	/v1/volume-manager/edit-lun-paths	Storage administrator
<a href="#">Editing namespace paths (on page 313)</a>	POST	/v1/volume-manager/edit-namespace-paths	System administrator Storage administrator
<a href="#">Getting auto-selection paths (on page 317)</a>	GET	/v1/volume-manager/auto-path-select	Storage administrator System administrator Security administrator Monitoring
<a href="#">Shredding volumes (on page 320)</a>	POST	/v1/volume-manager/shred	Storage administrator
<a href="#">Interrupting volume shredding (on page 324)</a>	POST	/v1/volume-manager/shred/ interrupt	Storage administrator

The following requests can be used when you want to make bulk volume management requests:

Request	Method	URI	Role
<a href="#">Creating multiple volumes (on page 263)</a>	POST	/v1/volume-manager/create	Storage administrator
<a href="#">Attaching volumes (on page 269)</a>	POST	/v1/volume-manager/attach	Storage administrator
<a href="#">Attaching and protecting volumes (on page 278)</a>	POST	/v1/volume-manager/attach-protect	Storage administrator
<a href="#">Creating, attaching, and protecting volumes (on page 285)</a>	POST	/v1/volume-manager/create-attach-protect	Storage administrator
<a href="#">Updating volumes (on page 298)</a>	POST	/v1/volume-manager/update	Storage Administrator
<a href="#">Detaching volumes from multiple servers (on page 303)</a>	POST	/v1/volume-manager/detach-from-multiple-servers	Storage administrator

## Listing volumes

You can display a list of all volumes in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volumes
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable

### Response structure

The response body structure is as shown:

```
{
  "resources": [
    {
      "volumeId": ,
      "storageSystemId": "",
      "storageSystemName": "",
      "resourceGroupId": ,
      "resourceGroupName": "",
      "poolId": "",

```

```

    "poolName": "",
    "label": "",
    "size": ,
    "usedCapacity": ,
    "availableCapacity": ,
    "utilization": ,
    "attributes": [""],
    "status": "",
    "type": "",
    "provisioningStatus": "",
    "portIds": [""],
    "hostGroupNames": [""],
    "luns": [],
    "numberOfLunPaths": ,
    "attachedVolumeServerSummary": [
      {
        "serverId": ,
        "serverName": "",
        "paths": [
          {
            "storagePortId": "",
            "storageSystemId": "",
            "lun": ,
            "hostGroupId": "",
            "name": "",
            "hostMode": "",
            "wwns": [""],
            "hostModeOptions": [""],
            "iscsiTargetInformation": {},
            "preferredPath":
          },
          ...
        ],
        "namespacePath": {
          "storageSystemId": "",
          "nvmSubsystemId": ,
          "namespaceId": ,
          "storagePortIds": [
            "",
            ...
          ],
          "hostNqns": [
            {
              "hostNqn": ""
            },
            ...
          ]
        }
      },
      ...
    ],

```

```

"dataProtectionSummary": {
  "replicationType": [""],
  "volumeType": [""],
  "replicationGroupIdMap": {},
  "hasFailures": ,
  "secondaryVolumeCount": ,
  "secondaryVolumeFailures": ,
  "mirrors": [
    {
      "volumeType": "",
      "pairStatus": "",
      "journalId":
    }
  ]
},
"gadSummary": {
  "vsmId": "",
  "virtualLdevId": ,
  "volumeType": "",
  "pairStatus": "",
  "consistencyId":,
  "mirrors" : [
    {
      "mirrorId": ,
      "volumeType": "",
      "pairStatus": "",
      "consistencyId":
    },
    ...
  ]
},
"dkcDataSavingType": "",
"virtualStorageMachineInformation": {
  "virtualStorageMachineId": "",
  "storageSystemId": "",
  "model": "",
  "virtualVolumeId":
},
"migrationSummary": {
  "ownerTaskId": ,
  "migrationType": ""
},
"aluaEnabled": ,
"tieringPolicy": {
  "id": ,
  "name": "",
  "userDefined":
},
"t10PiEnabled":,
"compressionAcceleration": ,
"commandDevice": {

```

```

    "securityEnabled": ,
    "userAuthenticationEnabled": ,
    "deviceGroupSettingEnabled":
  },
  "namespaceId": "",
  "nvmSubsystem": {
    "nvmSubsystemId": "",
    "name": ""
  }
},
...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
resourceGroupId	Integer	ID of the resource group.
resourceGroupName	String	Name of the resource group.
poolId	String	ID of the pool from which the resource is allocated.
poolName	String	Name of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage= (usedCapacity/size) *100.

Parameter	Type	Description
attributes	List	<p>List of the attributes of the volume. Valid values:</p> <ul style="list-style-type: none"> <li>▪ THIN: a volume for thin provisioning.</li> <li>▪ CMD: a volume used as a command device.</li> <li>▪ VVOL: a secondary volume for creating snapshots.</li> <li>▪ GUARD: a volume for Data Retention Utility.</li> <li>▪ MIGRATION_RESERVED: a volume for the data migration.</li> <li>▪ HA: a primary or secondary volume for High Availability.</li> <li>▪ HA_RESERVED: a reserved volume for High Availability.</li> <li>▪ NAS_TYPE_USER: a volume used as a user LU of the storage system includes NAS modules.</li> <li>▪ ALUA: a volume of which ALUA mode is enabled.</li> <li>▪ T10PI: a volume of which T10PI mode is enabled.</li> <li>▪ COMPRESSION: a volume of which compression is enabled.</li> <li>▪ DEDUPLICATION: a volume of which deduplication is enabled.</li> <li>▪ DRS: a volume of which DRS is enabled.</li> <li>▪ JOURNAL: a volume used as a journal.</li> </ul>
status	String	Volume status. Valid values: NORMAL, BLOCKED, BUSY, SHREDDING, UNKNOWN, or NONE.
type	String	Type of pool from which the volume is allocated. Valid values: THIN, TIERED, or SNAP.

Parameter	Type	Description
provisioningStatus	String	Provisioning status of a volume. Valid values: ATTACHED, UNATTACHED, or UNMANAGED.
portIds	List	List of the storage port IDs.
hostGroupNames	List	List of the host group names.
luns	List	List of the LUN IDs.
numberOfLunPaths	Integer	The number of paths from WWNs or iSCSI names to volumes (excluding paths where LUN security is disabled).
attachedVolumeServerSummary	List	Volume provisioning summary details.
serverId	Integer	ID of the server.
serverName	String	Name of the server.
paths	List	<p>Paths that exist on the volume.</p> <p>For the namespace, it represents host groups connecting between the HBA and the storage port which this namespace is visible on.</p> <p>If all ports included in <code>namespacePath</code> are LUN security OFF, this has empty list.</p> <p>Each object does not have lun.</p>
storagePortId	Long	ID of the storage port.
storageSystemId	String	ID of the storage system.
lun	Integer	ID of the LUN.
hostModeOptions	List of Integers	Host mode options for the volume.
name	String	Name of the resource.
hostMode	String	Host mode set for the volume.
wwns	List	List of WWNs of connected hosts. NULL for iSCSI path.
hostGroupId	Long	ID of the host group.
iscsiTargetInformation	Object	Displays iSCSI target information. NULL for FC host groups.

Parameter	Type	Description
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> <li>▪ ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
volumeType	Set	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
replicationGroupIdMap	Object	Replication group ID map. Consisting of the replication group ID and the replication group name for each of the replication group the volume belongs to.
hasFailures	Boolean	Whether the volume has replication failures.
secondaryVolumeCount	Integer	Count of secondary volume pairs protecting the primary volume.
secondaryVolumeFailures	Integer	Count of failed volume pairs where this volume is an S-VOL.
mirrors	Object	List of the volume pair attributes per mirror of the volume.
volumeType	String	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.



Parameter	Type	Description
pairStatus	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ SMPP: a volume pair with the clone attribute is being deleted.</li> <li>▪ PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
journalId	Integer	The ID of the journal. Set only if it is in replication group, otherwise null.
gadSummary	Object	List of the GAD attributes of the volume. If there is no GAD pair, a NULL value is returned.
vsmlId	String	ID number of the virtual storage machine (VSM).
virtualLdevID	String	ID number of the virtual volume.

Parameter	Type	Description
volumeType	String	Volume type. Valid values: Active-Primary, Active-Secondary  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>volumeType</code> parameter of the <code>mirrors</code> object instead.
pairStatus	String	The status of the given volume in the volume pair. Valid values: <ul style="list-style-type: none"><li>▪ PAIR: a volume is in paired status.</li><li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li><li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li><li>▪ COPY: a volume pair is in data synchronizing status.</li><li>▪ PSUE: a volume pair is in suspended status with error.</li><li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li><li>▪ UNKNOWN: a volume pair is in unknown status.</li><li>▪ NONE: a volume is not paired.</li></ul> <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>pairStatus</code> parameter of the <code>mirrors</code> object instead.
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>consistencyId</code> parameter of the <code>mirrors</code> object instead.
mirrors	Object	List of the GAD attributes per mirror of the volume.

Parameter	Type	Description
volumeType	String	Volume type. Valid values: ACTIVE_PRIMARY, ACTIVE_SECONDARY, NOT_AVAILABLE
pairStatus	String	The status of the given volume in the volume pair. Valid values: <ul style="list-style-type: none"> <li>PAIR: the volume is in paired status.</li> <li>PSUS: the volume pair is in suspended status for the primary volume.</li> <li>SSUS: the volume pair is in suspended status for the secondary volume.</li> <li>COPY: the volume pair is in data synchronizing status.</li> <li>PSUE: the volume pair is in suspended status with error.</li> <li>SSWS: the volume pair is in suspended status for swapping the secondary volume.</li> </ul>
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.  For storage systems without an SVP, a NULL value is returned.
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEDUPLICATION_AND_COMPRESSION, and NONE.
virtualStorageMachineInformation	Object	Displays the virtual storage machine information for the volume. A value of NULL is returned if there are no VSMs.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The serial number of the VSM to which the volume belongs.
model	String	The model of the VSM to which the volume belongs.

Parameter	Type	Description
virtualVolumeld	Long	The virtual volume ID. If the virtual volume is not defined, a value of NULL is returned.
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	Migration type. Valid values: <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
aluaEnabled	Boolean	Whether or not ALUA mode of the volume is enabled.
tieringPolicy	Object	Tiering policy information
id	Integer	Tier level between 0 and 31.
name	String	Name of the tier. This value is editable outside of Hitachi Ops Center Administrator for tier level 6 and higher.
userDefined	Boolean	True for tier levels 6 and higher. False, otherwise.
t10PiEnabled	Boolean	Whether or not T10PI mode of the volume is enabled.
compressionAcceleration	String	Whether the compression accelerator is enabled for the volume. Valid values: ENABLED, DISABLED, -
commandDevice	Object	Command device settings for the volume.  The value of this parameter is null in case of storage systems without SVP or not command device.
securityEnabled	Boolean	Whether or not the command device security setting is enabled.
userAuthenticationEnabled	Boolean	Whether or not user authentication for the command device is enabled.
deviceGroupSettingEnabled	Boolean	Whether or not device group information authentication for the command device is enabled.

Parameter	Type	Description
namespacePath	Object	Namespace path information.
storageSystemId	String	Storage system ID.
storagePortId	String	Storage Port ID.
nvmSubsystemId	Integer	NVM subsystem ID.
namespaceId	Integer	Namespace ID.
hostNqns	List	NQNs of the connected hosts.
hostNqn	String	NVMe Qualified Name of the host.
nvmSubsystem	Object	NVM subsystem information.
nvmSubsystemId	Integer	NVM subsystem ID.
name	String	NVM subsystem name.
namespaceId	Integer	Namespace ID.



**Note:** The API does not return the NAA ID of the volume.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://172.17.64.116/v1/storage-systems/41020/volumes
```

### Example response

```
{
  "resources": [
    // Not Namespace
    {
      "volumeId": 0,
      "storageSystemId": "41020",
      "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
      "resourceGroupId": 0,
      "resourceGroupName": "meta_resource",
      "poolId": "3",
      "poolName": "test-pool",
      "label": "test-aaa",
      "size": 2147483648,
      "usedCapacity": 0,
      "availableCapacity": 2147483648,
      "utilization": 0,
      "attributes": [
        "THIN"
      ],
      "status": "NORMAL",
      "type": "THIN",
      "provisioningStatus": "ATTACHED",
      "portIds": [
        "CL1-E",
        "CL3-F"
      ],
      "hostGroupNames": [
        "DocServer",
        "windows16"
      ],
      "luns": [
        1,
        2
      ],
      "numberOfLunPaths": 2,
      "attachedVolumeServerSummary": [
        {

```

```

    "serverId": null,
    "serverName": null,
    "paths": [
      {
        "storagePortId": "CL3-F",
        "storageSystemId": "41020",
        "lun": 1,
        "hostGroupId": "CL3-F-6",
        "name": "windows16",
        "hostMode": "WIN",
        "wwns": [
          "1000000533267214"
        ],
        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
      },
      ...
    ]
  },
  {
    "serverId": 2,
    "paths": [
      {
        "storagePortId": "CL1-E",
        "storageSystemId": "41020",
        "lun": 2,
        "hostGroupId": "CL1-E-12",
        "name": "DocServer",
        "hostMode": "SOLARIS",
        "wwns": [
          "5000000000000000"
        ],
        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
      },
      ...
    ]
  },
  ...
],
"gadSummary": {
  "vsmId": "7",
  "virtualLdevId": "2657",
  "volumeType": "ACTIVE_PRIMARY",
  "pairStatus": "PAIR",
  "consistencyId": 15,
  "mirrors" : [
    {
      "mirrorId": 0,

```

```

        "volumeType": "ACTIVE_SECONDARY",
        "pairStatus": "PAIR",
        "consistencyId": 15
    },
    {
        "mirrorId": 1,
        "volumeType": "ACTIVE_PRIMARY",
        "pairStatus": "COPY",
        "consistencyId": 17
    },
    ...
],
},
"virtualStorageMachineInformation": {
    "virtualStorageMachineId": "41503-VSPF700",
    "storageSystemId": "41010",
    "model": "VSP F700",
    "virtualVolumeId": 0
},
"compressionAcceleration": "ENABLED",
"commandDevice": {
    "securityEnabled": true,
    "userAuthenticationEnabled": false,
    "deviceGroupSettingEnabled": false
}
},
// Namespace
{
    "volumeId": 11016,
    "storageSystemId": "41020",
    "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
    "poolId": "24",
    "poolName": "example-nvme-test",
    "label": "example-nvme-test3",
    "size": 1073741824,
    "usedCapacity": 0,
    "availableCapacity": 1073741824,
    "utilization": 0,
    "attributes": [
        "THIN"
    ],
    "status": "NORMAL",
    "type": "TIERED",
    "provisioningStatus": "ATTACHED",
    "portIds": [],
    "hostGroupNames": [],
    "luns": [],
    "numberOfLunPaths": 0,
    "dataProtectionSummary": {
        "replicationType": [],
        "volumeType": [

```



```

    "UNPROTECTED"
  ],
  "replicationGroupIdMap": {},
  "hasFailures": false,
  "secondaryVolumeCount": 0,
  "secondaryVolumeFailures": 0,
  "mirrors": []
},
"gadSummary": {
  "vsmId": null,
  "virtualLdevId": null,
  "volumeType": "NOT_AVAILABLE",
  "pairStatus": "NONE",
  "consistencyId": null,
  "mirrors": []
},
"dkcDataSavingType": "NONE",
"virtualStorageMachineInformation": {
  "virtualStorageMachineId": "39342-VSP5200-5600",
  "storageSystemId": "39342",
  "model": "VSP 5200, 5600",
  "virtualVolumeId": 11016
},
"resourceGroupId": 0,
"resourceGroupName": "meta_resource",
"migrationSummary": {
  "ownerTaskId": null,
  "migrationType": "NONE"
},
"aluaEnabled": false,
"tieringPolicy": {
  "id": 0,
  "name": "All",
  "userDefined": false
},
"t10PiEnabled": false,
"compressionAcceleration": "-",
"commandDevice": null,
"attachedVolumeServerSummary": [
  {
    "serverId": 1,
    "serverName": "fcNVMeServer001",
    "paths": [],
    "namespacePath": {
      "storageSystemId": "41020",
      "nvmSubsystemId": 1,
      "namespaceId": 3,
      "storagePortIds": [
        "CL3-C"
      ],
      "hostNqns": [

```

```

        {
            "hostNqn": "nqn.1234.abcd"
        }
    ]
}
},
"namespaceId": 3,
"nvmSubsystem": {
    "nvmSubsystemId": 1,
    "name": "nvmSubsystem01"
}
},
...
],
"total": ,
"nextToken": ""
}

```

## Getting a volume

You can display the detailed information for a specific volume in the storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId
```

Use the storage system ID as the *storageSystemId*.

Use the volume ID as the *volumeId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
    "volumeId": ,
    "storageSystemId": "",
    "storageSystemName": "",
    "resourceGroupId": ,
    "resourceGroupName": "",
    "poolId": "",
    "poolName": "",
    "label": "",
    "size": ,
    "usedCapacity": ,
    "availableCapacity": ,

```

```

"utilization": ,
"attributes": [""],
"status": "",
"type": "",
"provisioningStatus": "",
"portIds": [""],
"hostGroupNames": [""],
"luns": [],
"numberOfLunPaths": ,
"attachedVolumeServerSummary": [
  {
    "serverId": ,
    "serverName": "",
    "paths": [
      {
        "storagePortId": "",
        "storageSystemId": "",
        "lun": ,
        "hostGroupId": "",
        "name": "",
        "hostMode": "",
        "wwns": [""],
        "hostModeOptions": [""],
        "iscsiTargetInformation": {},
        "preferredPath":
      },
      ...
    ],
    "namespacePath": {
      "storageSystemId": "",
      "nvmSubsystemId": ,
      "namespaceId": ,
      "storagePortIds": [
        "",
        ...
      ],
      "hostNqns": [
        {
          "hostNqn": ""
        },
        ...
      ],
    }
  },
  ...
],
"dataProtectionSummary": {
  "replicationType": [""],
  "volumeType": [""],
  "replicationGroupIdMap": {},
  "hasFailures": ,

```

```

    "secondaryVolumeCount": ,
    "secondaryVolumeFailures": ,
    "mirrors": [
      {
        "volumeType": "",
        "pairStatus": "",
        "journalId":
      }
    ]
  },
  "gadSummary": {
    "vsmId": "",
    "virtualLdevId": ,
    "volumeType": "",
    "pairStatus": "",
    "consistencyId":,
    "mirrors" : [
      {
        "mirrorId": ,
        "volumeType": "",
        "pairStatus": "",
        "consistencyId":
      },
      ...
    ]
  },
  "dkcDataSavingType": "",
  "virtualStorageMachineInformation": {
    "virtualStorageMachineId": "",
    "storageSystemId": "",
    "model": "",
    "virtualVolumeId": ,
  },
  "migrationSummary": {
    "ownerTaskId": ,
    "migrationType": ""
  },
  "aluaEnabled": ,
  "tieringPolicy": {
    "id": ,
    "name": "",
    "userDefined":
  },
  "tl0PiEnabled":,
  "compressionAcceleration": ,
  "commandDevice": {
    "securityEnabled": ,
    "userAuthenticationEnabled": ,
    "deviceGroupSettingEnabled":
  },
  "namespaceId": "",

```

```

"nvmSubsystem": {
  "nvmSubsystemId": "",
  "name": ""
}
}

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
resourceGroupId	Integer	ID of the resource group.
resourceGroupName	String	Name of the resource group.
poolId	String	ID of the pool from which the resource is allocated.
poolName	String	Name of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage= (usedCapacity/size) *100.
attributes	List	List of the attributes of the volume. Valid values: <ul style="list-style-type: none"> <li>▪ THIN: a volume for thin provisioning.</li> <li>▪ CMD: a volume used as a command device.</li> <li>▪ VVOL: a secondary volume for creating snapshots.</li> <li>▪ GUARD: a volume for Data Retention Utility.</li> <li>▪ MIGRATION_RESERVED: a volume for the data migration.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>HA: a primary or secondary volume for High Availability.</li> <li>HA_RESERVED: a reserved volume for High Availability.</li> <li>NAS_TYPE_USER: a volume used as a user LU of the storage system includes NAS modules.</li> <li>ALUA: a volume of which ALUA mode is enabled.</li> <li>T10PI: a volume of which T10PI mode is enabled.</li> <li>COMPRESSION: a volume of which compression is enabled.</li> <li>DEDUPLICATION: a volume of which deduplication is enabled.</li> <li>DRS: a volume of which DRS is enabled.</li> <li>JOURNAL: a volume used as a journal.</li> </ul>
status	String	Volume status. Valid values: NORMAL, BLOCKED, BUSY, SHREDDING, UNKNOWN, or NONE.
type	String	Type of pool from which the volume is allocated. Valid values: THIN, TIERED, or SNAP.
provisioningStatus	String	Provisioning status of a volume. Valid values: ATTACHED, UNATTACHED, or UNMANAGED.
portIds	List	List of the storage port IDs.
hostGroupNames	List	List of the host group names.
luns	List	List of the LUN IDs.
numberOfLunPaths	Integer	The number of paths from WWNs or iSCSI names to volumes (excluding paths where LUN security is disabled).
attachedVolumeServerSummary	List	Volume provisioning summary details.
serverId	Integer	ID of the server.

Parameter	Type	Description
serverName	String	Name of the server.
paths	List	<p>Paths that exist on the volume.</p> <p>For the namespace, it represents host groups connecting between the HBA and the storage port which this namespace is visible on.</p> <p>If all ports included in <code>namespacePath</code> are LUN security OFF, this has empty list.</p> <p>Each object does not have lun.</p>
storagePortId	Long	ID of the storage port.
storageSystemId	String	ID of the storage system.
lun	Integer	ID of the LUN.
hostModeOptions	List of Integers	Host mode options for the volume.
name	String	Name of the resource.
hostMode	String	Host mode set for the volume.
wwns	List	<p>List of WWNs of connected hosts.</p> <p>NULL for iSCSI path.</p>
hostGroupId	Long	ID of the host group.
iscsiTargetInformation	Object	<p>Displays iSCSI target information.</p> <p>NULL for FC host groups.</p>
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	<p>Volume replication type. Valid values:</p> <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
volumeType	Set	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
replicationGroupIdMap	Object	Replication group ID map. Consisting of the replication group ID and the replication group name for each of the replication group the volume belongs to.
hasFailures	Boolean	Whether the volume has replication failures.
secondaryVolumeCount	Integer	Count of secondary volume pairs protecting the primary volume.
secondaryVolumeFailures	Integer	Count of failed volume pairs where this volume is an S-VOL.
mirrors	Object	List of the volume pair attributes per mirror of the volume.
volumeType	String	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
pairStatus	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>SMPP: a volume pair with the clone attribute is being deleted.</li> <li>PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>COPY: a volume pair is in data synchronizing status.</li> <li>PSUE: a volume pair is in suspended status with error.</li> </ul>



Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
journalId	Integer	The ID of the journal. Set only if it is in replication group, otherwise null.
gadSummary	Object	List of the GAD attributes of the volume. If there is no GAD pair, a NULL value is returned.
vsmlId	String	ID number of the virtual storage machine (VSM).
virtualLdevID	String	ID number of the virtual volume.
volumeType	String	<p>Volume type. Valid values: Active-Primary, Active-Secondary</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>volumeType</code> parameter of the <code>mirrors</code> object instead.</p>
pairStatus	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>UNKNOWN: a volume pair is in unknown status.</li> <li>NONE: a volume is not paired.</li> </ul> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>pairStatus</code> parameter of the <code>mirrors</code> object instead.</p>
<code>consistencyId</code>	Integer	<p>The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>consistencyId</code> parameter of the <code>mirrors</code> object instead.</p>
<code>mirrors</code>	Object	List of the GAD attributes per mirror of the volume.
<code>volumeType</code>	String	Volume type. Valid values: ACTIVE_PRIMARY, ACTIVE_SECONDARY, NOT_AVAILABLE
<code>pairStatus</code>	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: the volume is in paired status.</li> <li>PSUS: the volume pair is in suspended status for the primary volume.</li> <li>SSUS: the volume pair is in suspended status for the secondary volume.</li> <li>COPY: the volume pair is in data synchronizing status.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>PSUE: the volume pair is in suspended status with error.</li> <li>SSWS: the volume pair is in suspended status for swapping the secondary volume.</li> </ul>
consistencyId	Integer	<p>The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.</p> <p>For storage systems without an SVP, a NULL value is returned.</p>
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEDUPLICATION_AND_COMPRESSION, and NONE.
virtualStorageMachineInformation	Object	Displays the virtual storage machine information for the volume. A value of NULL is returned if there are no VSMs.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The serial number of the VSM to which the volume belongs.
model	String	The model of the VSM to which the volume belongs.
virtualVolumeId	Long	The virtual volume ID. If the virtual volume is not defined, a value of NULL is returned.
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	<p>Migration type. Valid values:</p> <ul style="list-style-type: none"> <li>MIGRATION</li> <li>NONE</li> </ul>
aluaEnabled	Boolean	Whether ALUA mode of the volume is enabled.
tieringPolicy	Object	Tiering policy information
id	Integer	Tier level between 0 and 31.

Parameter	Type	Description
name	String	Name of the tier. This value is editable outside of Hitachi Ops Center Administrator for tier level 6 and higher.
userDefined	Boolean	True for tier levels 6 and higher. False, otherwise.
t10PiEnabled	Boolean	Whether T10PI mode of the volume is enabled.
compressionAcceleration	String	Whether the compression accelerator is enabled for the volume.  Valid values: ENABLED, DISABLED, -
commandDevice	Object	Command device settings for the volume.  The value of this parameter is null in case of storage systems without SVP or not command device.
securityEnabled	Boolean	Whether or not the command device security setting is enabled.
userAuthenticationEnabled	Boolean	Whether or not user authentication for the command device is enabled.
deviceGroupSettingEnabled	Boolean	Whether or not device group information authentication for the command device is enabled.
namespacePath	Object	Namespace path information.
storageSystemId	String	Storage system ID.
storagePortId	String	Storage Port ID.
nvmSubsystemId	Integer	NVM subsystem ID.
namespaceId	Integer	Namespace ID.
hostNqns	List	NQNs of the connected hosts.
hostNqn	String	NVMe Qualified Name of the host.
nvmSubsystem	Object	NVM subsystem information.
nvmSubsystemId	Integer	NVM subsystem ID.
name	String	NVM subsystem name.
namespaceId	Integer	Namespace ID.



**Note:** The API does not return the NAA ID of the volume.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/storage-systems/41020/volumes/68
```

### Example response

```
{
  "volumeId": 11016,
  "storageSystemId": "41020",
  "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
  "poolId": "24",
  "poolName": "example-nvme-test",
  "label": "example-nvme-test3",
}
```

```

"size": 1073741824,
"usedCapacity": 0,
"availableCapacity": 1073741824,
"utilization": 0,
"attributes": [
  "THIN"
],
"status": "NORMAL",
"type": "TIERED",
"provisioningStatus": "ATTACHED",
"portIds": [],
"hostGroupNames": [],
"luns": [],
"numberOfLunPaths": 0,
"dataProtectionSummary": {
  "replicationType": [],
  "volumeType": [
    "UNPROTECTED"
  ],
  "replicationGroupIdMap": {},
  "hasFailures": false,
  "secondaryVolumeCount": 0,
  "secondaryVolumeFailures": 0,
  "mirrors": []
},
"gadSummary": {
  "vsmId": null,
  "virtualLdevId": null,
  "volumeType": "NOT_AVAILABLE",
  "pairStatus": "NONE",
  "consistencyId": null,
  "mirrors": []
},
"dkcDataSavingType": "NONE",
"virtualStorageMachineInformation": {
  "virtualStorageMachineId": "39342-VSP5200-5600",
  "storageSystemId": "39342",
  "model": "VSP 5200, 5600",
  "virtualVolumeId": 11016
},
"resourceGroupId": 0,
"resourceGroupName": "meta_resource",
"migrationSummary": {
  "ownerTaskId": null,
  "migrationType": "NONE"
},
"aluaEnabled": false,
"tieringPolicy": {
  "id": 0,
  "name": "All",
  "userDefined": false
}

```

```

    },
    "t10PiEnabled": false,
    "compressionAcceleration": "-",
    "commandDevice": null,
    "attachedVolumeServerSummary": [
      {
        "serverId": 1,
        "serverName": "fcNVMeServer001",
        "paths": [],
        "namespacePath": {
          "storageSystemId": "41020",
          "nvmSubsystemId": 1,
          "namespaceId": 3,
          "storagePortIds": [
            "CL3-C"
          ],
          "hostNqns": [
            {
              "hostNqn": "nqn.1234.abcd"
            }
          ]
        }
      }
    ],
    "namespaceId": 3,
    "nvmSubsystem": {
      "nvmSubsystemId": 1,
      "name": "nvmSubsystem01"
    }
  }
}

```

## Getting a volumes summary

You can display a list of volumes with pool types attached to the volumes.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volumes/summary
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "volumeCountByType":

```

```
{
  "THIN":
  "TIERED":
  "SNAP":
},
"numberOfVolumes":
}
```

Parameter	Type	Description
volumeCountByType	List	List of pool types where the volume is attached.
numberOfVolumes	Integer	Total number of volumes.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/storage-systems/410209/volumes/summary
```

### Example response

```
{
  "volumeCountByType":
  {
    "TIERED": 1,
```



```

    "THIN": 6
  },
  "numberOfVolumes": 7
}

```

## Creating a volume

You can create a volume on a given pool.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/volumes
```

Use the storage system ID where the volume is to be created as the *storageSystemId*.

### Request structure

The request body structure is as follows:

```

{
  "capacityInBytes": "",
  "poolId": "",
  "dkcDataSavingType": "",
  "label": "",
  "virtualStorageMachineId": "",
  "tieringPolicyId": ,
  "commandDevice": {
    "commandDeviceEnabled": ,
    "securityEnabled": ,
    "userAuthenticationEnabled": ,
    "deviceGroupSettingEnabled":
  },
  "drsEnabled":,
  "t10PiEnabled":
}

```

Parameter	Required	Type	Description
capacityInBytes	Yes	Long	The size of the volume to be created.
poolId	Yes	String	ID of the storage pool.

Parameter	Required	Type	Description
dkcDataSavingType	No	String	Type of controller-based capacity saving. Valid values are COMPRESSION and DEDUPLICATION_AND_COMPRESSION. The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression. COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools.  NONE cannot be specified for VSP One Block.
label	No	String	Description of the volume up to 32 characters.
virtualStorageMachineId	No	String	Specifies the virtual storage machine where the volume is created. If you don't specify this, the volume is created from the default VSM.
tieringPolicyId	No	Integer	A number between 0 and 31 that specifies the tier level.
commandDevice	No	Object	Command device settings for the volume.
commandDeviceEnabled	No	Boolean	Whether to configure the volume as a command device.
securityEnabled	No	Boolean	Whether to enable the command device security setting. If commandDeviceEnabled is true and this value is omitted, false is assumed.
userAuthenticationEnabled	No	Boolean	Whether to enable user authentication for the command device. If commandDeviceEnabled is true and this value is omitted, true is assumed.
deviceGroupSettingEnabled	No	Boolean	Whether to enable device group information authentication for the command device. If commandDeviceEnabled is true and this value is omitted, false is assumed.
drsEnabled	No	Boolean	Whether or not DRS setting of the volume is enabled.

Parameter	Required	Type	Description
t10PiEnabled	No	Boolean	Whether to enable T10PI for the volume. If this value is omitted, false is assumed.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.

Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "capacityInBytes": "5368709120",
  "poolId": "0",
  "dkcDataSavingType": "DEDUPLICATION_AND_COMPRESSION",
  "label": "test-volume-MD",
  "virtualStorageMachineId": "456789-VSPF800andVSPG800",
  "tieringPolicyId": 5,
  "commandDevice": {
    "commandDeviceEnabled": true,
```

```

    "securityEnabled": true,
    "userAuthenticationEnabled": false,
    "deviceGroupSettingEnabled": false
  },
  "drsEnabled": false,
  "t10PiEnabled": false
}

```

### Example request

```
https://172.17.64.111/v1/storage-systems/410209/volumes
```

### Example response

```

{
  "jobId": "1f201bfe-a49b-4269-84b7-dc53c38f5bf6",
  "title":
  {
    "text": "Create volume",
    "messageCode": "CreateVolumeJobTitleMessage",
    "parameters":
    {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1456964712680,
  "endDate": null,
  "parentJobId": null,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/1f201bfe-a49b-4269-84b7-dc53c38f5bf6"
    }
  ],
  "tags":
  [
  ],
  "isSystem": false
}

```

## Updating a volume

You can rename or expand a volume on a storage system. If a volume is a part of a replication group it cannot be deleted. For VSP G1000, VSP G1500, and VSP F1500, a volume can be updated to be part of a replication group, regardless. You can also update the ALUA mode settings for the volume.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId
```

Use the storage system ID where the volume is to be updated as the *storageSystemId*.

### Request structure

The request body structure is as follows:

```
{
  "capacityInBytes": "",
  "label": "",
  "dkcDataSavingType": "",
  "aluaEnabled": ,
  "tieringPolicyId": ,
  "commandDevice": {
    "commandDeviceEnabled": ,
    "securityEnabled": ,
    "userAuthenticationEnabled": ,
    "deviceGroupSettingEnabled":
  }
}
```

Parameter	Required	Type	Description
capacityInBytes	No	Long	Expanded size of the volume. You can specify a size that is greater than or equal to the current size.
label	No	String	Description of the volume up to 32 characters.  For a namespace, the namespace name is also set with the same value. If the value contains characters that cannot be used in a namespace name, the namespace name will be set with those characters replaced by underscores (_).

Parameter	Required	Type	Description
dkcDataSavingType	No	String	Type of controller-based capacity saving. Valid values are NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION. The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression. COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools. NONE disables current capacity saving settings. NONE cannot be specified for VSP One Block.
aluaEnabled	No	Boolean	Describes whether ALUA mode of the volume is enabled.
tieringPolicyId	No	Integer	A number between 0 and 31 that specifies the tier level.
commandDevice	No	Object	Command device settings for the volume.
commandDeviceEnabled	No	Boolean	Whether to configure the volume as a command device. Specify true also in case of updating the security settings only.
securityEnabled	No	Boolean	Whether to enable the command device security setting. If commandDeviceEnabled is true and this value is omitted, false is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.
userAuthenticationEnabled	No	Boolean	Whether to enable user authentication for the command device. If commandDeviceEnabled is true and this value is omitted, true is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.



Parameter	Required	Type	Description
deviceGroupSettingEnabled	No	Boolean	Whether to enable device group information authentication for the command device. If commandDeviceEnabled is true and this value is omitted, false is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

The request with JSON command:

```
https://172.17.64.111/v1/storage-systems/410209/volumes/volumeId
```

```
{
  "capacityInBytes": "5368709120",
  "label": "test-volume-MD",
  "dkcDataSavingType": "DEDUPLICATION_AND_COMPRESSION",
  "tieringPolicyId": 5,
  "commandDevice": {
    "commandDeviceEnabled": true,
    "securityEnabled": true,
    "userAuthenticationEnabled": false,
    "deviceGroupSettingEnabled": false
  }
}
```

**Deleting a volume**

You can delete a volume from a specified storage system.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId
```

Use the storage system ID where the volume is to be deleted as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

The request with JSON command:

```
https://172.17.64.111/v1/storage-systems/410209/volumes/17
```

**Example response**

```
{
  "jobId": "fa9e6498-a578-43ab-a870-7a47cf7f821e",
  "title":
  {
    "text": "Delete volume",
    "messageCode": "DeleteVolumeJobTitleMessage",
    "parameters":
    {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1456966858017,
  "endDate": null,
}
```

```

    "parentJobId": null,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/fa9e6498-a578-43ab-a870-7a47cf7f821e"
        }
    ],
    "tags":
    [
    ],
    "isSystem": false
}

```

## Deleting volumes

You can delete multiple volumes from a specified storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/delete
```

Use the storage system ID where the volumes are to be deleted as the *storageSystemId*.

### Request structure

```

{
  "volumeIds": [],
  "storageSystemId": ""
}

```

Parameter	Required	Type	Description
volumeIds	Yes	List	List of the volume IDs to be deleted. The volume ID type is long.
storageSystemId	Yes	String	The ID of the storage system.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":

```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).



Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Job status. Valid values are: <ul style="list-style-type: none"> <li>IN_PROGRESS</li> <li>SUCCESS</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>SUCCESS_WITH_ERRORS</li> <li>FAILED</li> </ul>
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets it to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example

```
{
  "jobId": "ad4203ba-67a0-4785-8bb1-8383ce7501dc",
  "title": {
    "text": "Delete volumes",
    "messageCode": "DeleteVolumeJobTitleMessage",
    "parameters": {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 20190723130000,
  "endDate": null,
  "parentJobId": null,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/ad4203ba-67a0-4785-8bb1-8383ce7501dc"
    }
  ],
  "tags": [
  ],
  "isSystem": false
}
```

## Detaching volumes

You can detach volumes from a server.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/volume-manager/detach
```

**Request Structure**

```
{
  "volumeId": ,
  "volumeIds": [],
  "serverId": ,
  "storageSystemId": "",
  "removeConnection":
}
```

Parameter	Required	Type	Description
volumeId	No	Integer	ID of the volume to be detached. You must specify either <code>volumeId</code> or <code>volumeIds</code> , but not both.
volumeIds	No	List	The list of the volumes to be detached. The volume ID type is long. You must specify either <code>volumeId</code> or <code>volumeIds</code> , but not both.
serverId	Yes	Integer	The ID of the server from which the volume is to be detached.
storageSystemId	Yes	String	The ID of the storage system.
removeConnection	No	Boolean	Specify whether the zoning access to the server is removed.  FALSE if you specified NULL for the FC port.  Must be NULL for iSCSI port or the port whose operation mode is NVMe mode.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
  }
}
```

```

    {
    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.

Parameter	Type	Description
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.111/v1/volume-manager/detach
```

**Example request to detach a single volume**

```
{
  "volumeId": "99",
  "serverId": "1",
  "storageSystemId": "410209",
  "removeConnection": "true"
}
```

**Example request to detach multiple volumes**

```
{
  "volumeIds": [99, 100, 101],
  "serverId": "1",
  "storageSystemId": "410209",
  "removeConnection": "true"
}
```

## Creating multiple volumes

You can create different volumes, poolType, and tier on the storage system. If a pool ID is not specified, the least used pool for the given pool type is selected.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/volume-manager/create
```

## Request structure

The request body structure is as follows:

```
{
  "storageSystemId": "",
  "volumes": [{
    "poolType": "",
    "numberOfVolumes": ,
    "label": "",
    "suffix": ,
    "capacity": "",
    "poolId": ,
    "dkcDataSavingType": "",
    "tieringPolicyId": ,
    "commandDevice": {
      "commandDeviceEnabled": ,
      "securityEnabled": ,
      "userAuthenticationEnabled": ,
      "deviceGroupSettingEnabled":
    },
    "drsEnabled": ,
    "t10PiEnabled": ,
    "idRange": {
      "from": ,
      "to":
    }
  }
],
  "virtualStorageMachineId": ""
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	String	Storage system ID.
poolType	Yes	String	The pool type can be TIERED or the name of a tier that is available in the system.
numberOfVolumes	Yes	Integer	Number of volumes. Must be greater than zero.
label	No	String	Name of the volume.
suffix	No	Integer	Suffix number appended to the end of the volume name.
capacity	Yes	Long	The size of the volume to be created.



Parameter	Required	Type	Description
poolId	No	String	ID of the storage pool. If poolId is not specified, then the least used pool of the specified type is selected.
dkcDataSavingType	No	String	Type of controller-based capacity saving. Valid values are COMPRESSION and DEDUPLICATION_AND_COMPRESSION. The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression. COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools.  NONE cannot be specified for VSP One Block.
virtualStorageMachineId	No	String	Specifies the virtual storage machine where the volumes are created. If you don't specify this, the volumes are created from the default VSM.
tieringPolicyId	No	Integer	A number between 0 and 31 that specifies the tier level.
idRange	No	Object	An ID range for creating volumes.
from	No	Integer	Starting volume ID of the range (in decimal).
to	No	Integer	Ending volume ID for the range (in decimal)
commandDevice	No	Object	Command device settings for the volume.
commandDeviceEnabled	No	Boolean	Whether to configure the volume as a command device.
securityEnabled	No	Boolean	Whether to enable the command device security setting. If commandDeviceEnabled is true and this value is omitted, false is assumed.
userAuthenticationEnabled	No	Boolean	Whether to enable user authentication for the command device. If commandDeviceEnabled is true and this value is omitted, true is assumed.

Parameter	Required	Type	Description
deviceGroupSettingEnabled	No	Boolean	Whether to enable device group information authentication for the command device. If commandDeviceEnabled is true and this value is omitted, false is assumed.
drsEnabled	No	Boolean	Whether or not DRS setting of the volume is enabled.
t10PiEnabled	No	Boolean	Whether to enable T10PI for the volume. If this value is omitted, false is assumed.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
}
```

```
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "storageSystemId": "410209",
  "volumes": [
    {
      "poolType": "TIERED",
      "numberOfVolumes": 1,
      "label": "Test",
      "suffix": 0,
      "capacity": "1073741824",
      "poolId": 0,
      "dkcDataSavingType": null,
      "drsEnabled": false,
      "t10PiEnabled": false,
      "idRange": {
        "from": 500,
        "to": 1000
      },
      "tieringPolicyId": 2,
      "commandDevice": {
```

```

        "commandDeviceEnabled": true,
        "securityEnabled": true,
        "userAuthenticationEnabled": false,
        "deviceGroupSettingEnabled": false
    }
}
],
"virtualStorageMachineId": "456789-VSPF800andVSPG800"
}

```

### Example request

```
https://172.17.64.118/v1/volume-manager/create
```

### Example response

```

{
  "jobId": "9759454d-1c97-4d9a-9528-152855406af2",
  "title": {
    "text": "Create volumes from template",
    "messageCode": "CreateVolumesFromTemplateJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1456776122736,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/9759454d-1c97-4d9a-9528-152855406af2"
    }
  ],
  "tags": [],
  "isSystem": false
}

```

## Attaching volumes

You can attach one or more volumes to servers registered in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/attach
```

## Request structure

The request body structure is as follows:

```
{
  "storageSystemId": "",
  "intendedImageType": "",
  "hostModeOptions": [
  ],
  "enableZoning": ,
  "enableLunUnification": ,
  "forceOverwriteChapSecret": ,
  "shareHgByAllServers": ,
  "hostGroupName": ,
  "volumes": [
    {
      "lun": ,
      "namespaceId": ,
      "volumeId": ,
      "virtualIdRange": {
        {
          "from": ,
          "to":
        }
      }
    },
    ...
  ],
  "ports": [
    {
      "serverId": ,
      "serverWwns": [""],
      "iscsiInitiatorNames": [""],
      "portIds": [""],
    },
    ...
  ],
  "nvmSubsystemName": "",
  "nvmServers": {
    "ids": []
  },
  "nvmSubsystemPortIds": [""],
  "nvmSubsystemHostMode": "",
  "nvmSubsystemHostModeOptions": [
  ]
}
```

Parameter	Required	Type	Description
storageSystemId	No	String	ID of the storage system.
intendedImageType	No	String	Host mode set for the volume.
hostModeOptions	No	List	Host mode options set for the volume. Default values are set automatically for a VMWARE_EX or WIN_EX server OS. The valid value is a host mode options number without any prefix, or null for auto select.
enableZoning	No	Boolean	Whether zones are created on the SAN fabric. If enableZoning is set to false, then zoning is disabled.  The default value is false.  This is valid only for FC servers and must be NULL for other protocol servers.
enableLunUnification	No	Boolean	Whether Lun (logical unit number) assignments for volumes that span multiple servers are consistent.
forceOverwriteChapSecret	No	Boolean	Whether Hitachi Ops Center Administrator overwrites the CHAP user secret when there is any port that exists with the same CHAP user name. The default value is FALSE.

Parameter	Required	Type	Description
shareHgByAllServers	No	Boolean	Whether to share host groups among servers. The default setting is False, which does not allow sharing. Specify True to share host groups among servers.
lun	No	Integer	Logical unit number. Enter a number from 0 to 2047.
volumeId	Yes	Long	ID of the volume.
virtualIdRange	No	Object	A range of a virtual volume IDs to use for the creating volume. If specified, the first usable value in the range is used. If not specified, do the same behavior as the conventional API.
from	No	Integer	Starting volume ID of the range (in decimal)
to	No	Integer	Ending volume ID of the range (in decimal)
ports	No	List	Information about the ports.
portIds	No	List	List of ports.
serverId	Yes	Integer	ID of the server.
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.



Parameter	Required	Type	Description
iscsiInitiatorNames	No	List	<p>The iSCSI names of the server to attach.</p> <p>If iscsiInitiatorNames is not specified, then all iSCSI names of the server are used to attach.</p> <p>You must specify either serverWwns or iscsiInitiatorNames but not both.</p>
hostGroupName	No	String	<p>The host group name value must be uppercase letters (A-Z), lowercase letters (a-z), numbers (0-9), commas (,), hyphens(-), periods (.), at marks (@), and underscores (_).</p> <p>String length is restricted to the following depending on port type:</p> <ul style="list-style-type: none"> <li>▪ Fiber: 60 when creating and 64 for editing.</li> <li>▪ iSCSI: 28 when creating.</li> </ul>
namespaceId	No	Integer	Namespace ID. If this attribute is omitted, a value is automatically set.
nvmSubsystemName	No	String	NVM subsystem name. If this attribute is omitted, a value is automatically set.
nvmServers	No	Object	NVMe over FC server Information.
ids	No	List	List of server IDs.

Parameter	Required	Type	Description
nvmSubsystemPortIds	No	List	List of the NVM subsystem port IDs.
nvmSubsystemHostMode	No	String	The host mode set for the NVM subsystem. For the specifiable values, see your storage system's Provisioning Guide.
nvmSubsystemHostModeOptions	No	List	The host mode option set for the NVM subsystem. For the specifiable values, see your storage system's Provisioning Guide.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
```

```

    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type not the existing type.
412	Precondition failed	User has not specified <code>forceOverwriteChapSecret</code> when the storage system has any host group with the same CHAP user name.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.118/v1/volume-manager/attach
```

```
// For FC Server
{
  "storageSystemId": "10054",
  "intendedImageType": "LINUX",
  "hostModeOptions": [
    54,
    63
  ],
  "enableZoning": false,
  "forceOverwriteChapSecret": false,
  "shareHgByAllServers": false,
  "volumes": [
    {
      "lun": 10,
      "volumeId": 495
    }
  ],
  "ports": [
    {
      "serverId": 1,
      "serverWwns": [
        "20000090FA34B747"
      ],
      "portIds": [
        "CL1-A"
      ]
    }
  ]
}

// For iSCSI Server
{
  "storageSystemId": "10054",
  "intendedImageType": "LINUX",
  "hostModeOptions": [
  ],
  "forceOverwriteChapSecret": false,
  "shareHgByAllServers": true,
  "volumes": [
    {
      "volumeId": 498
    },
    {
      "volumeId": 499
    }
  ],
}
```

```

"ports": [
  {
    "serverId": 2,
    "iscsiInitiatorNames": [
      "iqn.2017-11.com.example:Linux:array1"
    ],
    "portIds": [
      "CL1-C"
    ]
  },
  {
    "serverId": 5,
    "iscsiInitiatorNames": [
      "iqn.2017-11.com.example:Linux:array3",
      "iqn.2017-11.com.example:Linux:array4"
    ],
    "portIds": [
      "CL1-C"
    ]
  }
]
}

// For NVMe over FC Server
{
  "storageSystemId": "39342",
  "volumes": [
    {
      "volumeId": 492,
      "namespaceId": 1
    }
  ],
  "nvmSubsystemName": "FC-NVMe-Test",
  "nvmServers": {
    "ids": [
      3, 4
    ]
  },
  "nvmSubsystemPortIds": [
    "CL1-A", "CL2-B"
  ],
  "nvmSubsystemHostMode": "VMWARE",
  "nvmSubsystemHostModeOptions": [
    132, 133
  ]
}

```

## Attaching and protecting volumes

You can attach and protect volumes in Ops Center Administrator.

When creating a high availability replication group, note that there are differences in the specifications between a Remote replication group created with Ops Center Administrator prior to v11.0.3 and that created with v11.0.3 and later versions. For more information, see "Replication groups" in the *Hitachi Ops Center Administrator User Guide*.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/attach-protect
```

### Request structure

```
{
  "storageSystemId": "",
  "hostModeOptions": [],
  "intendedImageType": "",
  "ports": [{
    "serverId": ,
    "serverWwns": [""],
    "portIds": [""],
    "preferredPath":
  }],
  "enableZoning": ,
  "enableLunUnification": ,
  "aluaEnabled": ,
  "hostGroupName": ,
  "volumeIds": [],
  "replicationGroup": {
    "replicationType": "",
    "consistencyGroupNeeded": ,
    "replicationGroupName": "",
    "replicationGroupId": ,
    "secondaryStorageSystemId": "",
    "secondaryPoolId":,
    "quorumId":,
    "secondaryPorts": [
      {
        "serverId": ,
        "serverWwns": [""],
        "portIds": [""],
        "preferredPath":
      }
    ]
  }
}
```

Parameter	Required	Type	Description
storageSystemId	No	String	ID of the storage system.

Parameter	Required	Type	Description
hostModeOptions	No	Intended Image	Host mode options set for the volume.
intendedImageType	No	String	The server operating system. If an OS is not specified, then all the servers must have the same OS. Valid values: "HP_UX, SOLARIS, AIX, WIN, LINUX, TRU64, OVMS, NETWARE, HI_UX, VMWARE, VMWARE_EX, WIN_EX, UVM".
ports	No	List	Collection of ports.
enableZoning	No	Boolean	Whether zones are created on the SAN fabric. If enableZoning is set to FALSE, then zoning is disabled. The default value is FALSE. This is valid only for FC servers and must be NULL for iSCSI servers.
enableLunUnification	No	Boolean	<p>Whether forced LUN (logical unit number) assignments for paths of a volume that span multiple servers and/or between primary and secondary volumes of each high availability pair are consistent.</p> <p>If set to true, Ops Center Administrator is forced to use same LUN for all paths of the volume, and if the same LUN cannot be assigned, the operation will fail.</p> <p>If set to false, Ops Center Administrator attempts to use same LUN for all paths of the volume, and if the same LUN cannot be assigned, it uses available LUNs.</p> <p>The default value is true.</p>
aluaEnabled	No	Boolean	Whether ALUA mode of the volume is enabled.
volumelds	Yes	List	Collection of volume IDs. Volume must be attached to the server.
replicationGroup	Yes	Object	Replication group information.
serverId	Yes	Integer	ID of the server.



Parameter	Required	Type	Description
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.
portIds	No	List	Collection of ports.
preferredPath	No	Boolean	Whether the LU path (host group) is preferred or not.
replicationType	No	String	Type of replication technology to use. Must be HA.
consistencyGroup Needed	No	Boolean	Whether a consistency group is needed or not.
replicationGroupName	No	String	Name of the replication group. Enter up to 28 alphanumeric characters, hyphens, and underscores in the name, but must not start with a hyphen.
replicationGroupId	No	Long	ID of the replication group.
secondaryStorage SystemId	No	String	Specify an ID of the secondary storage system.
secondaryPoolId	No	String	Specify an ID of the pool of the secondary volume.
quorumId	No	Integer	Specify an ID of the quorum disk.
secondaryPorts	Yes	Object	Storage ports where the secondary volume is attached.
serverId	Yes	Integer	ID of the server.
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.
portIds	No	List	Storage ports where the volume is attached. If ports are not specified, it automatically selects an available port.
preferredPath	No	Boolean	Whether the LU path (host group) is preferred or not.
hostGroupName	No	String	The host group name value must be uppercase letters (A-Z), lowercase letters (a-z), numbers (0-9), commas (,), hyphens(-), periods (.), at marks (@), and underscores (_). String length is

Parameter	Required	Type	Description
			restricted to the following depending on port type: <ul style="list-style-type: none"> <li>▪ Fiber: 60 when creating and 64 for editing.</li> <li>▪ iSCSI: 28 when creating.</li> </ul>

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "storageSystemId": "410209",
  "aluaEnabled": true,
  "intendedImageType": "VMWARE_EX",
  "hostModeOptions": [
    54,
    63
  ],
  "enableZoning": false,
  "enableLunUnification": false,
  "ports": [
    {
      "serverId": 12,
      "serverWwns": [
```

```

        "4488336622442211"
    ],
    "portIds": [
        "CL8-E"
    ],
    "preferredPath": true
  }
],
"replicationGroup": {
  "replicationType": "HA",
  "consistencyGroupNeeded": false
  "replicationGroupName": "test-to-ha-repli-grp",
  "secondaryStorageSystemId": "411209",
  "secondaryPoolId": 4,
  "quorumId": 11,
  "secondaryPorts": [
    {
      "serverId": 12,
      "serverWwns": [
        "1122442266338844"
      ],
      "portIds": [
        "CL1-A"
      ],
      "preferredPath": false
    }
  ]
},
"volumeIds": [
  84,
  85
]
}

```

## Creating, attaching, and protecting volumes

You can create multiple volumes of different sizes, attach them to multiple servers, and configure data protection in a single process.

When creating a high availability replication group, note that there are differences in the specifications between a Remote replication group created with Ops Center Administrator prior to v11.0.3 and that created with v11.0.3 and later versions. For more information, see "Replication groups" in the *Hitachi Ops Center Administrator User Guide*.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/create-attach-protect
```

## Request Structure

The request body structure is as follows:

```
{
  "storageSystemId": "",
  "hostModeOptions": [],
  "intendedImageType": "",
  "ports": [
    {
      "serverId": ,
      "serverWwns": [""],
      "iscsiInitiatorNames": [""],
      "portIds": [""],
      "preferredPath":
    }
  ],
  ...
  "enableZoning": ,
  "enableLunUnification": ,
  "forceOverwriteChapSecret": ,
  "aluaEnabled": ,
  "shareHgByAllServers": ,
  "hostGroupName": "",
  "volumes": [
    {
      "poolType": "",
      "numberOfVolumes": ,
      "label": "",
      "suffix": ,
      "capacity": "",
      "poolId": "",
      "dkcDataSavingType": "",
      "drsEnabled": ,
      "tieringPolicyId": ,
      "commandDevice": {
        "commandDeviceEnabled":
      },
      "t10PiEnabled": ,
      "idRange": {
        "from": ,
        "to":
      },
      "virtualIdRange": {
        "from": ,
        "to":
      }
    }
  ],
  ...
  "skipProtection": ,
}
```

```

"replicationGroup": {
  "replicationType": "",
  "consistencyGroupNeeded": ,
  "replicationGroupName": "",
  "replicationGroupId": "",
  "schedule": {
    "recurringUnit": "",
    "minute": ,
    "hour": ,
    "recurringUnitInterval": ,
    "dayOfWeek": [""],
    "dayOfMonth":
  },
  "numberOfBackups": ,
  "targetPoolId": ,
  "secondaryStorageSystemId": "",
  "secondaryPoolId": ,
  "quorumId": ,
  "secondaryPorts": [
    {
      "serverId":,
      "serverWwns": [""],
      "portIds": [""],
      "preferredPath":,
    }
    ...
  ],
  "shareHgByAllServers": ,
  "secondaryVolumeLabel": "",
  "drsSetting": "",
  "capacitySavingSetting": "",
  "journal": {
    "primaryJournalPoolId": ,
    "secondaryJournalPoolId": ,
    "size": ,
    "unit": "",
    "journalLabel": "",
    "primaryJournalId": ,
    "secondaryJournalId": ,
  }
},
"virtualStorageMachineId": ,
"nvmSubsystemName": "",
"nvmServers": {
  "ids": []
},
"nvmSubsystemPortIds": [""],
"nvmSubsystemHostMode": "",
"nvmSubsystemHostModeOptions": []
}

```

Parameter	Required	Type	Description
storageSystemId	No	String	ID of the storage system.
hostModeOptions	No	List	Host mode options set for the volume. Default values are set automatically for a VMWARE_EX or WIN_EX server OS. The valid value is a host mode options number without any prefix, or null for auto select.
intendedImageType	No	String	The server operating system. If an OS is not specified, then all the servers must have the same OS. Valid values: "HP_UX,SOLARIS,AIX,WIN,LINUX,TRU64,OVMS,NETWARE,HI_UX,VMWARE,VMWARE_EX,WIN_EX,UVM".
ports	No	List	Collection of ports.
portId	No	String	ID of the port.
serverId	Yes	Integer	ID of the server.
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.
iscsiInitiatorNames	No	List	The iSCSI names of the server to attach.  If iscsiInitiatorNames is not specified, then all iSCSI names of the server are used to attach.  You must specify either serverWwns or iscsiInitiatorNames but not both.
forceOverwriteChapSecret	No	Boolean	Whether Hitachi Ops Center Administrator overwrites the CHAP user secret when there is any port that exists with the same CHAP user name. The default is FALSE.
aluaEnabled	No	Boolean	Whether ALUA mode of the volume is enabled.
shareHgByAllServers	No	Boolean	Whether to share host groups among servers. The default setting is False, which does not allow sharing. Specify True to share host groups among servers.
portIds	No	String	Storage ports where the volume is attached. If ports are not specified, it automatically selects an available port.



Parameter	Required	Type	Description
preferredPath	No	Boolean	Whether the LU path (Host Group) is preferred or not.
enableZoning	No	Boolean	Whether zones are created on the SAN fabric. If enableZoning is set to false, then zoning is disabled.  The default value is false.  This is valid only for FC servers and must be NULL for other protocol servers.
enableLunUnification	No	Boolean	Whether forced LUN (logical unit number) assignments for paths of a volume that span multiple servers and/or between primary and secondary volumes of each high availability pair are consistent.  If set to true, Ops Center Administrator is forced to use same LUN for all paths of the volume, and if the same LUN cannot be assigned, the operation will fail.  If set to false, Ops Center Administrator attempts to use same LUN for all paths of the volume, and if the same LUN cannot be assigned, it uses available LUNs.  The default value is true.
volumes	No	List	Collection of volume items.
poolType	Yes	String	The pool type can be TIERED or the name of a tier that is available in the system.
numberOfVolumes	Yes	Integer	Number of volumes. Must be greater than zero.
label	No	String	Name of the volume.
suffix	No	Integer	Suffix number appended to the end of the volume name.
capacity	Yes	String	Capacity of the resource, in bytes.
poolId	No	String	ID of the storage pool.

Parameter	Required	Type	Description
dkcDataSavingType	No	String	Type of controller-based capacity saving. Valid values are COMPRESSION and DEDUPLICATION_AND_COMPRESSION. The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression. COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools. NONE cannot be specified for VSP One Block.
skipProtection	Yes	Boolean	Whether to skip data protection. When skipProtection is true, all listed replication parameters are ignored.
replicationGroup	No	Object	Replication group information.
replicationType	No	String	Type of replication technology to use, such as SNAP, SNAP_ON_SNAP, CLONE, HA or ASYNC_REMOTE_CLONE.
consistencyGroupNeeded	No	Boolean	Whether a consistency group is needed or not.
replicationGroupName	No	String	Name of the replication group. Enter up to 28 alphanumeric characters, hyphens, and underscores in the name, but it must not start with a hyphen.
replicationGroupId	No	Long	ID of the replication group.
schedule	Yes	Object	Required if type is SNAP or SNAP_ON_SNAP. Interval at which the snapshots are taken, such as: <ul style="list-style-type: none"> <li>hour; Integer, valid values: 0-23</li> <li>minute; Integer, valid values: 0-59</li> <li>recurringUnit; String, ('HOURLY', 'DAILY', 'WEEKLY', 'MONTHLY')</li> <li>recurringUnitInterval; Integer, (null, or any positive integer)</li> </ul>

Parameter	Required	Type	Description
			<ul style="list-style-type: none"> <li>dayOfWeek; String[ ], (null, or 'SUN', 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT')</li> <li>dayOfMonth; Integer, (null, or 1-31)</li> </ul> <p>Note:</p> <ul style="list-style-type: none"> <li>Minute is required if HOURLY is chosen.</li> <li>Hour and minute are required if DAILY is chosen</li> <li>recurringUnitInterval is only applicable if HOURLY is chosen</li> <li>dayOfWeek is only applicable if WEEKLY is chosen</li> <li>dayOfMonth is only applicable if MONTHLY is chosen</li> </ul>
numberOfBackups	No	Integer	Number of backup copies that need to be created.
targetPoolId	No	Integer	If the user specifies <code>poolId</code> , the snapshot is taken from the specified pool. Do not specify this parameter when you select a DRS-VOL as the primary volume. Ops Center Administrator automatically selects the same pool to which the P-VOL belongs.
secondaryStorageSystemId	No	String	Specifies the ID of the secondary storage system.
secondaryPoolId	No	Integer	Specifies the ID of the pool of the secondary volume.
quorumId	No	Integer	Specifies the ID of the quorum disk.
secondaryPorts	No	Object	Storage ports where the secondary volume is attached.
serverId	Yes	Integer	ID of the server.
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.
portIds	No	String	Storage ports where the volume is attached. If ports are not specified, an available port is automatically selected.
preferredPath	No	Boolean	Whether the LU path (Host Group) is preferred or not.

Parameter	Required	Type	Description
secondaryVolumeLabel	No	String	Label of secondary volume of asynchronous remote clone pair.
drsSetting	No	String	Whether or not DRS setting of the secondary volume of asynchronous remote clone pair is enabled. Valid values are ENABLED and DISABLED.
capacitySavingSetting	No	String	Type of controller-based capacity saving. Valid values are NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION.
journal	No	Object	Journal information.
primaryJournalPoolId	No	Integer	ID of primary storage system's pool where the new journal will be created.
secondaryJournalPoolId	No	Integer	ID of secondary storage system's pool where the new journal will be created.
size	No	Long	Numerical part of journal's capacity.
unit	No	String	Unit part of journal's capacity. Valid values are MiB, GiB, and TiB.
journalLabel	No	String	Label of the new Journal.
primaryJournalId	No	Integer	ID of Journal in primary storage to be used.
secondaryJournalId	No	Integer	ID of Journal in secondary storage to be used.
virtualStorageMachineId	No	String	Specifies the virtual storage machine where the volumes are created. If you don't specify this, the volumes are created from the default VSM. If the volumes are protected by HA, you must specify the ID.
hostGroupName	No	String	The host group name value must be uppercase letters (A-Z), lowercase letters (a-z), numbers (0-9), commas (,), hyphens(-), periods (.), at marks (@), and underscores (_). String length is restricted to the following depending on port type: <ul style="list-style-type: none"> <li>▪ Fiber: 60 when creating and 64 for editing.</li> <li>▪ iSCSI: 28 when creating.</li> </ul>

Parameter	Required	Type	Description
tieringPolicyId	No	Integer	A number between 0 and 31 that specifies the tier level.
drsEnabled	No	Boolean	Whether or not DRS setting of the volume is enabled.
t10PiEnabled	No	Boolean	Whether to enable T10PI for the volume. If this value is omitted, false is assumed.
idRange	No	Object	An ID range for creating volumes.
from	No	Integer	Starting volume ID of the range (in decimal).
to	No	Integer	Ending volume ID for the range (in decimal)
virtualIdRange	No	Object	A range of a virtual volume IDs to use for the creating volume. If specified, the first usable value in the range is used. If not specified, do the same behavior as the conventional API.
from	No	Integer	Starting volume ID of the range (in decimal)
to	No	Integer	Ending volume ID of the range (in decimal)
nvmSubsystemName	No	String	NVM subsystem name. If this attribute is omitted, a value is automatically set.
nvmServers	No	Object	NVMe over FC server Information.
ids	No	List	List of server ID.
nvmSubsystemPortIds	No	List	List of the NVM subsystem port IDs.
nvmSubsystemHostMode	No	String	The host mode set for the NVM subsystem. For the specifiable values, see your storage system's Provisioning Guide.
nvmSubsystemHostModeOptions	No	List	The host mode option set for the NVM subsystem. For the specifiable values, see your storage system's Provisioning Guide.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	User has not specified forceOverwriteChapSecret when the storage system has any host group with the same CHAP user name.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/volume-manager/create-attach-protect
```

**Example request**

```
// For FC Server and iSCSI Server
{
  "storageSystemId": "411209",
  "hostModeOptions": [],
  "intendedImageType": "LINUX",
  "ports": [
    {
      "portId" : "CL1-A",
      "serverId" : 4,
      "serverWwns" : [
        "20000090FA34B747",
        "20000090FA34B746"
      ],
      "iscsiInitiatorNames": ["iqn.2017-11.com.example:Linux:array0", "storagePort",
        "CL2-A"],
      "preferredPath": true
    }
  ],
}
```



```

"enableZoning": false,
"enableLunUnification": false,
"forceOverwriteChapSecret": false,
"aluaEnabled": true,
"shareHgByAllServers": true,
"volumes": [
  {
    "poolType": "Platinum",
    "numberOfVolumes": 1,
    "label": "john",
    "suffix": 0,
    "capacity": "1073741824",
    "poolId": 0
    "dkcDataSavingType": "DEDUPLICATION_AND_COMPRESSION",
    "tieringPolicyId": 2,
    "drsEnabled": false,
    "t10PiEnabled": false,
    "idRange": {
      "from": 500,
      "to": 1000
    }
  }
],
"skipProtection": false,
"replicationGroup": {
  "replicationType": "SNAP",
  "consistencyGroupNeeded": false,
  "replicationGroupName": "my-snapshot",
  "replicationGroupId": null,
  "schedule": {
    "hour": 0,
    "minute": 0,
    "recurringUnit": "DAILY",
    "recurringUnitInterval": null,
    "dayOfWeek": null,
    "dayOfMonth": null
  },
  "numberOfBackups": 1,
  "targetPoolId": 1,
},
"virtualStorageMachineId": "456789-VSPF800andVSPG800"
}

// For NVMe over FC Server
{
  "storageSystemId": "39305",
  "volumes": [{
    "numberOfVolumes": 1,
    "label": "nvme_sample",
    "capacity": 1073741824,
    "poolType": "Platinum"
  }

```

```

    }},
    "skipProtection":true,
    "nvmServers": {
        "ids":[1582]
    },
    "nvmSubsystemPortIds":["CL4-A"]
}

```

## Updating volumes

You can modify multiple volumes' label and command device settings across multiple storage systems at once.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/update
```

### Request structure

The request body structure is as follows:

```

{
  "label": "",
  "dkcDataSavingType": "",
  "commandDevice": {
    "commandDeviceEnabled":,
    "securityEnabled":,
    "userAuthenticationEnabled":,
    "deviceGroupSettingEnabled":
  },
  "updateTargetItems": [
    {
      "storageSystemId": "",
      "volumeIds": []
    },
    ...
  ]
}

```

Parameter	Required	Type	Description
label	No	String	Description of the volume up to 32 characters.

Parameter	Required	Type	Description
			For a namespace, the namespace name is also set with the same value. If the value contains characters that cannot be used in a namespace name, the namespace name will be set with those characters replaced by underscores (_).
dkcDataSavingType	No	String	Type of controller-based capacity saving. Valid values are NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION. The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression. COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools. NONE disables current capacity saving settings. NONE cannot be specified for VSP One Block.
commandDevice	No	Object	Command device settings for the volume.
commandDeviceEnabled	No	Boolean	Whether to configure the volume as a command device. Specify true also in case of updating the security settings only.
securityEnabled	No	Boolean	Whether to enable the command device security setting. If commandDeviceEnabled is true and this value is omitted, false is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.
userAuthenticationEnabled	No	Boolean	Whether to enable user authentication for the command device. If commandDeviceEnabled is true and this value is omitted, true is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.

Parameter	Required	Type	Description
deviceGroupSetting Enabled	No	Boolean	Whether to enable device group information authentication for the command device. If commandDeviceEnabled is true and this value is omitted, false is assumed. Specify this parameter to prevent the setting from being unexpectedly disabled.
updateTargetItems	Yes	List	The list of the storage systems and volume IDs.
storageSystemId	Yes	string	ID of the storage system.
volumelds	Yes	List	The list of the volumes to update. The volume ID type is long.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [

```

```

],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type not match the existing type.
500	Internal Server Error	Some errors occurred inside the API server.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

The request with JSON command:

```
https://172.17.64.111/v1/volume-manager/update
```

```
{
  "label": "volumeLabel1",
  "dkcDataSavingType": "COMPRESSION",
  "updateTargetItems": [
    {
      "storageSystemId": "39304",
      "volumeIds": [100, 101]
    },
    {
      "storageSystemId": "39305",
      "volumeIds": [200, 201]
    }
  ]
}
```

```
]
}
```

## Detaching volumes from multiple servers

You can detach volumes from multiple servers.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/detach-from-multiple-servers
```

### Request Structure

```
{
  "storageSystemId": ,
  "detachTargetItems": [
    {
      "serverId": ,
      "volumeIds": [],
    },
    {
      "serverId": ,
      "volumeIds": [],
    },
    ...
  ],
  "removeConnection":
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	String	The ID of the storage system.
detachTargetItems	Yes	List	List of the items containing servers and volumes to be detached.
serverId	Yes	Integer	The ID of the server from which the volumes are to be detached.
volumeIds	Yes	List	The list of the volumes to be detached. The volume ID type is long.
removeConnection	No	Boolean	Specify whether the zoning accesses to the servers are removed.  FALSE if you specified NULL for the FC port.

Parameter	Required	Type	Description
			Must be NULL for iSCSI port or the port whose operation mode is NVMe mode.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      {}
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.



Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.111/v1/volume-manager/detach-from-multiple-servers
```

**Example request**

```
{
  "storageSystemId": "410209",
  "detachTargetItems": [
    {
      "serverId": 1,
      "volumeIds": [10, 11],
    },
    {
      "serverId": 2,
      "volumeIds": [100, 101],
    }
  ]
}
```

```

    }
    ...
  ],
  "removeConnection": true
}

```

## Editing volume LUN paths

### HTTP request syntax (URI)

POST <https://ipAddress/v1/volume-manager/edit-lun-paths>

### Request structure

```

{
  "enableZoning":,
  "hostMode": "",
  "hostModeOptions": [],
  "forceOverwriteChapSecret": ,
  "updates": [
    {
      "storageSystemId": "",
      "volumeId":,
      "currentPath": {
        "serverWwn": "",
        "iscsiInitiatorName": "",
        "storagePort": ""
      },
      "newPath": {
        "serverWwn": "",
        "iscsiInitiatorName": "",
        "storagePort": ""
      }
    }
  ]
}

```

Parameter	Required	Type	Description
enableZoning	Yes	Boolean	Provide the value "true" to edit the volume LUN path.
hostMode	Yes	String	Host mode set for the volume.

Parameter	Required	Type	Description
hostModeOptions	No	List	Host mode options set for the volume. Default values are set automatically for a VMWARE_EX or WIN_EX server OS. The valid value is a host mode options number without any prefix, or null for auto select.
updates	No	List	List of updates.
storageSystemId	No	String	ID of the storage system.
volumeId	No	Integer	ID of the volume.
forceOverwriteChapSecret	No	Boolean	Whether Hitachi Ops Center Administrator overwrites the CHAP user secret when there is any port with the same CHAP user name. The default is FALSE.

Parameter	Required	Type	Description
currentPath	No	Object	<p>The three objects are as follows:</p> <ul style="list-style-type: none"> <li>serverWwn (String): If the target server has FC ports, specify the target serverWwn.</li> <li>iscsiInitiatorName (String): If the target server has iSCSI ports, specify the target iscsiInitiatorName .</li> <li>storagePort (String): Specify the current storage port that connects to the target server port.</li> </ul>
newPath	No	Object	<p>The three objects are as follows:</p> <ul style="list-style-type: none"> <li>serverWwn (String): If the target server has FC ports, specify the new serverWwn.</li> <li>iscsiInitiatorName (String): If the target server has iSCS ports, specify the new iscsiInitiatorName .</li> <li>storagePort (String): Specify the new storage port that connects to the target server port.</li> </ul>

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
412	Precondition failed	User has not specified forceOverwriteChapSecret when the storage system has any host group with the same CHAP user name.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "enableZoning": false,
  "hostMode": "LINUX",
  "hostModeOptions": [1,2],
  "forceOverwriteChapSecret": false,
  "updates": [{
    "storageSystemId": "targetStorageId",
    "volumeId": "00:00:01",
    "lun": 0,
    "currentPath": {
      "serverWwn": null,
      "iscsiInitiatorName": "iqn.2017-11.com.example:Linux:array0",
      "storagePort": "CL1-A"
    },
    "newPath": {
      "serverWwn": null,
      "iscsiInitiatorName": "iqn.2017-11.com.example:Linux:array0",
      "storagePort": "CL1-B"
    }
  },
  {
    "storageSystemId": "targetStorageId",
    "volumeId": "00:00:01",
    "lun": 0,
    "currentPath": {
      "serverWwn": null,
      "iscsiInitiatorName": "iqn.2017-11.com.example:Linux:array2",
      "storagePort": "CL2-A"
    },
    "newPath": {
      "serverWwn": null,
      "iscsiInitiatorName": "iqn.2017-11.com.example:Linux:array2",
```



```

        "storagePort", "CL2-B"
    }
}
]
}

```

## Editing namespace paths

You can edit namespace paths.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/edit-namespace-paths
```

### Request structure

```

{
  "storageSystemId": "",
  "hostMode": "",
  "hostModeOptions": [],
  "portIds": [""],
  "volumes": [
    {
      "volumeId": ,
      "namespaceId":
    }
  ]
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	The Storage System ID.
hostMode	No	String	Host mode of NVM subsystem.
hostModeOptions	No	List	Host mode options of NVM subsystem.
portIds	No	List	Port IDs of NVM subsystem.
volumes	Yes	List	Target attached volumes.
volumeId	Yes	Long	Target volume ID.
namespaceId	No	Integer	Namespace ID of the volume. If this parameter is specified, servers will not be able to communicate with the namespace while the namespace ID is being reset.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
500	Internal Server Error	Some errors occurred inside the API server.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.111/v1/volume-manager/edit-namespace-paths
```

**Example request**

```
{
  "storageSystemId": "11016",
  "hostMode": "VMWARE",
  "hostModeOptions": [
    132, 133
  ],
  "portIds": [
    "CL2-C",
    "CL5-E"
  ],
  "volumes": [
    {
      "volumeId": 123,
      "namespaceId": 2
    },
    {
      "volumeId": 6789,
      "namespaceId": 12
    }
  ]
}
```

```
]
}
```

## Getting auto-selection paths

If there are no existing host groups, this command specifies the return paths that Ops Center Administrator will select.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/auto-path-select
```

### Request structure

```
{
  "storageSystemId": "",
  "hostMode": "",
  "hostModeOptions": [
  ],
  "serverIds": [
  ],
  "virtualStorageMachineId":
}
```

Parameter	Required	Type	Description
storageSystemId	No	String	ID of the storage system.
hostMode	Yes	String	Host mode set for the volume.
hostModeOptions	No	List	Host mode options set for the volume. Default values are set automatically for a VMWARE_EX or WIN_EX server OS. The valid value is a host mode options number without any prefix, or null for auto select.

Parameter	Required	Type	Description
virtualStorageMachineId	No	String	If existing volumes are being attached, specify the volume's virtualStorageMachineId. The VSM is verified and the same VSM's port is selected. When creating, attaching, and protecting volumes, specify null.

### Response structure

```
{
  "pathResources": [
    {
      // For FC server port
      "portId": "",
      "serverWwn": "",
      "iscsiInitiatorName": ,
      "hostMode": "",
      "hostModeOptions": [
      ]
    },
    {
      // For iSCSI server port
      "portId": "",
      "serverWwn": ,
      "iscsiInitiatorName": "",
      "hostMode": "",
      "hostModeOptions": [
      ]
    }
  ]
}
```

Parameter	Type	Description
portId	String	Port ID.
serverWwn	String	World wide network ID of the server.

Parameter	Type	Description
hostMode	String	Host mode set for the volume.
hostModeOptions	List of Integers	Host mode options for the volume.
iscsiInitiatorName	String	Displays the iSCSI name for the iSCSI initiator. NULL for FC path.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "storageSystemId": "410209",
  "hostMode": "LINUX",
  "hostModeOptions": [
    4,
    2
  ],
  "serverIds": [
    6,
    34
  ],
  "virtualStorageMachineId": "456789-VSPF800andVSPG800"
}
```

**Example response**

```
{
  "pathResources": [
    {
      // For FC server port
      "portId": "1",
      "serverWwn": "50000000001",
      "iscsiInitiatorName": null,
      "hostMode": "LINUX",
      "hostModeOptions": [
        ]
    },
    {
      // For iSCSI server port
      "portId": "2",
      "serverWwn": null,
      "iscsiInitiatorName": "iqn.1994-04.com.example:rsd.h8m.t.10013.CL4.1 ",
      "hostMode": "LINUX",
      "hostModeOptions": [
        ]
    },
    ...
  ]
}
```

**Shredding volumes**

You can shred volumes in Ops Center Administrator.



**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/volume-manager/shred
```

**Request structure**

The request body structure is as follows:

```
{
  "storageSystemId": "",
  "volumeIds": [ , ... ],
  "patterns": [ "", ... ]
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the storage system.
volumeIds	Yes	List	List of the volume IDs to shred.  Maximum number of volumes that can be shredded at the same time in a single storage system is 300.
patterns	No	List	List of the pattern strings used for shredding. Maximum number of patterns is 7.  Each pattern must be a string representing a hex value of up to 0xFFFFFFFF (regular expression: [0-9a-fA-F]{1,8}).  For each specified <pattern> in the API payload, actual shredding passes are ["00000000", <pattern>, "00000000"].

Parameter	Required	Type	Description
			If not specified, a pre-defined pattern ["FFFFFFFF"] will be used.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      "text": ""
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.

Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status Code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "storageSystemId": "",
  "volumeIds": [ , ... ],
  "patterns": [ "", ... ]
}
```

## Interrupting volume shredding

You can interrupt the shredding of volumes in Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/volume-manager/shred/interrupt
```

### Request structure

The request body structure is as follows:

```
{
  "storageSystemId": ""
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the storage system.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Parameter	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Host group management resources**

Request	Method	URI	Role
<a href="#">Getting host groups (on page 329)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /host-groups	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a host group (on page 334)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /host-groups/ <i>hostGroupId</i>	Storage administrator System administrator

Request	Method	URI	Role
			Security administrator Monitoring
<a href="#">Creating host groups (on page 338)</a>	POST	/v1/host-group-manager/ create	Storage administrator System administrator
<a href="#">Editing a host group (on page 344)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> /host-groups/ <i>hostGroupId</i>	Storage administrator System administrator
<a href="#">Adding volumes to host groups (on page 348)</a>	POST	/v1/host-group-manager/ add-volumes	Storage administrator System administrator
<a href="#">Removing volumes from host groups (on page 352)</a>	POST	/v1/host-group-manager/ remove-volumes	Storage administrator System administrator
<a href="#">Adding a mutual CHAP user of a host group (on page 355)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> /host-groups/ <i>hostGroupId</i>	Storage administrator System administrator Security administrator
<a href="#">Updating a mutual CHAP user of a host group (on page 359)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> /host-groups/ <i>hostGroupId</i>	Storage administrator System administrator Security administrator
<a href="#">Deleting a mutual CHAP user of a host group (on page 363)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> /host-groups/ <i>hostGroupId</i>	Storage administrator System administrator Security administrator



Request	Method	URI	Role
<a href="#">Deleting host groups (on page 367)</a>	POST	/v1/host-group-manager/delete	Storage administrator System administrator

## Getting host groups

You can get a list of host groups for a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/host-groups
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources": [
    // For FC Host Group
    {
      "protocol": "",
      "hostGroupId": "",
      "hostGroupNumber": ,
      "hostGroupName": "",
      "storagePortId": "",
      "storageSystemId": "",
      "hostMode": "",
      "hbaWwns": [],
      "hostModeOptions": [],
      "luns": [],
      "iscsiTargetInformation": {},
      "preferredPath": ,
      "numOfHostPortIds": ,
      "numOfLuns": ,
      "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "",
        "storageSystemId": "",
        "model": ""
      }
    },
  ],
}
```

```

        "resourceGroupId": ,
        "resourceGroupName": ""
    },
    // For iSCSI Target
    {
        "protocol": "",
        "hostGroupId": "",
        "hostGroupNumber": ,
        "hostGroupName": "",
        "storagePortId": "",
        "storageSystemId": "",
        "hostMode": "",
        "hbaWwns": [],
        "hostModeOptions": [],
        "luns": [],
        "iscsiTargetInformation": {
            "iscsiTargetName": "",
            "iscsiInitiatorNames": [
                ""
            ],
            "mutualChapUser": "",
            "chapUsers": [
                ""
            ],
            "authenticationMode": "",
            "authenticationDirection": ""
        },
        "preferredPath": ,
        "numOfHostPortIds": ,
        "numOfLuns": ,
        "virtualStorageMachineInformation": {
            "virtualStorageMachineId": "",
            "storageSystemId": "",
            "model": ""
        },
        "resourceGroupId": ,
        "resourceGroupName": ""
    },
    ...

],
"total": ,
"nextToken": ""
}

```

Parameter	Type	Description
protocol	Enum	Protocol type of this port, either FIBRE or iSCSI.
hostGroupId	Long	The ID of the host group.
hostGroupNumber	Integer	The host group or iSCSI target ID number.
hostGroupName	String	The host group name.
storagePortId	Long	The storage port ID.
storageSystemId	String	The storage system ID.
hostMode	String	The host mode set for the volume.
hbaWwns	List	The list of WWNs for the HBA.
hostModeOptions	Integer[]	The host mode options for the volume.
luns	List	The list of LUNs and volumes.
iscsiTargetInformation	Object	Displays the iSCSI target information. This is NULL for FC host groups.
preferredPath	Boolean	Specifies whether LU paths for the host group are preferred.
numOfHostPortIds	integer	The number of WWNs in the host group, or the number of iSCSI names in the iSCSI Target.
numOfLuns	integer	The number of LUNs in the Host Group or iSCSI Target
virtualStorageMachineInformation.virtualStorageMachineId	string	The ID of the virtual storage machine to which the host group or iSCSI target belongs.
virtualStorageMachineInformation.storageSystemId	string	The serial number of the virtual storage machine to which the host group or iSCSI target belongs.
virtualStorageMachineInformation.model	string	The model of the virtual storage machine to which the host group or iSCSI target belongs.
resourceGroupId	integer	The ID of the resource group to which the host group or iSCSI target belongs.
resourceGroupName	string	The name of the resource group to which the host group or iSCSI target belongs.
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.

Parameter	Type	Description
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	<p>The CHAP authentication mode for the iSCSI target. This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ CHAP: CHAP-authentication mode.</li> <li>▪ NONE: No-authentication mode.</li> <li>▪ BOTH: Both CHAP-authentication mode and no-authentication mode.</li> </ul>
authenticationDirection	Enum	<p>The CHAP authentication direction for the iSCSI target. This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ ONEWAY: The iSCSI target authenticates the iSCSI initiator.</li> <li>▪ MUTUAL: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/storageSystems/410209/host-groups
```

### Example response

```
{
  "resources": [
    {
      "hostGroupId": "CL3-B-66",
      "hostGroupNumber": 66,
      "storagePortId": "CL3-B",
      "storageSystemId": "15283",
      "protocol": "FIBRE",
      "hostMode": "VMWARE_EX",
      "hbaWwns": [
        "3333000000009511"
      ],
      "hostModeOptions": [
        54,
        63
      ],
      "luns": [
        {
          "lun": 1,
          "volumeId": 791
        }
      ],
      "iscsiTargetInformation": null,
      "preferredPath": true,
      "hostGroupName": "fc-cluster-node149",
      "numOfHostPortIds": 1,
      "numOfLuns": 1,
      "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "15283-VSP5100H-5500H",
        "storageSystemId": "15283",
        "model": "VSP 5100H, 5500H"
      },
      "resourceGroupId": 1,
      "resourceGroupName": "RSG1"
    }
  ]
}
```

```
]
}
```

## Getting a host group

You can retrieve information regarding a host group when you specify a host group ID in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/host-groups/hostGroupId
```



**Note:** The format for the host group ID is *portId-hostGroupName*. For example, CL4-G-0.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows.

For Fibre Channel host group:

```
{
  "resources": [
    // For FC Host Group
    {
      "protocol": "",
      "hostGroupId": "",
      "hostGroupNumber": ,
      "hostGroupName": "",
      "storagePortId": "",
      "storageSystemId": "",
      "hostMode": "",
      "hbaWwns": [],
      "hostModeOptions": [],
      "luns": [],
      "iscsiTargetInformation": {},
      "preferredPath": ,
      "numOfHostPortIds": ,
      "numOfLuns": ,
      "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "",
        "storageSystemId": "",
        "model": ""
      },
      "resourceGroupId": ,
    }
  ]
}
```

```
"resourceGroupName": ""
},
```

For iSCSI target:

```
{
  "protocol": "",
  "hostGroupId": "",
  "hostGroupNumber": ,
  "hostGroupName": "",
  "storagePortId": "",
  "storageSystemId": "",
  "hostMode": "",
  "hbaWwns": [],
  "hostModeOptions": [],
  "luns": [],
  "iscsiTargetInformation": {
    "iscsiTargetName": "",
    "iscsiInitiatorNames": [
      ""
    ],
    "mutualChapUser": "",
    "chapUsers": [
      ""
    ],
    "authenticationMode": "",
    "authenticationDirection": ""
  },
  "preferredPath": ,
  "numOfHostPortIds": ,
  "numOfLuns": ,
  "virtualStorageMachineInformation": {
    "virtualStorageMachineId": "",
    "storageSystemId": "",
    "model": ""
  },
  "resourceGroupId": ,
  "resourceGroupName": ""
},
```

Parameter	Type	Description
protocol	Enum	Protocol type of this port, either FIBRE or iSCSI.
hostGroupId	Long	The ID of the host group.
hostGroupNumber	integer	The host group or iSCSI target ID number.

Parameter	Type	Description
hostGroupName	String	The host group name.
storagePortId	Long	The storage port ID.
storageSystemId	String	The storage system ID.
hostMode	String	The host mode set for the volume.
hbaWwns	List	The list of WWNs for the HBA.
hostModeOptions	List of Integers	The host mode options for the volume.
luns	List	The list of LUNs and volumes.
iscsiTargetInformation	Object	Displays the iSCSI target information. This is NULL for FC host groups.
preferredPath	Boolean	Specifies whether LU paths for the host group are preferred.
numOfHostPortIds	integer	The number of WWNs in the host group, or the number of iSCSI names in the iSCSI Target.
numOfLuns	integer	The number of LUNs in the Host Group or iSCSI Target
virtualStorageMachineInformation.virtualStorageMachineId	string	The ID of the virtual storage machine to which the host group or iSCSI target belongs.
virtualStorageMachineInformation.storageSystemId	string	The serial number of the virtual storage machine to which the host group or iSCSI target belongs.
virtualStorageMachineInformation.model	string	The model of the virtual storage machine to which the host group or iSCSI target belongs.
resourceGroupId	integer	The ID of the resource group to which the host group or iSCSI target belongs.
resourceGroupName	string	The name of the resource group to which the host group or iSCSI target belongs.
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.



Parameter	Type	Description
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	<p>The CHAP authentication mode for the iSCSI target. This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ CHAP: CHAP-authentication mode.</li> <li>▪ NONE: No-authentication mode.</li> <li>▪ BOTH: Both CHAP-authentication mode and no-authentication mode.</li> </ul>
authenticationDirection	Enum	<p>The CHAP authentication direction for the iSCSI target. This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ ONEWAY: The iSCSI target authenticates the iSCSI initiator.</li> <li>▪ MUTUAL: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>

### Return codes

Status Code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

For Fibre Channel host group:

```
{
  "resources": [
    {
      "hostGroupId": "CL3-B-66",
      "hostGroupNumber": 66,
      "storagePortId": "CL3-B",
      "storageSystemId": "15283",
      "protocol": "FIBRE",
      "hostMode": "VMWARE_EX",
      "hbaWwns": [
        "3333000000009511"
      ],
      "hostModeOptions": [
        54,
        63
      ],
      "luns": [
        {
          "lun": 1,
          "volumeId": 791
        }
      ],
      "iscsiTargetInformation": null,
      "preferredPath": true,
      "hostGroupName": "fc-cluster-node149",
      "numOfHostPortIds": 1,
      "numOfLuns": 1,
      "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "15283-VSP5100H-5500H",
        "storageSystemId": "15283",
        "model": "VSP 5100H, 5500H"
      },
      "resourceGroupId": 1,
      "resourceGroupName": "RSG1"
    }
  ]
}
```

**Creating host groups**

You can create host groups in a storage system.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/host-group-manager/create
```

## Request structure

The request body structure is as follows:

```
{
  "hostGroups": [
    {
      "storageSystemId": "",
      "virtualStorageMachineId": "",
      "storagePortId": "",
      "hostGroupNumber": ,
      "hostGroupName": "",
      "hbaWwns": [
        "",
        ...
      ],
      "hostMode": "",
      "hostModeOptions": [],
      "preferredPath": ,
      "luns": [
        {
          "lun": ,
          "volumeId":
        },
        ...
      ],
      "virtualVolumeIdRange": {
        "from": ,
        "to":
      }
    },
    ...
  ]
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	string	The ID of the storage system to which the Host Group belongs.
storagePortId	Yes	string	The ID of the storage port to which the Host Group belongs.
virtualStorageMachineId	No	string	The ID of the Virtual Storage Machine to which the Host Group belongs. If you specify null, then the API selects the default VSM for the storage system automatically.

Parameter	Required	Type	Description
hostGroupNumber	No	integer	The Host Group number for the Host Group. If you specify null, then API selects the minimum number for the storage port automatically.
hostGroupName	Yes	string	The name of the Host Group.
hbaWwns	No	string[]	The HBA WWNs of the Host Group.
hostMode	Yes	string	The Host Mode of the Host Group.
hostModeOptions	No	integer[]	The Host Mode Options for the Host Group. If you specify null, then Ops Center Administrator sets the default values automatically based on the specified hostMode.
preferredPath	No	boolean	Specifies whether the Host Group enables the preferred path setting. The default value is true.
luns.volumeld	No	integer	The target volume ID.
luns.lun	No	integer	The target LUN number. If you specify null, then the API selects the minimum value in the storage port automatically.
virtualVolumeldRange.from	No	integer	The starting virtual volume ID of the range (in decimal).
virtualVolumeldRange.to	No	integer	The ending virtual volume ID of the range (in decimal)

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  }
}
```

```

    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The operation was accepted.
400	Bad request	Bad request
403	Forbidden	The operation is not authorized.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "hostGroups": [
    {
      "storageSystemId": "12345",
```

```

    "virtualStorageMachineId": "10000-G1500",
    "storagePortId": "CL3-B",
    "hostGroupNumber": 13,
    "hostGroupName": "fc-cluster-node149",
    "hbaWwns": [
        "3333000000009511"
    ],
    "hostMode": "VMWARE_EX",
    "hostModeOptions": [
        54,
        63
    ],
    "preferredPath": true,
    "luns": [
        {
            "lun": 1,
            "volumeId": 791
        },
        {
            "volumeId": 31
        }
    ],
    "virtualVolumeIdRange": {
        "from": 2000,
        "to": 2001
    }
}
]
}

```

## Multiple Host Groups

```

{
  "hostGroups": [
    {
      "storageSystemId": "12345",
      "virtualStorageMachineId": "10000-G1500",
      "storagePortId": "CL3-B",
      "hostGroupName": "fc-cluster-node149",
      "hbaWwns": [
        "3333000000009511"
      ],
      "hostMode": "VMWARE_EX",
      "hostModeOptions": [
        54,
        63
      ],
      "preferredPath": true,
      "luns": [
        {
          "volumeId": 31
        }
      ]
    }
  ]
}

```

```

    }
  ]
},
{
  "storageSystemId": "49853",
  "storagePortId": "CL4-B",
  "hostGroupNumber": 12,
  "hostGroupName": "fc-cluster-node177",
  "hbaWwns": [
    "3333000000009513"
  ],
  "hostMode": "VMWARE_EX",
  "hostModeOptions": [
    54,
    63
  ],
  "luns": [
    {
      "volumeId": 31
    }
  ],
  "virtualVolumeIdRange": {
    "from": 31,
    "to": 31
  }
}
]

```

## Editing a host group

You can edit the host mode, host mode options, host bus adapter (HBA) WWNs, preferred path setting, and name of a host group in Ops Center Administrator.

### HTTP request syntax (URI)

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/host-groups/hostGroupId
```

### Request structure

```

{
  "hostGroupName": "",
  "hbaWwns": [
    "",
    ...
  ],
  "hostMode": "",
  "hostModeOptions": [],
  "preferredPath":
}

```



Parameter	Required	Type	Description
hostGroupName	No	string	<p>The host group name.</p> <p>The host group name value must be uppercase letters (A-Z), lowercase letters (a-z), numbers (0-9), commas (,), hyphens(-), periods (.), at marks (@), and underscores (_). String length is restricted to the following depending on the port type:</p> <ul style="list-style-type: none"> <li>Fiber: 60 when creating and 64 for editing.</li> <li>iSCSI: 28 when creating.</li> </ul>
hbaWwns	No	string[]	The host group HBA WWNs.
hostMode	No	string	The host group host mode.
hostModeOptions	No	integer[]	The host group host mode options.
preferredPath	No	boolean	Specifies whether the host group enables the preferred path setting.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
    ]
}
```

```

    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.

Parameter	Type	Description
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP Name	Description
200	OK	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "hostGroupName": "hostgroup1",
  "hbaWwns": [
    "3333000000009511",
    "3333000000009512"
  ]
}
```

```

],
"hostMode": "VMWARE_EX",
"hostModeOptions": [
  54,
  63
],
"preferredPath": true
}

```

## Adding volumes to host groups

You can add volumes to host groups in a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/host-group-manager/add-volumes
```

### Request structure

The request body structure is as follows:

```

{
  "hostGroups": [
    {
      "storageSystemId": "",
      "hostGroupId": "",
      "luns": [
        {
          "lun": ,
          "volumeId":
        },
        ...
      ],
      "virtualVolumeIdRange": {
        "from": ,
        "to":
      }
    },
    ...
  ]
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	string	The ID of the storage system to which the Host Group belongs.
hostGroupId	Yes	string	The target host group ID.

Parameter	Required	Type	Description
luns.volumeld	Yes	integer	The target volume ID.
luns.lun	No	integer	The target LUN number. If you specify null, then the API selects the minimum value in the storage port automatically.
virtualVolumeldRange.from	No	integer	The starting virtual volume ID of the range (in decimal).
virtualVolumeldRange.to	No	integer	The ending virtual volume ID of the range (in decimal)

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
}
```

```
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The operation was accepted.
400	Bad request	Bad request
403	Forbidden	The operation is not authorized.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "hostGroups": [
    {
      "storageSystemId": "12345",
      "hostGroupId": "CL1-A-2",
      "luns": [
        {
          "lun": 33,
          "volumeId": 3974
        },
        {
          "volumeId": 3975
        }
      ],
      "virtualVolumeIdRange": {
        "from": 2000,
        "to": 2001
      }
    },
    {
      "storageSystemId": "12345",
      "hostGroupId": "CL1-A-3",
      "luns": [
        {
          "lun": 34,
          "volumeId": 3976
        },
        {
          "volumeId": 3977
        }
      ]
    }
  ]
}
```

```

    ],
    "virtualVolumeIdRange": {
      "from": 3000,
      "to": 3001
    }
  }
]
}

```

## Removing volumes from host groups

You can remove volumes from host groups in a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/host-group-manager/remove-volumes
```

### Request structure

The request body structure is shown below:

```

{
  "hostGroups": [
    {
      "storageSystemId": "",
      "hostGroupId": "",
      "volumeIds": [
        ...
      ]
    },
    ...
  ]
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	string	The target storage system ID.
hostGroupId	Yes	string	The target host group ID.
volumeIds	Yes	integer[]	The target volume IDs.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",

```



```

"title":
{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  }
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The operation was accepted.
400	Bad request	Bad request
403	Forbidden	The operation is not authorized.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "hostGroups": [
    {
      "storageSystemId": "12345",
      "hostGroupId": "CL1-A-83",
      "volumeIds": [
        3247,
        3774
      ]
    },
    {
      "storageSystemId": "12345",
      "hostGroupId": "CL1-B-83",
      "volumeIds": [
        3247,
        3774
      ]
    }
  ]
}
```

## Adding a mutual CHAP user of a host group

You can add a mutual CHAP user of a host group in Ops Center Administrator. Adding a CHAP user is only for iSCSI ports. In the URI, you must specify the host group ID whose protocol is iSCSI. Also, Add/Update/Delete uses the same URI. You modify the payload. To add, specify an empty string for `currentValue`. To delete, specify an existing user for `currentValue` and an empty string for `newValue`.

### HTTP request syntax (URI)

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/host-groups/hostGroupId
```

### Request structure

The request body structure is as follows:

```
{
  iscsiTargetInformation: {
    "mutualChapUser": {
```

```

        "userName": {
            "currentValue": "",
            "newValue": ""
        },
        "secret": ""
    }
}
}

```

Parameter	Required	Type	Description
iscsiTargetInformation	Yes	Object	Specify to update iSCSI information.
mutualChapUser	Yes	Object	New mutual CHAP user set to the host group.
userName	Yes	Object	Mutual CHAP user name.
currentValue	Yes	String	Current user name of the new mutual CHAP user.
newValue	Yes	String	New user name of the new mutual CHAP user.
secret	Yes	String	<p>User secret of the new mutual CHAP user.</p> <p>To add/update a mutual CHAP user, this parameter is required.</p> <p>To delete a mutual CHAP user, this parameter is not required.</p>

### Response structure

```

{
    "jobId": "",
    "title": {
        "text": "",
        "messageCode": "",
        "parameters": {}
    }
}

```

```

},
"user": "",
"status": "",
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports": [],
"links": [
  {
    "rel": "_self",
    "href": "/v1/jobs/"
  }
],
"tags": [],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	The ID of the job that is created to carry out the request.
title	Object	The title of the job in progress.
text	String	Text of the message.
messageCode	String	ID of the message. This maps to the message description.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	Name of the user who started the job.
status	String	Job status. Valid values: <ul style="list-style-type: none"> <li>• In Progress</li> <li>• Failed</li> <li>• Success</li> <li>• Success With Errors</li> </ul>
startDate	Integer	The date and time this job started. Format is the Unix epoch.
endDate	Integer	Date and time when this job ended. If the job is still in progress, this parameter does not return a value. Format is the Unix epoch.
parentJobId	Integer	The ID of the job that spawned this job. If not applicable, the value null is returned.

Parameter	Type	Description
reports	List	Messages associated with this job.
links	List	Displays related resources.
self	String	URI that includes the resource ID.
tags	List	List of user-defined identifiers. Each identifier (tag) must be a minimum of three characters in length.
isSystem	Boolean	Whether a job was created by a system or a user. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  iscsiTargetInformation: {
    "mutualChapUser": {
      "userName": {
        "currentValue": null,
        "newValue": "mutualChapY",
      },
      "secret": "123456789012"
    }
  }
}
```

## Updating a mutual CHAP user of a host group

You can update a mutual CHAP user in Ops Center Administrator. Add/Update/Delete uses the same URI. You modify the payload. To add, specify an empty string for `currentValue`. To delete, specify an existing user for `currentValue` and an empty string for `newValue`.

### HTTP request syntax (URI)

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/host-groups/hostGroupId
```

### Request structure

The request body structure is as follows:

```
{
  iscsiTargetInformation: {
    "mutualChapUser": {
      "userName": {
        "currentValue": "",
        "newValue": ""
      },
      "secret": ""
    }
  }
  "hostGroupName": ""
}
```

Parameter	Required	Type	Description
iscsiTargetInformation	Yes	Object	Specify to update iSCSI information.
mutualChapUser	Yes	Object	New mutual CHAP user set to the host group.
userName	Yes	Object	Mutual CHAP user name.
currentValue	Yes	String	Current user name of the new mutual CHAP user.
newValue	Yes	String	New user name of the new mutual CHAP user.
secret	Yes	String	<p>User secret of the new mutual CHAP user.</p> <p>To add/update a mutual CHAP user, this parameter is required.</p> <p>To delete a mutual CHAP user, this parameter is not required.</p>
hostGroupName	No	String	<p>The host group name value must be uppercase letters (A-Z), lowercase letters (a-z), numbers (0-9), commas (,), hyphens(-), periods (.), at marks (@), and underscores (_). String length is restricted to the</p>



Parameter	Required	Type	Description
			following depending on port type: <ul style="list-style-type: none"> <li>▪ Fiber: 60 when creating and 64 for editing.</li> <li>▪ iSCSI: 28 when creating.</li> </ul>

### Response structure

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {}
  },
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/"
    }
  ],
  "tags": [],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	The ID of the job that is created to carry out the request.
title	Object	The title of the job in progress.
text	String	Text of the message.
messageCode	String	ID of the message. This maps to the message description.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	Name of the user who started the job.
status	String	Job status. Valid values: <ul style="list-style-type: none"> <li>• In Progress</li> <li>• Failed</li> <li>• Success</li> <li>• Success With Errors</li> </ul>
startDate	Integer	The date and time this job started. Format is the Unix epoch.
endDate	Integer	Date and time when this job ended. If the job is still in progress, this parameter does not return a value. Format is the Unix epoch.
parentJobId	Integer	The ID of the job that spawned this job. If not applicable, the value null is returned.
reports	List	Messages associated with this job.
links	List	Displays related resources.
self	String	URI that includes the resource ID.
tags	List	List of user-defined identifiers. Each identifier (tag) must be a minimum of three characters in length.
isSystem	Boolean	Whether a job was created by a system or a user. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  iscsiTargetInformation: {
    "mutualChapUser": {
      "userName": {
        "currentValue": "mutualChapX",
        "newValue": "mutualChapY",
      },
      "secret": "123456789012"
    }
  }
}
```

## Deleting a mutual CHAP user of a host group

You can delete a mutual CHAP user of a host group in Ops Center Administrator. Add/Update/Delete uses the same URI. You modify the payload. To add, specify an empty string for `currentValue`. To delete, specify an existing user for `currentValue` and an empty string for `newValue`.

### HTTP request syntax (URI)

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/host-groups/hostGroupId
```

**Request structure**

The request body structure is as follows:

```
{
  iscsiTargetInformation: {
    "mutualChapUser": {
      "userName": {
        "currentValue": "",
        "newValue": ""
      }
    }
  }
}
```

Parameter	Required	Type	Description
iscsiTargetInformation	Yes	Object	Specify to update iSCSI information.
mutualChapUser	Yes	Object	New mutual CHAP user set to the host group.
userName	Yes	Object	Mutual CHAP user name.
currentValue	Yes	String	Current user name of the new mutual CHAP user.
newValue	Yes	String	New user name of the new mutual CHAP user.
secret	No	String	<p>User secret of the new mutual CHAP user.</p> <p>To add/update a mutual CHAP user, this parameter is required.</p> <p>To delete a mutual CHAP user, this parameter is not required.</p>

**Response structure**

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {}
  },
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/"
    }
  ],
  "tags": [],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	The ID of the job that is created to carry out the request.
title	Object	The title of the job in progress.
text	String	Text of the message.
messageCode	String	ID of the message. This maps to the message description.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	Name of the user who started the job.
status	String	Job status. Valid values: <ul style="list-style-type: none"> <li>• In Progress</li> <li>• Failed</li> <li>• Success</li> <li>• Success With Errors</li> </ul>

Parameter	Type	Description
startDate	Integer	The date and time this job started. Format is the Unix epoch.
endDate	Integer	Date and time when this job ended. If the job is still in progress, this parameter does not return a value. Format is the Unix epoch.
parentJobId	Integer	The ID of the job that spawned this job. If not applicable, the value null is returned.
reports	List	Messages associated with this job.
links	List	Displays related resources.
self	String	URI that includes the resource ID.
tags	List	List of user-defined identifiers. Each identifier (tag) must be a minimum of three characters in length.
isSystem	Boolean	Whether a job was created by a system or a user. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  iscsiTargetInformation: {
    mutualChapUser: {
      userName: {
        currentValue: "mutualChapX",
        newValue: null,
      }
    }
  }
}
```

## Deleting host groups

You can delete host groups from a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/host-group-manager/delete
```

### Request structure

The request body structure is shown below:

```
{
  "hostGroups": [
    {
      "storageSystemId":
      "hostGroupIds": [
        "",
        ...
      ]
    },
    ...
  ]
}
```

```
]
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	string	The ID of the target storage system.
hostGroupIds	Yes	string[]	The target host group IDs.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```



Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The operation was accepted.
400	Bad request	Bad request
403	Forbidden	The operation is not authorized.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "hostGroups": [
    {
      "storageSystemId": "12345"
      "hostGroupIds": [
        "CL1-A-83",
        "CL1-B-83"
      ]
    }
  ]
}
```

**NVM subsystem management resources**

Request	Method	URI	Role
<a href="#">Listing NVM subsystems (on page 371)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /nvm- subsystems	System administrator Storage administrator Security administrator Monitoring

Request	Method	URI	Role
<a href="#">Getting an NVM subsystem (on page 375)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /nvm- subsystems/ <i>nvmSubsystemId</i>	System administrator Storage administrator Security administrator Monitoring
<a href="#">Updating an NVM subsystem (on page 378)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> /nvm- subsystems/ <i>nvmSubsystemId</i>	Storage administrator

## Listing NVM subsystems

You can get a list of NVM subsystems for a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/nvm-subsystems
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "resources": [
    {
      "storageSystemId": "",
      "nvmSubsystemId": "",
      "nqn": "",
      "name": "",
      "storagePortIds": [],
      "hostNqns": [
        {
          "hostNqn": "",
          "nickname": ""
        },
        ...
      ],
      "namespaceSecurity": ""
    }
  ]
}
```

```

    "t10PiMode": "",
    "hostMode": "",
    "hostModeOptions": [],
    "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "",
        "storageSystemId": "",
        "model": ""
    },
    "resourceGroupId": ,
    "resourceGroupName": ""
}
],
"total": ,
"nextToken": ""
}

```

Parameter	Type	Description
storageSystemId	String	The Storage System ID.
nvmSubsystemId	Integer	The NVM subsystem ID.
nqn	String	The NVM subsystem NQN.
name	String	The NVM subsystem name.
storagePortIds	List	The IDs of NVM subsystem ports .
hostNqns	List	The list of host NQN information.
hostNqn	String	The host NQN assigned to the NVM subsystem.
nickname	String	The nickname of the host NQN assigned to the NVM subsystem.
namespaceSecurity	String	Namespace security settings. Valid values: <ul style="list-style-type: none"> <li>ENABLED: Enabled</li> <li>DISABLED: Disabled</li> <li>UNKNOWN: Status unknown (unsupported)</li> </ul>
t10PiMode	String	Status of the T10 PI mode. Valid values: <ul style="list-style-type: none"> <li>ENABLED: Enabled</li> <li>DISABLED: Disabled</li> <li>UNKNOWN: Status unknown (unsupported)</li> </ul>
hostMode	String	The host mode set for the NVM subsystem.

Parameter	Type	Description
hostModeOptions	List	The host mode options set for the NVM subsystem.
virtualStorageMachineInformation	Object	The information of virtual storage machine.
virtualStorageMachineId	String	The ID of the virtual storage machine to which the NVM subsystem belongs.
storageSystemId	String	The serial number of the virtual storage machine to which the NVM subsystem belongs.
model	String	The model of the virtual storage machine to which the NVM subsystem belongs.
resourceGroupId	Integer	ID of the resource group to which the NVM subsystem belongs.
resourceGroupName	String	Name of the resource group to which the NVM subsystem belongs.
total	Long	The total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.111/v1/storageSystems/41010/nvm-subsystems
```

**Example response**

```
{
  "resources": [
    {
      "storageSystemId": "41010",
      "nvmSubsystemId": 1,
      "nqn": "nqn.2015-04.com.example:nvme:storage-subsystems.5-10088-nvmssid.00001",
      "name": "nvmss_id_00001",
      "storagePortIds": [
        "CL1-A"
      ],
      "hostNqns": [
        {
          "hostNqn": "nqn.yyy",
          "nickname": "host1_app"
        }
      ],
      "namespaceSecurity": "ENABLED",
      "t10PiMode": "DISABLED",
      "hostMode": "LINUX",
      "hostModeOptions": [132, 133],
      "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "41010-VSP5100H-5500H",
        "storageSystemId": "41010",
        "model": "VSP 5100H, 5500H"
      },
      "resourceGroupId": 0,
      "resourceGroupName": "meta_resource"
    }
  ],
  "total": 1,
```

```
"nextToken": null
}
```

## Getting an NVM subsystem

You can retrieve information regarding an NVM subsystem when you specify an NVM subsystem ID in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/nvm-subsystems/nvmSubsystemId
```

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "storageSystemId": "",
  "nvmSubsystemId": "",
  "nqn": "",
  "name": "",
  "storagePortIds": [],
  "hostNqns": [
    {
      "hostNqn": "",
      "nickname": ""
    },
    ...
  ],
  "namespaceSecurity": "",
  "t10PiMode": "",
  "hostMode": "",
  "hostModeOptions": [],
  "virtualStorageMachineInformation": {
    "virtualStorageMachineId": "",
    "storageSystemId": "",
    "model": ""
  },
  "resourceGroupId": ,
  "resourceGroupName": ""
}
```

Parameter	Type	Description
storageSystemId	String	The Storage System ID.
nvmSubsystemId	Integer	The NVM subsystem ID.
nqn	String	The NVM subsystem NQN.
name	String	The NVM subsystem name.
storagePortIds	List	The IDs of NVM subsystem ports .
hostNqns	List	The list of host NQN information.
hostNqn	String	The host NQN assigned to the NVM subsystem.
nickname	String	The nickname of the host NQN assigned to the NVM subsystem.
namespaceSecurity	String	Namespace security settings. Valid values: <ul style="list-style-type: none"> <li>ENABLED: Enabled</li> <li>DISABLED: Disabled</li> <li>UNKNOWN: Status unknown (unsupported)</li> </ul>
t10PiMode	String	Status of the T10 PI mode. Valid values: <ul style="list-style-type: none"> <li>ENABLED: Enabled</li> <li>DISABLED: Disabled</li> <li>UNKNOWN: Status unknown (unsupported)</li> </ul>
hostMode	String	The host mode set for the NVM subsystem.
hostModeOptions	List	The host mode options set for the NVM subsystem.
virtualStorageMachineInformation	Object	The information of virtual storage machine.
virtualStorageMachineId	String	The ID of the virtual storage machine to which the NVM subsystem belongs.
storageSystemId	String	The serial number of the virtual storage machine to which the NVM subsystem belongs.
model	String	The model of the virtual storage machine to which the NVM subsystem belongs.



Parameter	Type	Description
resourceGroupId	Integer	ID of the resource group to which the NVM subsystem belongs.
resourceGroupName	String	Name of the resource group to which the NVM subsystem belongs.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/storageSystems/41010/nvm-subsystems/1
```

### Example response

```
{
  "storageSystemId": "41010",
  "nvmSubsystemId": 1,
  "nqn": "nqn.2015-04.com.example:nvme:storage-subsystemsn.5-10088-nvmssid.00001",
  "name": "nvmss_id_00001",
  "storagePortIds": [
    "CL1-A"
  ],
  "hostNqns": [
    {
```

```

        "hostNqn": "nqn.yyy",
        "nickname": "host1_app"
    }
],
"namespaceSecurity": "ENABLED",
"t10PiMode": "DISABLED",
"hostMode": "LINUX",
"hostModeOptions": [132, 133],
"virtualStorageMachineInformation": {
    "virtualStorageMachineId": "41010-VSP5100H-5500H",
    "storageSystemId": "41010",
    "model": "VSP 5100H, 5500H"
},
"resourceGroupId": 0,
"resourceGroupName": "meta_resource"
}

```

## Updating an NVM subsystem

You can update an NVM subsystem name.

### HTTP request syntax (URI)

```

PATCH https://ipAddress/v1/storage-systems/storageSystemId/nvm-subsystems/
nvmSubsystemId

```

### Request structure

```

{
  "name": ""
}

```

Parameter	Required	Type	Description
name	Yes	String	The NVM subsystem name.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":

```

```

    {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.

Parameter	Type	Description
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted Job	Returns the job information.
400	Bad request	The request contains a request payload that is not valid, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status code	HTTP name	Description
500	Internal Server Error	Some errors occurred inside the API server.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "name": "NVM_Subsystem_Example"
}
```

**Port management resources**

Request	Method	URI	Role
<a href="#">Listing ports (on page 382)</a>	GET	<i>/v1/storage-systems/ storageSystemId/storage- ports</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a port (on page 391)</a>	GET	<i>/v1/storage-systems/ storageSystemId/storage- ports/storagePortId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Updating a port (on page 399)</a>	POST	<i>/v1/storage-systems/ storageSystemId/storage- ports/storagePortId</i>	Storage administrator

Request	Method	URI	Role
Getting port login information (on page 406)	GET	/v1/storage-systems/ <i>storageSystemId</i> /ports-login- information	Storage administrator System administrator Security administrator Monitoring

## Listing ports

You can list all the ports in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/storage-ports
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources":
  [
    // For Fibre port
    {
      "storagePortId": "",
      "storageSystemId": "",
      "storageSystemName": "",
      "wwn": "",
      "attributes":
      [
        "",
        "",
        "",
        ""
      ],
      "speed": "",
      "type": "",
      "loopId": "",
      "topology": ""
    }
  ]
}
```

```

        "securitySwitchEnabled": ,
        "vsmPort": ,
        "iscsiPortInformation": ,
        "t10PiStatus": ,
        "portMode": ""
    },
    // For iSCSI port
    {
        "storagePortId": "",
        "storageSystemId": "",
        "storageSystemName": "",
        "wwn": null,
        "attributes":
        [
            "",
            "",
            "",
            ""
        ],
        "speed": "",
        "type": "",
        "loopId": "",
        "topology": "",
        "securitySwitchEnabled": ,
        "isVsmPort": ,
        "t10PiStatus":,
        "iscsiPortInformation": {
            "portIscsiName": "",
            "macAddress": "",
            "vlanUse": true,
            "vlanId": ,
            "ipv4Information": {
                "address": "",
                "subnetMask": "",
                "defaultGateway": ""
            },
            "ipv6Enabled": ,
            "ipv6Information": {
                "linklocalAddressingMode": "",
                "linklocalAddress": "",
                "globalAddressingMode": "",
                "globalAddress": "",
                "defaultGateway": ""
            },
        },
        "tcpPort": ,
        "selectiveAck": ,
        "delayedAck": ,
        "windowSizeInKBytes": ,
        "mtuSizeInBytes": ,
        "keepAliveTimerInSec": ,
        "isnsInformation": {

```

```

        "isnsServerIpAddress": "",
        "isnsServerPort": ,
    }
}
},
...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
storagePortId	String	ID of the storage port.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
wwn	String	World wide name of the storage port.
attributes	List	Attribute on the port. Valid values: TARGET_PORT, MCU_INITIATOR_PORT, RCU_TARGET_PORT, EXTERNAL_INITIATOR_PORT. All ports are universal ports.
speed	String	Speed of the port, such as 1G, 2G, 4G, 8G, 10G, 16G, 25G, 32G, 64G, or AUTO.
type	String	Type of port, such as FIBRE and ISCSI.
loopId	String	For disks that are connected using Fibre Channel-Arbitrated Loop (FC-AL or FC), the loop ID identifies the disk within its loop and is included in the disk name, which uniquely identifies the disk for the entire system. The loop ID is a hexadecimal number from 0x01 to 0xEF.  For iSCSI port, the loop ID is always 0x00.
topology	String	Topology of the port, such as the following. For Fibre port: <ul style="list-style-type: none"> <li>FABRIC_ON_ARB_LOOP</li> <li>FABRIC_ON_POINT_TO_POINT</li> <li>FABRIC_OFF_ARB_LOOP</li> <li>FABRIC_OFF_POINT_TO_POINT</li> </ul>



Parameter	Type	Description
		For iSCSI port: <ul style="list-style-type: none"> <li>▪ iSCSI</li> </ul>
securitySwitchEnabled	Boolean	Security status of the port. If the status is TRUE, security is enabled on the port.
vsmPort	Boolean	Whether the port is being used by a VSM.
iscsiPortInformation	Object	Displays port information related to iSCSI. NULL for FC port.
portIscsiName	String	Displays the iSCSI port name.
macAddress	String	Displays the MAC address of the port. NULL if the port does not support outputting the MAC address.
vlanUse	Boolean	Displays whether VLAN is enabled for this port. <ul style="list-style-type: none"> <li>▪ TRUE: VLAN is enabled</li> <li>▪ FALSE: VLAN is disabled</li> <li>▪ NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
vlanId	Number	Displays VLAN ID in decimal. NULL if VLAN ID is not set (vlanUse is FALSE).
ipv4Information	Object	Displays information related to IPv4.
address	String	Displays the IPv4 address.
subnetMask	String	Displays the IPv4 subnet address.
defaultGateway	String	Displays the IPv4 address of the gateway to the user for iSCSI communication.

Parameter	Type	Description
ipv6Enabled	Boolean	<p>Displays whether the port works with IPv6 address.</p> <ul style="list-style-type: none"> <li>▪ TRUE: The port works with both IPv4 and IPv6 addresses.</li> <li>▪ FALSE: The port works with IPv4 addresses.</li> <li>▪ NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
ipv6Information	Object	Displays information related to IPv6.
linklocalAddressingMode	Enum	<p>Displays the IPv6 link local addressing mode.</p> <ul style="list-style-type: none"> <li>▪ AUTO: The link local address is set automatically.</li> <li>▪ MANUAL: The specified link local address is set.</li> <li>▪ UNKNOWN: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
linklocalAddress	String	Displays the IPv6 link local address.
globalAddressingMode	Enum	<p>Displays the IPv6 global addressing mode.</p> <ul style="list-style-type: none"> <li>▪ AUTO: The link local address is set automatically.</li> <li>▪ MANUAL: The specified link local address is set.</li> <li>▪ UNKNOWN: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
globalAddress	String	Displays the IPv6 global address.
tcpPort	Number	<p>Displays the TCP port number for iSCSI communication.</p> <p>The value is between 1 and 65535.</p>

Parameter	Type	Description
selectiveAck	Boolean	<p>Displays whether the selective ACK mode is enabled.</p> <ul style="list-style-type: none"> <li>TRUE: The selective ACK is enabled.</li> <li>FALSE: The selective ACK is disabled.</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
delayedAck	Boolean	<p>Displays whether the delayed ACK mode is enabled.</p> <ul style="list-style-type: none"> <li>TRUE: The delayed ACK mode is enabled.</li> <li>FALSE: The delayed ACK mode is disabled.</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
windowSizeInKBytes	Number	<p>Displays the value of the window size for iSCSI communication.</p> <p>The value is in {64, 128, 256, 512, 1024} [KiB]</p>
mtuSizeInBytes	Number	<p>Displays the value of MTU for iSCSI communication.</p> <p>The value is in {1500/4500/900} [Byte]</p>
keepAliveTimerInSec	Number	<p>Displays the value of the keep-alive timer for iSCSI communication.</p> <p>The value is between 30 and 64800 [s].</p>
isnsServerInformation	Object	<p>Displays the iSNS server information.</p> <p>NULL if iSNS server mode is disabled for this port.</p>
isnsServerIpAddress	String	<p>Displays the address of the iSNS server.</p> <p>The format is IPv4 or IPv6.</p>

Parameter	Type	Description
isnsServerPort	Number	Displays the TCP port number of the iSNS server. The value is between 1 and 65535.
t10PiStatus	String	T10PI status of the port. For Fibre Port, valid values are: <ul style="list-style-type: none"> <li>ENABLED</li> <li>DISABLED</li> <li>UNSUPPORTED</li> </ul> Returns NULL for iSCSI.
portMode	Enum	Operation mode of the port. Valid values are: <ul style="list-style-type: none"> <li>SCSI: SCSI mode</li> <li>NVME: NVMe mode</li> </ul> Return NULL for iSCSI port.
total	Long	Total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example: <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/storage-systems/39305/storage-ports
```

**Example response**

```
{
  "resources":
  [
    // For Fibre port
    {
      "storagePortId": "CL1-D",
      "storageSystemId": "39305",
      "storageSystemName": "RN-SC-39305-HID_SVOS7.3-Gsd",
      "wwn": "50060E8012272F03",
      "attributes":
      [
        "TARGET_PORT",
        "MCU_INITIATOR_PORT",
        "RCU_TARGET_PORT",
        "EXTERNAL_INITIATOR_PORT"
      ],
      "speed": "AUTO",
      "type": "FIBRE",
      "loopId": "AC",
      "topology": "FABRIC_ON_POINT_TO_POINT",
      "securitySwitchEnabled": true,
      "vsmPort": false,
    }
  ]
}
```

```

        "iscsiPortInformation": null,
        "t10PiStatus": "ENABLED",
        "portMode": "SCSI"
    },
    // For iSCSI port
    {
        "storagePortId": "CL4-B",
        "storageSystemId": "39305",
        "storageSystemName": "RN-SC-39305-HID_SVOS7.3-Gsd",
        "wwn": null,
        "attributes":
        [
            "TARGET_PORT",
            "MCU_INITIATOR_PORT",
            "RCU_TARGET_PORT",
            "EXTERNAL_INITIATOR_PORT"
        ],
        "speed": "10G",
        "type": "ISCSI",
        "loopId": "0x00",
        "topology": "ISCSI",
        "securitySwitchEnabled": true,
        "isVsmPort": false,
        "t10PiStatus": null,
        "iscsiPortInformation": {
            "portIscsiName": "iqn.1994-04.com.example:rsd.h8s.i.125f77.4b",
            "macAddress": "00:1f:67:af:c1:0d",
            "vlanUse": true,
            "vlanId": 0,
            "ipv4Information": {
                "address": "192.168.116.237",
                "subnetMask": "255.255.0.0",
                "defaultGateway": "0.0.0.0"
            },
            "ipv6Enabled": true,
            "ipv6Information": {
                "linklocalAddressingMode": "AUTO",
                "linklocalAddress": "fe80::",
                "globalAddressingMode": "MANUAL",
                "globalAddress": "::",
                "defaultGateway": "::"
            },
            "tcpPort": 0,
            "selectiveAck": true,
            "delayedAck": true,
            "windowSizeInKBytes": 64,
            "mtuSizeInBytes": 1500,
            "keepAliveTimerInSec": 0,
            "isnsInformation": {
                "isnsServerIpAddress": "",
                "isnsServerPort": 0,

```

```

    }
  },
  ...
],
"total": 16,
"nextToken": null
}

```

## Getting a port

You can list port information for a storage port.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/storage-ports/storagePortId
```

Use the storage system ID as the *storageSystemId*.

Use the storage port ID as the *storagePortId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

// For Fibre port
{
  "storagePortId": "",
  "storageSystemId": "",
  "storageSystemName": "",
  "wwn": "",
  "attributes":
  [
    "",
    "",
    "",
    ""
  ],
  "speed": "",
  "type": "",
  "loopId": "",
  "topology": "",
  "securitySwitchEnabled": ,
  "vsmPort": ,
  "iscsiPortInformation":,
  "tl0PiStatus":,
  "portMode": ""
}

```

```

}

// For iSCSI port
{
    "storagePortId": "",
    "storageSystemId": "",
    "storageSystemName": "",
    "wwn": null,
    "attributes":
    [
        "",
        "",
        "",
        ""
    ],
    "speed": "",
    "type": "",
    "loopId": "",
    "topology": "",
    "securitySwitchEnabled": ,
    "isVsmPort": ,
    "tl0PiStatus": ,
    "iscsiPortInformation": {
        "portIscsiName": "",
        "macAddress": "",
        "vlanUse": true,
        "vlanId": ,
        "ipv4Information": {
            "address": "",
            "subnetMask": "",
            "defaultGateway": ""
        },
        "ipv6Enabled": ,
        "ipv6Information": {
            "linklocalAddressingMode": "",
            "linklocalAddress": "",
            "globalAddressingMode": "",
            "globalAddress": "",
            "defaultGateway": ""
        },
        "tcpPort": ,
        "selectiveAck": ,
        "delayedAck": ,
        "windowSizeInKBytes": ,
        "mtuSizeInBytes": ,
        "keepAliveTimerInSec": ,
        "isnsInformation": {
            "isnsServerIpAddress": "",
            "isnsServerPort": ,
        }
    }
}

```



```

    }
}

```

Parameter	Type	Description
storagePortId	String	ID of the storage port.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
wwn	String	World wide name of the storage port.
attributes	List	Attribute on the port. Valid values: TARGET_PORT, MCU_INITIATOR_PORT, RCU_TARGET_PORT, EXTERNAL_INITIATOR_PORT. All ports are universal ports.
speed	String	Speed of the port, such as 1G, 2G, 4G, 8G, 10G, 16G, 25G, 32G, 64G, or AUTO.
type	String	Type of port, such as FIBRE, SCSI, iSCSI, ENAS, FICON, ESCON, FCOE, HNASU, or HNASS.
loopId	String	For disks that are connected using Fibre Channel-Arbitrated Loop (FC-AL or FC), the loop ID identifies the disk within its loop and is included in the disk name, which uniquely identifies the disk for the entire system. The loop ID is a hexadecimal number from 0x01 to 0xEF.  For iSCSI port, the loop ID is always 0x00.
topology	String	Topology of the port, such as the following. For Fibre port: <ul style="list-style-type: none"> <li>FABRIC_ON_ARB_LOOP</li> <li>FABRIC_ON_POINT_TO_POINT</li> <li>FABRIC_OFF_ARB_LOOP</li> <li>FABRIC_OFF_POINT_TO_POINT</li> </ul> For iSCSI port: <ul style="list-style-type: none"> <li>ISCSI</li> </ul>
securitySwitchEnabled	Boolean	Security status of the port. If the status is TRUE, security is enabled on the port.
vsmPort	Boolean	Whether the port is being used by a VSM.

Parameter	Type	Description
iscsiPortInformation	Object	Displays port information related to iSCSI. NULL for FC port.
portIscsiName	String	Displays the iSCSI port name.
macAddress	String	Displays the MAC address of the port. NULL if the port does not support outputting the MAC address.
vlanUse	Boolean	Displays whether VLAN is enabled for this port. <ul style="list-style-type: none"> <li>TRUE: VLAN is enabled</li> <li>FALSE: VLAN is disabled</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
vlanId	Number	Displays VLAN ID in decimal. NULL if VLAN ID is not set (vlanUse is FALSE).
ipv4Information	Object	Displays information related to IPv4.
address	String	Displays the IPv4 address.
subnetMask	String	Displays the IPv4 subnet address.
defaultGateway	String	Displays the IPv4 address of the gateway to the user for iSCSI communication.
ipv6Enabled	Boolean	Displays whether the port works with IPv6 address. <ul style="list-style-type: none"> <li>TRUE: The port works with both IPv4 and IPv6 addresses.</li> <li>FALSE: The port works with IPv4 addresses.</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
ipv6Information	Object	Displays information related to IPv6.

Parameter	Type	Description
linklocalAddressingMode	Enum	<p>Displays the IPv6 link local addressing mode.</p> <ul style="list-style-type: none"> <li>AUTO: The link local address is set automatically.</li> <li>MANUAL: The specified link local address is set.</li> <li>UNKNOWN: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
linklocalAddress	String	Displays the IPv6 link local address.
globalAddressingMode	Enum	<p>Displays the IPv6 global addressing mode.</p> <ul style="list-style-type: none"> <li>AUTO: The link local address is set automatically.</li> <li>MANUAL: The specified link local address is set.</li> <li>UNKNOWN: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
globalAddress	String	Displays the IPv6 global address.
tcpPort	Number	<p>Displays the TCP port number for iSCSI communication.</p> <p>The value is between 1 and 65535.</p>
selectiveAck	Boolean	<p>Displays whether the selective ACK mode is enabled.</p> <ul style="list-style-type: none"> <li>TRUE: The selective ACK is enabled.</li> <li>FALSE: The selective ACK is disabled.</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>

Parameter	Type	Description
delayedAck	Boolean	Displays whether the delayed ACK mode is enabled. <ul style="list-style-type: none"> <li>TRUE: The delayed ACK mode is enabled.</li> <li>FALSE: The delayed ACK mode is disabled.</li> <li>NULL: Cannot get information from the storage system. Returns if the value is not defined in DKC and raidcom returns nothing. This case is extremely rare and cannot be expected to occur.</li> </ul>
windowSizeInKBytes	Number	Displays the value of the window size for iSCSI communication. The value is in {64, 128, 256, 512, 1024} [KiB]
mtuSizeInBytes	Number	Displays the value of MTU for iSCSI communication. The value is in {1500/4500/900} [Byte]
keepAliveTimerInSec	Number	Displays the value of the keep-alive timer for iSCSI communication. The value is between 30 and 64800 [s].
isnsServerInformation	Object	Displays the iSNS server information. NULL if iSNS server mode is disabled for this port.
isnsServerIpAddress	String	Displays the address of the iSNS server. The format is IPv4 or IPv6.
isnsServerPort	Number	Displays the TCP port number of the iSNS server. The value is between 1 and 65535.
t10PiStatus	String	T10PI status of the port. For Fibre Port, valid values are: <ul style="list-style-type: none"> <li>ENABLED</li> <li>DISABLED</li> <li>UNSUPPORTED</li> </ul> Returns NULL for iSCSI.

Parameter	Type	Description
portMode	Enum	Operation mode of the port. Valid values are: <ul style="list-style-type: none"> <li>▪ SCSI: SCSI mode</li> <li>▪ NVME: NVMe mode</li> </ul> Return NULL for iSCSI port.
total	Long	Total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example: <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>

### Return codes

Status code	HTTP name	Description
200	OK	Success
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/storage-systems/39305/storage-ports/CL1-D
```

**Example response**

```
// For Fibre port
{
  "storagePortId": "CL1-D",
  "storageSystemId": "39305",
  "storageSystemName": "RN-SC-39305-HID_SVOS7.3-Gsd",
  "wwn": "50060E8012272F03",
  "attributes":
  [
    "TARGET_PORT",
    "MCU_INITIATOR_PORT",
    "RCU_TARGET_PORT",
    "EXTERNAL_INITIATOR_PORT"
  ],
  "speed": "AUTO",
  "type": "FIBRE",
  "loopId": "AC",
  "topology": "FABRIC_ON_POINT_TO_POINT",
  "securitySwitchEnabled": true,
  "vsmPort": false,
  "iscsiPortInformation": null,
  "t10PiStatus": "ENABLED",
  "portMode": "SCSI"
}

// For iSCSI port
{
  "storagePortId": "CL4-B",
  "storageSystemId": "39305",
  "storageSystemName": "RN-SC-39305-HID_SVOS7.3-Gsd",
  "wwn": null,
  "attributes":
  [
    "TARGET_PORT",
    "MCU_INITIATOR_PORT",
    "RCU_TARGET_PORT",
    "EXTERNAL_INITIATOR_PORT"
  ],
  "speed": "10G",
  "type": "ISCSI",
  "loopId": "0x00",
  "topology": "ISCSI",
  "securitySwitchEnabled": true,
  "isVsmPort": false,
  "t10PiStatus": null,
  "iscsiPortInformation": {
```

```

    "portIscsiName": "iqn.1994-04.com.example:rsd.h8s.i.125f77.4b",
    "macAddress": "00:1f:67:af:c1:0d",
    "vlanUse": true,
    "vlanId": 0,
    "ipv4Information": {
      "address": "192.168.116.237",
      "subnetMask": "255.255.0.0",
      "defaultGateway": "0.0.0.0"
    },
    "ipv6Enabled": true,
    "ipv6Information": {
      "linklocalAddressingMode": "AUTO",
      "linklocalAddress": "fe80::",
      "globalAddressingMode": "MANUAL",
      "globalAddress": "::",
      "defaultGateway": "::"
    },
    "tcpPort": 0,
    "selectiveAck": true,
    "delayedAck": true,
    "windowSizeInKBytes": 64,
    "mtuSizeInBytes": 1500,
    "keepAliveTimerInSec": 0,
    "isnsInformation": {
      "isnsServerIpAddress": "",
      "isnsServerPort": 0,
    }
  }
}

```

## Updating a port

You can modify the port configuration settings for a specific storage port, such as topology, loop ID, security, and speed. For VSP G1000, VSP G1500, VSP F1500 or VSP 5000 series storage systems you can also change the port attribute.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/storage-ports/storagePortId
```

Use the storage system ID as the *storageSystemId*.

Use the storage port ID as the *storagePortId*.

### Request structure

The request body structure is shown below:

For updating an FC port:

```
{
  "topology": "",
  "loopId": "",
  "securitySwitchEnabled": "",
  "speed": "",
  "attribute": "",
  "portMode": ""
}
```

For updating an iSCSI port:

```
{
  "securitySwitchEnabled": "",
  "speed": "",
  "attribute": " ",
  "iscsiPortInformation": {
    "ipv6Enabled": ,
    "ipv4Information": {
      "address": "",
      "subnetMask": "",
      "defaultGateway": ""
    },
    "ipv6Information": {
      "linklocalAddressingMode": "",
      "linklocalAddress": "",
      "globalAddressingMode": "",
      "globalAddress": "",
      "defaultGateway": ""
    }
  }
}
```

Parameter	Required	Type	Description
topology	Yes	String	The topology of the port: <ul style="list-style-type: none"> <li>FABRIC_ON_ARB_LOOP</li> <li>FABRIC_ON_POINT_TO_POINT</li> <li>FABRIC_OFF_ARB_LOOP</li> <li>FABRIC_OFF_POINT_TO_POINT</li> </ul> Must be NULL for iSCSI port.



Parameter	Required	Type	Description
loopId	No	String	For disks that are connected using Fibre Channel-Arbitrated Loop (FC-AL or FC), the loop ID identifies the disk within its loop and is included in the disk name, which uniquely identifies the disk for the entire system. The loop ID is a hexadecimal number from 0x01 to 0xEF.  Must be NULL for iSCSI port.
securitySwitchEnabled	No	Boolean	Security status of the port. If the status is TRUE, security is enabled on the port.
speed	No	String	The speed of the port. Valid values: 1G, 2G, 4G, 8G, 10G, 16G, 25G, 32G, 64G, or AUTO.
attribute	No	String	Port attribute. Valid values: TARGET_PORT, RCU_TARGET_PORT, EXTERNAL_INITIATOR_PORT, MCU_INITIATOR_PORT, BIDIRECTIONAL_PORT.
portMode	No	Enum	Operation mode of the port. Valid values: <ul style="list-style-type: none"> <li>SCSI: SCSI mode</li> <li>NVME: NVMe mode</li> </ul>
iscsiPortInformation	No	Object	Updates iSCSI port information.  Must be NULL for FC port.
ipv6Enabled	No	Boolean	Updates whether the port works with IPv6. <ul style="list-style-type: none"> <li>TRUE: The port works with both IPv4 and IPv6 addresses.</li> <li>FALSE: The port works with IPv4 addresses.</li> </ul>
ipv4Information	No	Object	Specify if updating the IPv4 settings.  If NULL is specified, the IPv4 settings do not change.
address	No	String	Updates the IPv4 address.
subnetMask	No	String	Updates the IPv4 subnet mask.
defaultGateway	No	String	Updates the IPv4 address of the gateway for iSCSI communication.

Parameter	Required	Type	Description
ipv6Information	No	Object	Specify if updating the IPv6 settings. If NULL is specified, IPv6 settings are not changed.
linklocalAddressingMode	No	Enum	Updates the IPv6 link local addressing mode. <ul style="list-style-type: none"> <li>AUTO: The link local address is set automatically.</li> <li>MANUAL: The specified link local address is set.</li> </ul>
linklocalAddress	No	String	Updates the IPv6 link local address. Must be NULL if the addressing mode is AUTO. Must be specified if the addressing mode is MANUAL.
globalAddressingMode	No	Enum	Updates the IPv6 global addressing mode. <ul style="list-style-type: none"> <li>AUTO: The link local address is set automatically.</li> <li>MANUAL: Specified link local address is set.</li> </ul>
globalAddress	No	String	Updates the IPv6 global address. Must be NULL if the addressing mode is AUTO. Must be specified if the addressing mode is MANUAL.
defaultGateway	No	String	Updates the IPv6 address of the gateway for iSCSI communication.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
```

```

    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/storage-systems/440084/storage-ports/storagePortId
```

**Example request**

For updating an FC port:

```
{
  "topology": "FABRIC_ON_POINT_TO_POINT",
  "loopId": "EF",
  "securitySwitchEnabled": true,
  "speed": "AUTO",
  "attribute": "MCU_INITIATOR_PORT",
  "portMode": "SCSI"
}
```

For updating an iSCSI port:

```
{
  "securitySwitchEnabled": true,
  "speed": "10G",
}
```

```

"attribute": "TARGET_PORT",
"iscsiPortInformation": {
  "ipv6Enabled": true,
  "ipv4Information": {
    "address": "192.168.116.237",
    "subnetMask": "255.255.0.0",
    "defaultGateway": "0.0.0.0"
  },
  "ipv6Information": {
    "linklocalAddressingMode": "AUTO",
    "linklocalAddress": "fe80::",
    "globalAddressingMode": "AUTO",
    "globalAddress": "::",
    "defaultGateway": "::"
  }
}
}

```

## Getting port login information

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/ports-login-information
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

```

{
  "resources": [
    {
      "storageSystemId": "",
      "storagePortId": "",
      "type": "",
      "loginWwn": "",
      "loginIscsiName": ""
      "hostGroupId": "",
      "hostGroupName": "",
      "iscsiTargetName": "",
      "iscsiTargetAlias": "",
      "isLoggedIn":
    },
  ],
  "total": ,

```

```
"nextToken":
}
```

Parameter	Type	Description
storagePortId	String	ID of the storage port.
storageSystemId	String	ID of the storage system.
loginWwn	String	Login name for the WWN Fiber port.
loginIscsiName	String	Login name for the iSCSI port.
hostGroupId	String	The host group ID.
hostGroupName	String	The host group name.
iscsiTargetName	String	The iSCSI target name.
iscsiTargetAlias	String	The iSCSI target alias.
isLoggedIn	Boolean	Specifies whether the WWN/iSCSI Name is logged in. The value is false when the WWN/iSCSI Name is logged out or is not connected currently.
type	String	Type of port, such as FIBRE and ISCSI.
total	Long	Total number of resources.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>

**Return codes**

Status code	HTTP name	Description
200	OK	Success
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/storage-systems/410209/ports-login-information
```

**Example response**

```
{
  "resources": [
    {
      "storageSystemId": "410209",
      "storagePortId": "CL7-B",
      "type": "FIBRE",
      "loginWwn": "100000051EEE059C",
      "loginIscsiName": null
      "hostGroupId": "CL7-B-1",
      "hostGroupName": "hg-07-b",
      "iscsiTargetName": null,
      "iscsiTargetAlias": null,
      "isLoggedIn": true
    },
    {
      "storageSystemId": "410209",
      "storagePortId": "CL1-B",
      "type": "FIBRE",
      "loginWwn": "50060E80123ABF05",
      "loginIscsiName": null
      "hostGroupId": "CL1-B-1",
      "hostGroupName": "hg-01-b",
```



```

        "iscsiTargetName": null,
        "iscsiTargetAlias": null,
        "isLoggedIn": true
    },
    {
        "storageSystemId": "410209",
        "storagePortId": "CL5-B",
        "type": "FIBRE",
        "loginWwn": "50060E801227E135",
        "loginIscsiName": null
        "hostGroupId": "CL5-B-1",
        "hostGroupName": "hg-05-b",
        "iscsiTargetName": null,
        "iscsiTargetAlias": null,
        "isLoggedIn": true
    },
    {
        "storageSystemId": "410209",
        "storagePortId": "CL3-B",
        "type": "FIBRE",
        "loginWwn": "50060E80123ABF25",
        "loginIscsiName": null
        "hostGroupId": "CL3-B-1",
        "hostGroupName": "hg-03-b",
        "iscsiTargetName": null,
        "iscsiTargetAlias": null,
        "isLoggedIn": true
    }
    ],
    "total": 4,
    "nextToken": null
}

```

## Tier management resources

Request	Method	URI	Role
<a href="#">Listing tiers (on page 410)</a>	GET	/v1/templates/tiers	Storage administrator System administrator Security administrator Monitoring

Request	Method	URI	Role
<a href="#">Updating a tier (on page 413)</a>	POST	/v1/templates/tiers/ <i>tierId</i>	System administrator

## Listing tiers

You can display a list of all the tiers that are defined in Ops Center Administrator. The list is sorted by the tier ID.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/templates/tiers
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "tiers": [
    {
      "id": "",
      "tier": "",
      "subTiers": [
        {
          "diskType": "",
          "speed":
        }
      ],
      "priority":
    }
  ]
}
```

Parameter	Type	Description
tiers	List	Collection of tier definitions.
id	String	ID of the tier.
tier	String	Custom name of the tier, such as Diamond, Platinum, Gold, Silver, Bronze, External, or SDS.

Parameter	Type	Description
subTiers	List	List of items that form the sub tier.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Speed of the disk, measured in revolutions per minute. For FMD, SSD, SSD(RI), SSD NVMe, FMD DC2, SCM NVMe, or SSD(QLC), the speed is 0.
priority	Integer	Priority of the tier. 1 equals the highest tier priority.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/templates/tiers
```

### Example response

```
"tiers": [
  {
    "id": "6",
    "tier": "Diamond",
```

```

    "subTiers": [
      {
        "diskType": "SCM NVMe",
        "speed": 0
      }
    ],
    "priority": 1
  },
  {
    "id": "1",
    "tier": "Platinum",
    "subTiers": [
      {
        "diskType": "SSD",
        "speed": 0
      },
      {
        "diskType": "FMD DC2",
        "speed": 0
      }
    ],
    "priority": 2
  },
  {
    "id": "2",
    "tier": "Gold",
    "subTiers": [
      {
        "diskType": "SAS",
        "speed": 15000
      }
    ],
    "priority": 3
  },
  {
    "id": "3",
    "tier": "Silver",
    "subTiers": [
      {
        "diskType": "SAS",
        "speed": 10000
      }
    ],
    "priority": 4
  },
  {
    "id": "4",
    "tier": "Bronze",
    "subTiers": [
      {
        "diskType": "SAS",

```

```

        "speed": 7200
      }
    ],
    "priority": 5
  },
  {
    "id": "5",
    "tier": "External",
    "subTiers": [],
    "priority": 6
  },
  {
    "id": "7",
    "tier": "SDS",
    "subTiers": [],
    "priority": 7
  }
]

```

## Updating a tier

You can change the name of a tier.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/templates/tiers/tierId
```

Use the ID of the tier for the *tierId*.

### Request structure

The request body structure is shown below:

```

{
  "tierName":
}

```

Parameter	Required	Type	Description
tierName	Yes	String	The new name of the tier. The maximum name length is 256 characters. The name cannot start with a dash or underscore.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.

Status code	HTTP name	Description
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/templates/tiers/5
```

**Example request**

```
{
  "tierName":    "NewName"
}
```



---

## Chapter 3: Server management resources

This module describes the server management operations.

Request	Method	URI	Role
<a href="#">Listing servers (on page 419)</a>	GET	/v1/compute/servers	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a server (on page 428)</a>	GET	/v1/compute/servers/ <i>serverId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting servers summary (on page 436)</a>	GET	/v1/compute/servers/ summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Adding servers (on page 437)</a>	POST	/v1/compute/servers	System administrator
<a href="#">Updating a server (on page 445)</a>	POST	/v1/compute/servers/ <i>serverId</i>	System administrator
<a href="#">Deleting a server (on page 448)</a>	DELETE	/v1/compute/servers/ <i>serverId</i>	System administrator
<a href="#">Deleting multiple servers (on page 451)</a>	POST	/v1/compute/servers/delete	System administrator

Request	Method	URI	Role
<a href="#">Updating world wide port names (on page 455)</a>	POST	/v1/compute/servers/ <i>serverId</i> /update-wwpns	System administrator
<a href="#">Listing attached volumes (on page 460)</a>	GET	/v1/compute/servers/attached-volumes/?q= <i>serverId:serverId</i> AND <i>storageSystemId:storageSystemId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Updating iSCSI settings (on page 475)</a>	POST	/v1/compute/servers/ <i>serverId</i> /update-iscsi-settings	System administrator
<a href="#">Updating Host NVMe Qualified Names (on page 481)</a>	POST	/v1/compute/servers/ <i>serverId</i> /update-nqns	System Administrator
<a href="#">Scanning host groups (on page 484)</a>	POST	/v1/compute/servers/scan-host-groups	System administrator
<a href="#">Getting a list of server groups (on page 488)</a>	GET	/v1/compute/server-groups	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a server group (on page 491)</a>	GET	/v1/compute/server-groups/ <i>serverGroupId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing volumes attached to servers in a server group (on page 493)</a>	GET	/v1/compute/server-groups/ <i>serverGroupId</i> /volumes	Storage administrator System administrator Security administrator

Request	Method	URI	Role
			Monitoring
<a href="#">Creating a server group (on page 510)</a>	POST	/v1/compute/server-groups	System administrator
<a href="#">Updating a server group (on page 514)</a>	POST	/v1/compute/server-groups/ <i>serverGroupId</i>	System administrator
<a href="#">Adding servers to a server group (on page 517)</a>	POST	/v1/compute/server-groups/ <i>serverGroupId</i> /add-servers	System administrator
<a href="#">Deleting a server group (on page 521)</a>	DELETE	/v1/compute/server-groups/ <i>serverGroupId</i>	System administrator
<a href="#">Removing multiple servers from a server group (on page 525)</a>	POST	/v1/compute/server-groups/ <i>serverGroupId</i> /remove-servers	System administrator
<a href="#">Using existing LUN paths (on page 529)</a>	POST	/v1/compute/servers/create-similar-paths	System administrator

## Listing servers

You can display a list of servers.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/compute/servers
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources": [
    // For FC Server
    {
      "serverId": "",
      "protocol": "",
      "serverName": "",
      "description": "",
      "ipAddress": "",
      "wwpns": [
        ""
      ]
    }
  ]
}
```

```

    ],
    "wwpnsWithUserDefinedName": [
        {
            "wwpn": "",
            "wwpnUserDefinedName": ""
        }
    ],
    "iscsiNames": [],
    "iscsiNamesWithUserDefinedName": [],
    "osType": "",
    "chapUser": "",
    "attachedVolumeCount": ,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "",
        "hasFailures":
    },
    "dpStatus": "",
    "storageSystemIds": [
        ""
    ],
    "storageSystems": [
        {
            "id": "",
            "name": ""
        }
    ],
    "hostNqns": []
},
// For iSCSI Server
{
    "serverId": "",
    "protocol": "",
    "serverName": "",
    "description": "",
    "ipAddress": "",
    "wwpns": [],
    "wwpnsWithUserDefinedName": [],
    "iscsiNames":
    [
        ""
    ],
    "iscsiNamesWithUserDefinedName": [
        {
            "iscsiName": "",
            "iscsiNameUserDefinedName": ""
        }
    ],
    "osType": "",
    "chapUser": "",
    "attachedVolumeCount": ,

```

```

        "dataProtectionSummary": {
            "replicationType":
                [
                ],
            "protection": "",
            "hasFailures":
        },
        "dpStatus": "",
        "storageSystemIds": [
            ""
        ],
        "storageSystems": [
            {
                "id": "",
                "name": ""
            }
        ],
        "hostNqns": []
    },
    // For NVMe over FC Server
    {
        "serverId": "",
        "protocol": "",
        "serverName": "",
        "description": "",
        "ipAddress": "",
        "wwpns": [
            ""
        ],
        "wwpnsWithUserDefinedName": [
            {
                "wwpn": "",
                "wwpnUserDefinedName": ""
            }
        ],
        "iscsiNames": [],
        "iscsiNamesWithUserDefinedName": [],
        "osType": "",
        "chapUser": "",
        "attachedVolumeCount": ,
        "dataProtectionSummary": {
            "replicationType": [],
            "protection": "",
            "hasFailures":
        },
        "dpStatus": "",
        "storageSystemIds": [
            ""
        ],
        "storageSystems": [
            {

```

```

        "id": "",
        "name": ""
    }
],
"hostNqns": [
    {
        "hostNqn": ""
    }
]
}
]
"total": ,
"nextToken":
}

```

Parameter	Type	Description
dpStatus	String	Data protection status on the server. If data protection succeeded, the status is success. If data protection failed for any volume, the status is failure.
storageSystemIds	List	List of storage serial numbers attached to the server.
storageSystems	List	List of the storage systems attached to the server.
id	String	Storage system serial number attached to the server.
name	String	Storage system name attached to the server.
description	String	Description of the resource.
ipAddress	String	IP address of the resource.
wwpns	List	List of World Wide Port Names formatted as a 16-digit hexadecimal number.  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the wwpn parameter of the wwpnsWithUserDefinedName object instead.
wwpnsWithUserDefinedName	Object	List of combinations of World Wide Port Name and user-defined name.

Parameter	Type	Description
wwpn	String	World Wide Port Name formatted as a 16-digit hexadecimal number.
wwpnUserDefinedName	String	User-defined name for World Wide Port Name.
iscsiNamesWithUserDefinedName	Object	List of combinations of iSCSI name and user-defined name.
iscsiName	String	iSCSI name formatted as iSCSI qualified name (IQN) or extended unique identified (EUI) format.
iscsiNameUserDefinedName	String	User-defined name for iSCSI name.
osType	String	List of supported operating systems on the server.
attachedVolumeCount	Integer	Total number of the server attached volumes.
dataProtectionSummary	List	List of the data protection attributes.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> </ul>
protection	String	Data protection type. Valid values: PROTECTED, UNPROTECTED, or PARTIAL. <ul style="list-style-type: none"> <li>▪ if there are no volumes attached to a server or all of the attached volumes are unprotected, the status is UNPROTECTED.</li> <li>▪ If all the volumes that are attached to a server are PRIMARY volumes, the status is PROTECTED.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ If all the volumes that are attached to a server are SECONDARY volumes, the status is PARTIAL.</li> <li>▪ If its mix of primary, secondary, and unprotected volumes, the status is PARTIAL.</li> </ul>
hasFailures	Boolean	Whether the volume has replication failures.
serverName	String	Name of the server.
serverId	Integer	ID of the server.
protocol	Enum	Server HBA protocol. <ul style="list-style-type: none"> <li>▪ FIBRE: For FC HBA server.</li> <li>▪ ISCSI: For iSCSI HBA server.</li> <li>▪ FCNVME: For NVMe over FC server.</li> </ul>
iscsiNames	List	List of iSCSI names formatted as iSCSI qualified name (IQN) or extended unique identified (EUI) format. <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the iscsiName parameter of the iscsiNamesWithUserDefinedName object instead.</p>
chapUser	String	Displays the CHAP user name of the iSCSI initiator (host). NULL for FC servers.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target (host). NULL for FC servers.
hostNqns	List	List of NVMe Qualified Names of the host.
hostNqn	string	NVMe Qualified Name of the host.
total	Long	Total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of



Parameter	Type	Description
		resources, append a question mark (?) and "nextToken= ", and then the token. Example:  https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTTUNoSXVYNlFPUS1jZzswOw==

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/compute/servers
```

### Example response

```
{
  "resources": [
    // For FC Server
    {
```

```

    "serverId": 2,
    "protocol": "FIBRE",
    "serverName": "ESX-6425",
    "description": "ESX-6425",
    "ipAddress": "172.17.64.25",
    "wwpns": [
        "5000087000536424"
    ],
    "wwpnsWithUserDefinedName": [
        {
            "wwpn": "5000087000536424",
            "wwpnUserDefinedName": "ESX-6425_HBA1"
        }
    ],
    "iscsiNames": [],
    "iscsiNamesWithUserDefinedName": [],
    "osType": "VMWARE_EX",
    "chapUser": null,
    "attachedVolumeCount": 0,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "UNPROTECTED",
        "hasFailures": false
    },
    "dpStatus": "Success",
    "storageSystemIds": [
        "41020"
    ],
    "storageSystems": [
        {
            "id": "41020",
            "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
        }
    ],
    "hostNqns": []
},
// For iSCSI Server
{
    "serverId": 3,
    "protocol": "ISCSI",
    "serverName": "ESX-6426",
    "description": "ESX-6426",
    "ipAddress": "172.17.64.26",
    "wwpns": [],
    "wwpnsWithUserDefinedName": [],
    "iscsiNames": [
        "iqn.esx.6426"
    ],
    "iscsiNamesWithUserDefinedName": [
        {
            "iscsiName": "iqn.esx.6426",

```

```

        "iscsiNameUserDefinedName": "ESX-6426_HBA1"
    }
},
"osType": "WIN_EX",
"chapUser": "user1",
"attachedVolumeCount": 0,
"dataProtectionSummary": {
    "replicationType": [],
    "protection": "UNPROTECTED",
    "hasFailures": false
},
"dpStatus": "Success",
"storageSystemIds": [
    "41020"
],
"storageSystems": [
    {
        "id": "41020",
        "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
    }
],
"hostNqns": []
},
// For NVMe over FC Server
{
    "serverId": 4,
    "protocol": "FCNVME",
    "serverName": "NVM-1234",
    "description": "NVM-1234",
    "ipAddress": "172.17.64.27",
    "wwpns": [
        "240000102AB8620A"
    ],
    "wwpnsWithUserDefinedName": [
        {
            "wwpn": "240000102AB8620A",
            "wwpnUserDefinedName": ""
        }
    ],
    "iscsiNames": [],
    "iscsiNamesWithUserDefinedName": [],
    "osType": "VMWARE",
    "chapUser": null,
    "attachedVolumeCount": 0,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "UNPROTECTED",
        "hasFailures": false
    },
    "dpStatus": "Success",
    "storageSystemIds": [

```

```

        "41020"
      ],
      "storageSystems": [
        {
          "id": "41020",
          "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
        }
      ],
      "hostNqns": [
        {
          "hostNqn": "nqn.1234.abcd"
        }
      ]
    }
  ],
  "total": 3,
  "nextToken": null
}

```

## Getting a server

You can display details on a specific server.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/compute/servers/serverId
```

Use the ID of the server as the *serverId*.

### Request structure

Not applicable.

### Response structure

```

// For FC Server
{
  "serverId": "",
  "protocol": "",
  "serverName": "",
  "description": "",
  "ipAddress": "",
  "wwpns": [
    ""
  ],
  "wwpnsWithUserDefinedName": [
    {
      "wwpn": "",
      "wwpnUserDefinedName": ""
    }
  ]
}

```

```

    }
  ],
  "iscsiNames": [],
  "iscsiNamesWithUserDefinedName": [],
  "osType": "",
  "chapUser": "",
  "attachedVolumeCount": ,
  "dataProtectionSummary": {
    "replicationType": [],
    "protection": "",
    "hasFailures":
  },
  "dpStatus": "",
  "storageSystemIds": [
    ""
  ],
  "storageSystems": [
    {
      "id": "",
      "name": ""
    }
  ],
  "hostNqns": []
}
// For iSCSI Server
{
  "serverId": "",
  "protocol": "",
  "serverName": "",
  "description": "",
  "ipAddress": "",
  "wwpns": [],
  "wwpnsWithUserDefinedName": [],
  "iscsiNames":
  [
    ""
  ],
  "iscsiNamesWithUserDefinedName": [
    {
      "iscsiName": "",
      "iscsiNameUserDefinedName": ""
    }
  ],
  "osType": "",
  "chapUser": "",
  "attachedVolumeCount": ,
  "dataProtectionSummary": {
    "replicationType":
    [
  ],
    "protection": "",

```

```

        "hasFailures":
    },
    "dpStatus": "",
    "storageSystemIds": [
        ""
    ],
    "storageSystems": [
        {
            "id": "",
            "name": ""
        }
    ],
    "hostNqns": []
}
// For NVMe over FC Server
{
    "serverId": "",
    "protocol": "",
    "serverName": "",
    "description": "",
    "ipAddress": "",
    "wwpns": [
        ""
    ],
    "wwpnsWithUserDefinedName": [
        {
            "wwpn": "",
            "wwpnUserDefinedName": ""
        }
    ],
    "iscsiNames": [],
    "iscsiNamesWithUserDefinedName": [],
    "osType": "",
    "chapUser": "",
    "attachedVolumeCount": ,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "",
        "hasFailures":
    },
    "dpStatus": "",
    "storageSystemIds": [
        ""
    ],
    "storageSystems": [
        {
            "id": "",
            "name": ""
        }
    ],
    "hostNqns": [

```

```

{
  "hostNqn": ""
}
]
}

```

Parameter	Type	Description
dpStatus	String	Data protection status on the server. If data protection succeeded, the status is success. If data protection failed for any volume, the status is failure.
storageSystemIds	List	List of storage serial numbers attached to the server.
storageSystems	List	List of the storage systems attached to the server.
id	String	Storage system serial number attached to the server.
name	String	Storage system name attached to the server.
description	String	Brief description of the server.
ipAddress	String	IP address of the resource.
wwpns	List	List of World Wide Port Names formatted as a 16-digit hexadecimal number.  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the wwpn parameter of the wwpnsWithUserDefinedName object instead.
wwpnsWithUserDefinedName	Object	List of combinations of World Wide Port Name and user-defined name.
wwpn	String	World Wide Port Name formatted as a 16-digit hexadecimal number.
wwpnUserDefinedName	String	User-defined name for World Wide Port Name.
iscsiNamesWithUserDefinedName	Object	List of combinations of iSCSI name and user-defined name.
iscsiName	String	iSCSI name formatted as iSCSI qualified name (IQN) or extended unique identified (EUI) format.

Parameter	Type	Description
iscsiNameUserDefinedName	String	User-defined name for iSCSI name.
osType	String	List of supported operating systems on the server.
attachedVolumeCount	Integer	Total number of the server attached volumes.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> </ul>
protection	String	Data protection type. Valid values: P-VOL, S-VOL, or UNPROTECTED.
hasFailures	Boolean	Whether or not the volume has replication failures.
serverName	String	Name of the server.
serverId	Integer	ID of the server.
protocol	Enum	Server HBA protocol. <ul style="list-style-type: none"> <li>▪ FIBRE: For FC HBA server.</li> <li>▪ ISCSI: For iSCSI HBA server.</li> <li>▪ FCNVME: For NVMe over FC server.</li> </ul>
iscsiNames	List	List of iSCSI names formatted as iSCSI qualified name (IQN) or extended unique identified (EUI) format. <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the iscsiName parameter of the iscsiNamesWithUserDefinedName object instead.</p>



Parameter	Type	Description
chapUser	String	Displays the CHAP user name of the iSCSI initiator (host). NULL for FC servers.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target (host). NULL for FC servers.
hostNqns	List	List of NVMe Qualified Names of the host.
hostNqn	String	NVMe Qualified Name of the host.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/compute/servers/2
```

**Example response**

```
// For FC Server
{
  "serverId": 2,
  "protocol": "FIBRE",
  "serverName": "ESX-6425",
  "description": "ESX-6425",
  "ipAddress": "172.17.64.25",
  "wwpns": [
    "5000087000536424"
  ],
  "wwpnsWithUserDefinedName": [
    {
      "wwpn": "5000087000536424",
      "wwpnUserDefinedName": "ESX-6425_HBA1"
    }
  ],
  "iscsiNames": [],
  "iscsiNamesWithUserDefinedName": [],
  "osType": "VMWARE_EX",
  "chapUser": null,
  "attachedVolumeCount": 1,
  "dataProtectionSummary": {
    "replicationType": [],
    "protection": "UNPROTECTED",
    "hasFailures": false
  },
  "dpStatus": "Success",
  "storageSystemIds": [
    "41020"
  ],
  "storageSystems": [
    {
      "id": "41020",
      "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
    }
  ],
  "hostNqns": []
}

// For iSCSI Server
{
  "serverId": 3,
  "protocol": "ISCSI",
  "serverName": "ESX-7425",
  "description": "ESX-7425",
  "ipAddress": "172.17.74.25",
  "wwpns": [],
  "wwpnsWithUserDefinedName": [],
  "iscsiNames": [
    "iqn.esx.7425"
  ]
}
```

```

    ],
    "iscsiNamesWithUserDefinedName": [
        {
            "iscsiName": "iqn.esx.6426",
            "iscsiNameUserDefinedName": "ESX-6426_HBA1"
        }
    ],
    "osType": "LINUX",
    "chapUser": "user1",
    "attachedVolumeCount": 1,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "UNPROTECTED",
        "hasFailures": false
    },
    "dpStatus": "Success",
    "storageSystemIds": [
        "41020"
    ],
    "storageSystems": [
        {
            "id": "41020",
            "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
        }
    ],
    "hostNqns": []
}
// For NVMe over FC Server
{
    "serverId": 4,
    "protocol": "FCNVME",
    "serverName": "NVM-1234",
    "description": "NVM-1234",
    "ipAddress": "172.17.64.27",
    "wwpns": [
        "240000102AB8620A"
    ],
    "wwpnsWithUserDefinedName": [
        {
            "wwpn": "240000102AB8620A",
            "wwpnUserDefinedName": ""
        }
    ],
    "iscsiNames": [],
    "iscsiNamesWithUserDefinedName": [],
    "osType": "VMWARE",
    "chapUser": null,
    "attachedVolumeCount": 0,
    "dataProtectionSummary": {
        "replicationType": [],
        "protection": "UNPROTECTED",

```

```

    "hasFailures": false
  },
  "dpStatus": "Success",
  "storageSystemIds": [
    "41020"
  ],
  "storageSystems": [
    {
      "id": "41020",
      "name": "RN-SC-41020-HID_SVOS7.3-Gsd"
    }
  ],
  "hostNqns": [
    {
      "hostNqn": "nqn.1234.abcd"
    }
  ]
}

```

## Getting servers summary

You can display a list of servers by operating system type.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/compute/servers/summary
```

### Request structure

Not applicable.

### Response structure

```

{
  "osTypeCount":
  {
    "WIN":
  },
  "totalHost":
}

```

Parameter	Type	Description
osTypeCount	List	List of supported operating systems on the server.

Parameter	Type	Description
totalHost	Integer	Total number of host operating systems.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.111/v1/compute/servers/summary
```

### Example response

```
{
  "osTypeCount":
  {
    "WIN": 1
  },
  "totalHost": 1
}
```

## Adding servers

You can add servers with information about the server name, IP address, short description, World Wide Port Name (WWPN), and the supported OS types.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/compute/servers
```

**Request Structure**

The request body structure is shown below:

```
{
  "servers": [
    // For FC servers
    {
      "protocol": "FIBRE",
      "serverName": "",
      "ipAddress": "",
      "osType": "",
      "wwpns": [],
      "wwpnsWithUserDefinedName": [
        {
          "wwpn": "",
          "wwpnUserDefinedName": ""
        }
      ],
      "description": ""
    },
    // For iSCSI servers
    {
      "protocol": "ISCSI",
      "serverName": "",
      "ipAddress": "",
      "osType": "",
      "iscsiNames": [],
      "iscsiNamesWithUserDefinedName": [
        {
          "iscsiName": "",
          "iscsiNameUserDefinedName": ""
        }
      ],
      "description": "",
      "chapUser": {
        "userName": "",
        "secret": ""
      }
    },
    // For NVMe over FC servers
    {
      "protocol": "FCNVME",
      "serverName": "",
      "ipAddress": "",
      "osType": "",
      "hostNqns": [
```

```

    {
      "hostNqn": ""
    }
  ],
  "wwpnsWithUserDefinedName": [
    {
      "wwpn": "",
      "wwpnUserDefinedName": ""
    }
  ],
  "description": ""
}
]
}

```

Parameter	Required	Type	Description
serverName	Yes	String	Name of the server. Enter up to 256 alphanumeric characters. The only special characters that are supported are the hyphen ("-") and underscore ("_") .
ipAddress	No	String	IP address of the resource.
osType	Yes	String	Supported OS of the host. LINUX, VMWARE, VMWARE_EX, AIX can be specified if FCNVME is specified as the protocol.
hostNqns	No	List	List of NVMe Qualified Names of the host. hostNqns is required if FCNVME is specified as the protocol.
hostNqn	No	String	NVMe Qualified Name of the host.
wwpns	No	List	List of World Wide Port Names formatted as a 16 digit hexadecimal number. wwpnsWithUserDefinedName or wwpns is required if FIBRE is specified as the protocol.
wwpnsWithUserDefinedName	No	Object	List of combinations of World Wide Port Name and user-defined name. wwpnsWithUserDefinedName or wwpns is required if FIBRE is specified as the protocol, and can be specified optionally if FCNVME is specified.

Parameter	Required	Type	Description
wwpn	No	String	World Wide Port Names formatted as a 16-digit hexadecimal number. wwpn is required if wwpnsWithUserDefinedName is specified.
wwpnUserDefinedName	No	String	User-defined name for World Wide Port Name. Enter up to 64 alphanumeric characters, periods(.), at marks (@), underscore (_) and hyphens(-) in the name, but it must not start with a hyphen.
iscsiNamesWithUserDefinedName	No	Object	List of combinations of iSCSI name and user-defined name. iscsiNamesWithUserDefinedName or iscsiNames is required if iSCSI is specified as the protocol.
iscsiName	No	String	iSCSI names formatted as iSCSI qualified name (IQN) or extended unique identified (EUI) format. iscsiName is required if iscsiNamesWithUserDefinedName is specified.
iscsiNameUserDefinedName	No	String	User-defined name for iSCSI name. Enter up to 32 alphanumeric characters, periods(.), at marks (@), underscore (_) and hyphens(-) in the name, but it must not start with a hyphen.
description	No	String	Brief description of the server, up to 128 characters.
protocol	No	Enum	Server HBA protocol to create with the below values. <ul style="list-style-type: none"> <li>▪ FIBRE: For FC HBA server.</li> <li>▪ iSCSI: For iSCSI HBA server.</li> <li>▪ FCNVME: For NVMe over FC server.</li> </ul> For payload consistency from v2.2 or older, a payload is processed as FC if not specified.
iscsiNames	No	List	List of iSCSI names formatted as IQN or EUI format. iscsiNamesWithUserDefinedName or iscsiNames is required if iSCSI is specified as the protocol.



Parameter	Required	Type	Description
chapUser	No	Object	CHAP user name and secret of the iSCSI initiators (hosts). iSCSI targets (storages) authenticate the initiators with this information.
userName	No	String	User name of the new CHAP user. Both user name and secret are required when specifying a CHAP user.
secret	No	String	User secret of the new CHAP user. Both user name and secret are required when specifying a CHAP user.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
```

```
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/compute/servers
```

### Example request

```
{
  "servers": [
    // For FC servers
    {
      "protocol": "FIBRE",
```

```

    "serverName": "Windows_Server",
    "ipAddress": "10.20.90.243",
    "osType": "WIN_EX",
    "wwpnsWithUserDefinedName": [
      {
        "wwpn": "100000053326f721",
        "wwpnUserDefinedName": "Windows_Server_HBA1"
      }
    ],
    "description": ""
  },
  // For iSCSI servers
  {
    "protocol": "ISCSI",
    "serverName": "Windows_Server",
    "ipAddress": "10.20.90.243",
    "osType": "WIN_EX",
    "iscsiNamesWithUserDefinedName": [
      {
        "iscsiName": "iqn.esx.243",
        "iscsiNameUserDefinedName": "Windows_Server_HBA1"
      }
    ],
    "description": "",
    "chapUser": {
      "userName": "user1",
      "secret": "123456789012"
    }
  },
  // For NVMe over FC servers
  {
    "protocol": "FCNVME",
    "serverName": "Windows_Server",
    "ipAddress": "10.20.90.243",
    "osType": "WIN_EX",
    "hostNqns": [
      {
        "hostNqn": "nqn.yyy"
      }
    ],
    "wwpnsWithUserDefinedName": [
      {
        "wwpn": "100000053326f721",
        "wwpnUserDefinedName": "Windows_Server_HBA1"
      }
    ],
    "description": ""
  }
]
}

```

## Updating a server

You can update the server name, IP address, short description, or supported OS types.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/servers/serverId
```

Use the ID of the server as the *serverId*.

### Request structure

The request body structure is shown below:

```
{
  "serverName": "",
  "ipAddress": "",
  "osType": "",
  "description": ""
}
```

Parameter	Required	Type	Description
serverName	Yes	String	Name of the server. Enter up to 256 alphanumeric characters. The only special characters that are supported are the hyphen ("-") and underscore ("_") .
ipAddress	No	String	IP address of the resource.
osType	Yes	String	List of supported OS.
description	No	String	Brief description of the server, up to 128 characters.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  }
}
```

```

    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "serverName": "Win-MD",
  "ipAddress": "172.17.91.21",
  "osType": "Win_EX",
  "description": "Updating server info"
}
```

## Deleting a server

You can delete a server if there are no volumes attached to the server. You should verify that no volumes are attached to the server before you delete the server.

### HTTP request syntax (URI)

```
DELETE https://ipAddress/v1/compute/servers/serverId
```

Use the ID of the server as the *serverId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate": ,
}
```



```

    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

#### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

```
{
  "jobId": "104f169c-89f0-4f3c-a188-242593005a86",
  "title": {
    "text": "Delete server",
    "messageCode": "DeleteServerJobTitleMessage",
    "parameters": {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1456970658084,
  "endDate": null,
  "parentJobId": null,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/104f169c-89f0-4f3c-a188-242593005a86"
    }
  ],
  "tags": [
  ],
  "isSystem": false
}
```

## Deleting multiple servers

You can delete multiple servers.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/compute/servers/delete
```

**Request structure**

The request body structure is shown below:

```
{
  "serverIds": [],
  "forceDelete":
}
```

Parameter	Required	Type	Description
serverIds	Yes	List	The list of server IDs to be deleted. The server ID type is integer.
forceDelete	No	Boolean	Specifies whether to delete the servers when volumes are attached to them. Valid values are True or False. The default value is False.

**Example**

```
{
  "serverIds": [1, 3],
  "forceDelete": true
}
```

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
```

```

"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.

Parameter	Type	Description
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Response Code

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example response

```
{
  "jobId": "707929b6-1b1f-4a19-8bfa-62b303c6390d",
  "title": {
    "text": "Delete servers",
    "messageCode": "DeleteServersJobTitleMessage",
    "parameters": {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1576630177992,
  "endDate": null,
  "parentJobId": null,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/707929b6-1b1f-4a19-8bfa-62b303c6390d"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

## Updating world wide port names

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/servers/serverId/update-wwpns
```

Parameter	Required	Type	Description
serverId	Yes	Integer	ID of the server.

### Request structure

```
{
  "updateAttachedVolumes" : ,
  "updateZones" : ,
  "updates" : [
    {
      "currentValue": "",
      "newValue": "",
      "newUserDefinedName": "",
      "reference": ""
    }
  ],
}
```

Parameter	Required	Type	Description
updateAttachedVolumes	Yes	Boolean	Use <code>TRUE</code> to update WWN of already attached volumes.
updateZones	Yes	Boolean	Use <code>TRUE</code> to update WWN of already attached volumes.
currentValue	Yes	String	The current value for the WWN to be overwritten by <code>newValue</code> .  If <code>NULL</code> is specified, just add <code>newValue</code> .



Parameter	Required	Type	Description
newValue	Yes	String	The new value for the WWN to be added in place of currentValue. If NULL is specified and newUserDefinedName is not specified, just remove the oldValue. If NULL is specified and newUserDefinedName is specified, just overwrite the current user-defined name.
newUserDefinedName	No	String	The new user-defined name for the WWN specified in currentValue or newValue. Enter up to 64 alphanumeric characters, periods(.), at marks (@), underscore (_) and hyphens(-) in the name, but it must not start with a hyphen.
reference	No	String	Specifying this value with newValue adds the new WWN name to the WWN target to which the reference WWN name belongs. If NULL is specified, newValue is not added to any WWN targets.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
400	Error	The executing APIs are not for a Fibre server.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "updateAttachedVolumes": false,
  "updateZones": false,
  "updates": [
    {
      "currentValue": "900000053326C725",
      "newValue": "910000053326C725",
      "newUserDefinedName": "Windows_Server244_HBA1"
    }
  ]
}
```

## Listing attached volumes

You can display a list of all attached volumes from a specific storage system and the path to the attached volume.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/compute/servers/attached-volumes/?q=serverId:serverId AND
storageSystemId:storageSystemId
```

Use the ID of the server as the *serverId*.

Use the ID of the storage system as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

```
{
  "resources": [
    {
      "volumeId": ,
      "storageSystemId": "",
      "storageSystemName": "",
      "poolId": "",

```

```

"label": "",
"size": ,
"usedCapacity": ,
"availableCapacity": ,
"utilization": ,
"attributes": [""],
"status": "",
"type": "",
"provisioningStatus": "",
"dataProtectionSummary": {
  "replicationType": [],
  "volumeType": [
    ""
  ],
  "replicationGroupIdMap": {},
  "hasFailures": false,
  "secondaryVolumeCount": ,
  "secondaryVolumeFailures": ,
  "mirrors": [
    {
      "volumeType": "",
      "pairStatus": "",
      "journalId":
    }
  ]
},
"gadSummary": {
  "vsmId": ,
  "virtualLdevId": ,
  "volumeType": "",
  "pairStatus": "",
  "consistencyId": ,
  "mirrors": [
    {
      "mirrorId": ,
      "volumeType": "",
      "pairStatus": "",
      "consistencyId": ,
    },
    ...
  ]
},
"dkcDataSavingType": "",
"virtualStorageMachineInformation": {
  "virtualStorageMachineId": "",
  "storageSystemId": "",
  "model": "",
  "virtualVolumeId":
},
"migrationSummary": {
  "ownerTaskId": ,

```

```

        "migrationType": ""
    },
    "aluaEnabled": ,
    "serverId": ,
    "paths": [
        {
            "storagePortId": "",
            "storageSystemId": "",
            "lun": ,
            "hostGroupId": "",
            "name": "",
            "hostMode": "",
            "wwns": [
                ""
            ],
            "hostModeOptions": [],
            "iscsiTargetInformation": ,
            "preferredPath":
        },
        {
            "storagePortId": "",
            "storageSystemId": "",
            "lun": ,
            "hostGroupId": "",
            "name": "",
            "hostMode": "",
            "wwns": [
                ""
            ],
            "hostModeOptions": [],
            "iscsiTargetInformation": ,
            "preferredPath":
        },
        ...
    ],
    "namespacePath": {
        "storageSystemId": "",
        "nvmSubsystemId": ,
        "namespaceId": ,
        "storagePortIds": [
            ""
        ],
        "hostNqns": [
            {
                "hostNqn": ""
            }
        ],
    },
    "compressionAcceleration": ,
    "commandDevice": {
        "securityEnabled": ,

```

```

        "userAuthenticationEnabled": ,
        "deviceGroupSettingEnabled":
    },
    "namespaceId": ,
    "nvmSubsystem": {
        "nvmSubsystemId": ,
        "name": "",
        "hostMode": "",
        "hostModeOptions": []
    }
},
...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
poolId	String	ID of the pool from which the resource is allocated.
poolName	String	Name of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage= (usedCapacity/size) *100.
attributes	List	List of the attributes of the volume. Valid values: <ul style="list-style-type: none"> <li>THIN: a volume for thin provisioning.</li> <li>CMD: a volume used as a command device.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ VVOL: a secondary volume for creating snapshots.</li> <li>▪ GUARD: a volume for Data Retention Utility.</li> <li>▪ MIGRATION_RESERVED: a volume for the data migration.</li> <li>▪ HA: a primary or secondary volume for High Availability.</li> <li>▪ HA_RESERVED: a reserved volume for High Availability.</li> <li>▪ NAS_TYPE_USER: a volume used as a user LU of the storage system includes NAS modules.</li> <li>▪ ALUA: a volume of which ALUA mode is enabled.</li> <li>▪ T10PI: a volume of which T10PI mode is enabled.</li> <li>▪ COMPRESSION: a volume of which compression is enabled.</li> <li>▪ DEDUPLICATION: a volume of which deduplication is enabled.</li> <li>▪ DRS: a volume of which DRS is enabled.</li> <li>▪ JOURNAL: a volume used as a journal.</li> </ul>
status	String	Volume status. Valid values: NORMAL, BLOCKED, BUSY, SHREDDING, UNKNOWN, or NONE.
type	String	Type of pool from which the volume is allocated. Valid values: THIN, TIERED, or SNAP.
provisioningStatus	String	Provisioning status of a volume. Valid values: ATTACHED, UNATTACHED, or UNMANAGED.
portIds	List	List of the storage port IDs.
hostGroupNames	List	List of the host group names.
luns	List	List of the LUN IDs.



Parameter	Type	Description
numberOfLunPaths	Integer	The number of paths from WWNs or iSCSI names to volumes (excluding paths where LUN security is disabled).
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEDUPLICATION_AND_COMPRESSION, and NONE.
aluaEnabled	Boolean	Whether or not ALUA mode of the volume is enabled.
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	Migration type. Valid values: <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
virtualStorageMachineInformation	Object	Displays the virtual storage machine information for the volume. Returns null if there are no VSMs.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The serial number of the VSM to which the volume belongs.
model	String	The model of the VSM to which the volume belongs.
virtualVolumeId	Long	The virtual volume ID. If the virtual volume is not defined, returns null.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
volumeType	Set	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
replicationGroupIdMap	Object	Replication group ID map. Consisting of the replication group ID and the replication group name for each of the replication group the volume belongs to.
hasFailures	Boolean	Whether the volume has replication failures.
secondaryVolumeCount	Integer	Count of secondary volume pairs protecting the primary volume.
secondaryVolumeFailures	Integer	Count of failed volume pairs where this volume is an S-VOL.
mirrors	Object	List of the volume pair attributes per mirror of the volume.
volumeType	String	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
pairStatus	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>SMPP: a volume pair with the clone attribute is being deleted.</li> <li>PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>COPY: a volume pair is in data synchronizing status.</li> <li>PSUE: a volume pair is in suspended status with error.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
journalId	Integer	The ID of the journal. Set only if it is in replication group, otherwise null.
gadSummary	Object	List of the GAD attributes of the volume. If there is no GAD pair, a NULL value is returned.
vsmlId	String	ID number of the virtual storage machine (VSM).
virtualLdevID	String	ID number of the virtual volume.
volumeType	String	<p>Volume type. Valid values: Active-Primary, Active-Secondary</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>volumeType</code> parameter of the <code>mirrors</code> object instead.</p>
pairStatus	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>UNKNOWN: a volume pair is in unknown status.</li> <li>NONE: a volume is not paired.</li> </ul> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>pairStatus</code> parameter of the <code>mirrors</code> object instead.</p>
<code>consistencyId</code>	Integer	<p>The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>consistencyId</code> parameter of the <code>mirrors</code> object instead.</p>
<code>mirrors</code>	Object	List of the GAD attributes per mirror of the volume.
<code>volumeType</code>	String	Volume type. Valid values: ACTIVE_PRIMARY, ACTIVE_SECONDARY, NOT_AVAILABLE
<code>pairStatus</code>	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: the volume is in paired status.</li> <li>PSUS: the volume pair is in suspended status for the primary volume.</li> <li>SSUS: the volume pair is in suspended status for the secondary volume.</li> <li>COPY: the volume pair is in data synchronizing status.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>PSUE: the volume pair is in suspended status with error.</li> <li>SSWS: the volume pair is in suspended status for swapping the secondary volume.</li> </ul>
consistencyId	Integer	<p>The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.</p> <p>For storage systems without an SVP, a NULL value is returned.</p>
serverId	Integer	ID of the server.
paths	List	<p>Path that is being used to attach the volume to the server.</p> <p>For the namespace, it represents host groups connecting between the HBA and the storage port which this namespace is visible on.</p> <p>If all ports included in <code>namespacePath</code> are LUN security OFF, this has empty list.</p> <p>Each object does not have lun.</p>
storagePortId	String	ID of the storage port where the volume is attached to the host.
storageSystemId	String	ID of the storage system.
lun	Integer	LUN identifier for the volume where it connects to the port.
name	String	Name of the path from the storage port to the host port.
hostMode	String	Host mode set for the volume.
wwns	List	<p>List of WWNs of connected hosts formatted in IQN or EUI format.</p> <p>NULL for iSCSI path.</p>
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.

Parameter	Type	Description
iscsiTargetInformation	Object	Displays iSCSI target information. NULL for FC host groups.
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	CHAP authentication mode for the iSCSI target.  This information is obtained in the case of an iSCSI port. <ul style="list-style-type: none"> <li>▪ CHAP: CHAP-authentication mode.</li> <li>▪ NONE: No-authentication mode.</li> <li>▪ BOTH: Both CHAP-authentication mode and no-authentication mode.</li> </ul>
authenticationDirection	Enum	CHAP authentication direction for the iSCSI target.  This information is obtained in the case of an iSCSI port. <ul style="list-style-type: none"> <li>▪ One-way: The iSCSI target authenticates the iSCSI initiator.</li> <li>▪ Mutual: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>
hostModeOptions	List of Integers	Host mode options for the volume.
compressionAcceleration	String	Whether the compression accelerator is enabled for the volume.  Valid values: ENABLED, DISABLED, -
commandDevice	Object	Command device settings for the volume.

Parameter	Type	Description
		The value of this parameter is null in case of storage systems without SVP or not command device.
securityEnabled	Boolean	Whether or not the command device security setting is enabled.
userAuthenticationEnabled	Boolean	Whether or not user authentication for the command device is enabled.
deviceGroupSettingEnabled	Boolean	Whether or not device group information authentication for the command device is enabled.
namespacePath	Object	Namespace path information.
storageSystemId	String	Storage system ID.
storagePortId	String	Storage Port ID.
nvmSubsystemId	Integer	NVM subsystem ID.
namespaceId	Integer	Namespace ID.
hostNqns	List	NQNs of the connected hosts.
hostNqn	String	NVMe Qualified Name of the host.
nvmSubsystem	Object	NVM subsystem information.
nvmSubsystemId	Integer	NVM subsystem ID.
name	String	NVM subsystem name.
hostMode	String	Host mode of NVM subsystem.
hostModeOptions	List	HMOs of NVM subsystem.
namespaceId	Integer	Namespace ID.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
GET https://10.76.48.147/v1/compute/servers/attached-volumes?q=serverId:4
```

### Example response

```
{
  "resources": [
    {
      "volumeId": 10,
      "storageSystemId": "41020",
      "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
      "poolId": "11",
      "label": "LDS",
      "size": 1073741824,
      "usedCapacity": 308281344,
      "availableCapacity": 765460480,
      "utilization": 28,
      "attributes": [
        "THIN"
      ],
      "status": "NORMAL",
      "type": "TIERED",
      "provisioningStatus": "ATTACHED",
      "dataProtectionSummary": {
        "replicationType": [],
        "volumeType": [
          "UNPROTECTED"
        ],
        "replicationGroupIdMap": {}
      }
    }
  ]
}
```



```

        "hasFailures": false,
        "secondaryVolumeCount": 0,
        "secondaryVolumeFailures": 0,
        "mirrors": []
    },
    "gadSummary": {
        "vsmId": 7,
        "virtualLdevId": 2657,
        "volumeType": "ACTIVE_PRIMARY",
        "pairStatus": "PAIR",
        "consistencyId": 15,
        "mirrors" : [
            {
                "mirrorId": 0,
                "volumeType": "ACTIVE_SECONDARY",
                "pairStatus": "PAIR",
                "consistencyId": 15
            },
            {
                "mirrorId": 1,
                "volumeType": "ACTIVE_PRIMARY",
                "pairStatus": "COPY",
                "consistencyId": 17
            },
            ...
        ]
    },
    "dkcDataSavingType": "NONE",
    "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "41020-VSPF800andVSPG800",
        "storageSystemId": "41020",
        "model": "VSP F800 and VSP G800",
        "virtualVolumeId": 10
    },
    "migrationSummary": {
        "ownerTaskId": null,
        "migrationType": "NONE"
    },
    "aluaEnabled": false,
    "serverId": 4,
    "paths": [
        {
            "storagePortId": "CL1-E",
            "storageSystemId": "41020",
            "lun": 20,
            "hostGroupId": "CL1-E-2",
            "name": "win-9121",
            "hostMode": "WIN",
            "wwns": [
                "100000051EF972A9"
            ]
        },
    ],

```

```

        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
    },
    {
        "storagePortId": "CL4-F",
        "storageSystemId": "41020",
        "lun": 20,
        "hostGroupId": "CL4-F-2",
        "name": "win-9121",
        "hostMode": "WIN",
        "wwns": [
            "100000051EF972A9"
        ],
        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
    }
],
"compressionAcceleration": "ENABLED",
"commandDevice": {
    "securityEnabled": true,
    "userAuthenticationEnabled": false,
    "deviceGroupSettingEnabled": false,
},
// For NVMe over FC Server
"namespacePath": {
    "storageSystemId": "41020",
    "nvmSubsystemId": 4,
    "namespaceId": 3,
    "storagePortIds": [
        "CL3-C"
    ],
    "hostNqns": [
        {
            "hostNqn": "nqn.1234.abcd"
        }
    ],
},
"namespaceId": 3,
"nvmSubsystem": {
    "nvmSubsystemId": 4,
    "name": "nvmSubsystem04",
    "hostMode": "VMWARE",
    "hostModeOptions": []
}
},
...
],
"total": 31,

```

```
"nextToken": null
}
```

## Updating iSCSI settings

You can update server iSCSI names and CHAP user settings in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1
/compute/servers/serverId/update-iscsi-settings
```

### Request structure

The request body structure is shown below:

```
{
  "updateAttachedVolumes" : ,
  "iscsiNameUpdates" : [
    {
      "currentValue": "",
      "newValue": "",
      "newUserDefinedName": "",
      "reference": ""
    }
  ],
  "chapUser": {
    "userName": "",
    "secret": ""
  }
}
```

Parameter	Required	Type	Description
updateAttachedVolumes	Yes	Boolean	Use <code>TRUE</code> to update iSCSI names of already attached volumes.
iscsiNameUpdates	No	List	List of updated iSCSI names.  Each update must contain either <code>currentValue</code> or <code>newValue</code> .

Parameter	Required	Type	Description
currentValue	No	String	The current value for the iSCSI name to be overwritten by newValue.  If NULL is specified, just add newValue.
newValue	No	String	The new value for the iSCSI name to be added in place of currentValue. If NULL is specified and newUserDefinedName is not specified, just remove the oldValue.  If NULL is specified and newUserDefinedName is specified, just overwritten the current user-defined name.
newUserDefinedName	No	String	The new user-defined name for the iSCSI name specified in currentValue or newValue. Enter up to 32 alphanumeric characters, periods(.), at marks (@), underscore (_) and hyphens(-) in the name, but it must not start with a hyphen.

Parameter	Required	Type	Description
reference	No	String	Specifying this value with newValue adds the new iSCSI name to the iSCSI target to which the reference iSCSI name belongs. If NULL is specified, newValue is not added to any iSCSI targets.
chapUser	No	Object	<p>Updates initiator(host) CHAP user. There are 3 types of updates:</p> <ul style="list-style-type: none"> <li>▪ If NULL is specified, the CHAP user will not be updated.</li> <li>▪ If NULL is not specified and both userName and secret are NULL, the CHAP user is deleted.</li> <li>▪ If NULL is not specified and both userName and secret are not NULL, the CHAP user is updated.</li> </ul> <p>If the specified CHAP user already exists on the storage port, Hitachi Ops Center Administrator posts a job report regarding overwriting the CHAP secret.</p>

Parameter	Required	Type	Description
userName	No	String	User name of the new CHAP user.  If the specified user name is the same as the current name of the server, only update secret.
secret	No	String	User secret of the new CHAP user.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      }
    },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status Code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "updateAttachedVolumes": false,
  "iscsiNameUpdates": [
    {
      "currentValue": "iqn.esx.243",
      "newValue": "iqn.esx.244",
      "newUserDefinedName": "Windows_Server244_HBA1"
    }
  ],
  "chapUser": {
    "userName": "user1",
    "secret": "123456789012"
  }
}
```



## Updating Host NVMe Qualified Names

You can update the Host NVMe Qualified Names of the server.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/servers/serverId/update-nqns
```

Use the ID of the server as the *serverId*.

### Request structure

```
{
  "updateAttachedVolumes": ,
  "updates": [
    {
      "currentValue": "",
      "newValue": ""
    }
  ]
}
```

Parameter	Required	Type	Description
updateAttachedVolumes	Yes	Boolean	Use <code>TRUE</code> to update Host NQN of already attached volumes.
updates	Yes	List	The list of updates of Host NQNs.
currentValue	Yes	String	The current value for the Host NQN to be overwritten by <code>newValue</code> .
newValue	Yes	String	The new value for the Host NQN to be added in place of <code>currentValue</code> .

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource.
500	Internal Server	Error Some errors occurred inside the API server.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "updateAttachedVolumes": false,
  "updates": [
    {
      "currentValue": "nqn.2014-08.org.example:uuid:4519bd2d-f1da-b28c-1685-7001e29bc616",
      "newValue": "nqn.2014-08.org.example:uuid:f196b976-b204-10c7-db52-5bef5cbf53dd"
    }
  ]
}
```

## Scanning host groups

You can add servers by scanning the host groups of the storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/servers/scan-host-groups
```

### Request structure

The request body structure is shown below:

```
{
  "storageSystemIds": [""],
  "allStorageSystems":
}
```

Parameter	Required	Type	Description
storageSystemIds*	Yes	List	The list of storage system IDs to be scanned. The storage system ID type is String.
allStorageSystems*	Yes	Boolean	Specifies whether all managed storage systems are scanned. Valid values are True or False. The default value is False.
*: You must specify either one. You cannot specify both at the same time.			

**Example 1**

```
{
  "storageSystemIds": ["15283", "51305", "415248"]
}
```

**Example 2**

```
{
  "allStorageSystems": true
}
```

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
}
```

```

"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Example response

```
{
  "jobId": "6833e930-f107-49f5-9133-b096647a34ba",
  "title": {
    "text": "Scan host groups",
    "messageCode": "ScanServersJobTitleMessage",
    "parameters": {
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1576654327103,
  "endDate": null,
  "parentJobId": null,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/6833e930-f107-49f5-9133-b096647a34ba"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

**Response Code**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Getting a list of server groups

You can display a list of server groups

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/compute/server-groups
```

**Request structure**

Not applicable.



**Response structure**

```
{
  "resources": [
    {
      "serverGroupId": ,
      "serverGroupName": "",
      "description": "",
      "serverIds": [],
      "numberOfServers": ,
      "numberOfVolumes": ,
      "totalCapacity": ,
      "usedCapacity": ,
      "availableCapacity":
    }
  ],
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
availableCapacity	Long	Unused capacity of volumes in the given server in the server group.
description	String	Server group description.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>
numberOfServers	Integer	Number of servers in the server group.
numberOfVolumes	Integer	Number of volumes in the given server in the server group.
serverIds	List	List of server IDs. Server ID type is integer.
serverGroupId	Integer	ID of the server group.

Parameter	Type	Description
serverGroupName	String	Name of the server group.
total	Long	Total number of resources.
totalCapacityInBytes	Long	Total capacity of volumes in the given server in the server group.
usedCapacity	Long	Used capacity of volumes in the given server in the server group.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/compute/server-groups
```

### Example response

```
{
  "resources": [
    {
```

```

    "serverGroupId": 1,
    "serverGroupName": "TWServerGroupAlpha",
    "description": "Japan servers",
    "serverIds": [
      1,
      3
    ],
    "numberOfServers": 2,
    "numberOfVolumes": 3,
    "totalCapacity": 4294967296,
    "usedCapacity": 0,
    "availableCapacity": 4294967296
  },
  {
    "serverGroupId": 2,
    "serverGroupName": "TWServerGroupBeta",
    "description": "These servers are located in SC",
    "serverIds": [
      1,
      4
    ],
    "numberOfServers": 2,
    "numberOfVolumes": 3,
    "totalCapacity": 4294967296,
    "usedCapacity": 0,
    "availableCapacity": 4294967296
  }
],
"total": 2,
"nextToken": null
}

```

## Getting a server group

You can display a server group.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/compute/server-groups/serverGroupId
```

### Request structure

Not applicable.

### Response structure

```

{
  "serverGroupId": ,
  "serverGroupName": "",

```

```

    "description": "",
    "serverIds": [],
    "numberOfServers": ,
    "numberOfVolumes": ,
    "totalCapacity": ,
    "usedCapacity": ,
    "availableCapacity":
  }

```

Parameter	Type	Description
availableCapacity	Long	Unused capacity of the resource, in bytes.
description	String	Server group description.
numberOfServers	Integer	Number of servers in the server group.
numberOfVolumes	Integer	Number of volumes in the given server in the server group.
serverIds	List	List of server IDs. Server ID type is integer.
serverGroupId	Integer	ID of the server group.
serverGroupName	String	Name of the server group.
totalCapacityInBytes	Long	Total capacity of volumes in the given server in the server group.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
GET https://172.17.64.115/v1/compute/server-groups/1
```

**Example response**

```
{
  "serverGroupId": 1,
  "serverGroupName": "TWServerGroupAlpha",
  "description": null,
  "serverIds": [
    1,
    3
  ],
  "numberOfServers": 2,
  "numberOfVolumes": 3,
  "totalCapacity": 4294967296,
  "usedCapacity": 0,
  "availableCapacity": 4294967296
}
```

## Listing volumes attached to servers in a server group

You can display a list of all volumes that are attached to servers in the given server group .

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/compute/server-groups/serverGroupId/volumes
```

Use the ID of the server group as the *serverGroupId*.

**Request structure**

Not applicable.

**Response structure**

```
{
  "resources": [
    {
      "volumeId": ,
      "storageSystemId": "",
      "storageSystemName": "",
      "resourceGroupId": ,
      "resourceGroupName": "",
      "poolId": "",
      "poolName": "",
      "label": "",
      "size": ,
      "usedCapacity": ,
      "availableCapacity": ,
      "utilization": ,
      "attributes": [""],
      "status": "",
      "type": "",
      "provisioningStatus": "",
      "portIds": [""],
      "hostGroupNames": [""],
      "luns": [],
      "numberOfLunPaths": ,
      "attachedVolumeServerSummary": [
        {
          "serverId": ,
          "serverName": ,
          "paths": [
            {
              "storagePortId": "",
              "storageSystemId": "",
              "lun": ,
              "hostGroupId": "",
              "name": "",
              "hostMode": "",
              "wwns": [""],
              "hostModeOptions": [""],
              "iscsiTargetInformation": {
                "iscsiTargetName": "",
                "iscsiInitiatorNames": [""],
                "authenticationMode": "",
                "authenticationDirection": "",
                "chapUsers": [""],
                "mutualChapUser": ""
              }
            }
          ]
        }
      ]
    }
  ],
}
```

```

        "preferredPath":
        }
    ],
    "namespacePath": {
        "storageSystemId": "",
        "nvmSubsystemId": ,
        "namespaceId": ,
        "storagePortIds": [
            "",
            ...
        ],
        "hostNqns": [
            {
                "hostNqn": ""
            },
            ...
        ]
    }
},
...
],
"dataProtectionSummary": {
    "replicationType": [""],
    "volumeType": [""],
    "replicationGroupIdMap": {},
    "hasFailures": ,
    "secondaryVolumeCount": ,
    "secondaryVolumeFailures": ,
    "mirrors": [
        {
            "volumeType": "",
            "pairStatus": "",
            "journalId":
        }
    ]
},
"gadSummary": {
    "vsmId": "",
    "virtualLdevId": ,
    "volumeType": "",
    "pairStatus": "",
    "consistencyId":,
    "mirrors" : [
        {
            "mirrorId": ,
            "volumeType": "",
            "pairStatus": "",
            "consistencyId":
        },
        ...
    ]
}

```

```

    },
    "dkcDataSavingType": "",
    "virtualStorageMachineInformation": {
        "virtualStorageMachineId": "",
        "storageSystemId": "",
        "model": "",
        "virtualVolumeId":
    },
    "migrationSummary": {
        "ownerTaskId": ,
        "migrationType": ""
    },
    "aluaEnabled": ,
    "tieringPolicy": {
        "id": ,
        "name": "",
        "userDefined":
    },
    "tl0PiEnabled":,
    "serverGroupIds": [],
    "compressionAcceleration": ,
    "commandDevice": {
        "securityEnabled": ,
        "userAuthenticationEnabled": ,
        "deviceGroupSettingEnabled":
    },
    "namespaceId": "",
    "nvmSubsystem": {
        "nvmSubsystemId": "",
        "name": ""
    }
    },
    ...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
resourceGroupId	Integer	ID of the resource group.
resourceGroupName	String	Name of the resource group.



Parameter	Type	Description
poolId	String	ID of the pool from which the resource is allocated.
poolName	String	Name of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage= (usedCapacity/size) *100.
attributes	List	<p>List of the attributes of the volume. Valid values:</p> <ul style="list-style-type: none"> <li>▪ THIN: a volume for thin provisioning.</li> <li>▪ CMD: a volume used as a command device.</li> <li>▪ VVOL: a secondary volume for creating snapshots.</li> <li>▪ GUARD: a volume for Data Retention Utility.</li> <li>▪ MIGRATION_RESERVED: a volume for the data migration.</li> <li>▪ HA: a primary or secondary volume for High Availability.</li> <li>▪ HA_RESERVED: a reserved volume for High Availability.</li> <li>▪ NAS_TYPE_USER: a volume used as a user LU of the storage system includes NAS modules.</li> <li>▪ ALUA: a volume of which ALUA mode is enabled.</li> <li>▪ T10PI: a volume of which T10PI mode is enabled.</li> <li>▪ COMPRESSION: a volume of which compression is enabled.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ DEDUPLICATION: a volume of which deduplication is enabled.</li> <li>▪ DRS: a volume of which DRS is enabled.</li> <li>▪ JOURNAL: a volume used as a journal.</li> </ul>
status	String	Volume status. Valid values: NORMAL, BLOCKED, BUSY, SHREDDING, UNKNOWN, or NONE.
type	String	Type of pool from which the volume is allocated. Valid values: THIN, TIERED, or SNAP.
provisioningStatus	String	Provisioning status of a volume. Valid values: ATTACHED, UNATTACHED, or UNMANAGED.
portIds	List	List of the storage port IDs.
hostGroupNames	List	List of the host group names.
luns	List	List of the LUN IDs.
numberOfLunPaths	Integer	The number of paths from WWNs or iSCSI names to volumes (excluding paths where LUN security is disabled).
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEDUPLICATION_AND_COMPRESSIO N, and NONE.
aluaEnabled	Boolean	Whether or not ALUA mode of the volume is enabled.
tieringPolicy	Object	Tiering policy information
id	Integer	Tier level between 0 and 31.
name	String	Name of the tier. This value is editable outside of Hitachi Ops Center Administrator for tier level 6 and higher.
userDefined	Boolean	True for tier levels 6 and higher. False, otherwise.
t10PiEnabled	Boolean	Whether or not T10PI mode of the volume is enabled.

Parameter	Type	Description
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	Migration type. Valid values: <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
virtualStorageMachineInformation	Object	Displays the virtual storage machine information for the volume. Returns null if there are no VSMs.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The serial number of the VSM to which the volume belongs.
model	String	The model of the VSM to which the volume belongs.
virtualVolumeId	Long	The virtual volume ID. If the virtual volume is not defined, returns null.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> <li>▪ ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
volumeType	Set	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.

Parameter	Type	Description
replicationGroupIdMap	Object	Replication group ID map. Consisting of the replication group ID and the replication group name for each of the replication group the volume belongs to.
hasFailures	Boolean	Whether the volume has replication failures.
secondaryVolumeCount	Integer	Count of secondary volume pairs protecting the primary volume.
secondaryVolumeFailures	Integer	Count of failed volume pairs where this volume is an S-VOL.
mirrors	Object	List of the volume pair attributes per mirror of the volume.
volumeType	String	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.
pairStatus	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>SMPP: a volume pair with the clone attribute is being deleted.</li> <li>PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>COPY: a volume pair is in data synchronizing status.</li> <li>PSUE: a volume pair is in suspended status with error.</li> <li>SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
journalId	Integer	The ID of the journal. Set only if it is in replication group, otherwise null.
gadSummary	Object	List of the GAD attributes of the volume. If there is no GAD pair, a NULL value is returned.
vsmlId	String	ID number of the virtual storage machine (VSM).
virtualLdevID	String	ID number of the virtual volume.
volumeType	String	<p>Volume type. Valid values: Active-Primary, Active-Secondary</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>volumeType</code> parameter of the <code>mirrors</code> object instead.</p>
pairStatus	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ UNKNOWN: a volume pair is in unknown status.</li> <li>▪ NONE: a volume is not paired.</li> </ul>

Parameter	Type	Description
		<b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>pairStatus</code> parameter of the <code>mirrors</code> object instead.
<code>consistencyId</code>	Integer	The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>consistencyId</code> parameter of the <code>mirrors</code> object instead.
<code>mirrors</code>	Object	List of the GAD attributes per mirror of the volume.
<code>volumeType</code>	String	Volume type. Valid values: ACTIVE_PRIMARY, ACTIVE_SECONDARY, NOT_AVAILABLE
<code>pairStatus</code>	String	The status of the given volume in the volume pair. Valid values: <ul style="list-style-type: none"> <li>PAIR: the volume is in paired status.</li> <li>PSUS: the volume pair is in suspended status for the primary volume.</li> <li>SSUS: the volume pair is in suspended status for the secondary volume.</li> <li>COPY: the volume pair is in data synchronizing status.</li> <li>PSUE: the volume pair is in suspended status with error.</li> <li>SSWS: the volume pair is in suspended status for swapping the secondary volume.</li> </ul>
<code>consistencyId</code>	Integer	The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.  For storage systems without an SVP, a NULL value is returned.

Parameter	Type	Description
serverId	Integer	ID of the server.
serverName	String	Name of the server.
paths	List	<p>Path that is being used to attach the volume to the server.</p> <p>For the namespace, it represents host groups connecting between the HBA and the storage port which this namespace is visible on.</p> <p>If all ports included in <code>namespacePath</code> are LUN security OFF, this has empty list.</p> <p>Each object does not have lun.</p>
storagePortId	String	ID of the storage port where the volume is attached to the host.
storageSystemId	String	ID of the storage system.
lun	Integer	LUN identifier for the volume where it connects to the port.
name	String	Name of the path from the storage port to the host port.
hostMode	String	Host mode set for the volume.
wwns	List	<p>List of WWNs of connected hosts formatted in IQN or EUI format.</p> <p>NULL for iSCSI path.</p>
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
iscsiTargetInformation	Object	<p>Displays iSCSI target information.</p> <p>NULL for FC host groups.</p>
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.

Parameter	Type	Description
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	<p>CHAP authentication mode for the iSCSI target.</p> <p>This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ CHAP: CHAP-authentication mode.</li> <li>▪ NONE: No-authentication mode.</li> <li>▪ BOTH: Both CHAP-authentication mode and no-authentication mode.</li> </ul>
authenticationDirection	Enum	<p>CHAP authentication direction for the iSCSI target.</p> <p>This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ One-way: The iSCSI target authenticates the iSCSI initiator.</li> <li>▪ Mutual: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>
hostModeOptions	List of Integers	Host mode options for the volume.
compressionAcceleration	String	<p>Whether the compression accelerator is enabled for the volume.</p> <p>Valid values: ENABLED, DISABLED, -</p>
commandDevice	Object	<p>Command device settings for the volume.</p> <p>The value of this parameter is null in case of storage systems without SVP or not command device.</p>
securityEnabled	Boolean	Whether or not the command device security setting is enabled.
userAuthenticationEnabled	Boolean	Whether or not user authentication for the command device is enabled.
deviceGroupSettingEnabled	Boolean	Whether or not device group information authentication for the command device is enabled.



Parameter	Type	Description
namespacePath	Object	Namespace path information.
storageSystemId	String	Storage system ID.
storagePortId	String	Storage Port ID.
nvmSubsystemId	Integer	NVM subsystem ID.
namespaceId	Integer	Namespace ID.
hostNqns	List	NQNs of the connected hosts.
hostNqn	String	NVMe Qualified Name of the host.
nvmSubsystem	Object	NVM subsystem information.
nvmSubsystemId	Integer	NVM subsystem ID.
name	String	NVM subsystem name.
namespaceId	Integer	Namespace ID.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
GET https://10.76.48.147/v1/compute/server-groups/4/volumes
```

**Example response**

```
{
  "resources": [
    // Not Namespace
    {
      "volumeId": 130,
      "storageSystemId": "41020",
      "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
      "resourceGroupId": 0,
      "resourceGroupName": "meta_resource",
      "poolId": "17",
      "poolName": "test-pool",
      "label": "100-41776_41180129",
      "size": 1073741824,
      "usedCapacity": 0,
      "availableCapacity": 1073741824,
      "utilization": 0,
      "attributes": [
        "THIN"
      ],
      "status": "NORMAL",
      "type": "THIN",
      "provisioningStatus": "ATTACHED",
      "portIds": [
        "CL1-E",
        "CL3-F"
      ],
      "hostGroupNames": [
        "DocServer",
        "windows16"
      ],
      "luns": [
        1,
        2
      ],
      "numberOfLunPaths": 2,
      "attachedVolumeServerSummary": [
        {
          "serverId": 2,
          "serverName": "DocServer",
          "paths": [
            {
              "storagePortId": "CL7-A",
              "storageSystemId": "41020",
              "lun": 1,
              "hostGroupId": "CL7-A-12",

```

```

        "name": "ESX_6524",
        "hostMode": "VMWARE",
        "wwns": [
            "50000000000000001"
        ],
        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
    },
    ...
]
},
...
],
"dataProtectionSummary": {
    "replicationType": [],
    "volumeType": [
        "UNPROTECTED"
    ],
    "replicationGroupIdMap": {},
    "hasFailures": false,
    "secondaryVolumeCount": 0,
    "secondaryVolumeFailures": 0,
    "mirrors": []
},
"gadSummary": {
    "vsmId": "7",
    "virtualLdevId": "2657",
    "volumeType": "ACTIVE_PRIMARY",
    "pairStatus": "PAIR",
    "consistencyId": 15,
    "mirrors" : [
        {
            "mirrorId": 0,
            "volumeType": "ACTIVE_SECONDARY",
            "pairStatus": "PAIR",
            "consistencyId": 15
        },
        {
            "mirrorId": 1,
            "volumeType": "ACTIVE_PRIMARY",
            "pairStatus": "COPY",
            "consistencyId": 17
        },
        ...
    ],
},
"virtualStorageMachineInformation": {
    "virtualStorageMachineId": "41503-VSPF700",
    "storageSystemId": "41010",
    "model": "VSP F700",

```

```

    "virtualVolumeId": 0
  },
  "serverGroupIds": [1],
  "compressionAcceleration": "ENABLED",
  "commandDevice": {
    "securityEnabled": true,
    "userAuthenticationEnabled": false,
    "deviceGroupSettingEnabled": false
  }
},
// Namespace
{
  "volumeId": 11016,
  "storageSystemId": "41020",
  "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
  "poolId": "24",
  "poolName": "example-nvme-test",
  "label": "example-nvme-test3",
  "size": 1073741824,
  "usedCapacity": 0,
  "availableCapacity": 1073741824,
  "utilization": 0,
  "attributes": [
    "THIN"
  ],
  "status": "NORMAL",
  "type": "TIERED",
  "provisioningStatus": "ATTACHED",
  "portIds": [],
  "hostGroupNames": [],
  "luns": [],
  "numberOfLunPaths": 0,
  "dataProtectionSummary": {
    "replicationType": [],
    "volumeType": [
      "UNPROTECTED"
    ],
    "replicationGroupIdMap": {},
    "hasFailures": false,
    "secondaryVolumeCount": 0,
    "secondaryVolumeFailures": 0,
    "mirrors": []
  },
  "gadSummary": {
    "vsmId": null,
    "virtualLdevId": null,
    "volumeType": "NOT_AVAILABLE",
    "pairStatus": "NONE",
    "consistencyId": null,
    "mirrors": []
  },
},

```

```

    "dkcDataSavingType": "NONE",
    "virtualStorageMachineInformation": {
      "virtualStorageMachineId": "39342-VSP5200-5600",
      "storageSystemId": "39342",
      "model": "VSP 5200, 5600",
      "virtualVolumeId": 11016
    },
    "resourceGroupId": 0,
    "resourceGroupName": "meta_resource",
    "migrationSummary": {
      "ownerTaskId": null,
      "migrationType": "NONE"
    },
    "aluaEnabled": false,
    "tieringPolicy": {
      "id": 0,
      "name": "All",
      "userDefined": false
    },
    "tl0PiEnabled": false,
    "serverGroupIds": [1],
    "compressionAcceleration": "-",
    "commandDevice": null,
    "attachedVolumeServerSummary": [
      {
        "serverId": 1,
        "serverName": "DocServer",
        "paths": [],
        "namespacePath": {
          "storageSystemId": "41020",
          "nvmSubsystemId": 1,
          "namespaceId": 3,
          "storagePortIds": [
            "CL3-C"
          ],
          "hostNqns": [
            {
              "hostNqn": "nqn.1234.abcd"
            }
          ]
        }
      }
    ],
    "namespaceId": 3,
    "nvmSubsystem": {
      "nvmSubsystemId": 1,
      "name": "nvmSubsystem01"
    }
  },
  ...
],

```

```

"total": ,
"nextToken": ""
}

```

## Creating a server group

You can create a new server group.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/server-groups
```

### Request structure

```

{
  "serverGroupName": "",
  "description": "",
  "serverIds": []
}

```

Parameter	Required	Type	Description
description	No	String	Server group description.
serverIds	Yes	List	List of server IDs that belong to this server group. Server ID type is Integer. All servers in a single server group must use the same protocol.
serverGroupName	Yes	String	Name of the server group.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",

```

```

    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.



Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "serverGroupName": "TWserverGroupofThree",
  "description": "a cluster for application VMs",
  "serverIds": [1, 4, 3]
}
```

**Example request**

```
POST https://172.17.64.115/v1/compute/server-groups/
```

**Example response**

```
{
  "jobId": "5df76ea2-445b-4a32-9939-1967ed67be78",
  "title": {
    "text": "Creating a server group TWserverGroupofThree",
    "messageCode": "CreateServerGroupJobTitleMessage",
    "parameters": {
      "serverGroupName": "TWserverGroupofThree"
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1559339466700,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/5df76ea2-445b-4a32-9939-1967ed67be78"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

```
}
```

## Updating a server group

You can update a server group name and description.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/server-groups/serverGroupId
```

### Request structure

```
{
  "serverGroupName": "",
  "description": ""
}
```

Parameter	Required	Type	Description
description	No	String	Server group description.
serverGroup Name	No	String	Updated name of the server group.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":

```

```
[
],
"links":
[
{
"rel": "_self",
"href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "serverGroupName": "NewServerName",
  "description": "a description for application VMs",
}
```

**Example request**

```
POST https://172.17.64.115/v1/compute/server-groups/1
```

**Example response**

```
{
  "jobId": "84ec8cf2-d35a-4286-9cb4-d98f69ec1266",
  "title": {
    "text": "Updating the server group 4",
    "messageCode": "UpdateServerGroupJobTitleMessage",
    "parameters": {
      "serverGroupId": 4
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1559342491261,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/84ec8cf2-d35a-4286-9cb4-d98f69ec1266"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

## Adding servers to a server group

You can add servers to a server group.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/compute/server-groups/serverGroupId/add-servers
```

**Request structure**

```
{
  "serverIds": []
}
```

Parameter	Required	Type	Description
serverIds	Yes	List	List of server IDs to add to this server group. Server ID type is Integer. All servers in a single server group must use the same protocol.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      "text": ""
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ]
}
```

```

],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "serverIds": [3]
}
```

### Example request

```
POST https://172.17.64.115/v1/compute/server-groups/4/add-servers
```



**Example response**

```
{
  "jobId": "cd0d01da-5da7-4c52-8efd-b10054f6236c",
  "title": {
    "text": "Adding servers 3 to the server group 4",
    "messageCode": "AddServersToServerGroupJobTitleMessage",
    "parameters": {
      "serverIdList": "3",
      "serverGroupId": 4
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1559343194536,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/cd0d01da-5da7-4c52-8efd-b10054f6236c"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

## Deleting a server group

You can delete a server group.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/compute/server-groups/serverGroupId
```

**Request structure**

Not applicable.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
DELETE https://172.17.64.115/v1/compute/server-groups/1
```

**Example response**

```
{
  "jobId": "66388bf8-f2d2-4bd3-8eaf-8f0afbf03d32",
  "title": {
    "text": "Deleting the server group 1",
    "messageCode": "DeleteServerGroupJobTitleMessage",
    "parameters": {
      "serverGroupId": 1
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1559337235525,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/66388bf8-f2d2-4bd3-8eaf-8f0afbf03d32"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ]
}
```

```

    }
  ],
  "isSystem": false
}

```

## Removing multiple servers from a server group

You can remove servers from a server group.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/compute/server-groups/serverGroupId/remove-servers
```

### Request structure

```

{
  "serverIds": []
}

```

Parameter	Required	Type	Description
serverIds	Yes	List	List of server IDs to remove from this server group. Server ID type is Integer.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,

```

```

"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
{
  "serverIds": [3]
}
```

**Example request**

```
POST https://172.17.64.115/v1/compute/server-groups/4/remove-servers
```

**Example response**

```
{
  "jobId": "4ede4ac0-9bfl-4838-8f15-c01bb1511492",
  "title": {
    "text": "Removing servers 3 from the server group 4",
    "messageCode": "RemoveServersFromServerGroupJobTitleMessage",
    "parameters": {
      "serverIdList": "3",
      "serverGroupId": 4
    }
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1559341234515,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/4ede4ac0-9bfl-4838-8f15-c01bb1511492"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```



## Using existing LUN paths

### HTTP request syntax (URI)

```
POST https://ipAddress/v1
/compute/servers/create-similar-paths
```

### Request structure

```
{
  "storageSystemId": "",
  "referenceServerId": ,
  "servers": [
    {
      "serverId": ,
      "paths": [
        {
          "serverWwns": [""],
          "iscsiInitiatorNames": [""],
          "storagePortIds": [""],
        },
        ...
      ]
    },
    ...
  ]
}
```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the storage system.
referenceServerId	Yes	Integer	ID of the server to copy path connection information from.
serverId	Yes	Integer	ID of the server to create paths for.
serverWwns	No*	List of Strings	The WWNs of the server to create paths for.
iscsiInitiatorNames	No*	List of Strings	The iSCSI name of a server to create paths for.
storagePortIds	Yes	List of Strings	Ids of the storage port to create paths for.
*: This is either serverWwns or iscsiInitiatorNames but not both.			

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/compute/create-similar-paths
```

**Example request**

```
// For FC servers
{
  "storageSystemId": "410209",
  "referenceServerId": 1,
  "servers": [
    {
      "serverId": 2,
      "paths": [
        {
          "serverWwns": [ "50000000000000001", "50000000000000002" ],
          "storagePortIds": [ "CL1-A", "CL2-A" ]
        }
      ]
    }
  ]
}
```

```

    }
  ]
}
// For iSCSI servers
{
  "storageSystemId": "410309",
  "referenceServerId": 3,
  "servers": [
    {
      "serverId": 4,
      "paths": [
        {
          "iscsiInitiatorNames": [
            "iqn.1991-05.com.example:example"
          ],
          "storagePortIds": [ "CL1-B", "CL2-B" ]
        }
      ]
    }
  ]
}

```

## Chapter 4: Volume Migration resources

This module describes the Volume Migration operations.

Request	Method	URI	Role
<a href="#">Attaching volumes to storage (on page 536)</a>	POST	/v1/volume-manager/attach-to-storage	Storage administrator System administrator Security administrator
<a href="#">Creating external volumes (on page 542)</a>	POST	/v1/external-volume-manager/create	Storage administrator
<a href="#">Deleting external volumes (on page 550)</a>	POST	/v1/external-volume-manager/delete	Storage administrator
<a href="#">Discovering external devices (on page 553)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /external-devices/discover	Storage administrator
<a href="#">Listing external devices (on page 557)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /external-devices	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing external volumes (on page 560)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /external-volumes	Storage administrator System administrator Security administrator Monitoring

Request	Method	URI	Role
<a href="#">Getting an external volume (on page 566)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /external-volumes/volumeId	Storage administrator System administrator Security administrator Monitoring
<a href="#">Detaching volumes from storage (on page 572)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /volumes/ <i>volumeId</i> /detach-from-storage	Storage administrator System administrator Security administrator
<a href="#">Listing migration tasks (on page 575)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /migration-tasks	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a migration task (on page 578)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /migration-tasks/ <i>migrationTaskId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a migration task (on page 580)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /migration-tasks	Storage administrator
<a href="#">Interrupting a running migration job (on page 586)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /migration-tasks/ <i>migrationTaskId</i> /interrupt	Storage administrator
<a href="#">Updating a migration task (on page 588)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> /migration-tasks/ <i>migrationTaskId</i>	Storage administrator

Request	Method	URI	Role
<a href="#">Deleting a migration task (on page 594)</a>	DELETE	/v1/storage-systems/ <i>storageSystemId</i> /migration- tasks/ <i>migrationTaskId</i>	Storage administrator
<a href="#">Listing migration pairs (on page 596)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /migration- pairs? q=migrationTaskId: <i>migrationTaskId</i>	Storage administrator System administrator Security administrator Monitoring

## Attaching volumes to storage

You can set up connections between volumes on the source storage system and the target storage system according to FC or iSCSI protocols in Ops Center Administrator during Volume Migration.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/volume-manager/attach-to-storage
```

### Request structure

The request body structure is shown below:

```
{
  "sourceStorageSystemId": "",
  "targetStorageSystemId" : "",
  "chapUser":
    {
      "userName" : "",
      "secret" : ""
    }
  "mutualUser" :
    {
      "userName" : "",
      "secret" : ""
    }
  "portsInfo" : [
    {
      "srcPort" : "",
      "targetPort": ""
    }
  ]
}
```



```

    },
    {
      "srcPort" : "",
      "targetWwn" : "",
      "targetPort": null
    }
  ],
  "volumes" : [
    {
      "volumeId" : 62
    }
  ]
}

```

Parameter	Required	Type	Description
sourceStorageSystemId	Yes	String	ID of the source storage system.
targetStorageSystemId	Yes	String	ID of the target storage system.
chapUser	No	Object	Information about the CHAP user.
userName	No	String	User name.
secret	No	String	Secret of the user.
mutualUser	No	Object	Information about the mutual user.
portsInfo	Yes	List	Information about the ports.
srcPort	Yes	String	Source port.
targetPort	Yes	String	Target port.
volumes	Yes	List	List of logical units.
volumeId	Yes	Integer	Volume ID.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",

```

```

    "messageCode": "",
    "parameters":
      {
      }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.

Status Code	HTTP Name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified URI is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "sourceStorageSystemId": "420209",
  "targetStorageSystemId": "430209",
  "portsInfo": [
    {
      "srcPort": "CL1-A",
      "targetPort": "CL1-A"
    },
    {
      "srcPort": "CL1-D",
      "targetPort": "CL1-C"
    }
  ],
  "volumes": [
    {
      "volumeId": 138
    }
  ]
}
```

### Example response

```
{
  "jobId": "660f1c51-2e0b-4fef-8b25-e68486ce419f",
  "title": {
    "text": "Attach volumes to servers.",
    "messageCode": "AttachVolumesToServersJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
```

```

"status": "SUCCESS",
"startDate": 1527037563303,
"endDate": 1527037838400,
"parentJobId": null,
"reports": [
  {
    "reportMessage": {
      "text": "Storage System 410209. Attaching volumes with IDs: [113] to servers
with IDs: [13].",
      "messageCode": "AttachVolumesToServersPreStepMessage",
      "parameters": {
        "servers": [
          13
        ],
        "storageSystemId": "410209",
        "volumes": [
          113
        ]
      }
    },
    "severity": "INFORMATION",
    "creationDate": 1527037563355
  },
  {
    "reportMessage": {
      "text": "Storage System 410209. Completed attaching volumes with IDs: [113]
to servers with IDs: [13].",
      "messageCode": "AttachVolumesToServersPostStepMessage",
      "parameters": {
        "servers": [
          13
        ],
        "storageSystemId": "410209",
        "volumes": [
          113
        ]
      }
    },
    "severity": "INFORMATION",
    "creationDate": 1527037838345
  }
],
"links": [
  {
    "rel": "_self",
    "href": "/v1/jobs/660f1c51-2e0b-4fef-8b25-e68486ce419f"
  }
],
"tags": [
  {
    "tag": "rainier"
  }
]

```

```

    }
  ],
  "isSystem": false
}

```

## Creating external volumes

You can create external volumes in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/external-volume-manager/create
```

### Request structure

The request body structure is shown below:

```

{
  "storageSystemId": "",
  "externalDevices": [
    {
      "externalDeviceId": ""
      "externalPaths": [
        {
          "portId": "",
          "externalWwn": "",
          "externalIscsiInformation": [
            {
              "iscsiName": "",
              "ipAddress": ""
            }
          ],
          "externalLun": ""
        }
      ]
    }
  ],
  "attachExternalVolumeToServer": {
    "intendedImageType": "",
    "hostModeOptions": [],
    "enableZoning": ,
    "enableLunUnification": ,
    "forceOverwriteChapSecret": ,
    "shareHgByAllServers": ,
    "ports": [
      {
        "serverId": ,
        "serverWwns": [""],

```

```

    "iscsiInitiatorNames": [""],
    "portIds": [""],
  }
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the storage system.
externalDevices	Yes	Object	List of the available external devices.
externalDeviceId	Yes	String	ID of the external device.
externalPaths	No	Object	List of the available external paths. If you do not specify a path, the method automatically selects an available path.
portId	Yes	String	ID of the storage port of the internal storage system.
externalWwn	Yes	String	WWN of the storage port of the external storage system.
externalIscsiInformation	Yes	Object	iSCSI information of the storage port of the external storage system.
iscsiName	Yes	String	iSCSI target name of the storage port of the external storage system.
ipAddress	Yes	String	IP address of the storage port of the external storage system.
externalLun	Yes	Integer	ID of the LUN.

Parameter	Required	Type	Description
attachExternalVolumeToServer	No	Object	Information about the external volumes attached to the server.
intendedImageType	No	String	Host mode set for the volume.
hostModeOptions	No	List	Host mode options set for the volume. Default values are automatically set in case the server OS is either VMWARE_EX or WIN_EX. The valid value is a host mode options number without any prefix, or null for auto select.
enableZoning	No	Boolean	Whether or not zones are created on the SAN fabric. If enableZoning is set to false, then zoning is disabled.  The default value is false.  This is valid only for FC servers and must be NULL for iSCSI servers.
enableLunUnification	No	Boolean	Whether or not Lun (logical unit number) assignments for volumes that span multiple servers are consistent.



Parameter	Required	Type	Description
forceOverwriteChapSecret	No	Boolean	Whether or not Hitachi Ops Center Administrator overwrites the CHAP user secret when there is any port that exists with the same CHAP user name. The default value is FALSE.
shareHgByAllServers	No	Boolean	Whether to share host groups among servers. The default setting is False, which does not allow sharing. Specify True to share host groups among servers.
serverId	Yes	Integer	ID of the server.
serverWwns	No	List	The WWNs for a server. If a WWN is not specified, then all WWNs associated with the server are used.  You must specify either serverWwns or iscsiInitiatorNames.
iscsiInitiatorNames	No	List	The iSCSI names of the server to attach.  If iscsiInitiatorNames is not specified, then all iSCSI names of the server are used to attach.  You must specify either serverWwns or iscsiInitiatorNames but not both.
portIds	No	List	Port IDs.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
400	Bad request	The request contains invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "storageSystemId": "410209",
  "externalDevices": [
    {
      "externalDeviceId": " XYZ 50405F7702BC",
      "externalPaths": [
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7700",
          "externalIscsiInformation": null,
          "externalLun": 12
        },
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7710",
          "externalIscsiInformation": null,
          "externalLun": 12
        }
      ]
    }
  ],
  "attachExternalVolumeToServer":
  {

```

```

    "intendedImageType": "LINUX",
    "hostModeOptions": [ ],
    "enableZoning": false,
    "enableLunUnification": false,
    "forceOverwriteChapSecret": null,
    "shareHgByAllServers": true,
    "ports" :[
    {
        "serverId": 1,
        "serverWwns": ["50:00:00:11:22:33:44:55"],
        "iscsiInitiatorNames": null,
        "portIds": ["CL3-E"]
    }
    ]
}

```

### External paths auto select

```

{
    "storageSystemId": "410209",
    "externalDevices": [
        {
            "externalDeviceId": "ExampleCompany 50405F7701DC",
            "externalPaths": [ ]
        }
    ],
    "attachExternalVolumeToServer":
    {
        "intendedImageType": "LINUX",
        "hostModeOptions": [ ],
        "enableZoning": false,
        "enableLunUnification": false,
        "forceOverwriteChapSecret": null,
        "ports" :[
        {
            "serverId": 1,
            "serverWwns": ["50:00:00:11:22:33:44:55"],
            "iscsiInitiatorNames": null,
            "portIds": ["CL3-E"]
        }
        ]
    }
}

```

### Volume migration without attaching external volumes:

```

{
    "storageSystemId": "410209",
    "externalDevices": [
        {
            "externalDeviceId": "ExampleCompany 50405F7701DC",

```

```

    "externalPaths": []
  }
],
}

```

## Deleting external volumes

You can delete external volumes in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/external-volume-manager/delete
```

### Request structure

```

{
  "storageSystemId": "",
  "volumeIds": [],
  "cleanupZones":
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the storage system.
volumeIds	Yes	List	List of volume IDs. Volume ID type is long.
cleanupZones	No	Boolean	Remove zone for the Fibre Channel, if applicable.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  }
}

```

```

    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).

Parameter	Type	Description
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified URI is not valid or the resource does not exist.



Status Code	HTTP Name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request****Example response**

```
{
  "jobId": "e15119d7-2ea0-4ffe-9c28-18f905df5c687",
  "title": {
    "text": "Deleting Volume",
    "messageCode": "DeletingExternalVolumeJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1510816371239,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/e15119d7-2ea0-4ffe-9c28-18f905df5c687"
    }
  ],
  "tags": [
    {
      "tag": "rainier"
    }
  ],
  "isSystem": false
}
```

## Discovering external devices

You can update the external device cache of the specified port in Ops Center Administrator. If you are updating a different port between the last time and this time, the external device cache of the previous port is not changed.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/external-devices/discover
```

**Request structure**

The request body structure is shown below:

```
{
  "storagePortIds": [ "" ]
}
```

Parameter	Required	Type	Description
storagePortIds	Yes	List	The IDs of the storage port.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
```

```
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains invalid request payload, or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "storagePortIds": [ "CL1-A", "CL2-A" ]
}
```

## Listing external devices

You can retrieve external devices in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-devices
```

### Request structure

Not applicable.

### Response structure

The request body structure is shown below:

```
{
  "resources": [{
    {
      "storageSystemId": "",
      "externalDeviceId": "",
      "size": ,
      "productId": ,
      "externalStorageSystemInformation":
      {
        "serialNumber": "",
        "vendorId": "",
        "productId": ""
      },
      "externalPaths": [{
        "portId": "",
        "externalWwn": "",
        "externalIscsiInformation"
        {
          "iscsiName": "",
          "ipAddress": ""
        },
        "externalLun":
      }],
      "mapped": ""
    }
  ]
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
storageSystemId	String	ID of the storage system.
externalDeviceId	String	ID of the external device.
size	Long	Size of the volume, in bytes.
productId	String	Product name of the external device.
externalStorageSystemInformation	Object	External storage system of the external device.
serialNumber	String	ID of the external storage system.
vendorId	String	Vendor name of the external storage system.
productId	String	Product name of the external storage system.
externalPaths	Object	List of the available external paths.
portId	String	ID of the storage port of the internal storage system.
externalWwn	String	WWN of the storage port of the external storage system.
externalIscsiInformation	Object	iSCSI information of the storage port of the external storage system.
iscsiName	String	iSCSI name of the storage port of the external storage system.
ipAddress	String	IP address of the storage port of the external storage system.
externalLun	String	ID of the LUN of the storage port of the external storage system.
mapped	Boolean	Whether the external device has already been mapped to an external parity group.

**Return codes**

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

```
{
  "resources": [
    {
      "storageSystemId": "410209",
      "externalDeviceId": "XYZ 50405F7702BC",
      "size": 1073741824,
      "productId": "OPEN-V",
      "externalStorageSystemInformation": {
        "serialNumber": "424439",
        "vendorId": "XYZ",
        "productId": "VSP Gx00"
      },
      "externalPaths": [
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7700",
          "externalIscsiInformation": null,
          "externalLun": 12
        },
        {
          "portId": "CL1-E",
          "externalWwn": "50060E80125F7710",
          "externalIscsiInformation": null,
          "externalLun": 12
        }
      ],
      "mapped": false
    },
    {
      "total": 1,
      "nextToken": null
    }
  ]
}
```

## Listing external volumes

You can retrieve external volumes for Volume Migration in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-volumes
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources": [
    {
      "volumeId": ,
      "mappedVolumeId": ,
      "externalParityGroupId": "",
      "storageSystemId": "",
      "poolId": ,
      "label": "",
      "size": ,
      "usedCapacity": ,
      "availableCapacity": ,
      "utilization": ,
      "status": "",
      "type": "",
      "provisioningStatus": "",
      "attachedVolumeServerSummary":
      {
        [
          {
            "serverId": ,
            "serverName": "",
            "paths":
            [
              {
                "storagePortId": "",
                "storageSystemId": "",
                "lun": ,
                "name": "",
                "hostMode": "",
                "wwns": [],
                "hostModeOptions": [],
                "preferredPath": ,
                "iscsiTargetInformation": {
```



```

        "iscsiTargetName": "",
        "iscsiInitiatorNames": [""],
        "mutualChapUser": "",
        "chapUsers": [""],
        "authenticationMode": "",
        "authenticationDirection": ""
    }
}
]
}
]
},
"migrationSummary": {
    "ownerTaskId": ,
    "migrationType": ""
},
"externalStorageSystemId": "",
"externalStorageVendor": "",
"externalStorageProduct": ""
}
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
mappedVolumeld	Long	ID of the mapped volume.
externalParityGroupld	String	ID of the external parity group.
storageSystemld	String	ID of the storage system.
poolld	String	ID of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.

Parameter	Type	Description
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage=(usedCapacity/size)*100.
status	String	Volume status. Valid values: <ul style="list-style-type: none"> <li>NORMAL</li> <li>BLOCKED</li> <li>BUSY</li> <li>UNKNOWN</li> <li>NONE</li> </ul>
type	String	Type of pool from which the volume is allocated. Valid value: <ul style="list-style-type: none"> <li>EXTERNAL</li> </ul>
provisioningStatus	String	Provisioning status of a volume. Valid values: <ul style="list-style-type: none"> <li>ATTACHED</li> <li>UNATTACHED</li> <li>UNMANAGED</li> </ul>
attachedVolumeServerSummary	List	Volume provisioning summary details.
serverId	Integer	ID of the server.
serverName	String	Name of the server.
paths	List	Paths that exist on the volume.
storagePortId	String	ID of the storage port.
storageSystemId	String	ID of the storage system.
lun	Integer	ID of the LUN.
name	String	Name of the resource.
hostMode	String	Host mode set for the volume.
wwns	List	List of WWNs of connected hosts. NULL for iSCSI path.

Parameter	Type	Description
hostModeOptions	List of Integers	Host mode options for the volume.
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
iscsiTargetInformation	Object	Displays iSCSI target information. NULL for FC host groups.
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target formatted in IQN or EUI format.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	CHAP authentication mode for the iSCSI target. This information is obtained in the case of an iSCSI port. <ul style="list-style-type: none"> <li>▪ CHAP: CHAP authentication mode.</li> <li>▪ NONE: No authentication mode.</li> <li>▪ BOTH: Both CHAP authentication and no authentication mode.</li> </ul>
authenticationDirection	Enum	CHAP authentication direction for the iSCSI target.

Parameter	Type	Description
		<p>This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>ONEWAY: The iSCSI target authenticates the iSCSI initiator.</li> <li>MUTUAL: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	<p>Migration type. Valid values:</p> <ul style="list-style-type: none"> <li>MIGRATION</li> <li>NONE</li> </ul>
externalStorageSystemId	String	The ID of the external storage system.
externalStorageVendor	String	The vendor name of the external storage system.
externalStorageProduct	String	The model name of the external storage system.

### Return codes

Status Code	HTTP Name	Description
200	OK	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status Code	HTTP Name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
GET https://10.76.48.147/v1/storage-systems/410209/external-volumes
```

### Example response

```
{
  "resources": [
    {
      "volumeId": 87,
      "mappedVolumeId": 70,
      "externalDeviceId": "XYZ 50402904033B",
      "externalParityGroupId": "1-5",
      "storageSystemId": "410209",
      "poolId": "7",
      "label": "",
      "size": 4398046511104,
      "usedCapacity": 4398426095616,
      "availableCapacity": 0,
      "utilization": 100,
      "status": "NORMAL",
      "type": "EXTERNAL",
      "provisioningStatus": "UNMANAGED",
      "attachedVolumeServerSummary": [
        {
          "serverId": null,
          "serverName": null,
          "paths": [
            {
              "storagePortId": "CL1-F",
              "storageSystemId": "410209",
              "lun": 1,
              "hostGroupId": "CL1-F-2",
              "name": "Win-9121_001",
              "hostMode": "WIN_EX",
              "wwns": ["100000053326F7CC"]
            },
            {
              "storagePortId": "CL1-F",
              "storageSystemId": "410209",
              "lun": 2,
              "hostGroupId": "CL1-F-2",
              "name": "Win-9121_001",
              "hostMode": "WIN_EX",
              "wwns": ["100000053326F7CC"]
            }
          ],
          "hostModeOptions": [40,
            73
          ]
        }
      ]
    }
  ]
}
```

```

        ],
        "iscsiTargetInformation":null,
        "preferredPath":null
    }
]
}
],
"migrationSummary":
{
    "ownerTaskId":null,
    "migrationType":"NONE"
}
"externalStorageSystemId":"412345",
"externalStorageVendor":"Hitachi",
"externalStorageProduct":"VSP Gx00"

},
...
"total":11,
"nextToken":null
}

```

## Getting an external volume

You can retrieve a specific external volume for Volume Migration in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/external-volumes/volumeId
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
    "volumeId": ,
    "mappedVolumeId": ,
    "externalParityGroupId": "",
    "storageSystemId": "",
    "poolId": ,
    "label": "",
    "size": ,
    "usedCapacity": ,
    "availableCapacity": ,
    "utilization": ,

```

```

    "status": "",
    "type": "E",
    "provisioningStatus": "",
    "attachedVolumeServerSummary":
    {
      [
        {
          "serverId": ,
          "serverName": "",
          "paths":
          [
            {
              "storagePortId": "",
              "storageSystemId": "",
              "lun": ,
              "name": "",
              "hostMode": "",
              "wwns": [],
              "hostModeOptions": [],
              "preferredPath": ,
              "iscsiTargetInformation": {
                "iscsiTargetName": "",
                "iscsiInitiatorNames": [""],
                "mutualChapUser": "",
                "chapUsers": [""],
                "authenticationMode": "",
                "authenticationDirection": ""
              }
            }
          ]
        }
      ]
    },
    "migrationSummary": {
      "ownerTaskId": ,
      "migrationType": ""
    }
    "externalStorageSystemId": "",
    "externalStorageVendor": "",
    "externalStorageProduct": ""
  }

```

Parameter	Type	Description
volumeld	Long	ID number of the volume within the parent storage system.
mappedVolumeld	Long	Mapped volume ID.

Parameter	Type	Description
externalParityGroupId	String	ID of the external parity group.
storageSystemId	String	ID of the storage system.
poolId	String	ID of the pool from which the resource is allocated.
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage=(usedCapacity/size)*100.
status	String	Volume status. Valid values: <ul style="list-style-type: none"> <li>▪ NORMAL</li> <li>▪ BLOCKED</li> <li>▪ BUSY</li> <li>▪ UNKNOWN</li> <li>▪ NONE</li> </ul>
type	String	Type of pool from which the volume is allocated. Valid value: <ul style="list-style-type: none"> <li>▪ EXTERNAL</li> </ul>
provisioningStatus	String	Provisioning status of a volume. Valid values: <ul style="list-style-type: none"> <li>▪ ATTACHED</li> <li>▪ UNATTACHED</li> <li>▪ UNMANAGED</li> </ul>
attachedVolumeServerSummary	List	Volume provisioning summary details.
serverId	Integer	ID of the server.



Parameter	Type	Description
serverName	String	Name of the server.
paths	List	Paths that exist on the volume.
storagePortId	String	ID of the storage port.
storageSystemId	String	ID of the storage system.
lun	Integer	ID of the LUN.
name	String	Name of the resource.
hostMode	String	Host mode set for the volume.
wwns	List	List of WWNs of connected hosts. NULL for iSCSI path.
hostModeOptions	List of Integers	Host mode options for the volume.
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
iscsiTargetInformation	Object	Displays iSCSI target information. NULL for FC host groups.
iscsiTargetName	String	Displays the iSCSI name of the iSCSI target.
iscsiInitiatorNames	String	Displays the list of iSCSI names of the host bus adapters registered in the iSCSI target formatted in IQN or EUI format.
mutualChapUser	String	Displays the CHAP user name of the iSCSI target.
chapUsers	String	Displays the list of CHAP users of the host bus adapters registered in the iSCSI target.
authenticationMode	Enum	CHAP authentication mode for the iSCSI target. This

Parameter	Type	Description
		<p>information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ CHAP: CHAP authentication mode.</li> <li>▪ NONE: No authentication mode.</li> <li>▪ BOTH: Both CHAP authentication and no authentication mode.</li> </ul>
authenticationDirection	Enum	<p>CHAP authentication direction for the iSCSI target. This information is obtained in the case of an iSCSI port.</p> <ul style="list-style-type: none"> <li>▪ ONEWAY: The iSCSI target authenticates the iSCSI initiator.</li> <li>▪ MUTUAL: The iSCSI target and the iSCSI initiator authenticate each other.</li> </ul>
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	<p>Migration type. Valid values:</p> <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
externalStorageSystemId	String	The ID of the external storage system.
externalStorageVendor	String	The vendor name of the external storage system.
externalStorageProduct	String	The model name of the external storage system.

**Return codes**

Status Code	HTTP Name	Description
200	OK	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

```
{
  "volumeId":87,
  "mappedVolumeId":70,
  "externalDeviceId":"XYZ 50402904033B",
  "externalParityGroupId":"1-5",
  "storageSystemId":"410209",
  "poolId":"7",
  "label":"",
  "size":4398046511104,
  "usedCapacity":4398426095616,
  "availableCapacity":0,
  "utilization":100,
  "status":"NORMAL",
  "type":"EXTERNAL",
  "provisioningStatus":"UNMANAGED",
  "attachedVolumeServerSummary":[
    {
      "serverId":null,
      "serverName": null,
      "paths":[
        {
          "storagePortId":"CL1-F",
          "storageSystemId":"410209",
          "lun":1,

```

```

        "hostGroupId":"CL1-F-2",
        "name":"Win-9121_001",
        "hostMode":"WIN_EX",
        "wwns":["100000053326F7CC"]
    ],
    "hostModeOptions":
    [40,
        73
    ],
    "iscsiTargetInformation":null,
    "preferredPath":null
    }
    ]
    }
    ],
    "migrationSummary":
    {
        "ownerTaskId":null,
        "migrationType":"NONE"
    }
    "externalStorageSystemId":"412345",
    "externalStorageVendor":"Hitachi",
    "externalStorageProduct":"VSP Gx00"
}

```

## Detaching volumes from storage

This operation deletes the paths from source storage system to target storage system in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId/detach-
from-storage
```

### Request structure

The request body structure is shown below:

```

{
    targetStorageSystemId : ""
}

```

Parameter	Required	Type	Description
targetStorageSystemId	Yes	String	ID of the target storage system.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.

Parameter	Type	Description
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified URI is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Listing migration tasks

You can retrieve a list of migration tasks for Volume Migration in Ops Center Administrator.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks
```

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "resources": [
```

```

{
  "migrationTaskId": "",
  "migrationTaskName": "",
  "comments": "",
  "jobId": "",
  "schedule": {
    "datetime": ""
  },
  "migrationPairCount": ,
  "samePoolContainingSourceVolume": ,
  "volumeDeletion": ,
  "volumeShredding": ,
  "patterns": ["", ...]
},
...
],
"total": ,
"nextToken":
}

```

Parameter	Type	Description
migrationTaskId	Integer	ID of the migration task.
migrationTaskName	String	Name of the migration task. Min=1, max=32 characters.
comments	String	Comment for the migration task. Min = 1, max = 255 characters.
jobId	String	ID of the corresponding migration job. This parameter is only available once the job is executed.
schedule	Object	Schedule of the migration job.
datetime	String	Scheduled date and time of the migration job to be executed (in ISO 8601 format).
migrationPairCount	Integer	Number of migration pairs defined in the task.



Parameter	Type	Description
samePoolContainingSourceVolume	Boolean	Whether to use the same pool containing the source volume for the target volume.
volumeDeletion	Boolean	Whether to delete source volumes after the migration is completed.
volumeShredding	Boolean	Whether to shred source volumes after the migration is completed.
patterns	List	List of the pattern strings used for shredding.

### Return codes

Status Code	HTTP name	Description
200	OK	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example response

```
{
  "resources": [
    {
      "migrationTaskId": 1,
      "migrationTaskName": "MigrationTest",

```

```

        "comments": null,
        "jobId": null,
        "schedule": {
            "datetime": "2018-01-01T00:00:00.000Z"
        },
        "migrationPairCount": 1,
        "samePoolContainingSourceVolume": false,
        "volumeDeletion": true,
        "volumeShredding": false,
    }
],
"total": 1,
"nextToken": null
}

```

## Getting a migration task

You can retrieve a specific migration task for Volume Migration in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks/
migrationTaskId
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "migrationTaskId": "",
  "migrationTaskName": "",
  "comments": "",
  "jobId": "",
  "schedule": {
    "datetime": ""
  },
  "migrationPairCount":
  "samePoolContainingSourceVolume": ,
  "volumeDeletion": ,
  "volumeShredding": ,
  "patterns": ["", ...]
}

```

Parameter	Type	Description
migrationTaskId	Integer	ID of the migration task.
migrationTaskName	String	Name of the migration task. Min=1, max=32 characters.
comments	String	Comment for the migration task. Min=1, max=255 characters.
jobId	String	ID of the corresponding migration job. This parameter is only available once the job is executed.
schedule	Object	Schedule of the migration job.
datetime	String	Scheduled date and time of the migration job to be executed (in ISO 8601 format).
migrationPairCount	Integer	Number of migration pairs defined in the task.
samePoolContainingSource Volume	Boolean	Whether to use the same pool containing the source volume for the target volume.
volumeDeletion	Boolean	Whether to delete source volumes after the migration is completed.
volumeShredding	Boolean	Whether to shred source volumes after the migration is completed.
patterns	List	List of the pattern strings used for shredding.

**Return codes**

Status Code	HTTP name	Description
200	OK	The server has started the operation.

Status Code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example response

```
{
  "resources": [
    {
      "migrationTaskId": 1,
      "migrationTaskName": "MigrationTest",
      "comments": null,
      "jobId": null,
      "schedule": {
        "datetime": "2018-01-01T00:00:00.000Z"
      },
      "migrationPairCount": 1,
      "samePoolContainingSourceVolume": false,
      "volumeDeletion": true,
      "volumeShredding": false,
    }
  ],
  "total": 1,
  "nextToken": null
}
```

## Creating a migration task

You can create a migration task for Volume Migration in Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks
```

**Request structure**

The request body structure is shown below:

```
{
  "migrationTaskName": "",
  "comments": "",
  "schedule": {
    "datetime": ""
  },
  "volumeIdRange": {
    "from": "",
    "to": ""
  },
  "samePoolContainingSourceVolume": ,
  "targetPoolId": ,
  "sourceVolumeIds": [, ...],
  "drsSetting": "" ,
  "dkcDataSavingType": "" ,
  "volumeDeletion": ,
  "volumeShredding": ,
  "patterns": [ "", ... ]
}
```

Parameter	Required	Type	Description
migrationTaskName	Yes	String	Name of the migration task. Min=1, max=32 characters.
comments	No	String	Comment for the migration task. Min=1, max=255 characters.
schedule	No	Object	Schedule information of the migration job, such as: <ul style="list-style-type: none"> <li>datetime: Scheduled date and time of the migration job to be executed in ISO 8601 format (YYYY-MM-DDThh:mm:ssZ). If executing immediately, specify null.</li> </ul>
volumeIdRange	No	Integer	A volume ID range to assign as migration target volumes.
samePoolContainingSourceVolume	No	Boolean	Whether to use the same pool containing the source volume for the target volume.

Parameter	Required	Type	Description
targetPoolId	No	Integer	<p>The ID of the storage pool to be migrated.</p> <p>Omit this parameter if you want to use the same pool that contains the source volume instead of migrating it to a different pool.</p> <p>In this case, set the <code>samePoolContainingSourceVolume</code> parameter to true.</p>
sourceVolumeIds	Yes	List	List of up to 300 migration source volume IDs.
drsSetting	No	String	<p>The setting for DRS for the target volumes. Valid values are AUTO, ENABLED and DISABLED.</p> <p>AUTO: Setting the target volume to the same setting as the source volume.</p> <p><b>Note:</b> If AUTO is specified on external migration for VSP One Block, <code>drsSetting</code> for the target volume will be ENABLED.</p>
dkcDataSavingType	No	String	<p>Type of controller-based capacity saving. Valid values are AUTO, NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION.</p> <p>AUTO sets the target volume to the same setting as the source volume.</p> <p>If the source volume has controller-based capacity saving disabled and <code>drsSetting</code> is set to ENABLED, the target volume will be created using deduplication and compression.</p> <p>NONE results in no capacity saving setting on the target volume. NONE cannot be specified on migration for VSP One Block.</p> <p>The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression.</p> <p>COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools.</p>

Parameter	Required	Type	Description
			<p>COMPRESSION and DEDUPLICATION_AND_COMPRESSION cannot be set for VSP 5000 series if the subscription limit of the pool is not unlimited. If the option is not set, Administrator selects type which is the same as the source volume.</p> <p><b>Note:</b> If AUTO is specified on external migration for VSP One Block, dkcdDataSavingType for the target volume will be DEDUPLICATION_AND_COMPRESSION.</p>
volumeDeletion	No	Boolean	Whether to delete source volumes after the migration is completed. The default is false.
VolumeShredding	No	Boolean	Whether to shred source volumes after the migration is completed. The default is false.
patterns	No	List	List of the pattern strings used for shredding. The maximum number of patterns is 7. If patterns is not specified and volumeShredding is set to true, basic shredding is done.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
```

```
[
],
"links":
[
{
"rel": "_self",
"href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.



Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "migrationTaskName": "DpPool_001",
```

```

    "comments": "",
    "schedule": {
      "datetime": "2020-11-07T13:18:38.331Z"
    },
    "volumeIdRange": {
      "from": 0,
      "to": 50000,
    },
    "targetPoolId": 1,
    "sourceVolumeIds": [1234, 5678],
    "drsSetting": "AUTO",
    "dkcDataSavingType": "AUTO",
    "volumeDeletion": true
    "volumeShredding": false
  }

```

## Interrupting a running migration job

You can interrupt a running migration job in Ops Center Administrator.

### HTTP request syntax (URI)

```

POST https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks/
migrationTaskId/interrupt

```

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,

```

```

"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Updating a migration task

You can update a migration task for Volume Migration in Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks/
migrationTaskId
```

**Request structure**

The request body structure is shown below:

```
{
  "migrationTaskName": "",
  "comments": "",
  "schedule": {
    "datetime": ""
  },
  "volumeIdRange": {
    "from": "",
    "to": "",
  },
  "samePoolContainingSourceVolume": ,
  "targetPoolId": ,
  "drsSetting": "",
  "dkcDataSavingType": ""
  "volumeDeletion": ,
  "volumeShredding": ,
  "patterns": [ "", ... ]
}
```

Parameter	Required	Type	Description
migrationTaskName	No	String	Name of the migration task. Min=1, max=32 characters.
comments	No	String	Comment for the migration task. Min=1, max=255 characters.
schedule	No	Object	Schedule information for the migration job, such as: <ul style="list-style-type: none"> <li>datetime: Scheduled date and time of the migration job to be executed in ISO 8601 format (YYYY-MM-DDThh:mm:ssZ). If executing immediately, specify null.</li> </ul>
volumeIdRange	No	Integer	A volume ID range to assign as migration target volumes.
samePoolContainingSourceVolume	No	Boolean	Whether to use the same pool containing the source volume for the target volume.

Parameter	Required	Type	Description
targetPoolId	No	Integer	<p>The ID of the storage pool to be migrated.</p> <p>Omit this parameter if you want to use the same pool that contains the source volume instead of migrating it to a different pool.</p> <p>In this case, set the <code>samePoolContainingSourceVolume</code> parameter to true.</p>
drsSetting	No	String	<p>The setting for DRS for the target volumes. Valid values are AUTO, ENABLED and DISABLED.</p> <p>AUTO: Setting the target volume to the same setting as the source volume.</p> <p><b>Note:</b> If AUTO is specified on external migration for VSP One Block, <code>drsSetting</code> for the target volume will be ENABLED.</p>
dkcDataSavingType	No	String	<p>Type of controller-based capacity saving. Valid values are AUTO, NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION.</p> <p>AUTO sets the target volume to the same setting as the source volume.</p> <p>If the source volume has controller-based capacity saving disabled and <code>drsSetting</code> is set to ENABLED, the target volume will be created using deduplication and compression.</p> <p>NONE results in no capacity saving setting on the target volume. NONE cannot be specified on migration for VSP One Block.</p> <p>The deduplication setting of the target storage pool is automatically enabled if DEDUPLICATION_AND_COMPRESSION is selected, and if it is the first time a storage pool creates volumes using deduplication and compression.</p> <p>COMPRESSION and DEDUPLICATION_AND_COMPRESSION are not available for Snap pools.</p>

Parameter	Required	Type	Description
			<p>COMPRESSION and DEDUPLICATION_AND_COMPRESSION cannot be set for VSP 5000 series if the subscription limit of the pool is not unlimited. If the option is not set, Administrator selects type which is the same as the source volume.</p> <p><b>Note:</b> If AUTO is specified on external migration for VSP One Block, dkcdDataSavingType for the target volume will be DEDUPLICATION_AND_COMPRESSION.</p>
volumeDeletion	No	Boolean	Whether to delete source volumes after the migration is completed.
volumeShredding	No	Boolean	Whether to shred source volumes after the migration is completed.
patterns	No	List	List of the pattern strings used for shredding.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
    ]
}
```

```

    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.



Parameter	Type	Description
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "migrationTaskName": "DpPool_001",
  "comments": "",
  "schedule": {
    "datetime": "2020-11-07T13:18:38.331Z"
  },
  "volumeIdRange": {
    "from": 0,
    "to": 50000
  },
}
```

```

"targetPoolId":1,
"drsSetting":"AUTO",
"dkcDataSavingType":"AUTO",
"volumeDeletion": true,
"volumeShredding": false
}

```

## Deleting a migration task

You can delete a migration task in Ops Center Administrator. There are two use cases for this method:

- After the job for the migration task is finished, you should delete the migration task in order to clean up the resource in Ops Center Administrator.
- If the migration task is scheduled for the future and the job has not started, you can cancel the job as well as cleaning up the resource in Ops Center Administrator.

### HTTP request syntax (URI)

```

DELETE https://ipAddress/v1/storage-systems/storageSystemId/migration-tasks/
migrationTaskId

```

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
      {
    },
    "user": "",
    "status": "",
    "createdDate":,
    "scheduledDate":,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [

```

```

],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.

Parameter	Type	Description
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Listing migration pairs

You can retrieve a list of migration pairs for Volume Migration in Ops Center Administrator.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/migration-pairs?
q=migrationTaskId:migrationTaskId
```

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "migrationPairId": ,
  "migrationTaskId": ,
  "sourceVolumeId": ,
  "sourcePoolId":,
  "sourceExternalParityGroupId", ""
  "targetVolumeId": ,
  "targetPoolId": ,
  "status": "",
  "copyProgress":
  "copyGroupName": "",
  "drsSetting": "",
  "dkcDataSavingType": ""
}
```

Parameter	Type	Description
migrationPairId	Integer	ID of the migration pair.
migrationTaskId	Integer	ID of the migration task.
sourceVolumeId	Long	ID of the migration source volume.
sourcePoolId	Integer	ID of the pool from which the migration source volume is allocated.
sourceExternalParityGroupId	String	ID of the external parity group from which the migration source volume is allocated.
targetVolumeId	Long	ID of the migration target volume.
targetPoolId	Integer	ID of the pool from which the migration target volume is allocated.

Parameter	Type	Description
status	String	<p>The status of the migration copy. Valid values:</p> <ul style="list-style-type: none"> <li>▪ NOT_MIGRATED: Volume Migration has not started.</li> <li>▪ MIGRATING: Volume Migration is in progress.</li> <li>▪ MIGRATED: Volume Migration has completed.</li> <li>▪ MIGRATED_POST_PROCESSING: Volume Migration has completed and post process is running.</li> <li>▪ MIGRATED_POST_PROCESSED: Volume Migration has completed and post process is finished. Refer to the migration tasks's job result to check migration and post process result.</li> <li>▪ INVALID: source or target volume does not exist, or the pool of source or target volume changed.</li> </ul>
copyProgress	Integer	The progress of the migration copy (0-100).
copyGroupName	String	The name of the copy group for migration.
drsSetting	String	<p>DRS settings for the target volumes. Valid values are ENABLED and DISABLED.</p> <p>If the value null is returned, the target volume will be set to the same setting as the source volume.</p>
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEDUPLICATION_AND_COMPRESSION, and NONE.

**Return codes**

Status code	HTTP name	Description
200	OK	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

```
{
  "resources": [
    {
      "migrationPairId": 2,
      "migrationTaskId": 2,
      "sourceVolumeId": 684,
      "sourcePoolId": 10,
      "sourceExternalParityGroupId": null,
      "targetVolumeId": null,
      "targetPoolId": 0,
      "status": "NOT_MIGRATED",
      "copyProgress": null,
      "copyGroupName": null,
      "drsSetting": "ENABLED",
      "dkcDataSavingType": "COMPRESSION"
    }
  ],
  "total": 1,
  "nextToken": null
}
```

## Chapter 5: Fabric switch management resources

This module describes the fabric switch management operations.

Request	Method	URI	Role
<a href="#">Listing fabric switches (on page 600)</a>	GET	/v1/san-fabrics	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a fabric switch (on page 602)</a>	GET	/v1/san-fabrics/ <i>sanFabricId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a fabric switch (on page 604)</a>	POST	/v1/san-fabrics	System administrator
<a href="#">Editing a fabric switch (on page 608)</a>	POST	/v1/san-fabrics/ <i>sanFabricId</i>	System administrator
<a href="#">Deleting a fabric switch (on page 611)</a>	DELETE	/v1/san-fabrics/ <i>sanFabricId</i>	System administrator

### Listing fabric switches

You can display a list of fabric switches.

#### HTTP request syntax (URI)

```
GET https://ipAddress/v1/san-fabrics
```



**Request structure**

Not applicable.

**Response structure**

```
{
  "resources":
  [
    {
      "sanFabricId": "",
      "switchType": "",
      "virtualFabricId": ,
      "principalSwitchAddress": "",
      "principalSwitchUsername": "",
      "principalSwitchPortNumber":
    },
    ...
  ]
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
sanFabricId	String	Fabric switch identifier.
switchType	String	Type of switch, such as CISCO or BROCADE.
virtualFabricId	Integer	Virtual fabric identifier. For Cisco switches, this is the user-defined virtual storage area network identifier (VSAN ID). For Brocade switches, this is null.
principalSwitchAddress	String	Fabric switch IP Address.
principalSwitchUsername	String	Fabric switch user name.
principalSwitchPortNumber	Integer	Fabric switch port.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/san-fabrics
```

### Example response

```
{
  "resources":
  [
    {
      "sanFabricId": "2__4",
      "switchType": "BROCADE",
      "virtualFabricId": null,
      "principalSwitchAddress": "172.17.91.39",
      "principalSwitchUsername": "admin",
      "principalSwitchPortNumber": 22
    }
  ],
  "total": 4,
  "nextToken": null
}
```

## Getting a fabric switch

You can display the details of a specific fabric switch.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/san-fabrics/sanFabricId
```

Use the fabric switch identifier for *sanFabricId*.

### Request structure

Not applicable.

### Response structure

```
{
  "sanFabricId": "",
  "switchType": "",
  "virtualFabricId": "",
  "principalSwitchAddress": "",
  "principalSwitchUsername": "",
  "principalSwitchPortNumber":
}
```

Parameter	Type	Description
sanFabricId	String	Fabric switch identifier.
switchType	String	Type of switch, such as CISCO or BROCADE.
virtualFabricId	Integer	Virtual fabric identifier. For Cisco switches, this is the user-defined virtual storage area network identifier (VSAN ID). For Brocade switches, this is null.
principalSwitchAddress	String	Fabric switch IP Address.
principalSwitchUsername	String	Fabric switch user name.
principalSwitchPortNumber	Integer	Fabric switch port.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Code

Request with JSON command:

```
https://10.20.88.199:443/v1/san-fabrics/1__1
```

JSON Response:

```
{
  "sanFabricId": "1__1",
  "switchType": "CISCO",
  "virtualFabricId": "15",
  "principalSwitchAddress": "10.20.90.83",
  "principalSwitchUsername": "admin",
  "principalSwitchPortNumber": 22
}
```

## Creating a fabric switch

You can create a fabric switch.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/san-fabrics
```

### Request structure

```
{
  "fabrics": [{
    "principalSwitchAddress": "",
    "principalSwitchUsername": "",
    "principalSwitchPassword": "",
    "principalSwitchPortNumber": ,
  ]
}
```

```

    "virtualFabricId": "",
    "switchType": ""
  }]
}

```

Parameter	Required	Type	Description
principalSwitchAddress	Yes	String	Fabric switch IP address.
principalSwitchUsername	Yes	String	Fabric switch user name.
principalSwitchPassword	Yes	String	Fabric switch password
principalSwitchPortNumber	Yes	Integer	Fabric switch port. For Brocade switches with firmware versions later than 9.0, specify 443. For Cisco switches or for Brocade switches with firmware versions earlier than 9.0, specify ssh port of the target fabric switch.
virtualFabricId	Yes	String	Virtual fabric identifier. For Cisco switches, this is the user-defined virtual storage area network identifier (VSAN ID). For Brocade switches, this is null.
switchType	Yes	String	Type of switch, such as CISCO or BROCADE.

### Response structure

The response body structure is as follows:

```

{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,

```

```

    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
    "tags":
    [
    ],
    "isSystem":
  }

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.

Parameter	Type	Description
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.115/v1/san-fabrics
```

**Example request**

```
{
  "fabrics": [{
    "virtualFabricId": "2",
    "principalSwitchAddress": "172.17.91.26",
    "principalSwitchUsername": "name",
    "principalSwitchPassword": "XXXXX",
    "principalSwitchPortNumber": 22,
    "switchType": "CISCO"
  }]
}
```

**Editing a fabric switch**

You can edit the details of a specific fabric switch.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/san-fabrics/sanFabricId
```

Use the identifier for the switch that you want to update as the *sanFabricId*.

**Request structure**

```
{
  "virtualFabricId": "",
  "principalSwitchAddress": "",
  "principalSwitchUsername": "",
  "principalSwitchPassword": "",
  "principalSwitchPortNumber":
}
```

Parameter	Required	Type	Description
virtualFabricId	Yes	String	Virtual fabric identifier. For Cisco switches, this is the user-defined virtual storage area network identifier (VSAN ID). For Brocade switches, this is null.
principalSwitchAddress	Yes	String	Fabric switch IP address.
principalSwitchUsername	Yes	String	Fabric switch user name.



Parameter	Required	Type	Description
principalSwitchPassword	Yes	String	Fabric switch password.
principalSwitchPortNumber	Yes	String	Fabric switch port.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/san-fabrics/2__4
```

**Example request**

```
{
  "virtualFabricId": "null",
  "principalSwitchAddress": "172.17.91.39",
  "principalSwitchUsername": "MD",
  "principalSwitchPassword": "password",
  "principalSwitchPortNumber": 22
}
```

## Deleting a fabric switch

You can remove a fabric switch.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/san-fabrics/sanFabricId
```

Use the fabric switch ID as the *sanFabricId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

#### Return codes

Status code	HTTP name	Description
200	OK	Success.

Status code	HTTP name	Description
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

---

## Chapter 6: Virtual storage machine management resources

This module describes the virtual storage machine management operations.

Request	Method	URI	Role
<a href="#">Listing virtual storage machines (on page 618)</a>	GET	/v1/virtual-storage-machines	Storage administrat or System administrat or Security administrat or Monitoring
<a href="#">Listing volume IDs assigned to a physical storage system in a virtual storage machine (on page 627)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> / physical-storage-systems/ physicalStorageSystemId/ <i>assigned-volume-ids</i>	Storage administrat or System administrat or Security administrat or Monitoring
<a href="#">Getting a virtual storage machine (on page 621)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i>	Storage administrat or System administrat or Security administrat or Monitoring

Request	Method	URI	Role
<a href="#">Getting a physical storage system summary in a virtual storage machine (on page 624)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> / physical-storage-systems/ <i>physicalStorageSystemId</i> / summary	Storage administrator or System administrator or Security administrator or Monitoring
<a href="#">Creating a virtual storage machine (on page 639)</a>	POST	/v1/virtual-storage-machines	Storage administrator
<a href="#">Adding resources to a virtual storage machine (on page 645)</a>	POST	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /add- undefined-resources	Storage administrator
<a href="#">Listing volume IDs in a virtual storage machine (on page 629)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> / volume-ids	Storage administrator or System administrator or Security administrator or Monitoring
<a href="#">Getting a volume ID in a virtual storage machine (on page 632)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> / volume-ids? q=storageSystemId:  <i>storageSystemId</i> AND volumeId: <i>volumeId</i>	Storage administrator or System administrator or Security administrator or Monitoring
<a href="#">Listing host group IDs in a virtual storage machine (on page 634)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> / host-group-ids	Storage administrator



Request	Method	URI	Role
			System administrator Security administrator Monitoring
<a href="#">Getting a host group ID in a virtual storage machine (on page 637)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /host-group-ids? q=storageSystemId: <i>storageSystemId</i> AND hostGroupId: <i>hostGroupId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a virtual storage machine summary (on page 651)</a>	GET	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Moving volumes to a virtual storage machine (on page 652)</a>	POST	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /physical-storage-systems/ <i>physicalStorageSystemId</i> /add-existing-volumes	Storage administrator
<a href="#">Removing resources from a virtual storage machine (on page 656)</a>	POST	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /remove-undefined-resources	Storage administrator
<a href="#">Removing defined volumes from a virtual storage machine (on page 661)</a>	POST	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i> /physical-storage-systems/ <i>physicalStorageSystemId</i> /remove-existing-volumes	Storage administrator

Request	Method	URI	Role
<a href="#">Deleting a physical storage system from a virtual storage machine (on page 664)</a>	DELETE	/v1/virtual-storage-machines/ <i>virtualStorageSystemId</i> / physical-storage-systems/ <i>physicalStorageSystemId</i>	Storage administrator
<a href="#">Deleting a virtual storage machine (on page 667)</a>	DELETE	/v1/virtual-storage-machines/ <i>virtualStorageMachineId</i>	Storage administrator

## Listing virtual storage machines

You can display a list of all virtual storage machines in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  {
    "virtualStorageMachineId": "",
    "storageSystemId": "",
    "model": "",
    "physicalStorageSystemIds": [""],
    "resourceGroups": [
      {
        "physicalStorageSystemId": "",
        "resourceGroupId": ,
        "resourceGroupName": ""
      },
      ...
    ]
  },
  ...
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
virtualStorageMachineId	String	Unique key to identify the VSM.
storageSystemId	String	ID of the virtual storage system.
model	String	Name of the VSM model.
physicalStorageSystemIds	List	List of physical storage system IDs.
resourceGroups	List	List of the resource groups.
resourceGroups.physicalStorageSystemId	String	ID of the storage system.
resourceGroups.resourceGroupId	Integer	ID of the resource group.
resourceGroups.resourceGroupName	String	Name of the resource group.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTTUNoSXVYNlFPU1ljZzswOw==</pre>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Request example**

Request with JSON command:

```
https://172.17.64.118/v1/virtual-storage-machines
```

**Response example**

JSON response:

```
{
  "resources": [
    {
      "virtualStorageMachineId": "410501-VSPF400-F600andVSPG400-G600",
      "storageSystemId": "410501",
      "model": "VSP F400, F600 and VSP G400, G600",
      "physicalStorageSystemIds": ["410500", "410209"],
      "resourceGroups": [
        {
          "physicalStorageSystemId": "410500",
          "resourceGroupId": 1,
          "resourceGroupName": "rsg_name_1"
        },
        {
          "physicalStorageSystemId": "410209",
          "resourceGroupId": 2,
          "resourceGroupName": "rsg_name_2"
        }
      ]
    }
  ]
}
```

```

    ]
  },
  {
    "virtualStorageMachineId": "410209-VSPF800andVSPG800",
    "storageSystemId": "410209",
    "model": "VSP F800 and VSP G800",
    "physicalStorageSystemIds": ["410500", "410209"],
    "resourceGroups": [
      {
        "physicalStorageSystemId": "410500",
        "resourceGroupId": 3,
        "resourceGroupName": "rsg_name_3"
      },
      {
        "physicalStorageSystemId": "410209",
        "resourceGroupId": 0,
        "resourceGroupName": "meta_resource"
      }
    ]
  }
],

"total": 2,
"nextToken": null
}

```

## Getting a virtual storage machine

You can get information about a specific virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "virtualStorageMachineId": "",
  "storageSystemId": "",
  "model": "",
  "physicalStorageSystemIds": [""],
  "resourceGroups": [

```

```

    {
        "physicalStorageSystemId": "",
        "resourceGroupId": ,
        "resourceGroupName": ""
    },
    ...
]
}

```

Parameter	Type	Description
virtualStorageMachineId	String	Unique key to identify the VSM.
storageSystemId	String	ID of the virtual storage system.
model	String	Name of the VSM model.
physicalStorageSystemIds	List	List of physical storage system IDs.
resourceGroups	List	List of the resource groups.
resourceGroups.physicalStorageSystemId	String	ID of the storage system.
resourceGroups.resourceGroupId	Integer	ID of the resource group.
resourceGroups.resourceGroupName	String	Name of the resource group.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Request example**

Request with JSON command:

```
https://172.17.64.118/v1/virtual-storage-machines/410501-VSPF400-F600andVSPG400-G600
```

**Response example**

JSON response:

```
{
  "virtualStorageMachineId": "410501-VSPF400-F600andVSPG400-G600",
  "storageSystemId": "410501",
  "model": "VSP F400, F600 and VSP G400, G600",
  "physicalStorageSystemIds": ["410500", "410209"]
  "resourceGroups": [
    {
      "physicalStorageSystemId": "410500",
      "resourceGroupId": 1,
      "resourceGroupName": "rsg_name_1"
    },
    {
      "physicalStorageSystemId": "410209",
      "resourceGroupId": 2,
      "resourceGroupName": "rsg_name_2"
    }
  ]
}
```

## Getting a physical storage system summary in a virtual storage machine

You can display a summary of physical storage systems in a virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/physical-storage-systems/physicalStorageSystemId/summary
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "definedVolumeCount": ,
  "undefinedVolumeCount": ,
  "resourceGroups": [
    {
      "resourceGroupId": ,
      "resourceGroupName": "",
      "definedVolumeCount": ,
      "undefinedVolumeCount":
    },
    ...
  ],
  "hostGroups": [
    {
      "storagePortId": "",
      "definedCount": ,
      "undefinedCount": ,
      "resourceGroups": [
        {
          "resourceGroupId": ,
          "resourceGroupName": "",
          "definedCount": ,
          "undefinedCount":
        },
        ...
      ]
    },
    ...
  ]
}
```



Parameter	Type	Description
undefinedVolumeCount	Long	Undefined volume count.
definedVolumeCount	Long	Defined volume count.
resourceGroups	List	List of the resource groups.
resourceGroups.resourceGroupId	Integer	ID of the resource group.
resourceGroups.resourceGroupName	String	Name of the resource group.
resourceGroups.definedVolumeCount	Long	Defined volume count in the resource group.
resourceGroups.undefinedVolumeCount	Long	Undefined volume count in the resource group.
hostGroups	List	List of host groups.
storagePortId	String	Storage port ID of the host group.
undefinedCount(HG)	Long	Undefined host group count.
definedCount(HG)	Long	Defined host group count.
hostGroups.resourceGroups	List	List of host groups per resource group.
hostGroups.resourceGroupId	Integer	ID of the resource group.
hostGroups.resourceGroupName	String	Name of the resource group.
hostGroups.definedVolumeCount	Long	Defined host group count on the storage port in the resource group.
hostGroups.undefinedVolumeCount	Long	Undefined host group count on the storage port in the resource group.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Response example**

```
{
  "definedVolumeCount": 3,
  "undefinedVolumeCount": 7,
  "resourceGroups": [
    {
      "resourceGroupId": 1,
      "resourceGroupName": "rsg_name_1",
      "definedVolumeCount": 0,
      "undefinedVolumeCount": 3
    },
    {
      "resourceGroupId": 2,
      "resourceGroupName": "rsg_name_2",
      "definedVolumeCount": 3,
      "undefinedVolumeCount": 4
    }
  ],
  "hostGroups": [
    {
      "storagePortId": "CL1-A",
      "definedCount": 4,
      "undefinedCount": 2,
      "resourceGroups": [
        {
          "resourceGroupId": 2,
          "resourceGroupName": "rsg_name_2",

```

```
        "definedCount": 3,
        "undefinedCount": 2
      },
      {
        "resourceGroupId": 3,
        "resourceGroupName": "rsg_name_3",
        "definedCount": 1,
        "undefinedCount": 0
      }
    ]
  },
  {
    "storagePortId": "CL3-B",
    "definedCount": 1,
    "undefinedCount": 0,
    "resourceGroups": [
      {
        "resourceGroupId": 3,
        "resourceGroupName": "rsg_name_3",
        "definedCount": 1,
        "undefinedCount": 0
      }
    ]
  }
]
```

If the physical storage in the virtual storage machine has no resources:

```
{
  "definedVolumeCount": 0,
  "undefinedVolumeCount": 0,
  "resourceGroups": [],
  "hostGroups": []
}
```

## Listing volume IDs assigned to a physical storage system in a virtual storage machine

Lists the volume IDs assigned to a physical storage system in a virtual storage machine

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/physical-storage-systems/physicalStorageSystemId/assigned-volume-ids
```

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "definedVolumeIds": [],
  "undefinedVolumeIds": []
}
```

Parameter	Type	Description
definedVolumeIds	List	List of defined volume IDs in Long.
undefinedVolumeIds	List	List of undefined volume IDs in Long.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Response**

```
{
  "definedVolumeIds": [1001, 1002, ...],
}
```

```
"undefinedVolumeIds": [2001, 2002, ...]
}
```

## Listing volume IDs in a virtual storage machine

You can list volume IDs from a specific virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/volume-ids
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources": [
    {
      "virtualStorageMachineId": "",
      "storageSystemId": "",
      "volumeId": ,
      "virtualVolumeId": ,
      "label": "",
      "size": ,
      "isDefined": ,
      "hasLunPaths": ,
      "isExternalVol": ,
      "isSystemVol": ,
      "resourceGroupName": "",
      "resourceGroupId":
    },
    ...
  ],
  "total": ,
  "nextToken": ""
}
```

Parameter	Type	Description
volumeId	Long	The ID number of the volume within the parent storage system.

Parameter	Type	Description
virtualVolumeld	Long	The ID number of the virtual volume. If the ID is not assigned, null is returned.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The ID of the storage system.
label	String	The name of the volume.
size	String	The size of the volume, in bytes.
hasLunPaths	Boolean	Specifies whether the volume has LUN paths or not.
isExternalVol	Boolean	Specifies whether the volume is external.
isDefined	Boolean	Specifies whether the volume is defined or not.
resourceGroupId	Long	The ID number of the resource group.
resourceGroupName	String	The name of the resource group.
isSystemVol	Boolean	Specifies whether the volume is managed or not.
total	Long	The total number of resources.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append question mark (?) and "nextToken=", and then the token.</p> <p>Example:</p> <p><a href="https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnIBbmRGZXRjaDs xOzEyMTM6Q08yc2ZIRlhTTUNoSX VYNIFPUS1jZzswOw==">https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnIBbmRGZXRjaDs xOzEyMTM6Q08yc2ZIRlhTTUNoSX VYNIFPUS1jZzswOw==</a></p>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Response example**

JSON response:

```
{
  "resources": [
    {
      "volumeId": 0,
      "virtualVolumeId": 0,
      "virtualStorageMachineId": "15283-VSP5100H-5500H",
      "storageSystemId": "15283",
      "label": "volume_0",
      "size": "38297532",
      "hasLunPaths": true,
      "isExternalVol": false,
      "isDefined": true,
      "resourceGroupId": 0,
      "resourceGroupName": "meta_resource",
      "isSystemVol": true
    },
    {
      "volumeId": 1,
      "virtualVolumeId": 1,
      "virtualStorageMachineId": "15283-VSP5100H-5500H",
      "storageSystemId": "15283",
      "hasLunPaths": false,
      "isExternalVol": false,
      "isDefined": false,

```

```

        "resourceGroupId": 0,
        "resourceGroupName": "meta_resource",
        "isSystemVol": false
    },
    ...
],
"total": 1250,
"nextToken": "cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTTUNoSXVYNlFPUS1jZzswOw=="
}

```

## Getting a volume ID in a virtual storage machine

You can get volume IDs from specific virtual storage machines in Ops Center Administrator.

### HTTP request syntax (URI)

```

GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/volume-ids?
q=storageSystemId:storageSystemId AND volumeId:volumeId

```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "virtualStorageMachineId": "",
  "storageSystemId": "",
  "volumeId": ,
  "virtualVolumeId": ,
  "label": "",
  "size": ,
  "isDefined": ,
  "hasLunPaths": ,
  "isExternalVol": ,
  "isSystemVol": ,
  "resourceGroupName": "",
  "resourceGroupId":
}

```

Parameter	Type	Description
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.



Parameter	Type	Description
storageSystemId	String	The ID of the storage system.
volumeId	Long	The ID number of the volume within the parent storage system.
virtualVolumeId	Long	The ID number of the virtual volume. If the ID is not assigned, null is returned.
label	String	The name of the volume.
size	String	The size of the volume, in bytes.
isDefined	Boolean	Specifies whether the volume is defined.
hasLunPaths	Boolean	Specifies whether the volume has LUN paths.
isExternalVol	Boolean	Specifies whether the volume is external.
isSystemVol	Boolean	Specifies whether the volume is managed.
resourceGroupId	Long	The ID number of the resource group.
resourceGroupName	String	The name of the resource group.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Response example**

JSON response:

```
{
  "virtualStorageMachineId": "15283-VSP5100H-5500H",
  "storageSystemId": "15283",
  "volumeId": 0,
  "virtualVolumeId": 0,
  "label": "volume_0",
  "size": 38297532,
  "isDefined": true,
  "hasLunPaths": true,
  "isExternalVol": false,
  "isSystemVol": false,
  "resourceGroupName": "meta_resource",
  "resourceGroupId": 0
}
```

## Listing host group IDs in a virtual storage machine

You can get a list of host group IDs from a specific virtual storage machine in Ops Center Administrator.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/host-group-ids
```

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "resources": [
    {
      "hostGroupId": "",
      "hostGroupNumber": ,

```

```

        "storagePortId": "",
        "virtualStorageMachineId": "",
        "storageSystemId": "",
        "hostGroupName": "",
        "hasLunPaths": ,
        "isDefined": ,
        "resourceGroupId": ,
        "resourceGroupName": ""
    },
    ...
],
"total": ,
"nextToken": ""
}

```

Parameter	Type	Description
hostGroupId	String	ID of the host group
hostGroupNumber	Integer	ID number of the host group
storagePortId	String	ID of the storage port
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	ID of the storage system.
hostGroupName	String	Name of the host group
hasLunPaths	Boolean	Whether the volume has LUN paths or not.
isDefined	Boolean	Whether the volume is defined or not.
resourceGroupId	Long	The ID number of the resource group.
resourceGroupName	String	Name of the resource group.
total	Long	Total number of resources.

Parameter	Type	Description
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append question mark (?) and "nextToken= ", and then the token.</p> <p>Example:</p> <p><a href="https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZlRlhTTUNoSXVYNlFPUS1jZzswOw==">https://sa_server/v1/storage-systems/serial/disks?nextToken=cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZlRlhTTUNoSXVYNlFPUS1jZzswOw==</a></p>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Response example

JSON response:

```
{
  "resources": [
    {
      "hostGroupId": "CL1-A-0",
      "hostGroupNumber": 0,
      "storagePortId": "CL1-A",
      "virtualStorageMachineId": "15283-VSP5100H-5500H",
      "storageSystemId": "15283",

```

```

        "hostGroupName": "1A-G00",
        "hasLunPaths": true,
        "isDefined": true,
        "resourceGroupId": 0,
        "resourceGroupName": "meta_resource"
    },
    {
        "hostGroupId": "CL1-A-1",
        "hostGroupNumber": 1,
        "storagePortId": "CL1-A",
        "virtualStorageMachineId": "15283-VSP5100H-5500H",
        "storageSystemId": "15283",
        "hasLunPaths": false,
        "isDefined": false,
        "resourceGroupId": 0,
        "resourceGroupName": "meta_resource"
    },
    ...
],
"total": 1250,
"nextToken": "cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZIRlhTTUNoSXVYNlFPUS1jZzswOw=="
}

```

## Getting a host group ID in a virtual storage machine

You can get a host group ID from a specific virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/host-group-ids?q=storageSystemId:storageSystemId AND hostGroupId:hostGroupId
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
    "hostGroupId": "",
    "hostGroupNumber": ,
    "storagePortId": "",
    "virtualStorageMachineId": "",
    "storageSystemId": "",
    "hostGroupName": "",
    "hasLunPaths": ,

```

```

    "isDefined": ,
    "resourceGroupId": ,
    "resourceGroupName": ""
  }

```

Parameter	Type	Description
hostGroupId	String	ID of the host group
hostGroupNumber	Integer	ID number of the host group
storagePortId	String	ID of the storage port
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	ID of the storage system.
hostGroupName	String	Name of the host group
hasLunPaths	Boolean	Whether the volume has LUN paths or not.
isDefined	Boolean	Whether the volume is defined or not.
resourceGroupId	Long	The ID number of the resource group.
resourceGroupName	String	Name of the resource group.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Response example

JSON response:

```
{
  "hostGroupId": "CL1-A-0",
    "hostGroupNumber": 0,
    "storagePortId": "CL1-A",
    "virtualStorageMachineId": "15283-VSP5100H-5500H",
    "storageSystemId": "15283",
    "hostGroupName": "1A-G00",
    "hasLunPaths": true,
    "isDefined": true,
    "resourceGroupId": 0,
    "resourceGroupName": "meta_resource"
}
```

## Creating a virtual storage machine

You can create a new virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/virtual-storage-machines
```

### Request structure

The request body structure is shown below:

```
{
  "storageSystemId": "",
  "model": "",
  "physicalStorageSystems": [
    {
      "storageSystemId": "",
      "resourceGroupName": "",
      "numberOfVolumes": ,
      "volumeIdRange": {
        "from": ,
        "to":
      },
    },
  ],
}
```

```

    "hostGroups": [
      {
        "portId": "",
        "number": ,
      },
      ...
    ],
    "hostGroupIds": [""]
  },
  ...
]
}

```

Parameter	Required	Type	Description
storageSystemId	Yes	String	ID of the virtual storage system.
model	Yes	String	Name of the VSM model. The valid values are: <ul style="list-style-type: none"> <li>▪ VSP_F350</li> <li>▪ VSP_F370</li> <li>▪ VSP_F700</li> <li>▪ VSP_F900</li> <li>▪ VSP_G200</li> <li>▪ VSP_G350</li> <li>▪ VSP_G370</li> <li>▪ VSP_G700</li> <li>▪ VSP_G900</li> <li>▪ VSP_F800_AND_VSP_G800</li> <li>▪ VSP_F400_F600_AND_VSP_G400_G600</li> <li>▪ HUS_VM</li> <li>▪ VSP_F1500_AND_VSP_G1000_G1500</li> <li>▪ VSP</li> <li>▪ USP_VM</li> <li>▪ USP_V</li> <li>▪ USP</li> <li>▪ NSC</li> </ul>



Parameter	Required	Type	Description
			<ul style="list-style-type: none"> <li>VSP_5100_5500*</li> <li>VSP_5100H_5500H*</li> <li>VSP_5200_5600</li> <li>VSP_5200H_5600H</li> <li>VSP_E590</li> <li>VSP_E790</li> <li>VSP_E990</li> <li>VSP_E1090</li> <li>VSP_E590H</li> <li>VSP_E790H</li> <li>VSP_E1090H</li> <li>VSP_ONE_B24</li> <li>VSP_ONE_B26</li> <li>VSP_ONE_B28</li> </ul>
physicalStorageSystems	Yes	List	List of the physical storage systems.
storageSystemId	Yes	String	ID of the physical storage system.
resourceGroupName	No	String	Name of the resource group.
numberOfVolumes	No	Integer	Number of volumes.
hostGroups	No	List	List of the host groups or iSCSI targets.
portId	No	String	ID of the storage port.
number	No	Integer	Number of host groups or iSCSI targets.
volumeIdRange	No	Object	An ID range of undefined volumes to be added to a virtual storage machine. To add all undefined volumes within the range, specify null for numberOfVolumes.
from	No	Integer	Starting volume ID of the range (in decimal).

Parameter	Required	Type	Description
to	No	Integer	Ending volume ID for the range (in decimal).
hostGroupIds	No	List	List of the host group IDs.
<p>* You can also specify the following values (for compatibility).</p> <ul style="list-style-type: none"> <li>VSP_5000_SERIES_AFA</li> <li>VSP_5000_SERIES_HYBRID</li> </ul> <p>If you obtain the virtual storage system model for a virtual storage machine that was created by specifying one of the above values, one of the following values will be returned.</p> <ul style="list-style-type: none"> <li>For VSP_5000_SERIES_AFA: VSP_5100_5500</li> <li>For VSP_5000_SERIES_HYBRID: VSP_5100H_5500H</li> </ul>			

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
```

```
[
],
"isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

For specifying the number of host groups:

```
{
  "storageSystemId": "11111",
  "model": "VSP_F1500_AND_VSP_G1000_G1500",
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroups": [
        {
          "portId": "CL1-A",
          "number": 100
        }
      ]
    }
  ]
}
```

For specifying host group IDs:

```
{
  "storageSystemId": "11111",
  "model": "VSP_F1500_AND_VSP_G1000_G1500",
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroupIds": ["CL1-A-1", "CL1-B-2", "CL2-A-3", "CL2-B-10"]
    }
  ]
}
```

**Adding resources to a virtual storage machine**

You can add resources to a virtual storage machine in Ops Center Administrator..

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/add-undefined-resources
```

**Request structure**

The request body structure is shown below:

```
{
  "physicalStorageSystems": [
    {
      "storageSystemId": "",
      "resourceGroupName": "",
      "numberOfVolumes": ,
      "volumeIdRange": {
        "from": ,
        "to":
      },
      "hostGroups": [
        {
          "portId": "",
          "number": ,
        },
        ...
      ],
      "hostGroupIds": ["" ]
    },
    ...
  ]
}
```

Parameter	Required	Type	Description
physicalStorageSystemId	Yes	String	ID of the physical storage system.
numberOfVolumes	No	Integer	Number of volumes. Either resource (volume or host group) must be specified.
resourceGroupName	No	String	Name of the resource group.

Parameter	Required	Type	Description
hostGroups	No	List	List of the host group or iSCSI target IDs. Either resource (volume or host group) must be specified.
portId	No	String	Port ID (becomes required if <code>hostGroups</code> is specified)
number	No	Integer	Number of host groups (becomes required if <code>hostGroups</code> is specified).
volumeIdRange	No	Object	An ID range of undefined volumes to be added to a virtual storage machine. To add all undefined volumes within the range, specify null for <code>numberOfVolumes</code> .
from	No	Integer	Starting volume ID of the range (in decimal).
to	No	Integer	Ending volume ID for the range (in decimal).
hostGroupIds	No	List	List of the host group IDs.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": ""
  }
}
```

```

    "parameters":
      {
      }
    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
    "tags":
    [
    ],
    "isSystem":
  }

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.



Parameter	Type	Description
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

For specifying the number of host groups:

```
{
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroups": [
        {
          "portId": "CL1-A",
          "number": 100
        }
      ]
    }
  ]
}
```

For specifying the IDs of host groups:

```
{
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroups": [
        {
          "portId": "CL1-A",
          "number": 100
        }
      ]
    }
  ]
}
```

```

        "hostGroupIds": ["CL1-A-1", "CL1-B-2", "CL2-A-3", "CL2-B-10"]
    }
}

```

## Getting a virtual storage machine summary

You can get a summary of information about a specific virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/summary
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  registeredVolumeTotalCount: ,
  registeredVolumeDefinedCount: ,
  registeredHostGroupTotalCount: ,
  registeredHostGroupDefinedCount: ,
  registeredVolumeTotalCapacity: ""
}

```

Parameter	Type	Description
registeredVolumeTotalCount	Long	The number of all volumes registered in the virtual storage machine.
registeredVolumeDefinedCount	Long	The number of defined volumes registered in the virtual storage machine.
registeredHostGroupTotalCount	Long	The number of all host groups registered in the virtual storage machine.
registeredHostGroupDefinedCount	Long	The number of defined host groups registered in a virtual storage machine.

Parameter	Type	Description
registeredVolumeTotalCapacity	String	The total capacity of volumes registered in the virtual storage machine, in bytes.

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

#### Response example

JSON response:

```
{
  registeredVolumeTotalCount: 1000,
  registeredVolumeDefinedCount: 500,
  registeredHostGroupTotalCount: 100,
  registeredHostGroupDefinedCount: 50,
  registeredVolumeTotalCapacity: "879052348832"
}
```

## Moving volumes to a virtual storage machine

You can move volumes to a virtual storage machine in Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/physical-storage-systems/physicalStorageSystemId/add-existing-volumes
```

**Request structure**

The request body structure is shown below:

```
{
  "resourceGroupName": "",
  "volumeIds": []
}
```

Parameter	Required	Type	Description
resourceGroupName	No	String	Name of the resource group.
volumeIds	Yes	List	List of volume IDs.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
```

```

    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "resourceGroupName": "rsg_name_1",
  "volumeIds": [1, 2, 3]
}
```

## Removing resources from a virtual storage machine

You can remove resources from a virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/remove-undefined-resources
```

### Request structure

The request body structure is shown below:

```
{
  "physicalStorageSystems": [
    {
      "storageSystemId": "",
      "resourceGroupName": "",
      "numberOfVolumes": ,
      "volumeIdRange": {
        "from": ,
        "to":
      },
      "hostGroups": [
        {
          "portId": "",
          "number": ,
        },
        ...
      ],
      "hostGroupIds": [""],
    },
    ...
  ]
}
```

Parameter	Required	Type	Description
physicalStorageSystemId	Yes	String	ID of the physical storage system.
resourceGroupName	No	String	Name of the resource group.



Parameter	Required	Type	Description
numberOfVolumes	No	Integer	Number of volumes. Either resource (volume or host group) must be specified.
hostGroups	No	List	List of the host group or iSCSI target IDs. Either resource (volume or host group) must be specified.
portId	No	String	Port ID (becomes required if <code>hostGroups</code> is specified).
number	No	Integer	Number of host groups (becomes required if <code>hostGroups</code> is specified).
volumeIdRange	No	Object	An ID range of undefined volumes to be removed from a virtual storage machine. To remove all undefined volumes within the range, specify null for <code>numberOfVolumes</code> .
from	No	Integer	Starting volume ID of the range (in decimal).
to	No	Integer	Ending volume ID for the range (in decimal).
hostGroupIds	No	List	List of the host group IDs.

## Response structure

The response body structure is shown below:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "",
      "href": ""
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	The ID of the job that is created to carry out the request.
title	Object	The title of the job in progress.
text	String	Text of the message.
messageCode	String	ID of the message. This maps to the message description.
parameters	Object	List of parameters and the values, as captured in the job message.

Parameter	Type	Description
user	String	Name of the user who started the job.
status	String	Job status. Valid values: <ul style="list-style-type: none"> <li>• In Progress</li> <li>• Failed</li> <li>• Success</li> <li>• Success With Errors</li> </ul>
startDate	Integer	The date and time this job started. Format is the Unix epoch.
endDate	Integer	Date and time when this job ended. If the job is still in progress, this parameter does not return a value. Format is the Unix epoch.
parentJobId	Integer	The ID of the job that spawned this job. If not applicable, the value null is returned.
reports	List	Messages associated with this job.
links	List	Displays related resources.
self	String	URI that includes the resource ID.
tags	List	List of user-defined identifiers. Each identifier (tag) must be a minimum of three characters in length.
isSystem	Boolean	Whether a job was created by a system or a user. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets to false.

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

For specifying the number of host groups:

```
{
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroups": [
        {
          "portId": "CL1-A",
```

```

        "number": 100
      }
    ]
  }
}

```

For specifying the host group IDs:

```

{
  "physicalStorageSystems": [
    {
      "storageSystemId": "22222",
      "resourceGroupName": "rsg_name_1",
      "numberOfVolumes": 100,
      "volumeIdRange": {
        "from": 1000,
        "to": 2000
      },
      "hostGroupIds": ["CL1-A-1", "CL1-B-2", "CL2-A-3", "CL2-B-10"]
    }
  ]
}

```

## Removing defined volumes from a virtual storage machine

You can remove defined volumes from a virtual storage machine in Ops Center Administrator.

### HTTP request syntax (URI)

```

POST https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId/physical-storage-systems/physicalStorageSystemId/remove-existing-volumes

```

### Request structure

The request body structure is shown below:

```

{
  "volumeIds": [ , ... ]
}

```

Parameter	Required	Type	Description
volumelds	Yes	List	List of volume IDs. Volume ID type is long.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.

Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

## Deleting a physical storage system from a virtual storage machine

You can delete a physical storage system from a virtual storage machine in Ops Center Administrator.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/virtual-storage-machines/virtualStorageSystemId/physical-storage-systems/physicalStorageSystemId
```



**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

## Deleting a virtual storage machine

You can delete a virtual storage machine in Ops Center Administrator.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/virtual-storage-machines/virtualStorageMachineId
```

**Request structure**

Not applicable

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Chapter 7: Data protection management resources

This module describes the data resource management operations.

All GET APIs can be accessed by all Ops Center Administrator roles.

APIs using POST, PATCH, or DELETE methods require the Storage Administrator role.

Request	Method	URI	Role
<a href="#">Getting a data protection summary for all storage systems (on page 676)</a>	GET	/v1/data-protection/ summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a data protection summary for a storage system (on page 677)</a>	GET	/v1/data-protection/ storage-systems/ <i>storageSystemId</i> / summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing replication groups (on page 679)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a replication group by ID (on page 687)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i>	Storage administrator System administrator

Request	Method	URI	Role
			Security administrator Monitoring
<a href="#">Getting a replication group summary (on page 692)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Creating a replication group (on page 694)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups	Storage administrator
<a href="#">Adding volumes to a replication group on a storage system (on page 700)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i> /add- volumes	Storage administrator
<a href="#">Removing volumes from a replication group on a storage system (on page 704)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i> / remove-volumes	Storage administrator
<a href="#">Restoring volumes on a storage system (on page 707)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / volumes/ <i>volumeId</i> /restore	Storage administrator
<a href="#">Updating clone replication groups on a storage system (on page 710)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i>	Storage administrator
<a href="#">Updating a snapshot replication group on a storage system (on page 714)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i>	Storage administrator
<a href="#">Updating high availability replication groups on a storage system (on page 718)</a>	PATCH	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i>	Storage administrator



Request	Method	URI	Role
<a href="#">Suspending data replication (on page 721)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i> / suspend	Storage administrator
<a href="#">Resuming replication (on page 724)</a>	POST	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i> / resume	Storage administrator
<a href="#">Deleting a replication group (on page 727)</a>	DELETE	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i>	Storage administrator
<a href="#">Listing volume pairs (on page 730)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /volume-pairs	Storage administrator System administrator Security administrator Monitoring
<a href="#">Viewing volume pairs affected by actions performed on a replication group (on page 736)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> / replication-groups/ <i>replicationGroupId</i> / affected-volume-pairs	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing primary volume pairs (on page 741)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /volume-pairs? q=primaryVolume.id: <i>primaryVolumeId</i>	Storage administrator System administrator Security administrator Monitoring

Request	Method	URI	Role
<a href="#">Listing secondary volume pairs (on page 745)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /volume-pairs? q=secondaryVolume.id:se <i>condaryVolumId</i>	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing secondary volumes for a primary volume (on page 750)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> / volumes/ <i>volumId</i> / secondaryVolumes	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing failed volume pairs (on page 761)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /volume-pairs?q=state:ERROR	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting Ops Center Protector information (on page 765)</a>	GET	/v1/dp-manager	Storage administrator System administrator Security administrator Monitoring
<a href="#">Registering/Deleting the Hitachi Ops Center Protector (on page 767)</a>	PATCH	/v1/dp-manager	System administrator
<a href="#">Testing the connection to Ops Center Protector (on page 772)</a>	POST	/v1/dp-manager/test-connection	Storage administrator System administrator Security administrator

Request	Method	URI	Role
<a href="#">Importing high availability pairs from Ops Center Protector (on page 775)</a>	POST	/v1/dp-manager/import	Storage administrator System administrator
<a href="#">Listing quorum disks (on page 778)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /quorum-disks	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing remote paths (on page 781)</a>	GET	/v1/storage-systems/ <i>storageSystemId</i> /remote-paths	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a high availability setup status summary (on page 783)</a>	GET	/v1/ha-setup-status?primaryStorageSystemId={ssid}&secondaryStorageSystemId={ssid}	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing high availability status external volumes (on page 788)</a>	GET	/v1/ha-setup-status/external-volumes?primaryStorageSystemId={ssid}&secondaryStorageSystemId={ssid}	Storage administrator System administrator Security administrator Monitoring

## Getting a data protection summary for all storage systems

You can display a list of protected and unprotected volumes and capacity in all storage systems.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/data-protection/summary
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "protectedCapacity": ,
  "protectedVolumes": ,
  "unprotectedCapacity": ,
  "unprotectedVolumes": ,
  "secondaryCapacity": ,
  "secondaryVolumes": ,
  "failedVolumes":
}
```

Parameter	Type	Description
protectedCapacity	Long	Total capacity of all protected volumes, in bytes.
protectedVolumes	Integer	The number of protected volumes.
unprotectedCapacity	Long	Total capacity of all unprotected volumes, in bytes.
unprotectedVolumes	Integer	The number of unprotected volumes.
secondaryCapacity	Long	Total capacity of all secondary volumes, in bytes.
secondaryVolumes	Integer	The number of secondary volumes.
failedVolumes	Long	The number of volume has replication failures.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified storage system ID is not valid or the storage system does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
GET https://172.17.64.112/v1/data-protection/summary
```

**Example response**

```
{
  "protectedCapacity": 5064195939328,
  "protectedVolumes": 7,
  "unprotectedCapacity": 523975209956352,
  "unprotectedVolumes": 1126,
  "secondaryCapacity": 70849351026688,
  "secondaryVolumes": 52,
  "failedVolumes": 2
}
```

## Getting a data protection summary for a storage system

You can display a list of protected and unprotected capacity and volumes in a storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/data-protection/storage-systems/storageSystemId/summary
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "protectedCapacity": ,
  "protectedVolumes": ,
  "unprotectedCapacity": ,
  "unprotectedVolumes": ,
  "secondaryCapacity": ,
  "secondaryVolumes": ,
  "failedVolumes":
}
```

Parameter	Type	Description
protectedCapacity	Long	Total capacity of all protected volumes, in bytes.
protectedVolumes	Integer	The number of protected volumes.
unprotectedCapacity	Long	Total capacity of all unprotected volumes, in bytes.
unprotectedVolumes	Integer	The number of unprotected volumes.
secondaryCapacity	Long	Total capacity of all secondary volumes, in bytes.
secondaryVolumes	Integer	The number of secondary volumes.
failedVolumes	Long	The number of volume has replication failures.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
GET https://172.17.64.112/v1/data-protection/storage-systems/410031/summary
```

**Example response**

```
{
  "protectedCapacity": 5059900972032,
  "protectedVolumes": 3,
  "unprotectedCapacity": 39678455755776,
  "unprotectedVolumes": 914,
  "secondaryCapacity": 70832171157504,
  "secondaryVolumes": 36,
  "failedVolumes": 1
}
```

## Listing replication groups

You can display a list of all replication groups in a storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/replication-groups
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "resources": [{
    "id": ,
    "storageSystemId": "",
    "name": "",
    "comments": "",
    "type": "",
    "consistent": ,
    "numberOfCopies": ,
    "schedule": {
      "recurringUnit": "",
      "minute": ,
      "hour": ,
      "recurringUnitInterval": ,
      "dayOfWeek": ,
      "dayOfMonth":
    },
    "scheduleEnabled": ,
    "primaryVolumeIds": [
    ],
    "failures": ,
    "replicationStatuses": [""],
    "targetPoolId": ,
    "secondaryStorageSystemId": "",
    "quorumId": ,
    "secondaryPoolId": ,
    "dataFlowName": ,
    "importedFromDpManager": ,
    "legacyMode": ,
    "primaryJournal": {
      "name": "",
      "id": ,
    },
    "secondaryJournal": {
      "name": "",
      "id": ,
    },
  ]},
  "total": ,
  "nextToken": ,
}
```



Parameter	Type	Description
id	String	ID of the replication group.
storageSystemId	String	ID of the storage system to which the replication group belongs.
name	String	Name of the replication group.
comments	String	Comment for the replication group. Min = 1, max = 255 characters.
type	String	Replication type. Valid values: <ul style="list-style-type: none"> <li>CLONE</li> <li>SNAP: Snapshot</li> <li>SNAP_ON_SNAP</li> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone (universal replicator)</li> </ul>
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
numberOfCopies	Integer	Number of replication group copies. Min = 1, max = 1024. This parameter is only available when the <code>type</code> is SNAP.
schedule	Object	Interval at which the snapshots are taken, such as: <ul style="list-style-type: none"> <li>hour; Integer, valid values: 0-23</li> <li>minute; Integer, valid values: 0-59</li> <li>recurringUnit; String, ('HOURLY', 'DAILY', 'WEEKLY', 'MONTHLY')</li> <li>recurringUnitInterval; Integer, (null, or any positive integer)</li> <li>dayOfWeek; List of Strings, (null, or 'SUN', 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT')</li> <li>dayOfMonth; Integer, (null, or 1-31)</li> </ul>

Parameter	Type	Description
		<p>Notes:</p> <ul style="list-style-type: none"> <li>▪ This parameter is only available when the <code>type</code> is SNAP.</li> <li>▪ Only hour and minute are required if Daily is chosen</li> <li>▪ <code>recurringUnitInterval</code> is only applicable if Hourly is chosen</li> <li>▪ <code>dayOfWeek</code> is only applicable if Weekly is chosen</li> <li>▪ <code>dayOfMonth</code> is only applicable if Monthly is chosen</li> </ul>
<code>scheduleEnabled</code>	Boolean	Whether the schedule is enabled. This parameter is only available when the <code>type</code> is SNAP.
<code>primaryVolumelds</code>	List	List of the primary volume IDs.
<code>failures</code>	Integer	Count of data protection failed volumes.
<code>targetPoolId</code>	Integer	If the user sets a target pool for the snapshot, an integer value is returned as the target pool ID. If the user does not set a target pool, returns NULL. In this case, Ops Center Administrator automatically selects the pool when taking a snapshot.
<code>secondaryStorageSystemId</code>	String	The ID of the secondary storage system.
<code>secondaryPoolId</code>	String	The ID of the pool of the secondary volume.
<code>quorumId</code>	Integer	The ID of the quorum disk.
<code>dataFlowName</code>	String	Name of the data flow related to the replication group.
<code>importedFromDpManager</code>	Boolean	Whether the replication group is imported from Ops Center Protector.
<code>replicationStatuses</code>	String[]	This parameter is only used by the Ops Center Administrator GUI.
<code>legacyMode</code>	Boolean	Displays whether the replication group is created with Ops Center Administrator v11.0.2 or earlier for HA replicationType. Return NULL for replication group other than HA replicationType.

Parameter	Type	Description
primaryJournal	Object	Primary journal information.
name	String	Journal name.
id	Integer	Journal id.
secondaryJournal	Object	Secondary journal information.
name	String	Journal name.
id	Integer	Journal id.
total	Long	Total replication groups in a given storage system.
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/storage-systems/ serial/disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMTM6Q08yc2ZlRlhTT UNoSXVYNlFPUS1jZzswOw==</pre>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://172.17.64.116/v1/storage-systems/410209/replication-groups
```

### Example response

```
{
  "resources": [{
    "id": 1,
    "storageSystemId": "410209",
    "name": "testRg",
    "comments": "test comments",
    "type": "SNAP",
    "consistent": false,
    "numberOfCopies": 1,
    "schedule": {
      "recurringUnit": "HOURLY",
      "minute": 43,
      "hour": null,
      "recurringUnitInterval": 1,
      "dayOfWeek": null,
      "dayOfMonth": null
    },
    "scheduleEnabled": true,
    "primaryVolumeIds": [
      309
    ],
    "failures": 0,
    "replicationStatuses": [
      "PSUS",
      "SSUS"
    ],
    "targetPoolId": 1,
    "secondaryStorageSystemId": "",
    "quorumId": ,
    "secondaryPoolId": ,
    "dataFlowName": ,
    "legacyMode": null,
    "primaryJournal": null,
    "secondaryJournal": null
  },
  {
    "id": 2,
```

```

    "storageSystemId": "410209",
    "name": "testRg2",
    "comments": "test comments2",
    "type": "CLONE",
    "consistent": false,
    "numberOfCopies": null,
    "schedule": null,
    "scheduleEnabled": null,
    "primaryVolumeIds": [
        369
    ],
    "failures": 0,
    "replicationStatuses": [
        "PAIR"
    ],
    "targetPoolId": ,
    "secondaryStorageSystemId": "",
    "quorumId": ,
    "secondaryPoolId": ,
    "dataFlowName": ,
    "importedFromDpManager": false,
    "legacyMode": null,
    "primaryJournal": null,
    "secondaryJournal": null
},
{
    "id": 3,
    "storageSystemId": "410209",
    "name": "ARC-sample-rg",
    "comments": null,
    "type": "ASYNC_REMOTE_CLONE",
    "consistent": true,
    "numberOfCopies": null,
    "schedule": null,
    "scheduleEnabled": null,
    "primaryVolumeIds": [
        1152
    ],
    "failures": 0,
    "replicationStatuses": [
        "PAIR"
    ],
    "targetPoolId": null,
    "secondaryStorageSystemId": "417707",
    "secondaryPoolId": 11,
    "quorumId": null,
    "dataFlowName": "ARC-sample-rg",
    "importedFromDpManager": false,
    "legacyMode": false,
    "primaryJournal": {
        "name": "ID:4",

```

```

    "id": 4
  },
  "secondaryJournal": {
    "name": "ID:22",
    "id": 22
  }
}],
"total": 3,
"nextToken": null
}

```

### Example request

```
GET https://10.196.165.88/v1/storage-systems/410438/replication-groups?q=type:HA
```

### Example response

```

{
  "resources": [
    {
      "storageSystemId": "410438",
      "name": "hsa-test-en-cap-newcon1",
      "comments": null,
      "type": "HA",
      "consistent": true,
      "numberOfCopies": null,
      "schedule": null,
      "scheduleEnabled": null,
      "primaryVolumeIds": [
      ],
      "failures": 0,
      "replicationStatuses": [
        "PAIR"
      ],
      "targetPoolId": null,
      "secondaryStorageSystemId": "410111",
      "secondaryPoolId": 41,
      "quorumId": 13,
      "dataFlowName": "hsa-test-en-cap-newcon1",
      "id": 1,
      "legacyMode": true,
      "primaryJournal": null,
      "secondaryJournal": null
    },
    {
      "storageSystemId": "410438",
      "name": "test-to-ha-rg-multi",
      "comments": null,
      "type": "HA",
      "consistent": true,

```

```

    "numberOfCopies": null,
    "schedule": null,
    "scheduleEnabled": null,
    "primaryVolumeIds": [
    ],
    "failures": 0,
    "replicationStatuses": [
        "PAIR"
    ],
    "targetPoolId": null,
    "secondaryStorageSystemId": "410111",
    "secondaryPoolId": 4,
    "quorumId": 13,
    "dataFlowName": "test-to-ha-rg-multi",
    "id": 2,
    "legacyMode": true,
    "primaryJournal": null,
    "secondaryJournal": null
    }
  ],
  "total": 2,
  "nextToken": null
}

```

## Getting a replication group by ID

You can display details of a replication group in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/replicationGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "id": ,
  "storageSystemId": "",
  "name": "",
  "comments": "",

```

```

"type": "",
"consistent": ,
"numberOfCopies": ,
"schedule": {
  "recurringUnit": "",
  "minute": ,
  "hour": ,
  "recurringUnitInterval": ,
  "dayOfWeek": ,
  "dayOfMonth":
},
"scheduleEnabled": ,
"primaryVolumeIds": [
],
"failures": ,
"targetPoolId": ,
"secondaryStorageSystemId": "",
"quorumId": ,
"secondaryPoolId": ,
"dataFlowName": ,
"importedFromDpManager": ,
"replicationStatuses": [""],
"legacyMode": ,
"primaryJournal": {
  "name": "",
  "id": ,
},
"secondaryJournal": {
  "name": "",
  "id": ,
}
}

```

Parameter	Type	Description
id	String	ID of the replication group.
storageSystemId	String	ID of the storage system.
name	String	Name of the resource.
comments	String	Comment for the replication group. Min = 1, max = 255 characters.
type	String	Replication type. Valid values: <ul style="list-style-type: none"> <li>CLONE</li> <li>SNAP: Snapshot</li> <li>SNAP_ON_SNAP</li> </ul>



Parameter	Type	Description
		<ul style="list-style-type: none"> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone (universal replicator)</li> </ul>
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
numberOfCopies	Integer	Number of replication group copies. Min =1, max = 1024. This parameter is only available when the <code>type</code> is SNAP.
schedule	Object	<p>Interval at which the snapshots are taken, such as:</p> <ul style="list-style-type: none"> <li>hour; Integer, valid values: 0-23</li> <li>minute; Integer, valid values: 0-59</li> <li>recurringUnit; String, ('HOURLY', 'DAILY', 'WEEKLY', 'MONTHLY')</li> <li>recurringUnitInterval; Integer, (null, or any positive integer)</li> <li>dayOfWeek; List of Strings, (null, or 'SUN', 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT')</li> <li>dayOfMonth; Integer, (null, or 1-31)</li> </ul> <p>Notes:</p> <ul style="list-style-type: none"> <li>This parameter is only available when the <code>type</code> is SNAP.</li> <li>Only hour and minute are required if Daily is chosen</li> <li>recurringUnitInterval is only applicable if Hourly is chosen</li> <li>dayOfWeek is only applicable if Weekly is chosen</li> <li>dayOfMonth is only applicable if Monthly is chosen</li> </ul>
scheduleEnabled	Boolean	Whether the schedule is enabled. This parameter is only available when the <code>type</code> is SNAP.
primaryVolumeIds	List	List of the primary volume IDs.

Parameter	Type	Description
failures	Integer	Count of data protection failed volumes.
targetPoolId	Integer	If the user sets a target pool for the snapshot, an integer value is returned as the target pool ID. If the user does not set a target pool, returns NULL. In this case, Ops Center Administrator automatically selects the pool when taking a snapshot.
secondaryStorageSystemId	String	The ID of the secondary storage system.
secondaryPoolId	String	The ID of the pool of the secondary volume.
quorumId	Integer	The ID of the quorum disk.
dataFlowName	String	Name of the data flow related to the replication group.
importedFromDpManager	Boolean	Whether the replication group is imported from Ops Center Protector.
replicationStatuses	String[]	This parameter is only used by the Ops Center Administrator GUI.
legacyMode	Boolean	Displays whether the replication group is created with Ops Center Administrator v11.0.2 or earlier for HA replicationType. Return NULL for replication group other than HA replicationType.
primaryJournal	Object	Primary journal information.
name	String	Journal name.
id	Integer	Journal id.
secondaryJournal	Object	Secondary journal information.
name	String	Journal name.
id	Integer	Journal id.

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://172.17.64.112/v1/storage-systems/410031/replication-groups/1
```

### Example response

```
{
  "id": 1,
  "storageSystemId": "410031",
  "name": "testRg",
  "comments": "test comments",
  "type": "SNAP",
  "consistent": false,
  "numberOfCopies": 1,
  "schedule": {
    "recurringUnit": "HOURLY",
    "minute": 43,
    "hour": null,
    "recurringUnitInterval": 1,
    "dayOfWeek": null,
    "dayOfMonth": null
  },
  "scheduleEnabled": true,
  "primaryVolumeIds": [309],
  "failures": 0,
  "targetPoolId": 1,
  "secondaryStorageSystemId": null,
  "quorumId": null,
  "secondaryPoolId": null,
  "dataFlowName": null,
  "importedFromDpManager": false,
  "replicationStatuses": ["SSUS"],
  "legacyMode": null,
}
```

```

    "primaryJournal": null,
    "secondaryJournal": null
  }

```

### Example Request

```
GET https://172.17.64.112/v1/storage-systems/410209/replication-groups/3
```

### Example response

```

{
  "id": 3,
  "storageSystemId": "410209",
  "name": "ARC-sample-rg",
  "comments": null,
  "type": "ASYNC_REMOTE_CLONE",
  "consistent": true,
  "numberOfCopies": null,
  "schedule": null,
  "scheduleEnabled": null,
  "primaryVolumeIds": [1152],
  "failures": 0,
  "replicationStatuses": ["PAIR"],
  "targetPoolId": null,
  "secondaryStorageSystemId": "417707",
  "secondaryPoolId": 11,
  "quorumId": null,
  "dataFlowName": "ARC-sample-rg",
  "importedFromDpManager": false,
  "replicationStatuses": ["PAIR"],
  "legacyMode": false,
  "primaryJournal": {
    "name": "ID:4",
    "id": 4
  },
  "secondaryJournal": {
    "name": "ID:22",
    "id": 22
  }
}

```

## Getting a replication group summary

You can display the replication group summary by replication types.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/summary
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "replicationGroupCountByType":
  [
    {
      "replicationType": "",
      "count":
    },
    {
      "replicationType": "",
      "count":
    }
  ]
}
```

Parameter	Type	Description
replicationGroupCountByType	Set	The total number of replication group by type.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>CLONE</li> <li>SNAP: Snapshot</li> <li>SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone (universal replicator)</li> </ul>
count	Integer	Number of replication groups of the given type.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
GET https://172.17.64.112/v1/storage-systems/410031/replication-groups/summary
```

**Example response**

```
{
  "replicationGroupCountByType":
  [
    {
      "replicationType": "CLONE",
      "count": 1
    },
    {
      "replicationType": "HA",
      "count": 0
    }
  ]
}
```

## Creating a replication group

You can create a replication group in a storage system.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/replication-groups
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

The request body structure is shown here.

```
{
  "name": "",
  "comments": "",
  "type": "",
  "consistent": ,
  "numberOfCopies": ,
  "schedule": {
    "recurringUnit": "",
    "minute": ,
    "hour": ,
    "recurringUnitInterval": ,
    "dayOfWeek": ,
    "dayOfMonth": ,
  },
  "primaryVolumeIds": ,
  "targetPoolId": ,
  "secondaryStorageSystemId": "",
  "secondaryVolumeLabel": "",
  "drsSetting": "",
  "capacitySavingSetting": "",
  "journal": {
    "primaryJournalPoolId": ,
    "secondaryJournalPoolId": ,
    "size": ,
    "unit": "",
    "journalLabel": "",
    "primaryJournalId": ,
    "secondaryJournalId": ,
  }
}
```

Parameter	Required	Type	Description
name	Yes	String	The name of the replication group.
comments	No	String	Comments about the resource. Min = 1, max = 255.

Parameter	Required	Type	Description
type	Yes	String	Type of replication technology to use, such as SNAP, SNAP_ON_SNAP, CLONE, HA or ASYNC_REMOTE_CLONE.
consistent	No	Boolean	Whether copying takes place on all pairs in the group simultaneously.
numberOfCopies	Yes	Integer	Number of replication group copies. Min=1, max=1024. This parameter is only available when <code>type</code> is SNAP.
schedule	Yes	Object	<p>Required if type is SNAP or SNAP_ON_SNAP. Interval at which the snapshots are taken, such as:</p> <ul style="list-style-type: none"> <li>hour; Integer, valid values: 0-23</li> <li>minute; Integer, valid values: 0-59</li> <li>recurringUnit; String, ('HOURLY', 'DAILY', 'WEEKLY', 'MONTHLY')</li> <li>recurringUnitInterval; Integer, (null, or any positive integer)</li> <li>dayOfWeek; String[ ], (null, or 'SUN', 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT')</li> <li>dayOfMonth; Integer, (null, or 1-31)</li> </ul> <p>Note:</p> <ul style="list-style-type: none"> <li>Minute is required if HOURLY is chosen.</li> <li>Hour and minute are required if DAILY is chosen</li> <li>recurringUnitInterval is only applicable if HOURLY is chosen</li> <li>dayOfWeek is only applicable if WEEKLY is chosen</li> <li>dayOfMonth is only applicable if MONTHLY is chosen</li> </ul>
primaryVolumelds	Yes	List	List of the primary volume IDs.



Parameter	Required	Type	Description
targetPoolId	No	Integer	If the user specifies <code>poolId</code> , the snapshot is taken from the specified pool. Do not specify this parameter when you select a DRS-VOL as the primary volume. Ops Center Administrator automatically selects the same pool to which the P-VOL belongs.
secondaryStorageSystemId	No	String	Specifies the ID of the secondary storage system.
secondaryVolumeLabel	No	String	Label of secondary volume of asynchronous remote clone pair.
drsSetting	No	String	Whether or not DRS setting of the secondary volume of asynchronous remote clone pair is enabled. Valid values are ENABLED and DISABLED.
capacitySavingSetting	No	String	Type of controller-based capacity saving. Valid values are NONE, COMPRESSION and DEDUPLICATION_AND_COMPRESSION.
journal	No	Object	Journal information.
primaryJournalPoolId	No	Integer	ID of primary storage system's pool where the new journal will be created.
secondaryJournalPoolId	No	Integer	ID of secondary storage system's pool where the new journal will be created.
size	No	Long	Numerical part of journal's capacity.
unit	No	String	Unit part of journal's capacity. Valid values are MiB, GiB, and TiB.
journalLabel	No	String	Label of the new Journal.
primaryJournalId	No	Integer	ID of Journal in primary storage to be used.
secondaryJournalId	No	Integer	ID of Journal in secondary storage to be used.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets it to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
POST https://172.17.64.112/v1/storage-systems/410031/replication-groups
```

```
{
  "name": "testRg",
  "comments": "test comments",
  "consistent": false,
  "type": "SNAP",
  "primaryVolumeIds": [6],
  "numberOfCopies": 1,
  "schedule": {
    "recurringUnit": "Hourly",
    "minute": 10,
    "hour": null,
    "recurringUnitInterval": null,
    "dayOfWeek": null,
    "dayOfMonth": null
  },
  "targetPoolId": 1
}
```

## Adding volumes to a replication group on a storage system

You can add primary or secondary volumes to a replication group on a storage system. Note that this API cannot be used for a replication group with GAD attribute.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/
replicationGroupId/add-volumes
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

**Request structure**

```
{
  "primaryVolumeIds": []
}
```

Parameter	Required	Type	Description
primaryVolumeIds	Yes	List	List of the primary volume IDs.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
```

```

    }
  ],
  "tags":
  [
  ],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
POST https://172.17.64.113/v1/storage-systems/410031/replication-groups/1/add-volumes
```

```
{
  "primaryVolumeIds": [1]
}
```

## Removing volumes from a replication group on a storage system

You can remove primary or secondary volumes from a replication group on a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/
replicationGroupId/remove-volumes
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

### Request structure

```
{
  "primaryVolumeIds": [],
  "deleteSecondaryVolume":
  "removeConnection":
}
```

Parameter	Required	Type	Description
primaryVolumeIds	Yes	List	List of the primary volume IDs.
deleteSecondaryVolume	Yes	Boolean	Whether to delete the secondary volume.
removeConnection	No	Boolean	Specify whether to remove zone settings for the Fibre Channel between removed secondary volumes and servers, if applicable. False if you specified null. The value must be null if the replication type is not HA.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
  }
```



```

    {
    },
    "user": "",
    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
        {
            "rel": "_self",
            "href": "/v1/jobs/jobId"
        }
    ],
    "tags":
    [
    ],
    "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.

Parameter	Type	Description
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
POST https://172.17.64.113/v1/storage-systems/410031/replication-groups/1/remove-volumes
```

### Example Request

```
{
  "primaryVolumeIds": [14,3,101],
  "deleteSecondaryVolume": true
}
```

## Restoring volumes on a storage system

You can restore volumes on a storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId/restore
```

Use the storage system ID as the *storageSystemId*.

Use the primary or secondary volume ID as the *volumeId*.

### Request structure

```
{
  "secondaryVolumeId": ,
  "applyToAllGroupPairs":
}
```

Parameter	Required	Type	Description
secondaryVolumeId	Yes	Integer	ID of the secondary volume.

Parameter	Required	Type	Description
applyToAllGroupPairs	No	Boolean	Restore all pairs within a snapshot group that has the consistency parameter enabled. The default value is false.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
    }
  },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.

Parameter	Type	Description
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
POST https://172.17.64.113/v1/storage-systems/410031/volumes/3/restore
```

**Example Request**

```
{
  "secondaryVolumeId": 46,
  "applyToAllGroupPairs": false
}
```

## Updating clone replication groups on a storage system

You can update a clone replication group on a storage system. You can change the name or update comments.

**HTTP request syntax (URI)**

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/
replicationGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

**Request structure**

```
{
  "name": "",
  "comments": ""
}
```

Parameter	Required	Type	Description
name	No	String	The name of the resource. Min = 1, max = 26.
comments	No	String	Comments about the resource. Min = 1, max = 255.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
}
```

```

"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.



Parameter	Type	Description
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
PATCH https://172.17.64.113/v1/storage-systems/410031/replication-groups/1
```

### Example Request

```
{
  "name": "Clone group name",
  "comments": "This is a clone group for server-1"
}
```

## Updating a snapshot replication group on a storage system

Use this API to manage replication policy on a storage system. You can change, suspend, or resume the schedule, change the name, the numberOfCopies, or update comments. The policy type and consistency attributes cannot be changed after a policy is created. Using this API, you cannot change the volume set to which the policy is applied. Use the protect/unprotect APIs to update the volume set.

### HTTP request syntax (URI)

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/replicationGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

### Request structure

The request body structure is shown below:

```
{
  "comments": "",
  "name": "",
  "numberOfCopies": ,
  "schedule":
  {
    "hour": ,
    "minute": ,
    "recurringUnit": "",
    "recurringUnitInterval": ,
    "dayOfWeek": [""],
    "dayOfMonth":
  },
  "scheduleEnabled": "",
  "targetPoolId":
}
```

Parameter	Required	Type	Description
comments	No	String	Comments about the resource. Min = 1, max = 255.
name	No	String	The name of the resource. Min = 1, max = 26.
numberOfCopies	No	Integer	Number of replication group copies. Min = 1, max = 1024.

Parameter	Required	Type	Description
schedule	Yes	Object	<p>Required if type is SNAP or SNAP_ON_SNAP. Interval at which the snapshots are taken, such as:</p> <ul style="list-style-type: none"> <li>hour; Integer, valid values: 0-23</li> <li>minute; Integer, valid values: 0-59</li> <li>recurringUnit; String, ('HOURLY', 'DAILY', 'WEEKLY', 'MONTHLY')</li> <li>recurringUnitInterval; Integer, (null, or any positive integer)</li> <li>dayOfWeek; String[], (null, or 'SUN', 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT')</li> <li>dayOfMonth; Integer, (null, or 1-31)</li> </ul> <p>Note:</p> <ul style="list-style-type: none"> <li>Minute is required if HOURLY is chosen.</li> <li>Hour and minute are required if DAILY is chosen</li> <li>recurringUnitInterval is only applicable if HOURLY is chosen</li> <li>dayOfWeek is only applicable if WEEKLY is chosen</li> <li>dayOfMonth is only applicable if MONTHLY is chosen</li> </ul>
scheduleEnabled	No	Boolean	Whether the schedule is enabled.
targetPoolId	No	Integer	<p>If the user specifies <code>poolId</code>, the snapshot is taken from the specified pool. If the user does not specify <code>poolId</code>, Ops Center Administrator automatically selects the target pool when taking a snapshot. To keep the target pool, specify the current <code>poolId</code>. Do not specify this parameter when a DRS-VOL exists in specified replication group.</p>

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
```

```

{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  },
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
  {
    "rel": "_self",
    "href": "/v1/jobs/jobId"
  }
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
PATCH https://172.17.64.113/v1/storage-systems/410031/replication-groups/1
```

**Example Request**

```
{
  "comments": "This is a snapshot group for server 2",
  "name": "unique new name"
  "number of copies": 2
  "schedule":
  {
    "hour": ,
    "minute": 0 ,
    "recurringUnit": "HOURLY",
    "recurringUnitInterval": 2,
    "dayOfWeek": ,
    "dayOfMonth":
  },
  "scheduleEnabled":"true",
  "targetPoolId":1
}
```

## Updating high availability replication groups on a storage system

You can update high availability replication groups on a storage system in Ops Center Administrator.

**HTTP request syntax (URI)**

```
PATCH https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/replicationGroupId
```

**Request structure**

```
{
  "name": "",
  "comments": ""
}
```

Parameter	Required	Type	Description
name	No	String	The name of the resource. Min = 1, max = 26.
comments	No	String	Comments about the resource. Min = 1, max = 255.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title": {
    "text": "",
    "messageCode": "",
    "parameters": {
      }
    },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags": [

```

```

],
  "isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .



**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
PATCH https://172.17.64.113/v1/storage-systems/410031/replication-groups/1
```

**Example Request**

```
{
  "name": "HA group name",
  "comments": "This is an HA group for server-1"
}
```

## Suspending data replication

This API suspends data replication for all volumes in the given replication group in a storage system. This functionality only supported for a CLONE replication group. An attempt to suspend a SNAPSHOT replication group will result in an exception.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/
replicationGroupId/suspend
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

### Request structure

Not applicable

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.

Parameter	Type	Description
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
POST https://172.17.64.112/v1/storage-systems/410031/replication-groups/1/suspend
```

## Resuming replication

This API resumes data replication for all volumes in the given replication group in a storage system. This functionality only supported for a clone replication group. An attempt to suspend a snapshot replication group will result in an exception.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/replicationGroupId/resume
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *replicationGroupId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate": ,
  "scheduledDate": ,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
POST https://172.17.64.112/v1/storage-systems/410031/replication-groups/1/resume
```

## Deleting a replication group

You can delete a replication group in a storage system.

### HTTP request syntax (URI)

```
DELETE https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/replicationGroupId
```

Use the storage system ID as the *storageSystemId*.

Use the replication group ID as the *replicationGroupId*.

## Request structure

The request body structure is shown below:

```
{
  "removeConnection":
}
```

Parameter	Required	Type	Description
removeConnection	No	Boolean	Specify whether to remove zone settings for the Fibre Channel between removed secondary volumes and servers, if applicable. False if you specified null. The value must be null if the replication type is not HA.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
}
```



```

"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
DELETE https://172.17.64.112/v1/storage-systems/410031/replication-groups/1
```

## Listing volume pairs

You can display a list of all volume pairs in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volume-pairs
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources":
  [
    {
      "replicationGroup": ,
      "volumePairGroup": "",
      "primaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "secondaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "mirrorId": ,
      "splitTime": ,
      "consistent": ,
      "consistencyId": ,
      "type": "",
      "state": "",
      "quorumId": ,
      "primaryJournalId": ,
      "secondaryJournalId":
    }
  ],
  "total":,
  "nextToken": ""
}
```

Parameter	Type	Description
resources	Object	Resource information.
total	Long	Total number of resources

Parameter	Type	Description
nextToken	String	<p>The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token. Example:</p> <pre>https://sa_server/v1/ storage-systems/serial/ disks?nextToken= cXVlcnlBbmRGZXRjaDsxOzEyMT M6Q08yc2ZIRlhTTUNoSXVYNlFP US1jZzswOw==</pre>
replicationGroup	String	The name of the replication group.
volumePairGroup	String	The name of the copy group, for clones, or a snapshot group for snapshots.
primaryVolume	Object	Primary volume information.
secondaryVolume	Object	Secondary volume information.
id	Integer	ID of the volume.
storageSystemId	String	ID of the storage system.
status	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ SMPP: a volume pair with the clone attribute is being deleted.</li> <li>▪ PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
mirrorId	Integer	When multiple S-VOLs are created for one P-VOL, a mirror ID is assigned to each volume pair.
splitTime	Long	The time pair split is performed in Epoch time format.
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.

Parameter	Type	Description
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If not consistent, the value null is returned.
type	String	The replication type for the volume pair. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: high availability (global-active device)</li> <li>▪ ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
state	String	The volume pair state. Valid values: HEALTHY or ERROR.
quorumId	Integer	Quorum ID of the pair.
primaryJournalId	Integer	The ID of the primary journal. Set only if it is in replication group, otherwise null.
secondaryJournalId	Integer	The ID of the secondary journal. Set only if it is in replication group, otherwise null.

Status code	HTTP name	Description
200	OK	Success.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://10.76.48.147/v1/storage-systems/410500/volume-pairs?
q=primaryVolume.id:385+AND+type:HA
```

### Example response

```
{
  "resources": [
    {
      "replicationGroup": "test2",
      "volumePairGroup": null,
      "primaryVolume": {
        "id": 385,
        "storageSystemId": "410500",
        "status": "PAIR"
      },
      "secondaryVolume": {
        "id": 694,
        "storageSystemId": "410209",
        "status": "PAIR"
      },
      "mirrorId": 0,
      "splitTime": null,
      "consistent": true,
      "consistencyId": 2,
      "type": "HA",
      "state": "HEALTHY",
    }
  ]
}
```

```

        "quorumId": 4,
        "primaryJournalId": null,
        "secondaryJournalId": null
      }
    ],
    "total": 1,
    "nextToken": null
  }

```

## Viewing volume pairs affected by actions performed on a replication group

You can display a list of volume pairs affected by actions performed on a replication group in a storage system. Volumes in a replication group include all volumes explicitly added to a replication group using APIs or the web-based user interface. The affected volume pairs include volumes added outside of Ops Center Administrator to Ops Center Administrator-managed copy groups, snapshot groups, and consistency groups.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/replication-groups/
replicationGroupId/affected-volume-pairs
```

Use the storage system ID as the *storageSystemId*.

Use the replication group ID as the *replicationGroupId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "volumePairs":
  [
    {
      "replicationGroup": "",
      "volumePairGroup": "",
      "primaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "secondaryVolume":
      {

```



```

        "id": ,
        "storageSystemId": "",
        "status": ""
    },
    "mirrorId": ,
    "splitTime": ,
    "consistent": ,
    "consistencyId": ,
    "type": "",
    "state": "",
    "quorumId": ,
    "primaryJournalId": ,
    "secondaryJournalId":
    }
]
}

```

Parameter	Type	Description
replicationGroup	String	The name of the replication group.
volumePairGroup	String	The name of the copy group, for clones, or a snapshot group for snapshots.
id	Integer	ID of the volume.
storageSystemId	String	ID of the storage system.
status	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>SMPP: a volume pair with the clone attribute is being deleted.</li> <li>PSUP: a volume pair with the clone attribute is in suspended status.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
mirrorId	Integer	When multiple S-VOLs are created for one P-VOL, a mirror ID is assigned to each volume pair.
splitTime	Long	The time pair split is performed in Epoch time format.
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If not consistent, the value null is returned.

Parameter	Type	Description
type	String	The replication type for the volume pair. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: high availability (global-active device)</li> <li>▪ ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
state	String	The volume pair state. Valid values: HEALTHY or ERROR.
quorumId	Integer	Quorum ID of the pair.
primaryJournalId	Integer	The ID of the primary journal. Set only if it is in replication group, otherwise null.
secondaryJournalId	Integer	The ID of the secondary journal. Set only if it is in replication group, otherwise null.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://172.17.64.112/v1/storage-systems/410500/replication-groups/1/affected-volume-pairs
```

### Example response

```
{
  "volumePairs": [
    {
      "replicationGroup": "test2",
      "volumePairGroup": null,
      "primaryVolume": {
        "id": 385,
        "storageSystemId": "410500",
        "status": "PAIR"
      },
      "secondaryVolume": {
        "id": 694,
        "storageSystemId": "410209",
        "status": "PAIR"
      },
      "mirrorId": 0,
      "splitTime": null,
      "consistent": true,
      "consistencyId": 2,
      "type": "HA",
      "state": "HEALTHY",
      "quorumId": 4,
      "primaryJournalId": null,
      "secondaryJournalId": null
    }
  ]
}
```

```

    }
  ]
}

```

## Listing primary volume pairs

You can display a list of volume pairs listed by the primary volume in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volume-pairs?
q=primaryVolume.id:primaryVolumeId
```

Use the storage system ID as the *storageSystemId*.

Use the ID as the *volumeId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "resources":
  [
    {
      "replicationGroup": ,
      "volumePairGroup": "",
      "primaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "secondaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "mirrorId": ,
      "splitTime": ,
      "consistent": ,
      "consistencyId": ,
      "type": "",
      "state": "",
      "quorumId": ,
    }
  ]
}

```

```

    "primaryJournalId": ,
    "secondaryJournalId":
  }
]
}

```

Parameter	Type	Description
replicationGroup	String	The name of the replication group.
volumePairGroup	String	The name of the copy group, for clones, or a snapshot group for snapshots.
id	Integer	ID of the volume.
storageSystemId	String	ID of the storage system.
status	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ SMPP: a volume pair with the clone attribute is being deleted.</li> <li>▪ PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>PFUL: If data in the journal volume exceeds 80%.</li> <li>PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
mirrorId	Integer	When multiple S-VOLs are created for one P-VOL, a mirror ID is assigned to each volume pair.
splitTime	Long	The time pair split is performed in Epoch time format.
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If not consistent, the value null is returned.
type	String	<p>The replication type for the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>CLONE</li> <li>SNAP: Snapshot</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
state	String	The volume pair state. Valid values: HEALTHY or ERROR.
quorumId	Integer	Quorum ID of the pair.
primaryJournalId	Integer	The ID of the primary journal. Set only if it is in replication group, otherwise null.
secondaryJournalId	Integer	The ID of the secondary journal. Set only if it is in replication group, otherwise null.

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.



**Example Request**

```
GET https://10.76.48.147/v1/storage-systems/410500/volume-pairs?
q=primaryVolume.id:385+AND+primaryVolume.storageSystemId:410500
```

**Example response**

```
{
  "resources": [
    {
      "replicationGroup": "test2",
      "volumePairGroup": null,
      "primaryVolume": {
        "id": 385,
        "storageSystemId": "410500",
        "status": "PAIR"
      },
      "secondaryVolume": {
        "id": 694,
        "storageSystemId": "410209",
        "status": "PAIR"
      },
      "mirrorId": 0,
      "splitTime": null,
      "consistent": true,
      "consistencyId": 2,
      "type": "HA",
      "state": "HEALTHY",
      "quorumId": 4,
      "primaryJournalId": null,
      "secondaryJournalId": null
    }
  ],
  "total": 1,
  "nextToken": null
}
```

## Listing secondary volume pairs

You can display a list of volume pairs listed by the secondary volume in a storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volume-pairs?
q=secondaryVolume.id:secondaryVolumeId
```

Use the storage system ID as the *storageSystemId*.

Use the secondary volume ID as the *secondaryVolumeId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "resources":
  [
    {
      "replicationGroup": ,
      "volumePairGroup": "",
      "primaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "secondaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "mirrorId": ,
      "splitTime": ,
      "consistent": ,
      "consistencyId": ,
      "type": "",
      "state": "",
      "quorumId": ,
      "primaryJournalId": ,
      "secondaryJournalId":
    },
  ]
}
```

Parameter	Type	Description
replicationGroup	String	The name of the replication group.

Parameter	Type	Description
volumePairGroup	String	The name of the copy group, for clones, or a snapshot group for snapshots.
id	Integer	ID of the volume.
storageSystemId	String	ID of the storage system.
status	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ SMPP: a volume pair with the clone attribute is being deleted.</li> <li>▪ PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
mirrorId	Integer	When multiple S-VOLs are created for one P-VOL, a mirror ID is assigned to each volume pair.
splitTime	Long	The time pair split is performed in Epoch time format.
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If not consistent, the value null is returned.
type	String	<p>The replication type for the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> <li>▪ ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>

Parameter	Type	Description
state	String	The volume pair state. Valid values: HEALTHY or ERROR.
quorumId	Integer	Quorum ID of the pair.
primaryJournalId	Integer	The ID of the primary journal. Set only if it is in replication group, otherwise null.
secondaryJournalId	Integer	The ID of the secondary journal. Set only if it is in replication group, otherwise null.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example Request

```
GET https://10.76.48.147/v1/storage-systems/410209/volume-pairs?
q=secondaryVolume.id:694+AND+secondaryVolume.storageSystemId:410209
```

**Example response**

```
{
  "resources": [
    {
      "replicationGroup": null,
      "volumePairGroup": null,
      "primaryVolume": {
        "id": 385,
        "storageSystemId": "410500",
        "status": "PAIR"
      },
      "secondaryVolume": {
        "id": 694,
        "storageSystemId": "410209",
        "status": "PAIR"
      },
      "mirrorId": 0,
      "splitTime": null,
      "consistent": true,
      "consistencyId": 2,
      "type": "HA",
      "state": "HEALTHY",
      "quorumId": 4,
      "primaryJournalId": null,
      "secondaryJournalId": null
    }
  ],
  "total": 1,
  "nextToken": null
}
```

**Listing secondary volumes for a primary volume**

You can display a list of secondary volumes for a specific primary volume in a storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volumes/volumeId/
secondaryVolumes
```

Use the storage system ID as the *storageSystemId*.

Use the volume ID as the *volumeId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "volumeResourceCollection":
  {
    "volumes": [
      {
        "volumeId": ,
        "storageSystemId": "",
        "storageSystemName": "",
        "poolId": "",
        "poolName": "",
        "label": "",
        "size": ,
        "usedCapacity": ,
        "availableCapacity": ,
        "utilization": ,
        "attributes": [""],
        "status": "",
        "type": "",
        "provisioningStatus": "",
        "portIds": [""],
        "hostGroupNames": [""],
        "luns": [],
        "numberOfLunPaths": ,
        "attachedVolumeServerSummary": [
          {
            "serverId": ,
            "paths": [
              {
                "storagePortId": "",
                "storageSystemId": "",
                "lun": ,
                "hostGroupId": "",
                "name": "",
                "hostMode": "",
                "wwns": [""],
                "hostModeOptions": [""],
                "iscsiTargetInformation": {},
                "preferredPath":
              },
              ...
            ]
          },
          ...
        ],
      },
      ...
    ],
  },
}
```

```

    "dataProtectionSummary": {
      "replicationType": [""],
      "volumeType": [""],
      "replicationGroupIdMap": {},
      "hasFailures": ,
      "secondaryVolumeCount": ,
      "secondaryVolumeFailures":
    },
    "gadSummary": {
      "vsmId": "",
      "virtualLdevId": ,
      "volumeType": "",
      "pairStatus": "",
      "consistencyId":,
      "mirrors" : [
        {
          "mirrorId": ,
          "volumeType": "",
          "pairStatus": "",
          "consistencyId":
        },
        ...
      ]
    },
    "compressionAcceleration": ,
    "commandDevice":
  },
  ...
]
}
}

```

Parameter	Type	Description
volumeResourceCollection	Set	List of primary or secondary volumes.
volumeId	Long	ID number of the volume within the parent storage system.
storageSystemId	String	ID of the storage system.
storageSystemName	String	The name of the storage system.
poolId	String	ID of the pool from which the resource is allocated.
poolName	String	Name of the pool from which the resource is allocated.
label	String	Name of the volume.



Parameter	Type	Description
size	Long	Size of the volume, in bytes.
usedCapacity	Long	Sum of used capacity per volume resource, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage= (usedCapacity/size) *100.
attributes	List	<p>List of the attributes of the volume. Valid values:</p> <ul style="list-style-type: none"> <li>▪ THIN: a volume for thin provisioning.</li> <li>▪ VVOL: a secondary volume for creating snapshots.</li> <li>▪ GUARD: a volume for Data Retention Utility.</li> <li>▪ MIGRATION_RESERVED: a volume for the data migration.</li> <li>▪ HA: a primary or secondary volume for High Availability.</li> <li>▪ HA_RESERVED: a reserved volume for High Availability.</li> <li>▪ NAS_TYPE_USER: a volume used as a user LU of the storage system includes NAS modules.</li> <li>▪ ALUA: a volume of which ALUA mode is enabled.</li> <li>▪ T10PI: a volume of which T10PI mode is enabled.</li> <li>▪ COMPRESSION: a volume of which compression is enabled.</li> <li>▪ DEDUPLICATION: a volume of which deduplication is enabled.</li> <li>▪ DRS: a volume of which DRS is enabled.</li> </ul>
status	String	Volume status. Valid values: NORMAL, BLOCKED, BUSY, SHREDDING, UNKNOWN, or NONE.

Parameter	Type	Description
type	String	Type of pool from which the volume is allocated. Valid values: THIN, TIERED, or SNAP.
provisioningStatus	String	Provisioning status of a volume. Valid values: ATTACHED, UNATTACHED, or UNMANAGED.
portIds	List	List of the storage port IDs.
hostGroupNames	List	List of the host group names.
luns	List	List of the LUN IDs.
numberOfLunPaths	Integer	The number of paths from WWNs or iSCSI names to volumes (excluding paths where LUN security is disabled).
dkcDataSavingType	String	Type of controller-based capacity saving. Valid values are COMPRESSION, DEPLICATION_AND_COMPRESSIO N, and NONE.
aluaEnabled	Boolean	Whether or not ALUA mode of the volume is enabled.
migrationSummary	Object	List of migration attributes for the volume.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	Migration type. Valid values: <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
virtualStorageMachineInformation	Object	Displays the virtual storage machine information for the volume. A value of NULL is returned if there are no VSMs.
virtualStorageMachineId	String	The virtual storage machine ID that belongs to this volume.
storageSystemId	String	The serial number of the VSM to which the volume belongs.
model	String	The model of the VSM to which the volume belongs.
virtualVolumeId	Long	The virtual volume ID. If the virtual volume is not defined, a value of NULL is returned.

Parameter	Type	Description
attachedVolumeServerSummary	List	Volume provisioning summary details.
serverId	Integer	ID of the server.
paths	List	Paths that exist on the volume.
storagePortId	Long	ID of the storage port.
storageSystemId	String	ID of the storage system.
lun	Integer	ID of the LUN.
hostModeOptions	List of Integers	Host mode options for the volume.
name	String	Name of the resource.
hostMode	String	Host mode set for the volume.
wwns	List	List of WWNs of connected hosts. NULL for iSCSI path.
hostGroupId	Long	ID of the host group.
iscsiTargetInformation	Object	Displays iSCSI target information. NULL for FC host groups.
preferredPath	Boolean	Whether the LU path (host group) is preferred or not.
dataProtectionSummary	Object	List of the data protection attributes of the volume.
replicationType	String	Volume replication type. Valid values: <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> <li>▪ CLONE</li> <li>▪ SNAP: Snapshot</li> <li>▪ HA: High Availability (global-active device)</li> </ul>
volumeType	Set	Type of volume in the replication. Valid values: P-VOL, S-VOL, or UNPROTECTED.

Parameter	Type	Description
replicationGroupIdMap	Object	Replication group ID map. Consisting of the replication group ID and the replication group name for each of the replication group the volume belongs to.
hasFailures	Boolean	Whether the volume has replication failures.
secondaryVolumeCount	Integer	Count of secondary volume pairs protecting the primary volume.
secondaryVolumeFailures	Integer	Count of failed volume pairs where this volume is an S-VOL.
gadSummary	Object	List of the GAD attributes of the volume. If there is no GAD pair, a NULL value is returned.
vsmlId	String	ID number of the virtual storage machine (VSM).
virtualLdevID	String	ID number of the virtual volume.
volumeType	String	Volume type. Valid values: Active-Primary, Active-Secondary  <b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>volumeType</code> parameter of the <code>mirrors</code> object instead.
pairStatus	String	The status of the given volume in the volume pair. Valid values: <ul style="list-style-type: none"> <li>PAIR: a volume is in paired status.</li> <li>PSUS: a volume pair is in suspended status for the primary volume.</li> <li>SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>COPY: a volume pair is in data synchronizing status.</li> <li>PSUE: a volume pair is in suspended status with error.</li> <li>SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>UNKNOWN: a volume pair is in unknown status.</li> <li>NONE: a volume is not paired.</li> </ul> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>pairStatus</code> parameter of the <code>mirrors</code> object instead.</p>
<code>consistencyId</code>	Integer	<p>The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.</p> <p><b>Note:</b> This parameter is deprecated and will be removed in a future version. Use the <code>consistencyId</code> parameter of the <code>mirrors</code> object instead.</p>
<code>mirrors</code>	Object	List of the GAD attributes per mirror of the volume.
<code>volumeType</code>	String	Volume type. Valid values: ACTIVE_PRIMARY, ACTIVE_SECONDARY, NOT_AVAILABLE
<code>pairStatus</code>	String	<p>The status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>PAIR: the volume is in paired status.</li> <li>PSUS: the volume pair is in suspended status for the primary volume.</li> <li>SSUS: the volume pair is in suspended status for the secondary volume.</li> <li>COPY: the volume pair is in data synchronizing status.</li> <li>PSUE: the volume pair is in suspended status with error.</li> <li>SSWS: the volume pair is in suspended status for swapping the secondary volume.</li> </ul>

Parameter	Type	Description
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If the volume pair is not a part of consistency group, a NULL value is returned.  For storage systems without an SVP, a NULL value is returned.
compressionAcceleration	String	Whether the compression accelerator is enabled or not for the volume Valid values: ENABLED, DISABLED, -
commandDevice	Object	Command device settings for the volume.  The value of this parameter is null in case of storage systems without SVP or not command device.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
GET https://172.17.92.44v1/storage-systems/41020/volumes/694/secondaryVolumes
```

**Example response**

```
{
  "volumeResourceCollection":
  {
    "volumes":
    [
      {
        "volumeId": 0,
        "storageSystemId": "41020",
        "storageSystemName": "RN-SC-41020-HID_SVOS7.3-Gsd",
        "resourceGroupId": 0,
        "resourceGroupName": "meta_resource",
        "poolId": "3",
        "poolName": "test-pool",
        "label": "test-aua",
        "size": 2147483648,
        "usedCapacity": 0,
        "availableCapacity": 2147483648,
        "utilization": 0,
        "attributes": [
          "THIN"
        ],
        "status": "NORMAL",
        "type": "THIN",
        "provisioningStatus": "ATTACHED",
        "portIds": [
          "CL1-E",
          "CL3-F"
        ],
        "hostGroupNames": [
          "DocServer",
          "windows16"
        ],
        "luns": [
          1,
          2
        ],
        "numberOfLunPaths": 2,
        "attachedVolumeServerSummary": [
          {
            "serverId": null,
            "paths": [
              {
                "storagePortId": "CL3-F",
                "storageSystemId": "41020",
                "lun": 1,

```

```

        "hostGroupId": "CL3-F-6",
        "name": "windows16",
        "hostMode": "WIN",
        "wwns": [
            "1000000533267214"
        ],
        "hostModeOptions": [],
        "iscsiTargetInformation": null,
        "preferredPath": true
    },
    ...
]
},
{
    "serverId": 2,
    "paths": [
        {
            "storagePortId": "CL1-E",
            "storageSystemId": "41020",
            "lun": 2,
            "hostGroupId": "CL1-E-12",
            "name": "DocServer",
            "hostMode": "SOLARIS",
            "wwns": [
                "5000000000000000"
            ],
            "hostModeOptions": [],
            "iscsiTargetInformation": null,
            "preferredPath": true
        },
        ...
    ]
}
],
...
"gadSummary": {
    "vsmId": "7",
    "virtualLdevId": "2657",
    "volumeType": "ACTIVE_PRIMARY",
    "pairStatus": "PAIR",
    "consistencyId": 15,
    "mirrors" : [
        {
            "mirrorId": 0,
            "volumeType": "ACTIVE_SECONDARY",
            "pairStatus": "PAIR",
            "consistencyId": 15
        },
        {
            "mirrorId": 1,
            "volumeType": "ACTIVE_PRIMARY",

```



```

        "pairStatus": "COPY",
        "consistencyId": 17
      }
    ],
    "compressionAcceleration": "ENABLED",
    "commandDevice": null
  }
}

```

## Listing failed volume pairs

You can display a list of failed volume pairs in a storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/volume-pairs?q=state:ERROR
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "resources":
  [
    {
      "replicationGroup": ,
      "volumePairGroup": "",
      "primaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "secondaryVolume":
      {
        "id": ,
        "storageSystemId": "",
        "status": ""
      },
      "mirrorId": ,
      "splitTime": ,
      "consistent": ,
    }
  ]
}

```

```

        "consistencyId": ,
        "type": "",
        "state": "",
        "quorumId": ,
        "primaryJournalId": ,
        "secondaryJournalId":
    }
]
}

```

Parameter	Type	Description
replicationGroup	String	The name of the replication group.
volumePairGroup	String	The name of the copy group, for clones, or a snapshot group for snapshots.
id	Integer	ID of the volume.
storageSystemId	String	ID of the storage system.
status	String	<p>Status of the given volume in the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ PAIR: a volume is in paired status.</li> <li>▪ PSUS: a volume pair is in suspended status for the primary volume.</li> <li>▪ SSUS: a volume pair is in suspended status for the secondary volume.</li> <li>▪ SMPP: a volume pair with the clone attribute is being deleted.</li> <li>▪ PSUP: a volume pair with the clone attribute is in suspended status.</li> <li>▪ COPY: a volume pair is in data synchronizing status.</li> <li>▪ PSUE: a volume pair is in suspended status with error.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>▪ SSWS: a volume pair is in suspended status for swapping the secondary volume.</li> <li>▪ CPYP: A secondary volume is in the process of being assigned, released, or changed for the snapshot data.</li> <li>▪ PFUL: If data in the journal volume exceeds 80%.</li> <li>▪ PFUS: If the Data Overflow Watch period is exceeded, pair status changes from PFUL to PFUS.</li> </ul>
mirrorId	Integer	When multiple S-VOLs are created for one P-VOL, a mirror ID is assigned to each volume pair.
splitTime	Long	The time pair split is performed in Epoch time format.
consistent	Boolean	Whether copying takes place on all volume pairs in the group simultaneously.
consistencyId	Integer	The ID of the consistency group in which the volume pair resides. If not consistent, the value null is returned.
type	String	<p>The replication type for the volume pair. Valid values:</p> <ul style="list-style-type: none"> <li>▪ SNAP_ON_SNAP: Snapshot pair that can be cascaded.</li> <li>▪ SNAP_CLONE: A pair relationship in which the secondary volume of the pair will be a real volume of the primary volume.</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>CLONE</li> <li>SNAP: Snapshot</li> <li>HA: High Availability (global-active device)</li> <li>ASYNC_REMOTE_CLONE: Asynchronous Remote Clone</li> </ul>
state	String	The volume pair state. Valid values: HEALTHY or ERROR.
quorumId	Integer	Quorum ID of the pair.
primaryJournalId	Integer	The ID of the primary journal. Set only if it is in replication group, otherwise null.
secondaryJournalId	Integer	The ID of the secondary journal. Set only if it is in replication group, otherwise null.

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Request**

```
GET https://172.17.64.112/v1/storage-systems/410031/volume-pairs?state=ERROR
```

**Example response**

```
{
  "resources":
  [
    {
      "replicationGroup": null,
      "volumePairGroup": "RL-Multiple-snaps_1462426223934",
      "primaryVolume":
      {
        "id": 14,
        "storageSystemId": "410031",
        "status": "PSUS"
      },
      "secondaryVolume":
      {
        "id": 46,
        "storageSystemId": "410031",
        "status": "SSUS"
      },
      "mirrorId": 10,
      "splitTime": 1462441131000,
      "consistent": true,
      "consistencyId": null,
      "type": "SNAP",
      "state": "ERROR",
      "quorumId": 4,
      "primaryJournalId": null,
      "secondaryJournalId": null
    }
  ]
}
```

## Getting Ops Center Protector information

You can retrieve information about Ops Center Protector, such as its IP address or login user name, in Ops Center Administrator.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/dp-manager
```

**Request structure**

Not applicable.

**Response structure**

```
{
  "ipAddress": "",
  "tcpPort": ,
  "namespace": "",
  "username": "",
  "version": "",
  "lastUpdated":
}
```

Parameter	Required	Type	Description
ipAddress	Yes	String	IP address of the Ops Center Protector API.
tcpPort	Yes	Integer	TCP port number of the Ops Center Protector API.
namespace	Yes	String	Space name to which the user belongs
username	Yes	String	Login user name.
version	Yes	String	The version of the Ops Center Protector.
lastUpdated	Yes	Long	The time of last update in Epoch time format.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example response**

```
{
  "ipAddress": "10.76.49.230",
  "tcpPort": 443,
  "namespace": "master",
  "username": "Administrator",
  "version": "7.2.5",
  "lastUpdated": 1638136882062
}
```

## Registering/Deleting the Hitachi Ops Center Protector

You can use this operation to register or delete information about Hitachi Ops Center Protector in Ops Center Administrator.

**HTTP request syntax (URI)**

```
PATCH https://ipAddress/v1/dp-manager
```

**Request structure**

```
{
  "keepConnection": ,
  "connectionProfile": {
    "ipAddress": "",
    "tcpPort": ,
    "namespace": "",
    "username": "",
    "password": ""
  }
}
```

Parameter	Required	Type	Description
keepConnection	Yes	Boolean	Keeps a connection with Ops Center Protector alive. Specify this as false if you want to delete the Hitachi Ops Center Protector.
connectionProfile	No	Object	Necessary information for connecting the Hitachi Ops Center Protector. It is required if you want to register the Hitachi Ops Center Protector. It is optional if you want to delete the Hitachi Ops Center Protector.
ipAddress	Yes*	String	The IP address of the Hitachi Ops Center Protector.
tcpPort	Yes*	Integer	The TCP port number of the Hitachi Ops Center Protector (API).
namespace	Yes*	String	Space name to which the user belongs
username	Yes*	String	Login user name.
password	Yes*	String	Password of the user.
*: All the parameters inside connectionProfile are mandatory, if connectionProfile is being passed in the request.			

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",

```



```

"title":
{
  "text": "",
  "messageCode": "",
  "parameters":
  {
  }
},
"user": "",
"status": "",
"createdDate":,
"scheduledDate":,
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).

Parameter	Type	Description
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status Code	HTTP Name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
PATCH
{"keepConnection":true,"connectionProfile":{"ipAddress":"172.17.64.117","tcpPort":443,
"username":"Administrator","namespace":"master","password":"Welcome@123"}}
```

### Example response

```
{
  "jobId": "2cb2b2f6-56ff-4146-904c-6640ebef22da",
  "title": {
    "text": "Create Hitachi Ops Center Protector",
    "messageCode": "CreateHdidJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1548893079254,
  "endDate": null,
  "parentJobId": null,
  "reports": [],
  "links": [{
    "rel": "_self",
    "href": "/v1/jobs/2cb2b2f6-56ff-4146-904c-6640ebef22da"
  }],
  "tags": [{
    "tag": "rainier"
  }],
  "isSystem": false
}
```

## Testing the connection to Ops Center Protector

You can test the connection to the Ops Center Protector in Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/dp-manager/test-connection
```

### Request structure

```
{
  "ipAddress": "",
  "tcpPort": ,
  "namespace": "",
  "username": "",
  "password": ""
}
```

Parameter	Required	Type	Description
ipAddress	Yes	String	The IP address of the Hitachi Ops Center Protector.
tcpPort	Yes	Integer	The TCP port number of the Hitachi Ops Center Protector (API).
namespace	Yes	String	Space name to which the user belongs
username	Yes	String	Login user name.
password	No	String	Password of the user. Password is not mandatory.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
}
```

```

    "status": "",
    "createdDate": ,
    "scheduledDate": ,
    "startDate": ,
    "endDate": ,
    "parentJobId": ,
    "reports":
    [
    ],
    "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
    "tags":
    [
    ],
    "isSystem":
  }

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

#### Return codes

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

POST

```
{ "ipAddress": "172.17.64.117", "tcpPort": 443, "username": "Administrator",
  "namespace": "master", "password": "Hitachi@123" }
```

## Importing high availability pairs from Ops Center Protector

You can collect HA pairs from Ops Center Protector and import them to Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/dp-manager/import
```

**Request structure**

```
{
  "storageSystemIds": []
}
```

Parameter	Required	Type	Description
storageSystemIds	Yes	List	The IDs of the primary storage systems of the HA pairs in String format.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
```

```

"startDate": ,
"endDate": ,
"parentJobId": ,
"reports":
[
],
"links":
[
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.



Parameter	Type	Description
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Example response**

```
{
  "jobId": "cb01b71a-36f0-41ae-9060-2d82517eb858",
  {
    "text": "import HA pairs",
    "messageCode": "ImportHaPairsJobTitleMessage",
    "parameters":
    {
    },
  },
  "user": "sysadmin",
  "status": "IN_PROGRESS",
  "startDate": 1455837568839,
  "endDate": null,
  "parentJobId": null,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/cb01b71a-36f0-41ae-9060-2d82517eb858"
    }
  ],
  "tags":
  [
  ],
}
```

```
"isSystem": false
}
```

### Return codes

Status Code	HTTP Name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
400	Bad Request	Ops Center Protector is not registered yet.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The request could not be completed due to a conflict with the current state of the target resource.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
{
  "storageSystemIds": [
    "100542",
    "200555"
  ]
}
```

## Listing quorum disks

You can retrieve a list of quorum disks in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/quorum-disks
```

**Request structure**

Not applicable.

**Response structure**

```
{
  "resources":
  [
    {
      "quorumId": "",
      "volumeId": "",
      "volumeName": "",
      "remoteStorageSystemId": "",
      "status": ""
    }
  ],
  "total": ,
  "nextToken":
}
```

Parameter	Type	Description
resources	Array of objects	Resource information.
total	Long	Total number of resources.
nextToken	String	The API will return up to 100 resources with one call. nextToken is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken=", and then the token.
quorumId	Integer	ID of the quorum disk.
volumeId	Long	ID number of the volume within the storage system.
volumeName	String	Name of the volume within the remote storage system.
remoteStorageSystemId	String	ID of the remote storage system.

Parameter	Type	Description
status	String	<p>Displays the status of a quorum disk of GAD. Possible values are:</p> <ul style="list-style-type: none"> <li>▪ NORMAL: The quorum disk is in normal status.</li> <li>▪ TRANSITIONING: The status of the quorum is being changed.</li> <li>▪ BLOCKED: The quorum disk is blocked.</li> <li>▪ REPLACING: The quorum disk is being replaced.</li> <li>▪ FAILED: The quorum disk is in abnormal state.</li> <li>▪ NULL: This information is not available for this quorum disk.</li> </ul>

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
400	Bad request	The request contains an invalid request payload or the required HTTP header was not specified.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example**

```
{
  "resources": [
    {
      "quorumId": 0,
      "volumeId": 16383,
      "volumeName": "Quorum_Partition_42007_PG1-3",
      "remoteStorageSystemId": "410209",
      "status": "BLOCKED"
    },
    {
      "quorumId": 3,
      "volumeId": 16379,
      "volumeName": "Quorum_Gefn_PG1-1",
      "remoteStorageSystemId": "410209",
      "status": "NORMAL"
    },
    {
      "quorumId": 4,
      "volumeId": 272,
      "volumeName": "quorum-4",
      "remoteStorageSystemId": "410209",
      "status": "NORMAL"
    },
    {
      "quorumId": 5,
      "volumeId": 273,
      "volumeName": "quorum-5",
      "remoteStorageSystemId": "410209",
      "status": "NORMAL"
    }
  ],
  "total": 4,
  "nextToken": null
}
```

## Listing remote paths

Retrieves `RemotePathResource` object for requested storage system Id

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/storageSystemId/remote-paths
```

**Request structure**

Not applicable.

**Response structure**

List of RemotePathResource:

```
{
  "resources": [{
    "storageSystemId": "",
    "initiatorPortId": "",
    "targetPortId": "",
    "remoteStorageSystemId": "",
    "status": ""
  }],
  "total": 3,
  "nextToken": null
}
```

Parameters	Type	Description
storageSystemId	String	Storage System Id
initiatorPortId	String	Initiator Port
targetPortId	String	Target Port
remoteStorageSystemId	String	Remotely Connected Storage System Id
status	String	Displays the path status. Possible values are: <ul style="list-style-type: none"> <li>▪ NML_01 Normal</li> <li>▪ ERR_02 Initialization Failed</li> <li>▪ ERR_03 Communication Timeout</li> <li>▪ ERR_04 Logical Blockade</li> <li>▪ ERR_05 Resource Shortage</li> <li>▪ ERR_06 Serial Number Mismatch</li> <li>▪ ERR_10 Invalid Port</li> <li>▪ ERR_80 RCU Port Number Mismatch</li> <li>▪ ERR_81 RCU Port Type Mismatch</li> <li>▪ - Path Deletion in Progress</li> </ul>

**Return codes**

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example Response**

```
{
  "resources": [{
    "storageSystemId": "415039",
    "initiatorPortId": "CL1-E",
    "targetPortId": "CL2-R",
    "remoteStorageSystemId": "451390",
    "status": "Initialization Failed"
  }, {
    "storageSystemId": "415039",
    "initiatorPortId": "CL3-F",
    "targetPortId": "CL3-B",
    "remoteStorageSystemId": "451390",
    "status": "Normal"
  }, {
    "storageSystemId": "415039",
    "initiatorPortId": "CL2-E",
    "targetPortId": "CL2-F",
    "remoteStorageSystemId": "410209",
    "status": "Normal"
  }],
  "total": 3,
  "nextToken": null
}
```

## Getting a high availability setup status summary

Get status summary of high availability setup.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/ha-setup-status?
primaryStorageSystemId={ssid}&secondaryStorageSystemId={ssid}
```

**Request structure**

Not applicable.

**Response structure**

```
{
  "haSetupRemoteConnections": {
    "haPrimaryStorageSystemResource": {
      "resourcesFound" :,
      "resources": [{
        "storageSystemId": "",
        "initiatorPortId": "",
        "targetPortId": "",
        "remoteStorageSystemId": "",
        "status": ""
      }]
    },
    "haSecondaryStorageSystemResource": {
      "resources": [{
        "storageSystemId": "",
        "initiatorPortId": "",
        "targetPortId": "",
        "remoteStorageSystemId": "",
        "status": ""
      }]
    }
  },
  "haSetupQuorumDisks": {
    "resourcesFound" : ,
    "resources": [{
      "quorumId": ,
      "volumeId": ,
      "volumeName": ,
      "remoteStorageSystemId": "",
      "status": ""
    }]
  },
  "haSetupVsms": {
    "resourcesFound" : ,
    "resources": [{
      "virtualStorageMachineId": "",
      "storageSystemId": "",
      "model": "",
      "physicalStorageSystemIds": [
        "",
        ""
      ]
    }]
  }
}
```



```

    }
}

```

Parameters	Type	Description
storageSystemId	String	Storage System Id
remoteStorageSystemId	String	Remote Storage System Id
virtualStorageMachineId	String	ID number of the virtual storage machine (VSM).
haSetupRemoteConnections	Object	Lists remote connections for primary and secondary storage arrays.
haPrimaryStorageSystemResource	Object	Lists remote connections for primary storage array.
haSecondaryStorageSystemResource	Object	Lists remote connections for secondary storage array.
haSetupQuorumDisks	Object	Lists quorum disks between primary and secondary arrays.
haSetupVsms	Object	Lists VSMs between primary and secondary arrays.
resourcesFound	Boolean	Whether or not any resources were found for the given storage system.
quorumId	String	The ID of the Quorum Device.
volumeId	Long	ID number of the volume within the parent storage system.
initiatorPortId	String	Initiator Port
targetPortId	String	Target Port
remoteStorageSystemId	String	Remotely Connected Storage System Id
status	String	Remote connection status. Valid values: <ul style="list-style-type: none"> <li>▪ NORMAL</li> <li>▪ ERROR</li> <li>▪ UNKNOWN</li> </ul>

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Response Example**

```
{
  "haSetupRemoteConnections": {
    "haPrimaryStorageSystemResource": {
      "resourcesFound" : true,
      "resources": [{
        "storageSystemId": "415039",
        "initiatorPortId": "CL1-E",
        "targetPortId": "CL2-R",
        "remoteStorageSystemId": "451390",
        "status": "ERROR"
      }, {
        "storageSystemId": "415039",
        "initiatorPortId": "CL3-F",
        "targetPortId": "CL3-B",
        "remoteStorageSystemId": "451390",
        "status": "NORMAL"
      }]
    },
    "haSecondaryStorageSystemResource": {
      "resourcesFound" : true,
      "resources": [{
        "storageSystemId": "451390",
        "initiatorPortId": "CL1-B",
        "targetPortId": "CL1-F",
        "remoteStorageSystemId": "415039",
        "status": "NORMAL"
      }]
    }
  }
}
```

```

    }
  },
  "haSetupQuorumDisks": {
    "resourcesFound" : true,
    "resources": [{
      "quorumId": 1,
      "volumeId": null,
      "volumeName": null,
      "remoteStorageSystemId": "451390",
      "status": "UNKNOWN"
    },
    {
      "quorumId": 3,
      "volumeId": 20,
      "volumeName": "forQuorum_0011",
      "remoteStorageSystemId": "451390",
      "status": "NORMAL"
    }
  ]
},
  "haSetupVsms": {
    "resourcesFound" : true,
    "resources": [{
      "virtualStorageMachineId": "421671-VSPF800andVSPG800",
      "storageSystemId": "421671",
      "model": "VSP F800 and VSP G800",
      "physicalStorageSystemIds": [
        "415039",
        "451390"
      ]
    },
    {
      "virtualStorageMachineId": "415039-VSPF700",
      "storageSystemId": "415039",
      "model": "VSP F700",
      "physicalStorageSystemIds": [
        "415039",
        "451390"
      ]
    },
    {
      "virtualStorageMachineId": "467543-VSPF370",
      "storageSystemId": "467543",
      "model": "VSP F370",
      "physicalStorageSystemIds": [
        "415039",
        "451390"
      ]
    }
  ]
}

```

```

    }
  }
}

```

## Listing high availability status external volumes

### HTTP request syntax (URI)

```

GET https://ipAddress/v1/ha-setup-status/external-volumes?
primaryStorageSystemId={ssid}&secondaryStorageSystemId={ssid}

```

### Request structure

Not applicable.

### Response structure

```

{
  "resources": [
    {
      "volumeId": ,
      "mappedVolumeId": ,
      "externalDeviceId": "",
      "externalParityGroupId": "",
      "storageSystemId": "",
      "poolId": ,
      "label": "",
      "size": ,
      "usedCapacity": ,
      "availableCapacity": ,
      "utilization": ,
      "status": "",
      "type": "",
      "provisioningStatus": "",
      "attachedVolumeServerSummary": [],
      "migrationSummary": {
        "ownerTaskId": ,
        "migrationType": ""
      }
    }
  ]
}

```

Parameters	Type	Description
storageSystemId	String	ID of the storage system.

Parameters	Type	Description
mappedVolumeld	String	Remote Storage System Id
externalDeviceld	String	ID number of the virtual storage machine (VSM).
label	String	Name of the volume.
size	Long	Size of the volume, in bytes.
utilization	Integer	The percentage usage of the volume capacity. The utilization percentage=(usedCapacity/size)*100.
type	String	Type of pool from which the volume is allocated. Valid value: EXTERNAL
provisioningStatus	String	Provisioning status of a volume. Valid values: <ul style="list-style-type: none"> <li>▪ ATTACHED</li> <li>▪ UNATTACHED</li> <li>▪ UNMANAGED</li> </ul>
attachedVolumeServerSummary	String	Volume provisioning summary details.
migrationSummary	Object	List of migration attributes for the volume.
usedCapacity	String	Sum of used capacity across all pools of the specified type in the storage system, in bytes.
availableCapacity	Long	Unused capacity of the resource, in bytes.
poolId	String	ID of the pool from which the resource is allocated.
externalParityGroupId	String	ID of the parity group on external volumes.
ownerTaskId	String	The ID of the owner migration task.
migrationType	String	Migration type. Valid values: <ul style="list-style-type: none"> <li>▪ MIGRATION</li> <li>▪ NONE</li> </ul>
volumeld	Long	ID number of the volume within the parent storage system.
initiatorPortId	String	Initiator Port
targetPortId	String	Target Port

Parameters	Type	Description
remoteStorageSystemId	String	Remotely Connected Storage System Id
status	String	Volume status. Valid values: <ul style="list-style-type: none"> <li>▪ NORMAL</li> <li>▪ BLOCKED</li> <li>▪ BUSY</li> <li>▪ UNKNOWN</li> <li>▪ NONE</li> </ul>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Response Example

```
{
  "resources": [
    {
      "volumeId": 10,
      "mappedVolumeId": null,
      "externalDeviceId": "EXAMPLE 504027E10010",
      "externalParityGroupId": "1-3",
      "storageSystemId": "415039",
      "poolId": null,
      "label": "forQuorum410209",
      "size": 16106127360,
      "usedCapacity": 16106127360,
    }
  ]
}
```

```
    "availableCapacity": 0,  
    "utilization": 100,  
    "status": "BLOCKED",  
    "type": "EXTERNAL",  
    "provisioningStatus": "UNATTACHED",  
    "attachedVolumeServerSummary": [],  
    "migrationSummary": {  
      "ownerTaskId": null,  
      "migrationType": "NONE"  
    }  
  }  
]  
  
}
```

## Chapter 8: Monitoring resources

You can use Ops Center Administrator APIs for capacity, hardware, and SNMP monitoring operations.

### Capacity monitoring resources

Request	Method	URI	Role
<a href="#">Getting the total number of capacity alerts for all storage systems (on page 793)</a>	GET	/v1/monitoring/status/capacity	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing capacity alert details for all storage systems (on page 794)</a>	GET	/v1/monitoring/status/capacity/resourceType	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting the total number of capacity alerts for a storage system (on page 796)</a>	GET	/v1/monitoring/status/storageSystemId/capacity	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing capacity alert details for a storage system (on page 797)</a>	GET	/v1/monitoring/status/storageSystemId/capacity/resourceType	Storage administrator System administrator



Request	Method	URI	Role
			Security administrator Monitoring
<a href="#">Getting a summary of data reduction savings and capacity efficiency (on page 799)</a>	GET	/v1/capacity-savings/summary	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting a data reduction savings and capacity efficiency summary for a storage system (on page 801)</a>	GET	/v1/capacity-savings/storage-systems/ <i>storageSystemId</i> /summary	Storage administrator System administrator Security administrator Monitoring

## Getting the total number of capacity alerts for all storage systems

You can display the total number of issued alerts for all storage systems.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/capacity
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "totalComponentWiseCapacityAlerts": ,
  "capacityComponents":
  {
    "poolAlerts":
  }
}
```

Parameter	Type	Description
totalComponentWiseCapacityAlerts	Integer	Total number of capacity components with alerts.
capacityComponents	List	List of capacity components with alerts.
poolAlerts	Boolean	Whether or not a pool in the storage system issued an alert.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Listing capacity alert details for all storage systems

You can display the details of the capacity alerts that were issued for the storage systems.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/capacity/resourceType
```

Use pool as the *resourceType*.

### Request structure

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "capacityAlertInformationList": [
    {
      "storageSerialNumber": "",
      "storageNickname": "",
      "refCode": "",
      "resourceType": "",
      "timestamp": "",
      "description": "",
      "alertLevel": "",
      "resourceId": ""
    }
  ]
}
```

Parameter	Type	Description
storageSerialNumber	Integer	Storage system serial number.
storageNickname	String	Storage system name.
refCode	Integer	Alert reference code.
resourceType	String	Type of resource: pool.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.
resourceId	String	ID of the resource.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.115/v1/monitoring/status/capacity/pool
```

**Getting the total number of capacity alerts for a storage system**

You can display the total number of capacity alerts that were issued for a specified storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/monitoring/status/storageSystemId/capacity
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "totalComponentWiseCapacityAlerts": ,
  "capacityComponents": {
    "poolAlerts":
  }
}
```

Parameter	Type	Description
totalComponentWiseCapacityAlerts	Integer	Total number of components with capacity alerts.
capacityComponents	List	List of capacity components with alerts, such as poolAlerts.
poolAlerts	Boolean	Whether or not a pool in the storage system issued an alert.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Listing capacity alert details for a storage system

You can display the details of the capacity alerts for the specified storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/storageSystemId/capacity/resourceType
```

Use the storage system ID as the *storageSystemId*.

Use pool as the *resourceType*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "capacityAlertInformationList": [
    {
      "storageSerialNumber": "",
      "storageNickname": "",
      "refCode": "",
      "resourceType": "",
      "timestamp": "",
      "description": "",
      "alertLevel": "",
      "resourceId": ""
    }
  ]
}
```

Parameter	Type	Description
storageSerialNumber	String	Storage system serial number.
storageNickname	String	Storage system name.
refCode	String	Alert reference code.
resourceType	String	Type of resource: pool.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.
resourceId	String	ID of the resource.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

#### Example request

```
https://172.17.64.113/v1/monitoring/status/capacity/pool
```

## Getting a summary of data reduction savings and capacity efficiency

You can get a summary of data reduction savings from deduplication and compression technologies as well as capacity efficiency.

#### HTTP request syntax (URI)

```
GET https://ipAddress/v1/capacity-savings/summary
```

#### Request structure

Not applicable.

#### Response structure

The response body structure is shown below:

```
{
  "dataReductionSavingsRate": "",
  "capacityEfficiencyRate": ""
}
```

Parameter	Type	Description
dataReductionSavingsRate	Float	The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.
capacityEfficiencyRate	Float	<p>The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.</p> <p>If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.</p> <p>If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.</p> <p>If no compression technology is in use, the physical used capacity is the used capacity of the pools.</p>

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.



**Example code**

```
{
  "dataReductionSavingsRate" : 3.04,
  "capacityEfficiencyRate" : 65.72
}
```

## Getting a data reduction savings and capacity efficiency summary for a storage system

You can get a summary of data reduction savings and capacity efficiency for a specific storage system.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/capacity-savings/storage-systems/storageSystemId/summary
```

Use the storage system ID as the *storageSystemId*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "dataReductionSavingsRate": "",
  "capacityEfficiencyRate": ""
}
```

Parameter	Type	Description
dataReductionSavingsRate	Float	The ratio of logical used capacity to the physical used capacity, for all compression and deduplication technologies.
capacityEfficiencyRate	Float	<p>The ratio of Thin Free plus Thin Used to the physical used capacity. Capacity efficiency is only calculated for volumes on Thin, Tiered, and Snap pools.</p> <p>If disk-based compression is in use, either alone or in combination with controller-based compression, the physical used capacity is that resulting from disk-based compression alone.</p>

Parameter	Type	Description
		If only controller-based compression is in use, the physical used capacity is that resulting from controller-based compression.  If no compression technology is in use, the physical used capacity is the used capacity of the pools.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example code

```
{  
  'dataReductionSavingsRate' : 3.11,  
  'capacityEfficiencyRate' : 1056.72  
}
```

## Monitoring hardware resources

Request	Method	URI	Role
<a href="#">Getting the total number of hardware alerts for all storage systems (on page 804)</a>	GET	/v1/monitoring/status/hardware	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing resource-specific hardware alert details for all storage systems (on page 806)</a>	GET	/v1/monitoring/status/hardware/resourceType	Storage administrator System administrator Security administrator Monitoring
<a href="#">Getting the total number of hardware alerts for a storage system (on page 808)</a>	GET	/v1/monitoring/status/storageSystemId/hardware	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing resource-specific hardware alert details for a storage system (on page 810)</a>	GET	/v1/monitoring/status/storageSystemId/hardware/resourceType	Storage administrator System administrator Security administrator Monitoring
<a href="#">Listing disk alert information for all storage systems (on page 812)</a>	GET	/v1/monitoring/status/hardware/disk	Storage administrator System administrator Security administrator

Request	Method	URI	Role
			Monitoring
<a href="#">Listing disk alert information for a storage system (on page 815)</a>	GET	/v1/monitoring/status/ <i>storageSystemId</i> /hardware/disk	Storage administrator System administrator Security administrator Monitoring

## Getting the total number of hardware alerts for all storage systems

You can display the total number of alerts and alert types that were issued for all storage systems. Alerts from disk, power supply, battery, fan, port, cache, memory, and processors are displayed.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/hardware
```

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "totalComponentWiseHardwareAlerts": ,
  "hardwareComponents":
  {
    "diskAlerts": ,
    "powerSupplyAlerts": ,
    "batteryAlerts": ,
    "fanAlerts": ,
    "portAlerts": ,
    "cacheAlerts": ,
    "memoryAlerts": ,
    "processorAlerts":
  }
}
```

Parameter	Type	Description
totalComponentWiseHardwareAlerts	Integer	Total number of hardware alerts.
diskAlerts	Boolean	Whether there are any disk alerts.
powerSupplyAlerts	Boolean	Whether there are any power supply alerts.
batteryAlerts	Boolean	Whether there are any battery alerts.
fanAlerts	Boolean	Whether there are any fan alerts.
portAlerts	Boolean	Whether there are any port alerts.
cacheAlerts	Boolean	Whether there are any cache alerts.
memoryAlerts	Boolean	Whether there are any shared memory alerts.
processorAlerts	Boolean	Whether there are any processor alerts.

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

#### Example response

```
https://172.17.64.113/v1/monitoring/status/hardware
```

**Example response**

```
{
  "totalComponentWiseHardwareAlerts": 0,
  "hardwareComponents": {
    "diskAlerts": false,
    "powerSupplyAlerts": false,
    "batteryAlerts": false,
    "fanAlerts": false,
    "portAlerts": false,
    "cacheAlerts": false,
    "memoryAlerts": false,
    "processorAlerts": false
  }
}
```

## Listing resource-specific hardware alert details for all storage systems

You can display alerts for a specific hardware resource in all storage systems such as disk, power supply, battery, fan, port, cache, memory, and processor.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/monitoring/status/hardware/resourceType
```

Use one of the following hardware components as the *resourceType*.

- disk
- powerSupply
- battery
- fan
- port
- cache
- memory
- processor

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "alertInformationList": [
```

```

{
  "storageSerialNumber": "",
  "storageNickname": "",
  "refCode": "",
  "resourceType": "",
  "timestamp": "",
  "description": "",
  "alertLevel": ""
}
]
}

```

Parameter	Type	Description
storageSerialNumber	Integer	Storage system serial number.
storageNickname	String	Storage system name.
refCode	Integer	Alert reference code.
resourceType	String	Type of resource. Valid values: disk, fan, battery, cache, processor, powerSupply, port, or memory.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Getting the total number of hardware alerts for a storage system

You can display alerts for different hardware components, such as the power supply, battery, fan, port, cache, memory, and processors.

The alerts are received from the storage system. There is one alert per component type, for a maximum of eight.

The alert clearance process runs every 20 minutes for each storage system that includes components with errors. Alerts are only cleared when all components of a given type with errors return to the normal state. The exception is disks, each of which can have alerts cleared, even if other disks have errors. Alerts for ports and processors are cleared together, so alerts are cleared only when all ports and processors are normal.

For example, if there are five fans with alerts in one storage system, they are cleared only when each and every fan alert is cleared. Disk alerts are cleared for individual disks.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/storageSystemId/hardware
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```
{
  "totalComponentWiseHardwareAlerts": ,
  "hardwareComponents": {
    "diskAlerts": ,
    "powerSupplyAlerts": ,
    "batteryAlerts": ,
    "fanAlerts": ,
    "portAlerts": ,
    "cacheAlerts": ,
    "memoryAlerts": ,
    "processorAlerts":
  }
}
```



Parameter	Type	Description
totalComponentWiseHardwareAlerts	Integer	Total number of hardware components with alerts.
diskAlerts	boolean	Whether there are any disk alerts.
powerSupplyAlerts	boolean	Whether there are any power supply alerts.
batteryAlerts	boolean	Whether there are any battery alerts.
fanAlerts	boolean	Whether there are any fan alerts.
portAlerts	boolean	Whether there are any port alerts.
cacheAlerts	boolean	Whether there are any cache alerts.
memoryAlerts	boolean	Whether there are any shared memory alert.
processorAlerts	boolean	Whether there are any processor alerts

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Example request

```
https://172.17.64.113/v1/monitoring/status/410209/hardware/processor
```

**Example response**

```
{
  "totalComponentWiseHardwareAlerts": 0,
  "hardwareComponents": {
    "diskAlerts": false,
    "powerSupplyAlerts": false,
    "batteryAlerts": false,
    "fanAlerts": false,
    "portAlerts": false,
    "cacheAlerts": false,
    "memoryAlerts": false,
    "processorAlerts": false
  }
}
```

**Listing resource-specific hardware alert details for a storage system**

You can display the alert notification details for a particular resource for a specified storage system, such as disk, power supply, battery, fan, port, cache, memory, and processor.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/monitoring/status/storageSystemId/hardware/resourceType
```

Use the storage system ID as the *storageSystemId*.

Use one of the following resources as the *resourceType*.

- disk
- powerSupply
- battery
- fan
- port
- cache
- memory
- processor

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "alertInformationList": [
```

```

{
  "storageSerialNumber": "",
  "storageNickname": "",
  "refCode": "",
  "resourceType": "",
  "timestamp": "",
  "description": "",
  "alertLevel": ""
}
]
}

```

Parameter	Type	Description
storageSerialNumber	Integer	Storage system serial number.
storageNickname	String	Storage system name.
refCode	Integer	Alert reference code.
resourceType	String	Type of resource. Valid values: disk, fan, battery, cache, processor, powerSupply, port, or memory.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.113/v1/monitoring/status/410209/hardware/powerSupply
```

**Example response**

```
{
  "totalComponentWiseHardwareAlerts": 0,
  "hardwareComponents": {
    "diskAlerts": false,
    "powerSupplyAlerts": false,
    "batteryAlerts": false,
    "fanAlerts": false,
    "portAlerts": false,
    "cacheAlerts": false,
    "memoryAlerts": false,
    "processorAlerts": false
  }
}
```

## Listing disk alert information for all storage systems

You can display the disk alert information for all storage systems.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/monitoring/status/hardware/disk
```

**Request structure**

Not applicable.

**Response structure**

The response body structure is shown below:

```
{
  "diskAlertInformationList": [
    {
      "storageSerialNumber": "",
      "storageNickname": "",

```

```

    "refCode": "",
    "resourceType": "",
    "timestamp": "",
    "description": "",
    "alertLevel": "",
    "resourceLocation": "",
    "diskSpec": {
      "diskType": "",
      "speed": ,
      "capacity": {
        "bytes":
      }
    }
  }
]
}

```

Parameter	Type	Description
storageSerialNumber	Integer	Storage serial number.
storageNickname	String	Storage system name.
refCode	Integer	Alert reference code.
resourceType	String	Type of resource.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.
resourceId	String	Resource ID.
diskSpec	Object	Disk type, speed, and capacity of the disk.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Disk speed.
capacity	Integer	Disk capacity.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.113/v1/monitoring/status/hardware/disk
```

**Example response**

```
{
  "diskAlertInformationList": [
    {
      "storageSerialNumber": "111111",
      "storageNickname": "StorageSystem",
      "refCode": "DF5201",
      "resourceType": "Disk",
      "timestamp": "xxxxxx",
      "description": "xxxxxx",
      "alertLevel": "Critical",
      "resourceLocation": "01-01",
      "diskSpec": {
        "diskType": "SSD(RI)",
        "speed": 0,
        "capacity": {
          "bytes": 10000000
        }
      }
    },
    {
      "storageSerialNumber": "111111",
```

```

    "storageNickname": "StorageSystem",
    "refCode": "DF5201",
    "resourceType": "Disk",
    "timestamp": "xxxxxx",
    "description": "xxxxxx",
    "alertLevel": "Critical",
    "resourceLocation": "01-01",
    "diskSpec": {
      "diskType": "SSD",
      "speed": 0,
      "capacity": {
        "bytes": 10000000
      }
    }
  },
  ...
]
}

```

## Listing disk alert information for a storage system

You can display the disk alert information for the specified storage system.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/monitoring/status/storageSystemId/hardware/disk
```

Use the storage system ID as the *storageSystemId*.

### Request structure

Not applicable.

### Response structure

The response body structure is shown below:

```

{
  "diskAlertInformationList": [
    {
      "storageSerialNumber": "",
      "storageNickname": "",
      "refCode": "",
      "resourceType": "",
      "timestamp": "",
      "description": "",
      "alertLevel": "",
      "resourceLocation": "",
      "diskSpec": {
        "diskType": "",
        "speed": 0,

```

```

    "capacity": {
      "bytes": 0
    }
  }
}
]
}

```

Parameter	Type	Description
storageSerialNumber	String	Storage system serial number.
storageNickname	String	Storage system name.
refCode	String	Alert reference code.
resourceType	String	Type of resource.
timestamp	String	Timestamp of the alert.
description	String	Description of the alert.
alertLevel	String	Alert level: Warning or Critical.
resourceLocation	String	ID for the resource.
diskSpec	Object	Disk type, speed, and capacity of the disk.
diskType	String	Type of disk, such as FMD DC2, FMD, SAS, SSD, SSD(RI), SSD NVMe, SCM NVMe, or SSD(QLC).
speed	Integer	Disk speed.
capacity	Size	Disk capacity.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.



Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.113/v1/monitoring/status/hardware/disk
```

**Example response**

```
{
  "diskAlertInformationList": [
    {
      "storageSerialNumber": "111111",
      "storageNickname": "StorageSystem",
      "refCode": "DF5201",
      "resourceType": "Disk",
      "timestamp": "xxxxxx",
      "description": "xxxxxx",
      "alertLevel": "Critical",
      "resourceLocation": "01-01",
      "diskSpec": {
        "diskType": "SSD(RI)",
        "speed": 0,
        "capacity": {
          "bytes": 10000000
        }
      }
    },
    {
      "storageSerialNumber": "111111",
      "storageNickname": "StorageSystem",
      "refCode": "DF5201",
      "resourceType": "Disk",
      "timestamp": "xxxxxx",
      "description": "xxxxxx",
      "alertLevel": "Critical",
      "resourceLocation": "01-01",
      "diskSpec": {
        "diskType": "SSD",
        "speed": 0,
        "capacity": {
          "bytes": 10000000
        }
      }
    }
  ]
}
```

```

    }
  }
},
...
]
}
}

```

## SNMP resources

Request	Method	URI	Role
<a href="#">Listing SNMP managers (on page 818)</a>	GET	/v1/snmp-managers	Storage administrator System administrator Security administrator Monitoring
<a href="#">Adding SNMP managers (on page 820)</a>	POST	/v1/snmp-managers	System administrator
<a href="#">Updating an SNMP manager (on page 824)</a>	POST	/v1/snmp-managers/ <i>snmpMgrName</i>	System administrator
<a href="#">Deleting an SNMP manager (on page 827)</a>	DELETE	/v1/snmp-managers/ <i>snmpMgrName</i>	System administrator

## Listing SNMP managers

You can display a list of SNMP managers.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/snmp-managers
```

### Request structure

Not applicable.

## Response structure

The response body structure is shown below:

```
{
  "snmpManagerInformationList": [
    {
      "name": "",
      "ipAddress": "",
      "username": "",
      "privacyProtocol": "",
      "privacyPassword": ,
      "authProtocol": "",
      "authPassword": ,
      "port":
    }
  ]
}
```

Parameter	Type	Description
name	String	The name of the SNMP manager.
ipAddress	String	IP address of the resource.
username	String	User name of the SNMP manager.
privacyProtocol	String	Privacy protocol for the SNMP manager. Valid values: DES, TRIPLE_DES, AES_128, OR NO_PRIV.
privacyPassword	String	Privacy password for the SNMP manager.
authProtocol	String	The SNMP authentication protocol: MD5, SHA, or NO_AUTH.
authPassword	String	Authentication password.
port	String	The ethernet port to which the IP address for the SNMP manager is assigned.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Example request**

```
https://172.17.64.111/v1/snmp-managers
```

**Example response**

```
{
  "snmpManagerInformationList": [
    {
      "name": "snmp-manager-1",
      "ipAddress": "172.17.91.22",
      "username": "kh",
      "privacyProtocol": "DES",
      "privacyPassword": null,
      "authProtocol": "MD5",
      "authPassword": null,
      "port": 162
    }
  ]
}
```

**Adding SNMP managers**

You can add SNMP managers so they can receive SNMP traps related to the monitored components of the registered storage system.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/snmp-managers
```

**Request structure**

The request body structure is shown below:

```
{
  "snmpManagers": [
    {
      "name": "",
      "username": "",
      "ipAddress": "",
      "authProtocol": "",
      "authPassword": "",
      "privacyProtocol": "",
      "privacyPassword": "",
      "port": ""
    }
  ]
}
```

Parameter	Required	Type	Description
name	No	String	The name of the SNMP manager.
ipAddress	No	String	IP address of the resource.
username	No	String	User name of the SNMP manager.
privacyProtocol	No	String	Privacy protocol for the SNMP manager. Valid values: DES, TRIPLE_DES, AES_128, or NO_PRIV.
privacyPassword	No	String	Privacy password for the SNMP manager.
authProtocol	No	String	The SNMP authentication protocol: MD5, SHA, or NO_AUTH.
authPassword	No	String	Authentication password.
port	No	Integer	The SNMP port number in the range between 0 to 65535.

## Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
  ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.

Parameter	Type	Description
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the href parameter. If the value is _self, it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to true. If a user generates a job, the system sets it to false.

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Updating an SNMP manager

You can update information for an SNMP manager so it receives SNMP traps related to the monitored components of the registered storage system.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/snmp-managers/snmpMgrName
```

Use the SNMP manager name as the *snmpMgrName*.

### Request structure

The request body structure is shown below:

```
{
  "username": "",
  "ipAddress": "",
  "authProtocol": "",
  "authPassword": "",
  "privacyProtocol": "",
  "privacyPassword": "",
  "port": ""
}
```



Parameter	Required	Type	Description
ipAddress	No	String	IP address of the resource.
username	No	String	User name of the SNMP manager.
privacyProtocol	No	String	Privacy protocol for the SNMP manager. Valid values: DES, TRIPLE_DES, AES_128, or NO_PRIV.
privacyPassword	No	String	Privacy password for the SNMP manager.
authProtocol	No	String	The SNMP authentication protocol: MD5, SHA, or NO_AUTH.
authPassword	No	String	Authentication password.
port	No	Integer	The SNMP port number in the range between 0 to 65535.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ]
}
```

```

],
"tags":
[
],
"isSystem":
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.

Parameter	Type	Description
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

### Return codes

Status code	HTTP name	Description
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Deleting an SNMP manager

You can delete an SNMP manager.

### HTTP request syntax (URI)

```
DELETE https://ipAddress/v1/snmp-managers/snmpMgrName
```

Use the SNMP manager name as the *snmpMgrName*.

**Request structure**

Not applicable.

**Response structure**

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
    {
      "text": "",
      "messageCode": "",
      "parameters":
        {
        }
    },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
    [
    ],
  "links":
    [
      {
        "rel": "_self",
        "href": "/v1/jobs/jobId"
      }
    ],
  "tags":
    [
    ],
  "isSystem":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.

Parameter	Type	Description
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

**Return codes**

Status code	HTTP name	Description
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

## Chapter 9: System administration resources

You can use Ops Center Administrator APIs to perform system administration operations.

### Account domain resources

Request	Method	URI	Role
<a href="#">Listing account domains (on page 831)</a>	GET	/v1/security/account-domains	Security administrator
<a href="#">Getting an account domain (on page 833)</a>	GET	/v1/security/account-domains/ <i>domainId</i>	Security administrator
<a href="#">Adding an account domain (on page 835)</a>	POST	/v1/security/account-domains	Security administrator
<a href="#">Updating an account domain (on page 838)</a>	POST	/v1/security/account-domains/ <i>domainId</i>	Security administrator
<a href="#">Deleting an account domain (on page 841)</a>	DELETE	/v1/security/account-domains/ <i>domainId</i>	Security administrator

### Listing account domains

You can display account domains that have been added to Ops Center Administrator.

#### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/account-domains
```

#### Request structure

Not applicable.

#### Response structure

```
{
  "accountDomains": [
    {
      "id": "",
      "domain": "",

```

```

    "username": "",
    "type": ""
  }
]
}

```

Parameter	Type	Description
id	String	The ID that is assigned to the domain.
domain	String	The name or address of the domain.
username	String	The user name that is being used to access the domain.
type	String	The domain type <code>LOCAL</code> or <code>ACTIVE DIRECTORY</code> .

#### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.



Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Example request**

```
GET https://172.17.64.116/v1/security/account-domains
```

**Example response**

```
{
  "accountDomains": [
    {
      "id": "57503d78-3294-44c6-8c8a-08edd38a08be",
      "domain": "LOCAL",
      "username": "",
      "type": "LOCAL"
    }
  ]
}
```

## Getting an account domain

You can display information of a specific account domain.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/security/account-domains/domainId
```

**Request structure**

Not applicable.

**Response structure**

```
{
  "id": "",
  "domain": "",
  "username": "",
  "type": ""
}
```

Parameter	Type	Description
id	String	The ID that is assigned to the domain.
domain	String	The name or address of the domain.
username	String	The user name that is being used to access the domain.
type	String	The domain type (LOCAL or ACTIVE DIRECTORY).

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Example request**

```
GET https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd
```

**Example response**

```
{
  "id": "20ee96fe-fb69-4f68-994f-a2fbffcea9fd",
  "domain": "example.com",
  "username": "jdoe",
  "type": "ACTIVE_DIRECTORY"
}
```

## Adding an account domain

You can add an account domain to Ops Center Administrator.

**HTTP request syntax (URI)**

```
POST https://ipAddress/v1/security/account-domains
```

**Request structure**

```
{
  "domain": "",
  "username": "",
  "password": ""
}
```

Parameter	Required	Type	Description
domain	Yes	String	The name or address of the domain.
username	Yes	String	The user name that will be used to access the domain.
password	Yes	String	The password that will be used to access the domain.

**Response structure**

```
{
  "jobId": "",
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
}
```

```

"parentJobId": ,
"reports": [],
"tags": [],
"isSystem":,
"title":
{
  "text": "",
  "messageCode": "",
  "parameters": { }
},
"links": [
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
}

```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.
links	List	Link information of the job.
text	String	Title of the task that is in progress.

Parameter	Type	Description
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

Status code	HTTP name	Description
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
POST https://172.17.64.116/v1/security/account-domains
{
  "domain": "example.com",
  "username": "jdoe",
  "password": "test123"
}
```

## Updating an account domain

You can update the credentials that are used to access an account domain that has been added to You can add an account domain to Ops Center Administrator.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/security/account-domains/domainId
```

Use the domain ID as the *domainId*.

### Request structure

```
{
  "username": "jwei",
  "password": "newPassword"
}
```

Parameter	Required	Type	Description
username	Yes	String	The user name that will be used to access the domain.
password	Yes	String	The password that will be used to access the domain.

### Response structure

```
{
  "jobId": "",

```

```

"user": "",
"status": "",
"startDate": ,
"endDate": ,
"parentJobId": ,
"reports": [],
"tags": [],
"isSystem":,
"title":
{
  "text": "",
  "messageCode": "",
  "parameters": { }
},
"links": [
{
  "rel": "_self",
  "href": "/v1/jobs/jobId"
}
],
}

```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.

Parameter	Type	Description
links	List	Link information of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.



Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
POST https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd
{
  "username": "jwei",
  "password": "newPassword"
}
```

## Deleting an account domain

You can remove an account domain from Ops Center Administrator.

### HTTP request syntax (URI)

```
DELETE https://ipAddress/v1/security/account-domains/domainId
```

Use the domain ID as the *domainId*.

### Request structure

Not applicable.

### Response structure

```
{
  "jobId": "",
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "tags": [],
  "isSystem":,
  "title":
  {
```

```

    "text": "",
    "messageCode": "",
    "parameters": { }
  },
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
}

```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.
links	List	Link information of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.

Parameter	Type	Description
rel	String	Indicates the type of link for the href parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Example request**

```
DELETE https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd
```

## User management resources

Request	Method	URI	Role
<a href="#">Listing user groups (on page 844)</a>	GET	/v1/security/account-domains/ <i>domainId</i> /groups	Security administrator
<a href="#">Listing group mappings (on page 847)</a>	GET	/v1/security/account-domains/ <i>domainId</i> /group-mappings	Security administrator
<a href="#">Getting a group mapping (on page 849)</a>	GET	/v1/security/account-domains/ <i>domainId</i> /group-mappings/ <i>mappingId</i>	Security administrator
<a href="#">Creating role mappings (on page 851)</a>	POST	/v1/security/account-domains/ <i>domainId</i> /group-mappings	Security administrator
<a href="#">Deleting role mappings (on page 854)</a>	DELETE	/v1/security/account-domains/ <i>domainId</i> /group-mappings/ <i>mappingId</i>	Security administrator
<a href="#">Listing users (on page 856)</a>	GET	/v1/security/account-domains/ <i>domainId</i> /users	Security administrator
<a href="#">Getting a user (on page 858)</a>	GET	/v1/security/account-domains/ <i>domainId</i> /users/ <i>userId</i>	Security administrator
<a href="#">Updating a user (on page 860)</a>	POST	/v1/security/account-domains/ <i>domainId</i> /users/ <i>userId</i>	Security administrator

## Listing user groups

You can display a list of all the user groups in the account domain.

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/security/account-domains/domainId/groups
```

Use the account domain ID as the *domainId*.

**Request structure**

Not applicable.

Parameter	Required	Type	Description
filter	Yes	String	Standard parameter used to build a query. As an example, this can be set to a letter to filter by group names containing that letter.

**Response structure**

```
{
  "groups": [
    ""
  ]
}
```

Parameter	Type	Description
groups	String	Groups in the account domain.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.

Status code	HTTP name	Description
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
GET https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd/groups?filter=r
```

### Example response

```
{
  "groups": [
    "RAINIER_SECURITY@GSELAB.EXAMPLE.COM",
    "RAINIER_MONITORING@GSELAB.EXAMPLE.COM",
    "Enterprise Admins@GSELAB.EXAMPLE.COM",
    "Read-only Domain Controllers@GSELAB.EXAMPLE.COM",
    "Domain Computers@GSELAB.EXAMPLE.COM",
    "Domain Users@GSELAB.EXAMPLE.COM",
    "RAINIER_ADMIN@GSELAB.EXAMPLE.COM",
    "Domain Controllers@GSELAB.EXAMPLE.COM",
    "Enterprise Read-only Domain Controllers@GSELAB.EXAMPLE.COM",
    "Cloneable Domain Controllers@GSELAB.EXAMPLE.COM",
    "RAINIER_TENANT_ENG@GSELAB.EXAMPLE.COM",
    "DnsUpdateProxy@GSELAB.EXAMPLE.COM",
    "Group Policy Creator Owners@GSELAB.EXAMPLE.COM",
```

```

    "Protected Users@GSELAB.EXAMPLE.COM"
  ]
}

```

## Listing group mappings

You can display a list of all the user group mappings in Ops Center Administrator.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/account-domains/domainId/group-mappings
```

Use the account domain ID as the *domainId*.

### Request structure

Not applicable.

### Response structure

```

{
  "mappings": [
    {
      "id": "44c08be3-ba36-49eb-a104-48911a2815cb",
      "accountDomainId": "",
      "groupName": "",
      "userRole": ""
    }
  ]
}

```

Parameter	Type	Description
id	Integer	ID
accountDomainId	Integer	ID of the domain.
groupName	String	Name of the domain.
userRole	String	Role to be assigned to the user group. Values include the SystemAdministrator, StorageAdministrator, SecurityAdministrator, and MonitoringUser.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Example request**

```
GET https://172.17.64.116/v1/security/account-domains/44c08be3-ba36-49eb-a104-48911a2815cb/group-mappings
```

**Example response**

```
{
  "mappings": [
    {
      "id": "44c08be3-ba36-49eb-a104-48911a2815cb",
      "accountDomainId": "20ee96fe-fb69-4f68-994f-a2fbffcea9fd",
      "groupName": "admin",
      "userRole": "SecurityAdministrator"
    }
  ]
}
```



```

    }
  ]
}

```

## Getting a group mapping

You can display role mappings in a particular user group.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/account-domains/domainId/group-mappings/mappingId
```

Use the account domain ID as the *domainId*.

Use the group mapping ID for the *mappingId*.

### Request structure

Not applicable.

### Response structure

```

{
  "id": "",
  "accountDomainId": "",
  "groupName": "",
  "userRole": ""
}

```

Parameter	Type	Description
id	String	ID of the group mapping.
accountDomainId	String	ID of the domain.
groupName	String	Name of the domain.
userRole	String	Role to be assigned to the user group. Values include the SystemAdministrator, StorageAdministrator, SecurityAdministrator, and MonitoringUser.

### Return codes

Status code	HTTP name	Description
200	OK	Success.

Status code	HTTP name	Description
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
GET https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd/group-mappings/44c08be3-ba36-49eb-a104-48911a2815cb
```

### Example response

```
{
  "id": "44c08be3-ba36-49eb-a104-48911a2815cb",
  "accountDomainId": "20ee96fe-fb69-4f68-994f-a2fbffcea9fd",
  "groupName": "admin",
  "userRole": "SecurityAdministrator"
}
```

## Creating role mappings

You can create a user group and assign roles to the user group.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/security/account-domains/domainId/group-mappings
```

Use the account domain ID as the *domainId*.

### Request structure

```
{
  "groupName": "",
  "userRole": ""
}
```

Parameter	Required	Type	Description
groupName	Yes	String	Name of the group.
userRole	Yes	String	Role to be assigned to the user group. Values include the SystemAdministrator, StorageAdministrator, SecurityAdministrator, and MonitoringUser.

### Response structure

```
{
  "jobId": "",
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "tags": [],
  "isSystem":,
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters": { }
  },
  "links": [
    {
      "rel": "_self",
```

```

    "href": "/v1/jobs/jobId"
  }
  ],
}

```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.
links	List	Link information of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

**Example request**

```
POST https://ipAddress/v1/security/account-domains/20ee96fe-fb69-4f68-994f-
a2fbffcea9fd/group-mappings
{
  "groupName": "admin",
  "userRole": "SecurityAdministrator"
}
```

**Deleting role mappings**

You can remove a role that was assigned to a user group.

**HTTP request syntax (URI)**

```
DELETE https://ipAddress/v1/security/account-domains/domainId/group-mappings/mappingId
```

Use the domain ID as the *domainId*.

Use the group mapping ID for the *mappingId*.

**Request structure**

Not applicable.

**Response structure**

```
{
  "jobId": "",
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "tags": [],
  "isSystem":,
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters": { }
  },
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
}
```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.
links	List	Link information of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

### Return codes

Status code	HTTP name	Description
200	OK	Success.

Status code	HTTP name	Description
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
DELETE https://172.17.64.116/v1/security/account-domains/57503d78-3294-44c6-8c8a-08edd38a08be/group-mappings/44c08be3-ba36-49eb-a104-48911a2815cb
```

## Listing users

You can display a list of users in the local domain.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/account-domains/domainId/users
```



Use the account domain ID as the *domainId*.

### Request structure

Not applicable.

### Response structure

```
{
  "users": [
    {
      "id": "",
      "accountDomainId": "",
      "loginName": ""
    }
  ]
}
```

Parameter	Type	Description
id	String	ID of the user in the account domain.
accountDomainId	String	ID of the account domain
loginName	String	Login name of the user.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
GET https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd/users
```

### Example response

```
{
  "users": [
    {
      "id": "b5d15f7f-3e2e-43c1-9734-c447cfb260f7",
      "accountDomainId": "20ee96fe-fb69-4f68-994f-a2fbffcea9fd",
      "loginName": "jwei"
    }
  ]
}
```

## Getting a user

You can get details on a specific user in the domain.

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/security/account-domains/domainId/users/userId
```

Use the account domain ID as the *domainId*.

Use the user ID as the *userId*.

**Request structure**

Not applicable.

**Response structure**

```
{
  "id": "",
  "accountDomainId": "",
  "loginName": ""
}
```

Parameter	Type	Description
id	String	ID of the user in the account domain.
accountDomainId	String	ID of the account domain
loginName	String	Login name of the user.

**Return codes**

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
GET https://172.17.64.116/v1/security/account-domains/20ee96fe-fb69-4f68-994f-a2fbffcea9fd/users/b5d15f7f-3e2e-43c1-9734-c447cfb260f7
```

### Example response

```
{
  "id": "b5d15f7f-3e2e-43c1-9734-c447cfb260f7",
  "accountDomainId": "20ee96fe-fb69-4f68-994f-a2fbffcea9fd",
  "loginName": "jwei"
}
```

## Updating a user

You can change the password of a user in the local domain.

### HTTP request syntax (URI)

```
POST https://ipAddress/v1/security/account-domains/domainId/users/userId
```

Use the account domain ID as the *domainId*.

Use the User ID as the *userId*.

### Request structure

```
{
  "password": ""
}
```

Parameter	Required	Type	Description
password	Yes	String	The user password.

### Response structure

```
{
  "jobId": "",
  "user": "",
  "status": "",
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports": [],
  "tags": [],
  "isSystem":,
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters": { }
  },
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
}
```

Parameter	Type	Description
jobId	String	ID of the job.
user	String	User who initiated the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.

Parameter	Type	Description
reports	List	Messages associated with this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether or not a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
title	Object	Title of the job.
links	List	Link information of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*.  *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").

Status code	HTTP name	Description
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Example request

```
POST https://ipAddress/v1/security/account-domains/20ee96fe-fb69-4f68-994f-
a2fbffcea9fd/users/b5d15f7f-3e2e-43c1-9734-c447cfb260f7
{
  "password": "newpassword"
}
```

## Getting a job

You can display information about a task that was submitted. This returns the information about who submitted the task, the time that the task was submitted, and the action taken by Ops Center Administrator.

You must have one of the following roles:

- System administrator
- Storage administrator
- Security administrator
- Monitoring

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/jobs/jobId
```

Use the ID of the job as the *jobId*.

### Request structure

Not applicable.

### Response structure

The response body structure is as follows:

```
{
  "jobId": "",
  "title":
  {
    "text": "",
    "messageCode": "",
    "parameters":
    {
    }
  },
  "user": "",
  "status": "",
  "createdDate":,
  "scheduledDate":,
  "startDate": ,
  "endDate": ,
  "parentJobId": ,
  "reports":
  [
  ],
  "links":
  [
    {
      "rel": "_self",
      "href": "/v1/jobs/jobId"
    }
  ],
  "tags":
  [
```



```

],
"isSystem":,
"resources": [
  {
    "type": "",
    "ids": [],
    "childResources": [
      {
        "type": "",
        "ids": [],
        "childResources": [
          ...
        ]
      },
      ...
    ]
  },
  ...
]
},
...
]
}

```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: IN_PROGRESS, SUCCESS, SUCCESS_WITH_ERRORS, or FAILED.
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).

Parameter	Type	Description
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .
resources	List	List of the resources operated in the job.
type	Enum	Type of the resources.
ids	List	List of IDs of the resources.
childResources	List	List of the child resources belonging to the resource.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.
502	Bad Gateway	The service is starting. Try your request again after the service has started.

Status code	HTTP name	Description
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Request example

```
https://172.17.64.116/v1/ffa07b8a-e35d-4dc9-b054-232c6e4a9f51
```

### Response example

```
{
  "jobId": "ffa07b8a-e35d-4dc9-b054-232c6e4a9f51",
  "title": {
    "text": "Attach volumes to server.",
    "messageCode": "AttachVolumesToServerJobTitleMessage",
    "parameters": {}
  },
  "user": "sysadmin",
  "status": "SUCCESS",
  "startDate": 1456869156565,
  "endDate": 1456869229109,
  "parentJobId": "9d66fc27-473f-4d8b-8998-635da11f0260",
  "reports": [
    {
      "reportMessage": {
        "text": "Storage System \"410033\". Attaching volumes Lun{volumeId=474, lun=1} to server 1.",
        "messageCode": "AttachVolumesToServerPreStepMessage",
        "parameters": {
          "storageSystemId": "410033",
          "volumes": "Lun{volumeId=474, lun=1}",
          "serverId": 1
        }
      }
    },
    {
      "severity": "INFORMATION",
      "creationDate": 1456869156627
    }
  ],
  "links": [
    {
      "rel": "_self",
      "href": "/v1/jobs/ffa07b8a-e35d-4dc9-b054-232c6e4a9f51"
    }
  ],
  "tags": [],
  "isSystem": false,
  "resources": [
```

```

{
  "type": "STORAGE_SYSTEM",
  "ids": [
    "20055",
  ],
  "childResources": [
    {
      "type": "VOLUME",
      "ids": [
        "100",
        "101"
      ],
    }
  ],
},
{
  "type": "SERVER",
  "ids": [
    "2"
  ],
}
]
}

```

## Listing jobs

You can display information about submitted tasks. The information includes, who submitted the task, the time that the task was submitted, and the action taken by Ops Center Administrator. In a paginated response, if more than 100 jobs are in the system, this API call does not return all of the jobs. At the bottom of the returned response is a link to another GET call you can make to retrieve the next page of jobs. Copy the href link that includes the next token and paste it in your Ops Center Administrator browser. Perform this step if you want to retrieve all the jobs in the system.

You must have one of the following roles:

- System administrator
- Storage administrator
- Security administrator
- Monitoring

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/jobs
```

### Request structure

Not applicable.

**Response structure**

```

{
  "jobs": [
    {
      "jobId": "",
      "title": {
        "text": "",
        "messageCode": "",
        "parameters": {
        }
      },
      "user": "",
      "status": "",
      "createdDate": ,
      "scheduledDate": ,
      "startDate": ,
      "endDate": ,
      "parentJobId": ,
      "reports": [
      ],
      "links": [
        {
          "rel": "_self",
          "href": "/v1/jobs/jobId"
        }
      ],
      "tags": [
      ],
      "isSystem": ,
      "resources": [
        {
          "type": "",
          "ids": [
          ],
          "childResources": [
            {
              "type": "",
              "ids": [
              ],
              "childResources": [
              ]
            }
          ]
        },
        ...
      ]
    },
    ...
  ],
  "total": ,
  "links": [],

```

```
"nextToken":
}
```

Parameter	Type	Description
jobId	String	ID of the job.
text	String	Title of the task that is in progress.
messageCode	String	ID of the message.
parameters	Object	List of parameters and the values, as captured in the job message.
user	String	User who made the request.
status	String	Status of the job: <code>IN_PROGRESS</code> , <code>SUCCESS</code> , <code>SUCCESS_WITH_ERRORS</code> , or <code>FAILED</code> .
createdDate	Long	The date and time the job was created (in Epoch time format).
scheduledDate	Long	Scheduled date and time the job starts to run (in Epoch time format). For the job not scheduled to run on the specified time, this parameter is null.
startDate	Long	Start date and time of the job (in Epoch time format).
endDate	Long	End date and time of the job (in Epoch time format).
parentJobId	String	ID of the job that spawned this job. If there is no parent job, this value is null.
reports	List	Messages associated with this job.
rel	String	Indicates the type of link for the <code>href</code> parameter. If the value is <code>_self</code> , it identifies a resource equivalent to the containing element.
href	String	URL of this job.
tags	Set	Any tags applied to this job.
isSystem	Boolean	Whether a system or a user has created a job. If the job is generated by a system, the system automatically sets it to <code>true</code> . If a user generates a job, the system sets it to <code>false</code> .

Parameter	Type	Description
resources	List	List of the resources operated in the job.
type	Enum	Type of the resources.
ids	List	List of Ids of the resources.
childResources	List	List of the child resources belonging to the resource.
total	Long	The total number of resources.
nextToken	String	The API will return up to 100 resources with one call. <code>nextToken</code> is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token.

### Return codes

Status code	HTTP name	Description
200	OK	Success.
201	Created	The server has started the operation.
202	Accepted	The request has been accepted for processing, but the processing has not been completed.
204	No content	The request was successful, but the response does not exist.
400	Bad request	The required HTTP header was not specified or the format of the specified HTTP header was invalid*. *: The specified HTTP header is not handled correctly when the header contains a carriage return("\r").
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
404	Not found	The specified resource ID is not valid or the resource does not exist.

Status code	HTTP name	Description
404	Not found	The specified storage system ID is not valid or the storage system does not exist.
409	Conflict	The specified resource type does not match the existing resource type.
412	Precondition failed	The server does not meet one of the preconditions that the requester put in the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.
504	Gateway timeout	The request timed out waiting for a response. The Ops Center Administrator is not able to connect to the node.

### Request example

```
https: //172.17.64.116/v1/jobs
```

### Response example

```
{
  "jobs": [
    {
      "jobId": "ffa07b8a-e35d-4dc9-b054-232c6e4a9f51",
      "title": {
        "text": "Attach volumes to server.",
        "messageCode": "AttachVolumesToServerJobTitleMessage",
        "parameters": {}
      },
      "user": "sysadmin",
      "status": "SUCCESS",
      "startDate": 1456869156565,
      "endDate": 1456869229109,
      "parentJobId": "9d66fc27-473f-4d8b-8998-635da11f0260",
      "reports": [
        {
          "reportMessage": {
            "text": "Storage System \"410033\". Attaching volumes Lun{volumeId=474, lun=1} to server 1.",

```



```

        "messageCode": "AttachVolumesToServerPreStepMessage",
        "parameters": {
            "storageSystemId": "410033",
            "volumes": "Lun{volumeId=474, lun=1}",
            "serverId": 1
        }
    },
    "severity": "INFORMATION",
    "creationDate": 1456869156627
},
]
"links": [
    {
        "rel": "_self",
        "href": "/v1/jobs/ffa07b8a-e35d-4dc9-b054-232c6e4a9f51"
    }
],
"tags": [],
"isSystem": false,
"resources": [
    {
        "type": "STORAGE_SYSTEM",
        "ids": [
            "20055",
        ],
        "childResources": [
            {
                "type": "VOLUME",
                "ids": [
                    "100",
                    "101"
                ],
            },
        ],
    },
    {
        "type": "SERVER",
        "ids": [
            "2"
        ],
    },
],
...
],
"total": 66,
"links": [
    {
        "rel": "_self",
        "href": "/v1/jobs"
    }
]

```

```

],
  "nextToken": null
}

```

## Listing storage system task information

You can display information about submitted storage system tasks. The information includes:

- Who submitted the task
- The time that the task was submitted
- The action taken by Ops Center Administrator



**Note:** For storage system configurations without SVP, an empty list is returned.

You must have one of the following roles:

- System administrator
- Storage administrator
- Security administrator
- Monitoring

### HTTP request syntax (URI)

```
GET https://ipAddress/v1/storage-systems/storageSystemId/system-tasks
```

### Request structure

Not applicable.

### Response structure

```

{
  "resources": [
    {
      "storageSystemId": "",
      "storageSystemName": "",
      "taskId": "",
      "taskType": "",
      "title": "",
      "user": "",
      "status": "",
      "startDate": ,
      "endDate":
    },
  ],
  "total": ,
}

```

```
"nextToken":
}
```

Parameter	Type	Description
storageSystemId	String	The storage system ID (serial number).
storageSystemName	String	The storage system name.
taskId	String	The task ID.
taskType	String	The task type.
title	String	The task title.
user	String	The user who initiated the request.
status	String	The task status. Possible values are: IN_PROGRESS, SUCCESS, WAITING, or FAILED.
startDate	Long	The job's start date and time in Epoch time format.
endDate	Long	The job's end date and time in Epoch time format.
total	Long	The total number of resources.
nextToken	String	The API will return up to 100 resources with one call. <code>nextToken</code> is used for pagination when there are more than 100 resources in the system. The token is included in the list of resources. To retrieve the next list of resources, append a question mark (?) and "nextToken= ", and then the token.

### Return codes

Status code	HTTP name	Description
200	OK	Success
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.

Status code	HTTP name	Description
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

### Response example

```
{
  "resources": [
    {
      "storageSystemId": "12345",
      "storageSystemName": "Storage_System_12345",
      "taskId":
"d5458c080435c3f88f702a36675dc5ae45ea9262340f6cdbae51c7d597b7c7aa",
      "taskType": "Delete LDEVs",
      "title": "200128-DeleteLDEVs",
      "user": "system-user"
      "status": "FAILED",
      "startDate": 1580187419899,
      "endDate": 1580187539545
    }
  ],
  "total": 1,
  "nextToken": null
}
```

## Getting a storage system task information summary

You can display summary information about submitted storage system tasks.



**Note:** For storage system configurations without SVP, an empty list is returned.

You must have one of the following roles:

- System administrator
- Storage administrator
- Security administrator
- Monitoring

**HTTP request syntax (URI)**

```
GET https://ipAddress/v1/storage-systems/system-tasks-summary
```

**Request structure**

Not applicable.

**Response structure**

```
{
  "taskCountByStatus": [
    {
      "status": "",
      "count":
    },
  ]
}
```

Parameter	Type	Description
taskCountByStatus	List	The total number of tasks by status.
status	String	The task status. Possible values are: IN_PROGRESS, SUCCESS, WAITING, or FAILED.
count	Long	The number of tasks of a given status.

**Return codes**

Status code	HTTP name	Description
200	OK	Success
401	Unauthorized	The operation is not authorized.
403	Forbidden	The server failed to authenticate the request.
502	Bad Gateway	The service is starting. Try your request again after the service has started.
503	Service unavailable	The server currently cannot receive requests. Try your request again.

**Response example**

```
{
  "taskCountByStatus": [
    {
      "status": "SUCCESS",
      "count": 10
    },
    {
      "status": "FAILED",
      "count": 2
    },
    {
      "status": "IN_PROGRESS",
      "count": 3
    },
    {
      "status": "WAITING",
      "count": 1
    }
  ]
}
```

---

## Appendix A: Supported REST APIs list for Virtual Storage Platform One SDS Block

Administrator can onboard Virtual Storage Platform One SDS Block and launch VSP One SDS Block Administrator as start point. This module describes the supported REST APIs for Virtual Storage Platform One SDS Block.

### Supported REST APIs list for Virtual Storage Platform One SDS Block

Management resources	Management	Operation
Block storage management resources	Storage system management	Listing storage systems
Block storage management resources	Storage system management	Getting a storage system
Block storage management resources	Storage system management	Getting storage systems summary
Block storage management resources	Storage system management	Adding a storage system
Block storage management resources	Storage system management	Deleting a storage system
Block storage management resources	Storage system management	Refreshing a storage system
Block storage management resources	Tier management resources	Listing tiers
Block storage management resources	Tier management resources	Updating a tier
Data protection management resources	Getting a data protection summary for all storage systems	Getting a data protection summary for all storage systems

Management resources	Management	Operation
Data protection management resources	Getting a data protection summary for a storage system	Getting a data protection summary for a storage system
Monitoring resources	Capacity monitoring resources	Getting a summary of data reduction savings and capacity efficiency
Monitoring resources	Capacity monitoring resources	Getting a data reduction savings and capacity efficiency summary for a storage system



## Hitachi Vantara

Corporate Headquarters  
2535 Augustine Drive  
Santa Clara, CA 95054 USA



[HitachiVantara.com/contact](https://HitachiVantara.com/contact)