

# Discrete Mathematics

## Graphs

H. Turgut Uyar Ayşegül Gençata Yayımlı Emre Harmancı

2001-2013

1 / 160

## License



©2001-2013 T. Uyar, A. Yayımlı, E. Harmancı

You are free:

- ▶ to Share – to copy, distribute and transmit the work
- ▶ to Remix – to adapt the work

Under the following conditions:

- ▶ Attribution – You must attribute the work in the manner specified by the author or licensor (but not in any way that suggests that they endorse you or your use of the work).
- ▶ Noncommercial – You may not use this work for commercial purposes.
- ▶ Share Alike – If you alter, transform, or build upon this work, you may distribute the resulting work only under the same or similar license to this one.

Legal code (the full license):

<http://creativecommons.org/licenses/by-nc-sa/3.0/>

2 / 160

## Topics

### Graphs

Introduction  
Connectivity  
Planar Graphs  
Searching Graphs

### Trees

Introduction  
Rooted Trees  
Binary Trees  
Decision Trees

### Weighted Graphs

Introduction  
Shortest Path  
Minimum Spanning Tree

3 / 160

## Graphs

### Definition


**graph:**  $G = (V, E)$

- ▶  $V$ : **node** (or **vertex**) set
- ▶  $E \subseteq V \times V$ : **edge** set
- ▶ if  $e = (v_1, v_2) \in E$ :
  - ▶  $v_1$  and  $v_2$  are *endnodes* of  $e$
  - ▶  $e$  is *incident* to  $v_1$  and  $v_2$
  - ▶  $v_1$  and  $v_2$  are *adjacent*
- ▶ node with no incident edge: *isolated node*

4 / 160

## Graph Example

### Example



$$\begin{aligned} V &= \{a, b, c, d, e, f\} \\ E &= \{(a, b), (a, c), \\ &\quad (a, d), (a, e), \\ &\quad (b, c), (b, e), \\ &\quad (c, e), (d, e), \\ &\quad (e, f)\} \end{aligned}$$

5 / 160

## Directed Graphs

### Definition


**directed graph** (or *digraph*):  $D = (V, A)$

- ▶  $A \subseteq V \times V$ : **arc** set
- ▶ *origin* and *terminating* nodes

6 / 160

## Directed Graph Example

Example



7 / 160

## Multigraphs

Definition

**parallel edges:** edges between the same pair of nodes

**loop:** an edge starting and ending in the same node


**plain graph:** a graph without any loops or parallel edges

**multigraph:** a graph which is not plain

8 / 160

## Multigraph Example

Example



- ▶ parallel edges: (a, b)
- ▶ loop: (e, e)

9 / 160

## Subgraph

Definition

$G' = (V', E')$  is a **subgraph** of  $G = (V, E)$ :

- ▶  $V' \subseteq V$
- ▶  $E' \subseteq E$
- ▶  $\forall (v_1, v_2) \in E' \quad v_1, v_2 \in V'$

10 / 160


## Representation

- ▶ **incidence matrix:**
  - ▶ rows represent nodes, columns represent edges
  - ▶ cell: 1 if the edge is incident to the node, 0 otherwise
- ▶ **adjacency matrix:**
  - ▶ rows and columns represent nodes
  - ▶ cells represent the number of edges between the nodes

11 / 160

## Incidence Matrix Example

Example




	$e_1$	$e_2$	$e_3$	$e_4$	$e_5$	$e_6$	$e_7$	$e_8$
$v_1$	1	1	1	0	1	0	0	0
$v_2$	1	0	0	1	0	0	0	0
$v_3$	0	0	1	1	0	0	1	1
$v_4$	0	0	0	0	1	1	0	1
$v_5$	0	1	0	0	0	1	1	0

12 / 160

## Adjacency Matrix Example

### Example




	$v_1$	$v_2$	$v_3$	$v_4$	$v_5$
$v_1$	0	1	1	1	1
$v_2$	1	0	1	0	0
$v_3$	1	1	0	1	1
$v_4$	1	0	1	0	1
$v_5$	1	0	1	1	0

13 / 160

## Adjacency Matrix Example

### Example



	$a$	$b$	$c$	$d$
$a$	0	0	0	1
$b$	2	1	1	0
$c$	0	0	0	0
$d$	0	1	1	0

14 / 160

## Degree

### Definition

**degree:** number of edges incident to the node

### Theorem


let  $d_i$  be the degree of node  $v_i$

$$|E| = \frac{\sum_i d_i}{2}$$

15 / 160

## Degree Example

### Example (plain graph)




$d_a$	=	5
$d_b$	=	2
$d_c$	=	2
$d_d$	=	2
$d_e$	=	3
$d_f$	=	2
Total	=	16
$ E $	=	8

16 / 160

## Degree Example

### Example (multigraph)



$d_a$	=	6
$d_b$	=	3
$d_c$	=	2
$d_d$	=	2
$d_e$	=	5
$d_f$	=	2
Total	=	20
$ E $	=	10

17 / 160

## Degree in Directed Graphs

### ▶ two types of degree

- ▶ in-degree:  $d_v^i$
- ▶ out-degree:  $d_v^o$

### ▶ node with in-degree 0: source

### ▶ node with out-degree 0: sink

$$\sum_{v \in V} d_v^i = \sum_{v \in V} d_v^o = |A|$$

18 / 160

## Degree

### Theorem

In an undirected graph, there is an even number of nodes which have an odd degree.

### Proof.

- ▶  $t_i$ : number of nodes of degree  $i$   
 $2|E| = \sum_i d_i = 1t_1 + 2t_2 + 3t_3 + 4t_4 + 5t_5 + \dots$   
 $2|E| - 2t_2 - 4t_4 - \dots = t_1 + t_3 + \dots + 2t_3 + 4t_5 + \dots$   
 $2|E| - 2t_2 - 4t_4 - \dots - 2t_3 - 4t_5 - \dots = t_1 + t_3 + t_5 + \dots$
- ▶ since the left-hand side is even, the right-hand side is also even

□

19 / 160

## Regular Graphs

### Definition


**regular** graph: all nodes have the same degree

- ▶  $n$ -regular: all nodes have degree  $n$

20 / 160

## Regular Graph Examples

### Example



21 / 160

## Completely Connected Graphs

### Definition


$G = (V, E)$  is **completely connected**:

- ▶  $\forall v_1, v_2 \in V \ (v_1, v_2) \in E$
- ▶ there is an edge between every pair of nodes
- ▶  $K_n$ : the completely connected graph with  $n$  nodes


22 / 160

## Completely Connected Graph Examples

### Example ( $K_4$ )



### Example ( $K_5$ )



23 / 160

## Bipartite Graphs

### Definition


$G = (V, E)$  is **bipartite**:

- ▶  $\forall (v_1, v_2) \in E \ v_1 \in V_1 \wedge v_2 \in V_2$
- ▶  $V_1 \cup V_2 = V, \ V_1 \cap V_2 = \emptyset$
- ▶ **complete bipartite**:  $\forall v_1 \in V_1 \ \forall v_2 \in V_2 \ (v_1, v_2) \in E$
- ▶  $K_{m,n}$ :  $|V_1| = m, |V_2| = n$


24 / 160

## Complete Bipartite Graph Examples

Example ( $K_{2,3}$ )



Example ( $K_{3,3}$ )



25 / 160

## Isomorphism

### Definition



$G = (V, E)$  and  $G^* = (V^*, E^*)$  are **isomorphic**:

- ▶  $\exists f : V \rightarrow V^* \ (u, v) \in E \Rightarrow (f(u), f(v)) \in E^*$
- ▶  $f$  is bijective
- ▶  $G$  and  $G^*$  can be drawn the same way

26 / 160

## Isomorphism Example

Example





- ▶  $f = \{(a, d), (b, e), (c, b), (d, c), (e, a)\}$

27 / 160

## Isomorphism Example

Example (Petersen graph)



- ▶  $f = \{(a, q), (b, v), (c, u), (d, y), (e, r), (f, w), (g, x), (h, t), (i, z), (j, s)\}$

28 / 160

## Homeomorphism

### Definition



$G = (V, E)$  and  $G^* = (V^*, E^*)$  are **homeomorphic**:

- ▶  $G$  and  $G^*$  are isomorphic except that some edges in  $E^*$  are divided with additional nodes

29 / 160

## Homeomorphism Example

Example



30 / 160

## Walk

### Definition

**walk**: a sequence of nodes and edges  
from a starting node ( $v_0$ ) to an ending node ( $v_n$ )

$$v_0, e_1, v_1, e_2, v_2, e_3, v_3, \dots, e_{n-1}, v_{n-1}, e_n, v_n$$


where  $e_i = (v_{i-1}, v_i)$

- ▶ no need to write the edges
- ▶ **length**: number of edges in the walk
- ▶ if  $v_0 \neq v_n$  **open**, if  $v_0 = v_n$  **closed**

31 / 160

## Walk Example

### Example



$(c, b), (b, a), (a, d), (d, e),$   
 $(e, f), (f, a), (a, b)$

$c, b, a, d, e, f, a, b$

length: 7

32 / 160

## Trail

### Definition


**trail**: a walk where edges are not repeated

- ▶ **circuit**: closed trail
- ▶ **spanning** trail: a trail that covers all the edges in the graph

33 / 160

## Trail Example

### Example



$(c, b), (b, a), (a, e), (e, d),$   
 $(d, a), (a, f)$

$c, b, a, e, d, a, f$

34 / 160

## Path

### Definition


**path**: a walk where nodes are not repeated

- ▶ **cycle**: closed path
- ▶ **spanning** path: a path that visits all the nodes in the graph

35 / 160

## Path Example

### Example



$(c, b), (b, a), (a, d), (d, e),$   
 $(e, f)$

$c, b, a, d, e, f$

36 / 160

## Connectivity

### Definition


**connected** graph: there is a path between every pair of nodes

- ▶ a disconnected graph can be divided into connected components

37 / 160

## Connected Components Example

### Example



- ▶ graph is disconnected: no path between  $a$  and  $c$
- ▶ connected components:  
 $a, d, e$   
 $b, c$   
 $f$

38 / 160

## Distance

### Definition

the **distance** between nodes  $v_i$  and  $v_j$ :

- ▶ the length of the shortest path between  $v_i$  and  $v_j$


### Definition

**diameter**: the largest distance in the graph

39 / 160

## Distance Example

### Example



- ▶ distance between  $a$  and  $e$ : 2
- ▶ diameter: 3

40 / 160

## Cut-Point

### Definition

$G - v$ :

- ▶ the graph obtained by deleting the node  $v$  and all its incident edges from the graph  $G$

### Definition


$v$  is a **cut-point** for  $G$ :

- ▶  $G$  is connected but  $G - v$  is disconnected


41 / 160

## Cut-Point Example

$G$



$G - d$



42 / 160


## Directed Walks

- ▶ same as in undirected graphs
- ▶ ignoring the directions on the arcs:  
*semi-walk, semi-trail, semi-path*

43 / 160

## Weakly Connected Graph

Example




Definition

*weakly connected:*  
there is a semi-path  
between every pair of nodes

44 / 160

## Unilaterally Connected Graph

Example




Definition

*unilaterally connected:*  
for every pair of nodes, there is  
a path from one to the other

45 / 160

## Strongly Connected Graph

Example




Definition

*strongly connected:*  
there is a path in both directions  
between every pair of nodes

46 / 160

## Bridges of Königsberg




- ▶ cross each bridge exactly once  
and return to the starting point

47 / 160

## Traversable Graphs

Definition

$G$  is **traversable**:  $G$  contains a spanning trail



48 / 160




## Traversable Graphs

- ▶ a node with an odd degree must be either the starting node or the ending node of the trail
- ▶ all nodes except the starting node and the ending node must have even degrees

49 / 160

## Traversable Graph Example


### Example



- ▶ degrees of  $a$ ,  $b$  and  $c$  are even
- ▶ degrees of  $d$  and  $e$  are odd
- ▶ a spanning trail can be formed starting from node  $d$  and ending at node  $e$  (or vice versa):  $d, b, a, c, e, d, c, b, e$

50 / 160

## Bridges of Königsberg



- ▶ all node have odd degrees: not traversable

51 / 160

## Euler Graphs

### Definition


**Euler graph:** a graph that contains a closed spanning trail

- ▶  $G$  is an Euler graph  $\Leftrightarrow$  the degrees of all nodes in  $G$  are even


52 / 160

## Euler Graph Examples

### Example (Euler graph)



### Example (not an Euler graph)



53 / 160

## Hamilton Graphs


### Definition

**Hamilton graph:** a graph that contains a closed spanning path


54 / 160

## Hamilton Graph Examples

Example (Hamilton graph)



Example (not a Hamilton graph)



55 / 160

## Connectivity Matrix

- ▶ if the adjacency matrix of the graph is  $A$ , the  $(i, j)$  element of  $A^k$  shows the number of walks of length  $k$  between the nodes  $i$  and  $j$
- ▶ in an undirected graph with  $n$  nodes, the distance between two nodes is at most  $n - 1$
- ▶ **connectivity matrix:**  

$$C = A^1 + A^2 + A^3 + \dots + A^{n-1}$$
  - ▶ if all elements are non-zero, then the graph is connected

56 / 160


## Warshall's Algorithm

- ▶ it is easier to find whether there is a walk between two nodes instead of finding the number of walks
- ▶ for each node:
  - ▶ from all nodes which can reach the chosen node (the rows that contain 1 in the chosen column)
  - ▶ to the nodes which can be reached from the chosen node (the columns that contain 1 in the chosen row)

57 / 160

## Warshall's Algorithm Example

Example




	a	b	c	d
a	0	1	0	0
b	0	1	0	0
c	0	0	0	1
d	1	0	1	0

58 / 160

## Warshall's Algorithm Example

Example




	a	b	c	d
a	0	1	0	0
b	0	1	0	0
c	0	0	0	1
d	1	1	1	0

59 / 160

## Warshall's Algorithm Example

Example




	a	b	c	d
a	0	1	0	0
b	0	1	0	0
c	0	0	0	1
d	1	1	1	0

60 / 160

## Warshall's Algorithm Example

Example




	a	b	c	d
a	0	1	0	0
b	0	1	0	0
c	0	0	0	1
d	1	1	1	1

61 / 160

## Warshall's Algorithm Example

Example



	a	b	c	d
a	0	1	0	0
b	0	1	0	0
c	1	1	1	1
d	1	1	1	1

62 / 160

## Planar Graphs

### Definition



A graph is **planar** if it can be drawn on a plane without intersecting its edges.

- ▶ a **map** of  $G$ : a planar drawing of  $G$

63 / 160

## Planar Graph Example

Example ( $K_4$ )



64 / 160

## Regions

- ▶ a map divides the plane into **regions**
- ▶ the **degree** of a region:  
the length of the closed trail that surrounds the region

### Theorem


let  $d_{r_i}$  be the degree of region  $r_i$

$$|E| = \frac{\sum_i d_{r_i}}{2}$$

65 / 160

## Region Example

Example



$$\begin{aligned} d_{r_1} &= 3 \text{ (abda)} \\ d_{r_2} &= 3 \text{ (bcdcb)} \\ d_{r_3} &= 5 \text{ (cdefec)} \\ d_{r_4} &= 4 \text{ (abcea)} \\ d_{r_5} &= 3 \text{ (adea)} \end{aligned}$$

$$\begin{aligned} \sum_r d_r &= 18 \\ |E| &= 9 \end{aligned}$$

66 / 160

## Euler's Formula

### Theorem (Euler's Formula)


Let  $G = (V, E)$  be a planar, connected graph and let  $R$  be the set of regions in a map of  $G$ :

$$|V| - |E| + |R| = 2$$

67 / 160

## Euler's Formula Example

### Example



►  $|V| = 6, |E| = 9, |R| = 5$

68 / 160

## Planar Graph Theorems

### Theorem

Let  $G = (V, E)$  be a connected, planar graph where  $|V| \geq 3$ :  
 $|E| \leq 3|V| - 6$

### Proof.

- the sum of region degrees:  $2|E|$
- degree of a region is at least 3  
 $\Rightarrow 2|E| \geq 3|R| \Rightarrow |R| \leq \frac{2}{3}|E|$
- $|V| - |E| + |R| = 2$   
 $\Rightarrow |V| - |E| + \frac{2}{3}|E| \geq 2 \Rightarrow |V| - \frac{1}{3}|E| \geq 2$   
 $\Rightarrow 3|V| - |E| \geq 6 \Rightarrow |E| \leq 3|V| - 6$

□

69 / 160

## Planar Graph Theorems

### Theorem

Let  $G = (V, E)$  be a connected, planar graph where  $|V| \geq 3$ :  
 $\exists v \in V \ d_v \leq 5$

### Proof.

- let  $\forall v \in V \ d_v \geq 6$   
 $\Rightarrow 2|E| \geq 6|V|$   
 $\Rightarrow |E| \geq 3|V|$   
 $\Rightarrow |E| > 3|V| - 6$


□

70 / 160

## Nonplanar Graphs

### Theorem

$K_5$  is not planar.



### Proof.

- $|V| = 5$
- $3|V| - 6 = 3 \cdot 5 - 6 = 9$
- $|E| \leq 9$  should hold
- but  $|E| = 10$

□

71 / 160

## Nonplanar Graphs

### Theorem

$K_{3,3}$  is not planar.

### Proof.

- $|V| = 6, |E| = 9$
- if planar then  $|R| = 5$
- degree of a region is at least 4  
 $\Rightarrow \sum_{r \in R} d_r \geq 20$
- $|E| \geq 10$  should hold
- but  $|E| = 9$

□

72 / 160

## Kuratowski's Theorem

### Theorem

$G$  contains a subgraph homeomorphic to  $K_5$  or  $K_{3,3}$ .  
 $\Leftrightarrow$   
 $G$  is not planar.

73 / 160


## Platonic Solids

- ▶ *regular polyhedron*: a 3-dimensional solid where the faces are identical regular polygons
- ▶ the projection of a regular polyhedron onto the plane is a planar graph
  - ▶ every corner is a node
  - ▶ every side is an edge
  - ▶ every face is a region

74 / 160

## Platonic Solids

### Example (cube)



75 / 160

## Platonic Solids

- ▶  $v$ : number of corners (nodes)
- ▶  $e$ : number of sides (edges)
- ▶  $r$ : number of faces (regions)
- ▶  $n$ : number of faces meeting at a corner (node degree)
- ▶  $m$ : number of sides of a face (region degree)
- ▶  $m, n \geq 3$
- ▶  $2e = n \cdot v$
- ▶  $2e = m \cdot r$

76 / 160

## Platonic Solids

- ▶ from Euler's formula:

$$2 = v - e + r = \frac{2e}{n} - e + \frac{2e}{m} = e \left( \frac{2m - mn + 2n}{mn} \right) > 0$$

- ▶  $e, m, n > 0$ :



$$2m - mn + 2n > 0 \Rightarrow mn - 2m - 2n < 0 \\ \Rightarrow mn - 2m - 2n + 4 < 4 \Rightarrow (m - 2)(n - 2) < 4$$

- ▶ the values that satisfy this inequation:

1.  $m = 3, n = 3$
2.  $m = 4, n = 3$
3.  $m = 3, n = 4$
4.  $m = 5, n = 3$
5.  $m = 3, n = 5$

77 / 160



## Tetrahedron



$$m = 3, n = 3$$

78 / 160



## Hexahedron



$$m = 4, n = 3$$

79 / 160



## Octahedron



$$m = 3, n = 4$$

80 / 160


## Dodecahedron



$$m = 5, n = 3$$

81 / 160

## Icosahedron



$$m = 3, n = 5$$

82 / 160

## Graph Coloring

### Definition

**proper coloring** of  $G = (V, E): f: V \rightarrow C$   
where  $C$  is a set of colors

- ▶  $\forall (v_i, v_j) \in E \ f(v_i) \neq f(v_j)$
- ▶ minimizing  $|C|$

83 / 160

## Graph Coloring Example

### Example


- ▶ a company produces chemical compounds
- ▶ some compounds cannot be stored together
- ▶ such compounds must be placed in separate storage areas
- ▶ store the compounds using the least number of storage areas

84 / 160

## Graph Coloring

### Example


- ▶ every compound is a node
- ▶ two compounds that cannot be stored together are adjacent



85 / 160

## Graph Coloring Example


### Example



86 / 160

## Graph Coloring Example


### Example



87 / 160

## Graph Coloring Example


### Example



88 / 160

## Graph Coloring Example

### Example



89 / 160

## Chromatic Number

### Definition


chromatic number of  $G$ :  $\chi(G)$

- ▶ the minimum number of colors needed to color the graph  $G$
- ▶ calculating  $\chi(G)$  is a very difficult problem
- ▶  $\chi(K_n) = n$

90 / 160

## Chromatic Number Example

### Example (Herschel graph)



- ▶ chromatic number: 2

91 / 160

## Graph Coloring Example

### Example (Sudoku)

5	3			7				
6			1	9	5			
	9	8					6	
8				6				3
4			8	3				1
7				2				6
	6					2	8	
			4	1	9			5
				8			7	9

- ▶ every cell is a node
- ▶ cells of the same row are adjacent
- ▶ cells of the same column are adjacent
- ▶ cells of the same  $3 \times 3$  block are adjacent
- ▶ every number is a color
- ▶ problem: properly color a graph that is partially colored

92 / 160

## Region Coloring

- ▶ coloring a map by assigning different colors to adjacent regions

### Theorem (Four Color Theorem)

*The regions in a map can be colored using four colors.*

93 / 160

## Searching Graphs

- ▶ searching nodes of graph  $G = (V, E)$  starting from node  $v_1$
- ▶ depth-first
- ▶ breadth-first

94 / 160

## Depth-First Search

1.  $v \leftarrow v_1$ ,  $T = \emptyset$ ,  $D = \{v_1\}$
2. find smallest  $i$  in  $2 \leq i \leq |V|$  such that  $(v, v_i) \in E$  and  $v_i \notin D$ 
  - ▶ if no such  $i$  exists: go to step 3
  - ▶ if found:  $T = T \cup \{(v, v_i)\}$ ,  $D = D \cup \{v_i\}$ ,  $v \leftarrow v_i$ , go to step 2
3. if  $v = v_1$  then the result is  $T$
4. if  $v \neq v_1$  then  $v \leftarrow \text{parent}(v)$ , go to step 2

95 / 160

## Breadth-First Search

1.  $T = \emptyset$ ,  $D = \{v_1\}$ ,  $Q = (v_1)$
2. if  $Q$  is empty: the result is  $T$
3. if  $Q$  not empty:  $v \leftarrow \text{front}(Q)$ ,  $Q \leftarrow Q - v$   
for  $2 \leq i \leq |V|$  check the edges  $(v, v_i) \in E$ :
  - ▶ if  $v_i \notin D$ :  $Q = Q + v_i$ ,  $T = T \cup \{(v, v_i)\}$ ,  $D = D \cup \{v_i\}$
  - ▶ go to step 3

96 / 160



## References

Required Reading: Grimaldi

- ▶ Chapter 11: **An Introduction to Graph Theory**
- ▶ Chapter 7: Relations: The Second Time Around
  - ▶ 7.2. **Computer Recognition: Zero-One Matrices and Directed Graphs**

97 / 160

## Tree

### Definition


**tree**: a connected graph that contains no cycle

- ▶ **forest**: a graph where the connected components are trees

98 / 160

## Tree Examples

### Example




99 / 160

## Tree Theorems

### Theorem

*In a tree, there is one and only one path between any two distinct nodes.*

- ▶ there is at least one path because the tree is connected
- ▶ if there were more than one path, they would form a cycle



100 / 160

## Tree Theorems

### Theorem

Let  $T = (V, E)$  be a tree:

$$|E| = |V| - 1$$

- ▶ proof method: induction on the number of edges

101 / 160

## Tree Theorems

### Proof: base step


- ▶  $|E| = 0 \Rightarrow |V| = 1$
- ▶  $|E| = 1 \Rightarrow |V| = 2$
- ▶  $|E| = 2 \Rightarrow |V| = 3$
- ▶ assume that  $|E| = |V| - 1$  for  $|E| \leq k$

102 / 160

## Tree Theorems

Proof: induction step.

►  $|E| = k + 1$



► let's remove the edge  $(y, z)$ :  
 $T_1 = (V_1, E_1)$ ,  $T_2 = (V_2, E_2)$

$$\begin{aligned} |V| &= |V_1| + |V_2| \\ &= |E_1| + 1 + |E_2| + 1 \\ &= (|E_1| + |E_2| + 1) + 1 \\ &= |E| + 1 \end{aligned}$$

□

103 / 160

## Tree Theorems

### Theorem

*In a tree, there are at least two nodes with degree 1.*

Proof.

►  $2|E| = \sum_{v \in V} d_v$

► assume that there is only 1 node with degree 1:  
 $\Rightarrow 2|E| \geq 2(|V| - 1) + 1$   
 $\Rightarrow 2|E| \geq 2|V| - 1$   
 $\Rightarrow |E| \geq |V| - \frac{1}{2} > |V| - 1$

□

104 / 160

## Tree Theorems

### Theorem

*$T$  is a tree ( $T$  is connected and contains no cycle).*

$\Leftrightarrow$

*There is one and only one path between any two distinct nodes in  $T$ .*

$\Leftrightarrow$

*$T$  is connected, but if any edge is removed it will no longer be connected.*

$\Leftrightarrow$

*$T$  contains no cycle, but if an edge is added between any pair of nodes one and only one cycle will be formed.*

105 / 160

## Tree Theorems

### Theorem

*$T$  is a tree ( $T$  is connected and contains no cycle).*

$\Leftrightarrow$

*$T$  is connected and  $|E| = |V| - 1$ .*

$\Leftrightarrow$

*$T$  contains no cycle and  $|E| = |V| - 1$ .*

106 / 160

## Rooted Tree

- a hierarchy is defined between nodes
- hierarchy creates a natural direction on edges  
 $\Rightarrow$  in and out degrees
- node with in-degree 0 (top of the hierarchy): **root**
- nodes with out-degree 0: **leaf**
- nodes that are not leaves: **internal node**

107 / 160

## Node Level

### Definition


**level** of a node: the distance of the node from the root

- **parent**: adjacent node in the next upper level
- **children**: adjacent nodes in the next lower level
- **sibling**: nodes which have the same parent

108 / 160

## Rooted Tree Example


### Example



109 / 160

## Rooted Tree Example

### Example



110 / 160

## Ordered Rooted Tree

- ▶ sibling nodes are ordered from left to right
- ▶ **universal address system**
  - ▶ assign the address 0 to the root
  - ▶ assign the positive integers  $1, 2, 3, \dots$  to the nodes at level 1, from left to right
  - ▶ let  $v$  be an internal node with address  $a$ , assign the addresses  $a.1, a.2, a.3, \dots$  to the children of  $v$  from left to right

111 / 160

## Lexicographic Order

### Definition

Let  $b$  and  $c$  be two addresses.


$b$  comes before  $c$  if one of the following holds:

1.  $b = a_1 a_2 \dots a_m x_1 \dots$   
 $c = a_1 a_2 \dots a_m x_2 \dots$   
 $x_1$  comes before  $x_2$
2.  $b = a_1 a_2 \dots a_m$   
 $c = a_1 a_2 \dots a_m a_{m+1} \dots$

112 / 160

## Lexicographic Order Example

### Example



113 / 160

## Binary Trees

### Definition

$T = (V, E)$  is a **binary tree**:  $\forall v \in V\ d_v^o \in \{0, 1, 2\}$

$T = (V, E)$  is a **complete binary tree**:  $\forall v \in V\ d_v^o \in \{0, 2\}$

114 / 160

## Expression Tree

- ▶ a binary operation can be represented as a binary tree
  - ▶ operator as the root, operands as the children
- ▶ every mathematical expression can be represented as a tree
  - ▶ operators at internal nodes, variables and values at the leaves

115 / 160

## Expression Tree Examples

Example  $(7 - a)$




Example  $(a + b)$




116 / 160

## Expression Tree Examples

Example  $((7 - a)/5)$




Example  $((a + b) \uparrow 3)$



117 / 160

## Expression Tree Examples


Example  $((((7 - a)/5) * ((a + b) \uparrow 3))$



118 / 160

## Expression Tree Examples

Example  $(t + (u * v)/(w + x - y \uparrow z))$



119 / 160


## Expression Tree Traversals

1. **inorder traversal**: traverse the left subtree, visit the root, traverse the right subtree
2. **preorder traversal**: visit the root, traverse the left subtree, traverse the right subtree
3. **postorder traversal**: traverse the left subtree, traverse the right subtree, visit the root
  - ▶ *reverse Polish notation*

120 / 160

## Inorder Traversal Example

Example




$t + u * v / w + x - y \uparrow z$

121 / 160

## Preorder Traversal Example

Example




$+ t / * u v + w - x \uparrow y z$

122 / 160

## Postorder Traversal Example

Example



$t u v * w x y z \uparrow - + / +$

123 / 160

## Expression Tree Evaluation

- ▶ inorder traversal requires parentheses for precedence
- ▶ preorder and postorder traversals do not require parentheses

124 / 160

## Postorder Evaluation Example

Example ( $t u v * w x y z \uparrow - + / +$ )

4 2 3 \* 1 9 2 3  $\uparrow$  - + / +

```

4 2 3 *
4 6 1 9 2 3  $\uparrow$ 
4 6 1 9 8 -
4 6 1 1 +
4 6 2 /
4 3 +
7
    
```

125 / 160

## Regular Tree

Definition

$T = (V, E)$  is an **m-ary tree**:  $\forall v \in V d_v^o \leq m$

$T = (V, E)$  is a complete m-ary tree:  $\forall v \in V d_v^o \in \{0, m\}$

126 / 160

## Regular Tree Theorem

### Theorem

Let  $T = (V, E)$  be a complete  $m$ -ary tree.

- ▶  $n$ : number of nodes
- ▶  $l$ : number of leaves
- ▶  $i$ : number of internal nodes

Then:

- ▶  $n = m \cdot i + 1$
- ▶  $l = n - i = m \cdot i + 1 - i = (m - 1) \cdot i + 1$

$$i = \frac{l - 1}{m - 1}$$

127 / 160

## Regular Tree Examples

### Example

- ▶ how many matches are played in a tennis tournament with 27 players?
- ▶ every player is a leaf:  $l = 27$
- ▶ every match is an internal node:  $m = 2$
- ▶ number of matches:  $i = \frac{l-1}{m-1} = \frac{27-1}{2-1} = 26$

128 / 160

## Regular Tree Examples

### Example

- ▶ how many extension cords with 4 outlets are required to connect 25 computers to a wall socket?
- ▶ every computer is a leaf:  $l = 25$
- ▶ every extension cord is an internal node:  $m = 4$
- ▶ number of cords:  $i = \frac{l-1}{m-1} = \frac{25-1}{4-1} = 8$

129 / 160

## Decision Trees


### Example

- ▶ one of 8 coins is counterfeit (it's heavier)
- ▶ find the counterfeit coin using a beam balance

130 / 160

## Decision Trees


### Example (in 3 weighings)



131 / 160

## Decision Trees

### Example (in 2 weighings)



132 / 160

## References

Required Reading: Grimaldi

- Chapter 12: Trees
  - 12.1. Definitions and Examples
  - 12.2. Rooted Trees

133 / 160

## Weighted Graphs

- assign labels to edges:  
weight, length, cost, delay, probability, ...

134 / 160


## Shortest Path

- find the shortest paths from a node to all other nodes:  
Dijkstra's algorithm

135 / 160

## Dijkstra's Algorithm Example

Example (initialization)




- starting node: c

a	$(\infty, -)$
b	$(\infty, -)$
c	$(0, -)$
f	$(\infty, -)$
g	$(\infty, -)$
h	$(\infty, -)$

136 / 160

## Dijkstra's Algorithm Example

Example (from node c - base distance=0)



- $c \rightarrow f : 6, 6 < \infty$
- $c \rightarrow h : 11, 11 < \infty$


a	$(\infty, -)$	
b	$(\infty, -)$	
c	$(0, -)$	✓
f	$(6, cf)$	
g	$(\infty, -)$	
h	$(11, ch)$	

- closest node: f

137 / 160

## Dijkstra's Algorithm Example

Example (from node f - base distance=6)



- $f \rightarrow a : 6 + 11, 17 < \infty$
- $f \rightarrow g : 6 + 9, 15 < \infty$
- $f \rightarrow h : 6 + 4, 10 < 11$


a	$(17, cfa)$	
b	$(\infty, -)$	
c	$(0, -)$	✓
f	$(6, cf)$	✓
g	$(15, cfg)$	
h	$(10, cfh)$	

- closest node: h

138 / 160

## Dijkstra's Algorithm Example

Example (from node  $h$  - base distance=10)



- $h \rightarrow a : 10 + 11, 21 \not< 17$
- $h \rightarrow g : 10 + 4, 14 < 15$


a	(17, cfa)	
b	( $\infty$ , -)	
c	(0, -)	✓
f	(6, cf)	✓
g	(14, cfhg)	✓
h	(10, cfh)	✓

- closest node:  $g$

139 / 160

## Dijkstra's Algorithm Example

Example (from node  $g$  - base distance=14)



- $g \rightarrow a : 14 + 17, 31 \not< 17$


a	(17, cfa)	
b	( $\infty$ , -)	
c	(0, -)	✓
f	(6, cf)	✓
g	(14, cfhg)	✓
h	(10, cfh)	✓

- closest node:  $a$

140 / 160

## Dijkstra's Algorithm Example

Example (from node  $a$  - base distance=17)



- $a \rightarrow b : 17 + 5, 22 < \infty$

a	(17, cfa)	✓
b	(22, cfab)	
c	(0, -)	✓
f	(6, cf)	✓
g	(14, cfhg)	✓
h	(10, cfh)	✓

- last node:  $b$

141 / 160

## Spanning Tree

### Definition

#### spanning tree:

a subgraph which is a tree and contains all the nodes of the graph

### Definition

#### minimum spanning tree:

a spanning tree for which the total weight of edges is minimal

142 / 160

## Kruskal's Algorithm


### Kruskal's algorithm

1.  $i \leftarrow 1$ ,  $e_1 \in E$ ,  $wt(e_1)$  is minimal
2. for  $1 \leq i \leq n-2$ :  
the selected edges are  $e_1, e_2, \dots, e_i$   
select a new edge  $e_{i+1}$  from the remaining edges such that:
  - $wt(e_{i+1})$  is minimal
  - $e_1, e_2, \dots, e_i, e_{i+1}$  contains no cycle
3.  $i \leftarrow i + 1$ 
  - $i = n-1 \Rightarrow$  the subgraph  $G$  containing the edges  $e_1, e_2, \dots, e_{n-1}$  is a minimum spanning tree
  - $i < n-1 \Rightarrow$  go to step 2

143 / 160

## Kruskal's Algorithm Example

Example (initialization)




- $i \leftarrow 1$
- minimum weight: 1  
( $e, g$ )
- $T = \{(e, g)\}$

144 / 160



## Kruskal's Algorithm Example

### Example ( $1 < 6$ )




- ▶ minimum weight: 2  
(d, e), (d, f), (f, g)
- ▶  $T = \{(e, g), (d, f)\}$
- ▶  $i \leftarrow 2$

145 / 160

## Kruskal's Algorithm Example

### Example ( $2 < 6$ )




- ▶ minimum weight: 2  
(d, e), (f, g)
- ▶  $T = \{(e, g), (d, f), (d, e)\}$
- ▶  $i \leftarrow 3$

146 / 160

## Kruskal's Algorithm Example

### Example ( $3 < 6$ )




- ▶ minimum weight: 2  
(f, g) forms a cycle
- ▶ minimum weight: 3  
(c, e), (c, g), (d, g)  
(d, g) forms a cycle
- ▶  $T = \{(e, g), (d, f), (d, e), (c, e)\}$
- ▶  $i \leftarrow 4$

147 / 160

## Kruskal's Algorithm Example

### Example ( $4 < 6$ )




- ▶  $T = \{$   
 $(e, g), (d, f), (d, e),$   
 $(c, e), (b, e)$   
 $\}$
- ▶  $i \leftarrow 5$

148 / 160

## Kruskal's Algorithm Example

### Example ( $5 < 6$ )




- ▶  $T = \{$   
 $(e, g), (d, f), (d, e),$   
 $(c, e), (b, e), (a, b)$   
 $\}$
- ▶  $i \leftarrow 6$

149 / 160

## Kruskal's Algorithm Example

### Example ( $6 \not< 6$ )



- ▶ total weight: 17

150 / 160

## Prim's Algorithm


### Prim's algorithm

1.  $i \leftarrow 1, v_1 \in V, P = \{v_1\}, N = V - \{v_1\}, T = \emptyset$
2. for  $1 \leq i \leq n-1$ :  
 $P = \{v_1, v_2, \dots, v_i\}, T = \{e_1, e_2, \dots, e_{i-1}\}, N = V - P$   
 select a node  $v_{i+1} \in N$  such that for a node  $x \in P$   
 $e = (x, v_{i+1}) \notin T, wt(e)$  is minimal  
 $P \leftarrow P + \{v_{i+1}\}, N \leftarrow N - \{v_{i+1}\}, T \leftarrow T + \{e\}$
3.  $i \leftarrow i + 1$ 
  - ▶  $i = n \Rightarrow$  the subgraph  $G$  containing the edges  $e_1, e_2, \dots, e_{n-1}$  is a minimum spanning tree
  - ▶  $i < n \Rightarrow$  go to step 2

151 / 160

## Prim's Algorithm Example

### Example (initialization)




- ▶  $i \leftarrow 1$
- ▶  $P = \{a\}$
- ▶  $N = \{b, c, d, e, f, g\}$
- ▶  $T = \emptyset$

152 / 160

## Prim's Algorithm Example

### Example ( $1 < 7$ )




- ▶  $T = \{(a, b)\}$
- ▶  $P = \{a, b\}$
- ▶  $N = \{c, d, e, f, g\}$
- ▶  $i \leftarrow 2$

153 / 160

## Prim's Algorithm Example

### Example ( $2 < 7$ )




- ▶  $T = \{(a, b), (b, e)\}$
- ▶  $P = \{a, b, e\}$
- ▶  $N = \{c, d, f, g\}$
- ▶  $i \leftarrow 3$

154 / 160

## Prim's Algorithm Example

### Example ( $3 < 7$ )




- ▶  $T = \{(a, b), (b, e), (e, g)\}$
- ▶  $P = \{a, b, e, g\}$
- ▶  $N = \{c, d, f\}$
- ▶  $i \leftarrow 4$

155 / 160

## Prim's Algorithm Example

### Example ( $4 < 7$ )




- ▶  $T = \{(a, b), (b, e), (e, g), (d, e)\}$
- ▶  $P = \{a, b, e, g, d\}$
- ▶  $N = \{c, f\}$
- ▶  $i \leftarrow 5$

156 / 160

## Prim's Algorithm Example

Example ( $5 < 7$ )




- ▶  $T = \{(a, b), (b, e), (e, g), (d, e), (f, g)\}$
- ▶  $P = \{a, b, e, g, d, f\}$
- ▶  $N = \{c\}$
- ▶  $i \leftarrow 6$

157 / 160

## Prim's Algorithm Example

Example ( $6 < 7$ )




- ▶  $T = \{(a, b), (b, e), (e, g), (d, e), (f, g), (c, g)\}$
- ▶  $P = \{a, b, e, g, d, f, c\}$
- ▶  $N = \emptyset$
- ▶  $i \leftarrow 7$

158 / 160

## Prim's Algorithm Example

Example ( $7 \not< 7$ )



- ▶ total weight: 17

159 / 160

## References

Required Reading: Grimaldi

- ▶ Chapter 13: Optimization and Matching
  - ▶ 13.1. [Dijkstra's Shortest Path Algorithm](#)
  - ▶ 13.2. [Minimal Spanning Trees: The Algorithms of Kruskal and Prim](#)

160 / 160