```
20:34:20.651 -> I'm in a loop!!
20:34:22.265 -> [ADV
                      26545] Packet received from E6:0C:92:04:F8:3A
20:34:22.265 ->
                      PAYLOAD 28 bytes
                              02-01-06-02-0A-00-03-14-0A-18-11-07-9E-CA-DC-24-0E-
20:34:22.265 ->
E5-A9-E0-93-F3-A3-B5-01-00-40-6E
20:34:22.265 ->
                         RSSI -80 dBm
20:34:22.265 ->
                    ADV TYPE Connectable undirected
20:34:22.265 -> TX PWR LEVEL 0
20:34:22.265 -> 128-Bit UUID @@@$@@@6E400001-B5A3-F393-E0A9-E50E24DCCA9E
20:34:22.265 ->
                     BLE UART UUID Found!
20:34:22.265 -> Possibly connected
                     BLE UART UUID Found!
20:34:22.265 ->
20:34:22.265 -> Enable TXD's notify
20:34:22.265 -> No clientUart
20:34:22.265 ->
20:34:22.651 -> Loopdy loop!!
20:34:22.651 -> I'm in a loop!!
20:34:24.649 -> Loopdy loop!!
20:34:24.649 -> I'm in a loop!!
20:34:26.642 -> Loopdy loop!!
20:34:26.642 -> I'm in a loop!!
```