Without rounds, a swarm holds its proof less firmly

Simulation 2 (asynchronous activation), setup `task003-symmetric`: first results

LLM-free simulator; extended with the efficiency of control, 12 October 2026; runs of 9 October 2026

How the simulator works. The world, `task_003`, has three candidate allocations; A0 is the correct one. Each of 24 agents is given one true fact about it and reasons as an exact Bayesian: its *belief* is the exact probability of A0, A1 and A2 given the facts it currently remembers. There are no rounds. Each agent acts at random times, on average once per time unit: it reads q posts drawn at random from the 48 most recent posts on a shared *board* (never its own), adds their facts to its memory, recomputes its belief, *votes* by probability matching (a vote drawn from its belief) and posts one remembered fact that supports its vote, or nothing if none does. Every remembered fact is forgotten after a random lifetime (on average a fraction ρ survives one time unit; reading it again renews it). A *controller* with a target, A0 (truth) or A2 (false), acts at random times at rate λ_c until $t = 30$: it reads q_c recent agent posts and, unless the *vote gate* (at least 75% of them from agents voting for its target) or the *proof stop* (its target already proved) silences it, posts the one fact from its pool that best supports its target, at most 30 messages per episode. Agents continue alone until $t = 40$. Every episode is run three times with the same random draws: without a controller, with the truth controller and with the false controller.

Summary. The 24 agents together hold a proof of allocation A0 (the truth). Simulation 2 removes the day/night rounds of Simulation 1: agents and the controller act at random times, remembered facts fade continuously, and the shared board fades too. When agents forget, **the swarm holds its own proof less firmly** than in Simulation 1, and **the false controller is weaker** (gain 0.13 against 0.22). How fast the controller acts matters little for where the swarm ends up, but **fast controllers overshoot and then relax**. Turning the vote gate off doubles the truth controller's gain at six times the messages. As in Simulation 1, help with the truth **replaces the agents' own proofs**. Effects persist for ten time units after the controller stops. Main hypotheses were confirmed on a second, independent set of random draws.

1 Setup




Diagram 1. Simulation 2. There are no rounds. Each remembered fact is forgotten after a random lifetime (on average a fraction ρ survives one time unit) and comes back if read again. The controller acts for $0 \le t < 30$; agents continue alone until $t = 40$.

Agents are exact Bayesian reasoners. An agent's vote is drawn from its posterior (probability matching). The *vote gate* keeps the controller silent when at least 75% of the posts it read come from agents who voted for its target; the *proof stop* keeps it silent when what it read already proves its target. The grid: posts read $q \in \{3, 6, 12\}$, $q_c \in \{3, 6, 12, 24\}$, memory $\rho \in \{0.75, 1\}$, controller rate $\lambda_c \in \{0.5, 1, 2, 4, 8\}$ actions per time unit, gate on/off, proof stop on/off; 1,000 episodes per setting. Control is measured by the *gain*

$$G(t) = \frac{1}{E}\sum_{e=1}^{E}\Big[m_{\text{target}}(t)^{\text{ctrl}}(e) - m_{\text{target}}(t)^{\text{silent}}(e)\Big], \tag{1}$$

where $m_k(t)$ is the agents' mean belief in allocation k and each episode e uses the same random draws with and without the controller. Unless stated otherwise: $q = 6$, $q_c = 12$, $\rho = 0.75$, gate on, proof stop on.

2 Without a controller: the proof is held less firmly




Figure 1: Silent swarm, $\rho = 0.75$: mean belief in A0 (blue) and A2 (red) over time. Dots: Simulation 1, end of each day. Lines: Simulation 2.

With forgetting, the silent swarm settles at a lower belief in the truth than in Simulation 1: $m_{\mathrm{A0}}(30) = 0.60/0.72/0.78$ against $0.65/0.84/0.94$ for $q = 3/6/12$ (Figure 1); confirmed with fresh random draws (-0.12 at $q = 6$). In Simulation 1 memories change only at dawn, and every agent acts right after a full day of new posts. Here facts expire at random moments between an agent's actions, so fewer facts are held together at any time and complete proofs are rarer. With full memory ($\rho = 1$) both simulations end with every agent proving A0, and no controller can change that: all gains at $\rho = 1$ are zero.

3 Control




Figure 2: Gain over time, Eq. (1), by controller rate λ_c; the controller stops at $t = 30$ (dashed). Bands: 95% intervals.




Figure 3: Left: gain at $t = 30$ against the controller rate (target A0 blue, A2 red; gate on solid, off dashed; dotted: Simulation 1 with one fact per night). Right: messages sent per episode (budget 30).

- **The false controller is weaker than in Simulation 1**: $G(30) = 0.13$ against 0.22 (one fact per night in Simulation 1); confirmed with fresh draws (-0.09). The truth controller is unchanged (0.08 in both).
- **The rate changes the path more than the end point** (Figures 2, 3). From $\lambda_c = 0.5$ to 8 the gain at $t = 30$ rises from 0.10 to 0.14 (target A2) and from 0.07 to 0.11 (target A0). A fast controller spends its budget within a few time units, its gain peaks early and then relaxes: target A2 at $\lambda_c = 8$ peaks at 0.26 ($t \approx 4.5$) and falls to 0.14.
- **The effect persists**: ten time units after the controller stops, the gain has changed by at most 0.021 in every setting, less than one agent's worth of belief ($1/24 \approx 0.042$); confirmed with fresh draws.




Figure 4: Gain $G(30)$ over controller rate (x) and posts read by the controller q_c (y), for every q (columns) and ρ (rows); gate on. Top: target A2; bottom: target A0. Grey numbers: 95% interval includes 0.

4 The vote gate and the proof stop

The false controller is almost never stopped by the gate (the A2 share rarely reaches 75%), so turning the gate off changes nothing for it. The truth controller often is: with the gate off it sends about six times as many messages (9.3 against 1.6 at $\lambda_c = 0.5$) and its gain roughly doubles ($0.066 \to 0.123$; $+0.055$ at $\lambda_c = 1$, confirmed

with fresh draws). The proof stop has no effect larger than one agent's worth of belief (1/24) in any setting, and turning it off costs up to 25 extra messages per episode.

5 Help with the truth replaces the agents' own proofs




Figure 5: Share of agents whose memory proves A0 at $t = 30$: from all their facts (black) and from the agents' original facts only (green); dotted: silent swarm.

Without a controller, 12% of agents prove A0 at $t = 30$, all from the agents' own facts. The truth controller raises the share proving A0 to 20–30%, but the share proving it *from the agents' own facts* falls to 6% (slow, gated controller) and to almost 0 when it posts more (Figure 5). Agents posting a controller fact do not post their own, so their own evidence circulates less. The false controller, whose facts are also true, raises proofs of A0 too (to 14–16%) while own-evidence proofs fall to 1–3%. Simulation 1 showed the same substitution.

6 The controller overestimates its support




Figure 6: Error of the controller's estimate $\hat{v}$ (share of posts read whose author voted for the target) against the true current share of all 24 agents' last votes; solid gate on, dashed off.

Unlike in Simulation 1, $\hat{v}$ is biased upward, and **the faster the controller, the larger the bias**: about +0.014 at $\lambda_c \leq 1$, rising to +0.05 (gate on) and +0.14 (gate off) at $\lambda_c = 8$. A likely reason, not yet tested: the posts it reads come from agents who acted recently, often just after reading the controller's facts, while the true share also counts older votes. More posts read (q_c) reduce the error's spread but not the bias.

7 How efficiently does the controller steer?

A controller can change the swarm in two ways: in the direction it is asked to, or in ways that happen whatever its target. We measure how readable the command is in the swarm, how far each controller gets toward its target, how much of its change is directed, what each fact it posts buys, and how unsure the agents become. Throughout, the target is chosen by a fair coin, and all quantities are taken at one time t, across the 1,000 episodes of each arm (not over whole trajectories). Setting: probability matching, $q = 6$.

7.1 Measures




Diagram 2. Three distributions of the swarm's state at time t, one per arm, each over the episodes of that arm. The controller's total change C splits exactly into a part that depends on its target (I, from the mixture Q to each arm) and a part that does not (R, from silence to Q). Efficiency $\eta = I/C$ is the directed share.

Distributions. For each arm a (silent 0, target A0 +, target A2 −) and a time t, each episode e contributes a probability vector $y_a(e)$ over the values x of the state X: at *one-agent* level its vote shares (the vote of a randomly chosen agent), at *swarm* level a mark on the bin of $s = m_{\mathrm{A0}} - m_{\mathrm{A2}}$ (difference of mean beliefs, three equal bins on $[-1, 1]$). Then $\hat{P}_a = \frac{1}{n}\sum_e y_a(e)$. Any pair of controllers can be written as

$$\hat{P}_\pm = \hat{P}_0 + c \pm \Delta, \qquad c = \tfrac{1}{2}(\hat{P}_+ + \hat{P}_-) - \hat{P}_0, \quad \Delta = \tfrac{1}{2}(\hat{P}_+ - \hat{P}_-), \tag{2}$$

a *common* part c (what control does on average, whatever the target) and a *directional* part Δ.
Readability and the pair efficiency. With $\hat{Q} = \hat{P}_0 + c$ and $\mathrm{KL}(p\|q) = \sum_x p(x)\log_2[p(x)/q(x)]$,

$$I = \tfrac{1}{2}\mathrm{KL}(\hat{P}_+\|\hat{Q}) + \tfrac{1}{2}\mathrm{KL}(\hat{P}_-\|\hat{Q}), \quad C = \tfrac{1}{2}\mathrm{KL}(\hat{P}_+\|\hat{P}_0) + \tfrac{1}{2}\mathrm{KL}(\hat{P}_-\|\hat{P}_0) = I + R, \quad R = \mathrm{KL}(\hat{Q}\|\hat{P}_0), \quad \eta = I/C. \tag{3}$$

I is the mutual information between the target and the state: how readable the command is (at most 1 bit). I depends only on Δ, R only on c; the reference $\hat{P}_0$ is the silent arm. For small changes, $\mathrm{KL}(p + \epsilon\|p) \approx \sum_x \epsilon(x)^2/(2\ln 2\, p(x))$ gives

$$\eta \approx \frac{1}{1 + \|c\|^2/\|\Delta\|^2}, \qquad \|v\|^2 = \sum_x \frac{v(x)^2}{\hat{P}_0(x)}. \tag{4}$$

So $\eta = 1$ exactly when the two controllers' changes are mirror images ($c = 0$), whatever their size, and η falls only through the *ratio* of common to directional change: when both push the same way (a common push), or one moves the swarm much more than the other (a lopsided pair: along one direction with sizes a and b, $\|c\|/\|\Delta\| = |a-b|/(a+b)$). It is a property of the pair, not of either controller, and it stays constant whenever both effects grow together. At swarm level C is often infinite (the controlled swarm reaches states silence never visits); there we use $\eta_{JS} = I/(I + \mathrm{JS}(\hat{Q}, \hat{P}_0))$ with the bounded Jensen–Shannon divergence.
Each controller against its own target z (one agent, votes):

$$S_z = \mathrm{KL}\big(\mathrm{Bern}(\hat{P}_z(z)) \,\|\, \mathrm{Bern}(\hat{P}_0(z))\big), \qquad \pi_z = \frac{S_z}{\log_2[1/\hat{P}_0(z)]}, \qquad \varphi_z = \frac{S_z}{\mathrm{KL}(\hat{P}_z\|\hat{P}_0)}, \qquad \text{price} = \frac{S_z}{\text{facts posted}}. \tag{5}$$

S_z is the least information any intervention must inject to raise the target's share from its silent value to the observed one (raise the target, scale the other answers in proportion). **Progress** π_z is the share of the way from silence to unanimity on the target, in bits; **focus** φ_z the share of the controller's actual change that was needed for that gain; both are negative when the controller moved its target *down*. The **price** is the information injected per fact the controller posted. Finally, the agents' own uncertainty: $\Delta\bar{H}$ (mean entropy of their beliefs) and ΔJSD (disagreement, the entropy of the mean belief minus $\bar{H}$), controlled minus silent, same episode.

7.2 Over time, at one setting

- **Control builds slowly and stays**: 90% of the $t = 30$ progress by $t \approx 15$ (target A0) and 19 (target A2); it is still there at $t = 40$. The truth controller gets 18% of the way to unanimity, the false controller 2% (A2 starts at 12%, far from unanimity).
- **Both are focused** ($\varphi \geq 0.99$) and the pair is balanced ($\eta = 0.91$).
- **The false controller splits the swarm** (ΔJSD +0.13) without changing individual certainty; the truth controller makes agents surer (−0.18 bits).




Figure 7: At $\rho = 0.75$, $q_c = 12$, $\lambda_c = 1$, gate on (the controller stops at $t = 30$, dashed): readability $I(t)$, each controller's progress $\pi_z(t)$, directedness (focus φ_z, pair efficiency η, η_{JS}), and the agents' uncertainty. Bands: 95% intervals over episodes.




Figure 8: Progress π_z of each controller at $t = 30$ over the reading budget q_c and the controller rate λ_c (one agent, votes). Red: the controller moved its target down. Dash: undefined (silence already at unanimity).



Figure 9: Left: focus φ_z (negative: the change went against the target). Right: price, information injected per fact posted (bits). $t = 30$; gate on. Dash: undefined (no change, or the controlled swarm considers an answer silence rules out completely).




Figure 10: Pair efficiency at $t = 30$ over q_c and the controller rate λ_c: one-agent η (beliefs) and swarm η_{JS}. Dash: undefined.

7.3 Across the control plane

- **The truth controller's progress varies fourfold where η is flat**: 0.10–0.40 with the gate on, 0.22–0.48 off; it grows with the rate and falls with q_c (reading more posts lets the gate keep it silent). The false controller stays at 0.01–0.05.
- **Focus is 0.95 or more everywhere.**
- **Slow control is cheapest**: 0.011–0.021 bits per fact at $\lambda_c = 0.5$, 0.003–0.011 at $\lambda_c = 8$ (target A0, gate on).

7.4 Readability, pair efficiency and uncertainty against the controller rate




Figure 11: Readability I (left), pair efficiency (middle) and the change in the agents' uncertainty (right; circles $\Delta\bar{H}$, triangles ΔJSD) at $t = 30$ against the controller rate λ_c ($q_c = 12$; solid: gate on; dashed: gate off). Bars: 95% intervals.




Figure 12: Readability and pair efficiency over time, $\rho = 0.75$, $q_c = 12$, gate on, one line per rate; the controller stops at $t = 30$ (dashed). Bands: 95% intervals.

- η **is almost constant (0.88–0.94) because every knob scales both controllers alike.** From $\lambda_c = 0.5$ (gate on) to $\lambda_c = 8$ (gate off) the A0 share moves $+0.07/-0.09$ and then $+0.11/-0.17$: both changes grow 1.7–2 times, I and R grow together, and by Eq. (4) their ratio, hence η, stays. In Simulation 1, larger batches made the false controller much stronger while the truth controller hit the ceiling, so η fell.
- With full memory every agent proves A0; nothing is measurable.

7.5 Precision at 50, 100 and 300 paths

Table 1: Value from 1,000 paths per arm, and root-mean-square error of the estimate from 50, 100 or 300 paths (200 random subsets each), at $t = 30$, $\lambda_c = 1$, $q_c = 12$, gate on, $\rho = 0.75$. *: share of subsets in which the quantity is infinite or undefined.

quantity	1,000 paths	error, 50	error, 100	error, 300
steering I, swarm (3 bins)	0.297	0.060	0.041	0.023
steering I, one agent (votes)	0.053	0.014	0.009	0.004
efficiency η, one agent (votes)	0.906	0.069	0.054	0.025
efficiency η_{JS}, swarm	0.899	0.047	0.032	0.015
progress π, target A0 (votes)	0.182	0.056	0.035	0.018
progress π, target A2 (votes)	0.024	0.009	0.007	0.003
focus φ, target A0 (votes)	0.987	0.042	0.028	0.013
focus φ, target A2 (votes)	0.998	0.034	0.016	0.005
$\Delta\bar{H}$, target A0	-0.182	0.029	0.019	0.010
$\Delta\bar{H}$, target A2	-0.000	0.023	0.015	0.008
ΔJSD, target A0	-0.001	0.009	0.006	0.003
ΔJSD, target A2	0.133	0.012	0.008	0.004

Across all settings, at 100 paths: readability ± 0.01 (one agent) to ± 0.03 (swarm), progress ± 0.02, focus ± 0.01–0.02, η ± 0.02–0.03, $\Delta\bar{H}$ ± 0.02, ΔJSD ± 0.006. Two settings that differ by at least 0.02 are ordered correctly in 90–100% of subsets.

Caveats. One world (task_003), 24 agents, exact-Bayesian agents, probability-matching votes; a controller without memory that posts one fact at a time; a budget of 30 messages. Means over 1,000 episodes per setting. Full analysis, code and tables: `analysis/task003_llm_free/simulation_2/analysis/` (report of 9 October, reviewer guide).