Without rounds, a swarm holds its proof less firmly

Simulation 2 (asynchronous activation), setup `task003-symmetric`: first results

LLM-free simulator; extended with the efficiency of control, 12 October 2026; runs of 9 October 2026

How the simulator works. The world, `task_003`, has three candidate allocations; A0 is the correct one. Each of 24 agents is given one true fact about it and reasons as an exact Bayesian: its *belief* is the exact probability of A0, A1 and A2 given the facts it currently remembers. There are no rounds. Each agent acts at random times, on average once per time unit: it reads q posts drawn at random from the 48 most recent posts on a shared *board* (never its own), adds their facts to its memory, recomputes its belief, *votes* by probability matching (a vote drawn from its belief) and posts one remembered fact that supports its vote, or nothing if none does. Every remembered fact is forgotten after a random lifetime (on average a fraction ρ survives one time unit; reading it again renews it). A *controller* with a target, A0 (truth) or A2 (false), acts at random times at rate λ_c until $t = 30$: it reads q_c recent agent posts and, unless the *vote gate* (at least 75% of them from agents voting for its target) or the *proof stop* (its target already proved) silences it, posts the one fact from its pool that best supports its target, at most 30 messages per episode. Agents continue alone until $t = 40$. Every episode is run three times with the same random draws: without a controller, with the truth controller and with the false controller.

Summary. The 24 agents together hold a proof of allocation A0 (the truth). Simulation 2 removes the day/night rounds of Simulation 1: agents and the controller act at random times, remembered facts fade continuously, and the shared board fades too. When agents forget, **the swarm holds its own proof less firmly** than in Simulation 1, and **the false controller is weaker** (gain 0.13 against 0.22). How fast the controller acts matters little for where the swarm ends up, but **fast controllers overshoot and then relax**. Turning the vote gate off doubles the truth controller's gain at six times the messages. As in Simulation 1, help with the truth **replaces the agents' own proofs**. Effects persist for ten time units after the controller stops. Main hypotheses were confirmed on a second, independent set of random draws.

1 Setup




Diagram 1. Simulation 2. There are no rounds. Each remembered fact is forgotten after a random lifetime (on average a fraction ρ survives one time unit) and comes back if read again. The controller acts for $0 \le t < 30$; agents continue alone until $t = 40$.

Agents are exact Bayesian reasoners. An agent's vote is drawn from its posterior (probability matching). The *vote gate* keeps the controller silent when at least 75% of the posts it read come from agents who voted for its target; the *proof stop* keeps it silent when what it read already proves its target. The grid: posts read $q \in \{3, 6, 12\}$, $q_c \in \{3, 6, 12, 24\}$, memory $\rho \in \{0.75, 1\}$, controller rate $\lambda_c \in \{0.5, 1, 2, 4, 8\}$ actions per time unit, gate on/off, proof stop on/off; 1,000 episodes per setting. Control is measured by the *gain*

$$G(t) = \frac{1}{E}\sum_{e=1}^{E}\Big[m_{\text{target}}(t)^{\text{ctrl}}(e) - m_{\text{target}}(t)^{\text{silent}}(e)\Big], \tag{1}$$

where $m_k(t)$ is the agents' mean belief in allocation k and each episode e uses the same random draws with and without the controller. Unless stated otherwise: $q = 6$, $q_c = 12$, $\rho = 0.75$, gate on, proof stop on.

2 Without a controller: the proof is held less firmly




Figure 1: Silent swarm, $\rho = 0.75$: mean belief in A0 (blue) and A2 (red) over time. Dots: Simulation 1, end of each day. Lines: Simulation 2.

With forgetting, the silent swarm settles at a lower belief in the truth than in Simulation 1: $m_{\mathrm{A0}}(30) = 0.60/0.72/0.78$ against $0.65/0.84/0.94$ for $q = 3/6/12$ (Figure 1); confirmed with fresh random draws (-0.12 at $q = 6$). In Simulation 1 memories change only at dawn, and every agent acts right after a full day of new posts. Here facts expire at random moments between an agent's actions, so fewer facts are held together at any time and complete proofs are rarer. With full memory ($\rho = 1$) both simulations end with every agent proving A0, and no controller can change that: all gains at $\rho = 1$ are zero.

3 Control




Figure 2: Gain over time, Eq. (1), by controller rate λ_c; the controller stops at $t = 30$ (dashed). Bands: 95% intervals.




Figure 3: Left: gain at $t = 30$ against the controller rate (target A0 blue, A2 red; gate on solid, off dashed; dotted: Simulation 1 with one fact per night). Right: messages sent per episode (budget 30).

- **The false controller is weaker than in Simulation 1**: $G(30) = 0.13$ against 0.22 (one fact per night in Simulation 1); confirmed with fresh draws (-0.09). The truth controller is unchanged (0.08 in both).
- **The rate changes the path more than the end point** (Figures 2, 3). From $\lambda_c = 0.5$ to 8 the gain at $t = 30$ rises from 0.10 to 0.14 (target A2) and from 0.07 to 0.11 (target A0). A fast controller spends its budget within a few time units, its gain peaks early and then relaxes: target A2 at $\lambda_c = 8$ peaks at 0.26 ($t \approx 4.5$) and falls to 0.14.
- **The effect persists**: ten time units after the controller stops, the gain has changed by at most 0.021 in every setting, less than one agent's worth of belief ($1/24 \approx 0.042$); confirmed with fresh draws.




Figure 4: Gain $G(30)$ over controller rate (x) and posts read by the controller q_c (y), for every q (columns) and ρ (rows); gate on. Top: target A2; bottom: target A0. Grey numbers: 95% interval includes 0.

4 The vote gate and the proof stop

The false controller is almost never stopped by the gate (the A2 share rarely reaches 75%), so turning the gate off changes nothing for it. The truth controller often is: with the gate off it sends about six times as many messages (9.3 against 1.6 at $\lambda_c = 0.5$) and its gain roughly doubles ($0.066 \to 0.123$; $+0.055$ at $\lambda_c = 1$, confirmed

with fresh draws). The proof stop has no effect larger than one agent's worth of belief (1/24) in any setting, and turning it off costs up to 25 extra messages per episode.

5 Help with the truth replaces the agents' own proofs




Figure 5: Share of agents whose memory proves A0 at $t = 30$: from all their facts (black) and from the agents' original facts only (green); dotted: silent swarm.

Without a controller, 12% of agents prove A0 at $t = 30$, all from the agents' own facts. The truth controller raises the share proving A0 to 20–30%, but the share proving it *from the agents' own facts* falls to 6% (slow, gated controller) and to almost 0 when it posts more (Figure 5). Agents posting a controller fact do not post their own, so their own evidence circulates less. The false controller, whose facts are also true, raises proofs of A0 too (to 14–16%) while own-evidence proofs fall to 1–3%. Simulation 1 showed the same substitution.

6 The controller overestimates its support




Figure 6: Error of the controller's estimate $\hat{v}$ (share of posts read whose author voted for the target) against the true current share of all 24 agents' last votes; solid gate on, dashed off.

Unlike in Simulation 1, $\hat{v}$ is biased upward, and **the faster the controller, the larger the bias**: about $+0.014$ at $\lambda_c \leq 1$, rising to $+0.05$ (gate on) and $+0.14$ (gate off) at $\lambda_c = 8$. A likely reason, not yet tested: the posts it reads come from agents who acted recently, often just after reading the controller's facts, while the true share also counts older votes. More posts read (q_c) reduce the error's spread but not the bias.

7 How efficiently does the controller steer?

A controller can change the swarm in two ways: in the direction it is asked to, or in ways that happen whatever its target (for example pulling agents out of A1, or splitting them). We call the share of the first kind its *efficiency*. The target is chosen by a fair coin, so how much the swarm's state reveals about it is a well-defined information.




Diagram 2. Three distributions of the swarm's state at time t, one per arm, each over the episodes of that arm. The controller's total change C splits exactly into a part that depends on its target (I, from the mixture Q to each arm) and a part that does not (R, from silence to Q). Efficiency $\eta = I/C$ is the directed share.

For each arm a (silent 0, target A0 $+$, target A2 $-$) and a fixed time t, each episode e contributes a probability vector $y_a(e)$ over the values x of the state X, and

$$\hat{P}_a(x) = \frac{1}{n}\sum_{e=1}^{n} y_a(e)(x), \qquad I = \tfrac{1}{2}\,\mathrm{KL}(\hat{P}_+\|\hat{Q}) + \tfrac{1}{2}\,\mathrm{KL}(\hat{P}_-\|\hat{Q}), \qquad C = \tfrac{1}{2}\,\mathrm{KL}(\hat{P}_+\|\hat{P}_0) + \tfrac{1}{2}\,\mathrm{KL}(\hat{P}_-\|\hat{P}_0), \quad (2)$$

with $\hat{Q} = \frac{1}{2}(\hat{P}_+ + \hat{P}_-)$ and $\mathrm{KL}(p\|q) = \sum_x p(x)\log_2[p(x)/q(x)]$. Exactly $C = I + \mathrm{KL}(\hat{Q}\|\hat{P}_0)$, and $\eta = I/C \in [0,1]$. Two resolutions: **one agent** (X = the vote of a randomly chosen agent; $y_a(e)$ = that episode's vote shares) and the **swarm** ($X = s = m_{\mathrm{A0}} - m_{\mathrm{A2}}$, the difference of the agents' mean beliefs, in three equal bins on $[-1,1]$; $y_a(e)$ marks the episode's bin). At swarm level the controlled swarm often reaches states the silent swarm never visits, which makes C infinite; there we use the bounded version $\eta_{JS} = I/(I + \mathrm{JS}(\hat{Q},\hat{P}_0))$, with JS the Jensen–Shannon divergence. We also measure how unsure the agents become: $\bar{H}$, the mean entropy of the agents' beliefs (0 to 1.58 bits), and the disagreement $\mathrm{JSD} = H(\text{mean belief}) - \bar{H}$, each as controlled minus silent in the same episode ($\Delta\bar{H}$, ΔJSD). All quantities are taken at one time, across episodes; they are not divergences between whole trajectories (those would be at least as large). Setting: probability matching, $q = 6$, $q_c = 12$; 1,000 episodes per arm.




Figure 7: Steering I (left), efficiency (middle) and the change in the agents' uncertainty (right; circles $\Delta\bar{H}$, triangles ΔJSD) at $t = 30$ against the controller rate λ_c (solid: gate on; dashed: gate off). Bars: 95% intervals.




Figure 8: Over time, $\rho = 0.75$, gate on, one line per rate; the controller stops at $t = 30$ (dashed). Bands: 95% intervals.

Findings. (Figures 7, 8; $\rho = 0.75$.)

- **Control is small but clean.** The swarm reveals the target only weakly ($I = 0.22$–0.33 bits; one agent 0.04–0.12), but almost all of the change is directed ($\eta = 0.90$–0.95 at one agent, $\eta_{JS} = 0.88$–0.93): more than in Simulation 1 (0.56–0.73).
- **Faster controllers and turning the gate off steer more** without losing efficiency.
- **The false controller confuses**: it leaves individual certainty unchanged ($|\Delta\bar{H}| \leq 0.02$) but splits the swarm ($\Delta$JSD +0.10 to +0.13). The truth controller makes agents surer (-0.15 to -0.34 bits), more so with the gate off.
- **With full memory there is nothing to measure**: every agent proves A0, $I = 0$.
- **100 paths**: see Table 1; the small effects make efficiency the least precise quantity.

Table 1: Precision. Value from 1,000 paths per arm, and root-mean-square error of the estimate from 50, 100 or 300 paths (200 random subsets each), at $t = 30$, $\lambda_c = 1$, gate on, $\rho = 0.75$. *: share of subsets in which the quantity is infinite or undefined.

quantity	1,000 paths	error, 50	error, 100	error, 300
steering I, swarm (3 bins)	0.297	0.060	0.041	0.023
steering I, one agent (votes)	0.053	0.014	0.009	0.004
efficiency η, one agent (votes)	0.906	0.069	0.054	0.025
efficiency η_{JS}, swarm	0.899	0.047	0.032	0.015
$\Delta\bar{H}$, target A0	-0.182	0.029	0.019	0.010
$\Delta\bar{H}$, target A2	-0.000	0.023	0.015	0.008
ΔJSD, target A0	-0.001	0.009	0.006	0.003
ΔJSD, target A2	0.133	0.012	0.008	0.004

Caveats. One world (task_003), 24 agents, exact-Bayesian agents, probability-matching votes; a controller without memory that posts one fact at a time; a budget of 30 messages. Means over 1,000 episodes per setting. Full analysis, code and tables: `analysis/task003_llm_free/simulation_2/analysis/` (report of 9 October, reviewer guide).