

Table of contents

\\MR-Physics

<table border="1"><tr><td>Freudensprung</td></tr></table>	Freudensprung
Freudensprung	

<table border="1"><tr><td><table border="1"><tr><td>Cestineers</td></tr></table></td></tr></table>	<table border="1"><tr><td>Cestineers</td></tr></table>	Cestineers
<table border="1"><tr><td>Cestineers</td></tr></table>	Cestineers	
Cestineers		

<table border="1"><tr><td><table border="1"><tr><td>WIP_C6</td></tr></table></td></tr></table>	<table border="1"><tr><td>WIP_C6</td></tr></table>	WIP_C6
<table border="1"><tr><td>WIP_C6</td></tr></table>	WIP_C6	
WIP_C6		

<table border="1"><tr><td><table border="1"><tr><td><table border="1"><tr><td>AAhead_scout</td></tr></table></td></tr></table></td></tr></table>	<table border="1"><tr><td><table border="1"><tr><td>AAhead_scout</td></tr></table></td></tr></table>	<table border="1"><tr><td>AAhead_scout</td></tr></table>	AAhead_scout
<table border="1"><tr><td><table border="1"><tr><td>AAhead_scout</td></tr></table></td></tr></table>	<table border="1"><tr><td>AAhead_scout</td></tr></table>	AAhead_scout	
<table border="1"><tr><td>AAhead_scout</td></tr></table>	AAhead_scout		
AAhead_scout			

<table border="1"><tr><td><table border="1"><tr><td><table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table></td></tr></table></td></tr></table>	<table border="1"><tr><td><table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table></td></tr></table>	<table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table>	wipCEST_latest_CAIPIRINIA6
<table border="1"><tr><td><table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table></td></tr></table>	<table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table>	wipCEST_latest_CAIPIRINIA6	
<table border="1"><tr><td>wipCEST_latest_CAIPIRINIA6</td></tr></table>	wipCEST_latest_CAIPIRINIA6		
wipCEST_latest_CAIPIRINIA6			

\MR-Physics\Freudensprung\Cestineers\WIP_C6\AAhead_scout

TA: 14 sec Coil Selection: Auto Voxel Size: 1.6×1.6×1.6 mm³ Acc:: 3 Rel. SNR: 1.00

Properties

Start measurement without further preparation	Off
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	On
Graphic segment	Default
Inline Movie	Off

Resolution - Common

Slice Thickness	1.6 mm
Base Resolution	160
Phase Resolution	100 %
Slice Resolution	69 %
Trajectory	Cartesian

Resolution - Acceleration

Acceleration Mode	GRAPPA
Reference Scans	Integrated
Acceleration Factor PE	3
Reference Lines PE	24
Acceleration Factor 3D	1
Phase Partial Fourier	6/8
Slice Partial Fourier	6/8
Asymmetric Echo	Weak

Routine

Slab Group	1
Slabs	1
Distance Factor	20 %
Position	L0.0 A30.0 H0.0 mm
Orientation	Sagittal
Phase Encoding Dir.	A >> P
Slices per Slab	128
Phase Oversampling	0 %
Slice Oversampling	0.0 %
FOV Read	260 mm
FOV Phase	100.0 %
Slice Thickness	1.6 mm
TR	3.25 ms
TE	1.53 ms
Averages	1
Concatenations	1
AutoAlign	Head

Resolution - Filter

Raw Filter	Off
Elliptical Filter	Off
Distortion Correction	3D
Normalize	B1 Filter
Image Filter	Off

Geometry - Common

Slab Group	1
Slabs	1
Distance Factor	20 %
Position	L0.0 A30.0 H0.0 mm
Orientation	Sagittal
Phase Encoding Dir.	A >> P
Slices per Slab	128
Phase Oversampling	0 %
Slice Oversampling	0.0 %
FOV Read	260 mm
FOV Phase	100.0 %
Slice Thickness	1.6 mm
TR	3.25 ms
Multi-Slice Mode	Sequential
Series	Ascending
Concatenations	1

Contrast - Common

TR	3.25 ms
TE	1.53 ms
Flip Angle	16 deg
Fat-Water Contrast	Standard
Contrasts	1
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Measurements	1
Time to Center	6.3 s

Resolution - Common

FOV Read	260 mm
FOV Phase	100.0 %

Geometry - AutoAlign

Slab Group	1
Position	L0.0 A30.0 H0.0 mm
Orientation	Sagittal
Phase Encoding Dir.	A >> P
AutoAlign	Head
Initial Position	Isocenter
L	0.0 mm
P	0.0 mm

Geometry - AutoAlign

H	0.0 mm
Initial Orientation	Transversal
Initial Rotation	0.00 deg

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combination	Sum of Squares
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Tune up
B1 Shim	TrueForm
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
Excitation	Non-sel.

System - Tx/Rx

Frequency 1H	297.152943 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Subtraction

Subtract	Off
----------	-----

Inline - Subtraction

Measurements	1
StdDev	Off
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Composing**Inline - MapIt**

MapIt	None
Flip Angle	16 deg
Measurements	1
Contrasts	1
TE	1.53 ms
TR	3.25 ms
Save Original Images	On

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	fl
Dimension	3D
Excitation	Non-sel.
RF Pulse Type	Fast
Gradient Mode	Normal
Bandwidth	540 Hz/Px
Asymmetric Echo	Weak

Sequence - Part 2

Introduction	On
RF Spoiling	On
Breast Application	Off
Phase Enc. Order	Automatic

Sequence - Assistant

SAR Assistant	Off
---------------	-----

\\MR-Physics\Freudensprung\Cestineers\WIP_C6\wipCEST_latest_CAIPIRINIA6

TA: 10 sec Coil Selection: Auto Voxel Size: 2.0x2.0x4.0 mm³ Acc:: 6 Rel. SNR: 1.00**Properties**

Start measurement without further preparation	On
Wait for User to Start	Off
Start measurements	Single Measurement
Prio Recon	Off
Auto Open Inline Display	Off
Auto Close Inline Display	Off
Load Images to MR View&GO	On
Auto Store Images	On
Disable auto transfer to PACS	Off
Load Images to Stamp Segments	Off
Load Images to Graphic Segments	Off
Graphic segment	Default
Inline Movie	Off

Routine

Slab Group	1
Slabs	1
Distance Factor	20 %
Position	L6.5 P10.2 F14.2 mm
Orientation	Transversal
Phase Encoding Dir.	R >> L
Slices per Slab	36
Phase Oversampling	0 %
Slice Oversampling	100.0 %
FOV Read	224 mm
FOV Phase	82.1 %
Slice Thickness	4.0 mm
TR	4.12 ms
TE	1.69 ms
Averages	1
Concatenations	1
AutoAlign	---

Contrast - Common

TR	4.12 ms
TE	1.69 ms
Flip Angle	6 deg
Fat-Water Contrast	Standard
Lines per Shot	772
Contrasts	1
Reconstruction	Magnitude

Contrast - Dynamic

Dynamic Mode	Standard
Temporal Interpolation	1
Measurements	1
Multiple Series	Off
3D Reordering	Standard
Burn Time to Center	Off

Resolution - Common

FOV Read	224 mm
FOV Phase	82.1 %
Slice Thickness	4.0 mm
Base Resolution	112
Phase Resolution	100 %
Slice Resolution	100 %
Trajectory	Cartesian
Interpolation	Off

Resolution - Acceleration

Acceleration Mode	CAIPIRINHA
CAIPIRINHA Mode	Free
Total Factor	6
Reference Scans	GRE/Separate
Acceleration Factor PE	3
Reference Lines PE	48
Acceleration Factor 3D	2
Reference Lines 3D	36
Reordering Shift 3D	1
Phase Partial Fourier	7/8
Slice Partial Fourier	7/8
Asymmetric Echo	Off
Elliptical Scanning	On

Resolution - Filter

Raw Filter	On
Elliptical Filter	Off
POCS	Off
Distortion Correction	2D
Normalize	Off
Image Filter	Off

Geometry - Common

Slab Group	1
Slabs	1
Distance Factor	20 %
Position	L6.5 P10.2 F14.2 mm
Orientation	Transversal
Phase Encoding Dir.	R >> L
Slices per Slab	36
Phase Oversampling	0 %
Slice Oversampling	100.0 %
FOV Read	224 mm
FOV Phase	82.1 %
Slice Thickness	4.0 mm
TR	4.12 ms
Series	Ascending
Concatenations	1

Geometry - AutoAlign

Slab Group	1
Position	L6.5 P10.2 F14.2 mm
Orientation	Transversal
Phase Encoding Dir.	R >> L
AutoAlign	---
Initial Position	L6.5 P10.2 F14.2
L	6.5 mm
P	10.2 mm
F	14.2 mm
Initial Orientation	Transversal
Initial Rotation	90.00 deg

Geometry - Saturation

Special Saturation	None
--------------------	------

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table Position	0 mm
Table Position	H

System - Miscellaneous

Coil Selection	Auto Coil Select
Radial Sorting	Off
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combination	Adaptive Combine
Matrix Optimization	Off
Coil Focus	Flat

System - Adjustments

Adjustment Strategy	Standard
B0 Shim	Brain
B1 Shim	TrueForm
Adjustment Tolerance	Auto
Adjust with Body Coil	Off
Confirm Frequency	Never
Assume Silicone	Off

System - Adjust Volume

Position	L6.5 P10.2 F14.2 mm
Orientation	Transversal
Rotation	90.00 deg
R >> L	184 mm
A >> P	224 mm
F >> H	144 mm
Reset	Off

System - pTx

B1 Shim	TrueForm
Excitation	Slab-sel.
pTx Pulse	1

System - Tx/Rx

Frequency 1H	297.152943 MHz
? Ref. Amplitude 1H	0.000 V
Reset	Off
Image Scaling	1.000

Physio - PACE

Resp. Control	Off
Concatenations	1

Inline - Liver

Liver Registration	Off
Save Original Images	On

Inline - Subtraction

Subtract	Off
Measurements	1
StdDev	Off
Save Original Images	On

Inline - MIP

MIP Sag	Off
MIP Cor	Off
MIP Tra	Off
MIP Time	Off
Radial MIP	Off
Save Original Images	On
MPR Sag	Off
MPR Cor	Off
MPR Tra	Off

Inline - Soft Tissue

Wash-in	Off
Wash-out	Off
TTP	Off
PEI	Off
MIP Time	Off
Measurements	1

Inline - Composing**Inline - MapIt**

MapIt	None
Flip Angle	6 deg
Measurements	1
Contrasts	1
TE	1.69 ms
TR	4.12 ms
Save Original Images	On

Inline - Open Recon

Algorithm	None
-----------	------

Sequence - Part 1

Sequence Name	flWIP
---------------	-------

Sequence - Part 1

Dimension	3D
Excitation	Slab-sel.
RF Pulse Type	Fast
Gradient Mode	Fast
Bandwidth	450 Hz/Px
Asymmetric Echo	Off
Optimization	Min. TE
Segments	1

Sequence - Part 2

Introduction	Off
RF Spoiling	On
Incr. Gradient Spoiling	Off
Breast Application	Off
Phase Enc. Order	Automatic

Sequence - Special

Interpolation Mode	Post Volume
DL Recon	DL-CAIPI-7
Run in Background	Off
Denoising Strength	0.0
Read File	Off
CEST	OFF
PulSeq	OFF

Sequence - Assistant

SAR Assistant	Off
Allowed Delay	0 s
Optimization	Min. TE