

The SignalIntegrator function block performs discrete-time signal integration, with support for enabling/disabling, resetting, integration limiting, and saturation detection.

Inputs

Name	Type	Description
------	------	-------------

IN	REAL	The input signal to be integrated.
----	------	------------------------------------

DT_STEP	REAL	Time step per scan cycle (e.g., in seconds).
---------	------	--

ENABLE	BOOL	Enables integration when TRUE.
--------	------	--------------------------------

RESET	BOOL	Resets the integrator to zero when TRUE.
-------	------	--

MAX_ACCUM	REAL	Maximum absolute value the integrator can accumulate (anti-windup).
-----------	------	---

DELTA_LIMIT	REAL	Maximum absolute value allowed for a single integration step (rate limiting).
-------------	------	---

Outputs

Name	Type	Description
------	------	-------------

OUT	REAL	Current integrated output value.
-----	------	----------------------------------

DELTA	REAL	Value added to the accumulator during this cycle (after limiting).
-------	------	--

SATURATED	BOOL	TRUE if the accumulator has reached \pm MAX_ACCUM saturation.
-----------	------	---

Internal Variables

Name	Type	Description
------	------	-------------

Accumulated	REAL	The running sum of the integrated signal.
-------------	------	---

StepValue	REAL	Raw computed step before limiting (IN * DT_STEP).
-----------	------	---

LimitedDelta	REAL	Clamped version of StepValue respecting DELTA_LIMIT.
--------------	------	--