Virtual Machine Assists

From:

“Virtual Machines” JE.Smith, R.Navir

Uhlig, Rich, et al. "Intel virtualization technology." *Computer* 38.5 (2005): 48-56.

Performance: The fee for VM?

- Not only “maximize” server utilization but, how to achieve near-native performance?
  - Early usages with VM reports 20-30% performance degradation
- The flexibility provide by the VMM has to be paid somehow
  - Apparently, always there will a performance hit of using VM
- (next)… The components of such “fee” and how to minimize each one (with emphasis in x86)

Reasons for VM Slowdown

- Setup a Save state
  - Each time the VM is activated/deactivated the state of the processor/MMU should be copied from/to memory
  - Copy of registers, timing facilities and perhaps MMU structures
- Emulation
  - Not all insn can be executed natively
  - Some insn should be emulated (mostly through interpretation)
    - Trap to VMM
    - Interpretation by VMM
    - Return from VMM to guest
- Interrupt handling
  - Reflect through VMM before getting to Guest/OS
- Virtual Memory Management
  - Shadow page faults when page is already mapped
- Duplicated effort between VMM and Guest/OS
  - Memory management done by both
- Interval timer
  - Notion of time of guest/OS can be lost (because all the previous reasons)

Virtual Machine Assists

- Ways of making application on VM run faster
  - Have no performance effect if run in native mode
  - i.e. Minimize VMM interventions

1. Instruction Emulation Assist
2. System Call intervention
3. Shadow Table Management
4. Non-architected TLB management
5. Virtual interval timer
6. Exclusive hardware access
7. …

Instruction Emulation Assist (IEA)

- Avoid VMM intervention when a privileged instruction has to be executed
  - Translate to the hardware the functionality of the VMM
  - Do it for the most frequent and "annoying" critical instructions
- Example LPSW (IBM 370) modify state register (and PC)
  - With IEA, the hardware (through microcode) perform the required actions
    - Check if the guest has privilege (i.e., is OS code), the user accessible portion and the memory copy (of the VM) of the state register
  - A control register has to enable and disable this behavior (to differentiate VM from native mode). ISA adds a Control Register (CR6)
    - ***Bit 0 VM Assist On/Off (do LPSW from microcode, enabled when VMM dispatches VM)***
    - ***Bit 1 Virtual user/supervisor state (change the "virtual" PSR or "virtually" trap)***
    - Bit 4 SVC handling On/Off
    - Bit 5 Shadow table fixup On/Off
    - Bit 7 Virtual interval timer assist
    - Bits 8-28 address of VM pointer list
  - CR6 Set by VMM when Guest is dispatched
- VMM and ISA should be co-designed. No OS knowledge is required

Virtual Machine Monitor Assists

- Context switch
  - Use hardware assist to store and restore in VM switches
- Decoding privileged instructions
  - Avoid VMM soft-"decode" of a privileged instruction
  - Not instruction Emulation Assist (i.e. VMM intervention occurs), just ease the VMM overhead
- Virtual Interval Timer
  - OS is designed with time in mind: OS ticks, scheduler, responsiveness, etc…
  - VMM can "emulate" to the guest-time using soft-counters: imprecise and resource consuming
  - Hardware assisted: use a real timer when the guest is running and fake it when not
- Adding new instructions to the ISA
  - According usage, some "common" operations of the VMM can be mapped to hardware
  - IBM/370: Page lock, page unlock, Translate VA and test for shared page, invalidate segment/page table, etc…

Entry and Exit from IE mode



IBM Interpretive Execution Facility

- Provides a way to execute most of the VMM functions in hardware
- Function of VMM separated between hardware and software
  - Cleaner separation compared to earlier VM assists
- Advantages of interpretive execution
  - Better performance
  - Better predictability of performance
  - Applicable for all types of guest operating systems
- Key instruction: SIE (Start Interpretive Execution)
  - Used by VMM to give control to hardware
  - Architectural state of VM in table accessible to hardware
  - Privileged instructions interpreted in hardware
  - Occasionally need to get back to the software part of the VMM (I/O or infrequent instructions)

Improving performance of the Guest/OS

- The *classical* concept is guest/OS shouldn't be aware of the presence of a VMM
  - It is VMM task to handle interrupts and to ensure that privileged insn do the same than in a privileged environment
  - Perfect from the point of view of abstraction

- But, if the guest/OS is aware of the situation, it might be useful:
  - To relegate some functionality to VMM
  - To provide VMM with some hints to improve performance: this exchange of information is called ***Handshaking***
    - IBM/370 provides the insn DIAGNOSE to do it

Handshaking: examples of use

- Non paged mode
  - Run the guest/OS without dynamic address translation: just virtual addresses
  - Translation is handled by VMM. "*Just*" shadow PT
- Pseduo-page-fault handling
  - Prevent VMM to replace silently a page allocated by a VM
  - Match real page faults with virtual page faults
- Spool Files
  - Connect spool files in the VMM with spool files in guest/OS
- Inter-VM- communication
  - Avoid "I/O" path when two VM in the same host want to communicate
  - Not only reduce VMM overhead but even speed-up communication over a native implementation

Xen Para-virtualization

- Use handshaking approach (i.e. let the guest/OS aware) to avoid “critical” IA-32 insns
  - Rewrite the guest kernel (xenderized kernels) and transform system calls in “hypercalls”
- Also runs the guest/OS code mode in ring-1 (32-bits)
- The changes are restricted to the kernel: user level applications will run natively
- Initially only 3000 lines of Linux kernel where changed
- Since virtualization extensions in x86, this in no longer strictly true/necessary

Other optimizations

- Shadow table bypass assist
  - Use inside the guest/OS pointers to shadow-PT
  - No “real” pages: just virtual and physical pages
  - Hardware is intercepting all PT and TLB guest manipulation to reflect such changes in shadow-PT
  - Hardware pays special care with “special pages” (such as page0 in IBM/370)

- Preferred-machine assist
  - Allow the guest/OS to run in system mode
  - Hardware protection to isolate VMM from guest

- Segment sharing across VM
  - Allow share “read-only” segments within virtual machines (reentrant code)
  - Less pressure over TLB and memory
  - Can be emulated in software by the VMM (but with expensive checking and controlling). If hardware support it

Example machine: IBM 360/370/390

- CP-67 on 360/67 in 1960s
  - First production VM implementation
  - Provided means for supporting timesharing via Multiple guest versions of CMS – single user OS
  - Used basic virtualization concepts described by Goldberg
- VM/370 (1972) led to widespread use of VMs
- Virtual Machine Assist (1974)
  - Enhancements to support VMs
- Extended Control Program Support (1978)
  - Further enhances VM support
- Handshaking
  - Lets guest/OS in on the secret
- Interpretive Execution Facility (IEF) (1991)
- Still in use in Z-Series (see http://www.vm.ibm.com)

X86 VIRTUALIZATION EXTENSIONS

Four Generations

- 1st Generation: VT-x
  - Processor virtualization
- 2nd Generation: EPT
  - MMU virtualization
- 1st' Generation: VT-d and VT-c
  - I/O virtualization & network virtualization (SDN)
- 3th Generation:
  - Virtualization Nesting
- Details about what is supported in each processor model in http://ark.intel.com/Products/VirtualizationTechnology

1st Generation: Intel VT-x (Vanderpool)

- x86 Virtualization Extensions used since 2005 (Pentium 663/667)
  - AMD did the same with AMD-v (Pacifica)
  - Conceptually similar to IBM Interpretive Execution z/VM in zSeries systems
- New VMX mode
  - Two privilege levels: root and non-root
- Root level
  - Similar to conventional x86
  - Plus new VMX instructions
  - VMM runs in root level
- Non-root level
  - Limited control of resources
  - Including when in ring 0
  - Guest OS plus apps runs in non-root level

VT-x Operation

- Transition from normal mode to VMX root mode via **`vmxon`** instruction
- VMM in root level, sets up the environment for each VM and initiates the virtual machine via **`vmlaunch`** instruction
- Attempts to modify resource cause return to root level
- Explicit **`vmcall`** causes return to root mode
- **`vmresume`** instructions causes return to guest in non-root mode
- **`vmxoff`** instruction causes exit from VMX mode



VT-x Capabilities

- Root mode eliminates need to run all guest code in user mode (no emulation needed)
  - VMM runs in root mode
  - For code regions with no critical instructions, HW “can be” as fast as in regular state (not really)

- VT-x HW maps state-holding data elements directly to native structures during VM execution.
  - VMCS (virtual machine control structure) encapsulates VM state
  - HW implementation can take over loading and unloading state
  - No need for VMM to perform data manipulation of state info from memory (the data is directly accessed by the processor)

- Eliminates the need for paravirtualization, code patching, etc…
  - Allows standard versions of OSes to be used as guests
  - Still **`vmcall`** instruction, can be used to pass hints and data to the VMM (if required)

VMCS (Virtual Machine Control Structure)

- Can be manipulated by HW or SW in root mode
  - VMM is implementation-dependent
- Aligned on 4KB boundary identifies the current running VM
- Each VM has a pointer to its VMCS through the VMPTR register (one active per logical processor)
  - Load VMPTR with **`vmptrld`** instruction
  - Read VMCS with **`vmread`** ; Write VMCS with **`vmwrite`**
- Keeps architected state of the VM: “shadow” copies of control register, segment register, etc…

State Area	Guest State	Register State
		Interruptibility State
	Host State	Register State
Control Area	VM Execution Controls	Pin-based Execution Controls
		Processor-based Execution Controls
		Bitmap Fields
		etc.
	VM Exit Controls	Control Bitmap
		MSR Controls
	VM Entry Controls	Control Bitmap
		MSR Controls
		Controls for Event Injection
VM Exit Information	Basic Information	VM-Exit Information
		Vectoring Event Information
	Other Exit Information	Due to Event Delivery
		Due to Instruction Execution

Critical Instructions

- Programmable VM exit conditions given in VMCS
  - E.g., which instructions should cause exit to VMM
- **Example**: Read Time Stamp Counter (RDTSC)
  - Reads *Time-stamp register* IA32_TIME_STAMP_COUNTER (a MSR o Model-specific Register) in a GP registers
  - Works in any mode if TSD (*Time-stamp Disable*) bit in control register 4 (CR4) is off
  - If TSD is on, RDTSC does:
    - If ring == 0, ignores TSD
    - If ring !=0, traps (*protection mode exception*)

RDST


rdtsc instruction encountered
Machine in VMX mode?
Yes
No
Perform normal operation
RDTSC exiting bit is set in VMCS?
No
Yes
Save exit information Exit VM.
Return control to VMM
TSD bit of CR4 is set in VM?
No
Yes
Ring 0 operation?
Yes
No
Protection Exception. Save exit information. Exit VM.
Return control to VMM
Use TSC Offsetting bit is set in VMCS?
No
Return time-stamp counter value
Yes
Add TSC offset to time-stamp counter value.
Return sum
Fall back
(if VMM wants
to handle TSC)

2nd Generation: MMU virtualization

- Intel EPT or AMD NPT
  - Intel Nehalem, AMD Barcelona
- A VMM must protect host physical memory at all cost!
  - Multiple guest operating systems share the same host physical memory
  - VMM typically implements protections through "page-table shadowing" in software
- Page-table shadowing might accounts for a large portion of virtualization overheads
  - VM exits due to: page faults, invalidate TLB entry, Changes in CR3,….

Extended Page Table

- Concept of Extended Page Table (EPT) :
  - Instead of walking along with only one page table hierarchy, EPT technique implement one more page table hierarchy.
    - One page table is maintained by guest/OS, which is used to generate guest physical address.
    - The other page table is maintained by VMM, which is used to keep guest physical address under “control”
  - For each PT manipulation, EPT will transparently “translate” guest physical address into host physical address

What Is EPT?



- Extended Page Table
- A new page-table structure, under the control of the VMM
  - Defines mapping between guest- and host-physical addresses
  - EPT base pointer (new VMCS field) points to the EPT page tables
  - EPT (optionally) activated on VM entry, deactivated on VM exit
- Guest has full control over its own page tables
  - No VM exits due to guest page faults, TLB manipulation, etc…

EPT Translation: Ugly Details



- All guest-physical memory addresses go through EPT tables
  - CR3, PDE, PTE, etc…
- Above example is for 2-level table for 32-bit address space
  - Translation possible for other page-table formats (e.g., PAE)

TLB management

- 1st generation force TLB flush in each VMX transaction (**`vmxon`**, **`vmlaunch`**, **`vmresume`**, etc…)

- 2nd generation introduced the VPID
  - New 16-bit virtual-processor-ID field (VPID) field in VMCS
    - VMM allocates unique value for each guestOS
    - VMM uses VPID of 0x0000, no guest can have this VPID
  - TLB is tagged with VPID (Similar to ASID but at VM level)
  - No need for TLB flush at **`vmexit`**
  - VPID is managed by VMM
    - Freed at VM termination

1st' Generation: I/O virtualization

- Intel VT-d and AMD IOMMU
- I/O device assignment
  - VM owns real device
- DMA remapping
  - Support address translation for DMA
- Interrupt remapping
  - Routing device interrupt

VT-d Overview

- VT-d is platform infrastructure for I/O virtualization
  - Defines architecture for DMA remapping
  - Implemented as part of platform core logic
  - It is supported broadly in Intel server and client chipsets



Intel VT-d

- Add DMA remapping hardware component.



VT-d Usage

- Basic infrastructure for I/O virtualization
  - Enable direct assignment of I/O devices to unmodified or paravirtualized VMs
- Improves system reliability
  - Contain and report errant DMA to software
- Enhances security
  - Support multiple protection domains under SW control
  - Provide foundation for building trusted I/O capabilities
- Other usages
  - Generic facility for DMA scatter/gather
  - Overcome addressability limitations on legacy devices

VT-c (Network)

- VMDq
  - Multiple queue pairs for partitioning
  - Filters a specific VM's unicast packets into individual receive queues
    - Such as MAC filtering, VLAN filtering
  - Ensures transmit fairness between VMs
    - Prevents head-of-line blocking
- PCI-SIG Single Root I/O Virtualization (SR-IOV) allows partitioning of a single Server Adapter port into multiple virtual functions.
  - Use these virtual ports to create with native-performance and isolated connections to virtual machines
- Using switches SDN capable (Software-defined networking), a fully virtualized data-center!
  - SDN is like computing virtualization but at networking level

3th Generation: Virtualization Nesting

- VM nesting is interesting for
  - Cloud development and cloud outsourcing
  - Added flexibility (eg. XP on Win 7/8)
- Since Haswell, hardware partial support for accelerated nesting
  - Virtual EPT
  - VMCS shadowing
- Latest version of Xen supports nesting
  - Still a big penalty in performance
- Interesting topic for research