

Optical Integrated Sensing and Communication for 6G: A Cross-Modality Survey and Metric-Governed Roadmap

Fatih Dönmez, Ahmet Altuncu, and Mustafa Namdar, *Member, IEEE*

Abstract—Optical Integrated Sensing and Communication (O-ISAC) is emerging as a 6G design direction because optical carriers can support high-rate links and sensing functions across guided fiber, free-space optical, VLC/LiFi, and photonics-assisted high-frequency platforms. Yet the literature remains fragmented by modality, terminology, measurement plane, and metric semantics, making direct comparison risky without an explicit governance layer.

This systematic review synthesizes 220 peer-reviewed O-ISAC studies using a PRISMA-grounded process and develops a cross-modality taxonomy spanning medium class, integration mechanism, detection/observability regime, and sensing task. We introduce a metric-governed reporting contract that separates bandwidth-limited range resolution $\Delta r_{\min}$, estimator-level accuracy such as σ_r /RMSE, CRB/FIM bound statements, fiber spatial granularity Δz , and optical/electrical signal-quality planes. This contract enables conservative rate-resolution analysis and capacity-resolution quotient (CRQ) synthesis only when rate and sensing metrics are reported under compatible scenario records.

The review further maps enabling technologies, including optical RIS/ORIS, optical phased arrays, photonic integration, photonics-assisted mmWave/THz generation, and ML/security-aware adaptation, and links them to deployment constraints and benchmark needs. The resulting roadmap identifies the reporting practice, taxonomy alignment, reproducible evaluation workflows, scalable hardware, and domain-aware validation needed for credible O-ISAC progress.

Index Terms—Optical integrated sensing and communication, O-ISAC, free-space optics, visible light communication, distributed fiber sensing, photonic-THz systems, systematic review.

I. INTRODUCTION

Integrated sensing and communication (ISAC) has become a central 6G theme because future networks are expected to exchange data, infer geometry, localize users and objects, monitor infrastructure, and adapt to environmental context within the same operating fabric [1], [2]. Optical integrated sensing and communication (O-ISAC) extends this joint-service idea into optical carriers, guided fiber links, free-space optical links, visible-light/LiFi deployments, and photonics-assisted mmWave/THz chains [3]–[5]. This move is not simply RF-ISAC at a higher carrier frequency. Optical systems expose much larger nominal spectral resources, strong spatial directionality, and mature photonic multiplexing, but they also introduce medium-specific constraints: fiber is guided and often monitored through distributed sensing granularity,

FSO is weather- and pointing-sensitive, VLC/LiFi is intensity-domain and illumination-constrained, and photonic-THz systems couple optical generation/distribution to high-frequency wireless propagation [1], [6]–[8].

The attraction of the optical domain is visible in representative demonstrations. Photonic-THz and fiber-wireless systems report very high data rates together with ranging or radar-style sensing, while multicore and coherent fiber studies show that communication capacity and distributed monitoring can coexist in guided infrastructure [9]–[14]. VLC and LiFi studies, in contrast, often couple indoor data access with positioning, gesture, occupancy, or pose estimation through direct-detection and lighting-aware channels [8], [15]–[18]. These examples motivate O-ISAC as a family of architectures rather than a single pooled performance category.

Fig. 1 provides the opening landscape. It separates the broad optical resource argument from the cross-modality synthesis problem. Wide optical bandwidth can support high-rate and fine-delay measurements, yet a fiber Δz , a wireless $\Delta r_{\min}$, an estimator RMSE, a CRB/FIM bound, an optical OSNR value, and an electrical SNR value are not interchangeable evidence objects. This review is built around that distinction. Instead of ranking papers by headline rate or sensing number, it asks when cross-paper comparison is admissible and which reporting fields are needed to make such comparison defensible.

The related survey landscape remains fragmented. RF-ISAC surveys and standardization-oriented discussions establish the broader 6G context but do not resolve optical-plane measurement issues [2], [19]. VLC/VLP surveys explain visible-light positioning and indoor optical channels, yet usually remain single-modality [4], [5], [20]. Fiber-oriented reviews emphasize distributed fiber-optic sensing, cabled infrastructure, or optical communication coexistence rather than cross-modality optical ISAC [6], [21], [22]. Photonic-THz and fiber-wireless reviews highlight high-frequency generation and integrated waveforms but do not fully bridge fiber, FSO, VLC/LiFi, and hybrid platforms under one metric contract [1], [3], [23], [24]. Table I summarizes the gap.

Four fragmentation mechanisms motivate the review. First, terminology is unstable: optical papers use O-ISAC, LiSAC, optical JCS, photonic ISAC, fiber-ISAC, fiber sensing/communication coexistence, and THz-over-fiber labels for overlapping ideas [3], [4], [21], [26], [27]. Second, the dominant metrics are not isomorphic across modalities. Third, the communities cite and benchmark within separate silos even when waveforms, calibration, or receiver concepts might transfer [28]–[32]. Fourth, application studies often show domain-specific feasibility without stating which evidence can generalize to other optical media [33]–[38].

Fatih Dönmez and Ahmet Altuncu are with the Department of Electrical and Electronics Engineering, Afyon Kocatepe University, Afyonkarahisar, Türkiye (e-mail: fatih.donmez@usr.aku.edu.tr; aaltuncu@aku.edu.tr). Fatih Dönmez ORCID: 0000-0003-0553-4418. Corresponding author: Fatih Dönmez.

Mustafa Namdar is with the Department of Electrical and Electronics Engineering, Faculty of Engineering, Kutahya Dumlupınar University, Kutahya, Türkiye (e-mail: mustafa.namdar@dpu.edu.tr).




Fig. 1. O-ISAC landscape across optical spectrum resources and the main fiber, FSO/photonic-THz, and VLC/LiFi branches.

TABLE I
RELATED SURVEY LANDSCAPE AND THE CONTRIBUTION OF THIS REVIEW.

Work	Year	Scope	Main emphasis	Syst.	Cross-med.	Tax.	Metric gov.	CRQ
[19]	2025	RF/6G ISAC	RF-centric survey framing and standardization context	No	No	Part	No	No
[4]	2024	VLC	Visible-light JCS prospects and indoor positioning links	No	No	Part	No	No
[20]	2024	VLC/VLP	VLC/VLP channel and localization survey	No	No	Part	No	No
[6]	2024	Fiber	Fiber-sensing ISAC challenges	No	No	Part	No	No
[3]	2024	Optical ISAC	Architecture, potential, and challenge tutorial	No	Part	Part	Part	No
[1]	2026	Photonic THz	Photonic THz-ISAC waveform/system view	No	Part	Part	No	Part
[25]	2025	RIS/ISAC	RIS-enabled ISAC enabler context	No	No	Part	Part	No
This review	2026	All optical	PRISMA $N = 220$, taxonomy, metric contract, governed tradeoff, enablers, applications, roadmap	Yes	Yes	Yes	Yes	Yes

This review contributes five items. First, it builds a PRISMA/TQAF evidence base over $N = 220$ peer-reviewed studies. Second, it defines a cross-modality taxonomy covering fiber, FSO, VLC/LiFi, photonic-THz, and hybrid platforms. Third, it introduces a metric-governance contract that separates $\Delta r_{\min}$, σ_r /RMSE, CRB/FIM, Δz , and OSNR/SNR/ESNR planes. Fourth, it performs a governed rate-resolution and CRQ synthesis that shows the CRQ-valid subset is sparse. Fifth, it links enablers, applications, and open challenges into a roadmap for reproducible, modality-aware O-ISAC research.

A. Why Optical O-ISAC Needs Its Own Survey Layer

The need for a dedicated O-ISAC survey follows from the fact that optical systems change both the useful resource and the failure mode. In RF-ISAC, the dominant constraints are typically spectrum availability, aperture size, waveform sharing, interference management, and regulatory coexistence. Optical systems inherit some of these concerns, but they also introduce wavelength-selective components, photodetection, optical/electrical conversion, beam pointing, eye-safety and illumination constraints, fiber dispersion and nonlinearities,

and very different receiver observability regimes. A visible-light positioning paper and a coherent fiber sensing paper may both be O-ISAC, but they do not report the same physical layer. The same is true for a photonic-THz system in which optics generate or distribute a high-frequency carrier before wireless propagation occurs. For this reason, the review treats O-ISAC as a cross-modality family whose members need common reporting fields but not a single common channel model.

This stance also affects how prior surveys are used. Related surveys provide valuable modality anchors, such as VLC/VLP positioning, distributed fiber sensing, RF-ISAC standardization, RIS-enabled ISAC, and photonic-THz waveform discussions. They do not, however, provide a systematic evidence base that simultaneously compares fiber, FSO, VLC/LiFi, photonic-THz, and hybrid optical platforms under a metric contract. The resulting gap is not merely bibliographic. Without a common taxonomy and metric-governed reading, a reader can easily misinterpret a fiber spatial granularity as wireless range resolution, a CRB as measured accuracy, an OSNR value as electrical SNR, or an unmatched rate and sensing value as a valid CRQ point.

B. How the Review Is Organized

The paper therefore proceeds from physical and metric foundations to evidence synthesis. Section II defines the receiver-plane and metric-governance contract. Section III explains the PRISMA/TQAF evidence base and why a structured synthesis is more appropriate than a statistical meta-analysis. Section IV develops the cross-modality taxonomy. Section V applies the metric contract to the rate–resolution and rate–accuracy evidence, preserving the sparse governed subset result. The final sections interpret enablers, deployment motifs, and roadmap challenges through the same governance lens rather than as isolated lists of technologies.

C. Optical Advantage and Fragmentation Detail

The optical spectrum supports dense multiplexing well beyond RF-sized blocks. In wireless settings, MDM combined with WDM has realized **64 parallel channels** (16 wavelengths $\times$ 4 OAM modes) ; in cabled settings, 7-core SDM fiber has reached **241.85 Tbps** over 38 km . Coexistence-oriented implementations further show that shared optical pipelines can preserve communication throughput while embedding sensing through polarization multiplexing and DSP-compatible integration . Together, these results validate optical parallelism beyond single-link RF limits.

a) Advantage 2: Enhancing Sensing Precision via Ultra-Wide Bandwidth: Range resolution in two-way sensing is bandwidth-limited as $\Delta r_{\min} = v/(2B_{\text{eff}})$. Optical bandwidths therefore enable wireless ranging regimes that narrowband RF systems struggle to match: photonic-THz demonstrations report **2.5 mm** resolution alongside 120 Gbps, giving $\text{CRQ}_{\Delta} = 4.8 \times 10^{13}$ bps/m . Throughout this review, we keep this bandwidth-limited resolution distinct from SNR-dependent estimation accuracy such as RMSE/σ_r ; fiber DAS contributes through sensitive distributed monitoring rather than fine free-space range resolution .

b) Advantage 3: Spatial Isolation and Reduced RF-EMI Coupling: The high directionality of optical beams provides deployment-dependent spatial isolation and can reduce multi-user interference relative to wide-beam RF sectors in clear line-of-sight settings . Wireless O-ISAC still faces turbulence and ambient-light sensitivity , but its weak coupling to conventional RF electromagnetic interference and milliradian-scale beam divergence support dense spatial reuse when propagation conditions are favorable.

c) Unified O-ISAC Taxonomy: Having established the optical advantages, we next delimit the scope of this review. O-ISAC is not a single monolithic system class; it clusters into modality families shaped by propagation medium, signal model, and dominant impairment. Section IV develops the evidence-based taxonomy from our PRISMA-compliant corpus, centered on 2020–2025 while retaining a small number of earlier protocol-eligible foundational studies: fiber, free-space optical, VLC/LiFi, and photonic-THz, each with distinct operating windows and sensing–communication conventions.

This shared reference frame is essential for later cross-modality comparison, but it also exposes a deeper issue:

terminology, metrics, and evaluation protocols remain inconsistent across communities. That inconsistency motivates the fragmentation challenge discussed next.

d) The Fragmentation Challenge: A Landscape Without Unity: Despite these physical advantages, the O-ISAC literature remains fragmented. Our systematic analysis of **220 peer-reviewed studies**, primarily from **2020–2025**, reveals four recurring fault lines: inconsistent terminology, non-standardized sensing metrics, siloed modality communities, and weak cross-domain technology transfer. Together, they impede reproducibility and defensible cross-study comparison.

Terminology Proliferation. Closely related ideas are labeled differently across communities: RF-oriented work still uses aliases such as RadCom and JRC , VLC papers alternate between JCS, ISAC, and SCI , visible-spectrum studies may foreground the optical band or control function rather than a shared ISAC vocabulary , and fiber work diverges into labels such as ISAC-OF, fiber-ISAC, and photonic ISAC . This aliasing complicates systematic discovery, inflates perceived novelty through re-labeling, and obscures conceptual links across modalities.

Metric Non-Isomorphism. Equally problematic is the absence of a shared sensing-performance language. A first-order example is the recurrent conflation of **physical resolution limits, estimator-dependent accuracy, and information-/estimation-theoretic bounds**. For ranging, the bandwidth-limited physical resolution is

where $v = c$ in free space and $v \approx c/n_g$ in guided media. In contrast, RMSE/σ_r and localization error remain SNR- and estimator-dependent, while CRB/FIM quantities describe information bounds under an explicit observation model . The same “resolution” label can therefore refer to different objects across modalities, and signal quality also shifts across reference planes: coherent fiber studies often report OSNR , whereas VLC studies usually report post-detection electrical SNR .

Sub-Domain Siloing and Limited Cross-Citation. Fiber DAS/communication co-design, hybrid fiber communication/sensing network planning, FSO ranging links, VLC positioning/data systems, and photonic-THz ISAC have largely evolved in separate channel, hardware, and evaluation cultures . As a result, a trade-off frontier in one modality is rarely comparable to another without harmonized assumptions. Recent assessments echo this separation, noting weak integration even within VLC/VLP ecosystems and persistent interoperability barriers across sectors .

Weak Cross-Domain Technology Transfer. Methods developed in one optical sub-domain are only weakly reused in others. Fiber-oriented waveform/probing structures seldom transfer to free-space or VLC links, and VLC-centric localization or learning pipelines rarely reappear in FSO or photonic-THz settings . The same pattern appears in application-facing designs, where UAV semantic communication, logistics orchestration, and vehicular path-loss adaptation are usually developed within narrow deployment silos rather than as reusable cross-modality building blocks . Without shared benchmarks and reporting protocols, it remains difficult to separate what is modality-specific from what is genuinely transferable .

The Missing Unifying Framework. These issues point to the same gap: O-ISAC still lacks a shared physical-layer taxonomy, a standardized reporting contract, and a cross-modality benchmark culture. At minimum, comparable studies should disclose communication performance, sensing performance separated into $\Delta r_{\min}$, estimator-level error, and CRB/FIM-style bounds, signal quality at an explicit reference plane, and the channel/scenario assumptions that govern comparability. Recent calls for standardized VLC channel models and interoperability-oriented standardization reinforce the urgency of this unification.

e) Related Surveys and Gap Analysis: RF-ISAC already has a mature survey landscape, but optical ISAC remains comparatively underserved. Existing review-style work is still modality-centric: VLC surveys emphasize positioning and indoor propagation, fiber reviews focus on DFOS/DAS integration and co-route monitoring, and FSO or photonic-THz surveys discuss architectures, waveforms, and high-CRQ demonstrations without bridging the full FSO–fiber–VLC divide. Parallel primary studies continue to deepen individual silos, for example in movable VLC access, sensing-front-haul coexistence, and W-band fiber-wireless integration, but they still do not add up to a unified cross-modality survey layer. Within our 220-study corpus, only the VLC-based LiSAC review explicitly treats optical ISAC as its primary topic, and even that work remains single-modality and non-PRISMA. RIS-for-ISAC surveys provide useful enabling-technology context but remain RF/THz-centric. Table I summarizes this landscape.

II. BACKGROUND AND METRIC-GOVERNANCE CONTRACT

An O-ISAC system can be represented as a source, modulation and waveform resources, a propagation medium, receiver observables, and communication/sensing estimators. This abstraction is useful only if the receiver and propagation planes remain explicit. Coherent optical receivers preserve complex-field information and therefore support phase-sensitive observability, carrier recovery, and optical-plane signal-quality measures. IM/DD receivers expose intensity-domain observations after photodetection, so their noise, SNR, and estimator behavior are normally electrical-plane quantities [8], [10], [16], [39]–[41]. Treating these observation modes as equivalent would erase a primary source of metric mismatch.

Fig. 2 summarizes the common chain while retaining modality-specific branches. In guided fiber, the signal propagates through a dispersive and nonlinear medium, and sensing often emerges through distributed fiber-optic sensing, vibration monitoring, strain, temperature, or co-route infrastructure monitoring [6], [13], [42]–[45]. In FSO, atmospheric loss, turbulence, pointing, and geometry shape both rate and ranging behavior [7], [23], [46], [47]. In VLC/LiFi, Lambertian emission, LoS/NLoS composition, illumination constraints, and direct detection dominate the receiver-level model [8], [15], [16], [48]. In photonic-THz or hybrid systems, optical carriers may generate, distribute, or coherently receive high-frequency signals while wireless propagation occurs at mmWave/THz bands [1], [10], [49]–[52]. Table II condenses these modality differences into a compact comparison scaffold.

The metric contract in Table III is the main guardrail. Bandwidth-limited range resolution is

$$\Delta r_{\min} = \frac{v}{2B_{\text{eff}}}, \quad (1)$$

where $v = c$ for free-space two-way propagation and $v \approx c/n_g$ for guided media under the corresponding convention. This expression is a physical resolution limit tied to effective bandwidth. It is not the same as estimator accuracy, localization RMSE, or an empirical standard deviation. Accuracy terms such as σ_r and RMSE depend on SNR, geometry, estimator design, and the data model; CRB/FIM quantities are lower bounds under an explicit observation model and cannot be treated as measured error [17], [18], [53], [54].

The OSNR/SNR distinction is especially important. Coherent optical studies frequently report OSNR before or around optical reception, while VLC and many OWC studies report electrical SNR after photodetection [40], [41], [54], [55]. Converting one plane into another requires receiver bandwidth, noise-equivalent power, responsivity, filtering, and detection model assumptions. Without those fields, OSNR and SNR are contextual signal-quality indicators rather than a common axis.

Fiber spatial granularity is a second frequent source of unsafe comparison. Distributed fiber systems report gauge length, segment spacing, or spatial granularity Δz . These quantities describe how a guided fiber is interrogated along its length; they do not directly describe free-space range resolution. Conversely, wireless optical $\Delta r_{\min}$ follows a delay/ranging convention tied to B_{eff} . A fiber study can be highly valuable for O-ISAC without being a point on the same range-resolution plane as an FSO or photonic-THz ranging record [6], [13], [42].

For the governed synthesis, the capacity-resolution quotient is retained only as

$$\text{CRQ}_{\Delta} = \frac{R}{\Delta r_{\min}}, \quad (2)$$

and only when rate R and $\Delta r_{\min}$ are reported for the same scenario record. This is a conservative rule: it excludes tempting but invalid combinations of one paper's rate with another paper's sensing resolution or one experiment's throughput with a different mode's sensing metric. Section V uses this rule to show that the CRQ-valid subset is sparse, which is a reporting finding rather than a statement that O-ISAC lacks high-performing systems.

A. Receiver Observability and Measurement Planes

The most important conceptual distinction is receiver observability. A coherent receiver has access to phase and amplitude after optical mixing and balanced detection, so it can support measurements that rely on complex-field perturbations, carrier phase, coherent DSP, or optical-frequency stability. An IM/DD receiver instead observes intensity after photodetection; it is often simpler and highly relevant for VLC/LiFi and some OWC settings, but it changes the noise plane and the meaning of SNR. A camera-assisted visible-light system introduces another observation layer because the




Fig. 2. Unified O-ISAC source–channel–observation abstraction with modality-specific propagation and receiver planes retained.

TABLE II
MODALITY-AWARE O-ISAC ABSTRACTION.

Modality	Channel basis	Receiver/observable	Typical task	Governance warning
Fiber	Guided dispersive/nonlinear link; DAS/DFOS granularity	Coherent or direct optical/electrical plane	Vibration, strain, co-route monitoring	Report Δz and OSNR plane; do not call it wireless range resolution
FSO	LoS optical wireless with turbulence and pointing	Direct or coherent photodetection	Ranging, tracking, link adaptation	Geometry and weather condition admissibility dominate comparison
VLC/LiFi	Lambertian LoS/NLoS indoor optical wireless	Mostly IM/DD; sometimes camera-assisted	Localization and indoor sensing	Electrical SNR/RMSE cannot be merged with optical OSNR or CRB without model disclosure
Photonic-THz/hybrid	Optical generation/distribution plus mmWave/THz links	Coherent photonic, electronic, or hybrid chains	High-rate ranging and fiber-wireless transfer	Separate optical generation, wireless propagation, and post-detection planes

TABLE III
METRIC CONTRACT FOR ADMISSIBLE O-ISAC COMPARISON.

Metric object	Valid role	Must report	Forbidden shortcut
$\Delta r_{\min}$	Bandwidth-limited resolution	B_{eff} , propagation convention, scenario	Replacing RMSE or CRB with resolution
σ_r /RMSE	Estimator-level accuracy	estimator, SNR plane, geometry, dataset/simulation setup	Treating as bandwidth-only resolution
CRB/FIM	Bound context	observation model, parameters, noise statistics	Treating as measured accuracy
Δz	Fiber spatial granularity	gauge length/segment, interrogator assumptions	Treating as wireless range resolution
OSNR/SNR/ESNR	Signal-quality plane	optical/electrical reference point and bandwidth	Mixing planes without receiver/noise model
CRQ_{Δ}	Rate per bandwidth-limited resolution	matched R and $\Delta r_{\min}$ in one scenario record	Combining unmatched rate and sensing entries

sensor may report pixel-domain, image-domain, or geometry-derived quantities. These differences are not implementation details. They define which sensing metrics are meaningful and which conversions must be disclosed before comparison.

The measurement-plane issue appears repeatedly in O-ISAC reporting. A coherent fiber experiment can report OSNR and BER under an optical receiver model, while a VLC localization study may report electrical SNR, received optical

power, RMSE, and room geometry. A photonic-THz record may report optical carrier properties, generated high-frequency power, wireless propagation distance, de-chirped receiver metrics, and post-DSP rate. Each value can be correct, but the values do not share one reference plane. The contract in Table III therefore asks authors to tag the plane before using the metric in cross-paper synthesis.

B. Guided, Wireless, and Photonic-Bridge Regimes

The medium split is not cosmetic. Guided fiber is naturally suited to distributed infrastructure monitoring, long-haul or access transport, and co-route sensing. Its impairments include attenuation, dispersion, nonlinearities, polarization effects, laser phase noise, and interrogator limits. Wireless optical links, by contrast, are shaped by geometry, pointing, turbulence, blockage, ambient light, and field-of-view constraints. VLC/LiFi adds illumination, dimming, flicker, and human-environment constraints. Photonic-THz/hybrid systems bridge these regimes by using optics to generate, distribute, or process a high-frequency wireless carrier. This bridge class is powerful, but it can also hide where the rate is measured and where the sensing interaction occurs.

Because of these regime differences, the review avoids a single “best O-ISAC” comparison. A fiber record may be most relevant for power-grid corridors, submarine cables, or metropolitan transport sensing; an FSO record may be most relevant for ranging under clear LoS; a VLC/LiFi record may be most relevant for indoor localization; and a photonic-THz record may be most relevant for high-rate fiber-wireless links. The taxonomy and metric contract make these deployment roles visible before Section V compares any rate–sensing points.

C. Admissibility Before Optimization

Many O-ISAC papers formulate optimization problems for power allocation, waveform design, beam steering, or joint communication-sensing objectives. Those formulations are valuable, but this review does not use them as a common mathematical scaffold because their variables and constraints are modality-specific. A normalized VLC power-allocation problem, an FSO Fisher-information constraint, a fiber sensing-precompensation method, and a photonic-THz waveform design cannot be collapsed into one optimization without losing the measurement plane. The survey therefore places admissibility before optimization: first identify what was measured, where it was measured, and whether the communication and sensing values belong to the same scenario; only then interpret a tradeoff.

D. Additional Metric-Governance Detail

The contract can be read as a sequence of admissibility checks. First, the receiver observation must be identified. Coherent optical records retain complex-field information after optical mixing and balanced detection, whereas IM/DD records report intensity-domain or post-detection electrical observations. Second, the medium must be declared because the dominant impairment changes across guided fiber, FSO, VLC/LiFi, and photonic-THz or fiber-wireless chains. Third, the sensing metric must be assigned a role: a bandwidth-limited resolution, an estimator-level error, a bound-level statement, or a guided-medium spatial granularity. Only after those fields are known can a communication rate be paired with a sensing metric.

This sequence is stricter than many individual papers require, but it is necessary for survey synthesis. A coherent

fiber paper may correctly report BER versus OSNR and spatial granularity along a cable, while an indoor VLC paper may report localization RMSE versus electrical SNR after photodetection. Both are valid O-ISAC evidence, but they do not share a common signal-quality plane or sensing axis. Similarly, a photonic-THz record may use optics for carrier generation and distribution while the sensing interaction occurs in a high-frequency wireless segment; the rate, bandwidth, receiver, and ranging metric must therefore be read at the correct stage of the chain.

The same caution applies to integration mechanisms. Shared waveform, shared hardware, shared time/frequency resources, shared processing, and shared front-end control are different forms of integration rather than a single maturity ladder. A communication-centric design may let sensing reuse a data waveform; a sensing-centric design may embed communication into a probing waveform; a joint design may tune waveforms, beams, or resources for both services. These operating intents are useful descriptors, but they are not a basis for pooling metrics unless the scenario and measurement planes also match.

For this reason, the review keeps the mathematical layer compact. We retain only the bandwidth-to-resolution relation in (1), the guarded CRQ definition in (2), and the taxonomy vector introduced later in (3). Fiber dispersion, nonlinear propagation, OPA steering, ORIS channel models, and multi-objective optimization formulations are discussed as modality- or enabler-specific context rather than restored as common equations in the main text. The larger notation, acronym, and auxiliary mathematical scaffolds remain in the supplementary material.

The practical effect of the contract is conservative exclusion, not evidence loss. If a record reports only fiber Δz , it can support the taxonomy, application map, and enabler discussion, but it cannot be used as a wireless $\Delta r_{\min}$ point. If a paper reports a CRB without the observation model needed to interpret the bound, it remains bound-level evidence rather than measured accuracy. If a study reports rate and sensing values in different scenarios, the values remain useful individually but are not merged into a CRQ point. Section V applies these checks to the extracted scenario ledger.

III. REVIEW METHODOLOGY

This review follows PRISMA 2020 and PRISMA-S search-reporting principles. The protocol was registered with OSF on February 12, 2026 (Registration ID: 7F6wb), and the formal database search used IEEE Xplore, Scopus, and Web of Science. The canonical search was frozen on November 30, 2025. Supplementary preprint monitoring and version tracing were retained for audit purposes, but the canonical PRISMA flow reported here is based on the peer-reviewed database record.

The search blocks combined optical-domain terms, ISAC/JCS terminology, modality-specific terms for fiber, FSO, VLC/LiFi, LiDAR, photonic-mmWave, and photonic-THz systems, and sensing/communication terms. Full search strings are kept in the supplementary evidence package to avoid

TABLE IV
COMPACT ELIGIBILITY CRITERIA USED FOR STUDY SELECTION.

Criterion	Include	Exclude
Topical scope	Optical, fiber, FSO, VLC/LiFi, photonic-mmWave/THz, or hybrid systems with both sensing and communication relevance	Pure communication, pure sensing, or non-optical RF-only ISAC without optical relevance
Evidence type	Peer-reviewed articles, conference papers, and survey/review works needed for context	Editorial-only, incomplete metadata, inaccessible, or duplicate records outside the audit ledger
Synthesis value	Reports architecture, metric, modality, experiment/simulation, or application information usable for taxonomy/TQAF extraction	No usable O-ISAC extraction fields after full-text assessment




Fig. 3. Compressed PRISMA flow for the final O-ISAC corpus.

spending main-text pages on reproducibility mechanics. The main manuscript instead reports the database set, freeze date, eligibility rationale, extraction fields, and the corpus-level synthesis logic. Table IV summarizes the eligibility boundary used to preserve optical relevance while retaining the field’s fragmented terminology.

Eligibility was intentionally broad enough to capture the fragmented vocabulary of the field but narrow enough to exclude pure optical communications, pure sensing, and RF-only ISAC papers that do not inform optical modality synthesis. During full-text assessment, 222 papers were assessed and 2 were excluded, giving a final included corpus of $N = 220$ peer-reviewed studies. Fig. 3 summarizes this final PRISMA flow, and the two full-text exclusions and their reasons are preserved in the structured exclusion ledger.

The TQAF appraisal used five dimensions: topical fit, metric transparency, modality/implementation clarity, methodological reproducibility, and contribution relevance to cross-modality synthesis. This appraisal was not used to create a single quality score that ranks papers; instead, it informed how strongly each record could support taxonomy, metric-governance, enabler, application, or roadmap claims. Simulation-only, experiment-only, and review-style records can all be useful, but they support different kinds of statements.

No statistical meta-analysis is attempted. O-ISAC studies do not yet report enough matched scenarios, common endpoints, uncertainty fields, or receiver-plane details to support pooled effect sizes. The appropriate synthesis is therefore structured and governed: the extraction ledger feeds the taxonomy in Section IV, while scenario-level rate and sensing metrics feed the governed tradeoff synthesis in Section V. The complete 220-study included-corpus ledger, extraction sheet, and supplementary evidence records are provided in the public repository / Zenodo package (Zenodo DOI: 10.5281/zenodo.19643231; repository: OISAC_PRISMA_COMST).

A. Extraction Fields and Evidence Use

Each included record was read for two complementary purposes. The first purpose was descriptive: identify the optical

medium, integration mechanism, receiver/observability class, sensing task, communication metric, sensing metric, and deployment domain. These fields support the taxonomy and the application map. The second purpose was analytical: identify whether a paper reports matched communication and sensing quantities under a scenario that can enter governed rate-resolution or rate-accuracy synthesis. A paper can therefore be important to the review even if it does not enter the Section V point cloud. For example, a review or device-oriented paper may support the enabler or roadmap synthesis, while a detailed experimental paper may support scenario-level tradeoff extraction.

The TQAF process was used as a traceability device rather than a ranking device. Records with unclear receiver planes, missing bandwidth conventions, or incomplete sensing definitions were not discarded automatically; instead, their claims were limited to the evidence role they could support. This is why the review distinguishes corpus membership from governed metric availability. The PRISMA corpus establishes the systematic review boundary, while the metric contract determines which subset can support direct cross-paper numerical comparison.

B. Why the Corpus Ledger Remains Outside the Main Reference List

The complete 220-study corpus is a systematic-review asset, but printing all 220 records in the main bibliography is not the best use of a COMST page budget. The main text therefore cites representative and load-bearing studies, while the full corpus remains traceable through the included-corpus ledger, extraction sheet, and supplementary evidence records. This separation protects systematic-review reproducibility while keeping the main bibliography focused on studies that directly support the narrative, taxonomy, enablers, applications, or governed metric synthesis.

C. Additional Methodological Detail

This systematic review adheres to the **Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) 2020** statement and the PRISMA-S extension for literature search reporting. To ensure transparency and minimize reporting bias, the study protocol, including research questions, search strategy, and eligibility criteria, was registered with the **Open Science Framework (OSF)** on **February 12, 2026** (Registration ID: 7f6wb). The protocol and associated metadata are accessible via the OSF Registries at <https://osf.io/7f6wb>. No substantive

amendments to the registered objectives, eligibility criteria, canonical information sources, or synthesis plan were made after registration; scope clarifications in the frozen manuscript were reporting-level clarifications only and did not alter the registered review workflow. The objective of this review is to systematically identify, screen, assess, and synthesize primary O-ISAC studies across fiber, free-space optical, VLC/LiFi, and photonic-THz platforms, with emphasis on taxonomy, metric governance, enabling technologies, applications, and open challenges.

A comprehensive literature search for the formal PRISMA identification stage was conducted across three engineering and physics databases: **IEEE Xplore**, **Scopus**, and **Web of Science**, all last searched on **November 30, 2025**. These three databases defined the canonical formal identification stage for the frozen PRISMA flow reported in this review. Supplementary search templates were retained for **arXiv** and **TechRxiv** to support preprint monitoring and version tracing, but these supplementary sources did not contribute separate records to the canonical PRISMA flow reported in this review (`other_sources_results = 0`).

The search strategy employed two mandatory concept blocks and one optional refinement block:

- 1) **Integrated Sensing and Communication Concepts:** Terms such as “integrated sensing and communication”, ISAC, “joint sensing and communication”, and related variants.
- 2) **Optical Medium Terms:** Terms restricting retrieval to optical carriers and platforms, such as optical/photonic, fiber/fibre, FSO, VLC, LiFi, and LiDAR.
- 3) **Physical-Layer Refinement (Optional):** Additional terms such as waveform, modulation, signal model, channel model, or optical front-end, used only when a database required extra disambiguation.

Consistent with the registered eligibility policy, the formal database searches were restricted to **English-language** records and to **peer-reviewed journal articles** or **full-length conference/proceedings papers** where platform filtering was available. The search coverage extended from **2000** to the **November 30, 2025** freeze date in order to retain protocol-eligible foundational optical studies that predate current O-ISAC terminology, while the synthesis remained centered on the **2020–2025** core window.

The exact executed search strings were preserved in the study records for auditability and methodological traceability. The search-stage evidence supporting the frozen PRISMA identification record, including reconstructed aggregate logs and audit notes where the original freeze-time raw exports were incomplete, was archived in the supplementary evidence package prepared for this review. The literature search was frozen as of **November 30, 2025**.

To ensure the review’s coherence and focus on the *optical* domain, strict inclusion and exclusion criteria were applied.

Inclusion Criteria:

- **Domain:** Systems utilizing optical carrier frequencies (infrared, visible, or ultraviolet) for *both* sensing and communication.

- **Integration:** Studies proposing shared hardware, spectrum, or waveforms (True O-ISAC) or coordinated coexistence.
- **Content and Time Frame:** Peer-reviewed journal articles and full-length conference papers providing technical depth on physical/link-layer architecture, performance limits, or experimental validation, primarily focused on the **2020–2025** period.

Within this scope, the final corpus is centered on the 2020–2025 period but retains a small number of earlier protocol-eligible foundational studies. Photonic-THz or hybrid entries were included only when an optical carrier or photonic front end remained integral to both sensing and communication; RF-only THz studies were excluded. Borderline records were retained when the optical carrier or photonic front end remained integral to both sensing and communication, even if the work was not explicitly labeled as O-ISAC; by contrast, optical links performing only auxiliary channel estimation, alignment, or beam tracking for communication maintenance were not treated as eligible joint sensing-and-communication studies.

Exclusion Criteria:

- **RF-Only:** ISAC systems operating solely in radio frequency/microwave/THz bands without an optical component.
- **Disjoint Functionality:** Pure sensing (e.g., standard LiDAR) or pure communication (e.g., standard FSO) papers without integration mechanisms.
- **Type:** Short abstracts, non-English publications, and grey literature (theses, white papers) lacking peer review.

Study selection followed a three-step PRISMA workflow:

- 1) **Deduplication:** Semi-automated identification and removal of duplicate candidates across databases using DOI-first and normalized-title metadata matching, supplemented by publication-year/author consistency checks and manual verification of ambiguous matches.
- 2) **Screening:** Title and abstract screening to remove clearly irrelevant (e.g., RF-only or biomedical sensing) records.
- 3) **Eligibility:** Full-text review of candidate papers against the inclusion criteria.

Following the registered protocol, two reviewers first calibrated the eligibility criteria on a pilot sample of 50 records, then independently conducted title/abstract screening and full-text eligibility assessment. Any record marked as *Include* or *Unsure* by at least one reviewer advanced to full-text review. Disagreements were resolved by consensus discussion and, where needed, third-reviewer arbitration, with adjudications archived in the structured screening logs.

The canonical aggregate PRISMA counts were maintained in a structured screening ledger and reconciled against stage-specific audit records. For the upstream stages, the identification, deduplication, and title/abstract totals were retained as canonical aggregate counts supported by the reconstructed search-stage evidence package; for the later stages, the full-text assessment, exclusion, and final inclusion ledgers were directly row-backed in the repository. In the reconciled record,

222 full-text articles were assessed, 2 were excluded at the full-text stage, and the final included corpus comprised $N = 220$ studies. The two reconciled full-text exclusions, together with their study identifiers, exclusion codes, and reasons, were retained in the structured exclusion log and mirrored in the supplementary exclusion appendix prepared for this review. In the present manuscript, the bibliography is representative rather than exhaustive: the main text cites load-bearing and illustrative studies, while the complete 220-paper corpus remains preserved in the structured screening archive, included-studies ledger, and supplementary evidence package.

Data extraction was performed using a standardized structured schema to rigorously map the O-ISAC landscape. Following the registered schema-driven workflow, two reviewers verified the core study descriptors, taxonomy-critical classifications, and synthesis-critical performance fields, and any ambiguous extractions were reconciled by consensus review rather than silent inference. Key extracted variables include modality coverage (categorizing fiber, FSO, VLC/LiFi, or hybrid regimes), integration depth (distinguishing true waveform/hardware sharing from resource coexistence), quantitative performance metrics (capturing sensing resolution and range alongside communication data rate and BER), and validation level (coding empirical evidence as simulation, experiment, prototype, or analytical). Values not explicitly reported in the source study were retained as unfilled/NR-type fields in the structured extraction records rather than being imputed from conjecture. This structured extraction directly feeds the quantitative trade-off frontiers evaluated in Section V.

To assess the reliability of the surveyed literature, we developed a custom **Technical Quality Assessment Form (TQAF)**. Each included study was evaluated independently by two reviewers across five formal dimensions:

- 1) **Modelling Fidelity:** Realism of channel and noise models, and their suitability for physical/link-layer evaluation.
- 2) **Experimental Validity:** Presence of hardware proof-of-concept versus pure analytical simulation.
- 3) **Metric Completeness:** Reporting of joint sensing and communication metrics versus cherry-picked single-function reporting.
- 4) **Reproducibility:** Explicitness of parameter assumptions and availability of code or datasets.
- 5) **Clarity:** Clear definition of assumptions and physical limitations.

Each dimension was scored on a 0–2 scale (low/moderate/high quality). Any scoring disagreements were resolved by consensus discussion or third-party arbitration. While TQAF scores did not determine study exclusion, they are used throughout Sections IV, VI, and VIII to formally weight the strength of evidence, highlighting methodological gaps where high-impact claims lack rigorous validation.

IV. UNIFIED O-ISAC TAXONOMY

The taxonomy is designed to make cross-modality comparison possible without hiding ambiguity. Each paper p is mapped

as

$$T(p) = (m(p), i(p), d(p), s(p)), \quad (3)$$

where m is medium class, i is integration class, d is detection/observability class, and s is sensing task. These axes were selected because they determine whether two reported performance points can be compared at all. Medium captures the propagation substrate. Integration captures how communication and sensing share waveform, hardware, resource, or processing layers. Detection/observability captures whether the receiver sees direct intensity, coherent field information, camera/Rydberg/other observations, or a mixed chain. Sensing task captures what is being estimated. Fig. 4 is retained as the single main-text taxonomy map; Table V gives the compact corpus-level summary.

The medium axis is the first filter. Fiber O-ISAC is the guided anchor of the corpus, with 45 records. It includes distributed acoustic sensing, OFDR/DFOS-style monitoring, coherent communications with embedded sensing pilots, multicore or co-wavelength coexistence, and cabled infrastructure monitoring [6], [13], [21], [22], [42], [56]–[58]. The key interpretation rule is that fiber evidence is not a wireless ranging baseline. It is a guided-medium integration story in which OSNR, gauge length, spatial granularity, and interrogator assumptions often carry more meaning than free-space $\Delta r_{\min}$.

FSO O-ISAC contains a smaller but important group of wireless optical records. It is strongly ranging-oriented and highly sensitive to link geometry, weather, turbulence, pointing, and blockage. FSO studies include DCO-OFDM, OCDM/FMCW-style waveform design, power allocation, remote phase-shift LiDAR with communication, retroreflective links, and UAV-aided or mixed FSO-RF designs [7], [23], [46], [47], [59]–[63]. Because FSO observability may be direct or coherent, its comparisons must remain receiver-model conditioned.

VLC/LiFi O-ISAC is the most direct-detection-heavy class. It includes indoor positioning, visible-light positioning and communication, LED-based joint systems, camera-assisted variants, gesture recognition, and multi-task learning under visible-light constraints [4], [5], [8], [15]–[18], [20], [48], [64]–[66]. The evidence is often rich for localization and indoor services, but it is tied to illumination geometry, Lambertian channel assumptions, electrical SNR, and direct-detection noise. Those assumptions make VLC/LiFi valuable but not directly poolable with coherent fiber or photonic-THz records.

Photonic-THz and hybrid O-ISAC form the bridge class. The optical carrier may drive high-frequency generation, local oscillator distribution, fiber-wireless transport, coherent de-chirping, or THz-over-fiber operation, while the sensing target may lie in a high-frequency wireless channel [1], [9]–[12], [14], [49]–[52], [67], [68]. This class is especially tempting for rate–resolution headlines, so it requires strict plane separation: optical generation/distribution evidence, wireless propagation evidence, and post-detection signal-quality evidence are not the same object.

The integration axis distinguishes shared waveform, shared hardware, shared resources, and shared processing. Shared-




Fig. 4. Semantic taxonomy map retained as the single main-text taxonomy figure.

TABLE V
COMPACT TAXONOMY SUMMARY ACROSS THE $N = 220$ CORPUS.

Medium	Corpus share	Dominant detection	Dominant task	Governance warning
Fiber	45/220	Coherent-leading, with direct tail	Range/vib. monitoring	Compare using guided-channel and Δz /OSNR semantics
FSO	19/220	Mixed direct/coherent	Ranging-heavy	Condition on geometry, turbulence, and pointing assumptions
VLC/LiFi	25/220	Direct IM/DD	Localization and ranging	Electrical-plane accuracy dominates; do not infer optical OSNR behavior
Photonic-THz / hybrid	116/220 hybrid; 39 photonic-THz anchors	Near-balanced coherent/direct	Ranging-heavy, multi-task tail	Separate optical generation/distribution from wireless propagation and receiver plane

waveform papers include OFDM/LFM/OCDFM/OTFS-like structures where the same waveform carries communication and sensing information [23], [69]–[75]. Shared-hardware records expose common apertures, front-ends, photonic chips, or fiber links [54], [76]–[81]. Shared-resource and shared-processing records express integration through time/frequency/power scheduling, beamforming, or inference pipelines [82]–[91].

The detection/observability axis prevents receiver-plane collapse. Direct IM/DD and coherent detection dominate the corpus, but the residual categories matter because they show that the field is not limited to a binary receiver taxonomy [10], [39], [40], [92], [93]. The sensing-task axis similarly separates ranging, localization, vibration/strain, environmental monitoring, object/gesture detection, and multi-task perception. Ambiguous records are retained with explicit tags rather than forced into a single dominant bucket. As a result, the taxonomy reports evidence concentration, not superiority.

A. Taxonomy as a Guardrail, Not a Ranking

The taxonomy is intentionally conservative. Its purpose is not to decide whether fiber, FSO, VLC/LiFi, or photonic-THz is the strongest O-ISAC platform. Each medium is solving a different version of the joint sensing-communication problem. Fiber has strong infrastructure relevance and mature optical transport machinery, but its sensing axis is often distributed and guided. FSO has clearer free-space ranging relevance but is highly scenario-sensitive. VLC/LiFi has a strong indoor localization and service-integration story but is dominated by direct-detection and illumination constraints. Photonic-THz/hybrid systems offer impressive rate and resolution demonstrations, yet they mix optical and wireless stages and therefore demand careful plane annotation.

The same logic applies to the integration axis. A shared waveform does not necessarily imply shared hardware, and a shared front-end does not necessarily imply a single optimization objective. Some papers integrate by embedding sensing pilots into communication signals. Others integrate

by reusing optical carriers, apertures, front-end components, time-frequency resources, or DSP pipelines. The taxonomy keeps these mechanisms distinct because they create different tradeoffs. A shared waveform can create interference between sensing and communication symbols; shared hardware can create calibration and impairment coupling; shared resources can create scheduling tradeoffs; shared processing can create dataset and inference dependencies.

B. Detection and Task Axes

Detection/observability is the axis most closely tied to metric governance. Coherent systems may support phase-sensitive ranging, vibration, or de-chirping, while direct-detection systems may be more natural for intensity-domain localization, received-signal-strength inference, or simple ranging. A camera-assisted visible-light system may extract geometry in a different way again. For this reason, the taxonomy does not report direct and coherent systems as interchangeable variants of one receiver. They define different admissible comparisons.

The sensing-task axis further limits generalization. Ranging, localization, vibration, strain, environmental monitoring, gesture recognition, and target detection do not share one performance unit. A localization RMSE in an indoor VLC room is not a substitute for a fiber vibration spatial granularity, and neither is directly comparable with a photonic-THz range resolution unless the scenario and metric role are explicit. This is why later sections phrase application evidence as deployment motifs and Section V separates rate- $\Delta r_{\min}$, rate- σ_r , and full-triplet subsets.

C. How Ambiguity Is Retained

Some records legitimately span multiple axes. A hybrid fiber-wireless paper may include optical generation, fiber distribution, wireless propagation, coherent reception, and DSP-based sensing. A VLC paper may combine direct photodiode reception with image-sensor or camera-assisted observability. A fiber study may report communication BER, OSNR, vibration recovery, and spatial granularity under one architecture. Rather than force such records into a single label, the extraction retains the dominant class and records ambiguity where it affects comparison. The result is a taxonomy that supports cautious synthesis and preserves the warning that prevalence is evidence concentration, not superiority.

D. Additional Axis-Level Taxonomy Detail

Section IV builds a unified O-ISAC taxonomy for cross-modality synthesis rather than modality ranking. Across the $N = 220$ corpus, the taxonomy is designed to satisfy three requirements simultaneously: cross-modality comparability, evidence traceability, and consistency with the Section II measurement-plane and metric-role contract. In practice, this means that studies are compared only after substrate, integration architecture, observability conditions, and sensing objective are explicitly aligned; otherwise the comparison is withheld or conservatively qualified.

To enforce deterministic synthesis, each study p is mapped to

Here, $m(p)$ denotes medium class, $i(p)$ integration class, $d(p)$ detection/observability class, and $s(p)$ sensing-task class. The four axes isolate the main comparability conditions in the corpus: medium captures propagation substrate, integration captures coupling architecture, detection captures receiver observability, and task captures sensing objective. At corpus level, the dominant states are hybrid 116/220, fiber 45/220, VLC/LiFi 25/220, and FSO 19/220 for medium; shared front-end 194/220 for integration; direct 118/220 and coherent 97/220 for detection; and ranging 162/220 for task. These counts indicate evidence concentration, not superiority, and they remain the basis for conditioned synthesis in the later sections.

Deterministic mapping is necessary because many O-ISAC papers report multi-stage systems, multi-task outcomes, or partially implicit measurement assumptions. The mapping pipeline therefore prioritizes structured descriptors, uses textual fallback only when needed, preserves multi-task labels while assigning one primary tabulation label, keeps hybrids explicit, normalizes labels before aggregation, and retains contradictions as flagged ambiguity rather than hiding them.

Measurement-plane governance follows the Section II contract:

No implicit OSNR-to-SNR substitution is allowed without an explicit receiver/noise model, and metric governance is equally strict: $\Delta r_{\min}$ and σ_r are not aliases and are pooled only within role-consistent subsets. In the current corpus, 84 ambiguity cases are retained under this contract, including 75 metric-aliasing cases and 9 measurement-plane ambiguity cases. That conservatism is intentional because it preserves auditability instead of inflating apparent agreement.

This operational contract binds axis assignment, deterministic mapping, and comparability protection.

Lesson (A): Unified O-ISAC taxonomy is defensible only when four-axis classification, deterministic mapping, and measurement-metric governance are enforced jointly under explicit ambiguity retention.

Section IV-B instantiates Axis 1 by grouping studies according to normalized medium labels and then conditioning mechanism, detection, and task interpretations on that grouping. Five classes dominate the corpus: hybrid 116/220 (52.7%), cabled fiber 45/220 (20.5%), VLC/LiFi 25/220 (11.4%), FSO 19/220 (8.6%), and terahertz 1/220 (0.5%), with the remaining 14/220 records forming a heterogeneous long tail. Shared front-end integration is common across the main classes, but detection and task profiles remain medium-dependent: cabled fiber is coherent-leaning, VLC/LiFi is strongly direct-detection dominant, FSO is mixed but ranging-heavy, and hybrid remains the main bridge class. Throughout this subsection, medium share is interpreted only as evidence concentration, and all comparisons remain subject to the Section II plane and metric-role guards.

Table V summarizes medium-based taxonomy classes, corpus share, and dominant operational profiles.

The cabled-fiber class is the guided-medium anchor of O-ISAC. In the corpus it covers 45 records (20.5%), is predominantly shared front-end (43/45), and is coherent-leading (27 coherent versus 18 direct), with a task profile centered

on ranging (27) and a visible vibration tail (8). Accordingly, fiber evidence is interpreted as communication-sensing co-design under guided-channel assumptions rather than as a direct wireless baseline, and all fiber comparisons preserve explicit plane semantics and the separation between resolution-type and accuracy-type metrics.

FSO covers 19 records (8.6%), remains mostly shared front-end (14/19), and is mixed in detection with a direct lead (11 direct, 8 coherent). Its task profile is tightly centered on ranging (18/19), so cross-class interpretation should treat FSO as ranging-dominant and observability-mixed rather than extrapolating from either direct-only or coherent-only behavior. Recent records in this class include remote phase-shift LiDAR, retroreflective OFDM/TDD links, and UAV-aided retroreflective platforms, all of which reinforce the class's geometry-conditioned ranging emphasis. As in the rest of Section IV, direct/coherent outcomes are not merged when metric definitions diverge, and accuracy is not inferred from resolution.

VLC/LiFi contributes 25 records (11.3%), is mostly shared front-end (18/25), and is overwhelmingly direct-detection based (24/25). Its task profile splits between ranging and a strong localization tail, making it the most localization-oriented class among the main wireless media. Visible-light evidence further includes PAM-based joint waveforms, Lambertian calibration, indoor localization services, and camera-assisted optical sensing/communication variants, all consistent with direct-detection and localization-heavy operation. That emphasis, however, remains tied to intensity-domain observability, so VLC/LiFi comparisons against coherent-leading classes require explicit receiver-model conditioning and preserve the Section II separation between resolution and accuracy.

Photonic-THz is best read as a bridge class rather than a self-contained medium bucket. The explicit terahertz label appears only once in the corpus, but anchor-level evidence is broader: among 39 papers with direct photonic-THz anchors, 31 are mapped to hybrid labels and only one to explicit terahertz. Anchor evidence also includes photonic-THz system overviews, 60-GHz photonic joint radar-communication, and recent W-band or THz demonstrations that combine ranging with flexible communication, which underscores that the class is operationally photonics-assisted rather than a standalone wireless-only bucket. For that reason, Section IV uses terahertz as a proxy class while interpreting most photonic-THz system behavior jointly with the hybrid evidence, under the same stage-aware ban on implicit cross-plane substitution.

Hybrid systems are the structural core of the corpus, accounting for 116/220 records (52.7%). They are strongly shared-front-end (106/116), near-balanced in coherent/direct detection (59/53, plus four residual labels), and ranging-dominant (95) while still carrying the broadest multi-task tail. That makes hybrid evidence the main bridge for transferability analysis, but only under full axis conditioning; cross-link reports that mix measurement planes or blur resolution and accuracy remain constrained evidence rather than pooled performance.

Shared-waveform integration has 34 unique papers under

combined direct+indirect support (13 direct-only), placing it below shared resources but above shared hardware. It is most naturally associated with high-coupling operating points in hybrid and cabled-fiber settings, although the separate-front-end shares in VLC/LiFi and FSO show that waveform unification is not required for integration. Its main value is tight joint reuse of signal degrees of freedom under explicit receiver and metric assumptions. Recent explicit examples include OFDM-LFM lidar-communication design, polarization-fraction-domain multiplexing through telecom pilots, and photonics-aided LFM CW-style mmWave signaling, all of which make waveform structure the primary coupling interface between sensing and communication.

Shared-hardware integration is the sparsest explicit mechanism class, with 15 unique papers under combined support and 5 direct-only anchors. The low concept-level support does not contradict the prevalence of shared front-end labels; rather, it shows that explicit hardware-sharing articulation is selective and should be read through implementation pragmatics such as impairment co-propagation, synchronization, and calibration burden rather than as a generic property of all shared-front-end systems. Representative hardware-centric records include heterogeneous III-V-on-SOI transmitters and monolithic III-nitride chip/circuit realizations, which make the integration claim concrete at device and photonic-platform level rather than only at block-diagram level.

Shared resources is the most explicit mechanism class, with 43 unique papers under combined support and 16 direct-only anchors. Its high support is consistent with VLC/LiFi and FSO settings where integration often occurs through time/frequency/power coordination rather than full hardware unification, but the mechanism also appears in shared-front-end-dominant classes. It should therefore be read as a control-plane mechanism spanning both co-designed and coexistence architectures, with outcomes governed mainly by contention and scheduling quality. The same control-plane interpretation is visible in low-altitude optical backbone studies, AI-enhanced fiber-wireless mobility support, and confluent edge-network coordination, where integration value is expressed through resource orchestration and network-state adaptation rather than through a single shared transceiver chain.

Shared processing has 30 unique papers under combined support and 8 direct-only anchors. It is less explicit than shared resources but remains materially represented, especially in hybrid-dominant settings where multi-stage pipelines benefit from joint inference. Its main contribution is algorithmic coupling across decoding and sensing inference, but any reported gain still depends on transparent model assumptions and robustness to task interference. Recent processing-centric examples include multimodal perception fusion for beam-forming, RF-to-LiDAR digital-twin inference, and learning-assisted photonics W-band ISAC reception, which all treat shared inference as a first-class integration layer rather than a downstream add-on.

This subsection instantiates Axis 3 by formalizing how detection model and signal observability constrain valid comparison. In the $N = 220$ corpus, detection labels are concentrated in direct 118/220 and coherent 97/220, with only five residual

records across unknown, other, envelope-detection, and MIMO labels. Structured receiver typing is populated in 218/220 records, so Axis 3 assignment is nearly fully deterministic. As elsewhere in Section IV, these counts indicate evidence concentration rather than superiority.

The taxonomy discussion below summarizes detection and observability classes, evidence intensity, and governance implications.

IM/DD and coherent detection are not interchangeable because they expose different observables and therefore different estimator and impairment sensitivities. At taxonomy level they account for 215/220 records, while medium-conditioned counts show coherent-leading fiber, direct-heavy VLC/LiFi, mixed FSO, and near-balanced hybrid profiles. At concept-evidence level, the corpus contains 29 unique papers with IM/DD support and 45 with coherent-detection support. These regimes are therefore compared only as model-conditioned contrasts with explicit receiver/noise alignment. The binary split also has a meaningful structured tail: records built around Rydberg-atomic reception or all-optical inference paths show why low-support receiver classes should be retained rather than force-mapped into the dominant bins.

Observability class determines which information is directly measurable and therefore which estimation structures are admissible. Intensity-only reporting is much more common than explicit complex-field reporting (118 versus 17 unique papers under combined support), but this asymmetry reflects corpus composition rather than intrinsic superiority. The practical consequence is that identical task labels such as ranging or localization can encode different uncertainty behavior depending on whether phase is directly observable, so observability remains a required conditioning variable in any cross-task or cross-medium aggregation. Beam-scanning and angle-oriented optical studies further show that observability depends on whether the platform exposes direct intensity cues, field-aware optical processing, or geometry-conditioned scan responses.

V. COMMUNICATION-SENSING TRADEOFF SYNTHESIS

The governed tradeoff synthesis is the core analytical contribution. The extraction produced 225 scenario points from the $N = 220$ paper corpus. Raw metric coverage initially appears broad because many papers report at least one communication metric and at least one sensing metric. Under the governance contract, however, a point is usable only when the relevant metrics belong to a compatible scenario record and the metric role is clear. After filtering, only 20 scenario records support rate plus $\Delta r_{\min}$, only 16 support rate plus σ_r /RMSE, and only 13 support the full rate- $\Delta r_{\min}$ - σ_r triplet. This attrition is the central result.

The first governed view uses rate and $\Delta r_{\min}$. This view is admissible for records that disclose a bandwidth-limited resolution quantity tied to the same scenario as the reported rate. Photonic-THz and fiber-wireless demonstrations are prominent in this view because they often report high rates and fine delay/ranging resolution in one experiment [1], [9]–[12], [14], [49], [51], [52]. Yet even here, the evidence is sparse compared

with the full corpus, and the view should not be interpreted as a universal frontier.

The second governed view uses rate and σ_r /RMSE. This view is different because it is estimator-level and often geometry- or SNR-dependent. VLC/LiFi localization and FSO resource-allocation studies can be important here, but only when the estimation metric, scenario, and signal-quality plane are clear [7], [8], [15], [17], [18], [48], [54], [83]. A small σ_r value is not automatically comparable with a small $\Delta r_{\min}$, and a CRB/FIM bound is not a measured RMSE. Fig. 5 therefore separates the operating clouds rather than overlaying all sensing values.

Table VII highlights why naive pooling is unsafe. Fiber records can dominate communication capacity or infrastructure monitoring relevance, but their sensing granularity and OSNR semantics differ from wireless range/accuracy metrics [13], [21], [29], [57], [58]. Wireless optical records often expose clearer ranging/localization tasks but are more sensitive to geometry, channel, and receiver assumptions [7], [8], [23], [46], [47], [94]. Photonic-THz/hybrid records provide many high-rate, high-frequency anchors, but they mix optical and wireless stages and must be read through the measurement-plane contract [10], [14], [49]–[52].

The CRQ-valid subset is therefore sparse and illustrative. CRQ is informative when R and $\Delta r_{\min}$ are matched, but it is not a stable design envelope for the field. The current evidence says more about reporting practice than about ultimate physical limits: many O-ISAC studies do not report the rate, bandwidth-limited resolution, estimator-level accuracy, receiver plane, and scenario fields needed for full cross-metric synthesis. A future benchmark culture should close this reporting gap before broad optical-ISAC frontiers are claimed.

A. Why Raw Coverage Overstates Comparability

If one counts only whether papers mention communication and sensing, the O-ISAC evidence base appears much denser than it is. Many records report a rate, BER, SE, throughput, OSNR, received power, or modulation result, and many also report a sensing quantity. The difficulty is that these quantities are often not attached to the same scenario, not expressed in the same metric role, or not accompanied by enough receiver-plane detail. A paper may report a communication rate in one operating mode and a sensing resolution in another; another may provide a CRB curve without measured accuracy; a third may report fiber spatial granularity and communication OSNR but no wireless range-resolution equivalent. These are useful results, but they cannot all enter a single frontier.

The governed attrition in Table VI should therefore be read as a reproducibility signal. The field is not short of promising demonstrations. It is short of reporting patterns that allow the demonstrations to be compared without hidden substitutions. The 20 rate- $\Delta r_{\min}$ points are the subset in which a rate and a bandwidth-limited resolution are co-reported with sufficient scenario alignment. The 16 rate- σ_r /RMSE points are the subset in which rate and estimator-level accuracy are co-reported. The 13 full-triplet records are the most conservative subset because they support both physical-resolution and estimator-accuracy readings.

TABLE VI
GOVERNANCE ATTRITION FROM REPORTED METRICS TO ADMISSIBLE SYNTHESIS.

Evidence layer	Available count	Main retained use	Main attrition cause
Scenario records	225	Corpus-level context	Heterogeneous reporting and modality planes
Rate + $\Delta r_{\min}$	20	CRQ-admissible resolution view	Missing matched bandwidth-limited resolution
Rate + σ_r /RMSE	16	Accuracy-conditioned operating view	Missing estimator/SNR/geometry detail
Full triplet	13	Most conservative cross-metric subset	Rate, resolution, and accuracy rarely co-reported




Fig. 5. Governed rate-resolution and rate-accuracy operating clouds after metric-role filtering.

TABLE VII
GOVERNED FIBER, WIRELESS, AND HYBRID SLICES.

Slice	Strong evidence	Weakness for pooling	Main reading
Fiber	Tb/s-class links and distributed sensing [13]	Δz and OSNR differ from wireless range/ESNR	Guided infrastructure anchor
Wireless optical	FSO/VLC ranging/localization and OPA links [7], [54]	Geometry, turbulence, ambient light, and estimator differences	Scenario-conditioned tradeoff
Photonic-THz/hybrid	High-rate photonic generation plus mmWave/THz ranging [10], [14]	Optical and wireless planes can be conflated	Bridge class, not a single medium

B. Resolution, Accuracy, and Bound-Level Evidence

The separation between $\Delta r_{\min}$, σ_r /RMSE, and CRB/FIM is not semantic hair-splitting. $\Delta r_{\min}$ answers a physical bandwidth question: given an effective bandwidth and propagation convention, what is the nominal resolvable range separation? σ_r or RMSE answers an estimator performance question: under a particular SNR, geometry, dataset, or algorithm, how far is the estimate from the truth? CRB/FIM answers a bound question: under a model and noise assumption, what lower bound applies to an unbiased estimator? These answers can be related inside one paper, but they are not exchangeable across papers unless the model and scenario are aligned.

This is why the review does not report a single sensing column for all O-ISAC records. A photonic-THz system with

very fine $\Delta r_{\min}$ can be a strong bandwidth-limited ranging example, but its value does not make a VLC localization RMSE irrelevant. A fiber system with excellent spatial monitoring can be central to infrastructure O-ISAC, but its Δz cannot become a wireless range-resolution point. A CRB/FIM study can clarify theoretical limits, but it cannot replace measured or simulated RMSE in the governed rate-accuracy cloud. The Section V synthesis is therefore deliberately plural.

C. Fiber, Wireless Optical, and Hybrid Slices

The fiber slice is strongest when interpreted as guided infrastructure sensing integrated with optical communication. It includes high-capacity transport, distributed vibration or strain monitoring, and coexistence mechanisms that share

wavelength, fiber, or DSP resources. Its communication evidence can be extremely strong, but its sensing evidence is often spatially distributed rather than target-ranging. This makes fiber essential to O-ISAC while also making naive pooling unsafe.

The wireless optical slice includes FSO and VLC/LiFi systems. FSO is often closer to a free-space ranging formulation and may report bandwidth-limited resolution, Fisher information, or power-allocation tradeoffs. VLC/LiFi is frequently localization- or indoor-service-oriented, and its direct-detection receiver makes electrical-plane SNR and room geometry central. These two wireless optical subclasses should not be merged blindly: FSO and VLC both propagate optically through air, but their deployment constraints and receiver models differ.

The photonic-THz/hybrid slice is the most important bridge for high-rate rate–resolution claims. It often combines optical generation, fiber distribution, high-frequency wireless propagation, and coherent or electronic reception. This architecture can produce impressive CRQ values, but the bridge nature also creates a governance hazard. The communication rate may be measured through a fiber-wireless link, the sensing resolution may be tied to a high-frequency waveform, and the signal-quality plane may move from optical to electrical to DSP stages. For that reason, the review treats this class as a bridge rather than a homogeneous medium bucket.

D. Interpretation of the Sparse CRQ Subset

The sparse CRQ-valid subset should be interpreted in two ways. Technically, it shows that a small number of O-ISAC demonstrations jointly report high rate and bandwidth-limited resolution under matched scenarios. Methodologically, it shows that most of the corpus cannot yet support CRQ comparison because the required fields are absent or unmatched. The second point is the stronger COMST contribution. A field can have many strong demonstrations and still lack the reporting discipline needed for cross-paper synthesis.

This also prevents overclaiming a Pareto frontier. The point clouds and CRQ subset are fixed-case summaries of reported scenarios. They are not optimized over hardware cost, power, aperture, waveform, environment, receiver complexity, or deployment domain. A nondominated point in the sparse subset is not a universal design envelope; it is an informative reported scenario under the review’s admissibility rules. Future O-ISAC benchmarks should make this distinction explicit by reporting matched rate, $\Delta r_{\min}$, σ_r /RMSE, CRB/FIM context, Δz when relevant, and signal-quality plane in the same record.

E. Additional Tradeoff Interpretation

Section V-A works on governed scenario records rather than raw study counts. Communication metrics are scoped to reported communication rate (R) and link-quality indicators, with strict separation between optical-plane OSNR and electrical-plane SNR/ESNR because the two are measured at different receiver-chain stages. Table VI summarizes the resulting plane-aware coverage.

Before governance filtering, communication reporting appears broad: the 225-point trade-off set includes rate in 197 records, electrical-plane SNR in 190, and optical-plane OSNR in 169. After the Section II filter, however, only 53/225 scenarios remain usable, 172 are blocked, and 169 papers lose all scenarios. The dominant blocker is metric-plane mixing (169 records), followed by Δz -to- $\Delta r_{\min}$ aliasing (19 records, with 16 overlapping both flags). Within the governed subset, rate-bearing records are concentrated in hybrid (17) and cabled fiber (12), yielding medians of 10 Gbps and 28.5 Gbps, respectively; the remaining media are sparse and should be read as anchors rather than distributions. Electrical-plane SNR survives in only 20 governed records, while governance-usable OSNR drops to zero, so Section V-A can support electrical-plane quality remarks but not optical-plane cross-medium comparisons. CRQ-linked comments are likewise bounded to the 20 eligible records, dominated by hybrid (14) and cabled fiber (4). The same pattern explains the section’s conservatism overall: the governance audit reports 299 MAJOR violations across 169 papers, including 261 metric-plane and 38 metric-aliasing violations, so communication synthesis remains intentionally selective rather than coverage-maximizing.

Section V-B keeps the same governed scenario scope but reorganizes sensing evidence by function rather than by lexical surface form. $\Delta r_{\min}$ represents physical resolution, σ_r estimator-level accuracy, CRB bound-level context, and Δz fiber spatial granularity; these roles are not interchangeable, so Table VI reports them separately and Fig. 5 preserves distinct resolution and accuracy layers.

Before governance filtering, sensing coverage is broad: across 225 scenario points, $\Delta r_{\min}$ appears in 195 records, $\Delta r_{\min}$ -eligible reporting in 173, σ_r in 186, CRB in 148, and Δz in 161, with similarly high paper-level coverage. After filtering, however, only 53/225 scenarios remain usable overall. At role level, only 20/173 $\Delta r_{\min}$ -eligible records and 16/186 σ_r records survive, while both CRB and Δz fall to zero usable entries. The exclusion pattern is highly structured rather than random: 151/153 blocked $\Delta r_{\min}$ -eligible records, 169/170 blocked σ_r records, and 147/148 blocked CRB records are plane-mixed. The synthesis therefore separates reported coverage from governance-usable coverage because raw prevalence overstates comparative readiness.

Within the governed subset, $\Delta r_{\min}$ -eligible points are concentrated in hybrid (14) and cabled fiber (4), with single anchors in wireless FSO and terahertz; across all usable points, $\Delta r_{\min}$ spans 0.0025–15 m with a median of 0.0397 m. Estimator-level accuracy is even sparser: only 16 usable records report σ_r (hybrid 8, cabled fiber 7, terahertz 1), spanning 0.001–1000 m with a median of 0.0575 m, and only 13 usable records contain both $\Delta r_{\min}$ and σ_r . This asymmetry is why Fig. 5 keeps separate resolution and accuracy panels. CRB and Δz remain contextual only, because neither survives governance filtering; OSNR is likewise absent from the usable sensing subset, whereas electrical-plane SNR remains available in 12/20 $\Delta r_{\min}$ -eligible and 14/16 σ_r records. The same conservatism also matches the qualitative trade-off record: DIRECT articulation exists, but it remains a minority pattern relative to total mention volume, and the 299

MAJOR governance violations across 169 papers continue to limit synthesis-ready support.

Section V-C is the synthesis core of the section: it converts the governed metric subsets into operating-cloud and frontier-style views without relaxing the Section II contract. Rate-versus-resolution is interpreted through rate and $\Delta r_{\min}$, rate-versus-accuracy through rate and σ_r , while CRB remains bound-level context and Δz is never used as a surrogate for $\Delta r_{\min}$. The main figure therefore keeps the resolution and accuracy layers separate, while the CRQ discussion is bounded to the valid subset.

The full trade-off table contains 225 scenario points from 220 papers, but the governed subset is much smaller: only 20 points support rate-plus- $\Delta r_{\min}$ interpretation and 16 support rate-plus- σ_r , with only 13 supporting the full triplet. This contraction is not cosmetic; it determines the admissible evidence for trade-off inference. Labels remain useful narrative cues, but dimensional interpretation is grounded in governed metric availability rather than label strings alone. The governed operating region is still numerically informative: rate spans 25 Mbps to 448 Gbps (median 10 Gbps), $\Delta r_{\min}$ spans 0.0025–15 m (median 0.0397 m), and σ_r spans 0.001–1000 m (median 0.0575 m). Coupling-mode coverage is likewise asymmetric, with `resource_division` dominant in both the raw and governed sets.

CRQ filtering makes the admissibility compression even clearer. The point taxonomy is 225 total points, 170 CRQ-candidate points, 20 CRQ-valid points, and only 2 Pareto points. The 20 valid points are distributed across hybrid (14), cabled fiber (4), terahertz (1), and wireless FSO (1), with CRQ spanning 6.67×10^8 to 4.8×10^{13} bps/m and a median of 4.33×10^{10} bps/m. Because the frontier itself contains only one hybrid and one wireless FSO point, this view should be read as a bounded illustrative frontier rather than a stable design envelope. The same caveat applies to measurement-plane conditioning: electrical-plane SNR remains available in part of the governed subset, but governance-usable OSNR remains absent throughout.

Trade-off-language extraction is consistent with this conservatism: explicit trade-off reasoning exists, but DIRECT articulation remains a minority pattern relative to total mention volume. The same 299 MAJOR governance violations across 169 papers therefore remain central to interpretation in V-C, because they explain much of the candidate-to-valid compression and the sparsity of the Pareto set.

Section V-D keeps the same governed scenario scope but changes the question from “what is available?” to “what can be compared responsibly?”. Medium labels remain exactly as normalized in Section IV, hybrid is retained as a bridge class rather than forced into either endpoint, and Table VII is the primary comparative anchor.

The contraction from raw to governed evidence directly shapes what can be compared. The raw trade-off set contains 225 scenario points across 12 medium labels, but governance filtering retains only 53, distributed mainly across hybrid (27), cabled fiber (15), and smaller wireless slices. Within that governed set, fiber contributes 15 points from 13 papers, wireless 9 points from 9 papers, and hybrid 27 points from 27

papers. Metric completeness is asymmetric: fiber contributes 12 rate values, 4 $\Delta r_{\min}$ values, and 7 σ_r values; wireless contributes 3, 1, and 0; hybrid contributes 17, 14, and 8. The comparative slice should therefore be read as a constrained synthesis over a reduced admissible set rather than as a mirror of raw-corpus prevalence.

The governed medians suggest different operating emphases, but not universal superiority claims. Fiber shows a median rate of 28.5 Gbps, wireless 1 Gbps, and hybrid 10 Gbps, yet the wireless slice is structurally unstable because it is sparse and heterogeneous. Sensing-side comparison is even more asymmetric: fiber has median $\Delta r_{\min} = 5.5$ m and median $\sigma_r = 0.1$ m, wireless has only one governed $\Delta r_{\min}$ value and no governed σ_r , and hybrid supports both metrics with medians of 0.019075 m and 0.01 m. CRQ comparison is similarly bounded to the 20 eligible points, while electrical-plane SNR remains available only for fiber, hybrid, and one wireless anchor. V-D is therefore intentionally conservative: it preserves comparison where support exists, keeps hybrid explicit, and treats sparse slices as non-ranking evidence.

VI. ENABLING TECHNOLOGIES AND SYSTEM-LEVEL CO-DESIGN

O-ISAC enablers matter because they determine whether the metric-governed taxonomy can become deployable systems. The main enabler families are ORIS/optical RIS, OPA, PIC and photonic integration, photonics-assisted mmWave/THz generation, and ML/security-aware adaptation. Table VIII keeps the synthesis compact while the surrounding prose explains what each family contributes and what must be reported.

ORIS and optical RIS concepts promise programmable optical reflection, beam shaping, and spatial reuse. They are most naturally connected to optical wireless deployments where geometry, blockage, or coverage can be controlled by reconfigurable surfaces [25], [96]–[99]. Their O-ISAC value depends on reporting the surface model, phase/amplitude control assumptions, alignment burden, and whether sensing observes the same controlled path as communication.

OPA technologies provide aperture-level beam steering for optical wireless ISAC. OPA-based optical wireless studies show how beamforming, target direction, and communication performance can be coupled in one front-end [54], [95], [100], [101]. The reporting challenge is that beam pattern, scan schedule, receiver aperture, estimator, and communication link budget must be tied to the same scenario. Otherwise a beam-steering gain may not support a sensing claim.

PIC and photonic integration provide the device and packaging path for practical O-ISAC. Heterogeneous integration, micro-ring and chip-scale demonstrations, photonic transmitters, and integrated coherent front-ends can reduce size and improve stability, but device-level performance is not automatically system-level sensing/communication evidence [76], [77], [80], [81], [102], [103]. The metric contract should therefore accompany PIC claims with source, modulator, receiver, calibration, and measurement-plane disclosure.

Photonics-assisted mmWave/THz generation is a key bridge for high-rate high-frequency O-ISAC. Optical carriers can sup-

TABLE VIII
COMPACT ENABLER SYNTHESIS FOR O-ISAC.

Enabler	Main O-ISAC role	Evidence center	Reporting risk
ORIS / optical RIS	Programmable reflection, beam control, spatial reuse	Optical wireless and RIS-adjacent ISAC [25]	Disclose geometry and control overhead
OPA	Beam steering and joint aperture use	OPA-based optical wireless ISAC [54], [95]	Link beam pattern, scan schedule, and estimator
PIC / photonic integration	Compact source/modulator/receiver integration	Fiber-wireless and chip-scale demonstrations [76], [77]	Map device results to system metric planes
Photonics-assisted mmWave/THz	High-frequency generation and reception	W-band, D-band, and THz-over-fiber systems [1], [10]	Separate optical generation from wireless propagation
ML/security adaptation	Inference, calibration, and attack-aware control	Learning-assisted VLC/fiber-wireless studies [8], [90]	Disclose dataset, generalization, and threat model




Fig. 6. Deployment-oriented systems map linking optical enablers, impairments, control, and benchmark discipline.

port generation, distribution, coherent reception, de-chirping, or THz-over-fiber transport, enabling W-band, D-band, and THz demonstrations [1], [10]–[12], [49]–[52], [68], [104]. The governance issue is that optical and wireless stages must not be collapsed: a high-quality optical generation chain still needs wireless propagation, receiver, and estimator fields for sensing claims.

ML and security-aware adaptation appear across VLC/LiFi localization, fiber-wireless reception, beam management, channel prediction, and robustness studies [8], [87]–[90], [105]–[109]. ML can help with calibration, nonlinear compensation, inference, resource allocation, or semantic/context-aware control, but it also introduces dataset dependence, generalization risk, attack surfaces, and privacy concerns. O-ISAC reporting should therefore include data origin, train/test separation, channel variation, threat model, and uncertainty.

Fig. 6 and Table IX convert the enabler discussion into a

TABLE IX
MINIMUM REPRODUCIBLE REPORTING FIELDS.

Field	Required disclosure
Scenario	medium, geometry, range, mobility, weather/ambient state
Link	rate, BER/throughput method, bandwidth, modulation, multiplexing
Sensing Plane	task, $\Delta r_{\min}$ or Δz , RMSE/ σ_r , CRB/FIM if used
Evidence	OSNR/SNR/ESNR reference point and conversion model if any simulation/experiment, data/code availability, uncertainty reporting

reporting contract. Programmable optical hardware, photonic high-frequency generation, and ML adaptation are not enough on their own. They become comparable O-ISAC evidence only when the channel, scenario, metric plane, estimator, and benchmark workflow are disclosed together.

A. Enabler Maturity and Evidence Boundaries

The enabler literature is uneven across optical modalities. OPA and photonics-assisted high-frequency generation have relatively direct links to joint communication-sensing demonstrations because they can shape beams, create high-bandwidth waveforms, or connect optical transport to mmWave/THz sensing. ORIS and optical RIS concepts are important for future controllable optical environments, but their evidence often remains closer to architecture and channel-control framing than to full deployment validation. PIC and photonic integration provide a practical route to compact hardware, but many records are device-level or subsystem-level and therefore need careful translation into system metrics. ML/security studies are similarly heterogeneous: they may improve localization, compensation, beam management, or robustness, but they depend heavily on data and threat assumptions.

This spread of evidence means that enablers should not be ranked by citation count or by a single performance number. The relevant question is which bottleneck each enabler addresses. ORIS and OPA address spatial control and link geometry. PIC addresses integration density, packaging, and repeatability. Photonics-assisted generation addresses bandwidth and high-frequency carrier access. ML addresses inference, calibration, and adaptation, while security-aware design addresses reliability and trust. The reporting contract binds these families together by asking them to disclose the same scenario and metric roles.

B. Benchmark Implications

Benchmarking should be enabler-aware. An OPA benchmark should include aperture, steering range, beamwidth, sidelobes, scan schedule, receiver aperture, and sensing estimator. An ORIS benchmark should include surface size, phase/amplitude model, placement, alignment, and channel estimation overhead. A PIC benchmark should include optical power budget, insertion loss, stability, modulation format, receiver model, and packaging assumptions. A photonic-THz benchmark should separate optical generation, fiber distribution, wireless propagation, and receiver processing. An ML benchmark should disclose datasets, train/test split, channel variation, generalization tests, and attack or privacy assumptions when security is claimed. Without these fields, enabler claims remain hard to transfer across modalities.

C. Additional Enabler Detail

Programmable optical enablers matter because they convert optical propagation from a mostly fixed channel into a controllable channel. OPA studies expose transmit-side beam agility, angular selectivity, and joint waveform support, whereas ORIS studies expose environment-side path shaping, alignment assistance, and blockage mitigation through reflected or reconstructed paths. This distinction is important: OPA and ORIS should be written as complementary control authorities rather than as interchangeable technologies. Finite receiver field of view, grating-lobe behavior, insertion loss, quantized control, and channel impairments prevent ideal steering or reflection

gains from translating automatically into reproducible O-ISAC gains.

PIC, programmable photonics, and photonics-assisted signal generation are treated here as supporting substrates beneath the programmable-aperture story rather than as a detached maturity tier. Their main value is explanatory: they clarify packaging, integration pathway, optical power budget, and high-frequency generation/distribution feasibility. Measurable O-ISAC gains are still anchored to declared receiver planes, waveform assumptions, link distances, and sensing tasks; therefore prevalence wording remains conservative.

Robustness is a first-order concern because the same optical impairment can degrade communication reliability and sensing fidelity. FSO and many hybrid links are shaped by turbulence, weather attenuation, and pointing error; VLC/LiFi deployments are often shaped by room geometry, illumination, finite field of view, and ambient light; guided-fiber systems require a different impairment vocabulary centered on dispersion, nonlinearities, polarization, and interrogator limits. Programmable surfaces or beam-steering mechanisms are useful only insofar as they remain effective under the dominant impairment regime and report the operating assumptions that make the gain reproducible.

Joint co-design remains promising but heterogeneous. Waveform, beam, power, ORIS state, and receiver processing choices share physical constraints, and IM/DD implementations additionally require nonnegative intensity and optical-power feasibility. Coherent and programmable settings add phase control, steering, refresh latency, calibration, and quantization constraints. The evidence supports structured co-design in well-specified exemplars, but many studies still report formulation-level gains without harmonized disclosure of runtime burden, baseline choice, robustness testing, or replication fields.

Benchmarking is therefore the hinge of Section VI. An enabler result should disclose link distance, medium class, receiver plane, communication KPI, role-consistent sensing metric, bound-level context when used, hardware/control assumptions, and validation level. For Section II consistency, a benchmark may report $\Delta r_{\min}$ in bandwidth-limited ranging settings or Δz in guided-fiber spatial-granularity settings, but these quantities are not interchangeable. The reporting contract in Table IX is the bridge from enabler choice to deployment-ready evaluation and is inherited by the application and roadmap sections.

VI-D takeaway. The strongest immediate need is a shared benchmark contract rather than more isolated case studies. Benchmark discipline is what turns promising enablers into cumulative evidence and enables the shift from feasibility to scale in VI-E.

Networked O-ISAC introduces burdens that do not appear in single-link settings: multi-user interference, feedback overhead, sensing-fusion consistency, and coordination delay. The corpus already reports explicit FoV and grating-lobe interference effects in multi-user OPA settings, tracking burden growth with user count in mobile ORIS systems, protocol-level overhead sensitivity in VLC-based networked settings, and newer RO-ISAC/Industry-IoT SDMA extensions that make

long-range user separation itself a system-level burden .

Network-level formulations are useful when they make communication, sensing, and ORIS quantization constraints explicit in one multi-user setting. Their interpretation still requires fixed detection semantics for link-quality terms and a role-consistent sensing objective rather than a mixed resolution-accuracy score. At this point, the narrative starts to connect directly to Section VII: once user count, fusion policy, fairness, and control overhead dominate, the key question is whether a deployment setting can absorb the coordination cost.

VI-E takeaway. Multi-user optical O-ISAC is supported by a growing set of targeted studies, but network-level overhead metrics, control-plane timing, and cooperative benchmark contracts remain under-standardized. This is where enabler analysis becomes deployment analysis: coordination cost, fairness, and sensing-fusion policy begin to determine application readiness, which in turn motivates VI-F.

AI-assisted adaptation and security-aware design are emerging layers in O-ISAC, especially in dynamic channels where static policies may underperform. Repository tag views disagree on the exact ML prevalence under strict versus broad evidence rules, so this section treats ML as a material but uneven subset rather than a precise maturity count. The available literature contains targeted reports of learning-driven adaptation, learning-assisted compensation and receiver refinement, and learning-based angle estimation, together with secrecy, authentication, and resilience formulations, but jointly validated AI-plus-security optical benchmarks remain limited. In the review flow, this subsection functions as a forward-looking systems layer rather than a co-equal replacement for the physical enabler evidence in VI-A.

Security-aware and robust-control studies capture a central tension of the subsection: adaptation gains matter only if they survive uncertainty, overhead, and adversarial pressure rather than only nominal channels. Here again, rate, secrecy-rate, and CRB-style quantities must be interpreted as role-specific metrics rather than mutually convertible scores, and the current evidence should still be read as focused demonstrations rather than proof of mature end-to-end AI-secure O-ISAC stacks.

Section VI should also keep maturity asymmetry visible here: OPA and ORIS mechanics are presently better evidenced than long-horizon AI adaptation, trust, and adversarial robustness under reproducible protocols. AI/security therefore belongs in Section VI as an emerging overlay on top of better-evidenced optical controllability, not yet as a co-equal maturity tier.

VI-F takeaway. AI/ML and security are relevant emerging directions in optical O-ISAC, but current evidence is uneven and should be synthesized cautiously. The field still needs reproducible attack models, overhead-aware reporting, and benchmark-quality evaluation of adaptation under domain shift before strong maturity claims are warranted. VI-F is therefore best read as a bounded forward layer on top of better-evidenced optical controllability before the manuscript turns to application settings in Section VII.

VII. APPLICATIONS AND USE CASES ACROSS DOMAINS

Application evidence is treated as a deployment map rather than a maturity scorecard. The corpus spans smart infrastructure, indoor VLC/LiFi localization, automotive and optical V2X, underwater or harsh OWC, and space/NTN or satellite-oriented photonic systems. Table X compresses these domains into five motifs while preserving the transfer warning for each.

Smart infrastructure and cabled-fiber corridors are natural O-ISAC domains because installed fiber can carry data while sensing vibration, strain, temperature, intrusion, or environmental events along the route [29], [42], [56]–[58], [110]. Their value is strongest for guided infrastructure and transport monitoring. Transfer to wireless optical ISAC is conditional because the sensing object is a distributed guided medium rather than a free-space target.

Indoor VLC/LiFi localization uses lighting infrastructure, room-scale data access, and direct-detection observability to support positioning, gesture recognition, occupancy, and multi-task sensing [8], [15]–[17], [48], [64], [69], [111]. The deployment motif is compelling because luminaires are already spatially structured, but the results remain tied to room geometry, ambient light, receiver orientation, camera or photodiode assumptions, and electrical-plane metrics.

Automotive and optical V2X records connect O-ISAC to short-range optical links, beam-controlled access, cooperative perception, and ranging/pose estimation [3], [94], [112]–[116]. The transfer warning is stronger here: weather, blockage, eye safety, mobility, synchronization, and field-of-view constraints must be explicit before a laboratory optical link can be interpreted as deployment evidence.

Underwater and harsh OWC cases appear where RF propagation is limited or environmental sensing is part of the communication mission. Representative records include underwater or harsh-medium optical links, salinity/environmental monitoring, and hybrid OWC designs [46], [61], [117]–[120]. These applications are highly medium-specific because absorption, scattering, turbulence, and alignment dominate both communication and sensing performance.

LEO, satellite, and space photonic O-ISAC are more roadmap-oriented. Optical backhaul, NTN integration, tracking, ranging, and space/airborne network control suggest a future O-ISAC role in multi-layer networks [1], [78], [108], [121]–[126]. The evidence should not be read as mature across all space deployments; it is a transfer map showing where photonic links, pointing, tracking, and network orchestration may converge.

A. Transfer Rules Across Application Motifs

The application map is useful only if transfer is conditional. A technique that works in cabled fiber may transfer to another guided infrastructure setting, but it usually does not transfer directly to VLC or FSO because the observation plane, channel, and sensing target change. A VLC localization method may transfer across indoor lighting layouts if geometry and receiver orientation are handled, but it does not automatically support outdoor FSO ranging. A photonic-THz waveform may inform

TABLE X
APPLICATION PORTFOLIO COMPRESSED TO FIVE MACRO-DOMAINS.

Macro-domain	Communication motif	Sensing motif	Transfer warning
Smart infrastructure / cabled-fiber corridor	High-capacity transport and monitoring overlays	Vibration, strain, intrusion, seismic/corridor awareness	Strong for guided infrastructure; weak as wireless baseline
Indoor VLC/LiFi localization	Lighting/data access and room-scale links	Positioning, gesture, occupancy, camera-assisted sensing	Direct-detection and ambient-light assumptions dominate
Automotive / optical V2X	Short-range optical links and beam-controlled access	Ranging, pose, cooperative perception	Geometry, eye safety, weather, and blockage must be disclosed
Underwater or harsh OWC	Optical wireless where RF is limited	Salinity, environmental, and link-state monitoring	Medium absorption/scattering makes transfer highly conditional
LEO/satellite or space photonic O-ISAC	Space/NTN optical backhaul and hybrid network support	Tracking, ranging, situational awareness	Evidence is roadmap-oriented and needs deployment validation

high-frequency fiber-wireless sensing, but it still requires propagation and receiver-plane disclosure before being compared with guided fiber or VLC metrics.

This is why the review avoids application maturity scoring. The corpus contains strong demonstrations, but not enough shared field trials, common benchmarks, or uncertainty reporting to rank domains by deployment readiness. Instead, Table X identifies recurring deployment motifs and their transfer warnings. In a later benchmark culture, each motif should have a scenario template: corridor length and fiber interrogator fields for cabled infrastructure; room geometry and lighting fields for VLC/LiFi; mobility, blockage, and weather fields for optical V2X; absorption/scattering fields for underwater or harsh OWC; and pointing, tracking, and network-orchestration fields for space/NTN cases.

B. Application Metrics and Governance

Application sections often mix user-facing language with physical-layer results. For O-ISAC, that mix can hide metric assumptions. A smart-infrastructure paper may care about event localization, false alarms, and fiber coverage; an indoor LiFi paper may care about positioning accuracy, data rate, lighting quality, and user motion; an optical V2X paper may care about ranging, blockage, latency, and safety; an underwater OWC paper may care about link survival and environmental observability. These are legitimate application metrics, but they must be mapped back to the Section II contract before they support cross-modality claims.

VIII. OPEN CHALLENGES AND RESEARCH ROADMAP

The roadmap is organized around five challenge domains: standardization/interoperability, hardware scalability, channel modeling/evaluation, security/privacy/reliability, and deployment convergence. Fig. 7 links these domains back to the metric contract, enablers, and application motifs; Table XI summarizes the challenge set, and Table XII converts it into a five-item agenda.

Standardization and interoperability are the first bottleneck. O-ISAC currently spans multiple naming conventions, channel models, and reporting cultures. A common vocabulary should

not erase modality differences; it should require authors to declare medium, integration mechanism, detection/observability class, sensing task, metric role, and signal-quality plane [2], [19], [20]. The most practical near-term step is a reporting template aligned with Table III and Table IX.

Hardware scalability is the second bottleneck. OPA, ORIS, PIC, and photonics-assisted mmWave/THz systems are promising, but they are not yet evaluated under a shared deployment and benchmark protocol [25], [54], [76], [95], [97], [100]. Future prototypes should report aperture, beam-control, calibration, packaging, thermal, synchronization, and receiver-plane details together with communication and sensing metrics.

Channel modeling and evaluation remain fragmented. Fiber, FSO, VLC/LiFi, and photonic-THz systems require different channel assumptions, and a benchmark should not pretend that one model covers all of them [7], [8], [17], [21], [23], [46]. The roadmap should therefore define scenario families: guided infrastructure, indoor visible light, atmospheric FSO, photonic-THz/fiber-wireless, underwater/harsh OWC, and NTN/space optical links. Each family needs common reporting fields and uncertainty treatment.

Security, privacy, and reliability become more important as O-ISAC moves from link demonstrations to sensing-rich deployments. Optical beams offer spatial isolation, but narrow beams, reflected paths, sensing data, ML inference, and programmable surfaces create attack and failure modes that differ from conventional optical communications [87], [96], [127]–[130]. The field needs threat-modeled benchmarks rather than security claims attached only as future work.

Deployment convergence is the final challenge. O-ISAC must connect physical-layer metrics, network orchestration, application requirements, and reproducible evidence. Smart infrastructure, indoor LiFi, vehicular optical links, harsh OWC, and NTN/space photonics each define different success criteria [78], [108], [110], [121], [123], [131], [132]. The roadmap is therefore not a single technology ladder; it is a set of domain-conditioned validation paths.

The resulting COMST roadmap is methodological and technological at the same time. O-ISAC needs better hardware, but it also needs interoperable taxonomy, metric-governed reporting, reproducible workflows, benchmark channels, and




Fig. 7. Challenge-to-roadmap dependency map for taxonomy, metrics, benchmarks, hardware, security, and deployment validation.

TABLE XI
COMPRESSED O-ISAC CHALLENGE DOMAINS.

Domain	Bottleneck	Roadmap response
Std./interoperability	Inconsistent terminology, taxonomy, and reporting fields	Shared O-ISAC taxonomy, PRISMA-style ledgers, metric-governed templates
Hardware scalability	Promising but uneven OPA/ORIS/PIC/photonic-THz integration	Co-designed aperture, source, receiver, calibration, and packaging metrics
Channel modeling/evaluation	Fiber, FSO, VLC, and photonic-THz assumptions are often mixed	Scenario-tagged benchmark channels and plane-aware signal-quality reporting
Security/reliability	ML, sensing data, and narrow beams add attack/failure surfaces	Threat-modeled evaluation with robustness and privacy fields
Deployment convergence	Application claims outpace cross-domain validation	Domain-aware pilots tied to reproducible evaluation workflows

TABLE XII
FIVE-ITEM PRIORITIZED RESEARCH AGENDA.

Pri.	Agenda item	Concrete deliverable	Risk if deferred
1	Metric-governed reporting	Required fields for rate, $\Delta r_{\min}$, σ_r /RMSE, CRB/FIM, Δz , and OSNR/SNR plane	Unsafe comparisons persist
2	Reproducible corpus workflow	Public ledgers, search strings, extraction sheets, and code for figures/tables	Weak systematic-review traceability
3	Cross-modality benchmarks	Fiber/FSO/VLC/photonic-THz scenario templates with uncertainty reporting	Non-transferable performance claims
4	Scalable hardware evidence	OPA/ORIS/PIC/photonic-THz prototypes evaluated with shared fields	Enabler claims remain isolated
5	Deployment validation	Domain pilots for infrastructure, indoor, vehicle, harsh OWC, and space/NTN cases	Application map remains aspirational

domain-aware validation before cross-modality performance claims become robust.

A. From Reporting Contract to Benchmark Culture

The most immediate roadmap item is reporting discipline. A useful O-ISAC benchmark should not merely ask authors to report rate and sensing accuracy. It should require a

medium label, integration mechanism, receiver/observability class, sensing task, communication metric, sensing metric, signal-quality plane, scenario geometry, and uncertainty statement. The benchmark should also state whether a sensing value is $\Delta r_{\min}$, σ_r /RMSE, CRB/FIM, Δz , or another metric. This makes negative space visible: when a paper cannot support CRQ, that absence becomes a documented limitation

rather than an implicit comparison.

Reproducible workflows are the second step. The PRISMA ledger, extraction sheet, and figure-generation scripts should be treated as part of the scientific contribution, not as administrative residue. O-ISAC is moving quickly, and new papers will continue to introduce terminology variants and hybrid architectures. A public ledger allows the community to update counts, re-run taxonomy summaries, and identify whether reporting practice improves over time.

B. Hardware and Channel Roadmap

Hardware progress should be evaluated at the system boundary. For OPA and ORIS, the boundary includes beam control, link budget, sensing estimator, alignment, and control overhead. For PIC and photonic integration, it includes source/modulator/receiver integration, calibration, packaging, and stability. For photonics-assisted mmWave/THz, it includes optical generation, high-frequency propagation, receiver processing, and measurement-plane conversion. The roadmap should therefore push prototypes toward shared reporting fields rather than isolated best-case demonstrations.

Channel modeling is equally important. A cross-modality survey cannot impose one channel model, but it can require that each modality state its model clearly. Fiber studies should disclose span, dispersion/nonlinearity assumptions, gauge length, and interrogator fields. FSO studies should disclose range, weather/turbulence, pointing, aperture, and link geometry. VLC/LiFi studies should disclose room, reflectivity, LED/PD/camera model, and ambient light. Photonic-THz studies should disclose the optical generation chain, wireless frequency, propagation distance, bandwidth, and receiver processing.

C. Security, Privacy, and Deployment Validation

Security and privacy are not add-ons once sensing is integrated with communication. O-ISAC systems may observe location, motion, vibration, infrastructure state, or human activity. They may also depend on narrow beams, programmable surfaces, ML models, and control loops. This creates attack surfaces around spoofing, beam manipulation, data leakage, adversarial inference, and reliability under blockage or environmental change. Future work should report threat models with the same care as link budgets.

Finally, deployment validation must be domain-aware. A laboratory optical bench, an indoor LiFi room, a fiber corridor, an outdoor FSO link, and a satellite optical path test different assumptions. The roadmap should not demand one grand validation experiment. It should demand that each domain define its own scenario template, core metrics, uncertainty fields, and reproducibility package. That is the practical route from promising O-ISAC prototypes to credible 6G-facing systems.

IX. CONCLUSIONS

This review synthesized optical integrated sensing and communication as a family of architectures rather than a

monolithic interchangeable design space. Using a PRISMA-grounded corpus of 220 studies, it organized fiber, FSO, VLC/LiFi, photonic-THz, and hybrid work through a cross-modality taxonomy and a metric-governed comparison contract. The central lesson is that comparability requires explicit modality, metric role, measurement plane, and deployment context: $\Delta r_{\min}$ is not σ_r/RMSE , CRB/FIM is a bound-level statement, fiber Δz is not wireless range resolution, and OSNR and electrical SNR cannot be exchanged without a receiver/noise model. Under that governed reading, the rate-resolution evidence is informative but sparse: only small subsets of the 225 extracted scenario records support admissible CRQ or full triplet synthesis. Future progress therefore depends as much on reporting practice as on hardware advances. Reproducible workflows, benchmark definitions, scalable OPA/ORIS/PIC and photonic-THz hardware, security-aware adaptation, and domain-aware validation are the necessary path from promising O-ISAC demonstrations to credible 6G systems.

REFERENCES

- [1] Z. Lyu, L. Zhang, Q. Deng, X. Fang, L. Bai, Y.-T. Sun, O. Ozolins, G. Liu, X. Pang, and X. Yu, "Exploring photonic thz-isac systems with integrated waveforms," *Journal of Lightwave Technology*, vol. 44, no. 3, p. 868–877, Feb. 2026. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3615209>
- [2] A. Ghosh, T. Wild, J. Du, J. Tan, A. Grudnitsky, D. Chizhik, S. Mandelli, Y. Xing, F. Schaich, and H. Viswanathan, "A unified future: Integrated sensing and communication (isac) in 6g," *IEEE Journal of Selected Topics in Electromagnetics, Antennas and Propagation*, vol. 1, no. 1, p. 365–374, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jstap.2025.3603540>
- [3] Y. Wen, F. Yang, J. Song, and Z. Han, "Optical integrated sensing and communication: Architectures, potentials and challenges," *IEEE Internet of Things Magazine*, vol. 7, no. 4, p. 68–74, Jul. 2024. [Online]. Available: <http://dx.doi.org/10.1109/iotm.001.2300196>
- [4] Z. Salem, C. Krutzler, and A. Peter, "Joint communication and sensing prospects: Potential through visible light," in *2024 International Conference on Broadband Communications for Next Generation Networks and Multimedia Applications (CoBCom)*. IEEE, Jul. 2024, p. 1–7. [Online]. Available: <http://dx.doi.org/10.1109/cobcom62281.2024.10631227>
- [5] S. Sharma, H. Kumar, and C. Thareja, "Digital signal processing over analog signal processing," *Journal of Advance Research in Electrical & Electronics Engineering (ISSN: 2208-2395)*, vol. 1, no. 2, p. 01–02, Feb. 2014. [Online]. Available: <http://dx.doi.org/10.53555/nneec.v1i2.255>
- [6] Y. Wu, C. Xu, F. Chen, Y. Wang, G. Wu, P. Xin, Z. Chen, P. Zhan, Z. Zhou, Z. Zhang, W. Ma, M. Li, J. Yan, M. Pa, Y. Li, Y. Zhao, and J. Zhang, "Recent advancements and challenges in integrated sensing and communication in optical fiber," in *2024 IEEE 24th International Conference on Communication Technology (ICCT)*. IEEE, Oct. 2024, p. 137–141. [Online]. Available: <http://dx.doi.org/10.1109/icct62411.2024.10946617>
- [7] Y. Wen, F. Yang, J. Song, and Z. Han, "Free-space optical integrated sensing and communication based on dco-ofdm: Performance metrics and resource allocation," *IEEE Internet of Things Journal*, vol. 12, no. 2, p. 2158–2173, Jan. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3469279>
- [8] T. Wei, S. Liu, and X. Du, "Visible light integrated positioning and communication: A multi-task federated learning framework," *IEEE Transactions on Mobile Computing*, vol. 22, no. 12, p. 7086–7103, Dec. 2023. [Online]. Available: <http://dx.doi.org/10.1109/tmc.2022.3207164>
- [9] M. Lei, Z. Lyu, Q. Zhou, J. Zhang, H. Li, B. Hua, J. Zhang, Y. Cai, J. Ding, X. Chen, L. Zhang, J. Yu, and M. Zhu, "Demonstration of photonic sub-thz isac system with real-time 251.03-gbps communication rate and offline 2.5-cm sensing resolution," in *2024 22nd International Conference on Optical Communications and Networks (ICOON)*. IEEE, Jul. 2024, p. 1–3. [Online]. Available: <http://dx.doi.org/10.1109/icocn63276.2024.10648485>

- [10] B. Dong, Z. Li, S. Xing, Y. Liu, J. Zhao, O. Huang, J. Jia, J. Shi, Y. Zhou, H. Wang, N. Chi, and J. Zhang, "Thz integrated sensing and communication with full-photon direct lfm reception and de-chirping for d-band fiber-wireless network," *IEEE Transactions on Microwave Theory and Techniques*, vol. 73, no. 8, p. 5383–5395, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1109/tmtt.2025.3549729>
- [11] B. Dong, J. Jia, G. Li, J. Shi, H. Wang, Z. Tang, J. Zhang, S. Pan, and N. Chi, "Photonic-based w-band flexible tdfm integrated sensing and communication system for fiber-wireless network," in *2023 Optical Fiber Communications Conference and Exhibition (OFC)*. IEEE, Mar. 2023, p. 1–3. [Online]. Available: <http://dx.doi.org/10.23919/ofc49934.2023.10116069>
- [12] B. Dong, J. Jia, L. Tao, G. Li, Z. Li, C. Huang, J. Shi, H. Wang, Z. Tang, J. Zhang, S. Pan, and N. Chi, "Photonic-based w-band integrated sensing and communication system with flexible time-frequency division multiplexed waveforms for fiber-wireless network," *Journal of Lightwave Technology*, vol. 42, no. 4, p. 1281–1295, Feb. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2024.3354070>
- [13] L. Gu, C. Liu, M. Xiang, P. Xu, H. Yang, W. Sun, J. Yang, S. Fu, Y. Wang, and Y. Qin, "Co-wavelength-channel integration of ultra-low-frequency distributed acoustic sensing and high-capacity communication," *Photonics Research*, vol. 13, no. 6, p. 1611, May 2025. [Online]. Available: <http://dx.doi.org/10.1364/prj.551958>
- [14] Z. Lyu, L. Zhang, H. Zhang, Z. Yang, C. Zhang, H. Yang, N. Li, V. Bobrov, O. Ozolins, X. Pang, G. Liu, and X. Yu, "Multi-channel photonic thz-isac system based on integrated lfm-qam waveform," *Journal of Lightwave Technology*, vol. 42, no. 11, p. 3981–3988, Jun. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2024.3392282>
- [15] C. Xu, C. Masouros, S. Sugiura, P. Petropoulos, R. G. Maunder, L.-L. Yang, H. Haas, and L. Hanzo, "Integrated positioning and communication relying on wireless optical ofdm," *IEEE Journal on Selected Areas in Communications*, vol. 43, no. 5, p. 1721–1737, May 2025. [Online]. Available: <http://dx.doi.org/10.1109/jsac.2025.3543532>
- [16] L. Shi, B. Béchadargue, L. Chassagne, and H. Guan, "Joint visible light sensing and communication using m-cap modulation," *IEEE Transactions on Broadcasting*, vol. 69, no. 1, p. 276–288, Mar. 2023. [Online]. Available: <http://dx.doi.org/10.1109/tbc.2022.3201649>
- [17] B. Zhou, A. Liu, and H. C. So, "Visible light communication-enabled simultaneous position and orientation detection for harnessing multipath interference and random fading," *IEEE Transactions on Intelligent Transportation Systems*, vol. 25, no. 2, p. 1938–1952, Feb. 2024. [Online]. Available: <http://dx.doi.org/10.1109/tits.2023.3324361>
- [18] B. Zhou, X. Wang, Y. Shen, and P. Fan, "6-dof location-and-pose estimation toward integrated visible light communication and sensing: Algorithm design and performance limits," *IEEE Transactions on Signal Processing*, vol. 72, p. 2576–2593, 2024. [Online]. Available: <http://dx.doi.org/10.1109/tsp.2024.3383285>
- [19] K. Wu, Y. Bigdeli, S. A. Keivani, J. Deng, and P. Burasa, "Integrated sensing and communication (isac) transceiver: Hardware architectures, enabling technologies, and emerging trends," *IEEE Journal of Selected Topics in Electromagnetics, Antennas and Propagation*, vol. 1, no. 1, p. 37–64, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jstap.2025.3610564>
- [20] P. Tang, Y. Yin, Y. Tong, S. Liu, L. Li, T. Jiang, Q. Wang, and M. Chen, "Channel characterization and modeling for vlc-ioe applications in 6g: A survey," *IEEE Internet of Things Journal*, vol. 11, no. 21, p. 34872–34895, Nov. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3430326>
- [21] Z. Wang, H. Yang, Y. Li, Q. Yao, T. Yu, C. Zhang, W. Liu, W. Lin, J. Zhang, Y. Liu, and M. Cheriet, "Co-route fiber recognition and status diagnosis based on integrated sensing and communication in 6g transport networks," *IEEE Internet of Things Journal*, vol. 11, no. 18, p. 29348–29359, Sep. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3414863>
- [22] Y. Hu, K. Zhang, M. E. Mousa-Pasandi, R. Gutiérrez-Castrejón, M. O'Sullivan, F. Kong, B. Buscaino, J. Zhang, S. Bernal, C. St-Arnault, and D. V. Plant, "Demonstration of high sensitivity detection and high precision localization of vibrations in bidirectional coherent transmission systems enabled by carrier laser phase noise retrieval," *Journal of Lightwave Technology*, vol. 43, no. 18, p. 8637–8646, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3593142>
- [23] Z. Ban, J. Tang, Q. Xie, and Y. Li, "Ocdm-based fmcw waveform design for fso integrated sensing and communications," *Journal of Lightwave Technology*, vol. 43, no. 18, p. 8718–8728, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3592208>
- [24] B. Dong, J. Jia, Z. Li, G. Li, J. Shi, H. Wang, N. Chi, and J. Zhang, "Photonic-based flexible integrated sensing and communication with multiple targets detection capability for w-band fiber-wireless network," *IEEE Transactions on Microwave Theory and Techniques*, vol. 72, no. 8, p. 4878–4891, Aug. 2024. [Online]. Available: <http://dx.doi.org/10.1109/tmtt.2024.3355936>
- [25] A. Tishchenko, M. Khalily, A. Shojaeifard, F. Burton, E. Björnson, M. Di Renzo, and R. Tafazolli, "The emergence of multi-functional and hybrid reconfigurable intelligent surfaces for integrated sensing and communications - a survey," *IEEE Communications Surveys & Tutorials*, vol. 27, no. 5, p. 2895–2936, Oct. 2025. [Online]. Available: <http://dx.doi.org/10.1109/comst.2024.3519785>
- [26] G. Manavalan and S. Arnon, "Simultaneous optical wireless communication and sensing for brain implants," in *Neural Imaging and Sensing 2025*, Q. Luo, J. Ding, and L. Fu, Eds. SPIE, Mar. 2025, p. 28. [Online]. Available: <http://dx.doi.org/10.1117/12.3046996>
- [27] C. Fragner, A. P. Weiss, F. P. Wenzl, and E. Leitgeb, "Integrated sensing and communication in the visible spectral range: A novel closed loop controller," in *2022 International Conference on Broadband Communications for Next Generation Networks and Multimedia Applications (CoBCom)*. IEEE, Jul. 2022, p. 1–7. [Online]. Available: <http://dx.doi.org/10.1109/cobcom55489.2022.9880677>
- [28] J. Wang, L. Lu, L. Wang, Y. Yan, A. P. T. Lau, and C. Lu, "High-efficiency isac to enable sub-meter level vibration sensing for coherent fiber networks," in *Optical Fiber Communication Conference (OFC) 2024*, ser. OFC. Optica Publishing Group, 2024, p. Tu2J.3. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2024.tu2j.3>
- [29] Y. Wang, L. Wang, Z. Lin, C. Lu, M. Tang, and C. Yu, "Endogenous isac enabled interference fading free sensing via telecom training sequence," in *2025 30th OptoElectronics and Communications Conference (OECC) and 2025 International Conference on Photonics in Switching and Computing (PSC)*. IEEE, Jun. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.23919/oecc/psc62146.2025.11110297>
- [30] L. Wang, Y. Wang, Y. Li, Z. Lin, Z. Wei, C. Lu, C. Yu, and M. Tang, "Integrated communication and in-band spectrum polarization-based sensing via fraction-division non-orthogonal multiple access," *Journal of Lightwave Technology*, vol. 44, no. 1, pp. 138–147, 2026.
- [31] J. Gao, D. Liang, T. Shi, and Y. Chen, "Microwave photonic integrated sensing and communication based on polarization multiplexing and frequency-to-time mapping," *IEEE Internet of Things Journal*, vol. 12, no. 12, p. 19846–19854, Jun. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2025.3542099>
- [32] Y. Wu, L. Sun, J. Cai, W. Wang, L. Zhang, R. Xu, G. Xu, G. Ning Liu, Y. Cai, H. Huang, and G. Shen, "Advanced integration of sensing and communication with high dsp compatibility for smart network," *IEEE Photonics Technology Letters*, vol. 37, no. 21, p. 1249–1252, Nov. 2025. [Online]. Available: <http://dx.doi.org/10.1109/lpt.2025.3593343>
- [33] L. Ruan, C. Liang, J. Yin, J. Li, X. Liang, and W. Ding, "Lumipane: Intelligent interaction through gesture sensing and ambient light communication," in *2024 IEEE Globecom Workshops (GC Wkshps)*. IEEE, Dec. 2024, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/gcwkshp64532.2024.11101040>
- [34] S. Wang and H. Chen, "Optical integrated sensing and communication for cooperative mobile robotics: Design and experiments," in *2023 21st International Symposium on Modeling and Optimization in Mobile, Ad Hoc, and Wireless Networks (WiOpt)*. IEEE, Aug. 2023, p. 207–214. [Online]. Available: <http://dx.doi.org/10.23919/wiopt58741.2023.10349823>
- [35] Y. Song, R. Mo, P. Zhang, C. Wang, Z. Sheng, Y. Sun, and Y. Yang, "Vehicletalk: Lightweight v2v network enabled by optical wireless communication and sensing," in *2024 IEEE 99th Vehicular Technology Conference (VTC2024-Spring)*. IEEE, Jun. 2024, p. 1–5. [Online]. Available: <http://dx.doi.org/10.1109/vtc2024-spring62846.2024.10683127>
- [36] X. Zhang, G. Klevering, K. Wijewardena, and L. Xiao, "Demo: Integrated on-site localization and optical camera communication for drones," in *2023 IEEE 24th International Symposium on a World of Wireless, Mobile and Multimedia Networks (WoWMoM)*. IEEE, Jun. 2023, p. 334–336. [Online]. Available: <http://dx.doi.org/10.1109/wowmom57956.2023.00055>
- [37] J. Freytag, I. F. Priyanta, R. Ahlbäumer, S. Kauffmann, and J. Emmerich, "Demo: Towards 6g-enabled multi-robot process orchestration in complex logistics environments," in *2025 IEEE 50th Conference on Local Computer Networks (LCN)*. IEEE, Oct. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.1109/lcn65610.2025.11146333>
- [38] Z. Wei, B. Mao, H. Guo, Y. Xun, J. Liu, and N. Kato, "An intelligent path loss prediction approach based on integrated sensing and communications for future vehicular networks," *IEEE Open*

- Journal of the Computer Society*, vol. 5, p. 170–180, 2024. [Online]. Available: <http://dx.doi.org/10.1109/ojcs.2024.3386733>
- [39] B. M. Rosmaninho, V. N. H. Silva, P. P. Monteiro, and M. C. R. Medeiros, “Modulation strategies for robust optical wireless communication and sensing in 6g,” in *2025 25th Anniversary International Conference on Transparent Optical Networks (ICTON)*, 2025, pp. 1–4.
- [40] Z. Huang, J. Li, X. Yu, J. He, Y. Qin, M. Xiang, and S. Fu, “Performance improvement for symmetric carrier-assisted differential detection receiver by pairwise coding,” in *2024 12th International Conference on Intelligent Computing and Wireless Optical Communications (ICWOC)*. IEEE, Jun. 2024, p. 82–86. [Online]. Available: <http://dx.doi.org/10.1109/icwoc62055.2024.10684954>
- [41] J. Yu, Y. Wang, J. Ding, J. Zhang, W. Li, F. Wang, C. Wang, K. Wang, Y. Tan, M. Zhu, Y. Cai, B. Hua, M. Lei, T. Xie, J. Yu, F. Zhao, W. Zhou, and X. You, “Broadband photon-assisted terahertz communication and sensing,” *Journal of Lightwave Technology*, vol. 41, no. 11, p. 3332–3349, Jun. 2023. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2023.3252821>
- [42] H. Guo, K. Liu, Y. Li, J. Liu, H. Wang, J. Deng, J. Jiang, T. Liu, and Z. Ding, “Single-ended > 100-km distributed vibration sensor based on ofdr using pearson correlation coefficient,” *IEEE Sensors Journal*, vol. 25, no. 9, p. 15143–15154, May 2025. [Online]. Available: <http://dx.doi.org/10.1109/jsen.2025.3554542>
- [43] L. Maoqi, W. Jingchuan, L. Chen, Y. Changyuan, and L. Chao, “Pre-compensation of lfm sensing probe via integrated sensing and communication over fiber system,” in *2025 30th OptoElectronics and Communications Conference (OECC) and 2025 International Conference on Photonics in Switching and Computing (PSC)*. IEEE, Jun. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.23919/oeccpsc62146.2025.11111272>
- [44] R. An, Y. Wang, X. Ping, K. Wen, Y. Yuan, S. Wang, J. Yang, Y. Wang, and Y. Qin, “Temperature compensation method for polarization-multiplexed fiber-optic vibration sensing unit,” *IEEE Sensors Journal*, vol. 25, no. 2, p. 2658–2666, Jan. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jsen.2024.3501256>
- [45] B. Yang, J. Tang, C. Cheng, L. Fan, P. Yang, S. Wang, T. Zhao, J. Liang, S. Gao, J. Wei, Y. Yao, and Y. Yang, “Integrated communication and enhanced forward phase-based sensing based on frequency-domain pilot tones in dscm systems using 100 khz ecls,” *Journal of Lightwave Technology*, vol. 43, no. 6, p. 2664–2671, Mar. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2024.3510371>
- [46] M. Nafees, M. Baniasadi, J. R. Hopgood, K. Safari, and J. S. Thompson, “Integrated sensing and communication for uav trajectory optimization in mixed fso-rf networks in dynamic weather conditions,” in *2025 IEEE Wireless Communications and Networking Conference (WCNC)*. IEEE, Mar. 2025, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/wcnc61545.2025.10978163>
- [47] Y. Wen, F. Yang, J. Song, and Z. Han, “Power allocation for ofdm-based free space optical integrated sensing and communication,” in *ICC 2024 - IEEE International Conference on Communications*. IEEE, Jun. 2024, p. 2408–2413. [Online]. Available: <http://dx.doi.org/10.1109/icc51166.2024.10622583>
- [48] R. Zhang, Y. Shao, M. Li, L. Lu, and Y. C. Eldar, “Optical integrated sensing and communication with light-emitting diode,” *IEEE Internet of Things Journal*, vol. 12, no. 9, p. 12896–12911, May 2025. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3523045>
- [49] B. Dong, J. Jia, G. Li, J. Shi, H. Wang, J. Zhang, and N. Chi, “W-band photonic-based integration of sensing and communication with frequency-division multiplexed waveforms in fiber-wireless integrated network,” in *2022 Asia Communications and Photonics Conference (ACP)*. IEEE, Nov. 2022, p. 1806–1810. [Online]. Available: <http://dx.doi.org/10.1109/acp55869.2022.10088790>
- [50] J. He, L. Yin, K. Liu, S. Xiao, and Z. Chen, “Zero-padding 2d-dft scheme for photonics-assisted w-band fiber-wireless isac system with orthogonal time frequency space modulation,” *Journal of Lightwave Technology*, vol. 43, no. 20, p. 9561–9567, Oct. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3602312>
- [51] L. Li, L. Zhang, H. Zhang, Z. Lyu, Z. Yang, X. Pang, V. Bobrov, O. Ozolins, H. Zhao, F. Li, C. Zhang, and X. Yu, “Thz-over-fiber system with orthogonal chirp division multiplexing for integrated sensing and communication,” *Journal of Lightwave Technology*, vol. 42, no. 1, p. 176–183, Jan. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2023.3311645>
- [52] —, “Thz-over-fiber system with orthogonal chirp division multiplexing for integrated sensing and communication,” *Journal of Lightwave Technology*, vol. 42, no. 1, p. 176–183, Jan. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2023.3311645>
- [53] A. G. Khorasgani, M. Mirmohseni, and A. Elzanaty, “Optical isac: Fundamental performance limits and transceiver design,” in *2024 IEEE Globecom Workshops (GC Wkshps)*. IEEE, Dec. 2024, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/gcwkshp64532.2024.11101062>
- [54] Y. Wen, F. Yang, J. Song, and Z. Han, “Optical wireless integrated sensing and communication based on optical phased array: Performance metric and optimal beamforming,” *IEEE Transactions on Wireless Communications*, vol. 24, no. 9, p. 7221–7236, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/twc.2025.3559254>
- [55] —, “Optical wireless integrated sensing and communication based on eado-ofdm: A flexible resource allocation perspective,” *IEEE Transactions on Wireless Communications*, vol. 24, no. 8, p. 6964–6979, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1109/twc.2025.3557061>
- [56] S. Chen, K. Zhu, J. Han, Q. Sui, and Z. Li, “Photonic integrated sensing and communication system harnessing submarine fiber optic cables for coastal event monitoring,” *IEEE Communications Magazine*, vol. 60, no. 12, p. 110–116, Dec. 2022. [Online]. Available: <http://dx.doi.org/10.1109/mcom.002.2200191>
- [57] J. Wang, L. Lu, J. Zhang, A. P. T. Lau, and C. Lu, “Integration of distributed sensing into optical coherent networks through non-orthogonal multiple access,” in *Optical Fiber Communication Conference (OFC) 2025*, ser. OFC. Optica Publishing Group, 2025, p. Tu3F.5. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2025.tu3f.5>
- [58] S. Chen, J. Han, Q. Sui, K. Zhu, C. Lu, and Z. Li, “Advanced signal processing in distributed acoustic sensors based on submarine cables for seismology applications,” *Journal of Lightwave Technology*, vol. 41, no. 13, p. 4164–4175, Jul. 2023. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2023.3273268>
- [59] W. Wang, H. Wang, Z. Zeng, C. He, and C. Chen, “Uav-aided flying retroreflective optical isac with angle diversity transmitters,” in *2025 30th OptoElectronics and Communications Conference (OECC) and 2025 International Conference on Photonics in Switching and Computing (PSC)*. IEEE, Jun. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.23919/oeccpsc62146.2025.11110803>
- [60] Y. Hai, Y. Luo, C. Liu, and A. Dang, “Remote phase-shift lidar with communication,” *IEEE Transactions on Communications*, vol. 71, no. 2, p. 1059–1070, Feb. 2023. [Online]. Available: <http://dx.doi.org/10.1109/tcomm.2023.3233962>
- [61] Y. Wen, F. Yang, J. Song, and Z. Han, “Free space optical integrated sensing and communication based on lfm and cpm,” *IEEE Communications Letters*, vol. 28, no. 1, p. 43–47, Jan. 2024. [Online]. Available: <http://dx.doi.org/10.1109/lcomm.2023.3332658>
- [62] H. Wang, C. Chen, Z. Zeng, S. Shao, and H. Haas, “Bidirectional retroreflective optical isac using time division duplexing and clipped ofdm,” *IEEE Photonics Technology Letters*, vol. 37, no. 10, p. 587–590, May 2025. [Online]. Available: <http://dx.doi.org/10.1109/lpt.2025.3541038>
- [63] C. Chen and P. Du, “Retroreflective optical isac using ofdm and corner cube reflector,” in *TENCON 2024 - 2024 IEEE Region 10 Conference (TENCON)*. IEEE, Dec. 2024, p. 1134–1134. [Online]. Available: <http://dx.doi.org/10.1109/tencon61640.2024.10902867>
- [64] Z. Liu, J. Zhu, J. Yang, Y. Sun, Y. Yang, and J. Luo, “Reflexgest: Recognizing hand gestures under vlc-capable lamps,” *IEEE Transactions on Mobile Computing*, vol. 24, no. 7, p. 6583–6594, Jul. 2025. [Online]. Available: <http://dx.doi.org/10.1109/tmc.2025.3545340>
- [65] J. Wang, N. Huang, C. Gong, W. Wang, and X. Li, “Pam waveform design for joint communication and sensing based on visible light,” *IEEE Internet of Things Journal*, vol. 11, no. 11, p. 20731–20742, Jun. 2024. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3373447>
- [66] A. A. Mohamed Nishar, S. Paul, and A. Ashok, “Poster abstract: Joint optical wireless communication and sensing using neuromorphic cameras,” in *2024 23rd ACM/IEEE International Conference on Information Processing in Sensor Networks (IPSN)*. IEEE, May 2024, p. 305–306. [Online]. Available: <http://dx.doi.org/10.1109/ipsn61024.2024.00053>
- [67] L. Zhang, Z. Lyu, O. Ozolins, X. Pang, and X. Yu, “Photonic terahertz integrated sensing and communication (isac) systems,” in *Optical Fiber Communication Conference (OFC) 2025*, ser. OFC. Optica Publishing Group, 2025, p. W4F.6. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2025.w4f.6>
- [68] W. Bai, X. Zou, P. Li, W. Pan, L. Yan, and B. Luo, “60-ghz photonic millimeter-wave joint radar-communication system,” in *2021 International Conference on Microwave and Millimeter Wave*

- Technology (ICMMT)*. IEEE, May 2021, p. 1–3. [Online]. Available: <http://dx.doi.org/10.1109/icmmt52847.2021.9618314>
- [69] M. Cao, Y. Wang, Y. Zhang, D. Gao, and H. Zhou, “A unified waveform for optical wireless integrated sensing and communication,” in *2022 Asia Communications and Photonics Conference (ACP)*. IEEE, Nov. 2022, p. 448–452. [Online]. Available: <http://dx.doi.org/10.1109/acp55869.2022.10088865>
- [70] J. Du, C. Chen, Z. Zeng, D. Wang, J. Ye, J. Song, and H. Haas, “Flexible waveform design for ro-isac based on ofdm-embedded maximum length sequence,” *IEEE Wireless Communications Letters*, vol. 14, no. 10, p. 3334–3338, Oct. 2025. [Online]. Available: <http://dx.doi.org/10.1109/lwc.2025.3593253>
- [71] G. Zhou, M. Cao, Q. Yang, Y. Zhang, S. Han, and H. Wang, “Integrated design of ofdm-lfm lidar communication in iov environment,” in *2024 IEEE 12th International Conference on Information, Communication and Networks (ICICN)*. IEEE, Aug. 2024, p. 160–164. [Online]. Available: <http://dx.doi.org/10.1109/icicn62625.2024.10761294>
- [72] L. Wang, Y. Wang, Z. Lin, H. Yu, Y. Li, C. Lu, C. Yu, and M. Tang, “Endogenous integration of communication and interference fading free sensing using telecom pilots via joint polarization-fraction domain multiplexing,” *Optics Express*, vol. 33, no. 16, p. 34663, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1364/oe.563557>
- [73] W. Wang, C. Chen, H. Wang, Z. Zeng, D. Wang, J. Ye, M. Kong, M. Liu, and H. Haas, “Multiuser retroreflective optical isac: Waveform design, joint sensing and multiple access,” *Journal of Lightwave Technology*, p. 1–9, 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3642513>
- [74] K. Li, J. Wang, H. Cui, B. Zhou, and P. Fan, “Low-papr ofdm-isac waveform design based on frequency-domain phase differences,” *IEEE Internet of Things Journal*, p. 1–1, 2025. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2025.3599171>
- [75] X. Xia, R. Yao, X. Nan, Z. Zhang, J. Feng, Y. Fan, and X. Zuo, “Three-stage super-resolution estimation of target parameter in ocdm isac systems,” *IEEE Wireless Communications Letters*, vol. 14, no. 9, p. 2947–2951, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/lwc.2025.3583732>
- [76] A. Safiriyu, M. Vargemidou, C. Vagionas, J. Ramirez, F. Salim, N. Pleros, A. Miliou, A.-L. Billabert, and C. Algani, “Heterogeneous integrated iii-v-on-soi transmitter for 6g fiwi mmwave/fso integrated sensing and communication,” in *2025 European Conference on Optical Communications (ECOC)*. IEEE, Sep. 2025, p. 1–5. [Online]. Available: <http://dx.doi.org/10.1109/ecoc66593.2025.11263375>
- [77] Y. Qiu, X. Ou, M. Luo, C. Yang, Z. He, X. Xiao, Y. Yang, and J. Tao, “Simultaneous sensing and communication over 20 km fiber based on si₃n₄ micro-ring,” in *2024 Conference on Lasers and Electro-Optics Pacific Rim (CLEO-PR)*. IEEE, Aug. 2024, p. 1–2. [Online]. Available: <http://dx.doi.org/10.1109/cleo-pr60912.2024.10676568>
- [78] K. Dong, W. Cao, and M. Wang, “Optical camera-based integrated sensing and communication for v2x applications: Model and optimization,” *Sensors*, vol. 25, no. 22, p. 7061, Nov. 2025. [Online]. Available: <http://dx.doi.org/10.3390/s25227061>
- [79] R. Kumar Gaur, “Research article,” *SciFed Virology Research Journal*, vol. 1, no. 1, Apr. 2017. [Online]. Available: <http://dx.doi.org/10.23959/sfjv-1000006>
- [80] X. Li, M. Han, M. Chen, Y. Li, F. Qin, G. Zhu, L. Wang, and Y. Wang, “Integrated sensing and communication chip based on iii-nitride for motion detection,” *ACS Omega*, vol. 8, no. 16, p. 14656–14661, Apr. 2023. [Online]. Available: <http://dx.doi.org/10.1021/acsomega.3c00521>
- [81] Y. Jiang, M. Xie, Z. Shi, and Y. Wang, “Monolithic iii-nitride photonic circuit for integrated sensing and communication system,” in *2023 20th China International Forum on Solid State Lighting & 2023 9th International Forum on Wide Bandgap Semiconductors (SSLCHINA: IFWS)*. IEEE, Nov. 2023, p. 457–460. [Online]. Available: <http://dx.doi.org/10.1109/sslchinaifws60785.2023.10399712>
- [82] J.-Y. Wang, H.-N. Yang, J.-B. Wang, M. Lin, and P. Shi, “Joint optimization of slot selection and power allocation in integrated visible light communication and sensing systems,” *IEEE Internet of Things Journal*, vol. 10, no. 24, p. 22415–22426, Dec. 2023. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2023.3303137>
- [83] Y. Wen, F. Yang, J. Song, and Z. Han, “Adaptive resource allocation in ado-ofdm for optical wireless integrated sensing and communication,” in *GLOBECOM 2024 - 2024 IEEE Global Communications Conference*. IEEE, Dec. 2024, p. 2311–2316. [Online]. Available: <http://dx.doi.org/10.1109/globecom52923.2024.10901628>
- [84] R. Raj, D. Dass, K. Kaevai, S. Patri, V. Sleiffer, B. Baeuerle, W. Heni, M. Ruffini, C. Browning, A. Naughton, R. Mackey, D. Mackey, B. Vukovic, J. Smajic, J. Leuthold, C. Natalino, L. Wosinska, T. Svensson, A. Kaszubowska-Anandarajah, I. Mesogiti, S. Pryor, A. Tzanakaki, R. Nejabati, P. Monti, and D. Kilper, “Towards efficient confluent edge networks,” in *2024 Joint European Conference on Networks and Communications & 6G Summit (EuCNC/6G Summit)*. IEEE, Jun. 2024, p. 1163–1168. [Online]. Available: <http://dx.doi.org/10.1109/eucnc/6gsummit60053.2024.10597093>
- [85] W. Bai, P. Li, X. Zou, N. Zhong, W. Pan, X. Deng, and L. Yan, “Photonics-assisted millimeter-wave multiband integrated sensing and communication system using coherent receiving,” *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 29, no. 6: Photonic Signal Processing, p. 1–11, Nov. 2023. [Online]. Available: <http://dx.doi.org/10.1109/jstqe.2023.3276903>
- [86] Y. Gong, Y. Zhao, S. Wang, M. Yang, Y. Wang, and J. Wang, “Machine learning-enhanced multipump rfa for high-performance optical backbone in low-altitude sensing and communication,” *IEEE Internet of Things Journal*, vol. 13, no. 4, p. 5451–5463, Feb. 2026. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2025.3626345>
- [87] Z. Ye, Y. He, G. Yu, and P. Loskot, “Radar-lidar fusion-aided rf beams prediction for vehicular communications,” *IEEE Open Journal of the Communications Society*, vol. 6, p. 5121–5134, 2025. [Online]. Available: <http://dx.doi.org/10.1109/ojcoms.2025.3577193>
- [88] Y. Xie, Y. Gong, Y. Zhao, M. Zhou, S. Wang, D. Zhang, Y. Wang, and J. Wang, “Mpfusionnet: Transformer-based multimodal perception fusion for predictive beamforming in low-altitude uav communication networks,” *IEEE Internet of Things Journal*, vol. 13, no. 4, p. 5517–5530, Feb. 2026. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2025.3623880>
- [89] S. Khunteta, Y. R. Guddeti, A. K. Reddy Chavva, and A. Agrawal, “Rf2lidar: Enabling digital twin using mimo rf signals,” in *2024 IEEE 99th Vehicular Technology Conference (VTC2024-Spring)*. IEEE, Jun. 2024, p. 1–5. [Online]. Available: <http://dx.doi.org/10.1109/vtc2024-spring62846.2024.10683334>
- [90] J. He, S. Xiao, C. Ying, Z. Chen, and Y. Xiao, “Sliding window-based lstm scheme for pam-4 photonics-assisted w-band isac systems,” *IEEE Photonics Technology Letters*, p. 1–1, 2025. [Online]. Available: <http://dx.doi.org/10.1109/lpt.2025.3614902>
- [91] E. Theodoropoulou, G. Lyberopoulos, F. Setaki, C. Marcus, O. Eriksson, B. Schrenk, P. Garcia, S. Royo, J. M. Fàbrega, R. Martínez, R. Casellas, J. R. Casas, and J. A. Lázaro, “6g-ewoc: Ai-enhanced fiber-wireless optical 6g network in support of connected mobility,” in *2024 IEEE 29th International Workshop on Computer Aided Modeling and Design of Communication Links and Networks (CAMAD)*. IEEE, Oct. 2024, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/camad62243.2024.10942755>
- [92] S. Gao, H. Chen, H. Zhang, Z. Sun, Y. Shen, and X. Lin, “All-optical computing for super-resolution direction of arrival estimation,” in *2024 Asia Communications and Photonics Conference (ACP) and International Conference on Information Photonics and Optical Communications (IPOC)*. IEEE, Nov. 2024, p. 1–4. [Online]. Available: <http://dx.doi.org/10.1109/acp/ipoc63121.2024.10809945>
- [93] M. Chen, T. Mao, Y. Zhao, W. Xiao, D. Zheng, Z. Wang, J. Zhang, and S. Chen, “New paradigm for integrated sensing and communication with rydberg atomic receiver,” *IEEE Communications Magazine*, vol. 63, no. 12, p. 104–111, Dec. 2025. [Online]. Available: <http://dx.doi.org/10.1109/mcom.001.2500371>
- [94] P. Dong, P. Tang, Y. Yin, L. Tian, and J. Zhang, “Analysis of visible light-based isac channel characteristics in a v2v scenario,” in *2025 IEEE Wireless Communications and Networking Conference (WCNC)*. IEEE, Mar. 2025, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/wcnc61545.2025.10978645>
- [95] Y. Wen, F. Yang, J. Song, and Z. Han, “Optimal beamforming for optical wireless integrated sensing and communication based on optical phased array,” in *ICC 2025 - IEEE International Conference on Communications*. IEEE, Jun. 2025, p. 2278–2283. [Online]. Available: <http://dx.doi.org/10.1109/icc52391.2025.11160979>
- [96] G. Cheng, F. Wang, Z. Zhang, X. Li, N. Cong Luong, and A. Nallanathan, “Optical irs-aided indoor visible light fingerprint localization,” *IEEE Transactions on Green Communications and Networking*, vol. 10, p. 533–545, 2026. [Online]. Available: <http://dx.doi.org/10.1109/tgcn.2025.3589348>
- [97] S. Soderi and A. Zappone, “Secrecy energy efficiency of hybrid wireless body area networks,” *IEEE Transactions on Mobile Computing*, vol. 25, no. 3, p. 3649–3662, Mar. 2026. [Online]. Available: <http://dx.doi.org/10.1109/tmc.2025.3618098>
- [98] E. Illi, M. Qaraqe, S. Althunibat, A. Alhasanat, M. Alsafasfeh, M. de Ree, G. Mantas, J. Rodriguez, W. Aman, and S. Al-Kuwari, “Physical layer security for authentication, confidentiality,

- and malicious node detection: A paradigm shift in securing iot networks,” *IEEE Communications Surveys & Tutorials*, vol. 26, no. 1, p. 347–388, 2024. [Online]. Available: <http://dx.doi.org/10.1109/comst.2023.3327327>
- [99] A. DeMaria, “Optical fiber technology,” *IEEE Journal of Quantum Electronics*, vol. 14, no. 6, p. 451–451, Jun. 1978. [Online]. Available: <http://dx.doi.org/10.1109/jqe.1978.1069822>
- [100] Y. Chen, X. Liao, J. Xiao, X. Wang, M. Ye, Y. Yu, and C. Wang, “Wide-steering integrated sensing and communication opa-based lidar design with joint waveform and thinned antenna,” in *2025 30th OptoElectronics and Communications Conference (OECC) and 2025 International Conference on Photonics in Switching and Computing (PSC)*. IEEE, Jun. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.23919/oecc/psc62146.2025.11111436>
- [101] N. S. Mannem, J. Park, E. Erfani, E. Liu, J. Lee, and H. Wang, “A reconfigurable phase-time array transmitter achieving keyless secured transmission and multi-receiver localization for low-latency joint communication and sensing,” *IEEE Journal of Solid-State Circuits*, vol. 58, no. 7, p. 1898–1912, Jul. 2023. [Online]. Available: <http://dx.doi.org/10.1109/jssc.2023.3237462>
- [102] R. Wu, J. Li, G. Zhou, M. Xiang, L. Zhang, Y. Qin, and S. Fu, “Simple and precise characterization of full-field frequency response for coherent tosa,” *Journal of Lightwave Technology*, vol. 42, no. 9, p. 3184–3191, May 2024. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2024.3352493>
- [103] A. Alshehry, A. Kassem, Z. Liu, and I. Darwazeh, “Clock and carrier synchronization using optical frequency combs in radio access networks,” in *2025 31st International Conference on Telecommunications (ICT)*. IEEE, Apr. 2025, p. 1–6. [Online]. Available: <http://dx.doi.org/10.1109/ict65093.2025.11046275>
- [104] C. Wang, Z. Lyu, L. Zhang, and X. Yu, “Photonics-enabled full-duplex millimeter-wave integrated sensing and communication,” in *2024 Asia Communications and Photonics Conference (ACP) and International Conference on Information Photonics and Optical Communications (IPOC)*. IEEE, Nov. 2024, p. 1–4. [Online]. Available: <http://dx.doi.org/10.1109/acp/ipoc63121.2024.10810000>
- [105] F. Li, X. Zhou, Q. Fan, Y. Gao, J. Huo, J. Yuan, and K. Long, “Double-effect dnn-based dbp scheme for integrated sensing and communications (isac),” in *Optical Fiber Communication Conference (OFC) 2022*, ser. OFC. Optica Publishing Group, 2022, p. Th2A.36. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2022.th2a.36>
- [106] H. Wang, Z. Zhang, Y. Ge, and B. Zhu, “Optical integrated sensing and communication system based on combination of oirs and pd array for mobile scenarios,” *IEEE Transactions on Wireless Communications*, vol. 23, no. 12, p. 19522–19536, Dec. 2024. [Online]. Available: <http://dx.doi.org/10.1109/twc.2024.3484569>
- [107] J. Wu, Z. Liu, L. Liu, H. Ji, and W. Shieh, “Simultaneous transmission and sensing emulation using interconnected counter-propagating recirculating loops,” in *2025 European Conference on Optical Communications (ECOC)*. IEEE, Sep. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.1109/ecoc66593.2025.11262977>
- [108] R. Skopec, “Research article,” *SciFed Journal of Immunology*, vol. 1, no. 1, Dec. 2017. [Online]. Available: <http://dx.doi.org/10.23959/sfji-1000005>
- [109] B. Dong, J. Jia, G. Li, J. Shi, H. Wang, J. Zhang, and N. Chi, “Demonstration of photonics-based flexible integration of sensing and communication with adaptive waveforms for a w-band fiber-wireless integrated network,” *Optics Express*, vol. 30, no. 22, p. 40936, Oct. 2022. [Online]. Available: <http://dx.doi.org/10.1364/oe.472693>
- [110] Y. Yan, J. Zhang, Y. Li, L. Lu, J. Wang, K. Chandramouli, C. Lu, and A. P. T. Lau, “Integrated sensing and communications for metropolitan environments,” in *Optical Fiber Communication Conference (OFC) 2025*, ser. OFC. Optica Publishing Group, 2025, p. Tu3C.3. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2025.tu3c.3>
- [111] H. Wang, Z. Zeng, C. Chen, B. Zhu, S. Shao, and M. Liu, “Retroreflective optical isac supporting 3d positioning in indoor environments,” in *2024 Asia Communications and Photonics Conference (ACP) and International Conference on Information Photonics and Optical Communications (IPOC)*. IEEE, Nov. 2024, p. 1–5. [Online]. Available: <http://dx.doi.org/10.1109/acp/ipoc63121.2024.10809915>
- [112] Y. Wen, F. Yang, J. Song, and Z. Han, “Pulse sequence sensing and pulse position modulation for optical integrated sensing and communication,” *IEEE Communications Letters*, vol. 27, no. 6, p. 1525–1529, Jun. 2023. [Online]. Available: <http://dx.doi.org/10.1109/lcomm.2023.3270184>
- [113] S. Chen, C. Chen, Z. Zeng, Y. Yang, and H. Haas, “Full-duplex ro-isac system: Wavelength division duplexing and hybrid waveform design,” *IEEE Photonics Technology Letters*, vol. 37, no. 15, p. 869–872, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1109/lpt.2025.3570997>
- [114] G. Wang, F. Yang, J. Song, and Z. Han, “Free space optical communication for inter-satellite link: Architecture, potentials and trends,” *IEEE Communications Magazine*, vol. 62, no. 3, p. 110–116, Mar. 2024. [Online]. Available: <http://dx.doi.org/10.1109/mcom.002.2300024>
- [115] U. Kopyiwattage, A. D. Ranjula, N. Jayaweera, D. Marasinghe, N. Rajatheva, S. Hakola, T. Koskela, O. Tervo, J. Karjalainen, and J. Hukkunen, “Lidar aided simulation pipeline for wireless communication in vehicular traffic scenarios,” in *2023 IEEE 34th Annual International Symposium on Personal, Indoor and Mobile Radio Communications (PIMRC)*. IEEE, Sep. 2023, p. 1–7. [Online]. Available: <http://dx.doi.org/10.1109/pimrc56721.2023.10294057>
- [116] A. Aboltins, V. Bepal'ko, and V. Kurtenoks, “Continuous event recording technology for integrated sensing and communications in space,” in *IGARSS 2024 - 2024 IEEE International Geoscience and Remote Sensing Symposium*. IEEE, Jul. 2024, p. 2971–2974. [Online]. Available: <http://dx.doi.org/10.1109/igarss53475.2024.10642111>
- [117] Y. Li, Q. Huang, C. Wang, Y. Huang, W. Wu, J. Ran, Y. Li, J. Xue, S. Ertman, C. Lu, O. Xu, X. Dong, T. R. Woliński, and P. Ping Shum, “Low crosstalk deep ocean salinity monitoring at 2 μ m wavelength band,” *IEEE Sensors Journal*, vol. 25, no. 15, pp. 28 380–28 389, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jsen.2025.3579715>
- [118] R. Zhang, Y. Shao, M. Li, L. Lu, and Y. C. Eldar, “Optical integrated sensing and communication with light-emitting diode,” *IEEE Internet of Things Journal*, vol. 12, no. 9, p. 12896–12911, May 2025. [Online]. Available: <http://dx.doi.org/10.1109/jiot.2024.3523045>
- [119] Z. Yixiao, L. Xuan, Z. Shanghong, W. Guodong, W. Ruiqiong, M. Qingqing, X. Lingrui, Q. Hao, and Z. Zihang, “Photonic-aided doppler-robust isac system based on index modulation and chirp multiplexing,” *Optics Express*, vol. 33, no. 17, p. 35059, Aug. 2025. [Online]. Available: <http://dx.doi.org/10.1364/oe.564416>
- [120] M. Wu, H. Yang, W. Liu, Q. Yao, J. Zhang, and M. Cheriet, “An adaptive control system for satellite-ground laser communication based on integrated sensing and communication,” in *2025 30th OptoElectronics and Communications Conference (OECC) and 2025 International Conference on Photonics in Switching and Computing (PSC)*. IEEE, Jun. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.23919/oecc/psc62146.2025.11110813>
- [121] F. Matera, M. Settembre, A. Rago, A. Fascista, G. Piro, L. A. Grieco, F. Malandrino, G. Virone, E. Cianca, M. Ruggieri, and S. Morosi, “Terrestrial and non-terrestrial networks for integrated sensing and communication,” in *2024 IEEE International Symposium on Systems Engineering (ISSE)*. IEEE, Oct. 2024, p. 1–5. [Online]. Available: <http://dx.doi.org/10.1109/isse63315.2024.10741118>
- [122] H. Xiao, W. Wang, K. Zhang, F. Li, and C. Sun, “Microalgae density measurement using quantum-dot-integrated sensing and communication system,” *IEEE Transactions on Instrumentation and Measurement*, vol. 74, p. 1–12, 2025. [Online]. Available: <http://dx.doi.org/10.1109/tim.2025.3595231>
- [123] J. Cai, L. Sun, Y. Wu, W. Wang, Y. Cai, G. N. Liu, and G. Shen, “Advanced smart network: empowering subsea monitoring with dense photonic integrated sensing and communication,” *Photonics Research*, vol. 13, no. 11, p. A21, Oct. 2025. [Online]. Available: <http://dx.doi.org/10.1364/prj.563034>
- [124] S. Gaiani, M. Fasano, A. Gatto, P. Parolari, P. Martelli, and P. Boffi, “Exploitation of fmf capabilities for joint communications and sensing,” in *2025 25th Anniversary International Conference on Transparent Optical Networks (ICTON)*. IEEE, Jul. 2025, p. 1–4. [Online]. Available: <http://dx.doi.org/10.1109/icton67126.2025.11125376>
- [125] P. J. Urban, E. M. Miśkiewicz, D. Karczewicz, W. Kogut, and J. Kopczyński, “Parallel path effect-free remote monitoring and sensing in live xgs-pon using legacy optical time domain reflectometry,” *Journal of Lightwave Technology*, vol. 43, no. 14, p. 6711–6719, Jul. 2025. [Online]. Available: <http://dx.doi.org/10.1109/jlt.2025.3563162>
- [126] X. Zhang, L. Xiao, and M. W. Mutka, “Poster: Holographic optical tag enabled omnidirectional iot connection,” in *Proceedings of the ACM SIGCOMM 2024 Conference: Posters and Demos*, ser. ACM SIGCOMM Posters and Demos '24. ACM, Aug. 2024, p. 31–32. [Online]. Available: <http://dx.doi.org/10.1145/3672202.3673726>
- [127] A. Liu, W. Jiang, S. Huang, and Z. Feng, “Multi-modal integrated sensing and communication in internet of things with large language models,” *IEEE Internet of Things Magazine*, vol. 8, no. 5, p. 103–111, Sep. 2025. [Online]. Available: <http://dx.doi.org/10.1109/miot.2025.3575888>

- [128] B. Li, J. Wang, D. Lian, Y. Gao, J. Lian, C. Tang, and B. Lian, "Passive sensing technique using cyclic prefix in power-constrained optical wireless communication systems," *IEEE Transactions on Vehicular Technology*, p. 1–12, 2025. [Online]. Available: <http://dx.doi.org/10.1109/tvt.2025.3640107>
- [129] J. Liu, Y. Hao, Z. He, M. Chen, L. Hu, and G. Wei, "Bigfibernet: Llms and fabric computing empowered large-scale non-disturbance mobile sensing networks," *IEEE Network*, vol. 39, no. 4, p. 120–130, Jul. 2025. [Online]. Available: <http://dx.doi.org/10.1109/mnet.2024.3519187>
- [130] J. Li, C. Pan, J. Pan, J. Lin, M. Lu, Z. L. Jiang, and J. Fang, "Long-distance, real-time led display-camera communication system based on led point clustering and lightweight image processing," *Photonics*, vol. 9, no. 10, p. 721, Oct. 2022. [Online]. Available: <http://dx.doi.org/10.3390/photonics9100721>
- [131] M. Anastasopoulos, J. Gutiérrez, and A. Tzanakaki, "Optical transport network optimization supporting integrated sensing and communication services," in *Optical Fiber Communication Conference (OFC) 2025*, ser. OFC. Optica Publishing Group, 2025, p. W2A.48. [Online]. Available: <http://dx.doi.org/10.1364/ofc.2025.w2a.48>
- [132] Y. Wang, Y. Zeng, S. Sun, and X. Zhang, "Coordinated fmcw and ofdm for integrated sensing and communication," *IEEE Transactions on Vehicular Technology*, p. 1–14, 2025. [Online]. Available: <http://dx.doi.org/10.1109/tvt.2025.3619057>