Add the Application Insights JavaScript SDK Loader Script as the first script in the `<head>` of each classic ASP page (or in a shared include file).

Steps

1. In the Azure portal, open your Application Insights resource → **Overview** → copy the **Connection String**.
2. Paste the loader script into your `.asp` pages (or a common include like `<!--#include file="ai.inc"-->` referenced in `<head>`).

Example (replace the connection string)

HTML

```
<script type="text/javascript">
!(function (cfg){function e(){cfg.onInit&&cfg.onInit(n)}var
x,w,D,t,E,n,C=window,O=document,b=C.location,q="script",I="ingestionendpoint",L="d
isableExceptionTracking",j="ai.device.";"instrumentationKey"[x="toLowerCase"]
(),w="crossOrigin",D="POST",t="appInsightsSDK",E=cfg.name||"appInsights",
(cfg.name||C[t])&&(C[t]=E),n=C[E]||function(g){var f=!1,m=!1,h=
{initialize:!0,queue:[],sv:"8",version:2,config:g};function v(e,t){var n=
{},i="Browser";function a(e){e=""+e;return 1===e.length?"0"+e:e}return
n[j+"id"]=i[x]
(),n[j+"type"]=i,n["ai.operation.name"]=b&&b.pathname||"_unknown_",n["ai.internal.
sdkVersion"]="javascript:snippet_"+(h.sv||h.version),{time:(i=new
Date).getUTCFullYear()+"-"+a(1+i.getUTCMonth())+"-
"+a(i.getUTCDate())+"T"+a(i.getUTCHours())+":"+a(i.getUTCMinutes())+":"+a(i.getUTC
Seconds())+"."+
(i.getUTCMilliseconds()/1e3).toFixed(3).slice(2,5)+"Z",iKey:e,name:"Microsoft.Appl
icationInsights."+e.replace(/-/g,"")+"."+t,sampleRate:100,tags:n,data:{baseData:
{ver:2}},ver:undefined,seq:"1",aiDataContract:undefined}}var
c,u,l="track",d="TrackPage",p="TrackEvent",l=
(e([l+"Event",l+"PageView",l+"Exception",l+"Trace",l+"DependencyData",l+"Metric",l
+"PageViewPerformance","start"+d,"stop"+d,"start"+p,"stop"+p,"addTelemetryInitiali
zer","setAuthenticatedUserContext","clearAuthenticatedUserContext","flush"]),h.Sev
erityLevel={Verbose:0,Information:1,Warning:2,Error:3,Critical:4},
(g.extensionConfig||{}).ApplicationInsightsAnalytics||
{});return!0!==g[L]&&!0!==l[L]&&(e(["_"+
(c="onerror")]),u=C[c],C[c]=function(e,t,n,i,a){var
o=u&&u(e,t,n,i,a);return!0!==o&&h["_"+c]
({message:e,url:t,lineNumber:n,columnNumber:i,error:a,evt:C.event}),o},g.autoExcep
tionInstrumented=!0),h}(cfg.cfg),(C[E]=n).queue&&0===n.queue.length?
(n.queue.push(e),n.trackPageView({})):e();})({
  src: "https://js.monitor.azure.com/scripts/b/ai.3.gbl.min.js",
  crossOrigin: "anonymous",
  cfg: {
    connectionString: "YOUR_CONNECTION_STRING_HERE"
  }
});
</script>
```

Tips for classic ASP

- Place it as the **first** script in `<head>` so it can track early errors and dependencies.
- For site-wide coverage, create an include file (e.g. `ai.inc`) containing only the `<script>...</script>` block and add `<!--#include file="ai.inc"-->` inside `<head>` on every page.
- After deployment, load a page and check the browser Network tab for the `ai.3.gbl.min.js` request (should return 200). Telemetry appears in Application Insights after a few minutes (page views, browser exceptions, etc.).
- This is **client-side only**. Server-side request telemetry is still unavailable for pure classic ASP.

Official docs: Application Insights JavaScript SDK