

# VUE.JS FOR REGULAR PEOPLE

Raymond Camden

# WHO AM I?

Raymond Camden

Regular Person at Amex

Blogging at [raymondcamden.com](http://raymondcamden.com)

Tweeting at [raymondcamden](https://twitter.com/raymondcamden)



**WHY VUE?**



**It is.**

Oh hell  
yeah it is.

Spoiler –  
it's Vue




**SIMPLE**





**NO BUILD PROCESS**





SCALABLE



# QUICK VUE FACTS

Created by Evan You (@youyuxi)

Released in February of 2014

Currently is version 2.6.8

Main site: [vuejs.org](https://vuejs.org)

GitHub: <https://github.com/vuejs>



# WHAT DOES VUE DO?

Two-way binding between your DOM and JavaScript

Template Language (aka Declarative Rendering)

And I know I said this - but it does more. A lot more.

# INSTALLATION

`npm install`

`cli install`

Download from site

Copy and paste a script tag FTW!!!!1!



# <SCRIPT> STYLE

```
<script src="https://unpkg.com/vue"></script>
```

# WRITE SOME CODE!

Identify where you're going to render stuff





Setup some data

Render that data

Add events (ie on this do that) and other fancy stuff



## Willy Nilly DOM Manipulation




`$('#somediv').html('woot');`

`$('#someotherdiv').val(2);`

`$('#yetanotherdiv').html('<b>This is awesome</b>');`

## Defining Vue's Place...





# EXAMPLES

<http://bit.ly/rayvuedemos>

```
<!-- header stuff -->  
<div id="app">  
</div>  
<!-- footer stuff -->
```

```
var app = new Vue({  
  el: '#app',  
  data: {  
    name: "Ray",  
    age: 44  
  }  
});
```

SOME CODE...

```
<!-- header stuff -->
<div id="app">
My name is {{name}} and
I'm {{age}} years old.
</div>
<!-- footer stuff -->
```

```
var app = new Vue({
  el: '#app',
  data: {
    name: "Ray",
    age: 44
  }
});
```

# SOME MORE CODE...

```
<div id="app">
  My name is {{name}}.
  <span v-if="age > 40">
    I remember floppies.
  </span>
</div>
```

```
<div id="app">
  My name is {{name}}.
  <span v-if="age > 40">
    I remember floppies.
  </span><span v-else>
    What's a floppy?
  </span>
</div>
```

# TEMPLATE DIRECTIVES - CONDITIONALS



```
<div id="app">
  My name is {{name}}. Here
  are things I like:
  <ul>
    <li v-for="thing in things">
      {{thing}}
    </li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    name: "Ray",
    things: [
      "cats",
      "star wars",
      "beer"
    ]
  }
});
```

# TEMPLATE DIRECTIVES - LOOPS

# WORKING WITH FORM FIELDS

v-model links to data field

Works in all kinds of form fields

```
<div id="app">
  <input type="text" id="name" v-model="name"><br/>
  My name is {{name}}.
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    count: 0
  },
  methods: {
    doIt: function() {
      this.count++;
    }
  }
})
```

# EVENTS

v-on:click="something"

Defined in methods block of Vue instance

Easy to do modifiers (v-on:submit.prevent)

@click="something"

```
<div id="app">
  <button v-on:click="doIt">Do It</button><br/>
  You did it {{count}} times.
</div>
```

# ATTRIBUTE BINDING

`v-bind:attribute="value"`

`:attribute="value"`

`v-bind:style="{bgcolor:curColor, font-style:textStyle}"`

`v-bind:class="{highlighted:isActive, color:appStatus}"`

```
<div id="app">  
    
</div>
```

# COMPUTED PROPERTIES

Virtual properties

Property X is based on real data A and B

Defined in the computed part of the Vue instance

```
<div id="app">
  <h2>Male Cats</h2>
  <ul>
    <li v-for="cat in cats"
        v-if="cat.gender === 'Male'">{{cat.name}}</li>
  </ul>

  <h2>Female Cats</h2>
  <ul>
    <li v-for="cat in cats"
        v-if="cat.gender === 'Female'">{{cat.name}}</li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    cats: [
      { "name": "Alred", "gender": "Male" },
      { "name": "Barry", "gender": "Male" },
      { "name": "China", "gender": "Female" },
      { "name": "Dolores", "gender": "Female" },
      { "name": "Enya", "gender": "Female" },
      { "name": "Franke", "gender": "Male" },
      { "name": "Georgia", "gender": "Female" }
    ]
  }
})
```

EXAMPLE (BEFORE)



```
<div id="app">
  <h2>Male Cats</h2>
  <ul>
    <li v-for="cat in maleCats">{{cat.name}}</li>
  </ul>

  <h2>Female Cats</h2>
  <ul>
    <li v-for="cat in femaleCats">{{cat.name}}</li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    cats: [
      { "name": "Alred", "gender": "Male" },
      { "name": "Barry", "gender": "Male" },
      { "name": "China", "gender": "Female" },
      { "name": "Dolores", "gender": "Female" },
      { "name": "Enya", "gender": "Female" },
      { "name": "Franke", "gender": "Male" },
      { "name": "Georgia", "gender": "Female" }
    ]
  },
  computed: {
    maleCats: function() {
      return this.cats.filter(c => c.gender === 'Male' );
    },
    femaleCats: function() {
      return this.cats.filter(c => c.gender === 'Female' );
    }
  }
})
```

# EXAMPLE (AFTER)

# VUE LIFECYCLE EVENTS

Events that occur while a Vue instance is doing stuff

beforeCreate, created, beforeMount, mounted, beforeUpdate, updated, activated, deactivated, beforeDestroy, destroyed, errorCaptured

<https://vuejs.org/v2/api/#Options-Lifecycle-Hooks>

# EXAMPLE

```
var app = new Vue({
  el: '#app',
  data: {
    films: []
  },
  created: function() {
    fetch('https://swapi.co/api/films/')
      .then(res => res.json())
      .then(res => {
        this.films = res.results;
      })
  }
})
```

```
<div id="app">
  <ul>
    <li v-for="film in films">
      {{film.title}}
    </li>
  </ul>
</div>
```

A close-up photograph of a tabby cat sleeping peacefully on a light-colored, ribbed fabric surface. The cat's eyes are closed, and its head is resting on the fabric. The image is overlaid with a dark, semi-transparent layer. The text "LET'S TAKE A QUICK BREAK..." is written in white, bold, sans-serif capital letters across the center of the image. A thin white vertical line is positioned to the right of the text.

**LET'S TAKE A QUICK  
BREAK...**

# FULL EXAMPLE: FORM VALIDATION

Do I need to explain this?

Check on submit, report on top

More examples: <https://vuejs.org/v2/cookbook/form-validation.html>

# FULL EXAMPLE: AJAX SEARCH

Accept user input

Send to remote API...

Render responses




# COMPONENTS

Re-usable objects of awesome-ness

Template + Logic + Style = Component

Also solves one of HTML's most glaring problems...

<nicolas-cage>



# EXAMPLE

---

```
Vue.component('nicolas-cage', {
  template: '',
  data() {
    return {
    }
  },
  computed: {
    url: function() {
      let theUrl = 'https://placecage.com/'+this.width+'/'+this.height;
      return theUrl;
    }
  },
  props: {
    height: {
      default: 400,
    },
    width: {
      default: 400
    }
  }
});
```

# EXAMPLE

```
<div id="app">
  <h2>Default</h2>
  <nicolas-cage></nicolas-cage>
  <p>
    <h2>H/W</h2>
    <nicolas-cage width="199" height="199"></nicolas-cage>
  </p>
</div>
```

# COMPONENT EXAMPLES

Google Static Maps: <https://www.npmjs.com/package/vue-static-map>

Bootstrap: <https://bootstrap-vue.js.org/>

Vuetify: <https://vuetifyjs.com/en/>

```
<b-tabs>
  <b-tab title="first" active>
    <br>I'm the first fading tab
  </b-tab>
  <b-tab title="second" >
    <br>I'm the second tab content
  </b-tab>
  <b-tab title="disabled" disabled>
    <br>Disabled tab!
  </b-tab>
</b-tabs>
```

# MORE COMPONENT STUFF

You can pass data in from the parent

You can listen for events from the component

Slots

# SLOT EXAMPLE

```
<mything thankyou="Hey buddy, thank you for doing that thing. I appreciate it. Here's a kitten."></mything>
```

```
<mything>
```

```
  <div slot="thankyou">
```

```
    Hey, I want to <i>really</i> thank you for taking  
    the time to do whatever. We here at Mega Corp truly  
    care that you took the time. Oh, and here, please  
    take a kitten!
```

```
  </div>
```

```
</mything>
```

# ROUTING

Not a part of Vue

Official library: vue-router (<https://router.vuejs.org>)

"If I'm at location /foo, I want to do Foo"

"If I'm at location /goo, I want to do Goo"



# EXAMPLE (FROM THE DOCS)

```
const routes = [
  { path: '/foo', component: Foo },
  { path: '/bar', component: Bar }
]

const router = new VueRouter({
  routes // short for `routes: routes`
});

const app = new Vue({
  el: '#app',
  router
});
```

# EXAMPLE (STILL FROM THE DOCS)

```
<div id="app">
  <h1>Hello App!</h1>
  <p>
    <router-link to="/foo">Go to Foo</router-link>
    <router-link to="/bar">Go to Bar</router-link>
  </p>
  <router-view></router-view>
</div>
```



# FULL EXAMPLE: MASTER/DETAIL

First page - list of data

Second page - detail

# STATE MANAGEMENT

Solves a problem you may not have!

One component, one set of data = easy

Two components, two set of data = mostly easy

Many components, one set of data = um....

# VUEX

(Another) library for Vue (deeply integrated)

"Store"

Components can read from the store

Components cannot change data in the store

# VUEX EXAMPLE

## Stocks

IBM	\$87.74
Amazon	\$80.45
Microsoft	\$118.94
Disney	\$109.11

## Holdings

IBM	0
Amazon	0
Microsoft	0
Disney	0

Total value of holdings: \$0.00

## Purchase and Sell Stocks

Buy  shares of  Purchase

Sell  shares of  Sell

You currently have \$1000.00 in cash.

# THE CLI

Scaffolding tool


Focused on SPAs (but also does prototyping well)

<https://cli.vuejs.org>

Supports Single File Components



# SINGLE FILE COMPONENTS



The image shows a code editor window titled "Hello.vue". The code is a Vue.js single-file component with three sections: template, script, and style. The template section contains a paragraph element with a binding for a variable named "greeting" and the text "World!". The script section defines a module with a data function that returns an object with a "greeting" property set to "Hello". The style section uses the "scoped" attribute and defines a CSS rule for the "p" element, setting the font size to 2em and text-align to center. The code is syntax-highlighted and includes line numbers from 1 to 20. The editor interface includes a file explorer on the left, a breadcrumb "Hello.vue", and a status bar at the bottom showing "Line 21, Column 1", "Spaces: 2", and "Vue Component".

```
1 <template>
2   <p>{{ greeting }} World!</p>
3 </template>
4
5 <script>
6 module.exports = {
7   data: function () {
8     return {
9       greeting: 'Hello'
10    }
11  }
12 }
13 </script>
14
15 <style scoped>
16 p {
17   font-size: 2em;
18   text-align: center;
19 }
20 </style>
```

Line 21, Column 1      Spaces: 2      Vue Component

# WALKTHROUGH

FYI, install via: `npm i -g @vue/cli`

Then: `vue create foo`

Or: `vue serve (with App.vue)`

BUT WAIT —  
THERE'S MORE!



# EVEN MOAR!!!

Devtools Extension (Chrome, Firefox, Electron, Apple Keynote Browser)

- <https://github.com/vuejs/vue-devtools>

Nuxt ([nuxtjs.org](https://nuxtjs.org))

Sarah Drasner on CSS-Tricks: <https://css-tricks.com/intro-to-vue-1-rendering-directives-events/>

Vue docs has a cool cookbook: <https://vuejs.org/v2/cookbook/>

My Stuff: <https://www.raymondcamden.com/tags/vuejs>

# ANY QUESTIONS?

Carol is judging your questions...

