



VUE.JS FOR REGULAR PEOPLE

Raymond Camden

WHO AM I?

Raymond Camden

Developer Evangelist at HERE

Blogging at raymondcamden.com

Tweeting at [raymondcamden](https://twitter.com/raymondcamden)

github.com/cfjedimaster/vue-pres0



WHY VUE?



Let's back up...



WHY VUE?






SIMPLE |



NO BUILD PROCESS



SCALABLE

QUICK VUE FACTS

Created by Evan You (@youyuxi)

Released in February of 2014

Currently is version 2.6.10

Main site: vuejs.org

GitHub: <https://github.com/vuejs>



BRACE YOURSELF

3.0 IS COMING

WHAT DOES VUE DO?

Two-way binding between your DOM and JavaScript

Template Language (aka Declarative Rendering)

And I know I said this - but it does more. A lot more.

INSTALLATION

npm install

cli install

Download from site

Copy and paste a script tag FTW!!!!1!



<SCRIPT> STYLE

```
<script src="https://unpkg.com/vue"></script>
```

WRITE SOME CODE!





Identify where you're going to render stuff

Setup some data

Render that data

Add events (ie on this do that) and other fancy stuff

Willy Nilly DOM Manipulation




`$('#somediv').html('woot');`

`$('#someotherdiv').val(2);`

`$('#yetanotherdiv').html('This is awesome');`

Defining Vue's Place...





EXAMPLES

<http://bit.ly/rayvuedemos>


```
<!-- header stuff -->
<div id="app">
</div>
<!-- footer stuff -->
```

```
var app = new Vue({
  el: '#app',
  data: {
    name: "Ray",
    age: 44
  }
});
```

SOME CODE...

```
<!-- header stuff -->
<div id="app">
My name is {{name}} and
I'm {{age}} years old.
</div>
<!-- footer stuff -->
```

```
var app = new Vue({
  el: '#app',
  data: {
    name: "Ray",
    age: 44
  }
});
```

SOME MORE CODE...

```
<div id="app">
  My name is {{name}}.
  <span v-if="age > 40">
    I remember floppies.
  </span>
</div>
```

```
<div id="app">
  My name is {{name}}.
  <span v-if="age > 40">
    I remember floppies.
  </span><span v-else>
    What's a floppy?
  </span>
</div>
```

TEMPLATE DIRECTIVES - CONDITIONALS

```
<div id="app">
  My name is {{name}}. Here
  are things I like:
  <ul>
    <li v-for="thing in things">
      {{thing}}
    </li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    name: "Ray",
    things: [
      "cats",
      "star wars",
      "beer"
    ]
  }
});
```

TEMPLATE DIRECTIVES - LOOPS

WORKING WITH FORM FIELDS

v-model links to data field

Works in all kinds of form fields

```
<div id="app">  
  <input type="text" id="name" v-model="name"><br/>  
  My name is {{name}}.  
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    count: 0
  },
  methods: {
    doIt: function() {
      this.count++;
    }
  }
})
```

EVENTS

v-on:click="something"

Defined in methods block of Vue instance

Easy to do modifiers (v-on:submit.prevent)

@click="something"

```
<div id="app">
  <button v-on:click="doIt">Do It</button><br/>
  You did it {{count}} times.
</div>
```

ATTRIBUTE BINDING

`v-bind:attribute="value"`

`:attribute="value"`

`v-bind:style="{bgcolor:curColor, font-style:textStyle}"`

`v-bind:class="{highlighted:isActive, color:appStatus}"`

```
<div id="app">
  
</div>
```

COMPUTED PROPERTIES

Virtual properties

Property X is based on real data A and B

Defined in the `computed` part of the Vue instance


```
<div id="app">
  <h2>Male Cats</h2>
  <ul>
    <li v-for="cat in cats"
        v-if="cat.gender === 'Male'">{{cat.name}}</li>
  </ul>

  <h2>Female Cats</h2>
  <ul>
    <li v-for="cat in cats"
        v-if="cat.gender === 'Female'">{{cat.name}}</li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    cats: [
      { "name": "Alred", "gender": "Male" },
      { "name": "Barry", "gender": "Male" },
      { "name": "China", "gender": "Female" },
      { "name": "Dolores", "gender": "Female" },
      { "name": "Enya", "gender": "Female" },
      { "name": "Franke", "gender": "Male" },
      { "name": "Georgia", "gender": "Female" }
    ]
  }
})
```

EXAMPLE (BEFORE)

```
<div id="app">
  <h2>Male Cats</h2>
  <ul>
    <li v-for="cat in maleCats">{{cat.name}}</li>
  </ul>

  <h2>Female Cats</h2>
  <ul>
    <li v-for="cat in femaleCats">{{cat.name}}</li>
  </ul>
</div>
```

```
var app = new Vue({
  el: '#app',
  data: {
    cats: [
      { "name": "Alred", "gender": "Male" },
      { "name": "Barry", "gender": "Male" },
      { "name": "China", "gender": "Female" },
      { "name": "Dolores", "gender": "Female" },
      { "name": "Enya", "gender": "Female" },
      { "name": "Franke", "gender": "Male" },
      { "name": "Georgia", "gender": "Female" }
    ]
  },
  computed: {
    maleCats: function() {
      return this.cats.filter(c => c.gender === 'Male' );
    },
    femaleCats: function() {
      return this.cats.filter(c => c.gender === 'Female' );
    }
  }
})
```

EXAMPLE (AFTER)

VUE LIFECYCLE EVENTS

Events that occur while a Vue instance is doing stuff

beforeCreate, created, beforeMount, mounted, beforeUpdate, updated, activated, deactivated, beforeDestroy, destroyed, errorCaptured

<https://vuejs.org/v2/api/#Options-Lifecycle-Hooks>

EXAMPLE

```
var app = new Vue({
  el: '#app',
  data: {
    films: []
  },
  created: function() {
    fetch('https://swapi.co/api/films/')
      .then(res => res.json())
      .then(res => {
        this.films = res.results;
      })
  }
})
```

```
<div id="app">
  <ul>
    <li v-for="film in films">
      {{film.title}}
    </li>
  </ul>
</div>
```


FILTERS

Allow you to define a "formatter" for a value

```
{{ birthDate | formatDate }}
```

```
v-bind:something="someValue | changeValue"
```

```
Chainable: {{ birthdate | makeMeNotOld | formatDate }}
```

```
Arguments: {{ birthdate | formatDate('short') }}
```

EXAMPLE

```
const app = new Vue({
  el: '#app',
  data: {
    theDate: new Date()
  },
  filters: {
    formatDate(d) {
      if(!window.Intl) return d;
      return new Intl.DateTimeFormat('en-US').format(new Date(d));
    }
  }
})
```

```
<div id="app" v-cloak>
  The date is {{ theDate | formatDate }}
</div>
```

FULL EXAMPLE: FORM VALIDATION

Do I need to explain this?

Check on submit, report on top

More examples: <https://vuejs.org/v2/cookbook/form-validation.html>

FULL EXAMPLE: AJAX SEARCH

Accept user input

Send to remote API...

- <https://itunes.apple.com/search?term=TERM&limit=10&media=music>

Render responses


COMPONENTS

Re-usable objects of awesome-ness

Template + Logic + Style = Component

Also solves one of HTML's most glaring problems...

<nicholas-cage>



EXAMPLE

```
Vue.component('nicolas-cage', {
  template: '',
  data() {
    return {
    }
  },
  computed: {
    url: function() {
      let theUrl = 'https://placecage.com/' + this.width + '/' + this.height;
      return theUrl;
    }
  },
  props: {
    height: {
      default: 400,
    },
    width: {
      default: 400
    }
  }
});
```

EXAMPLE

```
<div id="app">
  <h2>Default</h2>
  <nicolas-cage></nicolas-cage>
  <p>
    <h2>H/W</h2>
    <nicolas-cage width="199" height="199"></nicolas-cage>
  </p>
</div>
```

COMPONENT EXAMPLES

Google Static Maps: <https://www.npmjs.com/package/vue-static-map>

Bootstrap: <https://bootstrap-vue.js.org/>

Vuetify: <https://vuetifyjs.com/en/>

```
<b-tabs>
  <b-tab title="first" active>
    <br>I'm the first fading tab
  </b-tab>
  <b-tab title="second" >
    <br>I'm the second tab content
  </b-tab>
  <b-tab title="disabled" disabled>
    <br>Disabled tab!
  </b-tab>
</b-tabs>
```

MORE COMPONENT STUFF

You can pass data in from the parent

You can listen for events from the component

"Sub children" (Slots)

```
<mything>
```

```
<template v-slot:thankyou>
```

```
Hey, I want to <i>really</i> thank you for taking  
the time to do whatever. We here at Mega Corp truly  
care that you took the time. Oh, and here, please  
take a kitten!
```

```
</template>
```

```
</mything>
```

FULL EXAMPLE: PLACEHOLDER

Create an `<image-placeholder>` tag

Use placeholder.com (or any other service)

Accept height and width (with defaults)

ROUTING

Not a part of Vue

Official library: vue-router (<https://router.vuejs.org>)

Maps URL paths to components

Supports dynamic paths

EXAMPLE (FROM THE DOCS)

```
const routes = [
  { path: '/foo', component: Foo },
  { path: '/bar', component: Bar }
]

const router = new VueRouter({
  routes // short for `routes: routes`
});

const app = new Vue({
  el: '#app',
  router
});
```

EXAMPLE (STILL FROM THE DOCS)

```
<div id="app">
  <h1>Hello App!</h1>
  <p>
    <router-link to="/foo">Go to Foo</router-link>
    <router-link to="/bar">Go to Bar</router-link>
  </p>
  <router-view></router-view>
</div>
```



FULL EXAMPLE: MASTER/DETAIL

First page - list of data

Second page - detail

STATE MANAGEMENT

Solves a problem you may not have!

One component, one set of data = easy

Two components, two set of data = mostly easy

Many components, one set of data = um....

VUEX

(Another) library for Vue (deeply integrated)

"Store"

Components can read from the store

Components cannot change data in the store (directly)

VUEX EXAMPLE

Stocks

IBM	\$87.74
Amazon	\$80.45
Microsoft	\$118.94
Disney	\$109.11

Holdings

IBM	0
Amazon	0
Microsoft	0
Disney	0

Total value of holdings: \$0.00

Purchase and Sell Stocks

Buy shares of Purchase

Sell shares of Sell

You currently have \$1000.00 in cash.

THE CLI


Scaffolding tool

Focused on SPAs (but also does prototyping well)

<https://cli.vuejs.org>

Supports Single File Components

SINGLE FILE COMPONENTS



The image shows a code editor window titled 'Hello.vue'. The code is written in Vue.js Single File Component syntax and is as follows:

```
1 <template>
2   <p>{{ greeting }} World!</p>
3 </template>
4
5 <script>
6   module.exports = {
7     data: function () {
8       return {
9         greeting: 'Hello'
10      }
11    }
12  }
13 </script>
14
15 <style scoped>
16   p {
17     font-size: 2em;
18     text-align: center;
19   }
20 </style>
```

The editor interface includes a tab at the top labeled 'Hello.vue', a line number gutter on the left, and a status bar at the bottom showing 'Line 21, Column 1', 'Spaces: 2', and 'Vue Component'.

WALKTHROUGH

FYI, install via: `npm i -g @vue/cli`

Then: `vue create foo`

Or: `vue serve (with App.vue)`

BUT WAIT —
THERE'S MORE!



EVEN MOAR!!!

Devtools Extension (Chrome, Firefox, Electron, Apple Keynote Browser)

- <https://github.com/vuejs/vue-devtools>

Sarah Drasner on CSS-Tricks: <https://css-tricks.com/intro-to-vue-1-rendering-directives-events/>

Vue docs has a cool cookbook: <https://vuejs.org/v2/cookbook/>

Newsletters:

- <https://news.vuejs.org>
- <https://vuejsdevelopers.com/newsletter/>

My Stuff: <https://www.raymondcamden.com/tags/vuejs>

STUFF I DIDN'T COVER

Unit Testing (<https://vuejs.org/v2/guide/unit-testing.html>)

Transitions (<https://vuejs.org/v2/guide/transitions.html>)

Custom Directives (<https://vuejs.org/v2/guide/custom-directive.html>)

More....

ANY QUESTIONS?

Carol is judging your questions...

