CoMoTk User Guide

Carl Ganter

July 14, 2020

Contents

1	Con	afiguration Model 3
	1.1	Introduction
	1.2	Microscopic Scale
	1.3	Voxel Scale
	1.4	Spatial encoding
	1.5	Selective excitation
	1.6	Susceptibility effects
2	Usa	age 6
_	2.1	Initialize CoMoTk
	$\frac{2.1}{2.2}$	RF pulse
	$\frac{2.2}{2.3}$	Time interval
	$\frac{2.3}{2.4}$	Get results
	4.4	Get results
3	Cla	ss Reference 9
	3.1	Properties (selection)
		3.1.1 n_tissues
	3.2	Preparation
		3.2.1 CoMoTk
		3.2.2 set.R1 10
		3.2.3 get.R1 10
		3.2.4 set.R2 10
		3.2.5 get.R2
		3.2.6 set.D
		3.2.7 get.D
		3.2.8 set.B1
		3.2.9 get.B1 11
		3.2.10 set.mu
		3.2.11 get.mu
		3.2.12 set.dom
		3.2.13 get.dom
		3.2.14 set.R2p
		3.2.15 get.R2p
		3.2.16 set.k
		3.2.17 get.k
		3.2.18 set.options
		3.2.19 get.options
		3.2.20 init_configuration
		3.2.21 set_derivatives
	3.3	Execution
	3.4	Results

4	Des	ign Notes	1
	4.1	Units	1
	4.2	Spoiler gradients	1
	4.3	General properties of occupied configurations	1
	4.4	Storage considerations	1
	4.5	Bookkeeping	1
References			1

1 Configuration Model

1.1 Introduction

Any MRI sequence can be approximated by an alternating sequence of instantaneous RF pulses and time intervals with (optional) gradient activity. The evolution of the associated time-dependent microscopic magnetization density depends on tissue composition (and possibly motion). While local solutions (e.g. of the Bloch equations) can often be obtained transparently, signal localization (selective excitation, spatial encoding) usually relies on their numerical integration, without providing much physical insight.

More transparent alternatives like extended phase graphs (EPG) exist, but their scope is limited to equidistant sequences of instantaneous RF pulses (a good review of EPG has been given by Weigel [1]) and they do not include susceptibility effects.

It has been shown recently that these limitations can be overcome with a generalized version of the so-called *configuration model* (CM), (link follows) which is applicable to arbitrary sequences and their building blocks (such as selective RF pulses). While the underlying theory is microscopic, the CM works with a dedicated Fourier decomposition of the magnetization density, tailored for natural and concise inclusion of signal localization and susceptibility effects.

CoMoTk is a Matlab class, which implements the configuration model as described in section 1.2.

Signal localization (i.e. the transition to the voxel scale) is discussed in section 1.3.

1.2 Microscopic Scale

We consider an arbitrary sequence of instantaneous RF pulses at time points $t_0 < t_1 < t_2 < \cdots$ with flip angles $\alpha_{\nu}(\boldsymbol{x})$ (allowed to be zero) and phases $\varphi_{\nu}(\boldsymbol{x})$. Arbitrary gradients $\boldsymbol{G}(t)$ may be played out in each time separating interval $\mathcal{I}_{\nu} := [t_{\nu-1}, t_{\nu}]$ of duration $\tau_{\nu} := t_{\nu} - t_{\nu-1}$. The corresponding zero-order gradient moment vector \boldsymbol{p}_{ν} is defined as usual

$$\boldsymbol{p}_{\nu} := \gamma \int_{t_{\nu-1}}^{t_{\nu}} dt \, \boldsymbol{G}(t) \tag{1}$$

An equivalence relation on the set $\{\mathcal{I}_{\nu}\}$ can be defined by

$$\mathcal{I}_{\nu_1} \sim \mathcal{I}_{\nu_2} \iff \tau_{\nu_1} = \tau_{\nu_2} \wedge p_{\nu_1} = p_{\nu_2}$$
 (2)

It effects a partition into d different equivalence classes \mathcal{S}_{λ} , where $\lambda \in \{1, \ldots, d\}$. We will refer to d as the *dimension* of the configuration model and define the mapping $\lambda(\nu)$ by the condition $\mathcal{I}_{\nu} \in \mathcal{S}_{\lambda(\nu)}$. Note that the gradients G(t) in the intervals $\mathcal{I}_{\nu} \in \mathcal{S}_{\lambda}$ may differ by balanced gradients, e.g. in case of phase encoding.

A static spin, located at x with local off-resonance frequency $\omega(x)$, will accumulate the phase¹

$$\vartheta_{\lambda} := \omega(\mathbf{x}) \tau_{\lambda} - \mathbf{p}_{\lambda} \mathbf{x} \tag{3}$$

in any $\mathcal{I}_{\nu} \in \mathcal{S}_{\lambda}$.

Within the configuration model of dimension d, we write the magnetization vector density, immediately before or after any RF pulse, in the form

¹Note that the notations τ_{ν} , \boldsymbol{p}_{ν} and τ_{λ} , \boldsymbol{p}_{λ} refer to different indexing. The connection is defined by the mapping $\lambda(\nu)$.

$$m\left(\boldsymbol{x},t_{\nu}^{\pm}\right) \approx \sum_{\boldsymbol{n}\in\mathbb{Z}^{d}} e^{i\left[\omega(\boldsymbol{x})\tau_{\boldsymbol{n}}-\boldsymbol{p}_{\boldsymbol{n}}\boldsymbol{x}\right]} \boldsymbol{m}^{(\boldsymbol{n})}\left(t_{\nu}^{\pm}\right)$$
 (4)

with

$$\tau_{\boldsymbol{n}} := \sum_{\lambda=1}^{d} n_{\lambda} \tau_{\lambda} \qquad \boldsymbol{p}_{\boldsymbol{n}} := \sum_{\lambda=1}^{d} n_{\lambda} \boldsymbol{p}_{\lambda}$$
 (5)

We will refer to $m^{(n)}$ as configuration vector and n as configuration order.

1.3 Voxel Scale

At first glance, the configuration model (4) is just a cumbersome and redundant way to rewrite the microscopic magnetization density m(x).

The situation changes beyond the microscopic scale, in particular for the reconstructed voxel m_{ρ} , when its true value becomes apparent.

Actually, two fundamental mechanisms are available for signal localization:

- Selective Excitation
- Spatial Encoding

Both rely on the application of gradients, effecting more or less complicated signal modulations in the vininity of a given location \boldsymbol{x} . Under the assumption that other causes² for these variations can be neglected on the voxel scale, the superposition of configurations in Eq. (4) encodes just this information via the phase factors $e^{i\boldsymbol{n}\boldsymbol{\vartheta}(\boldsymbol{x})}$.

As an example, how to apply this knowledge for both localization mechanisms, let us consider some 2D sequence with Cartesian sampling and slice selective excitation. The finite readout duration is neglected and we assume the coordinate axes to be aligned parallel to the reconstructed image, such that $x_{1,2}$ encode the locations along the orthonormal in-plane vectors $e_{1,2}$ and x_3 the position along the slice normal e_3 .

1.4 Spatial encoding

Due to finite sampling, the discrete reconstructed voxel signal m_{ρ} at position \boldsymbol{x}_{ρ} results from convolution of the transverse magnetization density $m(\boldsymbol{x})$ with a point spread function $\phi(\boldsymbol{x})$

$$m_o \propto \phi * m(\boldsymbol{x}_o)$$
 (6)

which in our example is just a scaled sinc function³

$$\phi(\boldsymbol{x}) := \prod_{j=1}^{2} \operatorname{sinc}\left(\frac{x_{j}}{\Delta x_{j}}\right) \tag{7}$$

where Δx_j denotes the pixel resolution in direction j.

 $^{^2}$ Tissue properties, partial volume effects, B_0 inhomogeneity (beyond suceptibility variations), to name a few.

³We assume the normalized version: $\operatorname{sinc}(x) := \sin \pi x / \pi x$

We now insert the configuration model (4) into (6) with $f^{(n)} := e^{i \omega \tau_n} m^{(n)}$ and get after short calculation

$$m_{\rho} \propto \sum_{\boldsymbol{n} \in \mathbb{Z}^d} \int d\boldsymbol{k} \, e^{i\,\boldsymbol{k}\boldsymbol{x}_{\rho}} \, \hat{f}^{(\boldsymbol{n})}(\boldsymbol{k}) \cdot \prod_{j=1}^{2} u \left(\frac{\pi}{\Delta x_{j}} - |k_{j} + p_{\boldsymbol{n},j}| \right)$$
 (8)

where u is the unit step function.

If the support of $\hat{f}^{(n)}$ in direction j is approximately bounded by $\pi/\Delta x_j$, only configurations with

$$|p_{n,j}| < \frac{2\pi}{\Delta x_j} \tag{9}$$

contribute to m_{ρ} .

Essentially, this matches the often encountered statement that crusher gradients should effect a 2π dephasing over the voxel dimension, in order to be effective. But we also see that this is only approximately true and depends on the severity of partial volume effects.

To summarize, p_n provides information, which configurations $m^{(n)}$ contribute to the reconstructed signal m_{ρ} .

1.5 Selective excitation

In real acquisitions, selective excitation is performed via application of a resonant B_1^+ field in presence of slice encoding gradients. For example, an amplitude modulated RF pulse is usually split into a few hundred intervals of equal duration, within each of which the gradient and B_1^+ are held constant⁵. Since rotations around different axes do not commute in general, RF pulse design treats RF pulses as a series of instantaneous small tip angle pulses interleaved by short intervals⁶ τ of constant gradient moments p in direction of the slice normal e_3 , cf. [2]. The accuracy of this approximate description is determined by the choice of τ .

For the reconstructed voxel m_{ρ} , Eq. (6) still applies in principle, since it also includes an unbounded integral along the slice normal e_3 . Due to the approximate description of the RF pulse, however, the configuration model according to Eq. (4) becomes periodic in this direction

$$m(\mathbf{x}) \equiv m\left(\mathbf{x} + n \cdot \frac{2\pi}{p} \cdot \mathbf{e}_3\right)$$
 $n \in \mathbb{Z}$ (10)

and the x_3 integral should therefore be restricted to the interval $[-\pi/p, \pi/p]$. In presence of several pulses with possibly different p_{μ} , the excitation pulse⁷ defines the integration interval. In general, p is not the only gradient mit a nonzero component in direction of e_3 . For example, to restore spin coherence across the slice, subsequent time intervals include a rephasing moment parallel to e_3 .

The effect of selective excitation can therefore be handled by a weighting factor w_n in Eq. (4)

$$e^{-i\boldsymbol{p_n}\boldsymbol{x}}\cdot m^{(\boldsymbol{n})} \rightarrow w_{\boldsymbol{n}}\cdot m^{(\boldsymbol{n})}$$
 (11)

⁴This means that the reconstructed resolution recovers the essential fine structure of the sample. In a strict sense, $\hat{f}^{(n)}$ is not bounded at all, as it is the Fourier transform of a bounded function.

⁵VERSE pulses are an exception.

⁶In the configuration model, the small intervals generate a separate dimension with a unique index, say, $\mu = 1$ and the assignments $\tau_1 = \tau$ and $p_1 = p$.

⁷This should handle virtually all relevant cases: For (T)SE sequences, the excitation pulse is uniquely defined, since excitation due to imperfect refocusing cannot enter the signal (these paths are suppressed by the crusher gradients). On the other hand, every pulse in an SSFP sequence can excite spins, but here the RF pulses are usually identical (at least with respect to duration and gradient moment).

where

$$w_{n} := \frac{p}{2\pi} \cdot \int_{-\pi/p}^{\pi/p} dx_{3} e^{-i p_{n,3} x_{3}} = \operatorname{sinc}\left(\frac{p_{n,3}}{p}\right)$$
 (12)

Since p is rather small, it is sometimes possible to assume that the third component of all p_{μ} is some integer multiple of p. In this case, Eq. (12) simplifies to

$$w_{n} = \begin{cases} 1 : p_{n,3} = 0 \\ 0 : p_{n,3} \neq 0 \end{cases}$$
 (13)

If, additionally, all nonzero in-plane gradient moments refer to (large enough) crusher gradients, the restrictions due to spatial encoding and selective excitation can be combined in a single, handy statement:

$$w_{n} = \begin{cases} 1 : p_{n} = 0 \\ 0 : p_{n} \neq 0 \end{cases}$$
 (14)

1.6 Susceptibility effects

Susceptibility related intra-voxel frequency variations $\omega_s(\boldsymbol{x})$, as part of the local resonance frequency $\omega(\boldsymbol{x})$, are typically considered as independent of gradient induced frequency modulations in the integral (6).

Under this assumption, the fluctuations are assumed to be distributed according to some zero-mean density $p(\omega_s)$ within the voxel. The associated damping factor depends on the configuration (via τ_n) and is given by

$$\hat{p}(\tau_{\mathbf{n}}) := \int d\omega_s \, e^{i\,\omega_s \tau_{\mathbf{n}}} \cdot p(\omega_s) \tag{15}$$

To calculate m_{ρ} , we replace $m^{(n)} \to \hat{p}(\tau_n) \cdot m^{(n)}$ in the configuration model (4) for all contributing n. Most commonly, a Lorentzian distribution $p(\omega_s)$ is assumed and the damping factor $\hat{p}(\tau_n)$ takes the familiar form

$$\hat{p}\left(\tau_{n}\right) = e^{-R_{2}^{\prime}\tau_{n}} \tag{16}$$

2 Usage

To familiarize with the toolkit, the scripts in the test and examples folders are recommended as a good starting point. Following, a brief overview of the basic functionality.

2.1 Initialize CoMoTk

First, we need to create an instance of CoMoTk:

```
cm = CoMoTk:
```

Next, we have to setup a few mandatory tissue parameters. In the simpliest case of a 1-peak model without diffusion, this can look like this:

It is also possible, to specify more complex n-peak models with variable relative weighting (\propto proton density), chemical shift and diffusivity. Here, a 2-peak example:

Setting w and dom is optional. If not set, they default to 1 and 0, respectively.

Another optional variable is the relative B_1^+ field (default = 1):

```
cm.B1 = 0.8;
```

There are further options, for which it is possible to modify the default settings. The most important one is the desired accuracy. A nonzero value of epsilon is set, if the number of stored configurations needs to be restricted, e.g. due to memory or performance restrictions.

Now we have to specify the initial configuration vector, corresponding to $\mathbf{n} = 0$. It is supplied as a real vector (row or column) in the usual convention (m_x, m_y, m_z) :

```
cm.init_configuration ([0;0;1]); % longitudinal magnetization
```

In addition to $m_{\nu}^{(n)}$, knowledge of certain partial derivatives $\partial m_{\nu}^{(n)}/\partial \xi$ is sometimes desired as well, e.g. for numerical optimization. This is supported in CoMoTk for $\xi \in \{R_1, R_2, D, B_1, \alpha_{\mu}, \varphi_{\mu}, \tau_{\mu}, \mathbf{p}_{\mu}, \mathbf{s}_{\mu}, \mathbf{S}_{\mu}\}$. The following command (a full example, involving every possible variable) is used, to inform CoMoTk, which derivatives need to be calculated:⁸

```
cm.set_derivatives ( ...
'R1', [ 1, 3 ], ...
                              % tissue handles (n-peak model)
'R2', 2, ...
                             % for a 1-peak model the handle (= 1)
'D', [ 2, 3 ], ...
                             % must be supplied as well
                              % only B1 has no handle
'B1', ...
                             \% non-tissue handles can be chosen
'FlipAngle', [ 2, 3 ], ...
'Phase', [ 2, 1004, 12 ], ... % arbitrarily
'tau', [ 3, 4, 6 ], ...
                             % time interval (= \mu)
'p', [ 1, 2, 4 ], ...
                             % gradient moment (see below)
```

⁸Currently, CoMoTk supports isotropic diffusion only. Therefore, the gradient shape is determined by $s := (s_{\mu}, \operatorname{tr}(S_{\mu}))$. Derivatives with respect to s for a given interval μ make only sense, if the shape does not change.

```
's', [ 4, 7 ] ... % gradient shape (see below));
```

Of course, only the desired subset of parameter/handle combinations needs to be supplied. If the command is not given, no derivatives are calculated by default.

After having initialized everything, we proceed with the actual sequence. Here, we apply instantaneous RF pulses and time intervals, typically in an alternate fashion.⁹

2.2 RF pulse

Calling an RF pulse is as simple as:

```
cm.RF( flip, phase ); % RF pulse with flip angle and phase [rad]
```

If partial derivatives with respect to flip angle(s) and/or phase(s) have been set before, the associated handles can be additionally supplied according to the following format:¹⁰

```
cm.RF( flip, phase, 'FlipAngle', flip_handle, 'Phase', phase_handle );
```

2.3 Time interval

Whether the time derivatives are needed or not, executing the time interval always needs specification of the (otherwise arbitrary) index $\mathbf{m}\mathbf{u} := \mu$, which is defined as in section 1.2. At least in the first call of each distinct interval, the duration $\mathbf{tau} := \tau_{\mu}$ must be supplied also:

```
cm.time( mu, 'tau', tau );
```

If we also require the gradient moment $p := p_{\mu}$ for the simulations (diffusion effects) or the results (e.g. slice profile), we have to add this parameter as well:¹¹

```
cm.time( mu, 'tau', tau, 'p', p );
```

Called like this, a constant gradient shape according to (??) and (??) is assumed.

For arbitrary shapes, the variable $\mathbf{s} := (\mathbf{s}_{\nu}, \operatorname{tr}(\mathbf{S}_{\nu}))$ must be added too: 12

```
cm.time( mu, 'tau', tau, 'p', p, 's', s );
```

In later calls, only the handle is required: ¹³

```
cm.time( mu );
```

Note, however, that this shorthand form is not safe for nonzero epsilon, since the dimension mu could have been eliminated (together with any knowledge about tau and p) by a previous call of meltdown(). In case of doubt, always specify all parameters.

2.4 Get results

After any RF pulse or time interval, we can obtain the sum¹⁴ (4) like this:

```
res = cm.sum( param );
```

param is a structure with optional fields:

⁹There are no restrictions, though, i.e. multiple subsequent RF pulses or time intervals are allowed as well.

¹⁰If only the flip angle derivative is needed, the phase handle is not required (and vice versa). The user is responsible for the validity of value/handle combinations. Otherwise, the result is unpredicted.

 $^{^{11}}$ p must be a 3×1 or 1×3 array. If we set an element of p equal to Inf, it is interpreted as an ideal spoiler, as defined in section 4.2

in section 4.2. 12 s must be a 4×1 or 1×4 array.

 $^{^{13}}$ The full version is also allowed. Of course, s still needs to be supplied, if the shape is variable.

¹⁴For the isochromat the sum over all tissues (if there is more than one) is performed as well.

```
omega = Local angular off-resonance frequency \omega(x)
```

 $\mathbf{x} = \text{Position } \mathbf{x} \text{ according to the definition (3)}$

 $b_n = Subset$ from the set of stored configuration orders, S_{ν}^{\pm} , to be included in the result.

```
w_n = explicit weighting factors (length( w_n ) = sum( b_n ))
```

For unset fields, the following defaults are assumed:

- omega = 0
- x = 0
- $b_n = cm.b_n (= whole sum in Eq. (4))$
- $\bullet \ \mathtt{w_n} = 1$

The result is returned separately as transverse¹⁵ (res.xy) and longitudinal (res.z) component. Calculated derivatives with respect to X are returned as res.dm_dX.xy and res.dm_dX.z, where X is any member of the set $\{R1,R2,D,B1,FlipAngle,Phase,tau,p,s\}$. We have size(res.dm_dX) = [a,b], where a = 1, except for X = p with a = 3 and X = s with a = 4. The second dimension b is just the number of derivatives to be calculated for each parameter as defined in set_derivatives().

For a restriction of the summation, the find method can be used to generate b_n:

```
b_n = cm.find(mu, n);
```

If mu and n are scalars, we have $b_n = \{n \in S_{\nu}^{\pm} : n_{mu} = n\}$. If no matching configurations are found, $b_n = []$ is returned.

mu and n can also be 1d-arrays of equal length. This can be used as a shorthand for a combination with the | operator. For example, we obtain for arrays of length 3 a result equivalent to

```
b_n = ...
cm.find( mu( 1 ), n( 1 ) ) | ...
cm.find( mu( 2 ), n( 2 ) ) | ...
cm.find( mu( 3 ), n( 3 ) );
```

If we want to single out a specific configuration $n \in S_{\nu}^{\pm}$, we have to use the & operator explicitly. For example, we get for d=3:

```
b_n = ...
cm.find( cm.mu( 1 ), n( 1 ) ) & ...
cm.find( cm.mu( 2 ), n( 2 ) ) & ...
cm.find( cm.mu( 3 ), n( 3 ) ) );
```

It is also possible, to restrict the mask b_n directly. For example, to extract all stored configurations, which satisfy $p_n = 0$, cf. Eq. (14), one could use

```
b_n = cm.b_n & reshape( ~any( cm.p_n ), size( cm.b_n ) );
```

3 Class Reference

3.1 Properties (selection)

3.1.1 n_tissues

info: number of subspecies

format: integer (≥ 1)

¹⁵In the traditional interpretation res.xy = $m_x + i m_y = \sqrt{2} \cdot m_1$, where the last term corresponds to our chosen notation in Eq. (??).

3.2 Preparation

```
3.2.1
      CoMoTk
action: constructor, creates an instance cm of CoMoTk
call: cm = CoMoTk
input: none
output: instance of class
3.2.2 set.R1
action: set relaxation rate R_1 for all tissue subspecies
mandatory: yes
call: cm.R1 = R1
input: R1 is a vector (row or column). length(R1) == n_tissues
output: none
3.2.3 get.R1
action: get R_1 value(s)
call: cm.R1
input: none
output: (row) vector of R_1 of all subspecies
3.2.4 set.R2
action: set relaxation rate R_2 for all tissue subspecies
mandatory: yes
call: cm.R2 = R2
input: R2 is a vector (row or column). length( R2 ) == n_tissues
output: none
3.2.5 get.R2
action: get R_2 value(s)
call: cm.R2
input: none
output: (row) vector of R_2 of all subspecies
```

```
3.2.6 set.D
action: set apparent diffusion coefficient D (scalar or tensor) for all tissue subspecies
mandatory: yes
call: cm.D = D
input: D is the apparent diffusion coefficient. size(D) must be either [1, n_tissues] (isotropic
     diffusion coefficient) or [ 3, 3, n_tissues ] (diffusion tensor)
output: none
3.2.7 get.D
action: get apparent diffusion coefficient/tensor
call: cm.D
input: none
output: apparent diffusion coefficient/tensor, size(cm.D) == [1, n_tissues] (isotropic diffu-
     sion) or [ 3, 3, n_tissues ] (anisotropic diffusion)
3.2.8 set.B1
action: set relative B_1
mandatory: no (default = 1)
call: cm.B1 = B1
input: B1 is a scalar \geq 0
output: none
3.2.9 get.B1
action: get B_1 value
call: cm.B1
input: none
output: B_1 value
3.2.10 set.mu
action: set relative proton density for all tissue subspecies
mandatory: no (default = ones( 1, n_tissues ))
call: cm.mu = mu
input: mu is a vector (row or column). length( mu ) == n_tissues
output: none
```

```
3.2.11 get.mu
action: get relative proton density value(s)
call: cm.mu
input: none
output: (row) vector of proton densities of all subspecies
3.2.12
        set.dom
action: set chemical shift frequency \delta\omega for all subspecies
mandatory: no (default = zeros( n_tissues, 1 ))
call: cm.dom = dom
input: dom is a vector (row or column). length( dom ) == n_tissues
output: none
3.2.13 get.dom
action: get chemical shift frequency of all tissue subspecies
call: cm.dom
input: none
output: (column) vector of chemical shift frequencies
3.2.14 set.R2p
action: set decay rate R'_2 according to Lorentzian distribution for all tissue subspecies
mandatory: no (default = 0)
call: cm.R2p = R2p
input: R2p is a vector (row or column). length( R2p ) == n_tissues
output: none
3.2.15 get.R2p
action: get R'_2 value(s)
call: cm.R2p
input: none
output: (column) vector of R'_2 of all subspecies
3.2.16 set.k
action: set the matrix of transition rates for magnetization exchange.
mandatory: no (default = [])
call: cm.k = k
```

input: k is a matrix. size(k) == [n_tissues, n_tissues]. The element k(i, j) \geq 0 is the rate of the transition j \rightarrow i. Diagonal elements are ignored and calculated according to the sum rule for particle conservation as explained in the article (citation). For consistency with the equilibrium proton density, the condition cm.k * cm.mu' \equiv 0 must also be satisfied. (the matrix cm.k has the correct diagonal elements, see below) Note that this condition is *not* checked by CoMoTk and has to be guaranteed by the user!

output: none

3.2.17 get.k

action: get the transition matrix k

call: cm.k
input: none

output: transition matrix k with calculated diagonal elements

3.2.18 set.options

action: set various options

mandatory: no (default settings exist)

call: cm.options = options

input: options is a structure with the following (mandatory) elements (hint: use the get.options method to get a proper structure with default values and modify the parameters, you want to change):

alloc_d: predicted dimension of CM to avoid reallocation (default = 1). program should also work fine, if set too low

alloc_n: predicted number of occupied states of CM to avoid reallocation (default = 1000). program should also work fine, if set too low

epsilon: discard configuration vectors with L2 norm smaller than this to prevent memory overflow and to speed up the simulation. use only, if necessary. (default = 0, i.e. nothing is discarded)

rapid_meltdown: discarding configurations should be faster (not guaranteed though) but requires
 more memory (default = true)

 ${\tt verbose:}\ a\ bit\ more\ output\ such\ as\ actual\ number\ of\ occupied\ configurations\ (default={\tt false})$

 ${\tt debug:} \ {\tt stores} \ {\tt information} \ {\tt for} \ {\tt debugging} \ {\tt purposes} \ ({\tt default} = {\tt false})$

output: none

3.2.19 get.options

action: get program options

call: cm.options

input: none

output: cf. input of set.options

3.2.20 init_configuration

action: specify initial magnetization of all subspecies and prepare everything. should be called *after* any set.* method. (only set_derivatives can and must be called later)

```
mandatory: yes
```

```
call: cm.init_configuration( m )
```

input: m is the initial state with size(m) = [3, n_tissues]. it corrsponds to the zero order (n = 0) configuration, which is the only occupied state in absence of prior RF pulses.

output: none

3.2.21 set_derivatives

action: define the derivatives to be calculated

mandatory: no

```
call: cm.set_derivatives( param )
```

input: param is a structure with one or more fields X ∈ { R1, R2, D, B1, FlipAngle, Phase, tau,
 p, s, S }. The supplied information is situational:

- $X \in \{ R1, R2, D \}$
 - $-1 \le size(X) \le n_tissues$
 - X(j) \in { 1, ..., n_tissues } sets the subspecies, for which the derivatives are calculated.
- X = B1
 - value unimportant
 - derivatives with respect to B1 will be calculated, if field exists
- X \in \{\) FlipAngle, Phase \}
 - X(j) \in { supplied handles } (see method RF)
- $X \in \{ tau, p, s, S \}$
 - $X(j) \in \{ cm.lambda \} (see method time)$

output: none (see the sum method below for details about how the calculated derivatives can be accessed)

3.3 Execution

3.4 Results

4 Design Notes

The Matlab class CoMoTk implements the configuration model according to its definition in section 1.2. In addition to executing arbitrary sequences, various first order partial derivatives (with respect sequence and tissue parameters) may be extracted as well.

4.1 Units

The toolkit assumes the following units throughout:

• **time:** [ms]

• relaxation rate: [1/ms]

• angular frequency: [rad/ms]

• apparent diffusion coefficient: $[\mu m^2/ms]$

• angles: [rad]

• length, position: $[\mu m]$

• gradient moment, spatial frequency: $[rad/\mu m]$

• velocity: [mm/s]

4.2Spoiler gradients

Spoiler and crusher gradients can be differentiated by their intended action. While the latter are used in sequences for de- and rephasing, the task of the former is to destroy transverse coherences reliably [3]. In principle, this goal can be (partly) reached by two effects:

- Voxel scale: Suppression of unwanted configurations via crusher gradients (included in p_n), as outlined in section 1.4.
- Microscopic scale: By diffusion effects.

With respect to the second mechanism, it follows from Eq. (??) and the recursion (??) that ideal spoiling can be accomplished in the limit

$$\operatorname{tr}(\boldsymbol{D}\boldsymbol{S}_{\nu}) \to \infty$$
 (17)

since then we have

$$\mathbf{F}^{(n)}(\tau_{\mu}) \rightarrow \begin{pmatrix} 0 & & \\ & e^{-\tau_{\mu}} \mathbf{p}_{n}^{T} \mathbf{D} \mathbf{p}_{n} & \\ & & 0 \end{pmatrix}$$

$$\tag{18}$$

and transverse magnetization is eliminated in all configuration orders.

Note that the condition (17) does not necessarily 16 require $p_{\mu} \to \infty$ (or $p_n \to \infty$). On the other hand, $p_{\mu} \to \infty$ will usually require¹⁷ (17) as well.

General properties of occupied configurations 4.3

Proposition 1. In absence of magnetization transfer and for $T_2 \leq T_1$, we always have

$$\sum_{\boldsymbol{n}} \left\| \boldsymbol{m}^{(\boldsymbol{n})} \right\|_{2}^{2} \leq m_{eq}^{2} \tag{19}$$

 $^{^{16}}$ Strong balanced gradients with $p_{\mu}=0$ are a simple counterexample. In the specific case (??), however, the conditions (17) and $p_{\mu} \to \infty$ are equivalent.

17 More accurately, if we replace " ∞ " by "large", this follows from the actual limitations of gradient hardware.

Proof. The RF pulses do not affect $\|\boldsymbol{m}^{(n)}\|$. Therefore we only need to consider the time intervals and the proof can be done by induction. From (??), we derive

$$\left| m_{+,j}^{(n)} \right| = \begin{cases} \left| F_{\nu,0}^{(0)} E_{00} m_{-,0}^{(0)} + (1 - E_1) m_{eq} \right| & : \quad \boldsymbol{n} = \boldsymbol{0} \wedge j = 0 \\ \left| F_{\nu,j}^{(\boldsymbol{n} - j\boldsymbol{e}_{\mu})} E_{jj} \right| \left| m_{-,j}^{(\boldsymbol{n} - j\boldsymbol{e}_{\mu})} \right| & : \quad \text{else} \end{cases}$$
 (20)

In combination with $T_2 \leq T_1$ and assuming that (19) holds for $m_-^{(n)}$, we therefore obtain

$$\sum_{n} \left\| \boldsymbol{m}_{+}^{(n)} \right\|_{2}^{2} \leq E_{1}^{2} \cdot \sum_{n} \left\| \boldsymbol{m}_{-}^{(n)} \right\|_{2}^{2} + 2E_{1}(1 - E_{1}) \left| \boldsymbol{m}_{-,0}^{(0)} \right| m_{eq} + (1 - E_{1})^{2} m_{eq}^{2} \\
\leq \left(E_{1}^{2} + 2E_{1}(1 - E_{1}) + (1 - E_{1})^{2} \right) m_{eq}^{2} \\
= m_{eq}^{2} \tag{21}$$

which completes the proof.

4.4 Storage considerations

The actual state of the configuration is defined by the set $\{n\}$ of occupied configurations and their associated configuration vectors $m^{(n)}$.

The size of the set, n_c , will increase with every time interval

$$n_c \rightarrow \begin{cases} n_c + 2d : d \rightarrow d \\ 3n_c : d \rightarrow d + 1 \end{cases}$$
 (22)

The first case applies, if the same time interval μ has been played out before¹⁸, whereas the second case applies for new intervals¹⁹.

Eq. (22) implies that n_c becomes particularly large for high dimensional configuration models. The most extreme scenario is a fingerprinting-type excitation pattern with distinct random intervals τ_{μ} . This pattern generates $n_c = 3^n$ occupied configurations after n = d time intervals, easily exceeding the memory of actual computer hardware after less than about $n \approx 20$ intervals.

Fortunately, due to relaxation, magnetization forgets about its initial state with the consequence that many (if not most) of the occupied configuration vectors $\boldsymbol{m^{(n)}}$ may be safely ignored. Formally, this immediately follows from the upper bound on $\sum_{\boldsymbol{n}} \|\boldsymbol{m^{(n)}}\|_2^2$, derived in Proposition 1.

Based on some given, user-defined limit ε , we will therefore repeatedly discard all configuration vectors with $\|\boldsymbol{m}^{(n)}\|_2 < \varepsilon$. To this end, we invoke the method meltdown() after every time interval.

For this to work properly, the actual set $m^{(n)}$ is stored in a two-dimensional array m of size²⁰ $3 \times n_a$, where n_a specifies the allocated (not necessarily occupied) space. This storage concept requires a considerable amount of bookkeeping, which is described in more detail in section 4.5.

To improve performance further, reallocations²¹ and redundant computations²² are minimized as well.

 $^{^{18}}$ In this case, the dimension of the configuration model, d remains unchanged.

¹⁹Here, the dimension d is increased by 1.

²⁰The first dimension refers to the three vector components.

 $^{^{21}}$ Mainly achieved via a sufficiently large initial value of n_a .

²²Some quantities, which are repeatedly needed in calls of identical RF pulses or time intervals are stored for reuse. When possible, updates are limited to newly entering configurations.

4.5 Bookkeeping

The n_conf stored configuration orders n of dimension d are collected in the $n_a \times \mu_a$ array n. The associated location in the allocated storage is determined by the logical $n_a \times 1$ array b_n and the $1 \times \mu_a$ array b_mu.²³

The d distinct dimensions μ are stored in the $1 \times \mu_a$ array mu.

Prior to and after the ν^{th} time interval, we denote the set of *stored* configurations \boldsymbol{n} by S_{ν}^{-} and S_{ν}^{+} , respectively. To implement the time intervals properly, particularly recursions like (??), it is crucial to guarantee that S_{ν}^{\pm} does not contain any holes: If $\boldsymbol{n} \in S_{\nu}^{\pm}$ and $\boldsymbol{n} + c \cdot \boldsymbol{e}_{\mu} \in S_{\nu}^{\pm}$ for some $\boldsymbol{n} \in \mathbb{Z}^{d}$ and $c \in \mathbb{Z} > 0$, we must have $\boldsymbol{n} + b \cdot \boldsymbol{e}_{\mu} \in S_{\nu}^{\pm}$ for every $1 \leq b \in \mathbb{Z} < c$.

Since RF pulses do not change the set of occupied configurations, we set $S_{\nu+1}^- = S_{\nu}^+$.

For each $n \in S_{\nu}^{-}$ and each dimension μ , the information whether $n \pm e_{\mu} \in S_{\nu}^{-}$ is fulfilled, is stored in a separate variable.²⁴ In case of $n \pm e_{\mu} \in S_{\nu}^{-}$, the corresponding location in memory must be available as well.²⁵

Due to the method meltdown(), the n_conf $\leq n_c$ stored configurations are some subset of \mathbb{Z}^d with²⁶ $d \leq d$. We demand that the stored set remains connected along each dimension, i.e. free of holes, as described above. We also demand that n = 0 is included at all times.

References

- [1] Matthias Weigel. Extended phase graphs: Dephasing, RF pulses, and echoes pure and simple. J. Magn. Reson. Imaging, 41(2):266–295, April 2014.
- [2] J. Pauly, P. Le Roux, D. Nishimura, and A. Macovski. Parameter relations for the shinnar-Le roux selective excitation pulse design algorithm (NMR imaging). *IEEE Trans. Med. Imaging*, 10(1):53–65, March 1991.
- [3] Xiaohong Joe Zhou Matt A. Bernstein, Kevin F. King. *Handbook of MRI Pulse Sequences*. Elsevier, 2004.

 $^{^{23}{\}rm O\,bvioulsly,\,sum(\,\,b_n\,\,)}$ and sum(b_mu) must be equal to n_conf and d, respectively.

²⁴We define two logical $n_a \times \mu_a$ arrays b_up_free and b_do_free as follows: For each stored configuration n and dimension μ , the associated entry in b_up_free is true, if the direct neighbor $n + e_{\mu}$ is not stored and false otherwise. Similarly, b_do_free is true, if $n - e_{\mu}$ is not stored and false otherwise.

²⁵Similarly, we define two $n_a \times \mu_a$ arrays idx_up and idx_do as follows: For each stored configuration n and dimension μ , with the associated entry in b_up_free equal to false, the corresponding value idx_up gives the index (with respect to the first dimension of size n_a) of the direct neighbor $n + e_{\mu}$. For the other direction, $n - e_{\mu}$, the array idx_do is defined in complete analogy.

²⁶ A populated dimension μ , for which no configuration orders $n_{\mu} \neq 0$ are stored, is de facto nonexistent and can be discarded. This can, for example, happen, if the associated time period τ_{μ} has not been played out for a long time.