

Joining tables

Monday, June 8, 2026

i Today: Monday June 8

Before class

- Perusall Assignment: [DC §11.1–11.3](#)

Plan for today

- LEGO joins activity
- Why data gets split across tables
- Keys
- `left_join()`
- `join_by()`
- `anti_join()` and `semi_join()`

Helpful links

- [Syllabus](#) · [AI policy](#) · [Schedule](#) · [R4DS Ch. 19](#) · [DC Ch. 11](#) · [dplyr reference](#)

The four joins

What a join does

A **join** combines two tables by matching rows on a shared column, which is called the **key**.

	Role
Left table	Your primary data
Right table	The lookup table (columns you want to attach)

The join type controls which rows survive when a row in one table has no match in the other.

In R: `left_join(x, y, join_by(...))`.


- `x` is the left table
- `y` is the right table.

Brickerly College Joins

The data

Each person gets 6 student bricks + 4 department bricks + 1 baseplate.

inner · left · right · full



Activity overview

Each of you should have two sets of bricks, a baseplate, and a handout showing the two corresponding datasets. The two kinds of bricks are:

- **Department bricks** (STAT, ECON, PSY, ENG): the **right table** in R
- **Student bricks** (A–F, each with a declared major): the **left table** in R

We'll build **4 joins**, one at a time. Each slide describes a scenario and asks you to physically build the answer on your baseplate. After a minute or two, I'll show the answer on the projector.

Note

Stacking convention: department brick at the base, student bricks above it. This is just a physical arrangement for the activity; it has nothing to do with which table is “left” or “right” in R.

Join 1


“Brickerly College is printing a glossy brochure of Student-Department success stories. They only want to feature complete pairs. If a student in their directory no longer belongs to one of their college’s four departments, or if one of the four departments currently has no students, they will leave them off the brochure.”

Left table: students · Right table: departments

Build this join on your baseplate.

INNER JOIN: keep only rows that match in *both* tables.

Inner join



On the plate: A with STAT, B with STAT, C with ECON, D with PSY.

Off the plate: E (undeclared), F (major not in Brickerly College), ENG (no students). The inner join only keeps mutual matches.

```
inner_join(students, departments, join_by(major == code))
```

Join 2


“Academic advising needs to send a check-in email to every single student on the roster. We want to include their department if we have it, but even if they are undeclared or switched to a major outside of our college, they must be on the email.”

Left table: students · **Right table: departments**

Build this join on your baseplate.

LEFT JOIN: keep every row from the left table; attach matches from the right where they exist.

Left join



On the plate: A with STAT, B with STAT, C with ECON, D with PSY, E solo (no declared major) and F solo (major not in Brickerly College)

Off the plate: ENG (no students in the major)

```
left_join(students, departments, join_by(major == code))
```

Join 3


“Brickerly College is setting up booths for the Academic Fair. All four departments in the college must get a booth, even if they currently have zero students enrolled. If they have students, place them at the booth.”

Left table: students · Right table: departments

Build this join on your baseplate.

RIGHT JOIN: keep every row from the right table; attach matches from the left where they exist.

Right join



On the plate: A with STAT, B with STAT, C with ECON, D with PSY, ENG with no students

Off the plate: E (no major declared) and F (major not in Brickerly College)

```
right_join(students, departments, join_by(major == code))
```

Join 4


“The Provost has demanded a total audit of Brickerly College. Every student and every department must appear on the board at least once, regardless of whether they have a match or not.”

Left table: students · Right table: departments

Build this join on your baseplate.

FULL JOIN: keep every row from both tables; fill in NA where there's no match.

Full join



On the plate: A with STAT, B with STAT, C with ECON, D with PSY, E solo (no major declared), F solo (major not in Brickerly College), ENG solo (no students in the major)

Off the plate: no bricks

```
full_join(students, departments, join_by(major == code))
```

Recap

Join	On the baseplate	Left off
Inner	Matched stacks	E, F, ENG
Left	Stacks + E solo + F solo	ENG
Right	Stacks + ENG solo	E, F
Full	Stacks + E solo + F solo + ENG solo	nothing

In dplyr, the same four joins are `inner_join()`, `left_join()`, `right_join()`, and `full_join()`. `left_join()`, where you keep everything in your main table and attach what you can from the right, will likely be the one you use the most.

Why multiple tables?

Data is often split up on purpose

The `flights` dataset from `nycflights13` has 336,776 rows, one per flight. Each row has a `carrier` column ("UA", "AA", etc.), but not the airline's full name.

The full names live in a separate `airlines` table:

```
airlines
```

```
# A tibble: 16 x 2
  carrier name
  <chr>   <chr>
1 9E      Endeavor Air Inc.
2 AA      American Airlines Inc.
3 AS      Alaska Airlines Inc.
4 B6      JetBlue Airways
5 DL      Delta Air Lines Inc.
6 EV      ExpressJet Airlines Inc.
7 F9      Frontier Airlines Inc.
8 FL      AirTran Airways Corporation
9 HA      Hawaiian Airlines Inc.
10 MQ     Envoy Air
11 OO     SkyWest Airlines Inc.
12 UA     United Air Lines Inc.
13 US     US Airways Inc.
14 VX     Virgin America
15 WN     Southwest Airlines Co.
16 YV     Mesa Airlines Inc.
```

Storing the name separately isn't an oversight. The name belongs to the airline, not to each individual flight. Keeping it in one place means you only update it once, and you don't repeat "United Air Lines Inc." a hundred thousand times.

Joins bring the tables back together

A `join` matches rows from one table to rows in another and combines them side by side:

```
flights |>
  select(month, day, carrier, flight, origin, dest) |>
  left_join(airlines, join_by(carrier))
```



```
# A tibble: 336,776 x 7
  month   day carrier flight origin dest  name
  <int> <int> <chr>    <int> <chr>  <chr> <chr>
1     1     1     1 UA      1545 EWR   IAH   United Air Lines Inc.
2     1     1     1 UA      1714 LGA   IAH   United Air Lines Inc.
3     1     1     1 AA      1141 JFK   MIA   American Airlines Inc.
4     1     1     1 B6       725 JFK   BQN   JetBlue Airways
5     1     1     1 DL       461 LGA   ATL   Delta Air Lines Inc.
6     1     1     1 UA      1696 EWR   ORD   United Air Lines Inc.
7     1     1     1 B6       507 EWR   FLL   JetBlue Airways
8     1     1     1 EV      5708 LGA   IAD   ExpressJet Airlines Inc.
9     1     1     1 B6        79 JFK   MCO   JetBlue Airways
10    1     1     1 AA       301 LGA   ORD   American Airlines Inc.
# i 336,766 more rows
```

The **name** column is now attached to each flight. The airline name appears once in **airlines**, but as many times as needed in the result.

Keys

The columns that connect tables

A **key** is a column (or set of columns) that identifies rows and links tables together.

A **primary key** uniquely identifies each row in its own table:

- **airlines\$carrier**: each two-letter code appears exactly once
- **airports\$faa**: each airport code appears exactly once
- **planes\$tailnum**: each tail number appears exactly once

A **foreign key** refers to a primary key in another table:

- **flights\$carrier** refers to **airlines\$carrier**
- **flights\$dest** (and **flights\$origin**) refer to **airports\$faa**
- **flights\$tailnum** refers to **planes\$tailnum**

The key columns often share the same name in both tables, which makes the join straightforward. When they don't, you say so explicitly.

How the nycflights13 tables connect

`flights` is the central table. The others each add detail about one piece of a flight:

Column(s) in <code>flights</code>	Connects to	Table
<code>carrier</code>	<code>carrier</code>	<code>airlines</code>
<code>tailnum</code>	<code>tailnum</code>	<code>planes</code>
<code>origin, dest</code>	<code>faa</code>	<code>airports</code>
<code>origin + time_hour</code>	<code>origin + time_hour</code>	<code>weather</code>

Both `origin` and `dest` refer to the same column in `airports`. You can join on either one depending on what you're asking.

Checking a primary key

Before joining, it's worth verifying that a column is actually a primary key – no duplicates. Count and look for any `n > 1`:

```
airlines |>
  count(carrier) |>
  filter(n > 1)
```

```
# A tibble: 0 x 2
# i 2 variables: carrier <chr>, n <int>
```

An empty result confirms `carrier` is unique in `airlines`. If you got rows back, the column isn't a primary key and the join could produce more rows than you expected.

`left_join()`

The most common join

`left_join(x, y)` keeps every row from `x` and attaches matching columns from `y`. If there's no match in `y`, the new columns get `NA`.

```
flights |>
  select(month, day, tailnum, carrier) |>
  left_join(planes |> select(tailnum, manufacturer, model),
            join_by(tailnum))
```

A tibble: 336,776 x 6

	month	day	tailnum	carrier	manufacturer	model
	<int>	<int>	<chr>	<chr>	<chr>	<chr>
1	1	1	N14228	UA	BOEING	737-824
2	1	1	N24211	UA	BOEING	737-824
3	1	1	N619AA	AA	BOEING	757-223
4	1	1	N804JB	B6	AIRBUS	A320-232
5	1	1	N668DN	DL	BOEING	757-232
6	1	1	N39463	UA	BOEING	737-924ER
7	1	1	N516JB	B6	AIRBUS INDUSTRIE	A320-232
8	1	1	N829AS	EV	CANADAIR	CL-600-2B19
9	1	1	N593JB	B6	AIRBUS	A320-232
10	1	1	N3ALAA	AA	<NA>	<NA>

i 336,766 more rows



Tip

Use `left_join()` when you want to add information to a main table. The left table stays intact since you're just pulling in extra columns from the right.

When there's no match: NA

Some tail numbers in `flights` don't appear in `planes`. `left_join()` keeps those rows anyway and fills the new columns with NA:

```
flights |>
  filter(tailnum == "N3ALAA") |>
  select(month, day, tailnum, carrier) |>
  left_join(planes |> select(tailnum, manufacturer, model),
            join_by(tailnum))
```

A tibble: 63 x 6

	month	day	tailnum	carrier	manufacturer	model
	<int>	<int>	<chr>	<chr>	<chr>	<chr>

```

1      1      1 N3ALAA AA      <NA>      <NA>
2      1      2 N3ALAA AA      <NA>      <NA>
3      1      3 N3ALAA AA      <NA>      <NA>
4      1      7 N3ALAA AA      <NA>      <NA>
5      1      8 N3ALAA AA      <NA>      <NA>
6      1     16 N3ALAA AA      <NA>      <NA>
7      1     20 N3ALAA AA      <NA>      <NA>
8      1     22 N3ALAA AA      <NA>      <NA>
9      10     11 N3ALAA AA      <NA>      <NA>
10     10     14 N3ALAA AA      <NA>      <NA>
# i 53 more rows

```

That is intentional; the flight happened whether or not we have plane records. The missing information shows up as NA rather than disappearing silently.

join_by()

When the column names match

When the key has the same name in both tables, `join_by()` is simple:

```

flights |> left_join(airlines, join_by(carrier)) # carrier == carrier
flights |> left_join(planes,   join_by(tailnum)) # tailnum == tailnum

```

`dplyr` prints which columns it matched on, so you can check it did the right thing.

When the column names differ

`airports$faa` is the primary key, but `flights` uses `origin` and `dest` to refer to airports. You tell R which columns correspond with `==` inside `join_by()`:

```

flights |>
  select(month, day, origin, dest) |>
  left_join(airports |> select(faa, name, lat, lon),
            join_by(dest == faa))

```

```

# A tibble: 336,776 x 7
  month   day origin dest  name      lat    lon
  <int> <int> <chr>  <chr> <chr>    <dbl> <dbl>

```

1	1	1 EWR	IAH	George Bush Intercontinental	30.0	-95.3
2	1	1 LGA	IAH	George Bush Intercontinental	30.0	-95.3
3	1	1 JFK	MIA	Miami Intl	25.8	-80.3
4	1	1 JFK	BQN	<NA>	NA	NA
5	1	1 LGA	ATL	Hartsfield Jackson Atlanta Intl	33.6	-84.4
6	1	1 EWR	ORD	Chicago Ohare Intl	42.0	-87.9
7	1	1 EWR	FLL	Fort Lauderdale Hollywood Intl	26.1	-80.2
8	1	1 LGA	IAD	Washington Dulles Intl	38.9	-77.5
9	1	1 JFK	MCO	Orlando Intl	28.4	-81.3
10	1	1 LGA	ORD	Chicago Ohare Intl	42.0	-87.9

i 336,766 more rows

`join_by(dest == faa)` says: match rows where `dest` in the left table equals `faa` in the right table.

The natural join pitfall

If you omit `join_by()`, dplyr matches on **all** shared column names. This can go wrong quietly.

`flights` and `planes` both have a `year` column, but `flights$year` is the flight year and `planes$year` is the year the plane was built:

```
# joins on both tailnum AND year -- almost certainly not what you want
flights |>
  select(year, month, day, tailnum) |>
  left_join(planes)
```

Joining with ``by = join_by(year, tailnum)``

```
# A tibble: 336,776 x 11
   year month   day tailnum type manufacturer model engines seats speed engine
  <int> <int> <int> <chr>   <chr> <chr>          <chr>   <int> <int> <int> <chr>
1  2013     1     1 N14228 <NA>   <NA>          <NA>     NA    NA    NA <NA>
2  2013     1     1 N24211 <NA>   <NA>          <NA>     NA    NA    NA <NA>
3  2013     1     1 N619AA <NA>   <NA>          <NA>     NA    NA    NA <NA>
4  2013     1     1 N804JB <NA>   <NA>          <NA>     NA    NA    NA <NA>
5  2013     1     1 N668DN <NA>   <NA>          <NA>     NA    NA    NA <NA>
6  2013     1     1 N39463 <NA>   <NA>          <NA>     NA    NA    NA <NA>
7  2013     1     1 N516JB <NA>   <NA>          <NA>     NA    NA    NA <NA>
8  2013     1     1 N829AS <NA>   <NA>          <NA>     NA    NA    NA <NA>
```

```

  9  2013      1      1 N593JB <NA> <NA>          <NA>      NA      NA      NA <NA>
10  2013      1      1 N3ALAA <NA> <NA>          <NA>      NA      NA      NA <NA>
# i 336,766 more rows

```

Because almost no plane was built in 2013 with a matching tailnum, the result is full of NA. Always specify `join_by()` when columns share a name but mean different things.

Other mutating joins

left, inner, right, full

All four mutating joins add columns from the right table. The difference is which rows survive – the same four cases you just built with LEGO:

Join	Rows kept
<code>left_join()</code>	all rows from the left table
<code>inner_join()</code>	only rows with a match in both tables
<code>right_join()</code>	all rows from the right table
<code>full_join()</code>	all rows from either table

`left_join()` is the right choice for adding detail to a main table. `inner_join()` is useful when you only want rows that can be fully matched on both sides.

left vs. inner: what changes

```

# left_join: keeps all 336,776 flights; unmatched rows get NA
nrow(flights |> left_join(planes, join_by(tailnum)))

```

```
[1] 336776
```

```

# inner_join: drops any flight with no matching plane record
nrow(flights |> inner_join(planes, join_by(tailnum)))

```

```
[1] 284170
```

About 50,000 flights disappear with the inner join. Whether that's right depends on your question.

Filtering joins

`semi_join()` and `anti_join()`

Filtering joins don't add columns. They filter rows based on whether a match exists in another table:

Join	Keeps...
<code>semi_join(x, y)</code>	rows in <code>x</code> that have a match in <code>y</code>
<code>anti_join(x, y)</code>	rows in <code>x</code> that don't have a match in <code>y</code>

Only the columns of `x` appear in the result – nothing from `y` is added. This is handy for checking what's present or absent in one table relative to another.

`anti_join()`: finding what's missing

Which flights have a tail number that doesn't appear in `planes` at all?

```
flights |>
  anti_join(planes, join_by(tailnum)) |>
  distinct(tailnum)
```

```
# A tibble: 722 x 1
  tailnum
  <chr>
1 N3ALAA
2 N3DUAA
3 N542MQ
4 N730MQ
5 N9EAMQ
6 N532UA
7 N3EMAA
8 N518MQ
9 N3BAAA
10 N3CYAA
# i 712 more rows
```

Over 700 unique tail numbers in `flights` have no matching record in `planes`. Worth knowing before you join in plane characteristics for an analysis.

semi_join(): filtering by membership

`semi_join()` keeps only the rows from `x` that appear in `y`. Which airports actually appear as destinations in `flights`?

```
airports |>
  semi_join(flights, join_by(faa == dest))
```

```
# A tibble: 101 x 8
```

	faa	name	lat	lon	alt	tz	dst	tzone
	<chr>	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<chr>	<chr>
1	ABQ	Albuquerque International Sunport	35.0	-107.	5355	-7	A	Ameri~
2	ACK	Nantucket Mem	41.3	-70.1	48	-5	A	Ameri~
3	ALB	Albany Intl	42.7	-73.8	285	-5	A	Ameri~
4	ANC	Ted Stevens Anchorage Intl	61.2	-150.	152	-9	A	Ameri~
5	ATL	Hartsfield Jackson Atlanta Intl	33.6	-84.4	1026	-5	A	Ameri~
6	AUS	Austin Bergstrom Intl	30.2	-97.7	542	-6	A	Ameri~
7	AVL	Asheville Regional Airport	35.4	-82.5	2165	-5	A	Ameri~
8	BDL	Bradley Intl	41.9	-72.7	173	-5	A	Ameri~
9	BGR	Bangor Intl	44.8	-68.8	192	-5	A	Ameri~
10	BHM	Birmingham Intl	33.6	-86.8	644	-6	A	Ameri~

```
# i 91 more rows
```

Only 101 of the 1,458 airports in `airports` are actual destinations in this dataset.

What we covered today

- **Why joins:** data is split by design; joins combine it on demand without duplicating storage
- **Keys:** a primary key uniquely identifies rows in its table; a foreign key points to a primary key elsewhere
- **left_join():** keeps all left rows, pulls in columns from the right; unmatched rows get NA
- **join_by():** always specify the key; use `a == b` when column names differ between tables
- **Natural join pitfall:** shared column names get joined automatically and can silently give wrong results
- **Mutating join comparison:** left keeps all left rows; inner keeps only matches; right and full less common
- **anti_join():** rows with no match; useful for finding data quality gaps
- **semi_join():** rows with a match; useful for filtering by membership in another table

Wrap-up & looking ahead

Tomorrow (Tuesday): importing data from CSV files, Excel, and web URLs, plus a look at factors vs. strings.

Upcoming Deadlines

- Tue 6/9, before class: [DC §16.1–16.2, 16.4–16.5](#)
- Mon 6/15, 11:59 p.m.: [HW 4](#)
- Thu 6/11, in class: Exam

Reach out

Stuck? Office hours, or email me (cgc5478@psu.edu) or Xinyue (xpw5228@psu.edu).

Reference

[Syllabus](#) · [AI policy](#) · [Schedule](#) · [R4DS Ch. 19](#) · [DC Ch. 11](#) · [dplyr reference](#)