WynDoze-InfoScanOverload

WynDoze-InfoScanOverload is a local inventory scanner for one operator on this PC.

An agent reads process names, listening ports, service names, installed software names, and local administrator names. It does not read file contents and it does not scan the network.

A loopback dashboard on 127.0.0.1 scores the report with a YAML rule pack and stores findings in SQLite. You review those findings as cards in a browser on the same machine.

Flag returns to triage on the next matching scan. Archive and Suppress stay. Command lines stay off unless you opt in, and then the agent stores a sealed token. The dashboard does not decrypt it.

The agent does not call a vendor. Upload uses HTTPS, or HTTP only to 127.0.0.1 or ::1. An unset ingest token or dashboard password returns 401.

On macOS the agent still collects processes and listening ports. Services, installed software, and local administrator names stay empty there.

Start-WynDoze.ps1 opens the window. Start dashboard and Stop dashboard control the loopback server. Run scan collects only and does not upload. Open documentation opens this file when it is in the project folder.

Email alerts stay off until you check the box and fill in the SMTP host, port, username, password, and recipient. The password stays in that process. It is not written into the project.

Create scheduled task registers WynDoze-InfoScanOverload-scan for the current user, daily, weekly, or monthly, at 02:30. That task runs scan --no-upload. It does not upload and it does not send mail. It is not a SYSTEM task.

The Windows operator steps are in user-guide.md. The short start commands for Windows and macOS are in README.md.