

**Syslog—**

Set up your machine so that it logs *all* mail activity on your machine to a file called `/var/log/mymaillog`. Note: this is a change in the name of the log file. Send mail from your machine and make sure the new log file records this.

1) Report: the line you put into the `syslog.conf` that did this.

Set up your machine so that it logs *all mail* activity on your machine to `jaguar.net.cecs.csulb.edu`. (Please don't swamp jaguar by logging everything.)

Send mail from your machine and make sure the log records this works. Note: On `jaguar`, you will need to examine the `syslog.conf` to see what file that `jaguar` puts this log information into. The name of the log file on jaguar is slightly different from the name of the logfile I've asked you to use on your machine.

2) Report: the line you put into the `syslog.conf` that did this.

Clean up: Remove the `jaguar` entry from your `syslog.conf`.

**Printers—**

Remove everything from your print spool (`lprm`). Use `lpq` to make sure it's empty.

Your machine uses the `lpd` print server. Add a line to your `printcap` so that your machine can print to the printer on jaguar. This printer attached to `jaguar.net.cecs.csulb.edu` is as `jaguar` and as `lp`. Make the printer on `jaguar` the default printer for the system (`lp`). Make sure you can print

3) Report: the line that you added to the `printcap`. Do not submit the entire `printcap`.