

X-Informatics Case Study: e-Commerce and Life Style Informatics: Recommender Systems Technologies IV: k'th Nearest Neighbor Algorithms (Python Track)

June 19 2013

Geoffrey Fox

gcf@indiana.edu

<http://www.infomall.org/X-InformaticsSpring2013/index.html>

Associate Dean for Research, School of Informatics and
Computing

Indiana University Bloomington

2013

Big Data Ecosystem in One Sentence

Use **Clouds** running **Data Analytics Collaboratively**
processing **Big Data** to solve problems in
X-Informatics (or e-X)

X = Astronomy, Biology, Biomedicine, Business, Chemistry, Climate,
Crisis, Earth Science, Energy, Environment, Finance, Health,
Intelligence, Lifestyle, Marketing, Medicine, Pathology, Policy, Radar,
Security, Sensor, Social, Sustainability, Wealth and Wellness with
more fields (physics) defined implicitly
Spans Industry and Science (research)

Education: **Data Science** see recent New York Times articles
<http://datascience101.wordpress.com/2013/04/13/new-york-times-data-science-articles/>



Climate Informatics
network

How Wealth Informatics can help
with your financial freedom?



Xinformatics





Biomedical Informatics

Computer Applications in Health Care
and Biomedicine



AstroInformatics2012

Redmond, WA, September 10 - 14, 2012

Journal of
Pathology
Informatics



Opportunities and Challenges in Crisis Informatics



Noella Penelope Greer (Ed.)

Business Informatics
Information technology, Management,

policy informatics network




USC Center For Energy Informatics

Home Research Publications Smar

About the Center

Welcome to the Center For Energy Informatics (CEI) at USC, an Organized Research Unit (ORU) housed in the [Viterbi School of Engineering](#). Energy Informatics is the application of inf

Lifestyle Informatics



Applications of LI
How is the training classified?
Occupation Pr
Further study
Student at the
Watch the mov
Studying Abro

Admission and registration
VU Honours Programme

ENVIRONMENTAL INFORMATICS

Lifestyle Informatics: Let people l

The study Lifestyle Informatics is about s
this bachelor including applied psycholog
knowledge about language and informatic
short better. Lifestyle Informatics: let peo
[Lifestyle Informatics](#)

combine
body,
healthier,
[aining](#)



Python K-Nearest Neighbor Algorithms


Python Example

- **Machine Learning in Action**

Peter Harrington

April, 2012 | 384 pages

ISBN: 9781617290183



- http://www.manning.com/pharrington/MLiA_SourceCode.zip
- Chapter 2
- We will use software from this book with minor enhancements to write out file in format for 3D plotting program

Files Used in Recommender Engine Python

- **datingTestSet2.txt** # A dataset of 1000 points
- **ConvertToPviz.py** # Python driver to convert dataset to a format readable by PlotViz program (3D point plotter)
- **DatingRatingforPviz.txt** # Result of converting 1000 point file
- **DatingRating-OriginalLabels.pviz** The previous file saved by Plotviz with same data but some formatting additions
- **kNN.py** # Code from book to implement k'th nearest neighbor and various utilities
- **kNNDriver.py** # Driver to invoke kNN.py and produce results discussed

Create Dataset of 2D and 3D Values and Rating (Labels)

- Two “artificial” examples
 - Start with a simple example: 4 2D vectors with Labels
 - Then move onto 1000 3D Labels
- # Set up a dataset of 4 (2D vector) items -- each of which has one of two labels
- def createDataSet():
 - group = array([[1.0,1.1],[1.0,1.0],[0,0],[0,0.1]])
 - labels = ['A','A','B','B']
 - return group, labels

Python Example I: Four 2D Vectors

- `# Set Directory`
- `%cd d:\\Python\\RecommenderCh02`
- `import kNN`

- `FigDating = figure()` # This figure will have 3 parts (subplots)

- `# Set up 4 points and associate color to two groups`
- `group, labels = kNN.createDataSet()`
- `colormap1 = { 'A':'red', 'B':'blue' }`
- `ColoredGroupLabels = []`
- `for things in labels:`
- `ColoredGroupLabels.append(colormap1[things])`

- `# Plot four points`
- `ax1 = FigDating.add_subplot(311, xlim=(-0.1,1.1), ylim=(-.05,1.15))`
- `ax1.scatter(group[:,0], group[:,1], s= 20, c= ColoredGroupLabels, marker = 'o')`

Python Example I: Four 2D vectors Contd.

- # Here we classify and plot 3 points
- # Original points circles and test points crosses
- # Original points re two clusters – each of two points – red or blue
- # Color of test points indicates classification
- testvector = [.2, .2]
- answer = kNN.classify0(testvector, group, labels, 3)
- # type answer to see result or we will plot
- ax1.scatter(testvector[0], testvector[1], s= 20, c= colormap1[answer], marker = 'x')
- testvector = [.5, .5]
- answer = kNN.classify0(testvector, group, labels, 3)
- ax1.scatter(testvector[0], testvector[1], s= 20, c= colormap1[answer], marker = 'x')
- testvector = [.75, .75]
- answer = kNN.classify0(testvector, group, labels, 3)
- ax1.scatter(testvector[0], testvector[1], s= 20, c= colormap1[answer], marker = 'x')

Finding Nearest Neighbors


- `testvector = [.75, .75]`
- `answer = kNN.classify0(testvector, group, labels, 3)`
- `ax1.scatter(testvector[0], testvector[1], s= 20, c= colormap1[answer], marker = 'x')`
- # `kNN.classify0` implements k nearest neighbor algorithm
- # It takes `testvector` and finds its Euclidean distance to all the points in `group`
- # Then it sorts distances and finds the `k` (=3 in this case) smallest distances
- # It returns label that appears most often in set of k points whose label is specified in `labels`
- # We will look at code in detail later on

Python Example II: 1000 3D vectors

- **# Read in 1000 points in file and assign colors**
- `datingDataMat, datingLabels =
kNN.file2matrix('datingTestSet2.txt')`
- `datingLabelArray = array(datingLabels)`
- `colormap2 = { 1:'red', 2:'blue', 3:'green' }`
- `ColoredDatingLabel = []`
- `for things in datingLabelArray:`
- `ColoredDatingLabel.append(colormap2[things])`

Python Example II: 1000 3D vectors Contd.

- **# Plot unnormalized results**
- `ax2 = FigDating.add_subplot(312, xlim=(0,100000), ylim=(0,25))`
- `ax2.scatter(datingDataMat[:,0], datingDataMat[:,1], s= 20, c= ColoredDatingLabel, marker = 'o')`
- **# Normalize and Plot normalized results**
- `normMat, ranges, minVals = kNN.autoNorm(datingDataMat)`
- `ax3 = FigDating.add_subplot(313, xlim=(0,1), ylim=(0,1))`
- `ax3.scatter(normMat[:,0], normMat[:,1], s = 20, c= ColoredDatingLabel, marker = 'o')`
- **# One typically normalizes in some way – one approach is to make mean 0 and standard deviation 1 in each coordinate direction**
- **# autoNorm makes minimum value 0 and maximum 1 in each coordinate**
- `show()` **# Plot complete**




Visualization

PlotViz

- Now we look at PlotViz as a 3D viewer available at <http://salsahpc.indiana.edu/pviz3/>
- We will demonstrate now with first some snapshots and then interactive rotation
- The cluster separation varies according to view taken


One of 3D Rotated 2D Views of Clusters

Original labels (Clustering)




One of 3D Rotated 2D Views of Clusters

Original labels (Clustering)



One of 3D Rotated 2D Views of Clusters

Original labels (Clustering)



Testing K-Nearest Neighbor Algorithms

Test k NN Classification

- # final line in driver is
- `NumberBad = kNN.datingClassTest(0.1)`
gives
- The total error rate is: 0.050000
- Number Bad 5.000000
- # The argument(0.1 here) of `datingClassTest` represents a fraction f indicates that first f .Total Number of Vectors is a test set to be classified based on final $(1-f)$. Total Number of Vectors
- # Here the first 100 points are classified based on final 900
- # Function prints out number (here 5 or 5% of 100) of vectors whose k NN classification (using $k=3$ fixed in code) is different from input label
- # Note from picture the regions are not clearly separated and so points at edges of regions can be classified differently from this technique

Annotated kNN Classifier Function

- `# Use k Nearest Neighbors to classify inX according to existing dataSet with known ratings in labels`
- `def classify0(inX, dataSet, labels, k):`
- `dataSetSize = dataSet.shape[0] # Number of entries in dataSet`
- `diffMat = tile(inX, (dataSetSize,1)) - dataSet # Array of same shape as dataSet holding inX-dataSet entry in each position`
- `sqDiffMat = diffMat**2 # Square entries in diffMat`
- `sqDistances = sqDiffMat.sum(axis=1) # Sum over vector components`
- `distances = sqDistances**0.5 # Traditional Euclidean distance for each dataSet entry`
- `sortedDistIndicies = distances.argsort() # argsort returns indices that sort distances`
- `classCount={} # An empty dictionary key:value pairs key = labels value = number times this label in set of k`
- `for i in range(k): # Run over k nearest neighbors`
- `votellabel = labels[sortedDistIndicies[i]] # Label of this neighbor`
- `classCount[votellabel] = classCount.get(votellabel,0) + 1 # .get gets current count for votellabel and returns zero if first time votellabel seen (default = 0)`
- `sortedClassCount = sorted(classCount.iteritems(), key=operator.itemgetter(1), reverse=True) # Sort classCount (highest to lowest) by votellabel count`
- `# Note classCount entries are Label:# votes and we sort on # votes but return Label`
- `return sortedClassCount[0][0] # The label that occurs most often in k nearest neighbors`
- `# As in many such languages, compact but rather opaque and you need to know .get .iteritems and .itemgetter`