

Contents

1	What is CGmapTools	3
2	File Formats	5
2.1	ATCGmap Format	5
2.2	CGmap Format	5
2.3	ATCGbz Format	6
2.4	CGbz Format	8
3	File Manipulation	9
3.1	convert	9
3.2	fetch	10
3.3	refill	11
3.4	intersect	12
3.5	merge2	13
3.6	mergelist	14
3.7	sort	16
3.8	split	17
3.9	select	17
4	SNV calling	19
5	Methylation Analysis	21
5.1	dms	21
5.2	dmr	22
5.3	asm	23
5.4	mbed	25
5.5	mbin	26
5.6	mmbin	27
5.7	mfg	28
5.8	mstat	29
5.9	mtr	30
6	Coverage Analysis	33
6.1	oac	33
6.2	mec	35
7	Graphics	39
7.1	lollipop	39
7.2	heatmap	42
7.3	fragreg	43
7.4	tanghulu	45

8 Other Utilities	49
8.1 findCCGG	49
8.2 bed2fragreg	49

Chapter 1

What is CGmapTools

DNA methylation is crucial for a wide variety of biological processes. With the development of high throughput methylome profiling methods, huge volumes of data are generated and in egent need of computational tools for data analysis.

We proposed **CGmapTools**, a bisulfite sequencing analysis toolset with enhanced features on SNV calling and allele specific methylations and visualizations, in hope to set up a standard for bisulfite sequencing data related manipulation, including better data storage, extraction, visualization and improved performance in SNP calling. We also provide dozens of utilities and a seamless pipeline for bisulfite sequencing data analysis.

Command

```
cgmaptools -h
```

```
# Program : cgmaptools (Tools for analysis in CGmap/ATCGmap format)
# Version:  0.0.4
# Usage:   cgmaptools <command> [options]
# Commands:
#   -- File manipulation
#       convert      + data format conversion tools
#       fetch        + fetch a region by random accessing
#       refill       + refill the missing columns
#       intersect     + intersect two files
#       merge2        + merge two files into one
#       mergelist     + merge a list of files
#       sort          + sort lines by chromosome and position
#       split         + split file by chromosomes
#       select        + select lines by region/site
#   -- SNV analysis
#       snv           snv analysis
#   -- Methylation analysis
#       dms           differentially methylated site analysis
#       dmr           differentially methylated region analysis
#       asm           allele-specific methylation analysis
#       mbed          average methylation level in regions
#       mbin          * single sample, mC levels in bins
#       mmbin         multiple samples, mC levels in bins
#       mfg           methlation levels across fragmented region
#       mstat         * methyaltion statistic
#       mtr           methylation level to each region
```




Figure 1.1: Schematic diagram of CGmapTools

```
# -- Coverage analysis
#   oac      ** overall coverage (for ATCGmap)
#   mec      ** methylation effective coverage (for CGmap)
# -- Graph related functions
#   lollipop  * show local mC levels as lollipop bars
#   heatmap   * global mC distribution for multiple samples
#   fragreg   * show mC profile across fragmented regions
#   tanghulu  * show local mapped reads in Tanghulu shape
# -- Other Utils
#   findCCGG  get MspI cutting sites for RRBS
#   bed2fragreg get fragmented region based on region
# Note:
#   Commands support figures generation are marked with "*"
#   Commands contain sub-commands are marked with "+"
# Authors:
#   GUO, Weilong; guoweilong@126.com; http://guoweilong.github.io
#   ZHU, Ping; pingzhu.work@gmail.com; http://perry-zhu.github.io
```

Chapter 2

File Formats

To facilitate high throughput data manipulation and reduce storage usage, several file format have been proposed and generally accepted as the standard. Due to these great efforts (e.g. SAM/BAM and VCF), data analysis and tool development become more easier and highly efficient. However, when it comes to bisulfite sequencing data, currently, available tools possess their own tool specific data format. In consequence, integrating results from several tools leads to extra efforts in unifying data format and developing customized tools, which is time consuming and error prone.

The widely-used BS-seq alignment software *BS-Seeker2* defines **CGmap** and **ATCGmap** file formats for the representation of DNA methylomes. In CGmapTools, we used **ATCGmap** and **CGmap** as the standard file format interface, so that to simplify the development of downstream DNA methylation analysis tools and to provide standard formats for storing and sharing the DNA methylomes.

2.1 ATCGmap Format

Similar with **pileup**, **ATCGmap** format summarizes the information of mapped reads covered on each nucleotide on both strands, specially designed for BS-seq data.

Here, we defined ATCGmap file format to integrate both mapping and coverage of non-cytosine and cytosine sites with estimated DNA methylation in a single file.

- **Example**

chr1	T	3009410	--	--	0	10	0	0	0	0	3	0	0	0	na
chr1	C	3009411	CHH	CC	0	10	0	0	0	0	4	0	0	0	0.0
chr1	C	3009412	CHG	CC	0	10	0	0	0	0	9	1	0	0	0.0
chr1	C	3009413	CG	CG	0	10	50	0	0	0	20	1	0	0	0.83

- **Column Description**

2.2 CGmap Format

In cases we only want to retain DNA methylation on cytosines to save storage usage, we defined another file format called **CGmap** which provides sequence context and estimated DNA methylation level of any covered cytosines on the reference genome.

- **Example**

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{ 1,118 }	Query template NAME
2	NUC	Char	[ATCGN-]	The nucleotide on reference genome
3	POS	Int	[0,2 ³² -1]	1-based leftmost mapping position
4	CONT	String	{"--", "CG", "CHG", "CHH"}	context
5	DINUC	String	{"--", "CA", "CT", "CC", "CG"}	Dinucleotide context
6	WA	Int	[0,2 ¹⁴ -1]	Counts of reads on Watson strand support Adenine
7	WT	Int	[0,2 ¹⁴ -1]	Counts of reads on Watson strand support Thymine
8	WC	Int	[0,2 ¹⁴ -1]	Counts of reads on Watson strand support Cytosine
9	WG	Int	[0,2 ¹⁴ -1]	Counts of reads on Watson strand support Guanine
10	WN	Int	[0,2 ⁶ -1]	Counts of reads on Watson strand support None
11	CA	Int	[0,2 ¹⁴ -1]	Counts of reads on Crick strand support Adenine
12	CT	Int	[0,2 ¹⁴ -1]	Counts of reads on Crick strand support Thymine
13	CC	Int	[0,2 ¹⁴ -1]	Counts of reads on Crick strand support Cytosine
14	CG	Int	[0,2 ¹⁴ -1]	Counts of reads on Crick strand support Guanine
15	CN	Int	[0,2 ⁶ -1]	Counts of reads on Crick strand support None
16	METH	Float	[0,1] or "na"	Methylation level or "Not Available"

Figure 2.1: Description of ATCGmap

```
chr1    G    3000851    CHH    CC    0.1    1    10
chr1    C    3001624    CHG    CA    0.0    0    9
chr1    C    3001631    CG     CG    1.0    5    5
chr1    G    3001632    CG     CG    0.9    9    10
```

- Column Description

2.3 ATCGbz Format

ATCGbz format is the binary compressed version for **ATCGmap** format. **ATCGmap** format is readable, while quite large for storing, and difficult for fetching information in a specific position. **ATCGbz** is defined as the sorted binary version, that storing all information of **ATCGmap** into standard binary form, largely

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{ 1,118 }	Query template NAME
2	NUC	Char	[ATCGN-]	The nucleotide on reference genome
3	POS	Int	[0,2 ³² -1]	1-based leftmost mapping position
4	CONT	String	{"--", "CG", "CHG", "CHH"}	context
5	DINUC	String	{"--", "CA", "CT", "CC", "CG"}	Dinucleotide context
6	METH	Float	[0,1] or "na"	Methylation level or "Not Available"
7	MC	Int	[0,2 ¹² -1]	Counts of reads support methyalted Cytosine
8	NC	Int	[0,2 ¹² -1]	Counts of reads support all Cytosine

Figure 2.2: Description of CGmap

Field	Description	Type	Value
N_chr	# chromosome	uint32_t	
List of ChrInfo			
CHR	Name of chromosome	char [118]	
count	# of ATCGbzT under this chromosome	uint32_t	
List of ATCGbzT			
pos	Position on this chromosome	uint32_t	
info	The mapping information	uint32_t[4]	

Figure 2.3: Data structure of ATCGbz

info : uint32_t[4] 128 bit														
info [0]					info [1]			info [2]				info [3]		
1	2,3	4	5-18	19-32	1-14	15-28	29-32	1-2	3-16	17-30	31-32	1-12	13-26	27-32
strand	Dinuc	Context	WA	WT	WC	WG	WN	CA	CT	CC	CG	CN		
0 = + 1 = -	00=CA 01=CC 10=CT 11=CG	0=CNH 0=CNG	Count of reads mapped on Watson/Crick strands, supporting A, T, C, G or N											
	111 = "--" not CGG													

Figure 2.4: Data structure of info field of ATCGbz

reduced the storage requirement, and also supporting fast retrieval of methylation information for any position on genome.

- Data structure
- Related command

Command

```
cgmaptools fetch atcgbz -h
```

```
#
# Usage: cgmaptools fetch atcgbz -b <ATCGbz> -C <CHR> -L <LeftPos> -R <RightPos>
# (aka ATCGbzFetchRegion)
# Description: Convert ATCGbz format to ATCGmap format.
# Contact: Guo, Weilong; guoweilong@126.com
# Last update: 2016-12-07
#
# Options:
#
# -h, --help          output help information
# -b, --ATCGbz <arg> output ATCGbz file
# -C, --CHR <arg>     specify the chromosome name
# -L, --leftPos <arg> the left position
# -R, --rightPos <arg> the right position
```

Field	Description	Type	Value
N_chr	# chromosome	uint32_t	
List of ChrInfo			
CHR	Name of chromosome	char[118]	
count	# of CGbzT under this chromosome	uint32_t	
List of CGbzT			
pos	Position on this chromosome	uint32_t	
info	The mapping information	uint32_t	

Figure 2.5: Data structure of ATCGbz

info : uint32_t				
1	2,3	4	5-18	19-32
strand	Dinuc	Context	MC	NC
0: + 1: -	00=CA 01=CC 10=CT 11=CG 111 = "--" not CGG	0=CNH 0=CNG	# reads support methylated cytosine	# reads support all cytosine

Figure 2.6: Data structure of info field of CGbz

2.4 CGbz Format

CGbz format is the binary compressed version for CGmap format.

- Data structure
- Related command

Command

```
cgmaptools fetch cgbz -h
```

```
#
# Usage: cgmaptools fetch cgbz -b <CGbz> -C <CHR> -L <LeftPos> -R <RightPos>
#       (aka CGvzFetchRegion)
# Description: Convert CGbz file to CGmap format.
# Contact: Guo, Weilong; guoweilong@126.com
# Last update: 2016-12-07
#
# Options:
#
# -h, --help           output help information
# -b, --CGbz <arg>    output CGbz file
# -C, --CHR <arg>      specify the chromosome name
# -L, --leftPos <arg>  the left position
# -R, --rightPos <arg> the right position
```


Chapter 3

File Manipulation

CGmapTools provides multiple utilities to manipulate files in ATCGmap and CGmap format or compressed ATCGbz/CGbz format.

Usage: `cgmaptools <convert|fetch|refill|intersect|merge2|mergelist|sort|split|select|> [options]`

3.1 convert

- **Description** : File format conversion.
- **Table of command for converting formats:**

Commands	From	To
bam2cgmap	BAM	CGmap & ATCGmap
atcgmap2atcgbz	ATCGmap	ATCGbz
atcgbz2atcgmap	ATCGbz	ATCGmap
atcgmap2cgmap	ATCGmap	CGmap
cgmap2cgbz	CGmap	CGbz
cgbz2cgmap	CGbz	CGmap
cgmap2wig	CGmap	WIG
bismakr2cgmap	Bismark	CGmap

- **Command**

```
cgmaptools convert -h
```

```
# Usage:    cgmaptools convert <command> [options]
# Version:  0.0.4
# Commands:
#   bam2cgmap      BAM      => CGmap & ATCGmap
#   atcgmap2atcgbz ATCGmap => ATCGbz
#   atcgbz2atcgmap ATCGbz  => ATCGmap
#   atcgmap2cgmap  ATCGmap => CGmap
#   cgmap2cgbz     CGmap   => CGbz
#   cgbz2cgmap     CGbz    => CGmap
#   cgmap2wig      CGmap   => WIG
#   bismakr2cgmap  Bismark => CGmap
```

- **Example :**

- BAM to CGmap

```
cgmaptools convert bam2cgmap -b WG.bam -g genome.fa --rmOverlap -o WG
```

- BAM to CGmap

```
cgmaptools convert bam2cgmap -b RR.bam -g genome.fa --rmOverlap -o RR
```

- ATCGmap to ATCGbz

```
cgmaptools convert atcgmap2atcgbz -c WG.ATCGmap.gz -b WG.ATCGbz
```

- ATCGbz to ATCGmap

```
cgmaptools convert atcgbz2atcgmap -c WG2.ATCGmap.gz -b WG.ATCGbz
```

- CGmap to CGbz

```
cgmaptools convert cgmap2cgbz -c RR.CGmap.gz -b RR.CGbz
```

- CGbz to CGmap

```
cgmaptools convert cgbz2cgmap -c RR2.CGmap.gz -b RR.CGbz
```

- CGmap to WIG

```
cgmaptools convert cgmap2wig -i <CGmap> [-w <wig>] [-c <INT> -b <float>]
```

- bismark output to CGmap

```
cgmaptools convert bismark2cgmap -i bismark.dat -o output.CGmap
```

Note: please refer to the help message for usage details using -h option.

3.2 fetch

- **Description:** Fastly access methylation data in specified region.

- **Command**

```
cgmaptools fetch -h
```

```
# Usage:    cgmaptools fetch <command> [options]
# Version:  0.0.4
# Commands:
#           atcgbz      fetch lines from ATCGbz
#           cgbz        fetch lines from CGbz
```

3.2.1 fetch cgbz

- **Command**

```
cgmaptools fetch cgbz -h
```

```
#
# Usage: cgmaptools fetch cgbz -b <CGbz> -C <CHR> -L <LeftPos> -R <RightPos>
#       (aka CGvzFetchRegion)
# Description: Convert CGbz file to CGmap format.
# Contact: Guo, Weilong; guoweilong@126.com
# Last update: 2016-12-07
```

```
#
# Options:
#
# -h, --help          output help information
# -b, --CGbz <arg>    output CGbz file
# -C, --CHR <arg>     specify the chromosome name
# -L, --leftPos <arg> the left position
# -R, --rightPos <arg> the right position
```

- Example :

```
cgmmaptools fetch cgbz -b RR.CGbz -C chr3 -L 2200 -R 2400
```

3.2.2 fetch atcgbz

- Command

```
cgmmaptools fetch atcgbz -h
```

```
#
# Usage: cgmmaptools fetch atcgbz -b <ATCGbz> -C <CHR> -L <LeftPos> -R <RightPos>
#       (aka ATCGbzFetchRegion)
# Description: Convert ATCGbz format to ATCGmap format.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last update: 2016-12-07
#
# Options:
#
# -h, --help          output help information
# -b, --ATCGbz <arg>  output ATCGbz file
# -C, --CHR <arg>     specify the chromosome name
# -L, --leftPos <arg> the left position
# -R, --rightPos <arg> the right position
```

- Example :

```
cgmmaptools fetch atcgbz -b WG.ATCGbz -C chr2 -L 90 -R 100
```

3.3 refill

- Command

```
cgmmaptools refill -h
```

```
# Usage: cgmmaptools refill [-i <CGmap>] -g <genome.fa> [-o output]
#       (aka CGmapFillContext)
# Description: Fill the CG/CHG/CHH and CA/CC/CT/CG context.
#             Other fields will not be affected.
#             Can be applied to ATCGmap file.
# Contact:    Guo, Weilong; guoweilong@126.com;
# Last Update: 2016-12-07
# Index Ex:
#   Chr1  C      3541  -      -      0.0    0      1
# Output Ex:
#   Chr1  C      3541  CG     CG     0.0    0      1
```

```
#
# Options:
#   -h, --help      show this help message and exit
#   -i STRING       Input CGmap file (CGmap or CGmap.gz)
#   -g STRING       genome file, FASTA format (gzipped if end with '.gz')
#   -o STRING       Output file name (gzipped if end with '.gz')
#   -0, --0-base    0-based genome if specified [Default: 1-based]
```

- **File formats:**

The input CGmap file, which is lacking C context on the 3rd and 4th columns:

```
Chr1    C      3541    -      -      0.0    0      1
```

After refill processing, the CGmap file would be as below, added C context information:

```
Chr1    C      3541    CG      CG      0.0    0      1
```

- **Example:**

```
zcat RR2.CGmap.gz | gawk -F"\t" -vOFS="\t" '{ $4="-"; $5="-"; print; }' | cgmaptools
refill -g genome.fa -o RR3.CGmap.gz
```

3.4 intersect

- **Command**

```
cgmaptools intersect -h
```

```
# Usage: cgmaptools intersect [-1 <CGmap_1>] -2 <CGmap_2> [-o <output>]
#       (aka CGmapIntersect)
# Description:
#   Get the intersection of two CGmap files. Contact:      Guo, Weilong; guoweilong@126.com
# Last Update: 2016-08-18
# Output Format:
#   Chr1 C 3541 CG CG 0.8 4 5 0.4 4 10
# When 1st CGmap file is:
#   Chr1 C 3541 CG CG 0.8 4 5
# ,and 2nd CGmap file is:
#   Chr1 C 3541 CG CG 0.4 4 10
#
# Options:
#   -h, --help      show this help message and exit
#   -1 CGmap File   File name, end with .CGmap or .CGmap.gz.
#   -2 CGmap File   standard input if not specified
#   -o OUTFILE      To standard output if not specified. Compressed output
#                   if end with .gz
#   -C CONTEXT, --context=CONTEXT
#                   specific context: CG, CH, CHG, CHH, CA, CC, CT, CW
#                   use all sites if not specified
```

- **Example**

```
cgmaptools intersect -1 WG.CGmap.gz -2 RR.CGmap.gz -C CG -o intersect.CG.gz
```

- **Output format**

- **Example**

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	NUC	Char	[ATCGN-]	The nucleotide on reference genome
3	POS	Int	[0,2 ³² -1]	1-based leftmost mapping position
4	CONT	String	{"--", "CG", "CHG", "CHH"}	context
5	DINUC	String	{"--", "CA", "CT", "CC", "CG"}	Dinucleotide context
6	METH_1	Float	[0,1] or "na"	Methylation level in Sample 1
7	MC_1	Int	[0,2 ¹² -1]	Counts of reads support methyalted Cytosine in Sample 1
8	NC_1	Int	[0,2 ¹² -1]	Counts of reads support all Cytosine in Sample 1
9	METH_2	Float	[0,1] or "na"	Methylation level in Sample 2
10	MC_2	Int	[0,2 ¹² -1]	Counts of reads support methyalted Cytosine in Sample 2
11	NC_2	Int	[0,2 ¹² -1]	Counts of reads support all Cytosine in Sample 2

Figure 3.1: Output format description for cgmaptools intersect

```

Chr1  C  3541  CG  CG  0.8  4  5  0.4  4  10
Chr1  C  3542  CG  CG  0.8  3  5  0.2  2  10
Chr1  C  3545  CHG CA  0.0  0  5  0.1  1  10

```

– Column Description

3.5 merge2

Command

```
cgmaptools merge2 -h
```

```

# Usage:    cgmaptools merge2 <command> [options]
# Version:  0.0.4
# Commands:
#   atcgmap    merge two ATCGmap files into one
#   cgmap      merge two CGmap files into one

```

3.5.1 merge2 atcgmap

Command

```
cgmaptools merge2 atcgmap -h
```

```

# Unknown option: -h
# Usage:  cgmaptools merge2 atcgmap -1 <ATCGmap> -2 <ATCGmap>
#         (aka ATCGmapMerge)
# Contact: Guo, Weilong; guoweilong@126.com;
# Last Update: 2016-12-07
# Options:
#   -1    Input, 1st ATCGmap file
#   -2    Input, 2nd ATCGmap file
# Output to STDOUT in ATCGmap format
# Tips: Two input files should have the same order of chromosomes

```

- Example

```
cgmaptools merge2 atcgmap -1 WG.ATCGmap.gz -2 RR.ATCGmap.gz | gzip > merge.ATCGmap.gz
```

3.5.2 merge2 cgmap

Command

```
cgmaptools merge2 cgmap -h
```

```
# Usage: cgmaptools merge2 cgmap -1 <CGmap_1> -2 <CGmap_2> [-o <output>]
#      (aka CGmapMerge)
# Description: Merge two CGmap files together.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
# Note: The two input CGmap files should be sorted in the same order first.
#
#
# Options:
#   -h, --help  show this help message and exit
#   -1 FILE     File name end with .CGmap or .CGmap.gz
#   -2 FILE     If not specified, STDIN will be used.
#   -o OUTFILE  CGmap, output file. Use STDOUT if omitted (gzipped if end with
#               '.gz').
```

- Example

- Example command :

```
cgmaptools merge2 cgmap -1 WG.CGmap.gz -2 RR.CGmap.gz | gzip > merge.CGmap.gz
```

3.6 mergelist

- Command

```
cgmaptools mergelist -h
```

```
# Usage:    cgmaptools mergelist <command> [options]
# Version:  0.0.4
# Commands:
#   tomatrix  mC levels matrix from multiple files
#   tosingle  merge list of input files into one
```

3.6.1 mergelist tomatrix

- Command

```
cgmaptools mergelist tomatrix -h
```

```
# Usage: cgmaptools mergelist tomatrix [-i <index>] -f <IN1,IN2,...> -t <tag1,tag2,...> [-o output]
#      (aka CGmapFillIndex)
# Description: Fill methylation levels according to the Index file for CGmap files in list.
# Contact:    Guo, Weilong; guoweilong@126.com;
# Last Updated: 2016-12-07
# Index format Ex:
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]*	Query template NAME
2	POS	Int	[0,2 ³² -1]	Position

Figure 3.2: Format description for INDEX file

```
#      chr10    100005504
#  Output format Ex:
#      chr      pos      tag1      tag2      tag3
#      Chr1     111403  0.30      nan      0.80
#      Chr1     111406  0.66      0.40     0.60
#
#  Options:
#      -h, --help  show this help message and exit
#      -i FILE     TXT file, index file, use STDIN if omitted
#      -f STRING   List of (input) CGmap files (CGmap or CGmap.gz)
#      -t STRING   List of tags, same order with '-f'
#      -c INT      minimum coverage [default: 1]
#      -C INT      maximum coverage [default: 200]
#      -o STRING   Output file name (gzipped if end with '.gz')
```

- **Example**

```
zcat RR*.CGmap.gz WG.CGmap.gz | gawk '$8>=5' | cut -f1,3 | sort -u | cgmactools sort
-c 1 -p 2 > index
```

```
cgmactools mergelist tomatrix -i index -f RR.CGmap.gz,RR2.CGmap.gz,WG.CGmap.gz -t
RR,RR2,WG -c 5 -C 100 -o matrix.CG.gz
```

- **Format for Index file**

- **Example**

```
Chr1    940
Chr1    1840
Chr2    9060
```

- **Column Description**

- **Format for output file**

- **Example**

```
chr      pos      tag1      tag2      tag3
Chr1     111403  0.05      nan      0.02
Chr1     111500  1.00      0.80     0.60
Chr2     20000   0.96      0.33     0.66
```

- **Column Description**

3.6.2 mergelist tosingle

- **Command**

```
cgmactools mergelist tosingle -h
```

```
#  Usage: cgmactools mergelist tosingle -i f1,f2,...,fn [-o <output>]
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]*	Query template NAME
2	POS	Int	[0,2 ³² -1]	Position
3	METH_1	Float	[0.00, 1.00]	Methylation level in sample 1
...
n	METH_n	Float	[0.00, 1.00]	Methylation level in sample n

Figure 3.3: Output format description for cgmapttools fill tomatrix

```
#      (aka MergeListOfCGmap)
# Description: Merge multiple CGmap/ATCGmap files into one.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
# Note: Large memory is needed.
#
#
# Options:
#   -h, --help  show this help message and exit
#   -i FILE     List of input files; gzipped file ends with '.gz'
#   -f FILE     cgmap or atcgmap [Default: cgmap]
#   -o OUTFILE  To standard output if not specified; gzipped file if end with
#               '.gz'
```

- Example

3.7 sort

- Command

```
cgmapttools sort -h
```

```
# Usage: Sort_chr_pos [-i <input>] [-c 1] [-p 3] [-o output]
# Author : Guo, Weilong; guoweilong@gmail.com; 2014-05-11
# Last Update: 2016-12-07
# Description: Sort the input files by chromosome and position.
#              The order of chromosomes would be :
#              "chr1 chr2 ... chr11 chr11_random ... chr21 ... chrM chrX chrY"
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE              File name end with .CGmap or .CGmap.gz. If not specified,
#                       STDIN will be used.
#   -c INT, --chr=INT    The column of chromosome [default: 1]
#   -p INT, --pos=INT    The column of position [default: 2]
#   -o OUTFILE           To standard output if not specified
```

- Example

```
zcat RR*.CGmap.gz WG.CGmap.gz | gawk '$8>=5' | cut -f1,3 | sort -u | cgmapttools sort
-c 1 -p 2 > index
```


3.8 split

- Command

```
cgmaptools split -h
```

```
# Usage: cgmaptools split -i <input> -p <prefix[.chr.]> -s <[.chr.]suffix>
#      (aka CGmapSplitByChr)
# Description: Split the files by each chromosomes.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
#
# Options:
#   -h, --help  show this help message and exit
#   -i FILE      Input file, CGmap or ATCGmap format, use STDIN when not
#                specified.(gzipped if end with 'gz').
#   -p STRING    The prefix for output file
#   -s STRING    The suffix for output file (gzipped if end with 'gz').
```

- Example

```
cgmaptools split -i WG.CGmap.gz -p WG -s CGmap.gz
```

3.9 select

- Command

```
cgmaptools select -h
```

```
# Usage:    cgmaptools select <command> [options]
# Version:  0.0.4
# Commands:
#   region   select or exclude lines by region lists
#   site     select or exclude lines by site list
```

3.9.1 select region

- Command

```
cgmaptools select region -h
```

```
# Usage: cgmaptools select region [-i <CGmap/ATCGmap>] -r <BED> [-R]
#      (aka CGmapSelectByRegion)
# Description: Lines in input CGmap/ATCGmap be selected/excluded by BED file.
#              Strand is NOT considered.
#              Output to STDOUT in same format with input.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
# Options:
#   -i Input, CGmap/ATCGmap file; use STDIN if not specified
#       Please use "gunzip -c <input>.gz " and pipe as input for gzipped file.
#       Ex: chr12 G   19898796   ...
#   -r Input, Region file, BED file to store regions
#       At least 3 columns are required
#       Ex: chr12 19898766 19898966 XX XXX XXX
```

```
# -R [optional] Reverse selection. Sites in region file will be excluded when specified
# -h help
# Tips: program will do binary search for each site in regions
```

- **Example**

```
for CHR in 1 2 3 4 5; do (for P in 1 2 3 4 5; do echo | gawk -vC=$CHR -vP=$P -vOFS="\t"
'{print "chr"C, P*1000, P*1000+200, "+";}'; done) ; done > region.bed

zcat WG.CGmap.gz | cgmmaptools select region -r region.bed | head
```

3.9.2 select site

- **Command**

```
cgmmaptools select site -h
```

```
# Usage: cgmmaptools select site -i <index> [-f <CGmap/ATCGmap>] [-r] [-o output]
# (aka CGmapSelectBySite)
# Description: Select lines from input CGmap/ATCGmap in index or reverse.
# Contact: Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
# Index format example:
# chr10 100504
# chr10 103664
#
# Options:
# -h, --help show this help message and exit
# -i FILE Name of Index file required (gzipped if end with '.gz').
# -r reverse selected, remove site in index if specified
# -f STRING Input CGmap/ATCGmap files. Use STDIN if not specified
# -o STRING CGmap, Output file name (gzipped if end with '.gz').
```

- **Example**

```
gawk 'NR%100==50' index > site
cgmmaptools select site -f RR.CGmap.gz -i site -o RR_select.CGmap.gz
```

Chapter 4

SNV calling

Bisulfite sequencing data contains information of both methylation and genome sequences. In addition to DNA methylation analysis, we can also call variants using bisulfite data. Due to bisulfite conversion and PCR amplification during library preparation, the unmethylated cytosines on the DNA fragments would be converted to thymines. Thus, it's difficult to distinguish thymine produced by bisulfite conversion with the real thymine allele.

In recent years, few tools are adapted to bisulfite data for SNP calling. The main idea is removing vague reads that may contain unmethylated cytosines for a given position. Consequently, the rest reads can be regarded as reads generated from a normal genome DNA without bisulfite treatment and can be used to call variants using regular methods without consideration of bisulfite conversion.

However, removing the vague reads leads to information lost in most cases making variant calling less confident, especially when the sequencing depth is low. To solve this problem, we proposed two independent methods called BinomWC (based on binomial) and BayesWC (based on bayesian), taking vague reads into consideration.

Command

```
cgmaptools snv -h
```

```
# Usage: cgmaptools snv [-i <ATCGmap>] [-o <output> -v <VCF>]
# (aka SNVFromATCGmap)
# Description: Predict the SNV from ATCGmap file.
# Contact: Guo, Weilong; guoweilong@126.com
# Last update: 2017-08-24
# Output format example:
#   #chr  nuc  pos  ATCG_watson  ATCG_crack  predicted_nuc  p_value
#   chr1  G    4752  17,0,0,69    0,0,0,0      A,G            9.3e-07
#   chr1  A    4770  40,0,0,29    0,0,0,0      A,G            0.0e+00
#   chr1  T    8454  0,39,0,0     0,0,0,0      T/C            1.00e-01
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE              ATCGmap format, STDIN if not specified
#   -v FILE, --vcf=FILE VCF format file for output
#   -a, --all_nt         Show all sites with enough coverage (-l). Only show
#                       SNP sites if not specified.
#   -o OUTFILE           STDOUT if not specified
#   -m MODE, --mode=MODE Mode for calling SNP [Default: binom]
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	NUC	Char	[ATCGN-]	The nucleotide on reference genome
3	POS	Int	[0,2 ³² -1]	1-based leftmost mapping position
4	W_Count	String	[0-9,]+	Count of reads support A, T, C, G on Watson strand, seprated by ",", "
5	C_Count	String	[0-9,]+	Count of reads support A, T, C, G on Crick strand, seprated by ",", "
6	PRDNUC	String	[ATCG./]+	Predicted genotype ("," indicate two allele; "/" means "or")
7	PVALUE	Float	[0, 1]	P_value for confidence of this prediction

Figure 4.1: Output format description for cgmaptools snv

```
# binom: binomial, separate strands
# bayes: bayesian mode
# --bayes-e=BAYES_ER (BayesWC mode) Error rate for calling a nucleotide
# [Default: 0.05]
# --bayes-p=BAYES_PV (BayesWC mode) P value as cut-off [Default: 0.001]
# --bayes-dynamicP (BayesWC mode) Use dynamic p-value for different
# coverages install of specific p-value. (Recomended)
# "--bayes-p" will be ignored if "--bayes-dynamicP" is
# specified.
# --binom-e=BINOM_ER (BinomWC mode) Error rate for calling a nucleotide
# [Default: 0.05]
# --binom-p=BINOM_PV (BinomWC mode) P value as cut-off [Default: 0.01]
# --binom-cov=BINOM_COV
# (BinomWC mode) The coverage checkpoint [Default: 10]
```

- **Example commands :**

```
cgmaptools snv -i WG.ATCGmap.gz -m bayes -v bayes.vcf -o bayes.snv --bayes-dynamicP
cgmaptools snv -i WG.ATCGmap.gz -m binom -o binom.snv
```

- **Output format**

- **Example**

#chr	nuc	pos	ATCG_watson	ATCG_crick	predicted_nuc	p_value
chr1	G	4752	17, 0, 0, 69	0, 0, 0, 0	A,G	9.3e-07
chr1	A	4770	40, 0, 0, 29	0, 0, 0, 0	A,G	0.0e+00
chr1	T	8454	0, 39, 0, 0	0, 0, 0, 0	T/C	1.00e-01

- **Column Description**

Chapter 5

Methylation Analysis

5.1 dms

- Command

```
cgmaptools dms -h
```

```
# Usage: cgmaptools dms [-i <CGmapInter>] [-m 5 -M 100] [-o output]
#       (aka CGmapInterDiffSite)
# Description:
#   Get the differentially methylated sites for two samples.
# Contact:   Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
# Input Format, same as the output of CGmapIntersect.py:
#   Chr1 C 3541 CG CG 0.8 4 5 0.4 4 10
# Output Format:
#   chr1 C 4654 CG CG 0.92 1.00 8.40e-01
#   chr1 C 4658 CHH CC 0.50 0.00 3.68e-04
#   chr1 G 8376 CG CG 0.62 0.64 9.35e-01
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE             File name for CGmapInter, STDIN if omitted
#   -m INT, --min=INT   min coverage [default : 0]
#   -M INT, --max=INT   max coverage [default : 100]
#   -o OUTFILE          To standard output if omitted. Compressed output if
#                       end with .gz
#   -t STRING, --test-method=STRING
#                       chisq, fisher [default : chisq]
```

- Example

```
cgmaptools dms -i intersect.CG.gz -m 4 -M 100 -o DMS.gz -t fisher
```

- Output format

- Example

```
chr1    C    4654    CG  CG  0.92    1.00    8.40e-01
chr1    C    4658    CHH CC 0.50    0.00    3.68e-04
chr1    G    8376    CG  CG  0.62    0.64    9.35e-01
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	NUC	Char	[ATCGN-]	The nucleotide on reference genome
3	POS	Int	[0,2 ³² -1]	1-based position
4	CONT	String	{"--", "CG", "CHG", "CHH"}	context
5	DINUC	String	{"--", "CA", "CT", "CC", "CG"}	Dinucleotide context
6	METH_1	Float	[0,1] or "na"	Methylation level in Sample 1
9	METH_2	Float	[0,1] or "na"	Methylation level in Sample 2
11	PVALUE	Float	[0, 1]	P-value

Figure 5.1: Output format description for cgmaptools dms

– Column Description

5.2 dmr

• Command

```
cgmaptools dmr -h
```

```
# Usage: cgmaptools dmr [-i <CGmapInter>] [-m 5 -M 100] [-o output]
#       (aka CGmapInterDiffReg)
# Description:
#   Get the differentially methylated sites by Fisher's exact test.
# Author:      Guo, Weilong; guoweilong@126.com;
# Last Updated: 2017-08-12
# Input Format, same as the output of CGmapIntersect.py:
#   chr1 C 3541 CG CG 0.8 4 5 0.4 4 10
# Output Format, Ex:
#   #chr      start  end    t      pv      mC_A    mC_B    N_site
#   chr1 1004572 1004574 inf    0.00e+00 0.1100 0.0000 20
#   chr1 1009552 1009566 -0.2774 8.08e-01 0.0200 0.0300 15
#   chr1 1063405 1063498 0.1435 8.93e-01 0.6333 0.5733 5
#
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE             File name for CGmapInter, STDIN if omitted
#   -c INT, --minCov=INT min coverage [default : 4]
#   -C INT, --maxCov=INT max coverage [default : 500]
#   -s INT, --minStep=INT
#                       min step in bp [default : 100]
#   -S INT, --maxStep=INT
#                       max step in bp [default : 1000]
#   -n INT, --minNSite=INT
#                       min N sites [default : 5]
#   -o OUTFILE          To standard output if omitted. Compressed output if
#                       end with .gz
```

• Example

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	POS_L	Int	[0,2 ³² -1]	leftmost position for region
3	POS_R	Int	[0,2 ³² -1]	rightmost mapping position for region
4	T	Float	[0,2 ³² -1) or "inf"	Statistics of T test
5	PV	Float	[0, 1]	P-value of t test
6	METH_1	Float	[0,1] or "na"	Methylation level in Sample 1
7	METH_2	Float	[0,1] or "na"	Methylation level in Sample 2

Figure 5.2: Output format description for cgmaptools dmr




Figure 5.3: Dynamic Fragmentation Strategy

```
cgmaptools dmr -i intersect_CG.gz -o DMR.gz
```

- **Output format**

- **Example**

```
chr1    1004572 1004574 inf      0.00e+00    0.1100    0.0000
chr1    1009552 1009566 -0.2774 8.08e-01    0.0200    0.0300
chr1    1063405 1063498 0.1435 8.93e-01    0.6333    0.5733
chr1    1082130 1082133 -0.0822 9.42e-01    0.5000    0.5550
chr1    1123931 1123933 inf      0.00e+00    0.0600    0.0000
```

- **Column Description**

- **Strategy**

5.3 asm

- **Command**

```
cgmaptools asm -h
```

```
# DESCRIPTION
# Allele specific methylated region/site calling
```

```

#      * Fisher exact test for site calling.
#      * Students' t-test for region calling.
#
#  USAGE
#
#      cgmaptools asm [options] -r <ref.fa> -b <input.bam> -l <snp.vcf>
#      (aka ASM)
#
#  Options:
#      -r      Samtools indexed reference genome sequeunce, fasta format. eg. hg19.fa
#              - use samtools to index reference first: samtools faidx hg19.fa
#      -b      Samtools indexed Bam format file.
#              - use samtools to index bam file first: samtools index <input.bam>
#      -l      SNPs in vcf file format.
#      -s      Path to samtools eg. /home/user/bin/samtools
#              - by default, we try to search samtools in your system PATH,
#      -o      Output results to file. [default: STDOUT]
#      -t      C context. [default: CG]
#              - available context: C, CG, CH, CW, CC, CA, CT, CHG, CHH
#      -m      Specify calling mode. [default: asr]
#              - alternative: ass
#              - asr: allele specific methylated region
#              - ass: allele specific methylated site
#      -d      Minimum number of read for each allele linked site to call ass. [default: 3]
#              - ass specific.
#      -n      Minimum number of C site each allele linked to call asr. [default: 2]
#              - asr specific.
#      -D      Minimum read depth for C site to call methylation level when calling asr. [default: 1]
#              - asr specific.
#      -L      Low methylation level threshold. [default: 0.2]
#              - allele linked region [or site] with low methylation level should be no greater than
#      -H      High methylation level threshold. [default: 0.8]
#              - allele linked region[or site] with high methylation level should be no less than th
#      -q      Adjusted p value using Benjamini & Hochberg (1995) ("BH" or its alias "fdr"). [default
#      -h      Help message.
#
#  AUTHOR
#
#      Contact:      Zhu, Ping; pingzhu.work@gmail.com
#      Last update: 2016-12-07

```

- **Example**

```

gawk '{if(/^#/){print}else{print "chr"$0;}}' bayes.vcf > bayes2.vcf
cgmaptools asm -r genome.fa -b WG.bam -l bayes2.vcf > WG.asm

```

- **Output format for ASS (Allele-Specific methylated Site)**

- **Example**

Chr	SNP_Pos	Ref	Allele1	Allele2	C_Pos	Allele1_linked_C	Allele2_linked_C	Al
Chr1	8949221	T	T	A	8949252	30,2	6,0 0.94	1.00
Chr1	8965481	A	A	T	8965494	12,3	12,4 0.80	0.75

- **Column Description**

- **Output format for ASR (Allele-Specific methylated Region)**

- **Example**

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	SNP_Pos	Int	[0,2 ³² -1]	1-based leftmost mapping position of SNP site
3	Ref	Char	[ATCGN-]	The nucleotide on reference genome
4	Allele1	Char	[ATCG]	The nucleotide of allele1
5	Allele2	Char	[ATCG]	The nucleotide of allele2
6	C_Pos	Int	[0,2 ³² -1]	1-based leftmost mapping position of C site
7	Allele1_linked_C	Int	[0, 2 ³² -1]	Comma separated number of reads support methylated and unmethylated C linked by allele1 respectively
8	Allele2_linked_C	Int	[0, 2 ³² -1]	Comma separated number of reads support methylated and unmethylated C linked by allele2 respectively
9	Allele1_linked_C_met	Float	[0,1]	Methylation level of allele1 linked C site
10	Allele2_linked_C_met	Float	[0,1]	Methylation level of allele2 linked C site
11	pvalue	Float	[0,1]	P value of t test
12	fdr	Float	[0,1]	Adjusted p value using Benjamini & Hochberg method
13	ASM	Logical	TRUE/FALSE	TRUE indicates this C site is allele specific methylated. FALSE otherwise.

Figure 5.4: Output format description for cgmaptools asm -m ass

Chr	Pos	Ref	Allele1	Allele2	Allele1_linked_C	Allele2_linked_C	Allele1_linked_C_met	Allele2_linked_C_met	pvalue	fdr	ASM
chr1	8943402	A	A	T	1-1		0.8-1				
chr1	8966879	C	C	G	0.93-0-0	0.81-0-0					

– Column Description

5.4 mbed

• Command

```
cgmaptools mbed -h
```

```
# Usage: cgmaptools mbed [-i <CGmap>] -b <regin.bed> [-c 5 -C 500 -s]
# (aka CGmapMethylInBed)
# Description: Calculated bulk average methylation levels in given regions.
# Contact: Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
# Options:
# -i String, CGmap file; use STDIN if not specified
# Please use "gunzip -c <input>.gz " and pipe as input for gzipped file.
# Ex: chr1 G 3000851 CHH CC 0.1 1 10
# -b String, BED file, should have at least 4 columns
# Ex: chr1 3000000 3005000 -
# -c Int, minimum Coverage [Default: 5]
# -C Int, maximum Coverage [Default: 500]
# -s Strands would be distinguished when specified
# -h help
#
# Output to STDOUT:
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]{1,118}	Query template NAME
2	Pos	Int	[0,2 ³² -1]	1-based leftmost mapping position of SNP site
3	Ref	Char	[ATCGN-]	The nucleotide on reference genome
4	Allele1	Char	[ATCG]	The nucleotide of allele1
5	Allele2	Char	[ATCG]	The nucleotide of allele2
6	Allele1_linked_C	Float	[0,1]	'-' separated methylation level of C sites linked by allele1
7	Allele2_linked_C	Float	[0,1]	'-' separated methylation level of C sites linked by allele2
9	Allele1_linked_C_met	Float	[0,1]	Average methylation level of allele1 linked C sites
10	Allele2_linked_C_met	Float	[0,1]	Average methylation level of allele2 linked C sites
11	pvalue	Float	[0,1]	P value of t test
12	fdr	Float	[0,1]	Adjusted p value using Benjamini & Hochberg method
13	ASM	Logical	TRUE/FALSE	TRUE indicates this region is allele specific methylated. FALSE otherwise.

Figure 5.5: Output format description for cgmaptools asm -m asr

```
#      Title      Count    mean_mC
#      sense      34      0.2353
#      antisense   54      0.2778
#      total      88      0.2614
# Notice:
#   The overlapping of regions would not be checked.
#   A site might be considered multiple times.
```

- Example

```
zcat WG.CGmap.gz | cgmaptools mbed -b region.bed
```

- Output format

- Example

chr	sense_Count	sense_mC	anti_Count	anti_mC	all_Count	all_mC
chr1	203	0.08127	178	0.1148	381	0.09692
chr2	185	0.07045	257	0.05586	442	0.06197
chr3	313	0.1042	250	0.1358	563	0.1182
chr4	300	0.1218	271	0.13	571	0.1257
chr5	282	0.1272	222	0.1589	504	0.1412

5.5 mbin

- Command

```
cgmaptools mbin -h
```

```
# Usage: cgmaptools mbin [-i <CGmap>] [-c 10 --CXY 5 -B 5000000]
#      (aka CGmapMethInBins)
# Description: Generate the methylation in Bins.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-10-26
# Output Ex:
#   chr1      1      5000      0.0000
#   chr1     5001     10000     0.0396
#   chr2      1      5000     0.0755
```

```
#      chr2      5001      10000      0.0027
#      chr3       1        5000       na
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE              File name end with .CGmap or .CGmap.gz. If not
#                       specified, STDIN will be used.
#   -B BIN_SIZE          Define the size of bins [Default: 5000000]
#   -c COVERAGE          The minimum coverage for site selection [Default: 10]
#   -C CONTEXT, --context=CONTEXT
#                       specific context: CG, CH, CHG, CHH, CA, CC, CT, CW
#                       use all sites if not specified
#   --cXY=COVERAGEXY     Coverage for chrX/Y should be half that of autosome
#                       for male [Default: same with -c]
#   -f FIGTYPE, --figure-type=FIGTYPE
#                       png, pdf, eps. Will not generate figure if not
#                       specified
#   -H FLOAT             Height of figure in inch [Default: 4]
#   -W FLOAT             Width of figure in inch [Default: 8]
#   -p STRING            Prefix for output figures
#   -t STRING, --title=STRING
#                       title in the output figures
```

- Example

```
cgmmaptools mbin -i WG.CGmap.gz -B 500 -c 4 -f png -t WG -p WG > mbin.WG.data
```

- File format

The output format:

```
chr1      1        5000      0.0000
chr1      5001     10000     0.0396
chr2      1        5000      0.0755
chr2      5001     10000     0.0027
chr3      1        5000      na
```

5.6 mmbin

- Command

```
cgmmaptools mmbin -h
```

```
# Usage: cgmmaptools mmbin [-l <1.CGmap[,2.CGmap,...]>] [-c 10 --cXY 5 -B 5000000]
#      (aka CGmapsMethInBins)
# Description: Generate the methylation in Bins.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-07
# Output Ex:
#      chr1      1        5000      0.0000
#      chr1     5001     10000     0.0396
#      chr2      1        5000      0.0755
#      chr2     5001     10000     0.0027
#      chr3      1        5000      na
#
# Options:
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]*	Query template NAME
2	POS1	Int	[0,2 ³² -1]	Leftmost Position
3	POS2	Int	[0,2 ³² -1]	Rightmost Position
4	METH_1	Float	[0.00, 1.00]	Methylation level in sample 1
...
n	METH_n	Float	[0.00, 1.00]	Methylation level in sample n

Figure 5.6: Output format description for cgmaptools mmbin

```
# -h, --help          show this help message and exit
# -l FILE             File name list, end with .CGmap or .CGmap.gz. If not
#                     specified, STDIN will be used.
# -t FILE             List of samples
# -B BIN_SIZE         Define the size of bins [Default: 5000000]
# -C CONTEXT, --context=CONTEXT
#                     specific context: CG, CH, CHG, CHH, CA, CC, CT, CW
#                     use all sites if not specified
# -c COVERAGE         The minimum coverage for site selection [Default: 10]
# --cXY=COVERAGEXY   Coverage for chrX/Y should be half that of autosome
#                     for male [Default: same with -c]
```

- **Example**

```
cgmaptools mmbin -l WG.CGmap.gz,RR.CGmap.gz,RR2.CGmap.gz,merge.CGmap.gz -c 4 -B 2000
| gawk '{printf("%s:%s-%s", $1, $2, $3); for(i=4;i<=NF;i++){printf("\t%s", $i);}
printf("\n");}' > mmbin
““
```

- **Output format**

- **Example**

```
chr    pos1    pos2    tag1    tag2    tag3
Chr1   111403   113403   0.05    nan     0.02
Chr1   111500   112500   1.00    0.80    0.60
Chr2   20000    20500    0.96    0.33    0.66
```

- **Column Description**

5.7 mfg

- **Command**

```
cgmaptools mfg -h
```

```
# Usage: cgmaptools mfg [-i <CGmap>] -r <region> [-c 5 -C 500]
# Description: Calculated methylation profile across fragmented regions.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
# Options:
# -i String, CGmap file; use STDIN if not specified
```

```
# Please use "gunzip -c <input>.gz " and pipe as input for gzipped file.
# chr1 G 851 CHH CC 0.1 1 10
# -r String, Region file, at least 4 columns
# Format: chr strand pos_1 pos_2 pos_3 ...
# Regions would be considered as [pos_1, pos_2), [pos_2, pos_3)
# Strand information will be used for distinguish sense/antisense strand
# Ex:
# #chr strand U1 R1 R2 D1 End
# chr1 + 600 700 800 900 950
# chr1 - 1600 1500 1400 1300 1250
# -c Int, minimum Coverage [Default: 5]
# -C Int, maximum Coverage [Default: 500]
# Sites exceed the coverage range will be discarded
# -x String, context [use all sites by default]
# string can be CG, CH, CHG, CHH, CA, CC, CT, CW
# -h help
# Output to STDOUT:
# Region_ID U1 R1 R2 D1
# sense_ave_mC 0.50 0.40 0.30 0.20
# sense_sum_mC 5.0 4.0 3.0 2.0
# sense_sum_NO 10 10 10 10
# anti_ave_mC 0.40 0.20 0.10 NaN
# anti_sum_mC 8.0 4.0 2.0 0.0
# anti_sum_NO 20 20 20 0
# total_ave_mC 0.43 0.27 0.17 0.2
# total_sum_mC 13.0 8.0 5.0 2.0
# total_sum_NO 30 30 30 10
```

- Example:

```
for CHR in 1 2 3 4 5; do (for P in 1 2 3 4 5; do echo | gawk -vC=$CHR -vP=$P -vOFS="\t"
'{print "chr"C, P*1000, P*1000+1000, "+";}' ; done) ; done | cgmaptools bed2fragreg
-n 30 -F 50,50,50,50,50,50,50,50,50,50 -T 50,50,50,50,50,50,50,50,50,50 > fragreg.bed

gunzip -c WG.CGmap.gz | cgmaptools mfg -r fragreg.bed -c 2 -x CG > WG.mfg

cgmaptools fragreg -i WG.mfg -f pdf -o WG_mfg.pdf
```

5.8 mstat

- Command

```
cgmaptools mstat -h
```

```
# Usage: cgmaptools mstat [-i <CGmap>]
# (aka CGmapStatMeth)
# Description: Generate the bulk methylation.
# Contact: Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-08
# Output Ex:
# MethStat context C CG CHG CHH CA CC CT CH CW
# mean_mC global 0.0798 0.3719 0.0465 0.0403 0.0891 0.0071 0.0241 0.0419 0.0559
# sd_mCbyChr global 0.0078 0.0341 0.0163 0.0110 0.0252 0.0049 0.0076 0.0096 0.0148
# count_C global 10000 1147 2332 6521 3090 2539 3224 8853 6314
# contrib_mC global 1.0000 0.5348 0.1360 0.3292 0.3452 0.0228 0.0973 0.4652 0.4424
```




Figure 5.7: mC contribution example

```
#      quant_mC      [0]      8266      471      2012      5783      2422      2421      2952      7795      5374
#      quant_mC  (0.00 ,0.20] 705      182      155      368      272      97      154      523      426
#      mean_mC_byChr chr1      0.0840  0.4181  0.0340  0.0412  0.0794  0.0065  0.0251  0.0393  0.0513
#      mean_mC_byChr chr10     0.0917  0.4106  0.0758  0.0421  0.0968  0.0097  0.0349  0.0502  0.0655
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE              File name end with .CGmap or .CGmap.gz. If not
#                       specified, STDIN will be used.
#   -c COVERAGE          The minimum coverage for site selection [Default: 10]
#   -f FILE, --figure-type=FILE
#                       png, pdf, eps. Will not generate figure if not
#                       specified
#   -H FLOAT             Height of figure in inch [Default: 3]
#   -W FLOAT             Width of figure in inch [Default: 8]
#   -p STRING            Prefix for output figures
#   -t STRING, --title=STRING
#                       title in the output figures
```

- **Example**

```
cgmaptools mstat -i WG.CGmap.gz -c 4 -f png -p WG -t WG > WG.mstat.data
```

- **File format**

The output format:

MethStat	context	C	CG	CHG	CHH	CA	CC	CT	CH	CW
mean_mC	global	0.0798	0.3719	0.0465	0.0403	0.0891	0.0071	0.0241	0.0419	0.0559
sd_mCbyChr	global	0.0078	0.0341	0.0163	0.0110	0.0252	0.0049	0.0076	0.0096	0.0148
count_C	global	10000	1147	2332	6521	3090	2539	3224	8853	6314
contrib_mC	global	1.0000	0.5348	0.1360	0.3292	0.3452	0.0228	0.0973	0.4652	0.4424
quant_mC	[0]	8266	471	2012	5783	2422	2421	2952	7795	5374
quant_mC	(0.00 ,0.20]	705	182	155	368	272	97	154	523	426
mean_mC_byChr	chr1	0.0840	0.4181	0.0340	0.0412	0.0794	0.0065	0.0251	0.0393	0.0513
mean_mC_byChr	chr10	0.0917	0.4106	0.0758	0.0421	0.0968	0.0097	0.0349	0.0502	0.0655

- **Output figures**

5.9 mtr

- **Command**




Figure 5.8: Bulk mC example




Figure 5.9: mC fragmented distribution example

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]*	Query template NAME
2	POS_L	Int	[0,2 ³² -1]	Leftmost Position
3	POS_R	Int	[0,2 ³² -1]	Rightmost Position
4	MC_s	Float	[0, 2 ³² -1)	Average methylation levels by each site
5	NC_s	Int	[0,2 ³² -1]	Count of Cytosines in this region
6	MC_r	Float	[0, 2 ³² -1)	Average methylation levels recalculated by region
7	NC_r	Int	[0,2 ³² -1]	Sum of effective coverage for all cytosines in this region

Figure 5.10: Output format description for cgmaptools mtr

```
cgmaptools mtr -h
```

```
# Usage: cgmaptools mtr [-i <CGmap>] -r <region> [-o <output>]
#       (aka CGmapToRegion)
# Description: Calculated the methylation levels in regions in two ways.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
# Format of Region file:
#   #chr    start_pos  end_pos
#   chr1    8275      8429
# Output file format:
#   #chr  start_pos  end_pos  mean(mC)  #_C  #read(C)/#read(T+C)  #read(T+C)
#   chr1  8275      8429      0.34     72     0.40                164
# Note: The two input CGmap files should be sorted by Sort_chr_pos.py first.
#       This script would not distinguish CG/CHG/CHH contexts.
#
# Options:
#   -h, --help  show this help message and exit
#   -i FILE     File name end with .CGmap or .CGmap.gz. If not specified, STDIN
#               will be used.
#   -r FILE     Filename for region file, support *.gz
#   -o OUTFILE  To standard output if not specified.
```

- **Example**

```
cgmaptools mtr -i WG.CGmap.gz -r region.bed -o WG.mtr.gz
```

- **Input region format**

```
#chr    start_pos  end_pos
chr1    8275      8429
```

- **Output format**

- **Example**

```
chr1    8275    8429    0.34    72     0.40    164
chr1    8899    8999    0.20    40     0.33    198
chr2    8275    8429    0.50    12     0.45    40
```

- **Column Description**

Chapter 6

Coverage Analysis

6.1 oac

- Command

```
cgmaptools oac -h
```

```
# Usage:    cgmaptools oac <command> [options]
# Version:  0.0.4
# Commands:
#     bin      * overall coverage in bins
#     stat     * overall coverage statistics globally
```

6.1.1 oac bin

- Command

```
cgmaptools oac bin -h
```

```
# Usage: cgmaptools oac bin [-i <ATCGmap>] [-B 5000000]
#       (aka ATCGmapCovInBins)
# Description: Generate the overall coverage in Bins.
# Contact:    Guo, Weilong; guoweilong@126.com;
# Last Update: 2016-12-07
# Output Ex:
#   chr1    1      5000    29.0000
#   chr1    5001   10000    30.0396
#   chr2    1      5000    35.0755
#   chr2    5001   10000    40.0027
#   chr3    1      5000     na
#
# Options:
#   -h, --help          show this help message and exit
#   -i FILE             File name end with .ATCGmap or .ATCGmap.gz. If not
#                       specified, STDIN will be used.
#   -B BIN_SIZE         Define the size of bins [Default: 5000000]
#   -f FILE, --figure-type=FILE
#                       png, pdf, eps. Will not generate figure if not
#                       specified
```




Figure 6.1: MEC example

```
# -H FLOAT           Height of figure in inch [Default: 4]
# -W FLOAT           Width of figure in inch [Default: 8]
# -p STRING          Prefix for output figures
# -t STRING, --title=STRING
#                      title in the output figures
```

- Example

```
cgmaptools oac bin -i WG.ATCGmap.gz -B 1000 -f png -p WG -t WG > WG.oac_bin.data
```

- Output figure

6.1.2 oac stat

- Command

```
cgmaptools oac stat -h
```

```
# Usage: cgmaptools oac stat [-i <ATCGmap>]
#       (aka ATCGmapStatCov)
# Description: Get the distribution of overall coverages.
# Contact:    Guo, Weilong; guoweilong@126.com;
# Last Update: 2016-12-16
# Output Ex:
#   OverAllCov    global  47.0395
#   OverAllCov    chr1    45.3157
#   OverAllCov    chr10   47.7380
#   CovAndCount   1       1567
#   CovAndCount   2       655
#   CovAndCount   3       380
#
# Options:
```

```
# -h, --help          show this help message and exit
# -i FILE             File name end with .ATCGmap or .ATCGmap.gz. If not
#                     specified, STDIN will be used.
# -f FILE, --figure-type=FILE
#                     png, pdf, eps. Will not generate figure if not
#                     specified
# -H FLOAT            Scale ratio for the Height of figure [Default: 4]
# -W FLOAT            Width of figure in inch [Default: 8]
# -p STRING           Prefix for output figures
```

- **Example**

```
cgmmaptools oac stat -i WG.ATCGmap.gz -p WG -f png > WG.oac_stat.data
```

- **output format:**

The output format of bin:

```
chr1    1      5000    29.0000
chr1    5001   10000    30.0396
chr2    1      5000    35.0755
chr2    5001   10000    40.0027
chr3    1      5000     na
```

The output format of stat:

```
OverAllCov    global  47.0395
OverAllCov    chr1    45.3157
OverAllCov    chr10   47.7380
CovAndCount   1       1567
CovAndCount   2       655
CovAndCount   3       380
```

6.2 mec

- **Command**

```
cgmmaptools mec -h
```

```
# Usage:    cgmmaptools mec <command> [options]
# Version:  0.0.4
# Commands:
#   bin      * methylation effective coverage in bins
#   stat     * methylation effective coverage statistics globally
```

6.2.1 mec bin

- **Command**

```
cgmmaptools mec bin -h
```

```
# Usage: cgmmaptools mec bin [-i <CGmap>] [-B 5000000]
#       (aka CGmapCovInBins)
# Description: Generate the methylation-effective coverage in Bins.
# Contact:    Guo, Weilong; guoweilong@126.com;
# Last Update: 2016-12-07
# Output Ex:
```

```
# chr1 1 5000 29.0000
# chr1 5001 10000 30.0396
# chr2 1 5000 35.0755
# chr2 5001 10000 40.0027
# chr3 1 5000 na
#
# Options:
# -h, --help show this help message and exit
# -i FILE File name end with .CGmap or .CGmap.gz. If not
# specified, STDIN will be used.
# -B BIN_SIZE Define the size of bins [Default: 5000000]
# -f FILE, --figure-type=FILE
# png, pdf, eps. Will not generate figure if not
# specified
# -H FLOAT Height of figure in inch [Default: 4]
# -W FLOAT Width of figure in inch [Default: 8]
# -p STRING Prefix for output figures
# -t STRING, --title=STRING
# title in the output figures
# -C CONTEXT, --context=CONTEXT
# specific context: CG, CH, CHG, CHH, CA, CC, CT, CW
# use all sites if not specified
```

- Example

```
cgmmaptools mec bin -i WG.CGmap.gz -B 1000 -f png -p WG -t WG > WG.mec_bin.data
```

6.2.2 mec stat

- Command

```
cgmmaptools mec stat -h
```

```
# Usage: cgmmaptools mec stat [-i <CGmap>]
# (aka CGmapStatCov)
# Description: Get the distribution of methylation-effective coverages.
# Contact: Guo, Weilong; guoweilong@126.com
# Last Update: 2016-12-16
# Output Ex:
# MethEffectCove global 47.0395
# MethEffectCove chr1 45.3157
# MethEffectCove chr10 47.7380
# CovAndCount 1 1567
# CovAndCount 2 655
# CovAndCount 3 380
#
# Options:
# -h, --help show this help message and exit
# -i FILE File name end with .CGmap or .CGmap.gz. If not
# specified, STDIN will be used.
# -f FILE, --figure-type=FILE
# png, pdf, eps. Will not generate figure if not
# specified
# -H FLOAT Scale factor for the Height of figure [Default: 4]
# -W FLOAT Width of figure in inch [Default: 11]
```




Figure 6.2: MEC example

```
# -p STRING          Prefix for output figures
# -C CONTEXT, --context=CONTEXT
#                   specific context: CG, CH, CHG, CHH, CA, CC, CT, CW
#                   use all sites if not specified
```

- **Example**

```
cgmmaptools mec stat -i WG.CGmap.gz -p WG -f png > WG.mec_stat.data
```

- **Output figure**

Chapter 7

Graphics

7.1 lollipop

- Command

```
cgmaptools lollipop -h
```

```
# Usage: cgmaptools lollipop [options] file
#       (aka mCLollipop)
# Description: Plot local mC level for multiple samples
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2017-09-12
# Example:
#       mCLollipop [-i input] -o gene.png
# -Input Format (-i)
#       Can be output by "cgmaptools mergelist tomatrix". Use STDIN if omitted.
#       The 1st line (header line) is required.
#       Example:
#           chr    pos    tag1    tag2    tag3
#           Chr1   111403  0.30   nan     0.80
#           Chr1   111406  0.66   0.40    0.60
# -Site File (-s)
#       >= 3 columns, the 1st line (header line) is required, using R color name or "NaN".
#       To show specific sites (such as DMS, SNV) at the bottom as triangles.
#       Example:
#           chr    pos    A_vs_B  B_vs_C  A_vs_C
#           chr1   13116801  NaN     NaN     darkgreen
#           chr1   13116899  NaN     red     NaN
# -Region File (-b)
#       the first 4 columns are required.
#       To show specific region (such as DMR, Repeats) at the bottom as blocks.
#       Example:
#           chr    213941196  213942363  hyper-DMR
#           chr1   213942363  213943530  hypo-DMR
#           # chr    left    right    region-description
# -annotation file (-a), refFlat Format:
#       To show the structure of genes/transcripts. One-line in annotation, one-track in figure.
#       Example:
#           GeneA    TransA  chr2  +    1000    2000    1100    1950    3    1100,1500,1700, 1
```

```

#      #   GeneID  TrandID ChrID Strand TransLeft TransRight CDSLeft CDSRight nExon ExonLefts      E
#
#
#
# Options:
#   -i INFILE, --infile=INFILE
#       input file
#
#   -a ANNOTATION, --annotation=ANNOTATION
#       [opt] annotation file name, refFlat format
#
#   -o OUTFILE, --outfile=OUTFILE
#       [opt] output file
#
#   -f FORMAT, --format=FORMAT
#       [opt] the format for output figure: pdf (default), png, eps
#
#   -l LEFT, --left=LEFT
#       [opt] Left-most position
#
#   -r RIGHT, --right=RIGHT
#       [opt] Right-most position
#
#   -c CHR, --chr=CHR
#       [opt] chromosome name
#
#   -s SITE, --site=SITE
#       [opt] file of site to be marked
#
#   -b BED, --bed=BED
#       [opt] BED file for region to be marked
#
#   -t TITLE, --title=TITLE
#       [opt] text shown on title
#
#   -w WIDTH, --width=WIDTH
#       [opt] width (in inch). Default: 8.
#
#   --height=HEIGHT
#       [opt] height (in inch). Default: 8.
#
#   -h, --help
#       Show this help message and exit

```

- **Example**

```
cgmmaptools lollipop -i matrix.CG.gz -a anno.refFlat -f pdf
```

- **Figure examples**

- **refFlat** format

- **Example**

GeneA	TransA	chr2	+	1000	2000	1100	1950	3	1100,1500,1700, 1200,1580,1950,
<ul style="list-style-type: none"> • Description 									

Col 1: Gene ID




Figure 7.1: Lollipop example-1




Figure 7.2: Lollipop example-2

Col 2: Transcript ID
 Col 3: chromatine ID
 Col 4: strand, “+” or “-”
 Col 5: The left-most position of transcript
 Col 6: The right-most position of transcript
 Col 7: The left-most position of CDS
 Col 8: The right-most position of CDS
 Col 9: Number of exons
 Col 10: List of left-most position of exons, seperated by “,”
 Col 11: List of right-most position of exons, seperated by “,”

- Convert GTF format to refFlat format

The following is an example for *Z. mays*.

“gtfToGenePred” is a command tool downloaded from UCSC utility.

```
gtfToGenePred -genePredExt -geneNameAsName2 -allErrors AGPv4.gtf AGPv4.GenePred
paste <(cut -f13 AGPv4.GenePred) <(cut -f1-10 AGPv4.GenePred) > AGPv4.refFlat
paste <(cut -f13 AGPv4.GenePred) <(cut -f1-10 AGPv4.GenePred) | sed -i s/transcript://g | cut -f9 | gawk
cut -f1-10 AGPv4.GenePred > AGPv4.refFlat.tmp
gawk -F"\t" -vOFS="\t" 'ARGIND==1{GeneID[$1]=$2;} ARGIND==2{printf GeneID[$1]"\t"$0}' trans_gene_ID AGP
rm ${GN}.refFlat.txt AGPv4.GenePred
```

7.2 heatmap

- Command

```
cgmaptools heatmap -h
```

```
# Usage: cgmaptools heatmap [options]
# (aka mCBinHeatmap)
# Description: Plot methylation dynamics of target region for multiple samples [heatmap]
# Contact: Zhu, Ping; pingzhu.work@gmail.com
# Last update: 2016-12-07
# Example:
# mCBinHeatmap.R -i input -m white -o chr1.xxx-xxx.pdf
# -Input File Format:
# 1st line is the header.
# Each column contains methylation measurements of a sample.
# Example:
# Region Sample1 Sample2 ...
# Region1 0.1 0.1 ...
# Region2 0.1 0.1 ...
#
# Options:
# -i INFILE, --infile=INFILE
# input file
#
# -o OUTFILE, --outfile=OUTFILE
# [opt] output file name. [default: mCBinHeatmap.SysDate.pdf]
#
# -c, --cluster
# [opt] cluster samples by methylation in regions. [default: FALSE]
```

```

#
#   -l COLORLOW, --colorLow=COLORLOW
#       [opt] color used for the lowest methylation value. [default: cyan3]
#
#   -m COLORMID, --colorMid=COLORMID
#       [opt] color used for the middle methylation value. [default: null]
#
#   -b COLORHIGH, --colorHigh=COLORHIGH
#       [opt] color used for the highest methylation value. [default: coral2]
#
#   -n COLORNUMBER, --colorNumber=COLORNUMBER
#       [opt] desired number of color elements in the panel. [default: 10]
#
#   -W WIDTH, --width=WIDTH
#       [opt] width of figure (inch). [default: 7]
#
#   -H HEIGHT, --height=HEIGHT
#       [opt] height of figure (inch). [default: 7]
#
#   -f FORMAT, --format=FORMAT
#       [opt] format of output figure. Alternative: png. [default: pdf]
#
#   -R RESOLUTION, --resolution=RESOLUTION
#       [opt] Resolution in ppi. Only available for png format. [default: 300]
#
#   -h, --help
#       Show this help message and exit

```

- **Example:**

```
cgmaptools heatmap -i mmbin -c -o cluster.pdf -f pdf
```

- **Figure examples**

7.3 fragreg

- **Command**

```
cgmaptools fragreg -h
```

```

#   Usage: cgmaptools fragreg [options]
#       (aka mCFragRegView)
#   Description: Plot methylation dynamics of target and flanking region for multiple samples
#   Contact:     Zhu, Ping; pingzhu.work@gmail.com
#   Last update: 2016-12-07
#   Example:
#       FragRegView.R -i input -r 5 -o genebody.pdf
#   -Input File Format:
#       1st line is the header.
#   Each row contains methylation measurements of a sample.
#   Example:
#       Sample Up1  Up2  ...  Region1  Region2 ...  Down1  Down2  ...
#       Sample1 0.1  0.1  ...  0.2      0.2      ...  0.3    0.3    ...
#       Sample2 0.1  0.1  ...  0.2      0.2      ...  0.3    0.3    ...
#

```





Figure 7.4: FragRegMC example

- **Output format**

- **Example**

Region_ID	R_1	R_2	R_3	R_4
sense_ave_mC	0.50	0.40	0.30	0.20
sense_sum_mC	5.0	4.0	3.0	2.0
sense_sum_NO	10	10	10	10
anti_ave_mC	0.40	0.20	0.10	NaN
anti_sum_mC	8.0	4.0	2.0	0.0
anti_sum_NO	20	20	20	0
total_ave_mC	0.43	0.27	0.17	0.2
total_sum_mC	13.0	8.0	5.0	2.0
total_sum_NO	30	30	30	10

- **Column Description**

- * Tab-delimited file with header line
- * Content in 1st col is fixed
- * Column number is dynamic
- * Invalid number is annotated as “NaN”

- **Output figure**

7.4 tanghulu

- **Command**

```
cgmaptools tanghulu -h
```

```
# DESCRIPTION
#       Circle plot representing DNA methylation of each C [default CpG] site
#       on each mapped reads.
#
# USAGE
#       cgmaptools tanghulu [options] -r <ref> -b <bam> -l chr1:133-144
#       or: cgmaptools tanghulu [options] -r <ref> -b <bam> -l chr1:133
#       (aka mCTanghulu)
#
#       Options:
#       -r       Samtools indexed reference genome sequeunce, fasta format. eg. hg19.fa
#                - use samtools to index reference: samtools faidx <hg19.fa>
#       -b       Samtools indexed Bam file to view.
#                - use samtools to index bam file: samtools index <input.bam>
#       -l       Region in which to display DNA methylation.
#                - or specify a single position (eg. heterozygous SNP site), we will show allele specif
#       -s       Path to samtools eg. /home/user/bin/samtools
#                - by default, we try to search samtools in your system PATH.
#       -o       Output results to file [default: CirclePlot.Ctype.region.Date.pdf].
#       -t       C context. [default: CG]
#                - available context: C, CG, CH, CW, CC, CA, CT, CHG, CHH
#       -d       Ouput device. [default: pdf]
#                - alternative: png
#       -c       Seperate reads by chain. [default: OFF]
#                - specify this option to turn ON.
#       -v       Show vague allele linked reads. [ default: OFF]
#       -g       Genotype of heterozygous SNP site.
#                - This option provides two alleles of htSNP site. eg. AT
#                - The genotype information can be used to reduce vague alleles.
#                - This option is specific to display methylation in allele specific mode.
#       -D       Minimum number of reads (depth) covered in this region or allele linked. [default: 0|0]
#       -C       Minimum number of C (specified type) covered in this region or allele linked. [default
#       -W       Width of graphics reigon in inches. [default: 4]
#       -H       Height of graphics reigon in inches. [default: 4]
#       -R       Resolution in ppi. [default: 300]
#                - only available for png device.
#       -h       Help message.
#
# AUTHOR
#       Contact:      Zhu, Ping; pingzhu.work@gmail.com
#       Last update: 2016-12-07
```

- Example

```
cgmaptools tanghulu -r genome.fa -b WG.bam -l chr1:2000-2400 -t CG
```

- Output figure




Figure 7.5: FragRegMC example

Chapter 8

Other Utilities

8.1 findCCGG

- Command

```
cgmaptools findCCGG -h
```

```
# Usage: cgmaptools findCCGG -i <genome.fa> [-o <output>]
#       (aka FiindCCGG)
# Description: Get the positions of all the C'CGG---CCG'G fragments.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
# Output Ex:
#       chr1    4025    5652
#       chr1    8274    8431
#
# Options:
# -h, --help  show this help message and exit
# -i FILE     Genome sequence file in Fasta format
# -o FILE     Name of the output file (standard output if not
#             specified).Format: chr cCgg_pos ccGg_pos (0-base)
```

- Example

```
cgmaptools findCCGG -i genome.fa -o genome.ccgg
```

8.2 bed2fragreg

- Command

```
cgmaptools bed2fragreg -h
```

```
# Usage: cgmaptools bed2fragreg [-i <BED>] [-n <N>] [-F <50,50,...> -T <50,...>] [-o output]
#       (aka FragRegFromBED)
# Description: Generate fragmented regions from BED file.
# Contact:    Guo, Weilong; guoweilong@126.com
# Last Update: 2017-01-20
#       Split input region into N bins, get fragments from 5' end and 3' end.
# Input Ex:
```

Col	Field	Type	Regexp/Range	Brief description
1	CHR	String	[!-?A-~]*	Query template NAME
2	STRAND	Char	[+-]	Strand
3	POS_1	Int	[0,2 ³² -1]	The 1 st position from 5' end
4	POS_2	Int	[0,2 ³² -1]	The 2 nd position from 5' end
...
n+2	POS_n	Int	[0,2 ³² -1]	The nth position from 5' end

Figure 8.1: Output format description for cgmmaptools bed2fragreg

```
#      chr1    1000    2000    +
#      chr2    9000    8000    -
#  Output Ex:
#      chr1    +    940  950   1000 1200 1400 1600 1800 1850
#      chr2    -   9060 9050  9000 8800 8600 8400 8200 8150
#
#
#  Options:
#      -h, --help    show this help message and exit
#      -i FILE       BED format, STDIN if omitted
#      -F INT_list   List of region lengths in upstream of 5' end, Ex: 10,50. List
#                   is from 5'end->3'end
#      -T INT_list   List of region lengths in downstream of 3' end, Ex: 40,20. List
#                   is from 5'end->3'end
#      -n INT        Number of bins to be equally split [Default:1]
#      -o OUTFILE    To standard output if omitted. Compressed output if end with
#                   .gz
```

- **Example**

- **Output format**

- **Example**

```
chr1    +    940  950   1000 1200 1400 1600 1800 2000 2060 2080
chr2    -   9060 9050  9000 8800 8600 8400 8200 8000 7960 7940
```

- **Column Description**

[POS_1, POS_2), [POS_2, POS_3), ... [POS_(n-1), POS_n) will be used as input for cgmmaptools mfg