

ACRO

v2.2beta 2015/09/09

Typeset Acronyms

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/acro/>

contact@mychemistry.eu

ACRO not only allows you to create acronyms in a simple way but also lets you add them to different classes of acronyms. Lists can be created of separate classes wherever you want the list to appear.

ACRO also provides an option **single** which ignores acronyms that are used only once in the whole document.

As an experimental feature **ACRO** also offers the option **sort** which automatically sorts the list created by `\printacronyms`.

Table of Contents

1. Licence and Requirements	2	4.5. Reset or Mark as Used, Test if Acronym Has Been Used . . .	13
2. About	2	4.6. <code>\ac</code> and Friends in PDF Bookmarks, Accessibility Support, Tooltips	14
3. Basics	3	4.6.1. PDF Bookmarks	14
3.1. Creating New Acronyms . . .	3	4.6.2. Accessibility Support .	14
3.2. Using the Acronyms – the Commands	6	4.6.3. Tooltips	15
3.3. Plural Forms	8	4.7. Adding Acronyms to the Index	15
3.4. Alternative Short Forms . . .	9	5. Printing the List	16
3.5. Extra Information for the List Entry	10	6. Options and Customization	17
3.6. Foreign Language Acronyms .	10	6.1. General Options	17
4. Additional Commands and Possibilities	11	6.2. Options Regarding Acronyms	20
4.1. Indefinite Forms	11	6.3. Options Regarding the List . .	21
4.2. Uppercasing	12	7. Trailing Tokens and Special Action	22
4.3. Simulating the First Appearance	12	8. About Page Ranges	25
4.4. Using Classes	12		

9. Language Support	25	13.2. Own List Heading Command .	34
10. hyperref Support	25	14. Configuration Files	34
11. Defining Own Acronym Macros	26	A. All Acronyms Used in this Documentation	35
12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings	29	B. References	35
13. More on List Customization	31	C. Index	37
13.1. Own List Style	31		

1. Licence and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The software has the status “maintained.”

ACRO loads and needs the following packages: `expl3`,¹ `xparse`, `xtemplate`, `l3keys2e`,² `zref-abspace`³ and translations⁴ [Nie13].

2. About

Acronyms and initialisms are abbreviations formed from the initial components in a phrase or a word. These components may be individual letters (as in CEO) or parts of words (as in Benelux and Ameslan). There is no universal agreement on the precise definition of the various terms nor on written usage. [Wik12a]

After WIKIPEDIA told us what acronyms are and we won’t confuse them with units or other kinds of abbreviations – why would we need another package for them? There are several already: `acronym` [Oet12], `acromake` [Tho95], `acroterm` [Vos10], the abbreviations package `abbrevs` [Swio1] (the current version 1.4 has a bug,⁵ though), the nomenclature package `nomencl` [Vey+05], and of course the mighty glossaries [Tal13]. So there is really no *need* for a new package.

On the other hand acronym, the best of the acronym specific packages, has one or two shortcomings and sometimes using glossaries seems a bit of an overkill (or simply inconvenient as one has to run `makeglossaries`, `makeindex` or `xindy`, then⁶). So **ACRO** stands somewhere in between (but closer to acronym).

The main reason for the existence of **ACRO** is a question on T_EX.sx⁷ which intrigued me and

1. on CTAN as `l3kernel`: <http://mirrors.ctan.org/macros/latex/contrib/l3kernel/>

2. on CTAN as `l3packages`: <http://mirrors.ctan.org/macros/latex/contrib/l3packages/>

3. on CTAN as `oberdiek`: <http://mirrors.ctan.org/macros/latex/contrib/oberdiek/>

4. on CTAN as translations: <http://mirrors.ctan.org/macros/latex/contrib/translations/>

5. see <http://tex.stackexchange.com/q/59840/5049> for solutions.

6. Rumour has it there is going to be a version that can be used without running an external program

7. <http://tex.stackexchange.com/q/59449/5049>

in consequence led to **ACRO** and it's option **single**.

ACRO has many similarities with the acronym package. In fact, quite some macros have the same name and meaning.⁸

Please take a minute to think and decide which package will suit your needs best. Are you planning to add a glossary to your book? You should probably go with glossaries, then. Are you planning to add a nomenclature? You may want to choose nomencl (or again: glossaries) and so on. **ACRO** does a good job for lists of abbreviations.

3. Basics

3.1. Creating New Acronyms

Changed in
version 1.0

Acronyms are created with the command `\DeclareAcronym`.

`\DeclareAcronym{<id>}{<list of keys>}`

The basic command for declaring an acronym.

This command understands a number of keys which are listed below. Some of them are not described immediately but at appropriate places in the documentation.

short = {<text>} (required)
the short form of the acronym. This option is required: an acronym must have a short form. If this is set it *must* be set as first option! If another option is set first and notices the **short** option missing it assumes that the **ID** should be used as short version and sets it accordingly. A warning will be written to the log then.

long = {<text>} (required)
the long form of the acronym. This option is required: an acronym must have a description.

short-plural = {<text>} Default: s
the plural ending appended to the short form.

Introduced in
version 2.0

short-plural-form = {<text>}
the plural short form of the acronym; replaces the short form when used instead of appending the plural ending.

long-plural = {<text>} Default: s
the plural ending appended to the long form.

long-plural-form = {<text>}
plural long form of the acronym; replaces the long form when used instead of appending the plural ending.

Introduced in
version 2.0

alt-plural = {<text>} Default: s
the plural ending appended to the alternative form.

8. Not in the sense of `\meaning`!

3. Basics

Introduced in version 2.0	<code>alt-plural-form = {\langle text \rangle}</code> the plural alternative form of the acronym; replaces the alternative form when used instead of appending the plural ending.	
Introduced in version 1.4	<code>list = {\langle text \rangle}</code> if specified this will be written in the list as description instead of the long form.	
Introduced in version 1.2	<code>short-indefinite = {\langle text \rangle}</code> indefinite article for the short form.	Default: a
Introduced in version 1.2	<code>long-indefinite = {\langle text \rangle}</code> indefinite article for the long form.	Default: a
Introduced in version 1.1	<code>long-pre = {\langle text \rangle}</code> <code>\langle text \rangle</code> is prepended to the long form in the text but not in the list of acronyms.	
Introduced in version 1.1	<code>long-post = {\langle text \rangle}</code> <code>\langle text \rangle</code> is appended to the long form in the text but not in the list of acronyms.	
	<code>alt = {\langle text \rangle}</code> alternative short form.	
Introduced in version 1.2	<code>alt-indefinite = {\langle text \rangle}</code> indefinite article for the alternative form.	Default: a
	<code>extra = {\langle text \rangle}</code> extra information to be added in the list of acronyms.	
Introduced in version 1.3	<code>foreign = {\langle original long form \rangle}</code> can be useful when dealing with acronyms in foreign languages, see section 3.6 on page 10 for details.	
	<code>sort = {\langle text \rangle}</code> if used the acronym will be sorted according to this key instead of its ID.	
	<code>class = {\langle text \rangle}</code> the class the acronym belongs to.	
	<code>cite = {\langle prenote \rangle} {\langle postnote \rangle} {\langle citation keys \rangle}</code> a citation that is printed to the acronym according to an option explained later.	
	<code>short-format = {\langle TeX code \rangle}</code> the format used for the short form of the acronym.	
	<code>long-format = {\langle TeX code \rangle}</code> the format used for the long form of the acronym.	
	<code>first-long-format = {\langle TeX code \rangle}</code> the format used for the first long form of the acronym as set with <code>\ac</code> , <code>\acf</code> or <code>\acflike</code> and their uppercase, plural and indefinite forms.	

3. Basics

`pdfstring = {\langle text \rangle / \langle plural ending \rangle}`

used as PDF string replacement in bookmarks when used together with the hyperref package. The appended plural ending is optional. If you leave it (*and* the */*) the default ending is used.

`accsupp = {\langle text \rangle}`

sets the ActualText key as presented by the accsupp package for the acronym.

`tooltip = {\langle text \rangle}`

Introduced in
version 2.1

sets the tooltip description for an acronym. For actually getting tooltips you also need an appropriate setting of the `tooltip-cmd` option or to set the package option `tooltip`.

`index-sort = {\langle text \rangle}`

Introduced in
version 1.1

If you use the package option `index` every occurrence of an acronym is recorded to the index and sorted by its ID or (if set) by the value of the `sort` key. This key allows to set an individual sorting option for the index. See section 4.7 on page 15 for details.

`index = {\langle text \rangle}`

Introduced in
version 1.1

This key allows to overwrite the automatic index entry with an arbitrary one. See section 4.7 on page 15 for details.

`index-cmd = {\langle control sequence \rangle}`

Introduced in
version 1.1

This key let's you set an individual index creating command for this acronym. It should be a command that takes one mandatory argument. See section 4.7 on page 15 for details.

In its simplest form an acronym needs a short and a long form. Please note that both keys *must* be set and that the `short` key *must* always be the *first* key that is set.

```
1 % preamble:
2 \DeclareAcronym{test}{
3   short = ST ,
4   long  = Some Test
5 }
```

This creates the acronym “ST” with the ID “test” and the long form “Some Test.”

The `format` key allows you to choose a specific format for the short form of an acronym:

```
1 % preamble:
2 \DeclareAcronym{ot}{
3   short      = ot ,
4   long       = Other Test ,
5   short-format = \scshape
```

```
6 }
```

The short form now looks like this: OT.

The `\cite` key needs a bit explaining. It expects arguments like the standard `\cite` command, i.e., two optional arguments setting the $\langle prenote \rangle$ and $\langle postnote \rangle$ and one mandatory argument setting the citation key.

```
1 % preamble:
2 \DeclareAcronym{ny}{
3   short      = NY ,
4   short-plural = ,
5   long       = New York ,
6   long-plural = ,
7   cite      = {NewYork}
8 }
```

```
1 % bib file for use with biber/biblatex:
2 @online{NewYork,
3   author = {Wikipedia},
4   title  = {New York City},
5   urldate = {2012-09-27},
6   url    = {http://en.wikipedia.org/wiki/New_York_City},
7   year   = {2012}
8 }
```

The first appearance now looks as follows⁹: New York (NY) [Wik12b].

3.2. Using the Acronyms – the Commands

Acronyms are used with one of the following commands:

`\ac*{⟨id⟩}`

basic command; the first output is different from subsequent ones.

`\Ac*{⟨id⟩}`

same as `\ac` but capitalizes the first letter of the long form.

⁹. The appearance of the citation of course depends on the citation style you're using.

`\acs*{⟨id⟩}`

short form; the actual acronym.

`\acl*{⟨id⟩}`

long form; the meaning of the acronym.

`\Acl*{⟨id⟩}`

same as `\acl` but capitalizes first letter.

`\aca*{⟨id⟩}`

alternative short form as specified in the `alt` key of `\DeclareAcronym`; if it hasn't been specified this is identical to `\acs`.

`\acf*{⟨id⟩}`

first form; output like the first time `\ac` is output.

`\Acf*{⟨id⟩}`

same as `\acf` but capitalizes first letter of the long form.

`\acp*{⟨id⟩}`

plural form of `\ac`;

`\Acp*{⟨id⟩}`

same as `\acp` but capitalizes first letter of the long form.

`\acsp*{⟨id⟩}`

plural form of `\acs`;

`\aclp*{⟨id⟩}`

plural form of `\acl`;

`\Aclp*{⟨id⟩}`

same as `\aclp` but capitalizes first letter.

`\acap*{⟨id⟩}`

plural form of `\aca`;

`\acfp*{⟨id⟩}`

plural form of `\acf`;

`\Acfp*{⟨id⟩}`

same as `\acfp` but capitalizes first letter of the long form.

If an acronym is used the first time with `\ac` its output is different from subsequent uses. To be clear on this: the first time! If the acronym has been used with *any* of the output commands before it is *not* the first time any more.

If you use the starred variant an acronym will not be marked as used. This proves useful if an acronym is typeset in a section title, for example, since then the appearance in the table of contents won't mark it as used.

<pre> 1 % preamble: 2 % \DeclareAcronym{cd}{ 3 % short = cd , 4 % long = Compact Disc , 5 % short-format = \scshape 6 % } 7 first time: \ac{cd} \\ 8 second time: \ac{cd} \\ 9 short: \acs{cd} \\ 10 alternative: \aca{cd} \\ 11 first again: \acf{cd} \\ 12 long: \acl{cd} \\ 13 short plural: \acsp{cd} \\ 14 long plural: \aclp{cd} </pre>	<pre> first time: Compact Disc (CD) second time: CD short: CD alternative: CD first again: Compact Disc (CD) long: Compact Disc short plural: CDs long plural: Compact Discs </pre>
--	---

3.3. Plural Forms

If an acronym is defined in the standard way `\ACRO` uses an ‘s’ that’s appended to both the short and the long form when one of the plural commands is used. However, that is not always the best solution. For one thing not all acronyms may have a plural form. Second, the plural form especially of the long forms may be formed differently. And third, other languages can have other plural endings.

For these reasons `\DeclareAcronym` can get the following keys:

`short-plural = {⟨text⟩}` Default: s

The plural ending of the short form.

`long-plural = {⟨text⟩}` Default: s

The plural ending of the long form.

`long-plural-form = {⟨text⟩}`

An alternative plural form for the long form.

These keys are optional. If they’re not used, the default setting is s. If you use `long-plural-form` the long form will be replaced by the specified plural form when necessary.

Suppose we define the following acronyms:

```

1 \DeclareAcronym{cd}{
2   short      = cd ,
3   long       = Compact Disc ,
4   short-format = \scshape
5 }
6 \DeclareAcronym{ny}{
7   short      = NY ,
8   short-plural = ,

```



```

9   long      = New York ,
10  long-plural =
11  }
12  \DeclareAcronym{sw}{
13    short      = SW ,
14    long       = Sammelwerk ,
15    long-plural = e
16  }
17  \DeclareAcronym{MP}{
18    short      = MP ,
19    long       = Member of Parliament ,
20    long-plural-form = Members of Parliament
21  }

```

These acronyms now have the following plural appearances:

1 \acsp{cd}, \aclp{cd} \\ 2 \acsp{ny}, \aclp{ny} \\ 3 \acsp{sw}, \aclp{sw} \\ 4 \acsp{MP}, \aclp{MP}	CDS, Compact Discs NY, New York SWs, Sammelwerke MPs, Members of Parliament
---	--

3.4. Alternative Short Forms

For some acronyms it might be useful to have alternative forms. For this `\DeclareAcronym` has another key:

`alt = {⟨text⟩}`

Alternative short form.

```

1 % preamble:
2 % \DeclareAcronym{jpg}{
3 %   short = JPEG ,
4 %   alt   = JPG ,
5 %   long  = Joint Photographic Experts Group
6 % }
7 default: \acs{jpg} \\  
8 alt.: \aca{jpg}

```

default: JPEG
alt.: JPG

The alternative form uses the same plural ending as the default short form and is formatted in the same way.

3.5. Extra Information for the List Entry

Of course you can print a list of acronyms where their meaning is explained. Sometimes it can be useful to add additional information there. This is done with another key to `\DeclareAcronym`:

`extra = {\text}`

Additional information for the list of acronyms.

These information will only be displayed in the list. See section 5 on page 16 for the impact of the following example.

```

1 % preamble:
2 % \DeclareAcronym{nato}{
3 %   short      = nato ,
4 %   long       = North Atlantic Treaty Organization ,
5 %   extra      = \textit{deutsch}: Organisation des Nordatlantikvertrags ,
6 %   short-format = \scshape
7 % }
8 The \ac{nato} is an intergovernmental military alliance based on the
9 North Atlantic Treaty which was signed on 4~April 1949. \ac{nato}
10 headquarters are in Brussels, Belgium, one of the 28 member states
11 across North America and Europe, the newest of which, Albania and
12 Croatia, joined in April 2009.
```

The North Atlantic Treaty Organization (NATO) is an intergovernmental military alliance based on the North Atlantic Treaty which was signed on 4 April 1949. NATO headquarters are in Brussels, Belgium, one of the 28 member states across North America and Europe, the newest of which, Albania and Croatia, joined in April 2009.

3.6. Foreign Language Acronyms

I repeatedly read the wish for being able to add translations to acronyms when the acronyms stem from another language than the document language, *i.e.*, something like the following in a German document:

<pre> 1 \ac{ecu}\ 2 \ac{ecu}</pre>	<p>Steuergerät (Electronic Control Unit, ECU) ECU</p>
------------------------------------	---

That's why I decided to add the following key:

foreign = {*original long form*}

A description for an acronym originating in another language than the document language.

Here is the definition of the above mentioned ECU acronym:

```
1 \DeclareAcronym{ecu}{
2   short   = ECU ,
3   long    = Steuerger\at ,
4   foreign = Electronic Control Unit
5 }
```

As you have seen this adds the **foreign** entry to the first appearance of an acronym. It is also added in parentheses to the list of acronyms after the **long** entry. Actually the entry there is the argument to the following command:

\acroenparen{*argument*}

Places *argument* in parentheses: **\acroenparen**{example}: (example). See page 20 for a way to customize this other than redefining it.

4. Additional Commands and Possibilities

4.1. Indefinite Forms

Introduced in
version 1.2

Unlike many other languages¹⁰ in English the indefinite article is not determined by the grammatical case, gender or number but by the pronunciation of the following word. This means that the short and the long form of an acronym can have different indefinite articles. For these cases **ACRO** offers the keys **short-indefinite**, **alt-indefinite** and **long-indefinite** whose default is a. For every lowercase singular command two alternatives exist, preceded by **i** and **I**, respectively, which output the lowercase and uppercase version of the corresponding indefinite article.

```
1 % preamble:
2 % \DeclareAcronym{ufo}{
3 %   short      = UFO ,
4 %   long       = unidentified flying object ,
5 %   long-indefinite = an
6 % }
7 \Iac{ufo}; \iacs{ufo}; \iacl{ufo}
```

10. Let's better say: unlike the other languages where I know at least the basics.

An unidentified flying object (UFO); a UFO; an unidentified flying object

4.2. Uppercasing

`\acfirstupper{⟨token list⟩}`

Introduced in
version 1.3e

This command uppercases the first token in *⟨token list⟩*. The command is less powerful than `\makefirstuc` that is provided by the `mfirstuc` package [Tal12] but it is expandable. Obvious downsides are for example that it does not uppercase accented letters.

4.3. Simulating the First Appearance

Introduced in
version 1.2

Users told me¹¹ that there are cases when it might be useful to have the the acronym typeset according to the *first-style* but with another text than the long form. For such cases `ACRO` offers the following commands.

`\acflike*{⟨id⟩}{⟨instead of long form⟩}`

Write some alternative long form for acronym with ID *⟨id⟩* as if it were the first time the acronym was used.

`\acfplike*{⟨id⟩}{⟨instead of long form⟩}`

Plural form of `\acflike`.

```
1 \acsetup{first-style=footnote}
```

```
2 \acflike{ny}{the big apple}
```

NY^a

a. the big apple [Wik12b]

The plural ending in `\acfplike` is only appended to the short form. It makes no sense to append it to the text that is inserted manually anyway. Note that whatever text you're inserting might be gobbled depending on the *first-style* you're using.

4.4. Using Classes

The acronyms of `ACRO` can be divided into different classes. This doesn't change the output but allows different acronym lists, see section 5 on page 16. For this `\DeclareAcronym` has an additional key:

`class = {⟨text⟩}`

Associated class for an acronym.

This might be useful if you can and want to divide your acronyms into different types, technical and grammatical ones, say, that shall be listed in different lists.

¹¹. Well – one, to be precise ;)

```

1 % preamble:
2 % \DeclareAcronym{la}{
3 %   short      = LA ,
4 %   short-plural = ,
5 %   long       = Los Angeles ,
6 %   long-plural = ,
7 %   class      = city
8 % }
9 % \DeclareAcronym{ny}{
10 %   short      = NY ,
11 %   short-plural = ,
12 %   long       = New York ,
13 %   long-plural = ,
14 %   class      = city ,
15 %   cite       = NewYork
16 % }
17 \acl{la} (\acs{la}) \
18 \acl{ny} (\acs{ny})

```

Los Angeles (LA)
New York (NY)

4.5. Reset or Mark as Used, Test if Acronym Has Been Used

If you want for some reason to fool **ACRO** into thinking that an acronym is used for the first time you can call one of these commands:

\acreset{*<comma separated list of ids>*}

Introduced in
version 0.5

This will reset a used acronym such that the next use of **\ac** will again print it as if it were used the first time. This will *not* remove an acronym from being printed in the list if it actually *has* been used before.

\acresetall

Reset all acronyms.

\acifused{*<id>*}{*<true>*}{*<false>*}

Introduced in
version 1.3e

This command tests if the acronym with ID *<id>* has already been used and either puts **true** or **false** in the input stream.

```
1 \acreset{ny}\ac{ny}
```

New York (NY) [Wik12b]

Beware that both commands act *globally*! There are also commands that effectively do the opposite of **\acreset**, *i.e.*, mark acronyms as used:

\acuse{*<comma separated list of ids>*}

Introduced in
version 0.5

This has the same effect as if an acronym had been used twice, that is, further uses of **\ac** will

print the short form and the acronym will in any case be printed in the list (as long as its class is not excluded).

`\acuseall`

Mark all acronyms as used.

Introduced in
version 0.6a

4.6. `\ac` and Friends in PDF Bookmarks, Accessibility Support, Tooltips

4.6.1. PDF Bookmarks

`ACRO`'s commands usually are not expandable which means they'd leave unallowed tokens in PDF bookmarks. `hyperref` offers `\texorpdfstring` to circumvent that issue manually but that isn't really a nice solution. What's the point of having macros to get output for you if you have to specify it manually after all?

That is why `ACRO` offers a preliminary solution for this. In a bookmark every `\ac` like command falls back to a simple text string typesetting what `\acs` would do (or `\acsp` for plural forms). These text strings both can be accessed manually and can be modified to an output reserved for PDF bookmarks.

Introduced in
version 0.5

`\acpdfstring{<id>}`

Access the text string used in PDF bookmarks.

`\acpdfstringplural{<id>}`

Access the plural form of the text string used in PDF bookmarks.

`pdfstring = {{<pdfstring>/<plural ending>}}`

Key for `\DeclareAcronym` to declare a custom text string for PDF bookmarks. The plural ending can be set optionally.

For example the PDF acronym used in the title for this section is defined as follows:

```
1 \DeclareAcronym{pdf}{
2   short      = pdf ,
3   long       = Portable Document Format ,
4   format     = \scshape ,
5   pdfstring  = PDF ,
6   accsupp    = PDF
7 }
```

4.6.2. Accessibility Support

The last example also demonstrates the `accsupp` key. The idea is to have something different visible in the PDF file compared to what you get when you select and copy the corresponding

4. Additional Commands and Possibilities

string. In the example visible string is a lowercase pdf in small caps while the string copied is an uppercase PDF.

For this to work you need to use the *package option* `accsupp`, too, which will load the package `accsupp` if it isn't loaded by the user already. Then the key `accsupp` will set the `ActualText` property of `\BeginAccSupp`. Please refer to `accsupp`'s documentation for details. To see its effect copy PDF and paste it into a text file. You should get uppercase letters instead of lowercase ones.

`accsupp = {\text}`

Introduced in
version 1.0

Key for `\DeclareAcronym` to set the `ActualText` property of `\BeginAccSupp` (see `accsupp`'s documentation for details) to be used for an acronym. It only has an effect when the package option `accsupp` is used, too.

4.6.3. Tooltips

The idea of a tooltip is to have some text shown when you hover with the mouse over the short form of an acronym. This is only available in some PDF viewers, though. One possibility for such tooltips is loading the `pdfcomment` package [Kle12] and using its `\pdftooltip` macro.

`tooltip = true|false`

Default: false

Introduced in
version 2.1

This options loads the `pdfcomment` package and sets the command for creating tooltips to `\pdftooltip`.

`tooltip-cmd = {\control sequence}`

Default: `\@firstoftwo`

Introduced in
version 2.1

This allows users using another macro for tooltips – maybe one provided by another package or some own macro. It needs to be a macro with two mandatory arguments, the first being the string typeset in the PDF, the second being the tooltip description text.

For using this with acronyms they have a property `tooltip` which can be used inside `\DeclareAcronym` for specifying the description text of the tooltip. If the `tooltip` package option is used but the property is not set for an acronym then the `long` property is used instead.

If an acronym is used inside of another acronym then the tooltips of the “inner” acronyms are disabled.

4.7. Adding Acronyms to the Index

Introduced in
version 1.1

`ACRO` has the package option `index`. If it is used an index entry will be recorded every time an *unstarred* acronym command is used. The index entry will be `\langle id \rangle @ \langle short \rangle`, `\langle sort \rangle @ \langle short \rangle` if the `sort` key has been set, `\langle index-sort \rangle @ \langle short \rangle` if the `index-sort` has been set, or `\langle index \rangle` if the key `index` has been set for the specific acronym. The short versions appearing there are formatted according to the chosen format of the corresponding acronym, of course.

This document demonstrates the feature. You can find every acronym that has been declared in the index. In order to allow flexibility the indexing command can be chosen both globally via package option and individually for every acronym. This would allow to add acronyms to a specific index if more than one index is used, for example with help of the `imakeidx` package.

I'm not yet convinced this is a feature many people if anyone needs and if they do if it is flexible enough. If you have any thoughts on this I'd appreciate an email.

5. Printing the List

Changed in
version 1.0

Printing the whole list of acronyms is easy: just place `\printacronyms` where ever you want the list to be.

`\printacronyms[⟨options⟩]`

Print the list of acronyms.

The commands takes a few options, namely the following ones:

`include-classes = {⟨list of classes⟩}`

Takes a comma-separated list of the classes of acronyms that should be in the list.

`exclude-classes = {⟨list of classes⟩}`

Takes a comma-separated list of the classes of acronyms that should *not* be in the list.

`name = {⟨name of the list⟩}`

sets the name for the list.

`heading = {⟨sectioning command without leading backslash⟩}`

Default: `section*`

Sets the sectioning command for the heading of the list. A special value is `none` which suppresses the heading.

`sort = true|false`

Default: `true`

Set sorting for this list only.

Changed in
version 1.3

Introduced in
version 1.3

```
1 \acsetup{extra-style=comma}
2 \printacronyms[exclude-classes=city]
3
4 \printacronyms[include-classes=city,name={City Acronyms}]
```

Acronyms

CD Compact Disc

CTAN Comprehensive T_EX Archive Network

ECU Steuergerät (Electronic Control Unit)

ID identification string

JPEG Joint Photographic Experts Group

MP Member of Parliament

NATO North Atlantic Treaty Organization, *deutsch*: Organisation des Nordatlantikvertrags

PDF Portable Document Format

SW Sammelwerk

ST Some Test

UFO unidentified flying object

City Acronyms

LA Los Angeles

NY New York

You can see that the default layout is a description list with a `\section*` title. Both can be changed, see section 6.

The command `\printacronyms` needs two \LaTeX runs. This is a precaution to avoid error messages with a possibly empty list. But since almost all documents need at least two runs and often are compiled much more often than that, this fact shouldn't cause too much inconvenience.

6. Options and Customization

6.1. General Options

There are a few options which change the general behaviour of **ACRO**. Underlined values are used if no value is given.

`messages = silent|loud` Default: loud

Introduced in
version 1.6

Setting `messages = {silent}` will turn all of **ACRO**'s error messages into warnings and all of **ACRO**'s warnings into info messages. Be sure to check the log file carefully if you decide to set this option.

`single = true|false` Default: false

If set to `true` an acronym that's used only once (with `\ac`) in a document will only print the acronym in a specified form and will not be printed in the list.

`single-form = long|short|alt|first` Default: long

Introduced in
version 2.

Determines how a single appearance of an acronym is printed if `single = {true}` has been chosen.

`hyperref = true|false` Default: false

If set to `true` the short forms of the acronyms will be linked to their list entry.

6. Options and Customization

Introduced in version 1.5	<p><code>label = true false</code> Default: false</p> <p>If set to true this option will place <code>\label{⟨prefix⟩⟨id⟩}</code> the first time the acronym with ID <code>⟨id⟩</code> is used.</p>
Introduced in version 1.5	<p><code>label-prefix = {⟨text⟩}</code> Default: ac:</p> <p>The prefix for the <code>\label</code> that is placed when option <code>label = {true}</code> is used.</p>
	<p><code>record-pages = true false</code> Default: true</p> <p>Since ACRO can handle arabic, roman and Roman page numbers but <i>not</i> any other kind of numbering this option allows to turn the page number recording off for these cases as it would lead to errors else. This affects the whole document and can only be set in the preamble! It means you cannot have page numbers in the list of acronyms in this case. Or rather: you can if you use <code>pages = {first}</code>.</p>
	<p><code>only-used = true false</code> Default: true</p> <p>This option is true as default. It means that only acronyms that are actually used in the document are printed in the list. If false, all acronyms defined with <code>\DeclareAcronym</code> will be written to the list.</p>
Introduced in version 1.2	<p><code>mark-as-used = first any</code> Default: any</p> <p>This option determines whether an acronym is mark as used when the <i>first</i> form is used the first time (with <code>\ac</code>, <code>\acf</code> or <code>\acflike</code> and their uppercase, plural and indefinite forms) or when any of the <code>\ac</code>-like commands is used.</p>
	<p><code>macros = true false</code> Default: false</p> <p>If set to true this option will create a macro <code>\⟨id⟩</code> for each acronym as a shortcut for <code>\ac{⟨id⟩}</code>. Already existing macros will <i>not</i> be overwritten.</p>
Introduced in version 0.6	<p><code>xspace = true false</code> Default: false</p> <p>If set to true this option will append <code>\xspace</code> from the xspace package to the commands created with the <code>macros</code> option.</p>
	<p><code>strict = true false</code> Default: false</p> <p>If set to true and the option <code>macros = {true}</code> is in effect then already existing macros will be overwritten.</p>
	<p><code>sort = true false</code> Default: true</p> <p>If set to true the acronym list will be sorted automatically. The entries are sorted by their ID ignoring upper and lower case. This option needs the experimental package <code>l3sort</code> (from the <code>l3experimental</code> bundle) and can only be set in the preamble.</p>
	<p><code>cite = all first none</code> Default: first</p> <p>This option decides whether citations that are added via <code>cite</code> are added to each first, every or no appearance of an acronym.</p>
	<p><code>cite-cmd = {⟨control sequence⟩}</code> Default: <code>\cite</code></p> <p>This option determines which command is used for the citation. Each citation command that takes the cite key as argument is valid, for example biblatex's <code>\footcite</code>.</p>

6. Options and Customization

`cite-connect = {\code}` Default: `\nobreakspace`

Depending on the citation command in use a space should be inserted before the citation or maybe not (e.g. `\footcite...`). This option allows you to set this. Actually it can be used to place arbitrary code right before the citation.

`group-citation = true|false` Default: `false`

Introduced in
version 2.0

If set to true the short form (or the long form) and the citation of an acronym will be printed together in parentheses when an acronym is used the first time.

`group-cite-cmd = {\control sequence}` Default: `\cite`

Introduced in
version 2.0

This option determines which command is used for the citation when an acronym is used the first time and `group-citation = {true}`. Each citation command that takes the cite key as argument is valid, for example biblatex's `\footcite`.

`index = true|false` Default: `false`

Introduced in
version 1.1

If set to true an index entry will be recorded every time an *unstarred* acronym command is used for the corresponding acronym.

`index-cmd = {\control sequence}` Default: `\index`

Introduced in
version 1.1

Chooses the index command that is used when option `index` has been set to true.

`accsupp = true|false` Default: `false`

Introduced in
version 1.0

Activates the access support as provided by the accsupp package.

`tooltip = true|false` Default: `false`

Introduced in
version 2.1

Activates tooltip support for `ACRO` using the pdfcomment package.

`tooltip-cmd = {\control sequence}` Default: `\@firstoftwo`

Introduced in
version 2.1

A macro taking two mandatory arguments, the first being the short form of the acronym and the second being some tooltip description.

`uc-cmd = {\control sequence}` Default: `\acfirstupper`

The command that is used to capitalize the first word in the `\Ac` and the like commands. You can change it to another one like for example `\makefirstuc`¹² or `\MakeTextUppercase`.¹³

All options of this and the following sections can be set up either as package options or via the setup command:

`\acsetup{\options}`

Set up `ACRO` anywhere in the document. Or separate package loading from setup.

```
1 % with \acsetup{macros}
2 we could have used these before: \nato, \ny
```

12. from the mfirstuc package

13. from the textcase package

we could have used these before: NATO, NY

6.2. Options Regarding Acronyms

The options described in this section all influence the layout of one of the possible output forms of the acronyms.

short-format = { $\langle format \rangle$ } (initially empty)
Sets a format for all short forms. For example **short-format** = {\scshape} would print all short forms in small caps.

long-format = { $\langle format \rangle$ } (initially empty)
The same for the long forms.

Introduced in
version 1.3

foreign-format = { $\langle format \rangle$ } (initially empty)
The format for the **foreign** entry when it appears as part of the first appearance of an acronym.

Introduced in
version 1.2

first-long-format = { $\langle format \rangle$ } (initially empty)
The format for the long form on first usage (with \ac, \acf or \acflike and their uppercase, plural and indefinite forms).

Introduced in
version 1.1

list-short-format = { $\langle format \rangle$ } (initially empty)
An extra format for the short entries in the list. If not used this is the same as **short-format**. Please be aware that a call of **short-format** after this one will overwrite it again.

list-long-format = { $\langle format \rangle$ } (initially empty)
An extra format for the long entries in the list. If not used this is the same as **long-format**. Please be aware that a call of **long-format** after this one will overwrite it again.

list-foreign-format = { $\langle format \rangle$ } Default: \acroenparen
The format for the **foreign** entry as it appears in the list. This may be code that ends with a macro that takes a mandatory argument.

extra-format = { $\langle format \rangle$ } (initially empty)
The same for the extra information.

Changed in
version 1.1

first-style = default|plain|empty|square|short|reversed|plain-reversed|footnote|sidenote Default: default
The basic style of the first appearance of an acronym. The value sidenote needs the command \sidenote to be defined for example by the sidenotes package.

extra-style = default|plain|comma|paren|bracket Default: default
Defines the way the extra information is printed in the list.

plural-ending = { $\langle tokenlist \rangle$ } Default: s
With this option the default plural ending can be set.

```

1 % (Keep in mind that we're in
2 % a minipage here!)
3 \acsetup{first-style=empty}
4 \acf{ny} \\\
5 \acsetup{first-style=footnote}
6 \acf{ny} \\\
7 \acsetup{first-style=square}
8 \acf{ny} \\\
9 \acsetup{first-style=short}
10 \acf{ny} \\\
11 \acsetup{first-style=reversed}
12 \acf{ny} \\\
13 \acsetup{first-style=plain}
14 \acf{ny} \\\
15 \acsetup{first-style=plain-reversed}
16 \acf{ny}

```

NY
NY^a
New York [NY] [Wik12b]
NY [Wik12b]
NY (New York) [Wik12b]
New York – NY [Wik12b]
NY – New York [Wik12b]

a. New York [Wik12b]

6.3. Options Regarding the List

page-ref = none|plain|comma|paren Default: none

If this option is set to a value other than none the page numbers of the an acronym appeared on are printed in the list. Please note that this is an experimental feature and might fail in quite a number of cases. If you notice anything please send me an email!

pages = all|first Default: all

Introduced in
version 1.5

If the option **page-ref** has any value other than none this option determines whether all usages of the acronyms are listed or only the first time. Implicitly sets **label** = {true}.

page-name = {<page name>} Default: p.\@,\,

The “name” of the page label. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

pages-name = {<page name plural>} Default: pp.\@,\,

Introduced in
version 1.0

The “name” of the page label when there are more than one page. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

following-page = true|false Default: false

Introduced in
version 1.3

If set to true a page range in the list of acronyms that consists of two pages will be written by the first page and an appended f. This depends on the option **next-page**.

following-pages = true|false Default: false

Introduced in
version 1.3

If set to true a page range in the list of acronyms that set consists of more than two pages will be written by the first page and an appended ff. This depends on the option **next-pages**.

7. Trailing Tokens and Special Action

Introduced in version 1.0	<p><code>next-page = {\text}</code> Default: <code>\,f.\@</code></p> <p>Appended to a page number when <code>following-page</code> is set to <code>true</code> and the range is only 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.</p>
Introduced in version 1.0	<p><code>next-pages = {\text}</code> Default: <code>\,ff.\@</code></p> <p>Appended to a page number when <code>following-pages</code> is set to <code>true</code> and the range is more than 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.</p>
Changed in version 2.2	<p><code>list-style = description lof longtable extra-longtable extra-longtable-rev extra-tabular extra-tabular-rev tabular toc</code> Default: <code>description</code></p> <p>Choose with which style the list of acronyms should be typeset. If you choose <code>\longtable</code>, <code>extra-longtable</code> or <code>extra-longtable-rev</code> you have to load the <code>longtable</code> [Caro4] package in your preamble. The values <code>extra-⟨something⟩</code> put the extra information in a column of its own. <i>Be aware that per default all extra-table styles only use 1 column. Since acronym descriptions can easily get longer than a line you should probably define your own style if you want to use them.</i> See section 13 on page 31 for details.</p>
Changed in version 2.0	<p><code>list-heading = chapter chapter* section section* subsection subsection* subsubsection subsubsection* addchap addsec none</code> Default: <code>section*</code></p> <p>The heading type of the list. The last two only work with a KOMA-Script class that also defines the appropriate command. A special value is <code>none</code> which suppresses the heading.</p>
	<p><code>list-name = {\text}</code> Default: <code>Acronyms</code></p> <p>The name of the list. This is what's written in the list-heading. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.</p>
	<p><code>list-caps = true false</code> Default: <code>false</code></p> <p>Print the first letters of the long form capitalized.</p>

7. Trailing Tokens and Special Action

Introduced in version 2.0

ACRO has the possibility to look ahead for certain tokens and switch a boolean if it finds them. Per default **ACRO** knows about three tokens: the “dot” (`.`), the “dash” (`-`) and the “babel-hyphen” (`\babelhyphen`).

A token is made known to **ACRO** with the following macro:

`\AcroRegisterTrailing⟨token⟩{⟨name⟩}`

This registers the token `⟨token⟩` so **ACRO** looks if it follows directly after an acronym macro. `⟨name⟩` is the internal name for this token.

The **ACRO** package already registers the above mentioned tokens:

7. Trailing Tokens and Special Action

```
1 \AcroRegisterTrailing . {dot}
2 \AcroRegisterTrailing - {dash}
3 \AcroRegisterTrailing \babelhyphen {babel-hyphen}
```

If a token is registered it doesn't mean that **ACRO** looks for it. The token must first be activated for this:

activate-trailing-tokens = {*<csv list of token names>*}

Tell **ACRO** to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens. Per default only dot is activated.

deactivate-trailing-tokens = {*<csv list of token names>*}

Tell **ACRO** not to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens.

All of the above on its own does nothing visible. However: inside of an acronym, *i. e.*, for example inside the long or the short form it can be tested for those trailing tokens:

\aciftrailing{*<csv list of token names>*}{*<true>*}{*<false>*}

Check if one of the tokens listed in *<csv list of token names>* is following and either place *<true>* or *<false>* in the input stream.

ACRO uses this to define to further macros:

\acdote

Inserts a . if no dot follows.

\acspace

Inserts a **\space** if no dash or babel-hyphen follows.

The definitions are equivalent¹⁴ to the following code:

```
1 \newcommand*\acdote{\aciftrailing{dot}}{.}{\@}
2 \newcommand*\acspace{\aciftrailing{dash,babel-hyphen}}{\space}
```

This could be used to define an acronym as follows:

14. Not *quite*: **ACRO**'s definitions are engine protected.

```

1 \DeclareAcronym{etc}{
2   short = {\textit{etc}\acdot} ,
3   long  = {\textit{et cetera}} ,
4   short-plural = , long-plural =
5 }

```

If now you somewhere use

```

1 \ac{etc}.

```

there won't be two dots printed.

The command `\acspace` is used already in the definition of the first appearance of a macro. Let's say you're a German chemist and you have

```

1 \DeclareAcronym{PU}{
2   long = Polyurethan ,
3   long-plural = e
4 }

```

and you use it the first time like this:

```

1 \ac{PU}-Hartschaum

```

then according to German orthography and typesetting rules this should be printed as

“Polyurethan(PU)-Hartschaum”

i. e., with *no* space between long and short form. This is exactly what happens if you say

```

1 \acsetup{activate-trailing-tokens = {dash,babel-hyphen}}

```

in the preamble.

8. About Page Ranges

If you enable the `page-ref` option **ACRO** adds page numbers to the list of acronyms. In version 0.* it would add a page reference for an acronym in the list of acronyms that used `\pageref` to refer to the first appearance of an acronym. This is retained using `pages = {first}`. Version 1.0 uses a different approach that doesn't use a label but instead will list *all* pages an acronym appeared on. With `hyperref` the pages are referenced using `\hyperpage`.

There are some options that control how this list will be typeset, e.g., `following-page`, `next-pages` or the option `page-ref` itself. It is important to mention that the page list will always take at least two compilation runs until changes in the options or the actual page numbers affect it. This is due to the fact that the updated sequence is first written to the aux file and only read in during the next run.

9. Language Support

ACRO detects if packages `babel` or `polyglossia` are being loaded and tries to adapt certain strings to match the chosen language. However, due to my limited language knowledge only a few translations are provided. I'll show how the English translations are defined so you can add the translations to your preamble if needed. Even better would be you'd send me a short email at contact@mychemistry.eu with the appropriate translations for your language and I'll add them to **ACRO**.

```
1 \DeclareTranslation{English}{acronym-list-name}{Acronyms}
2 \DeclareTranslation{English}{acronym-page-name}{p.}
3 \DeclareTranslation{English}{acronym-pages-name}{pp.}
4 \DeclareTranslation{English}{acronym-next-page}{f.}
5 \DeclareTranslation{English}{acronym-next-pages}{ff.}
```

10. hyperref Support

The option `hyperref = {true}` adds internal links from all short (or alternative) forms to their respective list entries. Of course this only works if you have loaded the `hyperref` package in your preamble. You should use this option with care: if you don't use `\printacronyms` anywhere this option will result in loads of `hyperref` warnings. Also printing several lists can result in warnings if don't clearly separate the lists into different classes. If an acronym appears in more than one list there will also be more than one hypertarget for this acronym.

Using `hyperref` will also add `\hyperpage` to the page numbers in the list (provided they are displayed in the style chosen). Like with an index the references will thus not point to the acronyms directly but to the page they're on.

11. Defining Own Acronym Macros

Introduced in
version 2.0

The commands explained in section 3.2 on page 6 have all been defined with a dedicated command – there is a family of dedicated commands, actually:

`\NewAcroCommand{⟨cs⟩}{⟨code⟩}`

Defines a new **ACRO** acronym command `⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\NewDocumentCommand`. Inside `⟨code⟩` one can refer to the ID `⟨id⟩` with `#1`.

`\RenewAcroCommand{⟨cs⟩}{⟨code⟩}`

Defines a new **ACRO** acronym command `⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\RenewDocumentCommand`. Inside `⟨code⟩` one can refer to the ID `⟨id⟩` with `#1`.

`\DeclareAcroCommand{⟨cs⟩}{⟨code⟩}`

Defines a new **ACRO** acronym command `⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\DeclareDocumentCommand`. Inside `⟨code⟩` one can refer to the ID `⟨id⟩` with `#1`.

`\ProvideAcroCommand{⟨cs⟩}{⟨code⟩}`

Defines a new **ACRO** acronym command `⟨cs⟩`. This sets up the necessary framework needed by acronym commands and defines `⟨cs⟩` with an optional star argument and a mandatory argument for the acronym id using xparse's `\ProvideDocumentCommand`. Inside `⟨code⟩` one can refer to the ID `⟨id⟩` with `#1`.

Inside these macros one can use a number of low-level `expl3` commands.¹⁵

Acronym fetching commands

`\acro_use:n {⟨id⟩}`

Fetches the acronym using either the first or the long form depending on earlier uses.

`\acro_short:n {⟨id⟩}`

Fetches the short form of the acronym.

`\acro_long:n {⟨id⟩}`

Fetches the long form of the acronym.

`\acro_alt:n {⟨id⟩}`

Fetches the alternative short form of the acronym.

¹⁵ Which is why you need to use them inside an `expl3` programming environment. This means in the preamble surround the definitions with `\ExplSyntaxOn` and `\ExplSyntaxOff`.

`\acro_foreign:n {⟨id⟩}`

Fetches the foreign property of the acronym if available.

`\acro_extra:n {⟨id⟩}`

Fetches the extra property of the acronym if available.

Acronym setup commands

`\acro_first_upper:`

ACRO setup command which tells the macros above that we want to uppercase the first letter of the long version. Should be used *before* one of the acronym fetching commands.

`\acro_plural:`

ACRO setup command which tells the macros above that we want to use plural forms. Should be used *before* one of the acronym fetching commands.

`\acro_indefinite:`

ACRO setup command which tells the macros above that we want to add the indefinite article. Should be used *before* one of the acronym fetching commands.

`\acro_cite:`

ACRO setup command which tells the macros above that we want to add the citation in any case independent of the option `\cite`. Should be used *before* one of the acronym fetching commands.

`\acro_no_cite:`

ACRO setup command which tells the macros above that we want to have no citation independent of the option `\cite`. Should be used *before* one of the acronym fetching commands.

`\acro_index:`

ACRO setup command which tells the macros above that we want to add an index in any case independent of the option `\index`. Should be used *before* one of the acronym fetching commands.

`\acro_reset_specials:`

Introduced in
version 2.0b

This macro is called implicitly by `\NewAcroCommand` and `\NewPseudoAcroCommand`. If you plan to define an **ACRO** command by yourself using `\NewDocumentCommand` this should be the first macro after `\acro_begin:`. It ensures that in nested acronyms the inner acronyms don't inherit indefinite articles, uppercasing, endings...

Additional macros for further uses

`\acro_begin:`

When an acronym macro is defined “by hand”, *i. e.*, *not using* `\NewAcroCommand` then this must be the first macro in the code. *Must have a matching* `\acro_end:`.

`\acro_end:`

When an acronym macro is defined “by hand”, *i. e.*, *not using* `\NewAcroCommand` then this must be the last macro in the code. *Must have a matching* `\acro_begin:`.

11. Defining Own Acronym Macros

`\acro_check_and_mark_if:nn` {*<boolean expression>*} {*<id>*}

Checks if the acronym with the ID *<id>* exists and marks it as used when *<boolean>* expression evaluates to true. This macro is used inside `\NewAcroCommand` and friends implicitly.

`\acro_check_acronym:nn` {*<id>*} {true|false}

Checks if the acronym with the ID *<id>* exists and marks it as used if true or doesn't. This macro is used inside `\acro_check_and_mark_if:nn`.

`\acro_use_acronym:n` {true|false}

Tell `\acro_use:n` and similar commands whether to mark the acronym as used or not. This macro is used inside `\acro_check_acronym:nn`. If this macro is used explicitly it should be used before `\acro_use:n` (or a similar command) otherwise it has no effect. An acronym marked as used cannot be unmarked.

`\acro_mark_as_used:n` {*<id>*}

Explicitly use the acronym with the ID *<id>*. This is the `expl3` macro applied to all entries in `\acuse`.

* `\acro_if_acronym_used:nTF` {*<id>*} {*<true>*} {*<false>*}

The code-level version of `\acifused`. This macro is expandable.

`\acro_for_all_acronyms_do:n` {*<code>*}

Loops over all acronyms known when the macro is used. Inside of *<code>* you can refer to the ID *<id>* of an acronym with `#1`.

Examples The usage of above macros is best explained with a few examples. The following definition is done by `ACRO`:

```
1 \NewAcroCommand \ac { \acro_use:n {#1} }
```

An equivalent definition for `\ac` would be

```
1 \NewDocumentCommand \ac {sm}
2 {
3   \acro_begin:
4     \acro_reset_specials:
5     \acro_check_and_mark_if:nn {#1} {#2}
6     \acro_use:n {#2}
7   \acro_end:
8 }
```

12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings

which should explain what the actual framework is which `\NewAcroCommand` adds.

Other definitions by `ACRO` are for example the following ones:

```
1 \NewAcroCommand \Ac
2 {
3   \acro_first_upper:
4   \acro_use:n {#1}
5 }
6 \NewAcroCommand \iac
7 {
8   \acro_indefinite:
9   \acro_use:n {#1}
10 }
11 \NewAcroCommand \acp
12 {
13   \acro_plural:
14   \acro_use:n {#1}
15 }
16 \NewAcroCommand \Acp
17 {
18   \acro_plural:
19   \acro_first_upper:
20   \acro_use:n {#1}
21 }
22 \NewAcroCommand \Aclp
23 {
24   \acro_plural:
25   \acro_first_upper:
26   \acro_long:n {#1}
27 }
```

12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings

`ACRO` has a concept of *endings*. All of `ACRO`'s plural options are defined by saying

```
1 \ProvideAcroEnding {plural} {s} {s}
```

The command's syntax and what it does is as follows:

`\ProvideAcroEnding{⟨name⟩}{⟨short default⟩}{⟨long default⟩}`

This macro defines the options

- `⟨name⟩-ending`,
- `short-⟨name⟩-ending`,
- `alt-⟨name⟩-ending` and
- `long-⟨name⟩-ending`.

It also defines the acronym properties

- `short-⟨name⟩`,
- `short-⟨name⟩-form`,
- `alt-⟨name⟩`,
- `alt-⟨name⟩-form`,
- `long-⟨name⟩` and
- `long-⟨name⟩-form`.

Additionally it defines a setup macro as described in section 11 on page 26, `\acro_⟨name⟩`. If `⟨name⟩` contains a - (dash) it is replaced by `_` before `\acro_⟨name⟩` is built. So if you choose `my-name` the corresponding macro is named `\acro_my_name`. If you use any other non-letters you are on your own.

Note that you *must* use `\ProvideAcroEnding` before any acronym definition!

This could be used together with the macros described in section 11 on page 26 for adding support for possessive forms:

```

1 \ExplSyntaxOn
2 % this now only works because I've use the same already in the preamble so
3 % it does nothing here:
4 \ProvideAcroEnding {possessive} {'s} {'s}
5
6 \NewAcroCommand \acg
7 {
8   \acro_possessive:
9   \acro_use:n {#1}
10 }
11 \ExplSyntaxOff
12 The \acg{cd} booklet says\ldots

```

The CD's booklet says...

Please note that different endings are cumulative which you probably want to avoid! Imagine a macro

```

1 \NewAcroCommand \acgp
2 {
3   \acro_possessive:
4   \acro_plural:
5   \acro_use:n {#1}
6 }

```

This would give “CDs’s” instead of “CDs’”. To solve this you might want to consider

```

1 \ProvideAcroEnding {possessive-singular} {'s} {'s}
2 \ProvideAcroEnding {possessive-plural} {s'} {s'}

```

13. More on List Customization

13.1. Own List Style

The different existing list styles are all built from four different templates, `list`, `list-of`, `table` and `extra-table`. Those templates are defined with the help of the `xtemplate` package (from [L3Pa]). Each of these templates has a few options which are described in table 1 on the next page. New list styles now are defined via the following macro:

`\DeclareAcroListStyle{<name>}{<template>}{<options>}`

Declares a new **ACRO** list style `<name>`. `<name>` will be the value which can be chosen in the option `list-style`. `<template>` is the name of the template to be used by the style. Available styles are listed in table 1. `<options>` are the option settings for the corresponding template.

For defining new styles you need some information on what the different templates and options do:

- The option `list` of the `list` template sets the list environment. This must be a classic \LaTeX list where items are listed with `\item`. In those lists short entries will always be fed as optional argument to `\item`:
`\item[<short>]{<long>}{<extra>}{<page>}`
- The template `list-of` simulates a table of contents or a list of figures. This can be chosen by setting the option `style` to either `toc` or `lof`.
- The template `table` typesets the list in a table with two columns:
`<short> & <long>{<extra>}{<page>}` `\tabularnewline`
- The template `extra-table` typesets the list in a table with four columns:
`<short> & <long> & <extra> & <page>` `\tabularnewline`

TABLE 1: Available List Templates and Their Options

Template	Option	Option Type	Default
list	list	tokenlist	description
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
list-of	style	tokenlist	toc
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
table	table	tokenlist	tabular
	table-spec	tokenlist	lp{.7\linewidth}
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
extra-table	table	tokenlist	tabular
	table-spec	tokenlist	llll
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	

- The option `foreign-sep` is the code inserted between long form and foreign entry (if a foreign entry is present).
- The options `before` and `after` are inserted directly before and after the complete list.
- The option `reverse` switches the place of `<long>` with `<extra>`.
- The option `table-spec` sets the column types for the table templates. It must correspond to the number of columns the corresponding template uses.

As an example let's define a style `longtabu` which uses the corresponding table environment from the package `tabu` [Che11]:

```

1 \usepackage{tabu,longtable}
2 \DeclareAcroListStyle{longtabu}{table}{
3   table = longtabu ,
4   table-spec = @{}>{\bfseries}lX@{}
5 }
6 \acsetup{list-style=longtabu}

```

As another example let's define a new list with the help of the `enumitem` package [Bez11]:

```

1 % preamble:
2 % \usepackage{enumitem}
3 \newlist{acronyms}{description}{1}
4 \newcommand*\addcolon[1]{#1:}
5 \setlist[acronyms]{
6   labelwidth = 3em,
7   leftmargin = 3.5em,
8   noitemsep,
9   itemindent = 0pt,
10  font=\addcolon}
11 \DeclareAcroListStyle{mystyle}{list}{ list = acronyms }
12 \acsetup{ list-style = mystyle }

```

This would look as follows:

Acronyms

CD: Compact Disc

CTAN: Comprehensive T_EX Archive Network

ECU: Steuergerät (Electronic Control Unit)
ID: identification string
JPEG: Joint Photographic Experts Group
LA: Los Angeles
MP: Member of Parliament
NATO: North Atlantic Treaty Organization, *deutsch:* Organisation des Nordatlantikvertrags
NY: New York
PDF: Portable Document Format
SW: Sammelwerk
ST: Some Test
UFO: unidentified flying object

13.2. Own List Heading Command

With the option `list-heading` you can choose which command prints the heading of the list. If you need a different choice than what's already provided you can use the following command to define a new option:

`\DeclareAcroListHeading{<name>}{<control sequence>}`

Defines a new value `<name>` for the option `list-heading`. `<control sequence>` must be a control sequence which takes one mandatory argument.

As an example here is how the value section is defined:

```
1 \DeclareAcroListHeading{section}{\section}
```

14. Configuration Files

Introduced in
version 2.2

If you repeatedly have the same setup and definitions for **ACRO** in your preamble you might want to place those in a configuration file. If **ACRO** finds a file `acro.cfg` present it inputs it at the end of the package. The only thing to be aware of is that this file is input in an `expl3` programming environment. This means spaces are ignored and must be input explicitly with `~`. The characters `:` and `_` have category code 12, *i. e.*, they are letters and can be part of macro names. Since the file is included in the package also `@` has category code 12.

Details on `expl3` can be found in [L3Pb]. Most likely you can find it on your system:

```
~ $ texdoc interface3
```

A. All Acronyms Used in this Documentation

CD:	Compact Disc
CTAN:	Comprehensive T _E X Archive Network
ECU:	Steuergerät (Electronic Control Unit)
ID:	identification string
JPEG:	Joint Photographic Experts Group
LA:	Los Angeles
MP:	Member of Parliament
NATO:	North Atlantic Treaty Organization, <i>deutsch</i> : Organisation des Nordatlantikvertrags
NY:	New York
PDF:	Portable Document Format
SW:	Sammelwerk
ST:	Some Test
UFO:	unidentified flying object

B. References

- [Bez11] Javier BEZOS. enumitem. version 3.5.2, Sept. 28, 2011.
URL: <http://mirror.ctan.org/macros/latex/contrib/enumitem/>.
- [Caro4] David CARLISLE. longtable. version 4.11, Feb. 1, 2004.
URL: <http://mirror.ctan.org/macros/latex/required/tools/>.
- [Che11] Florent CHERVET. tabu. version 2.8, Feb. 26, 2011.
URL: <http://mirror.ctan.org/macros/latex/contrib/tabu/>.
- [Kle12] Josef KLEBER. pdfcomment. version 2.3a, Sept. 28, 2012.
URL: <http://mirror.ctan.org/macros/latex/contrib/pdfcomment/>.
- [L3Pa] THE L^AT_EX₃ PROJECT TEAM. l3packages. version SVN 5530, July 15, 2015.
URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages/>.
- [L3Pb] THE L^AT_EX₃ PROJECT TEAM. *The L^AT_EX₃ Interfaces*. Sept. 6, 2015. URL: <http://mirrors.ctan.org/macros/latex/contrib/l3kernel/interface3.pdf>.
- [Nie13] Clemens NIEDERBERGER. translations. version 1.1a, Sept. 30, 2013.
URL: <http://mirror.ctan.org/macros/latex/contrib/translations/>.
- [Oet12] Tobias OETIKER.
acronym. *An Acronym Environment for L^AT_EX 2_ε*. version 1.38, Oct. 29, 2012.
URL: <http://mirror.ctan.org/macros/latex/contrib/acronym/>.
- [Swio1] Matt SWIFT. abbrevs. version 1.4, Sept. 8, 2001. URL:
<http://mirror.ctan.org/macros/latex/contrib/frankenstein/abbrevs/>.
- [Tal12] Nicola L.C. TALBOT. mfirstuc. version 1.05, May 21, 2012.
URL: <http://mirror.ctan.org/macros/latex/contrib/glossaries/>.
- [Tal13] Nicola L.C. TALBOT. glossaries. version 3.05, Apr. 21, 2013.
URL: <http://mirror.ctan.org/macros/latex/contrib/glossaries/>.

B. References

- [Tho95] Paul A. THOMPSON. *acromake*. version na, July 16, 1995.
URL: <http://mirror.ctan.org/macros/latex/contrib/acromake/>.
- [Vey+05] Boris VEYTSMAN et al.
nomencl. A Package to Create a Nomenclature. version 4.2, Sept. 22, 2005.
URL: <http://mirror.ctan.org/macros/latex/contrib/nomencl/>.
- [Vos10] Jakob VOSS. *acroterm*. version 0.1, Nov. 19, 2010.
URL: <http://mirror.ctan.org/macros/latex/contrib/acroterm/>.
- [Wik12a] WIKIPEDIA. *Acronym and initialism*. 2012.
URL: <http://en.wikipedia.org/wiki/Acronyms> (visited on 06/21/2012).
- [Wik12b] WIKIPEDIA. *New York City*. 2012.
URL: http://en.wikipedia.org/wiki/New_York_City (visited on 09/27/2012).

C. Index

A	
abbrevs (package)	2
\Ac	6, 19, 29
\ac	4, 6 ff., 10, 13 f., 17 f., 20, 24, 28
\aca	7 ff.
\acap	7
accsupp	5, 14 f., 19
accsupp (package)	5, 15, 19
\acdot	23 f.
\Acf	7
\acf	4, 7 f., 18, 20 f.
\acfirstupper	12, 19
\acflike	4, 12, 18, 20
\Acfp	7
\acfp	7
\acfplike	12
\acg	30
\aciftrailing	23
\acifused	13, 28
\Acl	7
\acl	7 f., 13
\Aclp	7, 29
\aclp	7 ff.
\Acp	7, 29
\acp	7, 29
\acpdfstring	14
\acpdfstringplural	14
\acreset	13
\acresetall	13
\acroenparen	11, 20
acromake (package)	2
acronym (package)	2 f.
<i>Acronym and initialism</i>	2
\AcroRegisterTrailing	22 f.
acroterm (package)	2
\acs	7 ff., 13 f.
\acsetup	12, 16, 19, 21, 24, 33
\acsp	7 ff., 14
\acspace	23 f.
activate-trailing-tokens	23
\acuse	13, 28
\acuseall	14
alt	4, 7, 9
alt-indefinite	4, 11
alt-plural	3
alt-plural-form	4
B	
BEZOS, Javier	33
C	
CARLISLE, David	22
CHERVET, Florent	33
cite	4, 6, 18, 27
cite-cmd	18
cite-connect	19
class	4, 12
D	
deactivate-trailing-tokens	23
\DeclareAcroCommand	26
\DeclareAcroListHeading	34
\DeclareAcroListStyle	31, 33
\DeclareAcronym	3, 5–12, 14 f., 18, 24
E	
enumitem (package)	33
exclude-classes	16
expl3 (package)	2
extra	4, 10
extra-format	20
extra-style	20
F	
first-long-format	4, 20
first-style	12, 20
following-page	21 f., 25
following-pages	21 f.
foreign	4, 11, 20
foreign-format	20
format	5
G	
glossaries (package)	2 f.

- group-citation 19
- group-cite-cmd 19
- H**
- heading 16
- hyperref 17, 25
- hyperref (package) 5, 14, 25
- I**
- \Iac 11
- \iac 29
- \iaccl 11
- \iacs 11
- include-classes 16
- index 5, 15, 19, 27
- index-cmd 5, 19
- index-sort 5, 15
- K**
- KLEBER, Josef 15
- L**
- l3experimental (package) 18
- l3keys2e (package) 2
- l3packages (bundle) 31
- l3sort (package) 18
- label 18, 21
- label-prefix 18
- list 4
- list-caps 22
- list-foreign-format 20
- list-heading 22, 34
- list-long-format 20
- list-name 22
- list-short-format 20
- list-style 22, 31
- long 3, 11, 15
- long-format 4, 20
- long-indefinite 4, 11
- long-plural 3, 8
- long-plural-form 3, 8
- long-post 4
- long-pre 4
- longtable (package) 22
- LPPL 2
- M**
- macros 18
- \makefirsttuc 12
- mark-as-used 18
- messages 17
- mfirsttuc (package) 12, 19
- N**
- name 16
- New York City 6, 12 f., 21
- \NewAcroCommand 26–31
- \NewPseudoAcroCommand 27
- next-page 21 f.
- next-pages 21 f., 25
- NIEDERBERGER, Clemens 2
- nomenc (package) 2 f.
- O**
- OETIKER, Tobias 2
- only-used 18
- P**
- page-name 21
- page-ref 21, 25
- pages 18, 21, 25
- pages-name 21
- pdfcomment (package) 15, 19
- pdfstring 5, 14
- plural-ending 20
- \printacronyms 1, 16 f., 25
- \ProvideAcroCommand 26
- \ProvideAcroEnding 29 ff.
- R**
- record-pages 18
- \RenewAcroCommand 26
- S**
- short 3, 5
- short-format 4, 20
- short-indefinite 4, 11
- short-plural 3, 8
- short-plural-form 3
- single 1, 3, 17
- single-form 17

Index

<code>sort</code>	1, 4 f., 15 f., 18	V	
<code>strict</code>	18	VEYTSMAN, Boris	2
SWIFT, Matt	2	Voss, Jakob	2
T			
tabu (package)	33	W	
TALBOT, Nicola	2, 12	WIKIPEDIA	2, 6, 12 f., 21
<i>The L^AT_EX₃ Interfaces</i>	34	X	
THE L ^A T _E X ₃ PROJECT TEAM.....	31, 34	xparse (package)	2, 26
THOMPSON, Paul.....	2	<code>xspace</code>	18
<code>tooltip</code>	5, 15, 19	xtemplate (package)	2, 31
<code>tooltip-cmd</code>	5, 15, 19		
translations (package)	2		
U			
<code>uc-cmd</code>	19	Z	
		zref-abspace (package)	2