

# ACRO

v2.4a      2016/04/13

Typeset Acronyms

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/acro/>

[contact@mychemistry.eu](mailto:contact@mychemistry.eu)

**ACRO** not only allows you to create acronyms in a simple way but also lets you add them to different classes of acronyms. Lists can be created of separate classes wherever you want the list to appear.

**ACRO** also provides an option **single** which ignores acronyms that are used only once in the whole document.

As an experimental feature **ACRO** also offers the option **sort** which automatically sorts the list created by `\printacronyms`.

## Table of Contents

<b>1. Licence and Requirements</b>	<b>2</b>	3.6. Reset or Mark as Used, Test if Acronym Has Been Used . . .	13
<b>2. Basics</b>	<b>2</b>	3.7. <code>\ac</code> and Friends in PDF Bookmarks, Accessibility Support, Tooltips . . . . .	14
2.1. Creating New Acronyms . . .	2	3.7.1. PDF Bookmarks . . . .	14
2.2. Using the Acronyms – the Commands . . . . .	6	3.7.2. Accessibility Support .	15
2.3. Plural Forms . . . . .	8	3.7.3. Tooltips . . . . .	15
2.4. Alternative Short Forms . . .	9	3.8. Adding Acronyms to the Index	15
2.5. Extra Information for the List Entry . . . . .	9	<b>4. Printing the List</b>	<b>16</b>
2.6. Foreign Language Acronyms .	10	<b>5. Options and Customization</b>	<b>17</b>
<b>3. Additional Commands and Possibilities</b>	<b>11</b>	5.1. General Options . . . . .	17
3.1. Indefinite Forms . . . . .	11	5.2. Options Regarding Acronyms	20
3.2. Uppercasing . . . . .	11	5.3. Options Regarding the List . .	21
3.3. Simulating the First Appearance	12	<b>6. Trailing Tokens and Special Action</b>	<b>23</b>
3.4. Fetching the Single Appearance	12	<b>7. About Page Ranges</b>	<b>25</b>
3.5. Using Classes . . . . .	12		

<b>8. Dividing Your Document Into Pieces – Creating Local Lists</b>	<b>25</b>	<b>13. More on List Customization</b>	<b>32</b>
<b>9. Language Support</b>	<b>26</b>	13.1. Own List Style . . . . .	32
<b>10. hyperref Support</b>	<b>26</b>	13.2. Own List Heading Command .	35
<b>11. Defining Own Acronym Macros</b>	<b>27</b>	<b>14. Configuration Files</b>	<b>36</b>
<b>12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings</b>	<b>31</b>	A. All Acronyms Used in this Documentation	36
		B. References	36
		C. Index	38

## 1. Licence and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The software has the status “maintained.”

**ACRO** loads and needs the following packages: `expl3`,<sup>1</sup> `xparse`, `xtemplate`, `l3keys2e`,<sup>2</sup> `zref-abspage`<sup>3</sup> and translations<sup>4</sup> [Nie15].

## 2. Basics

### 2.1. Creating New Acronyms

Acronyms are created with the command `\DeclareAcronym`.

`\DeclareAcronym{<id>}{<list of keys>}`

The basic command for declaring an acronym.

This command understands a number of keys which are listed below. Some of them are not described immediately but at appropriate places in the documentation.

`short = {<text>}` (required)  
the short form of the acronym. This option is required: an acronym must have a short form. If this is set it *must* be set as first option! If another option is set first and notices the `short` option missing it assumes that the `ID` should be used as short version and sets it accordingly. A warning will be written to the log then.

`long = {<text>}` (required)  
the long form of the acronym. This option is required: an acronym must have a description.

1. on CTAN as `l3kernel`: <http://mirrors.ctan.org/macros/latex/contrib/l3kernel/>

2. on CTAN as `l3packages`: <http://mirrors.ctan.org/macros/latex/contrib/l3packages/>

3. on CTAN as `oberdiek`: <http://mirrors.ctan.org/macros/latex/contrib/oberdiek/>

4. on CTAN as `translations`: <http://mirrors.ctan.org/macros/latex/contrib/translations/>

**short-plural** = { $\langle text \rangle$ } Default: s  
the plural ending appended to the short form.

Introduced in  
version 2.0

**short-plural-form** = { $\langle text \rangle$ }  
the plural short form of the acronym; replaces the short form when used instead of appending the plural ending.

**long-plural** = { $\langle text \rangle$ } Default: s  
the plural ending appended to the long form.

**long-plural-form** = { $\langle text \rangle$ }  
plural long form of the acronym; replaces the long form when used instead of appending the plural ending.

Introduced in  
version 2.0

**alt-plural** = { $\langle text \rangle$ } Default: s  
the plural ending appended to the alternative form.

Introduced in  
version 2.0

**alt-plural-form** = { $\langle text \rangle$ }  
the plural alternative form of the acronym; replaces the alternative form when used instead of appending the plural ending.

Introduced in  
version 1.4

**list** = { $\langle text \rangle$ }  
if specified this will be written in the list as description instead of the long form.

Introduced in  
version 1.2

**short-indefinite** = { $\langle text \rangle$ } Default: a  
indefinite article for the short form.

Introduced in  
version 1.2

**long-indefinite** = { $\langle text \rangle$ } Default: a  
indefinite article for the long form.

Introduced in  
version 1.1

**long-pre** = { $\langle text \rangle$ }  
 $\langle text \rangle$  is prepended to the long form in the text but not in the list of acronyms.

Introduced in  
version 1.1

**long-post** = { $\langle text \rangle$ }  
 $\langle text \rangle$  is appended to the long form in the text but not in the list of acronyms.

**alt** = { $\langle text \rangle$ }  
alternative short form.

Introduced in  
version 1.2

**alt-indefinite** = { $\langle text \rangle$ } Default: a  
indefinite article for the alternative form.

**extra** = { $\langle text \rangle$ }  
extra information to be added in the list of acronyms.

Introduced in  
version 1.3

**foreign** = { $\langle original long form \rangle$ }  
can be useful when dealing with acronyms in foreign languages, see section 2.6 on page 10 for details.

## 2. Basics

Introduced in  
version 2.3

`foreign-lang = {\langle language \rangle}`

the babel [Bra16] or polyglossia [Cha15] language of the foreign form. This language is used to wrap the entry with `\foreignlanguage{\langle language \rangle}` if either babel or polyglossia is loaded. You'll need to take care that the corresponding language is loaded by babel or polyglossia.

Introduced in  
version 2.3

`single = {\langle text \rangle}`

if provided `\langle text \rangle` will be used instead of the long form if the acronym is only used a single time and the option `single = {true}` is active.

`sort = {\langle text \rangle}`

if used the acronym will be sorted according to this key instead of its ID.

Changed in  
version 2.4

`class = {\langle csv list \rangle}`

the class(es) the acronym belongs to.

`cite = {\langle prenote \rangle}[\langle postnote \rangle]{\langle citation keys \rangle}`

a citation that is printed to the acronym according to an option explained later.

`short-format = {\langle TEX code \rangle}`

the format used for the short form of the acronym.

`long-format = {\langle TEX code \rangle}`

the format used for the long form of the acronym.

`first-long-format = {\langle TEX code \rangle}`

the format used for the first long form of the acronym as set with `\ac`, `\acf` or `\acflike` and their uppercase, plural and indefinite forms.

Introduced in  
version 2.3

`single-format = {\langle TEX code \rangle}`

the format used for the acronym if the acronym is only used a single time.

`first-style = default | plain | empty | square | short | reversed | plain-reversed | footnote | sidenote`

Introduced in  
version 2.3

the style of the first appearance of the acronym, see also section 5.2.

`pdfstring = {\langle text \rangle / \langle plural ending \rangle}`

used as PDF string replacement in bookmarks when used together with the hyperref package. The appended plural ending is optional. If you leave it (*and* the `/`) the default ending is used.

`accsupp = {\langle text \rangle}`

sets the ActualText key as presented by the accsupp package for the acronym.

Introduced in  
version 2.1

`tooltip = {\langle text \rangle}`

sets the tooltip description for an acronym. For actually getting tooltips you also need an appropriate setting of the `tooltip-cmd` option or to set the package option `tooltip`.

Introduced in  
version 1.1

`index-sort = {\langle text \rangle}`

If you use the package option `index` every occurrence of an acronym is recorded to the index

and sorted by its ID or (if set) by the value of the `sort` key. This key allows to set an individual sorting option for the index. See section 3.8 on page 15 for details.

`index = {⟨text⟩}`

Introduced in  
version 1.1

This key allows to overwrite the automatic index entry with an arbitrary one. See section 3.8 on page 15 for details.

`index-cmd = {⟨control sequence⟩}`

Introduced in  
version 1.1

This key let's you set an individual index creating command for this acronym. It should be a command that takes one mandatory argument. See section 3.8 on page 15 for details.

In its simplest form an acronym needs a short and a long form. Please note that both keys *must* be set and that the `short` key *must* always be the *first* key that is set.

```
1 % preamble:
2 \DeclareAcronym{test}{
3   short = ST ,
4   long  = Some Test
5 }
```

This creates the acronym “ST” with the ID “test” and the long form “Some Test.”

The `format` key allows you to choose a specific format for the short form of an acronym:

```
1 % preamble:
2 \DeclareAcronym{ot}{
3   short      = ot ,
4   long       = Other Test ,
5   short-format = \scshape
6 }
```

The short form now looks like this: OT.

The `cite` key needs a bit explaining. It expects arguments like the standard `\cite` command, *i.e.*, two optional arguments setting the `⟨prenote⟩` and `⟨postnote⟩` and one mandatory argument setting the citation key.

```
1 % preamble:
2 \DeclareAcronym{ny}{
3   short      = NY ,
4   short-plural = ,
```

```

5   long      = New York ,
6   long-plural = ,
7   cite      = {NewYork}
8 }

```

```

1 % bib file for use with biber/biblatex:
2 @online{NewYork,
3   author = {Wikipedia},
4   title  = {New York City},
5   urldate = {2012-09-27},
6   url    = {http://en.wikipedia.org/wiki/New_York_City},
7   year   = {2012}
8 }

```

The first appearance now looks as follows<sup>5</sup>: .

## 2.2. Using the Acronyms – the Commands

Acronyms are used with one of the following commands:

`\ac*{⟨id⟩}`

basic command; the first output is different from subsequent ones.

`\Ac*{⟨id⟩}`

same as `\ac` but capitalizes the first letter of the long form.

`\acs*{⟨id⟩}`

short form; the actual acronym.

`\acl*{⟨id⟩}`

long form; the meaning of the acronym.

`\Acl*{⟨id⟩}`

same as `\acl` but capitalizes first letter.

`\aca*{⟨id⟩}`

alternative short form as specified in the `alt` key of `\DeclareAcronym`; if it hasn't been specified this is identical to `\acs`.

`\acf*{⟨id⟩}`

first form; output like the first time `\ac` is output.

---

5. The appearance of the citation of course depends on the citation style you're using.

`\Acf*{⟨id⟩}`  
 same as `\acf` but capitalizes first letter of the long form.

`\acp*{⟨id⟩}`  
**p**lural form of `\ac`;

`\Acp*{⟨id⟩}`  
 same as `\acp` but capitalizes first letter of the long form.

`\acsp*{⟨id⟩}`  
 plural form of `\acs`;

`\aclp*{⟨id⟩}`  
 plural form of `\acl`;

`\Aclp*{⟨id⟩}`  
 same as `\aclp` but capitalizes first letter.

`\acap*{⟨id⟩}`  
 plural form of `\aca`;

`\acfp*{⟨id⟩}`  
 plural form of `\acf`;

`\Acfp*{⟨id⟩}`  
 same as `\acfp` but capitalizes first letter of the long form.

If an acronym is used the first time with `\ac` its output is different from subsequent uses. To be clear on this: the first time! If the acronym has been used with *any* of the output commands before it is *not* the first time any more.

If you use the starred variant an acronym will not be marked as used. This proves useful if an acronym is typeset in a section title, for example, since then the appearance in the table of contents won't mark it as used.

Introduced in  
 version 0.5

<pre> 1 % preamble: 2 % \DeclareAcronym{cd}{ 3 %   short      = cd , 4 %   long       = Compact Disc , 5 %   short-format = \scshape 6 % } 7 first time: \ac{cd} \\ 8 second time: \ac{cd} \\ 9 short: \acs{cd} \\ 10 alternative: \aca{cd} \\ 11 first again: \acf{cd} \\ 12 long: \acl{cd} \\ 13 short plural: \acsp{cd} \\ 14 long plural: \aclp{cd} </pre>	<pre> first time: second time: CD short: CD alternative: CD first again: long: Compact Disc short plural: CDs long plural: Compact Discs </pre>
--	---

### 2.3. Plural Forms

If an acronym is defined in the standard way **ACRO** uses an ‘s’ that’s appended to both the short and the long form when one of the plural commands is used. However, that is not always the best solution. For one thing not all acronyms may have a plural form. Second, the plural form especially of the long forms may be formed differently. And third, other languages can have other plural endings.

For these reasons `\DeclareAcronym` can get the following keys:

`short-plural = {⟨text⟩}` Default: s

The plural ending of the short form.

`long-plural = {⟨text⟩}` Default: s

The plural ending of the long form.

`long-plural-form = {⟨text⟩}`

An alternative plural form for the long form.

These keys are optional. If they’re not used, the default setting is s. If you use `long-plural-form` the long form will be replaced by the specified plural form when necessary.

Suppose we define the following acronyms:

```

1 \DeclareAcronym{cd}{
2   short      = cd ,
3   long       = Compact Disc ,
4   short-format = \scshape
5 }
6 \DeclareAcronym{ny}{
7   short      = NY ,
8   short-plural = ,
9   long       = New York ,
10  long-plural =
11 }
12 \DeclareAcronym{sw}{
13   short      = SW ,
14   long       = Sammelwerk ,
15   long-plural = e
16 }
17 \DeclareAcronym{MP}{
18   short      = MP ,
19   long       = Member of Parliament ,
20   long-plural-form = Members of Parliament
21 }
```

These acronyms now have the following plural appearances:



1 <code>\acsp{cd}, \aclp{cd} \</code>	CDS, Compact Discs
2 <code>\acsp{ny}, \aclp{ny} \</code>	NY, New York
3 <code>\acsp{sw}, \aclp{sw} \</code>	SWs, Sammelwerke
4 <code>\acsp{MP}, \aclp{MP}</code>	MPs, Members of Parliament

## 2.4. Alternative Short Forms

For some acronyms it might be useful to have alternative forms. For this `\DeclareAcronym` has another key:

`alt = {⟨text⟩}`

Alternative short form.

```

1 % preamble:
2 % \DeclareAcronym{jpg}{
3 %   short = JPEG ,
4 %   alt   = JPG ,
5 %   long  = Joint Photographic Experts Group
6 % }
7 default: \acs{jpg} \
8 alt.: \aca{jpg}

```

---

default: JPEG  
alt.: JPG

The alternative form uses the same plural ending as the default short form and is formatted in the same way.

## 2.5. Extra Information for the List Entry

Of course you can print a list of acronyms where their meaning is explained. Sometimes it can be useful to add additional information there. This is done with another key to `\DeclareAcronym`:

`extra = {⟨text⟩}`

Additional information for the list of acronyms.

These information will only be displayed in the list. See section 4 on page 16 for the impact of the following example.

```

1 % preamble:
2 % \DeclareAcronym{nato}{
3 %   short      = nato ,
4 %   long       = North Atlantic Treaty Organization ,
5 %   extra      = \textit{deutsch}: Organisation des Nordatlantikvertrags ,
6 %   short-format = \scshape
7 % }
8 The \ac{nato} is an intergovernmental military alliance based on the
9 North Atlantic Treaty which was signed on 4~April 1949. \ac{nato}
10 headquarters are in Brussels, Belgium, one of the 28 member states
11 across North America and Europe, the newest of which, Albania and
12 Croatia, joined in April 2009.

```

---

The is an intergovernmental military alliance based on the North Atlantic Treaty which was signed on 4 April 1949. NATO headquarters are in Brussels, Belgium, one of the 28 member states across North America and Europe, the newest of which, Albania and Croatia, joined in April 2009.

## 2.6. Foreign Language Acronyms

Introduced in  
version 1.3

I repeatedly read the wish for being able to add translations to acronyms when the acronyms stem from another language than the document language, *i.e.*, something like the following in a German document:

```

1 \ac{ecu}\
2 \ac{ecu}

```

ECU

That's why I decided to add the following properties:

**foreign** = {*<original long form>*}

A description for an acronym originating in another language than the document language.

**foreign-lang** = {*<language>*}

The babel [Bra16] or polyglossia [Cha15] language of the foreign form. This language is used to wrap the entry with `\foreignlanguage{<language>}`.

Introduced in  
version 2.3

Here is the definition of the above mentioned ECU acronym:

```

1 \DeclareAcronym{ecu}{
2   short   = ECU ,

```

```

3 long    = Steuerger\"at ,
4 foreign = Electronic Control Unit ,
5 foreign-lang = english
6 }

```

As you have seen this adds the **foreign** entry to the first appearance of an acronym. It is also added in parentheses to the list of acronyms after the **long** entry. Actually the entry there is the argument to the following command:

`\acroenparen{⟨argument⟩}`

Places `⟨argument⟩` in parentheses: `\acroenparen{example}`: (example). See page 21 for a way to customize this other than redefining it.

### 3. Additional Commands and Possibilities

#### 3.1. Indefinite Forms

Introduced in  
version 1.2

Unlike many other languages<sup>6</sup> in English the indefinite article is not determined by the grammatical case, gender or number but by the pronunciation of the following word. This means that the short and the long form of an acronym can have different indefinite articles. For these cases **ACRO** offers the keys **short-indefinite**, **alt-indefinite** and **long-indefinite** whose default is a. For every lowercase singular command two alternatives exist, preceded by **i** and **I**, respectively, which output the lowercase and uppercase version of the corresponding indefinite article.

```

1 % preamble:
2 % \DeclareAcronym{ufo}{
3 %   short      = UFO ,
4 %   long       = unidentified flying object ,
5 %   long-indefinite = an
6 % }
7 \Iac{ufo}; \iacs{ufo}; \iacl{ufo}

```

---

; a UFO; an unidentified flying object

#### 3.2. Uppercasing

`\acfirstupper{⟨token list⟩}`

Introduced in  
version 1.3e

This command uppercases the first token in `⟨token list⟩`. The command is less powerful than `\makefirstuc` that is provided by the `mfirstuc` package [Tal15] but it is expandable. Obvious downsides are for example that it does not uppercase accented letters.

6. Let's better say: unlike the other languages where I know at least the basics.

### 3.3. Simulating the First Appearance

Introduced in  
version 1.2

Users told me<sup>7</sup> that there are cases when it might be useful to have the the acronym typeset according to the `first-style` but with another text than the long form. For such cases `ACRO` offers the following commands.

`\acflike*{⟨id⟩}{⟨instead of long form⟩}`

Write some alternative long form for acronym with ID `⟨id⟩` as if it were the first time the acronym was used.

`\acfplike*{⟨id⟩}{⟨instead of long form⟩}`

Plural form of `\acflike`.

```
1 \acsetup{first-style=footnote}
2 \acflike{ny}{the big apple}
```

The plural ending in `\acfplike` is only appended to the short form. It makes no sense to append it to the text that is inserted manually anyway. Note that whatever text you're inserting might be gobbled depending on the `first-style` you're using.

### 3.4. Fetching the Single Appearance

Introduced in  
version 2.3

There are macros that fetch the *single* appearance of an acronym even if it has been used more than once and the `single` option is active.

`\acsingle*{⟨id⟩}`

Write acronym as if it were used only a single time.

`\Acsingle*{⟨id⟩}`

Uppercase form of `\acsingle`.

```
1 \acsingle{ny}
```

New York

### 3.5. Using Classes

The acronyms of `ACRO` can be divided into different classes. This doesn't change the output but allows different acronym lists, see section 4 on page 16. For this `\DeclareAcronym` has an additional key:

---

7. Well – one, to be precise ;)

`class = {⟨csv list⟩}`

Changed in  
version 2.4

Associated class(es) for an acronym.

This might be useful if you can and want to divide your acronyms into different types, technical and grammatical ones, say, that shall be listed in different lists. Since every acronym can get a list of associated classes those classes can effectively be used like tags for filtering acronyms.

```

1 % preamble:
2 % \DeclareAcronym{la}{
3 %   short      = LA ,
4 %   short-plural = ,
5 %   long       = Los Angeles ,
6 %   long-plural = ,
7 %   class      = city
8 % }
9 % \DeclareAcronym{ny}{
10 %   short      = NY ,
11 %   short-plural = ,
12 %   long       = New York ,
13 %   long-plural = ,
14 %   class      = city ,
15 %   cite       = NewYork
16 % }
17 \acl{la} (\acs{la}) \
18 \acl{ny} (\acs{ny})

```

Los Angeles (LA)  
New York (NY)

### 3.6. Reset or Mark as Used, Test if Acronym Has Been Used

If you want for some reason to fool **ACRO** into thinking that an acronym is used for the first time you can call one of these commands:

`\acreset{⟨comma separated list of ids⟩}`

Introduced in  
version 0.5

This will reset a used acronym such that the next use of `\ac` will again print it as if it were used the first time. This will *not* remove an acronym from being printed in the list if it actually *has* been used before.

`\acresetall`

Reset all acronyms.

`\acifused{⟨id⟩}{⟨true⟩}{⟨false⟩}`

Introduced in  
version 1.3e

This command tests if the acronym with ID `⟨id⟩` has already been used and either puts `true` or `false` in the input stream.

```
1 \acreset{ny}\ac{ny}
```

Beware that both commands act *globally*! There are also commands that effectively do the opposite of `\acreset`, *i.e.*, mark acronyms as used:

`\acuse{⟨comma separated list of ids⟩}`

Introduced in  
version 0.5

This has the same effect as if an acronym had been used twice, that is, further uses of `\ac` will print the short form and the acronym will in any case be printed in the list (as long as its class is not excluded).

`\acuseall`

Introduced in  
version 0.6a

Mark all acronyms as used.

### 3.7. `\ac` and Friends in PDF Bookmarks, Accessibility Support, Tooltips

#### 3.7.1. PDF Bookmarks

**ACRO**'s commands usually are not expandable which means they'd leave unallowed tokens in PDF bookmarks. `hyperref` offers `\texorpdfstring` to circumvent that issue manually but that isn't really a nice solution. What's the point of having macros to get output for you if you have to specify it manually after all?

Introduced in  
version 0.5

That is why **ACRO** offers a preliminary solution for this. In a bookmark every `\ac` like command falls back to a simple text string typesetting what `\acs` would do (or `\acsp` for plural forms). These text strings both can be accessed manually and can be modified to an output reserved for PDF bookmarks.

`\acpdfstring{⟨id⟩}`

Access the text string used in PDF bookmarks.

`\acpdfstringplural{⟨id⟩}`

Access the plural form of the text string used in PDF bookmarks.

`pdfstring = {{⟨pdfstring⟩/⟨plural ending⟩}}`

Key for `\DeclareAcronym` to declare a custom text string for PDF bookmarks. The plural ending can be set optionally.

For example the PDF acronym used in the title for this section is defined as follows:

```
1 \DeclareAcronym{pdf}{
2   short      = pdf ,
3   long       = Portable Document Format ,
4   format     = \scshape ,
5   pdfstring  = PDF ,
6   accsupp    = PDF
```

### 3.7.2. Accessibility Support

The last example also demonstrates the `accsupp` key. The idea is to have something different visible in the PDF file compared to what you get when you select and copy the corresponding string. In the example visible string is a lowercase pdf in small caps while the string copied is an uppercase PDF.

For this to work you need to use the *package option* `accsupp`, too, which will load the package `accsupp` if it isn't loaded by the user already. Then the key `accsupp` will set the `ActualText` property of `\BeginAccSupp`. Please refer to `accsupp`'s documentation for details. To see its effect copy PDF and paste it into a text file. You should get uppercase letters instead of lowercase ones.

`accsupp = {\text}`

Introduced in  
version 1.0

Key for `\DeclareAcronym` to set the `ActualText` property of `\BeginAccSupp` (see `accsupp`'s documentation for details) to be used for an acronym. It only has an effect when the package option `accsupp` is used, too.

### 3.7.3. Tooltips

The idea of a tooltip is to have some text shown when you hover with the mouse over the short form of an acronym. This is only available in some PDF viewers, though. One possibility for such tooltips is loading the `pdfcomment` package [Kle12] and using its `\pdftooltip` macro.

`tooltip = true|false`

Default: false

Introduced in  
version 2.1

This options loads the `pdfcomment` package and sets the command for creating tooltips to `\pdftooltip`.

`tooltip-cmd = {\control sequence}`

Default: `\@firstoftwo`

Introduced in  
version 2.1

This allows users using another macro for tooltips – maybe one provided by another package or some own macro. It needs to be a macro with two mandatory arguments, the first being the string typeset in the PDF, the second being the tooltip description text.

For using this with acronyms they have a property `tooltip` which can be used inside `\DeclareAcronym` for specifying the description text of the tooltip. If the `tooltip` package option is used but the property is not set for an acronym then the `long` property is used instead.

If an acronym is used inside of another acronym then the tooltips of the “inner” acronyms are disabled.

## 3.8. Adding Acronyms to the Index

Introduced in  
version 1.1

`ACRO` has the package option `index`. If it is used an index entry will be recorded every time an *unstarred* acronym command is used. The index entry will be `\langle id \rangle @ \langle short \rangle`, `\langle sort \rangle @ \langle short \rangle` if the

## 4. Printing the List

`sort` key has been set,  $\langle index-sort \rangle @ \langle short \rangle$  if the `index-sort` has been set, or  $\langle index \rangle$  if the key `index` has been set for the specific acronym. The short versions appearing there are formatted according to the chosen format of the corresponding acronym, of course.

This document demonstrates the feature. You can find every acronym that has been declared in the index. In order to allow flexibility the indexing command can be chosen both globally via package option and individually for every acronym. This would allow to add acronyms to a specific index if more than one index is used, for example with help of the `imakeidx` package.

I'm not yet convinced this is a feature many people if anyone needs and if they do if it is flexible enough. If you have any thoughts on this I'd appreciate an email.

### 4. Printing the List

Changed in  
version 1.0

Printing the whole list of acronyms is easy: just place `\printacronyms` where ever you want the list to be.

`\printacronyms[ $\langle options \rangle$ ]`

Print the list of acronyms.

The commands takes a few options, namely the following ones:

`include-classes = { $\langle list of classes \rangle$ }`

Takes a comma-separated list of the classes of acronyms that should be in the list.

`exclude-classes = { $\langle list of classes \rangle$ }`

Takes a comma-separated list of the classes of acronyms that should *not* be in the list.

`name = { $\langle name of the list \rangle$ }`

sets the name for the list.

`heading = { $\langle sectioning command without leading backslash \rangle$ }`

Default: `section*`

Sets the sectioning command for the heading of the list. A special value is `none` which suppresses the heading.

`sort = true | false`

Default: `true`

Set sorting for this list only.

`local-to-barriers = true | false`

Default: `false`

This option can be used to create a list of only the acronyms of the current “barrier group”, see section 8.

Changed in  
version 1.3

Introduced in  
version 1.3

Introduced in  
version 2.4

```
1 \acsetup{extra-style=comma}
2 \printacronyms[exclude-classes=city]
3
4 \printacronyms[include-classes=city,name={City Acronyms}]
```



## Acronyms

**CD** Compact Disc

**CTAN** Comprehensive T<sub>E</sub>X Archive Network

**ECU** Steuergerät (Electronic Control Unit)

**ID** identification string

**JPEG** Joint Photographic Experts Group

**LPPL** L<sup>A</sup>T<sub>E</sub>X Project Public License

**MP** Member of Parliament

**NATO** North Atlantic Treaty Organization, *deutsch*: Organisation des Nordatlantikvertrags

**PDF** Portable Document Format

**SW** Sammelwerk

**ST** Some Test

**UFO** unidentified flying object

## City Acronyms

**LA** Los Angeles

**NY** New York

You can see that the default layout is a description list with a `\section*` title. Both can be changed, see section 5.

The command `\printacronyms` needs two L<sup>A</sup>T<sub>E</sub>X runs. This is a precaution to avoid error messages with a possibly empty list. But since almost all documents need at least two runs and often are compiled much more often than that, this fact shouldn't cause too much inconvenience.

## 5. Options and Customization

### 5.1. General Options

There are a few options which change the general behaviour of `ACRO`. Underlined values are used if no value is given.

## 5. Options and Customization

Introduced in version 1.6	<p><code>messages = silent loud</code> <span style="float: right;">Default: loud</span></p> <p>Setting <code>messages = {silent}</code> will turn all of <b>ACRO</b>'s error messages into warnings and all of <b>ACRO</b>'s warnings into info messages. Be sure to check the log file carefully if you decide to set this option.</p>
	<p><code>single = true false</code> <span style="float: right;">Default: false</span></p> <p>If set to <code>true</code> an acronym that's used only once (with <code>\ac</code>) in a document will only print the acronym in a specified form and will not be printed in the list.</p>
Introduced in version 2.	<p><code>single-form = long short alt first</code> <span style="float: right;">Default: long</span></p> <p>Determines how a single appearance of an acronym is printed if <code>single = {true}</code> has been chosen.</p>
	<p><code>hyperref = true false</code> <span style="float: right;">Default: false</span></p> <p>If set to <code>true</code> the short forms of the acronyms will be linked to their list entry.</p>
Introduced in version 1.5	<p><code>label = true false</code> <span style="float: right;">Default: false</span></p> <p>If set to <code>true</code> this option will place <code>\label{⟨prefix⟩⟨id⟩}</code> the first time the acronym with ID <code>⟨id⟩</code> is used.</p>
Introduced in version 1.5	<p><code>label-prefix = {⟨text⟩}</code> <span style="float: right;">Default: ac:</span></p> <p>The prefix for the <code>\label</code> that is placed when option <code>label = {true}</code> is used.</p>
	<p><code>record-pages = true false</code> <span style="float: right;">Default: true</span></p> <p>Since <b>ACRO</b> can handle arabic, roman and Roman page numbers but <i>not</i> any other kind of numbering this option allows to turn the page number recording off for these cases as it would lead to errors else. This affects the whole document and can only be set in the preamble! It means you cannot have page numbers in the list of acronyms in this case. Or rather: you can if you use <code>pages = {first}</code>.</p>
	<p><code>only-used = true false</code> <span style="float: right;">Default: true</span></p> <p>This option is <code>true</code> as default. It means that only acronyms that are actually used in the document are printed in the list. If <code>false</code>, all acronyms defined with <code>\DeclareAcronym</code> will be written to the list.</p>
Introduced in version 1.2	<p><code>mark-as-used = first any</code> <span style="float: right;">Default: any</span></p> <p>This option determines whether an acronym is mark as used when the <i>first</i> form is used the first time (with <code>\ac</code>, <code>\acf</code> or <code>\acflike</code> and their uppercase, plural and indefinite forms) or when any of the <code>\ac</code>-like commands is used.</p>
	<p><code>macros = true false</code> <span style="float: right;">Default: false</span></p> <p>If set to <code>true</code> this option will create a macro <code>\⟨id⟩</code> for each acronym as a shortcut for <code>\ac{⟨id⟩}</code>. Already existing macros will <i>not</i> be overwritten.</p>
Introduced in version 0.6	<p><code>xspace = true false</code> <span style="float: right;">Default: false</span></p> <p>If set to <code>true</code> this option will append <code>\xspace</code> from the <code>xspace</code> package to the commands created with the <code>macros</code> option.</p>

## 5. Options and Customization

`strict = true|false` Default: false  
 If set to true and the option `macros = {true}` is in effect then already existing macros will be overwritten.

`sort = true|false` Default: true  
 If set to true the acronym list will be sorted automatically. The entries are sorted by their ID ignoring upper and lower case. This option needs the experimental package `l3sort` (from the `l3experimental` bundle) and can only be set in the preamble.

`cite = all|first|none` Default: first  
 This option decides whether citations that are added via `cite` are added to each first, every or no appearance of an acronym.

`cite-cmd = {⟨control sequence⟩}` Default: `\cite`  
 This option determines which command is used for the citation. Each citation command that takes the `cite` key as argument is valid, for example `biblatex`'s `\footcite`.

`cite-connect = {⟨code⟩}` Default: `\nobreakspace`  
 Depending on the citation command in use a space should be inserted before the citation or maybe not (e.g. `\footcite...`). This option allows you to set this. Actually it can be used to place arbitrary code right before the citation.

Introduced in version 2.0 Default: false  
`group-citation = true|false`  
 If set to true the short form (or the long form) and the citation of an acronym will be printed together in parentheses when an acronym is used the first time.

Introduced in version 2.0 Default: `\cite`  
`group-cite-cmd = {⟨control sequence⟩}`  
 This option determines which command is used for the citation when an acronym is used the first time and `group-citation = {true}`. Each citation command that takes the `cite` key as argument is valid, for example `biblatex`'s `\footcite`.

Introduced in version 1.1 Default: false  
`index = true|false`  
 If set to true an index entry will be recorded every time an *unstarred* acronym command is used for the corresponding acronym.

Introduced in version 1.1 Default: `\index`  
`index-cmd = {⟨control sequence⟩}`  
 Chooses the index command that is used when option `index` has been set to true.

Introduced in version 1.0 Default: false  
`accsupp = true|false`  
 Activates the access support as provided by the `accsupp` package.

Introduced in version 2.1 Default: false  
`tooltip = true|false`  
 Activates tooltip support for `ACRO` using the `pdfcomment` package.

Introduced in version 2.1 Default: `\@firstoftwo`  
`tooltip-cmd = {⟨control sequence⟩}`  
 A macro taking two mandatory arguments, the first being the short form of the acronym and the second being some tooltip description.

`uc-cmd` = { $\langle$ control sequence $\rangle$ }

Default: `\acffirstupper`

The command that is used to capitalize the first word in the `\Ac` and the like commands. You can change it to another one like for example `\makefirstuc`<sup>8</sup> or `\MakeTextUppercase`.<sup>9</sup>

All options of this and the following sections can be set up either as package options or via the setup command:

`\acsetup{ $\langle$ options $\rangle$ }`

Set up **ACRO** anywhere in the document. Or separate package loading from setup.

```
1 % with \acsetup{macros}
2 we could have used these before: \nato, \ny
```

---

we could have used these before: NATO, NY

## 5.2. Options Regarding Acronyms

The options described in this section all influence the layout of one of the possible output forms of the acronyms.

`short-format` = { $\langle$ format $\rangle$ }

(initially empty)

Sets a format for all short forms. For example `short-format = {\scshape}` would print all short forms in small caps.

`long-format` = { $\langle$ format $\rangle$ }

(initially empty)

The same for the long forms.

`foreign-format` = { $\langle$ format $\rangle$ }

(initially empty)

The format for the **foreign** entry when it appears as part of the first appearance of an acronym.

Introduced in  
version 1.3

`single-format` = { $\langle$ format $\rangle$ }

(initially empty)

The format for the acronym when it is used only once. If not specified the formatting according to `single-form` is used.

Introduced in  
version 2.3

`first-long-format` = { $\langle$ format $\rangle$ }

(initially empty)

The format for the long form on first usage (with `\ac`, `\acf` or `\acflike` and their uppercase, plural and indefinite forms).

Introduced in  
version 1.2

`list-short-format` = { $\langle$ format $\rangle$ }

(initially empty)

An extra format for the short entries in the list. If not used this is the same as `short-format`. Please be aware that a call of `short-format` after this one will overwrite it again.

Introduced in  
version 1.1

---

8. from the `mfirstuc` package

9. from the `textcase` package

Introduced in  
version 2.1

`list-short-width = {\langle dim \rangle}` Default: 3em

This option controls the width reserved for the short forms of the acronyms in the `lof` list style.

`list-long-format = {\langle format \rangle}` (initially empty)

An extra format for the long entries in the list. If not used this is the same as `long-format`.

Please be aware that a call of `long-format` after this one will overwrite it again.

`list-foreign-format = {\langle format \rangle}` Default: `\acroenparen`

The format for the `foreign` entry as it appears in the list. This may be code that ends with a macro that takes a mandatory argument.

`extra-format = {\langle format \rangle}` (initially empty)

The same for the extra information.

Changed in  
version 1.1

`first-style = default | plain | empty | square | short | reversed | plain-reversed | footnote | sidenote` Default: `default`

The basic style of the first appearance of an acronym. The value `sidenote` needs the command `\sidenote` to be defined for example by the `sidenotes` package.

`extra-style = default | plain | comma | paren | bracket` Default: `default`

Defines the way the extra information is printed in the list.

`plural-ending = {\langle tokenlist \rangle}` Default: `s`

With this option the default plural ending can be set.

```

1 % (Keep in mind that we're in
2 % a minipage here!)
3 \acsetup{first-style=empty}
4 \acf{ny} \\\
5 \acsetup{first-style=footnote}
6 \acf{ny} \\\
7 \acsetup{first-style=square}
8 \acf{ny} \\\
9 \acsetup{first-style=short}
10 \acf{ny} \\\
11 \acsetup{first-style=reversed}
12 \acf{ny} \\\
13 \acsetup{first-style=plain}
14 \acf{ny} \\\
15 \acsetup{first-style=plain-reversed}
16 \acf{ny}

```

### 5.3. Options Regarding the List

`page-ref = none | plain | comma | paren` Default: `none`

If this option is set to a value other than `none` the page numbers of the an acronym appeared on

## 5. Options and Customization

are printed in the list. Please note that this is an experimental feature and might fail in quite a number of cases. If you notice anything please send me an email!

`pages = all|first` Default: all

Introduced in  
version 1.5

If the option `page-ref` has any value other than none this option determines whether all usages of the acronyms are listed or only the first time. Implicitly sets `label = {true}`.

`page-name = {\langle page name \rangle}` Default: p.\@,

The “name” of the page label. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`pages-name = {\langle page name plural \rangle}` Default: pp.\@,

Introduced in  
version 1.0

The “name” of the page label when there are more than one page. This is automatically translated to the active language. However for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`following-page = true|false` Default: false

Introduced in  
version 1.3

If set to true a page range in the list of acronyms that consists of two pages will be written by the first page and an appended f. This depends on the option `next-page`.

`following-pages = true|false` Default: false

Introduced in  
version 1.3

If set to true a page range in the list of acronyms that set consists of more than two pages will be written by the first page and an appended ff. This depends on the option `next-pages`.

`next-page = {\langle text \rangle}` Default: \, f.\@

Introduced in  
version 1.0

Appended to a page number when `following-page` is set to true and the range is only 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`next-pages = {\langle text \rangle}` Default: \, ff.\@

Introduced in  
version 1.0

Appended to a page number when `following-pages` is set to true and the range is more than 2 pages long. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`list-style = description | lof | longtable | extra-longtable | extra-longtable-rev | extra-tabular|extra-tabular-rev|tabular|toc` Default: description

Changed in  
version 2.2

Choose with which style the list of acronyms should be typeset. If you choose `\longtable`, `extra-longtable` or `extra-longtable-rev` you have to load the `longtable` [Car14] package in your preamble. The values `extra-⟨something⟩` put the extra information in a column of its own. *Be aware that per default all extra-table styles only use 1 columns. Since acronym descriptions can easily get longer that a line you should probably define your own style if you want to use them.* See section 13 on page 32 for details.

`list-heading = chapter | chapter* | section | section* | subsection | subsection* | subsubsection|subsubsection*|addchap|addsec|none` Default: section\*

Changed in  
version 2.0

The heading type of the list. The last two only work with a KOMA-Script class that also defines the appropriate command. A special value is none which suppresses the heading.

`list-name = {⟨list name⟩}`

Default: Acronyms

The name of the list. This is what's written in the list-heading. This is automatically translated to the active language. However, for the time being there are many translations missing, yet. Please notify me if you find your language missing.

`list-caps = true|false`

Default: false

Print the first letters of the long form capitalized.

## 6. Trailing Tokens and Special Action

Introduced in  
version 2.0

**ACRO** has the possibility to look ahead for certain tokens and switch a boolean if it finds them. Per default **ACRO** knows about three tokens: the “dot” (`.`), the “dash” (`-`) and the “babel-hyphen” (`\babelhyphen`).

A token is made known to **ACRO** with the following macro:

`\AcroRegisterTrailing⟨token⟩{⟨name⟩}`

This registers the token `⟨token⟩` so **ACRO** looks if it follows directly after an acronym macro. `⟨name⟩` is the internal name for this token.

The **ACRO** package already registers the above mentioned tokens:

```
1 \AcroRegisterTrailing . {dot}
2 \AcroRegisterTrailing - {dash}
3 \AcroRegisterTrailing \babelhyphen {babel-hyphen}
```

If a token is registered it doesn't mean that **ACRO** looks for it. The token must first be activated for this:

`activate-trailing-tokens = {⟨csv list of token names⟩}`

Tell **ACRO** to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens. Per default only dot is activated.

`deactivate-trailing-tokens = {⟨csv list of token names⟩}`

Tell **ACRO** not to look for trailing tokens. This is done by giving a csv list of the internal *names* of the tokens.

All of the above on its own does nothing visible. However: inside of an acronym, *i. e.*, for example inside the long or the short form it can be tested for those trailing tokens:

`\aciftrailing{⟨csv list of token names⟩}{⟨true⟩}{⟨false⟩}`

Check if one of the tokens listed in `⟨csv list of token names⟩` is following and either place `⟨true⟩` or `⟨false⟩` in the input stream.

**ACRO** uses this to define to further macros:

**\acdot**

Inserts a . if no dot follows.

**\acspace**

Inserts a \space if no dash or babel-hyphen follows.

The definitions are equivalent<sup>10</sup> to the following code:

```
1 \newcommand*\acdot{\aciftrailing{dot}}{\@.}
2 \newcommand*\acspace{\aciftrailing{dash,babel-hyphen}}{\space}
```

This could be used to define an acronym as follows:

```
1 \DeclareAcronym{etc}{
2   short = {\textit{etc}\acdot} ,
3   long  = {\textit{et cetera}} ,
4   short-plural = , long-plural =
5 }
```

If now you somewhere use

```
1 \ac{etc}.
```

there won't be two dots printed.

The command **\acspace** is used already in the definition of the first appearance of a macro. Let's say you're a German chemist and you have

```
1 \DeclareAcronym{PU}{
2   long = Polyurethan ,
3   long-plural = e
4 }
```

and you use it the first time like this:

---

10. Not *quite*: **ACRO**'s definitions are engine protected.



```
\ac{PU}-Hartschaum
```

then according to German orthography and typesetting rules this should be printed as

“Polyurethan(PU)-Hartschaum”

*i. e.*, with *no* space between long and short form. This is exactly what happens if you say

```
\acsetup{activate-trailing-tokens = {dash,babel-hyphen}}
```

in the preamble.

## 7. About Page Ranges

If you enable the `page-ref` option **ACRO** adds page numbers to the list of acronyms. In version 0.\* it would add a page reference for an acronym in the list of acronyms that used `\pageref` to refer to the first appearance of an acronym. This is retained using `pages = {first}`. Version 1.0 uses a different approach that doesn't use a label but instead will list *all* pages an acronym appeared on. With `hyperref` the pages are referenced using `\hyperpage`.

There are some options that control how this list will be typeset, e.g., `following-page`, `next-pages` or the option `page-ref` itself. It is important to mention that the page list will always take at least two compilation runs until changes in the options or the actual page numbers affect it. This is due to the fact that the updated sequence is first written to the aux file and only read in during the next run.

## 8. Dividing Your Document Into Pieces – Creating Local Lists

Introduced in  
version 2.4

**ACRO** introduces the concept of *barriers* which can divide the document into parts. It is possible to create lists of only those acronyms used between two such barriers.

`\acbarrier`

Sets a barrier at the point of use in the document. The begin and the end of the document mark implicit barriers.

`local-to-barriers = true|false`

Default: `false`

This option can be used as option to the `\printacronyms` command to create a list of only the acronyms of the current “barrier group”.

```

1 \acbarrier
2 \printacronyms[local-to-barriers]
3 \ac{ctan} and \ac{lppl}
4 \acbarrier

```

---

## Acronyms

**CTAN** Comprehensive T<sub>E</sub>X Archive Network

**LPPL** L<sup>A</sup>T<sub>E</sub>X Project Public License

CTAN and LPPL

`reset-at-barriers = true|false`

Default: false

If this option is set to true `\acbarrier` implicitly calls `\acresetall`.

## 9. Language Support

**ACRO** detects if packages babel [Bra16] or polyglossia [Bra16] are being loaded and tries to adapt certain strings to match the chosen language. However, due to my limited language knowledge only a few translations are provided. I'll show how the English translations are defined so you can add the translations to your preamble if needed. Even better would be you'd send me a short email to [contact@mychemistry.eu](mailto:contact@mychemistry.eu) with the appropriate translations for your language and I'll add them to **ACRO**.

```

1 \DeclareTranslation{English}{acronym-list-name}{Acronyms}
2 \DeclareTranslation{English}{acronym-page-name}{p.}
3 \DeclareTranslation{English}{acronym-pages-name}{pp.}
4 \DeclareTranslation{English}{acronym-next-page}{f.}
5 \DeclareTranslation{English}{acronym-next-pages}{ff.}

```

## 10. hyperref Support

The option `hyperref = {true}` adds internal links from all short (or alternative) forms to their respective list entries. Of course this only works if you have loaded the hyperref package in your preamble. You should use this option with care: if you don't use `\printacronyms` anywhere this option will result in loads of hyperref warnings. Also printing several lists can result in

warnings if don't clearly separate the lists into different classes. If an acronym appears in more than one list there will also be more than one hypertarget for this acronym.

Using `hyperref` will also add `\hyperpage` to the page numbers in the list (provided they are displayed in the style chosen). Like with an index the references will thus not point to the acronyms directly but to the page they're on.

## 11. Defining Own Acronym Macros

Introduced in  
version 2.0

The commands explained in section 2.2 on page 6 have all been defined with a dedicated command – there is a family of dedicated commands, actually:

`\NewAcroCommand{<cs>}{<code>}`

Defines a new **ACRO** acronym command `<cs>`. This sets up the necessary framework needed by acronym commands and defines `<cs>` with an optional star argument and a mandatory argument for the acronym id using `xparse`'s `\NewDocumentCommand`. Inside `<code>` one can refer to the ID `<id>` with `#1`.

`\RenewAcroCommand{<cs>}{<code>}`

Defines a new **ACRO** acronym command `<cs>`. This sets up the necessary framework needed by acronym commands and defines `<cs>` with an optional star argument and a mandatory argument for the acronym id using `xparse`'s `\RenewDocumentCommand`. Inside `<code>` one can refer to the ID `<id>` with `#1`.

`\DeclareAcroCommand{<cs>}{<code>}`

Defines a new **ACRO** acronym command `<cs>`. This sets up the necessary framework needed by acronym commands and defines `<cs>` with an optional star argument and a mandatory argument for the acronym id using `xparse`'s `\DeclareDocumentCommand`. Inside `<code>` one can refer to the ID `<id>` with `#1`.

`\ProvideAcroCommand{<cs>}{<code>}`

Defines a new **ACRO** acronym command `<cs>`. This sets up the necessary framework needed by acronym commands and defines `<cs>` with an optional star argument and a mandatory argument for the acronym id using `xparse`'s `\ProvideDocumentCommand`. Inside `<code>` one can refer to the ID `<id>` with `#1`.

Inside these macros one can use a number of low-level `expl3` commands.<sup>11</sup>

### Acronym fetching commands

`\acro_use:n {<id>}`

Fetches the acronym using either the first or the short form depending on earlier uses.

`\acro_short:n {<id>}`

Fetches the short form of the acronym.

<sup>11</sup>. Which is why you need to use them inside an `expl3` programming environment. This means in the preamble surround the definitions with `\ExplSyntaxOn` and `\ExplSyntaxOff`.

`\acro_long:n {⟨id⟩}`

Fetches the long form of the acronym.

`\acro_alt:n {⟨id⟩}`

Fetches the alternative short form of the acronym.

`\acro_foreign:n {⟨id⟩}`

Fetches the foreign property of the acronym if available.

`\acro_extra:n {⟨id⟩}`

Fetches the extra property of the acronym if available.

### Acronym setup commands

`\acro_first_upper:`

**ACRO** setup command which tells the macros above that we want to uppercase the first letter of the long version. Should be used *before* one of the acronym fetching commands.

`\acro_plural:`

**ACRO** setup command which tells the macros above that we want to use plural forms. Should be used *before* one of the acronym fetching commands.

`\acro_indefinite:`

**ACRO** setup command which tells the macros above that we want to add the indefinite article. Should be used *before* one of the acronym fetching commands.

`\acro_cite:`

**ACRO** setup command which tells the macros above that we want to add the citation in any case independent of the option **cite**. Should be used *before* one of the acronym fetching commands.

`\acro_no_cite:`

**ACRO** setup command which tells the macros above that we want to have no citation independent of the option **cite**. Should be used *before* one of the acronym fetching commands.

`\acro_index:`

**ACRO** setup command which tells the macros above that we want to add an index entry in any case independent of the option **index**. Should be used *before* one of the acronym fetching commands.

`\acro_reset_specials:`

This macro is called implicitly by `\NewAcroCommand` and `\NewPseudoAcroCommand`. If you plan to define an **ACRO** command by yourself using `\NewDocumentCommand` this should be the first macro after `\acro_begin:`. It ensures that in nested acronyms the inner acronyms don't inherit indefinite articles, uppercasing, endings...

Introduced in  
version 2.0b

**Additional macros for further uses****\acro\_begin:**

When an acronym macro is defined “by hand”, *i. e.*, *not using* `\NewAcroCommand` then this must be the first macro in the code. *Must have a matching* `\acro_end:`.

**\acro\_end:**

When an acronym macro is defined “by hand”, *i. e.*, *not using* `\NewAcroCommand` then this must be the last macro in the code. *Must have a matching* `\acro_begin:`.

**\acro\_check\_and\_mark\_if:nn** {<boolean expression>} {<id>}

Checks if the acronym with the ID <id> exists and marks it as used when <boolean> expression evaluates to true. This macro is used inside `\NewAcroCommand` and friends implicitly.

**\acro\_check\_acronym:nn** {<id>} {true|false}

Checks if the acronym with the ID <id> exists and marks it as used if true or doesn't. This macro is used inside `\acro_check_and_mark_if:nn`.

**\acro\_use\_acronym:n** {true|false}

Tell `\acro_use:n` and similar commands whether to mark the acronym as used or not. This macro is used inside `\acro_check_acronym:nn`. If this macro is used explicitly it should be used before `\acro_use:n` (or a similar command) otherwise it has no effect. An acronym marked as used cannot be unmarked.

**\acro\_mark\_as\_used:n** {<id>}

Explicitly use the acronym with the ID <id>. This is the `expl3` macro applied to all entries in `\acuse`.

**\*\acro\_if\_acronym\_used:nTF** {<id>} {<true>} {<false>}

The code-level version of `\acifused`. This macro is expandable.

**\acro\_for\_all\_acronyms\_do:n** {<code>}

Loops over all acronyms known when the macro is used. Inside of <code> you can refer to the ID <id> of an acronym with #1.

**\acro\_barrier:**

The code-level version of `\acbarrier`.

**Examples** The usage of above macros is best explained with a few examples. The following definition is done by `ACRO`:

```
1 \NewAcroCommand \ac { \acro_use:n {#1} }
```

An equivalent definition for `\ac` would be

## 11. Defining Own Acronym Macros

```
1 \NewDocumentCommand \ac {sm}
2 {
3   \acro_begin:
4   \acro_reset_specials:
5   \acro_check_and_mark_if:nn {#1} {#2}
6   \acro_use:n {#2}
7   \acro_end:
8 }
```

which should explain what the actual framework is which `\NewAcroCommand` adds.

Other definitions by `ACRO` are for example the following ones:

```
1 \NewAcroCommand \Ac
2 {
3   \acro_first_upper:
4   \acro_use:n {#1}
5 }
6 \NewAcroCommand \iac
7 {
8   \acro_indefinite:
9   \acro_use:n {#1}
10 }
11 \NewAcroCommand \acp
12 {
13   \acro_plural:
14   \acro_use:n {#1}
15 }
16 \NewAcroCommand \Acp
17 {
18   \acro_plural:
19   \acro_first_upper:
20   \acro_use:n {#1}
21 }
22 \NewAcroCommand \Aclp
23 {
24   \acro_plural:
25   \acro_first_upper:
26   \acro_long:n {#1}
27 }
```

## 12. About Plural Forms, Possessive Forms and Similar Constructs – the Concept of Endings

**ACRO** has a concept of *endings*. All of **ACRO**'s plural options are defined by saying

```
1 \ProvideAcroEnding {plural} {s} {s}
```

The command's syntax and what it does is as follows:

`\ProvideAcroEnding{<name>}{<short default>}{<long default>}`

This macro defines the options

- <name>-ending,
- short-<name>-ending,
- alt-<name>-ending and
- long-<name>-ending.

It also defines the acronym properties

- short-<name>,
- short-<name>-form,
- alt-<name>,
- alt-<name>-form,
- long-<name> and
- long-<name>-form.

Additionally it defines a setup macro as described in section 11 on page 27, `\acro-<name>:`. If `<name>` contains a - (dash) it is replaced by `_` before `\acro-<name>:` is built. So if you choose `my-name` the corresponding macro is named `\acro_my_name:`. If you use any other non-letters you are on your own.

Note that you *must use* `\ProvideAcroEnding` before any acronym definition!

This could be used together with the macros described in section 11 on page 27 for adding support for possessive forms:

```
1 \ExplSyntaxOn
2 % this now only works because I've used the same already in the preamble so
3 % it does nothing here:
4 \ProvideAcroEnding {possessive} {'s} {'s}
5
6 \ProvideAcroCommand \acg
```

```

7 {
8   \acro_possessive:
9   \acro_use:n {#1}
10 }
11 \ExplSyntaxOff
12 The \acg{cd} booklet says\ldots

```

---

The CD's booklet says...

Please note that different endings are cumulative which you probably want to avoid! Imagine a macro

```

1 \NewAcroCommand \acgp
2 {
3   \acro_possessive:
4   \acro_plural:
5   \acro_use:n {#1}
6 }

```

This would give “CDs's” instead of “CDs”. To solve this you might want to consider

```

1 \ProvideAcroEnding {possessive-singular} {'s} {'s}
2 \ProvideAcroEnding {possessive-plural} {s'} {s'}

```

## 13. More on List Customization

### 13.1. Own List Style

The different existing list styles are all built from four different templates, `list`, `list-of`, `table` and `extra-table`. Those templates are defined with the help of the `xtemplate` package (from [L3P]). Each of these templates has a few options which are described in table 1 on the next page. New list styles now are defined via the following macro:

`\DeclareAcroListStyle{<name>}{<template>}{<options>}`

Declares a new **ACRO** list style `<name>`. `<name>` will be the value which can be chosen in the option `list-style`. `<template>` is the name of the template to be used by the style. Available styles are listed in table 1. `<options>` are the option settings for the corresponding template.



TABLE 1: Available List Templates and Their Options

Template	Option	Option Type	Default
list	list	tokenlist	description
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
list-of	style	tokenlist	toc
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	
table	table	tokenlist	tabular
	table-spec	tokenlist	lp{.7\linewidth}
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
extra-table	table	tokenlist	tabular
	table-spec	tokenlist	llll
	foreign-sep	tokenlist	\space
	reverse	boolean	false
	before	tokenlist	
	after	tokenlist	

For defining new styles you need some information on what the different templates and options do:

- The option `list` of the `list` template sets the list environment. This must be a classic L<sup>A</sup>T<sub>E</sub>X list where items are listed with `\item`. In those lists short entries will always be fed as optional argument to `\item`:  
`\item[⟨short⟩]⟨long⟩⟨extra⟩⟨page⟩`
- The template `list-of` simulates a table of contents or a list of figures. This can be chosen by setting the option `style` to either `toc` or `lof`.
- The template `table` typesets the list in a table with two columns:  
`⟨short⟩ & ⟨long⟩⟨extra⟩⟨page⟩ \tabularnewline`
- The template `extra-table` typesets the list in a table with four columns:  
`⟨short⟩ & ⟨long⟩ & ⟨extra⟩ & ⟨page⟩ \tabularnewline`
- The option `foreign-sep` is the code inserted between long form and foreign entry (if a foreign entry is present).
- The options `before` and `after` are inserted directly before and after the complete list.
- The option `reverse` switches the place of `⟨long⟩` with `⟨extra⟩`.
- The option `table-spec` sets the column types for the table templates. It must correspond to the number of columns the corresponding template uses.

As an example let's define a style `longtabu` which uses the corresponding table environment from the package `tabu` [Che11]:

```

1 \usepackage{tabu,longtable}
2 \DeclareAcroListStyle{longtabu}{table}{
3   table = longtabu ,
4   table-spec = @{}>{\bfseries}lX@{}
5 }
6 \acsetup{list-style=longtabu}

```

As another example let's define a new list with the help of the `enumitem` package [Bez11]:

```

1 % preamble:
2 % \usepackage{enumitem}
3 \newlist{acronyms}{description}{1}
4 \newcommand*\addcolon[1]{#1:}
5 \setlist[acronyms]{

```

```

6   labelwidth = 3em,
7   leftmargin = 3.5em,
8   noitemsep,
9   itemindent = 0pt,
10  font=\addcolon}
11 \DeclareAcroListStyle{mystyle}{list}{ list = acronyms }
12 \acsetup{ list-style = mystyle }

```

This would look as follows:

## Acronyms

**CD:** Compact Disc  
**CTAN:** Comprehensive T<sub>E</sub>X Archive Network  
**ECU:** Steuergerät (Electronic Control Unit)  
**ID:** identification string  
**JPEG:** Joint Photographic Experts Group  
**LA:** Los Angeles  
**LPPL:** L<sup>A</sup>T<sub>E</sub>X Project Public License  
**MP:** Member of Parliament  
**NATO:** North Atlantic Treaty Organization. *deutsch:* Organisation des Nordatlantikvertrags  
**NY:** New York  
**PDF:** Portable Document Format  
**SW:** Sammelwerk  
**ST:** Some Test  
**UFO:** unidentified flying object

### 13.2. Own List Heading Command

With the option `list-heading` you can choose which command prints the heading of the list. If you need a different choice than what's already provided you can use the following command to define a new option:

`\DeclareAcroListHeading{<name>}{<control sequence>}`

Defines a new value `<name>` for the option `list-heading`. `<control sequence>` must be a control sequence which takes one mandatory argument.

As an example here is how the value section is defined:

```

1 \DeclareAcroListHeading{section}{\section}

```

## 14. Configuration Files

Introduced in  
version 2.2

If you repeatedly have the same setup and definitions for **ACRO** in your preamble you might want to place those in a configuration file. If **ACRO** finds a file named `acro.cfg` present it inputs it at the end of the package. The only thing to be aware of is that this file is input like a package which means that `@` is treated as a letter (category code 11).

### A. All Acronyms Used in this Documentation

<b>CD:</b>	Compact Disc
<b>CTAN:</b>	Comprehensive T <sub>E</sub> X Archive Network
<b>ECU:</b>	Steuergerät (Electronic Control Unit)
<b>ID:</b>	identification string
<b>JPEG:</b>	Joint Photographic Experts Group
<b>LA:</b>	Los Angeles
<b>LPPL:</b>	L <sup>A</sup> T <sub>E</sub> X Project Public License
<b>MP:</b>	Member of Parliament
<b>NATO:</b>	North Atlantic Treaty Organization. <i>deutsch</i> : Organisation des Nordatlantikvertrags
<b>NY:</b>	New York
<b>PDF:</b>	Portable Document Format
<b>SW:</b>	Sammelwerk
<b>ST:</b>	Some Test
<b>UFO:</b>	unidentified flying object

### B. References

- [Bez11] Javier BEZOS. enumitem. version 3.5.2, Sept. 28, 2011.  
URL: <http://mirror.ctan.org/macros/latex/contrib/enumitem/>.
- [Bra16] Johannes BRAAMS, current maintainer: Javier BEZOS.  
babel. version 3.9q, Feb. 24, 2016.  
URL: <http://mirror.ctan.org/macros/latex/required/babel/>.
- [Car14] David CARLISLE. longtable. version 4.11, Oct. 28, 2014.  
URL: <http://mirror.ctan.org/macros/latex/required/tools/>.
- [Cha15] François CHARETTE, current maintainer: Arthur REUTENAUER.  
polyglossia. version 1.42.0, Aug. 6, 2015.  
URL: <http://mirror.ctan.org/macros/latex/contrib/polyglossia/>.
- [Che11] Florent CHERVET. tabu. version 2.8, Feb. 26, 2011.  
URL: <http://mirror.ctan.org/macros/latex/contrib/tabu/>.
- [Kle12] Josef KLEBER. pdfcomment. version 2.3a, Sept. 28, 2012.  
URL: <http://mirror.ctan.org/macros/latex/contrib/pdfcomment/>.
- [L3P] THE L<sup>A</sup>T<sub>E</sub>X<sub>3</sub> PROJECT TEAM. l3packages. version SVN 6377, Jan. 19, 2016.  
URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages/>.

## *B. References*

- [Nie15] Clemens NIEDERBERGER. translations. version 1.2e, Nov. 7, 2015.  
URL: <http://mirror.ctan.org/macros/latex/contrib/translations/>.
- [Tal15] Nicola L.C. TALBOT. mfirstuc. version 2.02, Dec. 17, 2015.  
URL: <http://mirror.ctan.org/macros/latex/contrib/glossaries/>.

## C. Index

### A

`\Ac` ..... 6, 20, 30  
`\ac` ..... 4, 6 f., 10, 13 f., 18, 20, 24 ff., 29 f.  
`\aca` ..... 6 f., 9  
`\acap` ..... 7  
`\acbarrier` ..... 25 f., 29  
`accsupp` ..... 4, 15, 19  
`accsupp` (package) ..... 4, 15, 19  
`\acdot` ..... 24  
`\Acf` ..... 7  
`\acf` ..... 4, 6 f., 18, 20 f.  
`\acfirstupper` ..... 11, 20  
`\acflike` ..... 4, 12, 18, 20  
`\Acfp` ..... 7  
`\acfp` ..... 7  
`\acfplike` ..... 12  
`\acg` ..... 31 f.  
`\aciftrailing` ..... 23 f.  
`\acifused` ..... 13, 29  
`\Acl` ..... 6  
`\acl` ..... 6 f., 13  
`\Aclp` ..... 7, 30  
`\aclp` ..... 7, 9  
`\Acp` ..... 7, 30  
`\acp` ..... 7, 30  
`\acpdfstring` ..... 14  
`\acpdfstringplural` ..... 14  
`\acreset` ..... 13 f.  
`\acresetall` ..... 13, 26  
`\acroenparen` ..... 11, 21  
`\AcroRegisterTrailing` ..... 23  
`\acs` ..... 6 f., 9, 13 f.  
`\acsetup` ..... 12, 16, 20 f., 25, 34 f.  
`\Acsingle` ..... 12  
`\acsingle` ..... 12  
`\acsp` ..... 7, 9, 14  
`\acspace` ..... 24  
`activate-trailing-tokens` ..... 23  
`\acuse` ..... 14, 29  
`\acuseall` ..... 14  
`alt` ..... 3, 6, 9

`alt-indefinite` ..... 3, 11  
`alt-plural` ..... 3  
`alt-plural-form` ..... 3

### B

`babel` (package) ..... 4, 10, 26  
`BEZOS, Javier` ..... 4, 10, 26, 34  
`BRAAMS, Johannes` ..... 4, 10, 26

### C

`CARLISLE, David` ..... 22  
`CHARETTE, François` ..... 4, 10  
`CHERVET, Florent` ..... 34  
`cite` ..... 4 f., 19, 28  
`cite-cmd` ..... 19  
`cite-connect` ..... 19  
`class` ..... 4, 13

### D

`deactivate-trailing-tokens` ..... 23  
`\DeclareAcroCommand` ..... 27  
`\DeclareAcroListHeading` ..... 35  
`\DeclareAcroListStyle` ..... 32, 34 f.  
`\DeclareAcronym` ..... 2, 5 f., 8 ff., 12, 14 f., 18, 24

### E

`enumitem` (package) ..... 34  
`exclude-classes` ..... 16  
`expl3` (package) ..... 2  
`extra` ..... 3, 9  
`extra-format` ..... 21  
`extra-style` ..... 21

### F

`first-long-format` ..... 4, 20  
`first-style` ..... 4, 12, 21  
`following-page` ..... 22, 25  
`following-pages` ..... 22  
`foreign` ..... 3, 10 f., 20 f.  
`foreign-format` ..... 20  
`foreign-lang` ..... 4, 10  
`format` ..... 5

- G**
- `group-citation` ..... 19
  - `group-cite-cmd` ..... 19
- H**
- `heading` ..... 16
  - `hyperref` ..... 18, 26
  - `hyperref` (package) ..... 4, 14, 25 ff.
- I**
- `\Iac` ..... 11
  - `\iac` ..... 30
  - `\iacI` ..... 11
  - `\iacs` ..... 11
  - `include-classes` ..... 16
  - `index` ..... 4 f., 15 f., 19, 28
  - `index-cmd` ..... 5, 19
  - `index-sort` ..... 4, 16
- K**
- KLEBER, Josef ..... 15
- L**
- `l3experimental` (package) ..... 19
  - `l3keys2e` (package) ..... 2
  - `l3packages` (bundle) ..... 32
  - `l3sort` (package) ..... 19
  - `label` ..... 18, 22
  - `label-prefix` ..... 18
  - `list` ..... 3
  - `list-caps` ..... 23
  - `list-foreign-format` ..... 21
  - `list-heading` ..... 22, 35
  - `list-long-format` ..... 21
  - `list-name` ..... 23
  - `list-short-format` ..... 20
  - `list-short-width` ..... 21
  - `list-style` ..... 22, 32
  - `local-to-barriers` ..... 16, 25
  - `long` ..... 2, 11, 15
  - `long-format` ..... 4, 20 f.
  - `long-indefinite` ..... 3, 11
  - `long-plural` ..... 3, 8
  - `long-plural-form` ..... 3, 8
  - `long-post` ..... 3
  - `long-pre` ..... 3
  - `longtable` (package) ..... 22
  - LPPL ..... 2
- M**
- `macros` ..... 18 f.
  - `\makefirstuc` ..... 11
  - `mark-as-used` ..... 18
  - `messages` ..... 18
  - `mfirstuc` (package) ..... 11, 20
- N**
- `name` ..... 16
  - `\NewAcroCommand` ..... 27–30, 32
  - `\NewPseudoAcroCommand` ..... 28
  - `next-page` ..... 22
  - `next-pages` ..... 22, 25
  - NIEDERBERGER, Clemens ..... 2
- O**
- `only-used` ..... 18
- P**
- `page-name` ..... 22
  - `page-ref` ..... 21 f., 25
  - `pages` ..... 18, 22, 25
  - `pages-name` ..... 22
  - `pdfcomment` (package) ..... 15, 19
  - `pdfstring` ..... 4, 14
  - `plural-ending` ..... 21
  - `polyglossia` (package) ..... 4, 10, 26
  - `\printacronyms` ..... 1, 16 f., 25 f.
  - `\ProvideAcroCommand` ..... 27, 31
  - `\ProvideAcroEnding` ..... 31 f.
- R**
- `record-pages` ..... 18
  - `\RenewAcroCommand` ..... 27
  - `reset-at-barriers` ..... 26
  - REUTENAUER, Arthur ..... 4, 10
- S**
- `short` ..... 2, 5
  - `short-format` ..... 4, 20
  - `short-indefinite` ..... 3, 11

## Index

<code>short-plural</code> .....	3, 8	<code>tooltip-cmd</code> .....	4, 15, 19
<code>short-plural-form</code> .....	3	translations (package) .....	2
<code>single</code> .....	1, 4, 12, 18	<b>U</b>	
<code>single-form</code> .....	18, 20	<code>uc-cmd</code> .....	20
<code>single-format</code> .....	4, 20	<b>X</b>	
<code>sort</code> .....	1, 4 f., 16, 19	xparse (package) .....	2, 27
<code>strict</code> .....	19	<code>xspace</code> .....	18
<b>T</b>		xtemplate (package) .....	2, 32
tabu (package) .....	34	<b>Z</b>	
TALBOT, Nicola L.C. ....	11	zref-abspage (package) .....	2
THE L <sup>A</sup> T <sub>E</sub> X <sub>3</sub> PROJECT TEAM .....	32		
<code>tooltip</code> .....	4, 15, 19		