

ACRO

v3.0alpha-1 2020/04/07

Typeset Acronyms and other Abbreviations

Clemens NIEDERBERGER

<https://github.com/cgnieder/acro/>

contact@mychemistry.eu

ACRO allows you to define and manage acronyms and abbreviations. It can also be used for glossaries or nomenclatures.

Table of Contents

I. Get started with ACRO	1	III. Appendix	3
1. Licence and requirements	1	A. Acronyms	3
2. ACRO for the impatient	2	B. Index	4
II. Comprehensive details	3		

!

Hi and thanks that you are testing v3.0 of **ACRO** before it is released to CTAN. If you want to test the new version use `\usepackage[version=3]{acro}`. With version=2 or no option at all you get the old version of acro. Using `\usepackage[version=3,deprecation]{acro}` is supposed to give as much meaningful warnings and errors as possible.

Part I.

Get started with **ACRO**

1. Licence and requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>).

The software has the status “maintained.”

2. **ACRO** for the impatient

Acronyms are defined in the preamble via the command

`\DeclareAcronym{⟨id⟩}{⟨properties⟩}`

where `⟨id⟩` is a unique string to identify the acronym and `⟨properties⟩` is a key/value list of properties.

In the document acronyms are used with these commands:

`\ac{⟨id⟩}`

Prints the acronym `⟨id⟩`, the first time with full description and every subsequent use only the abbreviated form.

`\Ac{⟨id⟩}`

Does the same as `\ac` but uppercases the first letter – this may be needed at the beginning of a sentence.

`\acs{⟨id⟩}`

Prints the short form of the acronym `⟨id⟩`.

`\Acs{⟨id⟩}`

Does the same as `\acs` but uppercases the first letter.

`\acl{⟨id⟩}`

Prints the long form of the acronym `⟨id⟩`.

`\Acl{⟨id⟩}`

Does the same as `\acl` but uppercases the first letter.

`\acf{⟨id⟩}`

Prints the full form of the acronym `⟨id⟩`.

`\Acf{⟨id⟩}`

Does the same as `\acf` but uppercases the first letter.

Let’s say you defined CD as follows:

```
1 \DeclareAcronym{cd}{  
2   short = CD ,  
3   long  = compact disc  
4 }
```

Then the usage is

1	<code>\begin{tabular}{ll}</code>		
2	first & <code>\ac{cd}</code> \\\	first	compact disc (CD)
3	second & <code>\ac{cd}</code> \\\	second	CD
4	long & <code>\acl{cd}</code> \\\	long	compact disc
5	short & <code>\acs{cd}</code> \\\	short	CD
6	full & <code>\acf{cd}</code> \\\	full	compact disc (CD)
7	<code>\end{tabular}</code>		

Part II.

Comprehensive details

Part III.

Appendix

A. Acronyms

Below all abbreviations are listed which have been defined for the manual.

CD	compact disc	2
CTAN	Comprehensive T _E X Archive Network	1
ECU	Electronic Control Unit (<i>German</i> : Steuergerät)	
ID	identification string	
JPEG/JPG	Joint Photographic Experts Group	
LA	Los Angeles	
LPPL	L ^A T _E X Project Public License	
MP	Member of Parliament	
NATO	North Atlantic Treaty Organization (<i>German</i> : Organisation des Nordatlantikvertrags)	
NY	New York	
PDF	Portable Document Format	
T_EX.sx	T _E X StackExchange	
UFO	unidentified flying object	

B. Index

A	C
\Ac 2	CD 3
\ac 2 f.	CTAN 1
\Acf 2	D
\acf 2 f.	\DeclareAcronym 2
\Acl 2	L
\acl 2 f.	LPPL 1
\Acs 2	
\acs 2 f.	