

# guitarchordschemes


vo.3a 2013/05/01

Guitar Chord and Scale Tablatures with TikZ

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/guitarchordschemes/>  
[contact@mychemistry.eu](mailto:contact@mychemistry.eu)

English documentation



<b>Contents</b>	<b>3 Options</b>	<b>6</b>
<b>1 License and Requirements</b>	<b>4 Using realbookchords</b>	<b>8</b>
<b>2 The Commands</b>	<b>2 References</b>	<b>9</b>
2.1 Options for <code>\chordscheme</code> . . .		
2.2 Options for <code>\scales</code> . . . . .	<b>4 Index</b>	<b>10</b>

## 1 License and Requirements

**GUITARCHORDSCHEMES** is placed under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). It has the status “maintained”.

**GUITARCHORDSCHEMES** loads the packages TikZ [TWF10], etoolbox [Leh11] and pgfplots [Wri11]. It also loads the TikZ libraries shapes.misc, arrows and calc. Depending on an option it

also loads `realbookchords` [Nie13]. This package is not yet published on CTAN<sup>1</sup> and thus not part of any T<sub>E</sub>X distribution. Until it is you can find it at <https://bitbucket.org/cgnieder/realbookchords/>. See section 4 for details on this option.

## 2 The Commands

This package more or less provides a single command:

► `\chordscheme[<options>]`

► `\scales[<option>]`

These commands set the frame for the chord and scale tablatures and can be used to create sheets for manually writing down tablatures:

```
1 \chordscheme
```

E				
B				
G				
D				
A				
E				

Similarly `\scales` creates a frame with two more frets:

```
1 \scales
```

E						
B						
G						
D						
A						
E						

### 2.1 Options for `\chordscheme`

The [options] argument is where the actual details for a chord happen. These are the available ones for `\chordscheme`:

► `name = <chordsymbol>`

Set the chord symbol. This option accepts a list of entries.

<sup>1</sup> the COMPREHENSIVE T<sub>E</sub>X ARCHIVE NETWORK

- ▶ **position** = <position>  
Set the position for the first of the four frets.
- ▶ **finger** = <fret>/<string>:<label>  
Specify the finger positions for a chord. This option accepts a list of entries. The :<label> is optional.
- ▶ **root** = <fret>/<string>:<label>  
The same as finger but uses a square instead of a circle to indicate that this finger is playing the root of the chord. This option accepts a list of entries. The :<label> is optional.
- ▶ **show-root** = <fret>/<string>  
Specify positions of the root that are *not* part of the actual chord but are somewhere in the vicinity of it on the guitar neck. This option accepts a list of entries.
- ▶ **barre** = <fret>/<string range>:<label>  
Specify a barré position for a chord. The <string range> part must contain a two string numbers separated with a dash. This option accepts a list of entries. The :<label> is optional.
- ▶ **ring** = <string>  
Specify open strings. This option accepts a list of entries.
- ▶ **mute** = <string>  
Specify muted/unplayed strings. This option accepts a list of entries.

Let's take a look at a few examples:

```

1 \chordscheme[
2   name      = G ,
3   position  = I ,
4   finger    = {2/5:1} ,
5   root      = {3/6:2, 3/1:4} ,
6   ring      = {2,3,4}
7 ]


```

Or a more “jazzy” chord:

```

1 \chordscheme[
2   name      = G\textsuperscript{6} ,
3   position  = II ,
4   finger    = {1/4:1, 3/3:4, 2/2:3} ,
5   root      = 2/6:2 ,
6   show-root = 4/4 ,
7   mute      = {1,5}
8 ]

```




One with a barré:

```

1 \chordscheme[
2   name      = Gmi\textsuperscript{7} ,
3   position  = II ,
4   barre     = 2/2-4:3 ,
5   show-root = 4/4 ,
6   root      = 2/6:2 ,
7   mute      = {1,5}
8 ]

```



## 2.2 Options for \scales

The [options] argument for \scales are similar to the ones for \chordscheme:

- **name** = <title>  
Set a title for the scale.
- **position** = <position>  
Set the position for the first of the six frets.
- **finger** = <fret>/<string>:<label>  
Specify the finger positions for the scale. This option accepts a list of entries. The :<label> is optional.
- **root** = <fret>/<string>:<label>  
The same as finger but uses a square instead of a circle to indicate that this finger is playing the root of the scale. This option accepts a list of entries. The :<label> is optional.
- **fingering** = type 1|type 1A|type 2|type 3|type 4  
Set a whole predefined fingering. The types correspond to ones taught in Leavitt's *A Modern Method for Guitar* [Lea66]. This option assumes a ionic scale and places the roots correspondingly.

- **fingering\*** = type 1|type 1A|type 2|type 3|type 4  
The same as **fingering** but not scale is assumed and no roots are indicated.
- **fingering?** = type 1|type 1A|type 2|type 3|type 4  
The same as **fingering\*** but also no labels for the fingers are given.

Let's see an example:

```

1 \scales[
2   name      = F-major (Fingering Type~1A) ,
3   position  = I ,
4   fingering = type 1A
5 ]

```

F-major (Fingering Type 1A)

E	1s		2		4	
B			2		4	
G		1	2		4	
D		1	2		4	
A	1s		2		4	
E	1s		2		4	

An example for **fingering\***:

```

1 \scales[
2   name      = Fingering Type~3 ,
3   fingering* = type 3
4 ]

```

Fingering Type 3

E		1	2		4	
B		1	2		4	
G		1		3		
D		1		3	4	
A		1		3	4	
E		1	2		4	

Now an example for **fingering?**:


### 3 Options

```

1 \scales[
2   name      = Fingering Type~2 ,
3   fingering? = type 2
4 ]

```

Fingering Type 2




At last an example for an explicitly set scale:

```

1 \scales[
2   finger = {
3     2/1:1,          5/1:4,
4     2/2:1,          5/2:4,
5     2/3:1,          4/3:3, 5/3:4,
6     2/4:1,          4/4:3,
7     2/5:1, 3/5:2, 4/5:3,
8     2/6:1,          5/6:4
9   }
10 ]

```



### 3 Options

There are quite a number of options determining the layout of the tablatures. They can either be set as package options or via the setup command:

► `\setchordscheme{<options>}`

### 3 Options


Below every option and its corresponding default setting is described.

- ▶ `x-unit = <dim>` Default: .8cm  
The basic  $x$  unit for the TikZ picture the chord scheme is set in.
- ▶ `y-unit = <dim>` Default: .8cm  
The basic  $y$  unit for the TikZ picture the chord scheme is set in.
- ▶ `finger-format = <TeX code>` Default: `\sffamily\small`  
The format the numbers for the fingers are typeset with.
- ▶ `finger-format+ = <TeX code>` (initially empty)  
Code to be appended to `finger-format`.
- ▶ `position-format = <TeX code>` Default: `\sffamily`  
The format the number for the position is typeset with.
- ▶ `position-format+ = <TeX code>` (initially empty)  
Code to be appended to `position-format`.
- ▶ `name-format = <TeX code>` Default: `\large`  
The format the chord name/symbol is typeset with.
- ▶ `name-format+ = <TeX code>` (initially empty)  
Code to be appended to `name-format`.
- ▶ `string-name-format = <TeX code>` Default: `\sffamily\small`  
The format the names of the strings are typeset with.
- ▶ `string-name-format+ = <TeX code>` (initially empty)  
Code to be appended to `string-name-format`.
- ▶ `line-width = <dim>` Default: 1pt  
The line width used for all lines drawn in the chord scheme.
- ▶ `finger-radius = <dim>` Default: .1875  
The radius of the circles that represent the fingers in multiples of `x-unit`. Also determines the size of the root markers and the barré.
- ▶ `finger-x-offset = <dim>` Default: .375  
The  $x$  offset of the number with respect to the circle in multiples of `x-unit`.
- ▶ `finger-y-offset = <dim>` Default: .375  
The  $y$  offset of the number with respect to the circle in multiples of `y-unit`.
- ▶ `finger-style = <tikz style>` Default: `fill`  
The TikZ style the circles representing the fingers are drawn with. This is equivalent to `\tikzset{finger style/.style={<tikz style>}}`.

- **root-style** = <tikz style> Default: fill  
 The TikZ style the squares representing the roots are drawn with. This is equivalent to `\tikzset{root style/.style={<tikz style>}}`.
- **show-root-style** = <tikz style> Default: draw  
 The TikZ style the squares representing the “ghost roots” are drawn with. This is equivalent to `\tikzset{show root style/.style={<tikz style>}}`.
- **ringing-style** = <tikz style> Default: draw  
 The TikZ style the circles representing the open string markers are drawn with. This is equivalent to `\tikzset{ringing style/.style={<tikz style>}}`.
- **muted-style** = <tikz style> Default: {cross out,draw}  
 The TikZ style the nodes representing muted strings are drawn with. This is equivalent to `\tikzset{muted style/.style={<tikz style>}}`.
- **tuning** = <comma list of string names> Default: {E,B,G,D,A,E}  
 The tuning.
- **use-rbc** = `true|false` Default: false  
 If set to true the **name** will be set in the command `\rbc` from the *realbookchords*. If this option is not used as a package option then make sure you also load *realbookchords* [Nie13]. Please be aware that the latter requires  $\text{\LaTeX}$  or  $\text{\LuaTeX}$ . See section 4 for details.

## 4 Using *realbookchords*

Setting `\setchordscheme{use-rbc=true}` or using the same as package option will set the chord names/symbols in *realbookchords*’ command `\rbc`.

In order to use this option you need to install the *realbookchords* package [Nie13]. I expect it to go to CTAN eventually but until then you can get it at <https://bitbucket.org/cgnieder/realbookchords/>. The package uses Jochen Pietsch’s “New Real Book” font [Pie] for typesetting the chord symbols which you can get at <http://notation.jochenpietsch.de/>. It is placed under the Creative Commons Attribution-Noncommercial-Share Alike 3.0 Unported License .

*realbookchords* requires that you compile your document with  $\text{\LaTeX}$  or  $\text{\LuaTeX}$ .


Here is an example of how the chord symbol looks with *realbookchords*:



```

1 \setchordscheme{use-rbc=true}
2 \chordscheme[
3   name      = Gmi7(\b5) ,
4   position  = II ,
5   finger    = {1/2:1, 2/3:4, 2/4:3} ,
6   show-root = {4/4} ,
7   root      = {2/6:2} ,
8   mute      = {1,5}
9 ]

```



## References

- [Lea66] William G. Leavitt. *A Modern Method for Guitar*. Vol. 1. Berklee Press Publications, Boston, 1966.
- [Leh11] Philipp Lehman. etoolbox. Version 2.1, Jan. 21, 2011. URL: <http://mirror.ctan.org/macros/latex/contrib/etoolbox>.
- [Nie13] Clemens Niederberger. realbookchords. Version 0.1, Apr. 29, 2013. URL: <https://bitbucket.org/cgnieder/guitarchordschemes/>.
- [Pie] Jochen Pietsch. *Jazz Fonts*. URL: [http://notation.jochenpietsch.de/index\\_e.html](http://notation.jochenpietsch.de/index_e.html) (visited on 05/10/2012).
- [TWF10] Till Tantau, Mark Wibrow, and Christian Feuersänger. TikZ/pgf. Version 2.10, Feb. 25, 2010. URL: <http://sourceforge.net/projects/pgf/> (visited on 04/18/2013).
- [Wri11] Joseph Wright. pgfplots. Version 2.1, June 2, 2011. URL: <http://mirror.ctan.org/macros/latex/contrib/pgfplots>.

# Index

<b>B</b>		
<code>barre</code> .....	3	
<b>C</b>		
<code>\chordscheme</code> .....	2, 4	
<b>E</b>		
<code>etoolbox</code> .....	1, 9	
<b>F</b>		
<code>finger</code> .....	3f.	
<code>finger-format</code> .....	7	
<code>finger-format+</code> .....	7	
<code>finger-radius</code> .....	7	
<code>finger-style</code> .....	7	
<code>finger-x-offset</code> .....	7	
<code>finger-y-offset</code> .....	7	
<code>fingering</code> .....	4f.	
<code>fingering*</code> .....	5	
<code>fingering?</code> .....	5	
<b>L</b>		
<code>line-width</code> .....	7	
<b>M</b>		
<code>mute</code> .....	3	
<code>muted-style</code> .....	8	
<b>N</b>		
<code>name</code> .....	2, 4	
<code>name-format</code> .....	7	
<code>name-format+</code> .....	7	
<b>P</b>		
<code>pgfpts</code> .....	1, 9	
<code>position</code> .....	3f.	
<code>position-format</code> .....	7	
<code>position-format+</code> .....	7	
<b>R</b>		
<code>\rbc</code> .....	8	
<code>realbookchords</code> .....	1f., 8f.	
<code>ring</code> .....	3	
<code>ringing-style</code> .....	8	
<code>root</code> .....	3f.	
<code>root-style</code> .....	8	
<b>S</b>		
<code>\scales</code> .....	2, 4	
<code>\setchordscheme</code> .....	6, 8	
<code>show-root</code> .....	3	
<code>show-root-style</code> .....	8	
<code>string-name-format</code> .....	7	
<code>string-name-format+</code> .....	7	
<b>T</b>		
<code>TikZ</code> .....	1, 7f.	
<code>\tikzset</code> .....	7f.	
<code>tuning</code> .....	8	
<b>U</b>		
<code>use-rbc</code> .....	8	
<b>X</b>		
<code>x-unit</code> .....	7	
<b>Y</b>		
<code>y-unit</code> .....	7	