realbookchords

vo.1beta-a 2013/04/25

Typesetting jazz chords the 'Real Book' way

Clemens Niederberger

https://bitbucket.org/cgnieder/realbookchords/ contact@mychemistry.eu

English documentation

Contents			6	6 Typesetting Chords	
1	License and Requirements	1		6.1 Basics	4 4 5
2	About	2		6.4 Bass Notes	6 7
3	Setup	2	7	Song Titles	
4	The Fonts	2	8	See it in Action	8
	4.1 New Real Book Chords4.2 Real Book Title	3	References		10
	4.3 RealBook Chords		lm	Implementation	
5	5 Shortcomings		In	dex	18

1 License and Requirements

REALBOOKCHORDS is placed under the terms of the LaTeX Project Public License, version 1.3 or later (http://www.latex-project.org/lppl.txt). It has the status "maintained".

In order to function properly a rather up to date version of the l3kernel¹ is needed. REAL-BOOKCHORDS also needs xparse (part of the l3packages² bundle) and fontspec³ for proper font support.

REALBOOKCHORDS does not offer the fonts it uses. You need to install them on your system by yourself and then use this package with XHATEX or LualATEX to be able to use its features.

¹ CTAN: l₃kernel ² CTAN: l₃packages ³ CTAN: fontspec

2 About

On his website Jochen Pietsch offers three fonts [Pie] which mimic the styles of the famous The Real Book [Varoo] and its successor The New Real Book [Varoo]:

- New Real Book Chords
- Real Book Title
- RealBook Chords

REALBOOKCHORDS does *not* offer these fonts. Instead it offers easy to use macros to use the first font with X_TL^AT_EX or Lual^AT_EX if it is installed on your system. Especially a macro for the intuitive usage of the sometimes rather hidden symbols for the creation of chord symbols is offered.

3 Setup

REALBOOKCHORDS defines a few options which can be globally set using

► \RBCsetup{<options>}

The options follow a key/value system like in many other LATEX packages.

4 The Fonts

Please note, these fonts are still in beta-stage, so you might note some missing characters, or you may need to tweak the layout. Because my interest in this project has decreased, I have no plans to do any further improvements.

Jochen Pietsch

The license of the fonts forbids to use them for commercial purposes. This is not strictly true for this package but as it is rather useless without them, well...

This documentation defines new font families for two of the three fonts, the third one is defined by REALBOOKCHORDS.

```
% from the preamble of this document
newfontfamily\RealBookTitle{Real Book Title}
Newfontfamily\RealBookChords{RealBook Chords}
```

⁴ The original illegal edition is no longer available, though. I am uncertain if the 6th edition still uses the same handwritten font. ⁵ Just in case the website isn't reachable any more or the fonts are no longer distributed there you can also get a copy from me. In this case just send me an email.

The package provides this font family switch:

▶ \NewRealBookChords

activate the font family "New Real Book Chords"

4.1 New Real Book Chords

The most important font for this package is "New Real Book Chords". The font has only a limited number of characters since its purpose is to build chords. This also means that it has some unexpected symbols. But have a look for yourself:

4.2 Real Book Title

The following example is simply to show you the font, REALBOOKCHORDS does not use it at all.

4.3 RealBook Chords

The following example is simply to show you the font, REALBOOKCHORDS does not use it at all.

```
\normalsize\RealBookChords ABCDEFG ab s 01 34567 9 \#()+-\textasciicircum

ABCNEFG alt. هما ٥١ علم ٥١ علم ١٥٠ علم ١١٠ علم ١٥٠ علم ١٥٠
```

5 Shortcomings

Since the font is missing some symbols, for instance the uppercase delta for a maj7 chord or the striked through o (similar to \emptyset) for a half-diminished chord, for one thing this package does workarounds and else we have to live with it.

There are plans for the future to extend this package for the use with the more professional font available here: http://www.jazzfont.com/. But for that I'll first have to be able to buy the font and experiment with it a bit. *Finis coronat opus*.

6 Typesetting Chords

It's time to get to the important stuff: the chords. To typeset them there is one basic command:

▶ \rbc[<options>]{<chord specs>}

The {<chord specs>} will be explained in detail in the rest of the documentation.

6.1 Basics

The basic usage is pretty self-explanatory:

Note that this is nearly but not exactly the same as using the font directly:

```
NewRealBookChords Ab9 Cmi E+ Gma9 F\#mi9 Db13

Ab9 Cmi E+ Gma9 F#mi9 Db13
```

The font provides the characters **MI** and **MA**. \jc replaces the strings mi and ma with them. You have also seen that a b gives for a flat root and \# gives for a sharp root.

6.2 Extensions

One very important aspect of "jazzy" chords is tensions. The basic tensions are clear – just insert the intervall number:

```
\rbc\{G7\\rbc\{A9\\rbc\{F11\\rbc\{E13\\rbc\{B7+\}\}}\G^7 A^9 F^{11} E^{13} B^{7+}
```

Often enough one needs alterated extensions. **REALBOOKCHORDS** defines two macros to access the characters and easily:

▶ \b

minor/diminished extension

▶ \ k

major/augmented extension

Let's see them in action:

```
| \rbc{Fmi7(\b5)} \rbc{G7(\k9)} \rbc{Eb7(\b9)} \rbc{Db9(\k11)} \rbc{Cmi7(5-)}

| Fmi7(\b5) G^7(\psi4) E\b7(\b4) D\b9(\psi4) Cmi7(5-)
```

There are also six "extension descriptions":

Since they're not all available as single characters, REALBOOKCHORDS fakes the missing ones. This results in inconsistent looks. That's why REALBOOKCHORDS provides an option so that all six are faked:

Default: false

▶ use-fake-symbols = true | false switch between original characters and faked ones.

6.3 Double Extensions

Sometimes more than one alterated extension needs to be indicated. The "New Real Book Chords" font provides a number of characters for this purpose. REALBOOKCHORDS provides five macros to access them easily:

- ► \bb{<intervalls>} \rbc{\bb{13,9}} (13,9)
- ► \bk{<intervalls>} \rbc{\bk{13,9}} (*13,9)
- ► \kb{<intervalls>} \rbc{\kb{13,9}} (*13,9)

```
► \kk{<intervalls>}
\rbc{\kk{13,9}} (*13,9)
```

There are four different combinations of alterations. For each there is a macro. The fifth macro also provides a possibility to access to the for combinations but also enables to only alterate only one of the two extensions. Unlike the first four macros \dt is not only inside \rbc defined but can also be used in normal text.

All possible [<alterations>] are shown below:

The intervall numbers for both extensions are given seperated with a comma. If the combination is present as a character like for example $\overset{13}{\bullet}$ then the character is used else it is faked:

- ► fake-double-extensions = <u>true</u>|false Default: false when true *all* double extension numbers are faked.
- ► double-extensions-brackets = <u>true</u>|false Default: false enclose the double extensions in brackets or not.

There is a shortcut for the double-extensions-brackets option: \rbc*. The brackets can also be set explicitly using [and].

```
\rbc{Eb7\bk{9,5}} \rbc[double-extensions-brackets=false]{C\dt{9,6}} \rbc*{C\dt{9,6}} \rbc*{C\dt{9,6}}} \rbc*{C\dt{9,6}} \rbc*{C\dt{9,6}} \rbc*{C\dt{9,6}} \rbc*{C\dt{9,6}} \rbc*{C\dt{9,6}}
```

6.4 Bass Notes

If you want to indicate a different bass note for the chord you simply seperate the main chord from the bass note with a slash. Please note: if the bass note is a flat or sharp note you have to enclose it in braces:

```
\rbc{Cmi7/{Bb}} \rbc{C7/G} \rbc{E7/{G\#}}
```

$$C_{MI}^{7}_{B^{\flat}}C_{G}^{7}C_{G}E_{G^{\sharp}}^{7}$$

6.5 Disabling the Parsing

If you don't want all the parsing of the \rbc command but simply access the "New Real Book Chords" font you can of course use the font family switch presented earlier:

```
NewRealBookChords Ama7(omit3) [major] Ama<sup>7(</sup>omit<sup>3)</sup> (major)
```

You can also use the following option:

▶ parse = true | false switch off the parsing. Default: true

```
\texttt{parse=true}: \rbc{Ama7(omit3) [major]} \\
\texttt{parse=false}: \rbc[parse=false]{Ama7(omit3) [major]}

parse=true: Ama<sup>7(omit3)</sup> (major)

parse=false: Ama<sup>7(omit3)</sup> (major)
```

7 Song Titles

► \SongTitle[<left>] {<center>} [<right]

A centered title with options to put text to the left and the right of it.

► songtitle-format-left = <code>
Format of the text to the left.

Default: \NewRealBookChords\footnotesize

► songtitle-format-center = <code>
Format of the text in the center.

Default: \NewRealBookChords\Large\centering

► songtitle-format-right = <code>
Format of the text to the right.

Default: \NewRealBookChords\footnotesize

► songtitle-pos-left = l|c|r Alignment of the text to the left. Default: 1

► songtitle-pos-right = l|c|r Alignment of the text to the right. Default: 1

As an example: the following code ...

```
\SongTitle{Begin The Beguine}

\par\vskip\baselineskip

\SongTitle[Medium Swing Tempo]{Begin The Beguine}

\par\vskip\baselineskip

\SongTitle{Begin The Beguine}[Cole Porter\\arr.: Jerry Sears]

\par\vskip\baselineskip

\RBCsetup{songtitle-pos-right=r}

\SongTitle{Begin The Beguine}[Cole Porter\\arr.: Jerry Sears]
```

... produces this:

Begin The Beguine

Medium Swing Tempo

Begin The Beguine

Begin The Beguine

Cole Porter
arr.: Jerry Sears

Begin The Beguine Cole Porter arr.: Jerry Sears

8 See it in Action

Let's use the \rbc command together with musixtex for a real example. Both fontspec which is loaded be REALBOOKCHORDS and musixtex define the command \breve. The definition by fontspec takes place \AtBeginDocument.

A similar problem arises when musixtex is used together with biblatex⁷: they both define \addspace.

You can do something like the following to get them to work together:

```
documentclass{article}
lusepackage{musixtex}
let\mbreve\breve
let\breve\relax
lusepackage{realbookchords}
begin{document}
do stuff, e.g. restore the 'musixtex' definition of \breve
lend{document}
```

Or - even easier - load **REALBOOKCHORDS** with the load-musixtex option and let it handle things. However, this doesn't always work as expected, yet.

⁶ CTAN: musixtex ⁷ CTAN: biblatex

```
| \documentclass{article}
| \usepackage[load-musixtex]{realbookchords}
| \usepackage[document]
| do stuff, e.g. restore the 'musixtex' definition of \breve
| \end{document}
```

Note that this option should be used as a package option and *not* via \RBCsetup.

If you use this option **REALBOOKCHORDS** loads musixtex and sets \breve to the meaning of fontspec. You have the possibility to access musixtex's version:

▶ \musixtexbreve

musixtex's original definition.

▶ \fontspecbreve

fontspec's original definition.

▶ breve-version = fontspec|musixtex
 sets \breve to the definition of the specified package.

▶ \musixtexaddspace

REALBOOKCHORDS undefines musixtex's \addspace but stores the definition in \musixtexaddspace. You'll probably need to restore musixtex's definition. If you don't use biblatex in the same document there shouldn't be a problem.


▶ addspace-version = musixtex

restores musixtex's definition.

Let's take the first eight bars of Kenny Durham's "Blue Bossa" as an example:

```
\begin{music}
parindentOpt \generalmeter{\meterfrac44}\setsign{1}{-3}\nobarnumbers
4 \SongTitle{Blue Bossa}[\\Kenny Durham]
5 \startpiece
6 \addspace{.5\afterruleskip}%
   \NOtes\qa g\en
   \doublebar % 1
   \NOtes\Uptext{\rbc{Cmi6}}\qlp n\en
   \Notes\ca l\en
   \Notes\qa k\en
   \Notes\isluru0j\ca j\en
   \bar % 2
13
    \NOtes\tslur0j\hlp j\en
14
    \NOtes\qa i\en
15
    \bar % 3
    \NOTes\Uptext{\rbc{Fmi7}}\ha h\en
Notes\qlp n\en
19 \Notes\isluru0m\ca m\en
```

```
\bar % 4
\NOTEs\tslur0m\wh m\en
\bar % 5
\NOtes\Uptext{\rbc{Dmi7(\b5)}}\qlp m\en
\Notes\ca{lk}\qa j\en
\Notes\isluru0i\ca i\en
\bar % 6
\NOTEs\Uptext{\rbc{G7(\k5)}}\tslur0i\hlp i\en
\Notes\qa h\en
\Notes\qa h\en
\bar % 7
\NOTes\Uptext{\rbc{Cmi6}}\ha g\en
\Notes\qlp m\isluru0l\ca l\en
\bar % 8
\NOTEs\tslur0l\wh l\en
\endpiece
\end{music}
```



References

- [Pie] Jochen Pietsch. Jazz Fonts. URL: http://notation.jochenpietsch.de/index_e.html (visited on o5/10/2012).
- [Varoo] Various. *The Real Book Volume I. C Edition*. 6th edition. Hal Leonard Publishing Corporation, Jan. 1, 2000. ISBN: 978-0634060380.
- [Varo9] Various. *The New Real Book Volume I. C Edition*. 1st edition. Ama Verlag, Feb. 12, 2009. ISBN: 978-0961470142.

Implementation

- NequirePackage{expl3}[2012/03/03]
- 36 \ProvidesExplPackage
- 37 {realbookchords}
- 38 {2013/04/25}

```
{0.1beta-a}
     {Typesetting jazz chords the 'Real Book' way}
40
   \msg_new:nnnn { realbookchords } { wrong-engine }
42
     { 'realbookchords'~needs~either~to~be~run~with~XeLaTeX~or~with~LuaLaTeX. }
43
44
        'realbookchords'~needs~either~to~be~run~with~XeLaTeX~or~with~LuaLaTeX.~
45
       Since~you're~using~something~different~I~will~abort!
46
47
   \bool_if:nF { \xetex_if_engine_p: || \luatex_if_engine_p: }
49
     { \msg_error:nn { realbookchords } { wrong-engine } \tex_endinput:D }
50
51
   \RequirePackage { xparse , l3keys2e }
52
53
   \tl_new:N \l__rbc_tmpa_tl
   \tl_new:N \l__rbc_tmpb_tl
55
   % Options:
57
   \bool_new:N
                    \l__rbc_tensions_brackets_bool
   \bool_set_true:N \l__rbc_tensions_brackets_bool
                    \l__rbc_fake_symbols_bool
60 \bool_new:N
61 \bool_new:N
                    \l__rbc_parse_chord_bool
   \bool set true:N \l rbc parse chord bool
   \bool new:N
                    \l rbc fake double numbers bool
   \bool new:N
                    \l__rbc_load_musixtex_bool
   \keys define:nn { rbc }
66
67
       double-extensions-brackets .bool_set:N = \l__rbc_tensions_brackets_bool ,
68
       double-extensions-brackets .default:n = true ,
69
       use-fake-symbols
                                   .bool_set:N = \l__rbc_fake_symbols_bool ,
       use-fake-symbols
                                   .default:n = true ,
71
       fake-double-extensions
                                   .bool_set:N = \l__rbc_fake_double_numbers_bool ,
       fake-double-extensions
                                   .default:n = true ,
73
                                   .bool_set:N = \l__rbc_parse_chord_bool ,
       parse
74
                                   .default:n = true ,
       parse
       load-musixtex
                                   .code:n
         \bool_set_true:N \l__rbc_load_musixtex_bool
77
         \@ifpackageloaded{musixtex}{}
78
           {
             \RequirePackage { musixtex }
             \cs_set_eq:NN \musixtexbreve \breve
81
             \cs_undefine:N \breve
82
             \cs_set_eq:NN \musixtexaddspace \addspace
83
             \cs_undefine:N \addspace
           }
85
     }
86
```

```
% double tensions
      \cs_new:Npn \rbc_bb:n #1 { \rbc_read_double_tensions:nn { bb } { #1 } }
      \cs_new:Npn \rbc_kk:n #1 { \rbc_read_double_tensions:nn { kk } { #1 } }
      \cs_new:Npn \rbc_bk:n #1 { \rbc_read_double_tensions:nn { bk } { #1 } }
      \cs_new:Npn \rbc_b: \{ \ \ \ \ \}
      \cs_new:Npn \rbc_k: { ? }
95
96
      \prop_new:N
                            \l__rbc_double_tensions_signs_prop
      \prop_put:Nnn \l__rbc_double_tensions_signs_prop { bb } { \'{a} }
      \prop_put:Nnn \l__rbc_double_tensions_signs_prop { kk } { \aa{} }
      \prop_put:Nnn \l__rbc_double_tensions_signs_prop { bk } { \"{a} }
      \label{lem:loss} $$ \operatorname{prop\_put:Nnn \l_\_rbc\_double\_tensions\_signs\_prop { kb } { \n^{a} } $$
      \prop_put:Nnn \l__rbc_double_tensions_signs_prop { K } { \rbc_k: }
103
      \prop_put:Nnn \l__rbc_double_tensions_signs_prop { b } { \'{a} }
      \prop_put:Nnn \l_rbc_double_tensions_signs_prop { k } { \arraycolor=} 
                            \l__rbc_double_tensions_numbers_prop
      \prop_new:N
107
      \prop_put:Nnn \l__rbc_double_tensions_numbers_prop { 5,5 }
                                                                                                                { \'{A} }
108
      \prop_put:Nnn \l__rbc_double_tensions_numbers_prop { 9,5 }
                                                                                                                { \'{A} }
      \prop_put:Nnn \l__rbc_double_tensions_numbers_prop { 11,5 }
                                                                                                               { \^{A} }
      \prop put:Nnn \l rbc double tensions numbers prop { 13,5 }
                                                                                                               { \~{A} }
      \prop put:Nnn \l rbc double tensions numbers prop { 7,6 }
                                                                                                                { \"{E} }
      \prop_put:Nnn \l__rbc_double_tensions_numbers_prop { 9,9 }
                                                                                                                { \"{A} }
      115
      \prop_put:Nnn \l__rbc_double_tensions_numbers_prop { 13,13 } { \'{E} }
118
      \cs_new_protected:Npn \rac{rbc}{read_double_tensions:nn #1#2
119
120
             \bool_if:NT \l__rbc_tensions_brackets_bool { [ }
             \prop_get:NnNT \l__rbc_double_tensions_signs_prop { #1 } \l__rbc_tmpa_tl
                { \tl_use:N \l__rbc_tmpa_tl \tl_clear:N \l__rbc_tmpa_tl }
             \bool_if:NTF \l__rbc_fake_double_numbers_bool
                { \rbc_fake_double_numbers:w #2 \q_stop }
                {
                    \prop_get:NnNTF \l__rbc_double_tensions_numbers_prop { #2 } \l__rbc_tmpb_tl
                        { \tl_use:N \l__rbc_tmpb_tl \tl_clear:N \l__rbc_tmpb_tl }
                        { \rbc_fake_double_numbers:w #2 \q_stop }
130
             \bool_if:NT \l__rbc_tensions_brackets_bool { ] }
131
      \cs new protected:Npn \rbc dt:w
          { \peek_meaning:NTF [ { \rackledownberry.peek_meaning:NTF [ { \rackled
```

```
\cs_new:Npn \rbc_dt_auxi:w [#1]#2
     { \rbc_read_double_tensions:nn { #1 } { #2 } }
138
   \cs_new:Npn \rbc_dt_auxii:n #1
140
     { \rbc read double tensions:nn { } { #1 } }
141
142
   \cs_new:Npn \rbc_fake_double_numbers:w #1,#2 \q_stop
144
       \box_move_up:nn { .0ex } { \hbox:n { \addfontfeatures { Scale=.9 } #1 } }
145
       \tex_kern:D -.5ex
       \box_move_down:nn { .85ex } { \hbox:n { \addfontfeatures { Scale=.9 } #2 } }
147
148
149
   % main command:
   \cs_new_protected:Npn \rbc_rbc:n #1
       \group_begin:
153
         \cs_{eq:NN \bb \rbc_bb:n}
         \cs_set_eq:NN \bk \rbc_bk:n
155
         \cs_set_eq:NN \kb \rbc_kb:n
156
         \cs_set_eq:NN \kk \rbc_kk:n
157
         \cs_{eq:NN \dt} \cs_{dt:w}
         \cs_{eq:NN b} \cs_{ep}
159
         \cs set eq:NN \k \rbc k:
         \tl_set:Nn \l__rbc_tmpa_tl { #1 }
         \prop_map_inline:Nn \l__rbc_symbols_prop
163
             \tl_set_rescan:Nnn \l__rbc_tmpb_tl { } { ##1 }
164
             \tl_replace_all:NVn \l__rbc_tmpa_tl { \l__rbc_tmpb_tl } { ##2 }
           }
         \NewRealBookChords \tl_use:N \l__rbc_tmpa_tl
       \group_end:
168
     }
   \cs_generate_variant:Nn \tl_replace_all:Nnn { NV }
   % bass notes:
172
   \cs_new:Npn \rbc_bass_note:n #1
     \cs_new_protected:Npn \rac{rbc}{is_bass:
     { \peek_meaning:NT \rbc_bass_note:n { \tex_kern:D -.35ex } }
177
178
   % fake symbols:
   \cs_new:Npn \rbc_fake_symbol:nn #1#2
180
       \bool_if:nTF { \tl_if_blank_p:n { #2 } || \l__rbc_fake_symbols_bool }
182
         {
           \box_move_up:nn { 1.05ex }
```

```
{ \hbox:n { \addfontfeatures { Scale=.565 } #1 \tex_kern:D .1ex } }
                  }
186
                  { #2 }
           }
180
       \cs_new_protected:Npn \__rbc_peek_mima:
              \peek meaning:NTF >
192
                  { \tex kern:D -.4ex }
                  { \peek_meaning:NTF > { \tex_kern:D -.4ex } }
195
196
       \group begin:
197
       \char_set_catcode_letter:N \@
       \cs_gset:Npn \rbc_fake_add: { @ }
       \group_end:
201
       % symbols; strings to be replaced when parse=true
       \prop_new:N \l__rbc_symbols_prop
       204
       \label{lem:local_prop_put:Nnn l_rbc_symbols_prop { maj } { \begin{tabular}{l} \begin{ta
       \prop_put:Nnn \l__rbc_symbols_prop { ma }
                                                                                       { < }
       \prop put:Nnn \l rbc symbols prop { mi }
                                                                                        { > }
       \prop_put:Nnn \l__rbc_symbols_prop { alt } { \rbc_fake_symbol:nn { alt. } { } }
       \prop_put:Nnn \l__rbc_symbols_prop { sus } { \rbc_fake_symbol:nn { sus } { } }
       \prop_put:Nnn \l__rbc_symbols_prop { add } { \rbc_fake_symbol:nn { add } { \rbc_
          fake add: } }
                                                                                        { b \__rbc_peek_mima: }
       \prop_put:Nnn \l__rbc_symbols_prop { b }
                                                                                         { \ \ \ \ } \ \ \ \ \ \ \ \ \ \ }
       \prop_put:Nnn \l__rbc_symbols_prop { \# }
       \prop_put:Nnn \l__rbc_symbols_prop { * }
                                                                                         { * }
       \prop_put:Nnn \l__rbc_symbols_prop { \k }
                                                                                         { ? }
       \prop_put:Nnn \l__rbc_symbols_prop { \b }
                                                                                         { \b }
       \prop_put:Nnn \l__rbc_symbols_prop { 6/9 }
                                                                                       { \% }
       \prop_put:Nnn \l__rbc_symbols_prop { / }
                                                                                         { \rbc_bass_note:n }
       \prop_put:Nnn \l__rbc_symbols_prop { + }
                                                                                         { + }
       \prop_put:Nnn \l__rbc_symbols_prop { - }
                                                                                        { - }
       \prop_put:Nnn \l_rbc_symbols_prop { ° }
                                                                                         { \textordmasculine }
       \prop_put:Nnn \l__rbc_symbols_prop { \dim } { \textordmasculine }
       \prop_put:Nnn \l__rbc_symbols_prop { ( }
                                                                                         { ( }
       \prop_put:Nnn \l__rbc_symbols_prop { ) }
                                                                                         { ) }
       \prop_put:Nnn \l__rbc_symbols_prop { 0 }
                                                                                         { 0 \rbc_is_bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 1 }
                                                                                        { 1 \rbc_is_bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 2 }
                                                                                        { 2 \rbc_is_bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 3 }
                                                                                        { 3 \<u>rbc_</u>is_bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 4 }
                                                                                        { 4 \rbc is bass: }
       \prop put:Nnn \l rbc symbols prop { 5 }
                                                                                        { 5 \rbc is bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 6 }
                                                                                        { 6 \<u>rbc_</u>is_bass: }
       \prop_put:Nnn \l__rbc_symbols_prop { 7 }
```

```
\prop_put:Nnn \l__rbc_symbols_prop { 8 }
                                                  { 8 \rbc_is_bass: }
    \prop_put:Nnn \l__rbc_symbols_prop { 9 }
                                                  { 9 \rbc_is_bass: }
234
    % user commands:
236
    % the chords:
    \NewDocumentCommand \rbc { som }
238
        \group_begin:
240
          \IfBooleanT { #1 } { \bool_set_false:N \l__rbc_tensions_brackets_bool }
241
          \IfNoValueF { #2 } { \keys_set:nn { rbc } { #2 } }
          \bool_if:NTF \l__rbc_parse_chord_bool
243
            { \<u>rbc_</u>rbc:n { #3 } }
244
            { \NewRealBookChords #3 }
245
        \group_end:
246
      }
248
    % double extensions:
249
    \NewDocumentCommand \dt { om }
251
        \group_begin:
252
          \NewRealBookChords
253
          \rbc_read_double_tensions:nn { #1 } { #2 }
        \group_end:
255
      }
256
    % song titles:
    \tl_new:N \l__rbc_songtitle_format_left_tl
259
    \tl_set:Nn \l__rbc_songtitle_format_left_tl
      { \NewRealBookChords\footnotesize }
261
    \tl_new:N \l__rbc_songtitle_format_center_tl
    \tl_set:Nn \l__rbc_songtitle_format_center_tl
263
      { \NewRealBookChords\Large\centering }
    \tl_new:N \l__rbc_songtitle_format_right_tl
    \tl_set:Nn \l__rbc_songtitle_format_right_tl
      { \NewRealBookChords\footnotesize }
    \tl_new:N \l__rbc_songtitle_position_left_tl
268
    \tl_set:Nn \l__rbc_songtitle_position_left_tl { l }
    \tl_new:N \l__rbc_songtitle_position_right_tl
    \tl_set:Nn \l__rbc_songtitle_position_right_tl { l }
271
    \keys_define:nn { rbc }
274
        songtitle-format-left
                                 .tl_set:N = \l__rbc_songtitle_format_left_tl ,
        songtitle-format-center .tl_set:N = \l__rbc_songtitle_format_center_tl ,
276
        songtitle-format-right .tl_set:N = \l__rbc_songtitle_format_right_tl ,
        songtitle-pos-left
                                 .tl_set:N = \l__rbc_songtitle_position_left_tl ,
        songtitle-pos-right
                                 .tl set:N = \l rbc songtitle position right tl
279
      }
280
```

```
\NewDocumentCommand \SongTitle { omo }
283
        \IfNoValueF { #1 }
284
          {
            \hbox overlap right:n
286
                 \tl_use:N \l__rbc_songtitle_format_left_tl
                 \tabular { @{} \l__rbc_songtitle_position_left_tl } #1 \endtabular
          }
        \parbox [ b ] { \dim_eval:n { \linewidth - \parindent } }
          { \tl_use:N \l__rbc_songtitle_format_center_tl #2 }
293
        \IfNoValueF { #3 }
294
          {
            \hbox_overlap_left:n
                 \tl_use:N \l__rbc_songtitle_format_right_tl
298
                 \tabular { @{} \l__rbc_songtitle_position_right_tl } #3 \endtabular
          }
301
      }
302
303
304
    \NewDocumentCommand \RBCsetup { m } { \keys set:nn { rbc } { #1 } }
    \ProcessKeysOptions { rbc }
308
    \RequirePackage { fontspec }
309
310
    \cs_set_eq:NN \fontspecbreve \breve
311
312
    \cs_set:Nn \rbc_new_font_family:Nnn { \newfontfamily #1 [ #2 ] { #3 } }
313
314
    \rbc_new_font_family:Nnn \NewRealBookChords
315
      {
316
        BoldFont
                         = New~Real~Book~Chords ,
317
        ItalicFont
                         = New~Real~Book~Chords .
318
        BoldItalicFont = New~Real~Book~Chords ,
        SlantedFont
                         = New~Real~Book~Chords ,
        BoldSlantedFont = New~Real~Book~Chords ,
        SmallCapsFont = New~Real~Book~Chords ,
323
      { New~Real~Book~Chords}
324
325
    \keys_define:nn { rbc }
326
327
        breve-version
328
        breve-version / musixtex
                                      .code:n = \cs set eq:NN \breve \musixtexbreve ,
329
        breve-version / fontspec
                                      .code:n = \cs_set_eq:NN \breve \fontspecbreve ,
```

Index

Section titles are indicated **bold**, packages sans serif, commands \brown and options yellow.

A	J	P
\addspace8 f.	\jc4	parse 7
addspace-version9		
	K	R
В	\k5	\rbc 4, 6 ff.
\b5	\kb5	\rbc* 6
\bb5	\kk6	\RBCsetup 2, 9
biblatex8 f.		
\bk5	L	S
\breve8 f.	l3kernel1	\SongTitle7
breve-version9		songtitle-format-center7
	load-musixtex8	songtitle format-left
D		songtitle format-right7
double-extensions-brackets6	M	songtitle pos right
\dt6	musixtex 8 f.	songtitle-pos-right7
	\musixtexaddspace9	IJ
F	\musixtexbreve9	use-fake-symbols5
fake-double-extensions6		ase rake symbols
fontspec	N	X
•	\NewRealBookChords 3	xparse