

Practical adaptive quantum tomography

Christopher Granade

www.cgranade.com/research/talks/aip-2016

Joint work with:

Christopher Ferrie Steven T. Flammia

Centre of Excellence for Engineered Quantum Systems
University of Sydney, NSW

November 25, 2016

The Tomographic Problem

States: $\rho \in \mathbb{C}^{d \times d}$

Measurements: $P_k \in \mathbb{C}^{d \times d}$

$$\Pr(\text{click}|\rho; P_k) = \text{Tr}(P_k \rho)$$

Given data record $D = \{d_1, \dots, d_N\}$, what should we report as our estimate $\hat{\rho}$?

“Conventional” Approach

- Expand ρ, P_k in a basis $\{B_1, \dots, B_{d^2-1}\}$ of operators.

$$\rho = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} \theta_j B_j$$

$$P_k = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} x_{kj} B_j.$$

“Conventional” Approach

- Expand ρ, P_k in a basis $\{B_1, \dots, B_{d^2-1}\}$ of operators.

$$\rho = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} \theta_j B_j$$

$$P_k = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} x_{kj} B_j.$$

- Model as linear inversion problem.

$$\mathbf{f} = \frac{1}{d} + \mathbf{x}\boldsymbol{\theta}.$$

“Conventional” Approach

- Expand ρ, P_k in a basis $\{B_1, \dots, B_{d^2-1}\}$ of operators.

$$\rho = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} \theta_j B_j$$

$$P_k = \frac{\mathbb{1}}{d} + \sum_{j=1}^{d^2-1} x_{kj} B_j.$$

- Model as linear inversion problem.

$$\mathbf{f} = \frac{1}{d} + \mathbf{X}\boldsymbol{\theta}.$$

- Solve.

$$\hat{\boldsymbol{\theta}} = (\mathbf{X}^T \mathbf{X})^{-1} \mathbf{X}^T \left(\hat{\mathbf{f}} - \frac{1}{d} \right)$$

Oops.

Problems w/ linear inversion estimator:

- Doesn't enforce $\rho \geq 0$.
- Doesn't weight according to variance of $\hat{\mathbf{f}}$ about \mathbf{f} .
- Difficult to assess error bars.

Oops.

Problems w/ linear inversion estimator:

- Doesn't enforce $\rho \geq 0$.
- Doesn't weight according to variance of $\hat{\mathbf{f}}$ about \mathbf{f} .
- Difficult to assess error bars.

Alternative: maximum likelihood estimator.

$$\hat{\rho}_{\text{MLE}} := \arg \max_{\rho} \prod_k \Pr(d_k | \rho; P_k)$$

Problems w/ linear inversion estimator:

- Doesn't enforce $\rho \geq 0$.
- Doesn't weight according to variance of $\hat{\mathbf{f}}$ about \mathbf{f} .
- Difficult to assess error bars.

Alternative: maximum likelihood estimator.

$$\hat{\rho}_{\text{MLE}} := \arg \max_{\rho} \prod_k \Pr(d_k | \rho; P_k)$$

- Still tricky to get error bars.
- Reports rank-deficient estimates.
Blume-Kohout [doi:10/cn772j](https://doi.org/10.1103/cn772j)
- Can't include prior information.


Bayesian Approach

Use to find $\Pr(\rho|\text{data})$ from $\Pr(\text{data}|\rho)$.

- Particle filtering: easy to use numerical impl.

qinfer.org • 1610.00336

- Can include prior information.
- Built-in error bars.



Huszár and Houlsby [DOI 10/s86](https://doi.org/10.26434/chemrxiv-2018-s86), Granade *et al.* [DOI 10/bhdw](https://doi.org/10.26434/chemrxiv-2018-bhdw)

Tomography as Optimization

One big remaining drawback: adaptively picking each P_k .

Tomography as Optimization

One big remaining drawback: adaptively picking each P_k .

Express tomography as optimization problem:

$$|\hat{\psi}\rangle = \arg \max_{|\phi\rangle} |\langle \phi | \psi \rangle|^2$$

Overlap can be est. by measuring *test states* $|\phi\rangle$. Thus, optimization algorithms choose test states when they evaluate objective function f :

$$f(\phi) := |\langle \phi | \psi \rangle|^2$$
$$d_k \sim \text{Bin}(N, f(\phi_k)).$$


One particularly useful optimization algorithm: **Simultaneous Perturbative Stochastic Approximation**

- Pick initial test state $|\phi_0\rangle$ at random.
- For each iteration k :
 - Estimate $f(\phi_k)$ from measurements.
 - Pick perturbation δ at random.
 - Estimate $f(\phi_k \pm \alpha_k \delta)$.
 - Let $\phi_{k+1} = \phi_k + \beta_k (\hat{f}(\phi_k + \alpha_k \delta) - \hat{f}(\phi_k - \alpha_k \delta)) / 2\alpha_k$.


Parameters α_k, β_k control gain and step sizes; choose to decay exponentially with k .

Self-Guided Tomography

SPSA gives a particularly useful and simple *heuristic* for choosing test states. (About 5 lines in Python to implement.)




- Perform self-guided tomography, keeping data record.
- Re-analyze with Bayesian inference.



Granade, Ferrie, and Flammia 1605.05039


Important insight: SGT provides useful heuristic *even when its assumptions are wrong*.

Mixed States ($d=5$)



NB: Test states for process tomography are product states.

Mixed Two-Qubit States



Conclusions

- Bayesian tomography gives principled and easy-to-use approach to state estimation.
- Self-guided tomography gives a practical heuristic for adaptive experiment design.