CIS170 Project 11

The input file is CSINVP:

Record Layout of CSINVP
Record Format INVREC

Field	Description	Length/Type	(Decimal positions)	Notes
*PRODNO	Product number	6S	(0)	UNIQUE
PRODTYPE	Product type	3	--	--
PACT	Product active	1	--	--
DESCRP	Description	40	--	--
SELLPR	Selling price	6S	(2)	--
SHIPWT	Shipping weight	5	--	First three positions are pounds; last two are ounces
QTYOH	Quantity on hand	4P	(0)	--
RORPNT	Reorder point	4P	(0)	--
RORQTY	Reorder quantity	4P	(0)	--
RORCOD	Reorder code	1	--	Blank or R
SUPCOD	Supplier code	3	(0)	--
SHPCST	Shipping cost	6S	(2)	--
CURCST	Current cost	6S	(2)	--
AVGCST	Average cost	6S	(2)	--

Review "packed" data-- how many bytes will each of these packed items need? That determines the "from" and "to" on the input specs

Write the program to produce the report, exactly matching the following print specifications:

```
MM/DD/YY                          CloudServices24x7, Inc.                                    Page     1
                                  Inventory Master Report
Prod.                               Weight   Qty. On   Reorder   Reorder    Shipping   Average    Current    Selling
Num.    Description                 Lbs-Oz   Hand      Point     Qty        Cost       Cost       Cost       Cost
666666  00000000000000000000000000000000000000000000  00000   6,666-    6,666-    6666       -6,666.66  -6,666.66  -6,666.66  -6,666.66
```

You can choose to use prompting in either PDM/SEU green screen, or in RDi (F4 can be pressed in RDI as well, and the line commands shown in the demonstration video can also be used in RDi)

Do NOT code **Free at the top, this does not apply when using fixed form code.

1. Code FIXED-FORM File Specifications. The input file and output file are program-described. The input file is CSINVP. Use QPRINT as your output file name.
2. Code FIXED-FORM Input specifications. Even though not all the fields are used on this particular report, code input specs for all of the fields.
3. You may leave your calculation specs in free-form. Review the items in this unit and note that when mixing fixed and free form, the programmer must use /FREE and /END-FREE exactly as demonstrated.
4. Code FIXED-FORM Output specifications.

Fixed-Form: A place for everything, and everything in its place!