

CIS270A Project 11

Subfile with File Update

Be sure to refer to the Powerpoint WITH AUDIO CLIPS as well as the video.

1. Your application will update the CSORDPRP file. Familiarize yourself with the DDS definition of this file, found in QDDSSRCW inside RPGIV_5THS. Because you will update this file, you need to copy this file into your own file, MYORDPRP.
2. As explained in the video, you will need a logical file so that the file is presented in order first by status, then by order number, and then by product number. It is important that your PFILE keyword in the DDS is PFILE(MYORDPRP) so that it is not actually attaching a logical file to the CSORDPRP file.
3. Create your screen definition:
 - a. The first screen allows your user to key in SH or BO to select records. This is a traditional screen record. Include:
 - i. The current date
 - ii. Your name
 - iii. An appropriate title for the application
 - iv. Allow user to key in the status (SH or BO) – this should be a field defined in your DDS, NOT a referenced field. These are the only two status entries that should be allowed
 - v. Function key F3 as means of exit
 - vi. Display a message if user makes an entry that has no corresponding records
 - b. Next, you will need to code your subfile record format and the subfile control record format.
 - i. This can be handled as a “load all” subfile. Include:
 1. The current date
 2. An appropriate title for the application
 3. Appropriate column headings and data columns for:
 - a. Order number (display only, do not allow user to change)
 - b. Product number (display only, do not allow user to change)
 - c. Quantity ordered, zero suppressed
 - d. Quantity on hold, zero suppressed
 - e. Tracking number
 - f. Status
 - ii. Allow the user to change quantity ordered, quantity on hold, tracking number, and status.
 - iii. Add CHECK(RB) to the DDS for the quantity ordered and the quantity on hold so that your user can use field exit to right-adjust these values.

- iv. So that “more...” will display, add this entry to your subfile control record (using any indicator you wish)

A 52

SFLEND (*MORE)

- v. Caution: if your usual approach when designing a screen is to just guess at the line and beginning positions and then adjust later, be aware that any potential problems with positioning can cause your application to completely crash. So plan carefully when designing the subfile entries.

4. Create the RPG program.

- a. The user makes the entry described above and if no such entries exist a message should display.
- b. On the subfile screen, the user can make changes to the data (quantity ordered, quantity on hold, tracking number, status) that should be updated in the file. Be sure you are using your logical file that you created above.
 - i. In your Update subroutine, in the CHAIN operation, it is important that the Status field used in the chain is the field from your “first” screen (the subfile control record) to ensure that the READC operation will properly find all of the records that have that status to apply the changes, such as:

CHAIN (STSIN:ORD#:PRODNO)

// where STSIN matches the field name you chose for the status input
// on the subfile control record.

- c. Add in an indicator such as SFLEND to the indicator array and then set this indicator on at the top of your mainline logic as shown here, so that “more...” will display when the user can hit page down to view more data.

sflend = *on; // so that more... will display

- d. Test thoroughly.

Change at least two records that are in different locations

Change the status and be sure that it then appears under that new status

Test the page down key

Test “field exit” on Quantity Ordered and Quantity on Hold

On a keyboard that has a numeric keypad, pressing the “+” key is the “field exit”

If you do not have a numeric keypad, pressing “Ctrl” plus “Enter”

Test F12

Test F3