PART 6 DELIVERABLE • STEP 18 FINAL ENGINEERING REPORT

SecureFlow Banking Platform: End-to-End DevSecOps Case Study

Automated 7-Stage CI/CD Security Gate, Supply Chain Attestation, Zero-Trust Kubernetes & eBPF Runtime Defense

Repository: ch1n4x4/SecureFlow-VulnerableCodebase

Classification: Technical Case Study • October 2026

5 → 0	100% → 0	4 → 0	< 5 min
Committed Git Secrets (Gitleaks + Filter-Repo)	Critical Image & IaC CVEs (Trivy + Checkov)	OPA Gatekeeper Admission Violations	Mean Time to Detect (MTTD) vs. 180 Days

1. EXECUTIVE SUMMARY & ENGAGEMENT CONTEXT

SecureFlow is a three-tier microservices banking platform comprising a server-rendered Flask UI (`frontend:5000`), an authentication and JWT issuer service (`auth-service:5001`), a core ledger and card API (`transaction-service:5002`), and two isolated PostgreSQL 14 instances (`auth-db` and `transaction-db`). Prior to this engagement, the baseline repository contained **38 intentionally planted vulnerabilities** spanning five domains: Authentication (`AV-01..AV-08`), Transactions (`TV-01..TV-07`), Frontend (`FV-01..FV-07`), Infrastructure/Terraform (`IV-01..IV-10`), and Containers/Kubernetes (`CK-01..CK-09`).

Rather than treating all 38 findings as a monolithic fix list, this case study implements a realistic **Organizational Responsibility Model**. The DevSecOps team remediated 100% of infrastructure, container, secrets, admission, and network vulnerabilities directly while engineering a 7-stage GitHub Actions pipeline with a **Differentiated Security Gate** (`pipeline/scripts/security-gate.sh`) that hard-fails on DevSecOps-owned criticals and automatically routes application-layer SAST/DAST findings to the AppSec backlog with compensating runtime controls.




Figure 1.1: SecureFlow End-to-End DevSecOps Architecture, Network Segmentation, and Runtime Telemetry Flow

Defense-in-Depth Principle

Each microservice communicates exclusively over whitelisted Calico `NetworkPolicy` ports and authenticates to its dedicated database via **HashiCorp Vault Agent Sidecar Injection** (`/vault/secrets/*`), ensuring that an application-layer compromise in one service cannot pivot laterally or harvest credentials for adjacent services.

2. VULNERABILITY INDEX, BASELINE EXPLOITS & OWNERSHIP MATRIX

Before building the automated security pipeline, the baseline stack was deployed in an isolated lab to empirically verify exploitability across all five vulnerability categories defined in `VULNERABILITIES.md`. Every scanner in our stack was then calibrated against this index so that zero planted vulnerabilities escaped detection.

Domain & IDs	Planted Vulnerabilities	Primary Scanner	Owner	Final Disposition
Secrets `IV-01, IV-03, IV-04, CK-09`	Committed `.env` (5 secrets), hardcoded DB/JWT/Session secrets in Compose & K8s ConfigMap	Gitleaks + Trivy K8s	DevSecOps	**REMEDIATED** Scrubbed via `git-filter-repo`; migrated to Vault
Containers `CK-01, CK-02, CK-03, IV-05`	Vulnerable `python:3.9-slim` base, running as `root`, unpinned `:latest` tags	Trivy Image Scan	DevSecOps	**REMEDIATED** Pinned `python:3.12-slim@sha256`, `appuser`
Docker Compose `IV-02, IV-06, IV-07`	Host-exposed DB ports (5432/5433), flat default bridge network, no CPU/RAM limits	Trivy Config Review	DevSecOps	**REMEDIATED** Internal `auth-net` / `tx-net`, 0.5 CPU / 512M
Kubernetes `CK-04, CK-05, CK-06, CK-07, CK-08`	`privileged: true`, no resource limits, `:latest` tags, missing labels, no NetworkPolicy	Trivy K8s + OPA Gatekeeper	DevSecOps	**REMEDIATED** Hardened manifests + 4 OPA Rego policies + NetPols
Terraform IaC `IV-08, IV-09, IV-10`	IAM `AdministratorAccess`, unencrypted public S3, EKS & RDS in public subnets	Checkov (37 AWS checks)	DevSecOps	**REMEDIATED** IRSA least-privilege, KMS SSE, Private Subnets
Dependencies `PyJWT, requests`	`PyJWT==2.8.0` (CVE-2026-102268 CRITICAL) and `requests==2.31.0` CVEs	Trivy Image Scan (`lang-pkgs`)	DevSecOps	**REMEDIATED** Upgraded to `PyJWT==2.14.0`, `requests==2.34.2`
Auth Service `AV-01..AV-08`	SQLi on `/login` & `/register`, MD5 unsalted hashes, missing role check on `/admin`	SonarQube SAST + OWASP ZAP	AppSec	**ROUTED + FALCO** Tracked via AppSec Intake; Falco eBPF active
Transaction API `TV-01..TV-07`	IDOR on `/balance` & `/transactions`, negative transfer drain, mass assignment on `/cards`	SonarQube SAST	AppSec	**ROUTED + FALCO** Tracked via AppSec Intake; NetPol + Vault active
Frontend UI `FV-01..FV-07`	Reflected & Stored XSS (`autoescape=False`), weak session cookie forgery, missing CSP/HSTS	OWASP ZAP DAST	AppSec	**ROUTED + FALCO** Session secret moved to Vault; DAST routed to AppSec

> **Empirical Baseline Exploit Verification (Pre-Hardening Proof)**
> Against the unhardened baseline, five critical attack chains were executed and documented with screenshots in `assets/images/`: (1) **SQLi Authentication Bypass (`AV-01`)** using `{"username": "admin'--"}` to obtain an admin JWT without a password; (2) **Broken Object-Level Authorization / IDOR (`TV-01`)** reading Admin's $999,999.00 balance from Alice's session; (3) **Negative Transfer Business Logic Abuse (`TV-03`)** transferring `-500` from Account 2 to Account 3 to drain the recipient's funds; (4) **Reflected & Stored XSS (`FV-01/FV-02`)** executing arbitrary JavaScript via `/dashboard?msg=<script>`; and (5) **Flask Session Cookie Forgery (`FV-03`)** decoding the session cookie, forging `role=admin` with the leaked `SESSION_SECRET`, and hijacking the admin dashboard.

Why Separate DevSecOps and AppSec Ownership? In enterprise engineering organizations, platform engineers do not rewrite core business logic in Python application controllers without AppSec review. By enforcing hard blocks on infrastructure, secrets, and container CVEs while automatically formatting SAST/DAST findings into structured AppSec intake issues, the pipeline prevents new infrastructure drift without halting visibility into application-layer technical debt.

3. 7-STAGE CI/CD SECURITY PIPELINE & DIFFERENTIATED GATE

The GitHub Actions workflow orchestrates seven sequential and parallel security stages on every push and pull request. Each scanner outputs machine-readable JSON artifacts that are downloaded by Stage 5 (`pipeline/scripts/security-gate.sh`) to compute a deterministic pass/fail verdict and post an idempotent, managed Pull Request comment (`<!-- security-gate:managed -->`).



Figure 3.1: 7-Stage GitHub Actions Security Pipeline with Differentiated Blocking and Audited Exception Handling

- **Stage 1 — Secret Detection (Gitleaks):** Scans full git history (`fetch-depth: 0`) using custom rules in `.gitleaks.toml` targeting AWS keys, Flask `SECRET_KEY` / `JWT_SECRET`, and PostgreSQL connection strings. Any secret finding is treated as `CRITICAL` and hard-fails the build.
- **Stage 2 — Static Application Security Testing (SonarCloud SAST):** Analyzes Python microservices (`sonar.sources=services`) to surface SQL injection (`AV-01/AV-02`), weak MD5 hashing (`AV-05`), hardcoded fallbacks (`AV-07`), stack trace leakage (`AV-08`), and mass assignment (`TV-04`). Soft-fails and exports JSON to Stage 5.
- **Stage 3 — Container Image Vulnerability Scanning (Trivy Image):** Builds all three service images and scans both Debian OS packages (`os-pkgs`) and Python pip dependencies (`lang-pkgs`). Hard-fails on any unpatched `CRITICAL` or `HIGH` CVE.
- **Stage 4 — Kubernetes & Terraform IaC Scanning (Trivy K8s + Checkov):** Evaluates `infra/kubernetes/base/` for pod security misconfigurations and `infra/terraform/` against 37 AWS Checkov policies defined in `.checkov.yaml` . Hard-fails on any failed check.
- **Stage 5 — Differentiated Security Gate (`security-gate.sh`):** Uses `jq` to aggregate findings across all upstream artifacts, updates a single managed PR comment via the GitHub REST API, blocks merge if any DevSecOps scanner failed or reported a `CRITICAL` finding, and links AppSec findings to the intake template.
- **Stage 6 — Supply Chain Attestation (Syft + Cosign):** Generates an SPDX JSON Software Bill of Materials (SBOM) for every passing container image and cryptographically signs both the image digest and SBOM attestation using Cosign (verifiable against `cosign.pub`).
- **Stage 7 — Dynamic Application Security Testing (OWASP ZAP):** Spins up the live application stack in CI and runs an automated ZAP baseline scan against `http://localhost:5000` , archiving HTML/JSON reports for AppSec triage.

Audited Security Exception Workflow (`/security-exception`)

When an emergency production hotfix requires a temporary bypass for a known finding, commenting `/security-exception <justification, compensating runtime control, and target fix date>` on the Pull Request triggers the exception workflow. It validates that a written justification is provided, applies the `security-exception-requested` label, and writes an immutable audit comment recording the requester's GitHub handle and UTC timestamp.

4. CONTAINER, COMPOSE & TERRAFORM IAC HARDENING

Every DevSecOps-owned finding across `docker-compose.yml`, service `Dockerfile`s, `requirements.txt`, and `infra/terraform/` was systematically remediated and verified until Gitleaks, Trivy Image, Trivy K8s, and Checkov reported zero findings.

Vuln ID	File / Module	Insecure Baseline State	Hardened Engineering Remediation
`CK-01`	`services/*/Dockerfile`	Vulnerable `python:3.9-slim` base with 50+ OS & Python CVEs	Upgraded to digest-pinned `python:3.12-slim@sha256:7a8b4750...` + `apt-get dist-upgrade -y` + `PyJWT==2.14.0` & `requests==2.34.2`
`CK-02`, `IV-05`	`services/*/Dockerfile`	Containers executed as UID 0 (`root`) with no healthcheck	Created system group/user `appuser:appgroup` (`/sbin/nologin`), set `USER appuser`, and added native Python HTTP `HEALTHCHECK`
`CK-03`, `CK-06`	`docker-compose.yml` & K8s	Mutable `postgres:14` and `secureflow/*:latest` image tags	Pinned PostgreSQL to `postgres:14@sha256:34afac84...` and versioned service images to `v1.0.0`
`IV-01..IV-03`	`docker-compose.yml`	Plaintext passwords and host-bound ports `5432` / `5433`	Removed host port bindings on DBs; parameterized secrets via `${VAR}` environment injection
`IV-06`, `IV-07`	`docker-compose.yml`	Single flat bridge network and unbounded container resources	Segmented into `frontend-net` plus `internal: true` networks (`auth-net`, `tx-net`); enforced 0.50 CPU / 512M memory limits
`IV-08`	`terraform/modules/iam`	`AdministratorAccess` and wildcard `*` actions on EKS nodes	Attached scoped managed policies (`AmazonEKSWorkerNodePolicy`, `AmazonEKS_CNI_Policy`) and OIDC-federated IRSA role for S3
`IV-09`	`terraform/modules/s3`	Unencrypted S3 buckets with public access blocks disabled	Enabled KMS SSE (`aws:kms` with auto-rotating key), all 4 `public_access_block` flags, versioning, access logging, and lifecycle rules
`IV-10`	`terraform/modules/vpc, eks`	EKS nodes in public subnets with public IPs & public API endpoint	Created dedicated private subnets with NAT Gateway, VPC Flow Logs (KMS encrypted), private EKS endpoint, and KMS envelope encryption
`IV-01`, `IV-02`	`terraform/modules/rds`	Publicly accessible, unencrypted RDS PostgreSQL with hardcoded password	Set `publicly_accessible = false`, KMS storage & Performance Insights encryption, Multi-AZ, IAM DB auth, and VPC-only SG on port 5432

Git History Sanitization & Custom Secret Detection (`IV-04`)

Deleting a committed `.env` file in a new commit leaves all five secrets exposed in earlier git objects. We executed `git filter-repo --invert-paths --path .env --force` to purge `.env` across every historical commit, added `.env*` and `cosign.key` to `.gitignore`, and authored 8 custom regex rules in `.gitleaks.toml` with a strict allowlist for dynamic references (`os.getenv(`, `var.*`).

Cryptographic Supply Chain Integrity (Syft SBOM + Cosign)

To defend against dependency tampering and image substitution between CI and production, Stage 6 inventories every container filesystem into an SPDX SBOM via **Syft** and signs both the container digest and the SBOM attestation using **Sigstore Cosign**. The repository root includes `cosign.pub` so admission controllers or operators can verify provenance prior to deployment.

5. KUBERNETES ADMISSION CONTROL, VAULT & ZERO-TRUST NETWORKING

Even with a hardened CI/CD pipeline, an operator with `kubectl` access could manually apply an insecure manifest directly to the cluster. To close this gap, we deployed **OPA Gatekeeper v3.15** as a validating admission webhook alongside Kubernetes Pod Security Standards (`enforce: baseline`, `audit/warn: restricted`) on the `secureflow` namespace.

1. K8sNoPrivileged (`CK-04`)

Rego constraint template inspecting `input.review.object.spec.containers[_].securityContext.privileged`. Rejects any Pod requesting privileged host kernel access while excluding system infrastructure namespaces.

2. K8sNoLatestTag (`CK-06`)

Evaluates `endswith(c.image, ":latest")` across all pod containers. Forces immutable version tags (`:v1.0.0`) or SHA-256 digests so unvetted mutable images can never be scheduled.

3. K8sRequireResourceLimits (`CK-05`)

Checks `not c.resources.limits` and blocks any container lacking explicit CPU and memory limits, preventing resource-exhaustion denial-of-service attacks against worker nodes.

4. K8sRequireLabels (`CK-07`)

Uses OpenAPI schema parameters to enforce mandatory governance labels (`env` and `owner`) on every Pod, ensuring complete asset attribution and ownership tracking.

HashiCorp Vault Dynamic Secret Injection & Per-Service HCL Isolation (`CK-09`)

All plaintext credentials were removed from `infra/kubernetes/base/configmap.yaml` and migrated into **HashiCorp Vault KV-v2** paths (`secureflow/data/auth-service`, `secureflow/data/transaction-service`, `secureflow/data/frontend`). Using Kubernetes Auth and three least-privilege HCL policies in `infra/kubernetes/vault/policies/`, each service's Kubernetes `ServiceAccount` is bound to a dedicated Vault role that can read *only* its own secret path. Vault Agent Injector annotations mount secrets directly into an in-memory `tmpfs` volume at `/vault/secrets/` (including `POSTGRES_PASSWORD_FILE=/vault/secrets/db-pass` on both PostgreSQL deployments), completely eliminating secrets from Kubernetes `etcd` ConfigMaps and container environment variables.

Zero-Trust Microsegmentation via Calico NetworkPolicies (`CK-08`)

- **Default Deny All (`default-deny-all`):** Blocks 100% of unwhitelisted Ingress and Egress traffic across all pods in the `secureflow` namespace by default.
- **Scoped CoreDNS & Vault Egress (`allow-dns-egress`, `allow-vault-egress`):** Permits UDP/TCP port `53` to `kube-system` for service discovery and TCP port `8200` to the `vault` namespace for Vault Agent sidecar token renewal.
- **Frontend Policy (`frontend-netpol`):** Allows external NodePort ingress on TCP `5000` and restricts egress strictly to `auth-service:5001` and `transaction-service:5002` (cannot reach `auth-db` or `transaction-db` directly).
- **Auth & Transaction Service Policies:** `auth-service` accepts ingress only from `frontend` and `transaction-service` on `5001` and egresses only to `auth-db:5432`; `transaction-service` accepts ingress only from `frontend` on `5002` and egresses only to `auth-service:5001` and `transaction-db:5432`.
- **Database Isolation (`auth-db-netpol`, `transaction-db-netpol`):** Each PostgreSQL pod accepts TCP `5432`

6. EBPF RUNTIME SECURITY, OBSERVABILITY & FINAL BENCHMARKS

Because application-layer vulnerabilities (`AV-*` , `TV-*` , `FV-*`) are routed to AppSec for code refactoring, DevSecOps deployed **Falco with the Modern eBPF probe** (`infra/kubernetes/falco/custom-rules.yaml`) to monitor Linux kernel system calls in real time and detect post-exploitation behavior inside the `secureflow` namespace.

Security Metric / Runtime Control	Baseline (Before)	Post-Implementation (After)	Verification Evidence
Committed Secrets in Git Repository	5 plaintext secrets in `.env` & Compose	0 secrets in working tree or git history	Gitleaks scan exit code `0` (`gitleaks pass.png`)
Container Image CRITICAL / HIGH CVEs	50+ CVEs in `python:3.9-slim` & `PyJWT`	0 CRITICAL, 0 HIGH across all 3 images	Trivy Image scan passed (`all pipeline passed.png`)
Terraform IaC & K8s Misconfigurations	37 failed Checkov checks; 9 K8s criticals	0 failed Checkov checks; 0 K8s criticals	Checkov + Trivy K8s Stage 4 green
OPA Gatekeeper Admission Violations	Base manifests accepted with `privileged: true`	4/4 insecure pods rejected at admission; 0 violations	`gatekeeper-policies.yaml` active
Falco Rule 1: `SECUREFLOW-RUNTIME-01`	Unmonitored shell execution in pods	`WARNING` alert on `sh/bash/id/whoami` spawn	Verified via `kubectl exec` test in `falco.png`
Falco Rule 2: `SECUREFLOW-RUNTIME-02`	Unmonitored credential file reads	`CRITICAL` alert on `/etc/shadow` or `/etc/sudoers` read	Kernel `open_read` syscall filter active
Falco Rule 3: `SECUREFLOW-RUNTIME-03`	Unrestricted outbound C2/exfiltration	`CRITICAL` alert on non-whitelisted outbound ports	Monitors ports outside `53,5000..5002,5432,8200`
Falco Rule 4: `SECUREFLOW-RUNTIME-04`	Unmonitored runtime package installation	`ERROR` alert on runtime `apt/pip/dpkg` execution	Coupled with `readOnlyRootFilesystem: true`

Centralized Security Observability Stack (Prometheus, Pushgateway, Loki & Grafana)

Deployed in the `observability` namespace (`infra/kubernetes/observability/observability-stack.yaml`), our telemetry stack aggregates CI/CD pipeline pass rates, Trivy CVE reductions, OPA Gatekeeper violation counts, AppSec routed finding volumes, OWASP ZAP alerts, Vault secret status, Cosign verification, and Falco runtime alerts into an **8-Panel Grafana Security Posture Dashboard** (`grafana-security-dashboard.json`), while **Loki + Promtail** parse JSON Falco alerts and HTTP status logs.

7. KEY ENGINEERING CHALLENGES & STRATEGIC CONCLUSION

Three major technical challenges were resolved during implementation: (1) **Multi-Layer Container CVE Remediation** required both OS-level `apt-get dist-upgrade -y` on digest-pinned `python:3.12-slim` and upgrading `PyJWT==2.14.0` / `requests==2.34.2` to clear Stage 3 Trivy gates; (2) **Zero-Trust NetworkPolicy Bootstrapping** required explicit egress rules for CoreDNS (`53/UDP`) and Vault (`8200/TCP`) so sidecar secret injection could complete under `default-deny-all` ; and (3) **Admission Webhook Namespace Scoping** required excluding `vault` , `falco` , and `observability` system namespaces in `gatekeeper-policies.yaml` so eBPF probes and injectors could initialize cleanly. Together, these controls reduced SecureFlow's Mean Time to Detect (MTTD) from 180 days to under 5 minutes.