

Information System and Archiving Infrastructure

Server 1 — 10.0.211.249 & GPU / Clinical Assistant Server 2 — 10.0.211.250

1. Server 1 — Information System and Archiving Server

IP address: **10.0.211.249**

Container	Image	Status	Published ports
openmrs-app	openmrs/openmrs-reference-application-distro:latest	Up	8080 → 8080
orthanc-cors-proxy	nginx:alpine	Up	8043 → 80
ohif-viewer	ohif/app:v3.9.2	Up	3000 → 80
orthanc-pacs	orthancteam/orthanc:latest	Up	4242 → 4242; 8042 → 8042
openmrs-mysql	mysql:8.0	Up (healthy)	3306; 33060 (internal)
orthanc-postgres-db	postgres:13-alpine	Up (healthy)	5432 (internal)
nginx-proxy-manager-app-1	jc21/nginx-proxy-manager:latest	Up	80; 81; 443

Functional roles

OpenMRS provides the electronic medical record / information-system layer. Orthanc provides DICOM/PACS image storage and access. PostgreSQL stores Orthanc data, while MySQL stores OpenMRS data. OHIF provides web-based image visualization. The Nginx Proxy Manager container acts as the reverse-proxy entry point for the server.

2. Server 2 — GPU / Clinical Assistant Server

IP address: **10.0.211.250**

Container	Image	Status	Published ports
server2-proxy	nginx:1.27-alpine	Up (healthy)	80 → 80; 443 → 443
clinical-agent	chu-blida/clinical-agent:1.0.0	Up (healthy)	8000 (internal)

Functional role

The clinical-agent provides the clinical assistant service. It listens internally on port 8000 and is exposed externally through the Server 2 Nginx reverse proxy over HTTPS.

3. Overall Architecture

Server 1 (10.0.211.249) — OpenMRS + MySQL for the information system; Orthanc + PostgreSQL for medical-image archiving; OHIF for image visualization; Nginx Proxy Manager for reverse proxy and TLS termination.

Server 2 (10.0.211.250) — Nginx reverse proxy + clinical-agent service. The agent communicates with OpenMRS on Server 1 through HTTPS.

4. Verified Connectivity / Service State

The clinical-agent container was verified as healthy. Its internal /health endpoint returned status=ok. The Server 2 proxy was also able to reach clinical-agent:8000/health successfully. The agent successfully queried the OpenMRS FHIR metadata endpoint and reported known FHIR capabilities.

5. Network Summary

Source	Destination	Protocol / path	Purpose
Clients / hospital LAN	Server 1	HTTPS → NPM	OpenMRS / Orthanc / viewer access
Server 2 clinical-agent	Server 1	HTTPS → openmrs.hospital.lan	OpenMRS FHIR/API access
Server 2 Nginx	clinical-agent	HTTP → clinical-agent:8000	Reverse proxy

This document reflects the container inventory and architecture information provided for the two servers. It does not infer additional services or configurations beyond the supplied information.