

00-functions

June 12, 2022

1 Functions

```
def my_function():  
    pass
```

```
[1]: def my_function():  
      print('Hello from my_function')
```

```
[2]: # Invoking a function  
      my_function()
```

Hello from my_function

```
[3]: def welcome(name):  
      print(f'Hello {name}')  
      welcome("Moe")  
      welcome("Larry")  
      welcome("Curly")
```

Hello Moe
Hello Larry
Hello Curly

```
[4]: def welcome2(name, age):  
      print(f'Hello {name}, you are {age} years old.')  
      welcome2("Moe", 31)  
      welcome2("Larry", 34)
```

Hello Moe, you are 31 years old.
Hello Larry, you are 34 years old.

```
[5]: # Default return value is "None"  
      return_value = welcome("Moe")  
      print(return_value)
```

Hello Moe
None

```
[7]: def sum(num1, num2):  
      return num1 + num2  
  
      print(sum(1,3))  
      print(sum(5,5))
```

4
10

```
[8]: newNumber = sum(5,5) * 5  
      print(newNumber)
```

50

```
[9]: # Create default argument  
      def sum2(num1=5, num2=10):  
          return num1 + num2  
  
      print(sum2(num2=1))
```

6

```
[11]: # Multiple arguments (data type tuple)  
      def sum3(*args):  
          total = 0  
  
          for num in args:  
              total += num  
  
          return total  
  
      print(sum3(2,2,2,2,5,5,23,2))
```

70

```
[13]: # multiple keyword arguments (data type dictionary)  
      def welcome3(**kwargs):  
          print(kwargs)  
  
      welcome3(name="Moe", age=31)
```

{'name': 'Moe', 'age': 31}

```
[ ]:
```