

## Add DDQ Rule Columns Through Office GUI

### Check RE\_CONTEXTDETAILS for Target Column

Query the RE\_CONTEXTDETAILS table for the target column

```
SELECT * FROM RE_CONTEXTDETAILS
WHERE CONTEXT_ID = 'PRM_DDQ_CTX'
```

If you do not see the target ATTR\_NAME in the results, use the below insert statement to add a new row into the RE\_CONTEXTDDELAIS table

```
INSERT INTO RE_CONTEXTDETAILS
(CONTEXT_ID, ATTR_NAME, DESCRIPTION, DATA_TYPE, CHAR_LENGTH, DATA_PRECISION, DATA_SCALE, VA
VALUES
('PRM_DDQ_CTX', 'DDQGRADE', 'Product Family for DDQ', 'VARCHAR2', 25, NULL, NULL, NULL, 'W
```

#### IMPORTANT

Make sure to change the values of the above insert statement to match the target column.

### Add Column Through Office GUI

- Open the Office GUI
- Navigate to Rule Management > Rules > DDQ Rules
- Click on the 'EditTableStructure' button  
Edit Table Structure
- Click on the 'New' button  
Table Columns
- Select an option from the 'Kind of column' dropdown menu  
Kind of Column
- Select a 'Column Type'  
Column Type
- Select the 'Context attribute' (begin to type 'cx' and you should see a list of context attributes)  
Context Attribute
- Enter a 'Position' number (row position in table)  
Position Number
- Enter a numeric value for 'Default column width'  
Default column width
- Click the 'OK' button  
OK
- Verify column has been added and is in the correct position  
Verify Column