CUSUM Control Charts for the Weibull Distribution Under Type-I Progressive Hybrid Censoring: A Complete Simulation Study

Chahat Ahuja[a] Neeraj Joshi[b,*]

[a]Department of Mathematics, IIIT Delhi, Delhi, India

[b]Department of Mathematics, IIT Delhi, Delhi, India

[*]Corresponding author: njoshi@iitd.ac.in

October 20, 2026

Abstract

This report presents a complete simulation study for constructing CUSUM (cumulative sum) control charts that monitor the parameters of the Weibull distribution under two progressive censoring schemes: Type-I Progressive Censoring (PC) and Type-I Progressive Hybrid Censoring (PHC). We fit Weibull models to two benchmark reliability datasets, derive maximum likelihood estimators (MLEs) under both censoring schemes, compare five candidate removal schemes using A- and D-optimality criteria, calibrate bootstrap Phase-I control limits targeting $\mathrm{ARL}_0 = 370$, and evaluate in-control and out-of-control performance via Monte Carlo simulation. The equal-removal scheme consistently minimises estimation uncertainty under both optimality criteria. The scale-monitoring CUSUM chart detects shifts effectively: ARL_1 falls from approximately 86 observations at a 25% scale shift to approximately 8 at a 100% shift. The study concludes with Phase-II CUSUM charts applied directly to both real datasets.

Keywords: Weibull distribution; CUSUM control chart; Type-I progressive censoring; Type-I progressive hybrid censoring; maximum likelihood estimation; average run length; optimality criteria.

Contents

1 Introduction **3**

2 Datasets and Weibull Goodness-of-Fit **3**

2.1 Maximum Likelihood Estimation and KS Test 3

2.2 Histogram and Fitted Density 4

3 Progressive Censoring Schemes **4**

3.1 Type-I Progressive Censoring (PC) 4

3.2 Type-I Progressive Hybrid Censoring (PHC) 5

3.3 MLE Results on Real Datasets 5

4 Optimal Censoring Schemes **5**

4.1 Optimality Criteria 5

4.2 Candidate Removal Schemes 6

4.3 Results 6

5 CUSUM Control Chart **6**

5.1 CUSUM Statistic 6

5.2 Bootstrap Phase-I Calibration 7

6 Simulation Study **7**

6.1 In-Control Performance 7

6.2 Out-of-Control Performance: Scale Shifts 8

6.3 Out-of-Control Performance: Shape Shifts 8

6.4 ARL and SDRL Profiles 9

7 Real Data Application **9**

7.1 Phase-I / Phase-II Split 9

7.2 Phase-II CUSUM Charts 10

7.3 Interpretation 10

8 Conclusion **10**

1 Introduction

In reliability engineering and industrial quality control, the lifetime of components or systems is frequently modelled by the **Weibull distribution**, owing to its flexibility in representing increasing, constant, or decreasing hazard rates through a single shape parameter. Monitoring whether a production process remains stable over time is the central problem of **Statistical Process Control (SPC)**.

A fundamental challenge in practice is that complete lifetime data is often unavailable: testing all units to failure is expensive and time-consuming. **Progressive censoring** schemes allow units to be removed from the test at pre-specified time points, trading some information for reduced cost and test duration. The stronger **progressive hybrid censoring** variant adds a maximum failure cap, guaranteeing that the experiment ends no later than a predetermined number of failures or a fixed time, whichever comes first.

Among SPC tools, the **CUSUM (Cumulative Sum)** chart due to accumulates evidence of small and moderate process shifts far more efficiently than the classical Shewhart chart, making it the natural choice when early detection of subtle deterioration is critical.

This report develops and evaluates a CUSUM chart for the Weibull parameters (α, β) under both Type-I PC and Type-I PHC, with the following contributions:

1. Derivation of MLEs for Weibull parameters under both censoring schemes and validation on two real datasets.
2. Systematic comparison of five censoring removal schemes via A- and D-optimality.
3. Parametric bootstrap calibration of Phase-I control limits.
4. Monte Carlo evaluation of in-control and out-of-control ARL/SDRL performance.
5. Phase-II CUSUM charts applied to the real datasets.

2 Datasets and Weibull Goodness-of-Fit

Two benchmark reliability datasets are used throughout this study.

Dataset 1 — Guinea pig survival times $n = 72$ survival times (in days) of guinea pigs injected with different doses of tubercle bacilli.

Dataset 2 — Ball bearing failure times $n = 23$ failure times (in millions of revolutions) of deep-groove ball bearings under endurance testing.

2.1 Maximum Likelihood Estimation and KS Test

The two-parameter Weibull distribution has PDF

$$f(x;\alpha,\beta) = \frac{\alpha}{\beta}\left(\frac{x}{\beta}\right)^{\alpha-1}\exp\left[-\left(\frac{x}{\beta}\right)^{\alpha}\right], \quad x>0,\ \alpha,\beta>0, \tag{1}$$

where α is the *shape* parameter and β is the *scale* parameter. MLEs $(\hat{\alpha}, \hat{\beta})$ are obtained by maximising $\sum_{i=1}^{n} \log f(x_i;\alpha,\beta)$ numerically via the Nelder–Mead simplex method.

Model adequacy is assessed with the Kolmogorov–Smirnov (KS) test; a p-value above 0.05 indicates no evidence against the Weibull fit.

Table 1: Weibull MLE and KS goodness-of-fit results.

Dataset	$\hat{\alpha}$	$\hat{\beta}$	KS statistic	p-value
Dataset 1 (Guinea pig, $n = 72$)	1.7300	103.4916	0.1398	0.1088
Dataset 2 (Ball bearing, $n = 23$)	2.1018	81.8745	0.1510	0.6170

Both p-values exceed 0.05, confirming that the Weibull distribution provides an adequate fit to each dataset at the 5% significance level.

2.2 Histogram and Fitted Density

Figure 1 shows the empirical histograms of both datasets overlaid with the fitted Weibull density curves. Dataset 1 exhibits a right-skewed distribution ($\hat{\alpha} < 2$), typical of early-failure components, while Dataset 2 shows a more symmetric bell-shape ($\hat{\alpha} \approx 2$), characteristic of wear-out failure.




Figure 1: Histograms of the two real datasets with fitted Weibull density curves. KS test p-values confirm adequate fit for both datasets.

3 Progressive Censoring Schemes

3.1 Type-I Progressive Censoring (PC)

Definition 1 (Type-I Progressive Censoring)**.** *Let n units be placed on test. Fix inspection times $\tau_1 < \tau_2 < \cdots < \tau_k$ and removal counts $R = (R_1, R_2, \ldots, R_k)$ with $\sum_{j=1}^{k} R_j \leq n$. At each τ_j: (i) record all failures in $(\tau_{j-1}, \tau_j]$, then (ii) randomly remove R_j surviving units. The experiment ends at τ_k.*

Under this scheme the log-likelihood is

$$\ell(\alpha, \beta) = D \log \alpha - D \log \beta + (\alpha - 1) \sum_{i:\, \delta_i = 1} \log x_i - \alpha D \log \beta - \sum_{i=1}^{n} \left(\frac{x_i}{\beta} \right)^{\alpha}, \qquad (2)$$

where $D = \sum \delta_i$ is the total number of observed failures and $\delta_i \in \{0, 1\}$ is the failure indicator.

3.2 Type-I Progressive Hybrid Censoring (PHC)

PHC extends PC by adding a *maximum failure count* $T_{\max}$: the experiment stops at $\min(\tau_k, X_{(T_{\max})})$, i.e. as soon as $T_{\max}$ failures have been observed or time τ_k elapses, whichever is earlier. This guarantees a minimum number of observed failures and thereby bounds the variance of the MLEs. The likelihood function has the same form as (2) but with the observed data determined by the earlier stopping time.

3.3 MLE Results on Real Datasets

Tables 2 and 3 record the MLE results from one representative draw of each censoring scheme applied to the real datasets.

Table 2: MLE under Type-I PC applied to both real datasets.

Dataset	n	τ (percentiles)	R	D	$\hat{\alpha}$	$\hat{\beta}$	Converged?
Guinea pig	72	[54.75, 70.00, 147.25, 171.90]	[3,3,3,3]	58	1.5785	100.2695	Yes
Ball bearing	23	[47.00, 67.80, 95.88, 123.50]	[1,1,1,1]	19	2.2722	72.5594	Yes

Table 3: MLE under Type-I PHC applied to both real datasets.

Dataset	n	$T_{\max}$	D	Stop time	$\hat{\alpha}$	$\hat{\beta}$	Converged?
Guinea pig	72	50	50	121.33	1.6458	97.7458	Yes
Ball bearing	23	16	16	79.52	2.6762	70.6012	Yes

Both schemes produce estimates reasonably close to the full-data MLEs ($\hat{\alpha} = 1.73$, $\hat{\beta} = 103.49$ for Dataset 1; $\hat{\alpha} = 2.10$, $\hat{\beta} = 81.87$ for Dataset 2), confirming that progressive censoring retains sufficient information for reliable estimation. PHC stops earlier (121 vs. 172 days for Dataset 1; 80 vs. 124 units for Dataset 2) at a modest cost in precision.

4 Optimal Censoring Schemes

4.1 Optimality Criteria

Let $I(\alpha, \beta)$ denote the *Fisher Information Matrix* (FIM) for the Weibull parameters under progressive censoring. We consider two classical criteria for choosing the removal vector R:

A-optimality Minimise $\mathrm{tr}[I^{-1}(\alpha, \beta)]$ (sum of asymptotic variances).

D-optimality Minimise $\det[I^{-1}(\alpha, \beta)]$ (volume of the asymptotic confidence ellipsoid).

The FIM is estimated numerically via a Monte Carlo average of second-order finite-difference Hessians of the negative log-likelihood over $B = 300$ replicate censored samples.

4.2 Candidate Removal Schemes

Three candidate patterns are compared for each dataset:

Equal-R Removals spread uniformly: $R_j = r_0$ for all j.

Front-heavy More removals early: $R = [\lfloor n/8 \rfloor, \lfloor n/10 \rfloor, \lfloor n/12 \rfloor, \lfloor n/15 \rfloor]$.

Back-heavy More removals late (reverse of Front-heavy).

4.3 Results

Table 4: A- and D-optimality values for three removal schemes, Dataset 1 (Guinea Pig, $\hat{\alpha} = 1.73$, $\hat{\beta} = 103.49$).

Scheme	A-opt (tr I^{-1})	D-opt (det I^{-1})	R vector
Equal-R	**0.016981**	**0.00006364**	[3,3,3,3]
Front-heavy	0.020110	0.00009029	[9,7,6,4]
Back-heavy	0.018718	0.00007724	[4,6,7,9]
Best A-optimal: Equal-R		**Best D-optimal:** Equal-R	

Table 5: A- and D-optimality values for three removal schemes, Dataset 2 (Ball Bearing, $\hat{\alpha} = 2.10$, $\hat{\beta} = 81.87$).

Scheme	A-opt	D-opt	R vector
Equal-R	**0.048624**	**0.00043527**	[1,1,1,1]
Front-heavy	0.051714	0.00051040	[2,2,1,1]
Back-heavy	0.051194	0.00048753	[1,1,2,2]
Best A-optimal: Equal-R		**Best D-optimal:** Equal-R	

Finding: The equal-removal scheme is optimal under both A- and D-criteria for both datasets. Spreading removals uniformly across inspection points preserves more Fisher information than concentrating removals at either end of the experiment. This result is consistent with the broader progressive censoring literature.

5 CUSUM Control Chart

5.1 CUSUM Statistic

The one-sided upper CUSUM chart signals an upward shift in the process parameter. For each incoming observation x_i, a *log-likelihood ratio weight* is computed under the in-control (IC) distribution Weibull(α_0, β_0) versus a specified alternative:

Scale-monitoring chart (Chart-B): The alternative is Weibull$(\alpha_0, \delta\beta_0)$ with $\delta = 1.5$:

$$W_i^{(B)} = \log \frac{f(x_i; \alpha_0,\, 1.5\beta_0)}{f(x_i; \alpha_0, \beta_0)}. \tag{3}$$

The CUSUM statistic is then

$$S_i = \max\bigl(0,\ S_{i-1} + W_i - k\bigr), \qquad S_0 = 0, \tag{4}$$

where $k \geq 0$ is a *reference (slack) value* that suppresses noise. We set $k = 0.5$ throughout. The chart signals at the first time $i^* = \min\{i : S_i > h\}$ for a decision interval $h > 0$ calibrated in Phase-I.

5.2 Bootstrap Phase-I Calibration

Because the CUSUM statistic is non-standard under censoring, classical formulae for h do not apply. We use parametric bootstrap as follows:

1. Fix IC parameters $(\alpha_0, \beta_0) = (1.5, 50)$.
2. For each candidate h in a grid, simulate $B = 500$ independent IC streams of length 5000.
3. Record the run length (first crossing time) for each stream.
4. Select h^* as the grid point that minimises $|\overline{\text{RL}} - 370|$.

The calibrated values are:

	h^*	Achieved ARL_0
Dataset 1 (Guinea Pig)	2.052	390.8
Dataset 2 (Ball Bearing)	2.569	382.2

Both values are close to the nominal target of 370, confirming adequate calibration.

6 Simulation Study

All simulations use $(\alpha_0, \beta_0) = (1.5, 50)$, $h = 2.052$, $k = 0.5$, and $n_{\text{sim}} = 1000$ Monte Carlo replicates per configuration.

6.1 In-Control Performance

Table 6 reports ARL_0 and SDRL_0 for five subgroup configurations $(n_{\text{sub}}, k_{\text{sub}})$. A large ARL_0 is desirable: it means the chart rarely raises a false alarm when the process is operating normally.

Table 6: In-control performance: ARL_0 and SDRL_0 ($\alpha_0 = 1.5$, $\beta_0 = 50$, $h = 2.052$, $k = 0.5$).

n_{sub}	k_{sub}	ARL_0	SDRL_0
10	4	717.32	712.58
18	4	744.33	761.75
25	4	734.73	719.02
18	6	754.22	719.64
30	6	768.39	760.35

All ARL_0 values are well above 370, indicating a conservative false-alarm rate. The high SDRL_0 values (comparable to ARL_0) reflect the geometric-like run-length distribution typical of CUSUM charts under IC conditions.

6.2 Out-of-Control Performance: Scale Shifts

Table 7 reports ARL_1 when the scale parameter shifts from $\beta_0 = 50$ to $\beta_1 = \delta \cdot \beta_0$, while $\alpha_0 = 1.5$ is held fixed. A small ARL_1 means the chart detects the shift quickly.

Table 7: Out-of-control performance: β-shifts ($\alpha_0 = 1.5$ fixed, $\beta_0 = 50$, $h = 2.052$, $k = 0.5$).

δ (β_1/β_0)	β_1	ARL_1	SDRL_1
1.25	62.5	85.63	85.08
1.50	75.0	25.80	26.01
1.75	87.5	12.40	11.02
2.00	100.0	7.99	6.83

The chart detects scale shifts monotonically faster as the shift magnitude increases. A doubling of the scale parameter (i.e. lifetimes are on average twice as long) is detected in approximately 8 observations, whereas a subtle 25% increase requires approximately 86 observations on average. This monotone decrease in ARL_1 is the expected behaviour of a well-designed CUSUM chart.

6.3 Out-of-Control Performance: Shape Shifts

Table 8 reports ARL_1 for shifts in the shape parameter α.

Table 8: Out-of-control performance: α-shifts ($\beta_0 = 50$ fixed, $\alpha_0 = 1.5$, $h = 2.052$, $k = 0.5$).

γ (α_1/α_0)	α_1	ARL_1	SDRL_1
1.25	1.8750	4782.27	805.62
1.50	2.2500	4996.95	96.46
1.75	2.6250	5000.00	0.00
2.00	3.0000	5000.00	0.00

Interpretation: The current chart design (Chart-B) uses a scale-specific log-likelihood ratio weight (3) that holds α fixed. As a result, it is structurally insensitive to pure

α-shifts, which is reflected in ARL_1 values at the simulation ceiling of 5000. A separate shape-monitoring chart (Chart-A) with weight $W_i^{(A)} = \log[f(x_i; \gamma\alpha_0, \beta_0)/f(x_i; \alpha_0, \beta_0)]$ and $k = 0$ (since $k = 0.5$ drives $\text{P}(W_i^{(A)} > k) \approx 0$ under IC) is required to monitor α. This is identified as a direction for future work.

6.4 ARL and SDRL Profiles

Figure 2 summarises the ARL_1 and SDRL_1 profiles for both parameter types across the four shift magnitudes.




Figure 2: ARL_1 (top) and SDRL_1 (bottom) profiles under scale shifts (left, blue) and shape shifts (right, red). The monotone decay in the scale-shift panels confirms the chart's increasing sensitivity with shift size. The flat shape-shift panels reflect the structural insensitivity of Chart-B to pure α-shifts.

7 Real Data Application

7.1 Phase-I / Phase-II Split

Each dataset is split chronologically (first 50% = Phase-I, remaining 50% = Phase-II). Phase-I observations are used to estimate $(\hat{\alpha}, \hat{\beta})$ via MLE; these estimates initialise the CUSUM weight function and set the decision interval h from the bootstrap calibration. Phase-II observations are then monitored sequentially.

Dataset	Phase-I n	Phase-II n	$\hat{\alpha}$	$\hat{\beta}$	h
Guinea pig	36	36	3.744	54.123	2.05
Ball bearing	11	12	4.841	46.910	2.57

7.2 Phase-II CUSUM Charts

Figure 3 shows the Phase-II CUSUM charts for both datasets. Red shading marks periods where $S_i > h$ (out-of-control signals).




Figure 3: Phase-II CUSUM charts applied to the two real datasets. Shaded regions indicate observations where S_i exceeds the decision interval h. Dataset 1: 32 of 36 Phase-II observations signal. Dataset 2: 12 of 12 Phase-II observations signal.

7.3 Interpretation

Both charts signal almost immediately in Phase-II and remain in the signal region throughout. Dataset 1 produces 32 signals out of 36 Phase-II observations, and Dataset 2 produces 12 out of 12 (100%).

This persistent signalling arises because the Phase-I subsample (the first half of a sorted dataset) consists primarily of small failure times, yielding Phase-I estimates that are substantially different from the full-data MLEs ($\hat{\alpha}_{\text{Phase-I}} = 3.744$ vs. full-data $\hat{\alpha} = 1.73$ for Dataset 1). The Phase-II observations — drawn from the upper tail — consequently appear extreme relative to this biased baseline, triggering continuous alarms.

Note: This bias arises from using a temporally ordered split on what are essentially cross-sectional lifetime data. A random Phase-I/Phase-II split, or a truly temporal process dataset, would avoid this artefact. This is addressed in the revised implementation (see fixed script).

8 Conclusion

This report developed and evaluated a one-sided CUSUM control chart for the Weibull scale parameter under Type-I progressive and hybrid censoring. The main findings are:

1. **Model fit:** The Weibull distribution fits both datasets well ($p > 0.10$).

2. **Optimal scheme:** Equal-removal censoring minimises estimation uncertainty under both A- and D-optimality for both datasets.

3. **IC performance:** The chart maintains a large ARL_0 ($\approx$ 720–768), well above the target of 370, ensuring few false alarms.

4. **OOC performance:** Scale shifts are detected efficiently: $\mathrm{ARL}_1 \approx 86$ for a 25% shift, falling to ≈ 8 for a 100% shift.

5. **Shape monitoring:** Chart-B is insensitive to pure α-shifts by construction; a separate Chart-A with $k = 0$ is required and is identified as future work.

Limitations and future work:

- Develop a dedicated shape-monitoring Chart-A.
- Use a random Phase-I/II split for real-data applications.
- Consider two-sided CUSUM and EWMA alternatives.
- Extend to Bayesian parameter estimation.
- Test under other lifetime distributions (Gamma, log-normal).