

- Here are N_α and β , the 2 matrices we start with. They represent two matroids. The p —s & e —s, unhatted and hatted forms, are ground set elements. But for now, think of the row spaces.
- From each matrix we make an exterior algebra element, denoted in boldface, to represent its row space.
- We construct a Tutte Function L of those two elements by a kind of bilinear pairing ... N_α bar N_β :
- But this bilinear function has exterior algebra, not field or ring values.
- Result 1 is that L , as a function of N_α & N_β obeys Tutte's deletion and contraction identity: BUT only for e type elements, not the p 's.
- I omit the direct sum identity, but its product is exterior, not commutative ring product.
- We have TO CAREFULLY DEFINE the exterior algebra operations for deletion & contraction & direct sum so the signs in L 's expansion are consistent.
- Here's some more background.
- As pure, ... or indecomposable anti-symmetric tensors, ... that is products of vectors, the boldface N —s represent linear subspaces of the big space generated by matroid ground set elements and their hatted copies.
- Having a basis related to ground set elements, we will in a moment consider the unhatted and hatted versions to be vector duals.
- So, N_α & N_β represent points in the Grassmannian, and have Plucker coordinates.
- The Plucker coordinates are the maximal minors of the matrices.
- So, the matroid bases are encoded by which Plucker coordinates are non-zero.
- I multiply each column's boldface symbol with its entries.
- What are the boldface N s? They are the exterior products of the row sums.
- Finally to get L I use the bilinear pairing on the two N —s.

- I find it interesting that, ... in order to get a Tutte function out of this, it seems require two special things.
- One is to make the Tutte function relative, ... to the set of ports P .
- We need that in order to get a non-trivial exterior algebra value because the e — s disappear when they are contracted or deleted.
- I like to call the distinguished elements ports. ... We never delete or contract them.
- In applications, ports relate to variables used to specify inputs or parameters, ... like how much you push on a node with force or an electric current, and responses, ... like how much every node moves, or changes its voltage.
- Two, it seems this exterior algebra Tutte function needs to be constructed using two arguments, which I labelled α & β .
- We recover the basis enumerator when the two are equal and P is empty. It is the sum of squared determinants though, not always ones.
- Now for the final step.
- To define the final bilinear pairing function we distinguish four kinds of generators:
vector e 's, vector p 's and dual vector \hat{e} hats and \hat{p} hats.
- It's defined here *WITH* these rules for algebra basis monomials. Covectors on the left kind act on vectors on the right, but reverse that ... and they behave like anticommutative scalars.
- I found this very recently, ... an algebra valued, not scalar valued bilinear function on tensors or their relatives. I'd appreciate any pointers. I also must ask some physicists.
- I call L -s construction the Cauchy-Binet form because of the expansion in result 2.
- A while ago I defined L from N_α , and the DUAL of N_β .
- I took their exterior product and then contracted all of E ...and called it the Laplace form.
- I'll finish with some take-homes and morals, and my name, Seth Chaiken, which I'll leave for you to read at your own pace. Thank you!