

- Here N_α and β , the 2 matrices we start with. They represent two matroids. The p —s & e —s are ground set elements. But think of the row spaces for now.
- We make two exterior algebra elements to represent those row spaces: boldface N_α & N_β .
- We construct a Tutte Function L of those two things by a kind of bilinear pairing N_α bar N_β :
- But this bilinear function has exterior algebraic, not field or ring values.
- Result 1 is that L , as a function of pair N_α & N_β obeys result ONE, Tutte's deletion and contraction identity: BUT only for e type elements, not the p 's.
- I omit the direct sum identity, but its product is exterior, not commutative ring product.
- We have TO CAREFULLY DEFINE the exterior algebra operations for deletion & contraction & direct sum so the signs in L 's expansion are consistent.
- Here's some more background.
- As pure, ... or indecomposable anti-symmetric tensors, ... that is products of vectors, the boldface N s represent linear subspaces over the basis comprised of the matroids' ground sets.
- The ground elements correspond to the boldface p & e vectors, ... or dual vectors when they have hats.
- So, N_α & N_β represent points in the Grassmannian, and have Plucker coordinates.
- The Plucker coordinates are the maximal minors of the matrices.
- So, the matroid bases are encoded by which Plucker coordinates are non-zero.
- I multiply a column's boldface symbol with every numeric entry.
- What are the boldface N s? They are the exterior products of the row sums.
- Finally to get L I use the bilinear pairing on the two N s.

- I find it interesting that, ... in order to get a Tutte function out of this, it seems require two special things.
- One is to make the Tutte function relative, ... to the set of ports P .
- We need that in order to get a non-trivial exterior algebra for the Tutte function values to live in.
- The e — s disappear when they are contracted or deleted.
- I like to call the distinguished elements ports. ... We never delete or contract them.
- Those port elements in the exterior algebra are vectors, and the hatted ones are covectors, ie., 1-forms or dual vectors.
- In applications, ports relate to variables used to specify inputs or parameters, ... like how much you push on a node with force or an electric current, and responses, ... like how much every node moves, or change its voltage.
- Two, it seems the Tutte function needs pairs, $N_\alpha \dots N_\beta$.
- We recover the basis enumerator with P empty and $N_\alpha \dots N_\beta$.
- The bilinear pairing in the final step to construct L ... is defined after distinguishing four kinds of generators:
vector e 's, vector p 's and dual vector \hat{e} hats and \hat{p} hats.
- It's defined on the slide *WITH* these rules for algebra basis monomials.
- I found this very recently, ... a pairing that should return algebra values instead of ring values. I'd appreciate pointers if anyone recognizes something like it.
- I call L '— s construction the Cauchy-Binet form because of the expansion in result 2.
- A while ago I defined L from N_α , and the DUAL of N_β .
- I took their exterior product and then contracted all of E ...and called it the Laplace form.
- I'll finish with some take-homes and morals, and my name, Seth Chaiken, which I'll leave for you to read at your own pace. Thank you!