



Rapport d'audit de sécurité

CyberScan — Analyse automatisée multi-outils

■ Informations générales

Domaine analysé	alibaba.com
Date du scan	16/07/2026 15:27
Score global de sécurité	2.0/10
Score de risque IA	8.0/10
Niveau de risque	Critique
Identifiant scan	55

NIVEAU DE RISQUE : CRITIQUE | Sécurité 2.0/10 | Risque IA 8.0/10

■ Résumé exécutif

Ce rapport présente les résultats de l'audit de sécurité automatisé réalisé par CyberScan sur le domaine « alibaba.com » le 16/07/2026 à 15:27 (UTC). Le score global de sécurité est estimé à 2.0/10, correspondant à un niveau de risque « Critique » (score de risque IA : 8.0/10). Synthèse : 41 CVE référencée(s), 2 indicateur(s) SSL/TLS, 4 protocole(s) détecté(s), 17 technologie(s) web, 0 alerte(s) OWASP ZAP, 40 résultat(s) NVD. Des vulnérabilités critiques ou un score de risque élevé nécessitent une remédiation prioritaire. Consultez les sections CVE et Recommandations.

■ Résultats SSLScan

Protocoles : TLSv1.0, TLSv1.1, TLSv1.2, TLSv1.3. Vulnérabilités SSL : TLSv1.1, TLSv1.0.

```
Version: [32m2.1.5[0m
OpenSSL 3.5.6 7 Apr 2026
[0m
[32mConnected to 47.246.136.156[0m

Testing SSL server [32malibaba.com[0m on port [32m443[0m using SNI name [32malibaba.com[0m

[1;34mSSL/TLS Protocols:[0m
SSLv2 [32mdisabled[0m
SSLv3 [32mdisabled[0m
TLSv1.0 [33menabled[0m
TLSv1.1 [33menabled[0m
TLSv1.2 enabled
TLSv1.3 [32menabled[0m

[1;34mTLS Fallback SCSV:[0m
Server [32msupports[0m TLS Fallback SCSV

[1;34mTLS renegotiation:[0m
[32mSecure[0m session renegotiation supported

[1;34mTLS Compression:[0m
Compression [32mdisabled[0m

[1;34mHeartbleed:[0m
```

```

TLsv1.3 ■[32mnot vulnerable■[0m to heartbleed
TLsv1.2 ■[32mnot vulnerable■[0m to heartbleed
TLsv1.1 ■[32mnot vulnerable■[0m to heartbleed
TLsv1.0 ■[32mnot vulnerable■[0m to heartbleed

■[1;34mSupported Server Cipher(s):■[0m
■[32mPreferred■[0m ■[32mTLSv1.3■[0m ■[32m256■[0m bits ■[32mTLS_AES_256_GCM_SHA384 ■[0m Curve
■[32m25519■[0m DHE 253
Accepted ■[32mTLSv1.3■[0m ■[32m128■[0m bits ■[32mTLS_AES_128_GCM_SHA256 ■[0m Curve ■[32m25519■[0m DHE 253
Accepted ■[32mTLSv1.3■[0m ■[32m256■[0m bits ■[32mTLS_CHACHA20_POLY1305_SHA256 ■[0m Curve ■[32m25519■[0m DHE
253
■[32mPreferred■[0m TLSv1.2 ■[32m128■[0m bits ■[32mECDHE-ECDSA-AES128-GCM-SHA256■[0m Curve ■[32m25519■[0m
DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ■[32mECDHE-ECDSA-AES256-GCM-SHA384■[0m Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m128■[0m bits ECDHE-ECDSA-AES128-SHA256 Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ECDHE-ECDSA-AES256-SHA384 Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m128■[0m bits ■[32mECDHE-RSA-AES128-GCM-SHA256 ■[0m Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ■[32mECDHE-RSA-AES256-GCM-SHA384 ■[0m Curve ■[32m25519■[0m DHE 253

Accepted TLSv1.2 ■[32m128■[0m bits ECDHE-RSA-AES128-SHA256 Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ECDHE-RSA-AES256-SHA384 Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m128■[0m bits AES128-GCM-SHA256
Accepted TLSv1.2 ■[32m256■[0m bits AES256-GCM-SHA384
Accepted TLSv1.2 ■[32m128■[0m bits AES128-SHA256
Accepted TLSv1.2 ■[32m256■[0m bits AES256-SHA256
Accepted TLSv1.2 ■[32m128■[0m bits ECDHE-ECDSA-AES128-SHA Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ECDHE-ECDSA-AES256-SHA Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m128■[0m bits ECDHE-RSA-AES128-SHA Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m256■[0m bits ECDHE-RSA-AES256-SHA Curve ■[32m25519■[0m DHE 253
Accepted TLSv1.2 ■[32m128■[0m bits AES128-SHA
Accepted TLSv1.2 ■[32m256■[0m bits AES256-SHA
■[32mPreferred■[0m ■[33mTLSv1.1■[0m ■[32m128■[0m bits ECDHE-ECDSA-AES128-SHA Curve ■[32m25519■[0m DHE 253
Accepted ■[33mTLSv1.1■[0m ■[32m256■[0m bits ECDHE-ECDSA-AES256-SHA Curve ■[32m25519■[0m DHE 253
Accepted ■[33mTLSv1.1■[0m ■[32m128■[0m bits ECDHE-RSA-AES128-SHA Curve ■[32m25519■[0m DHE 253
Accepted ■[33mTLSv1.1■[0m ■[32m256■[0m bits ECDHE-RSA-AES256-SHA Curve ■[32m25519■[0m DHE 253
Accepted ■[33mTLSv1.1■[0m ■[32m128■[0m bits AES128-SHA
Accepted ■[33mTLSv1.1■[0m ■[32m256■[0m bits AES256-SHA
■[32mPreferred■[0m ■[33mTLSv1.0■[0m ■[32m128■[0m bits ECDHE-ECDSA-AES128-SHA Curve ■[3
[... sortie tronquée pour lisibilité du rapport ...]

```

■ Résultats OpenSSL

```

Connecting to 47.246.136.156
depth=2 OU=GlobalSign Root CA - R3, O=GlobalSign, CN=GlobalSign
verify return:1
depth=1 C=BE, O=GlobalSign nv-sa, CN=GlobalSign GCC R3 OV TLS CA 2024
verify return:1
depth=0 C=CN, ST=ZheJiang, L=HangZhou, O=Alibaba (China) Technology Co., Ltd., CN=*.alibaba.com
verify return:1
CONNECTED(00000003)
---
Certificate chain
0 s:C=CN, ST=ZheJiang, L=HangZhou, O=Alibaba (China) Technology Co., Ltd., CN=*.alibaba.com
i:C=BE, O=GlobalSign nv-sa, CN=GlobalSign GCC R3 OV TLS CA 2024
a:PKEY: EC, (prime256v1); sigalg: sha256WithRSAEncryption
v:NotBefore: Mar 16 11:57:07 2026 GMT; NotAfter: Oct 1 11:51:17 2026 GMT
1 s:C=BE, O=GlobalSign nv-sa, CN=GlobalSign GCC R3 OV TLS CA 2024
i:OU=GlobalSign Root CA - R3, O=GlobalSign, CN=GlobalSign
a:PKEY: RSA, 2048 (bit); sigalg: sha256WithRSAEncryption
v:NotBefore: Sep 18 03:14:38 2024 GMT; NotAfter: Mar 18 00:00:00 2029 GMT
2 s:OU=GlobalSign Root CA - R3, O=GlobalSign, CN=GlobalSign
i:C=BE, O=GlobalSign nv-sa, OU=Root CA, CN=GlobalSign Root CA
a:PKEY: RSA, 2048 (bit); sigalg: sha256WithRSAEncryption
v:NotBefore: Sep 19 00:00:00 2018 GMT; NotAfter: Jan 28 12:00:00 2028 GMT
---
Server certificate
-----BEGIN CERTIFICATE-----
MIIsGDCCkWcGAWIBAgIMQfzmEOTTo+SP+hKa+MA0GCSqGSIB3DQEBCwUAMFMxCzAJ
BgNVBAYTAkFJMRkwFwYDVQQKEgBhG9iYXNjaWwTaWduIG52LXNhMMSkwJwYDVQQDEyBH
bG9iYXNjaWwTaWduIEEdDQYBSMyBPVviBUTFMgQ0EgMjAyNDAAeFw0yNjAzMTYxMTU3MDda
Fw0yNjEwMDExMTUxMTU3MDdaMHoxCzAJBgNVBAYTAkNOMREwDwYDVQIEWhaaGVKawFu
ZzERMA8GA1UEBXMISGFuZ1pob3UxLTARBgNVBAoTJEFSaWJhYmEgKENoaW5hKSBU

```

ZWNobm9sb2d5IENvLiwgTHRKLjEwMBQGA1UEAwNKi5hbGlicWJhLmNvbTBZMBMG
ByqGSM49AgEGCCqGSM49AwEHA0IABHJi1Q8aS70yR0vvGK7kw9GIW5Wyp6hs2ISh
wKRWyKkLHmVbQMY4YAT8TLEiXrtNNBPCscQM4yVmJBRmuyswC8+jgim0MIipijAO
BgNVHQ8BAF8EBAMCB4AwDAYDVROTAQH/BAIwADCBkwYIKwYBBQUHAQEegYYwgYmW
RgYIKwYBBQUHMAKG0mh0dHA6Ly9zZWZWN1cmUuZ2xvYmFsc2lnbi5jb20vY2FjZXJ0
L2dzZ2NjcjNvdnRsc2NhMjAyNC5jcnQwOQYIKwYBBQUHAGGLWh0dHA6Ly9vY3Nw
Lmdsb2JhbHNpZ24uY29tL2dzZ2NjcjNvdnRsc2NhMjAyNDhBZG9vY3NwY3NwY3Nw
BmeBDAECAjBCBgorBgEEAAyCgECMDQwMgYIKwYBBQUHAgEwJmh0dHBzO18vd3d3
Lmdsb2JhbHNpZ24uY29tL2dzZ2NjcjNvdnRsc2NhMjAyNDhBZG9vY3NwY3NwY3Nw
dHA6Ly9jcmwuZ2xvYmFsc2lnbi5jb20vY3NnY2NmY292dGxzy2EyMDI0LmNybdCC

JlQGA1UdEQSCJkswgizHgg0qLmFsaWJhYmEuY29tghJndy5hcGkuYwXpYmFiYS5j
b22CE20uZHV0Y2guYwXpYmFiYS5jb22CGG0uaw5kb25lc2lhb25hbGlicWJhLmNv
bYIYc2VydmljZS5ibHVLmFsaWJhYmEuY29tghUqLjEwZS5hbGlicWJhLWluYy5j
b22CEyouNC5hbGlicWJhLWluYy5jb22CHyouYwFzLWVocC1kYXRhLXNlcnZpY2Uu
Yw1hcC5jb22CFcouYwQuYwXpYmFiYS1pbmMuY29tghAqLmFkZS50YW9iYW8ub3Jn
ghMqLmFkbWluLmFsaWJhYmEuY29tghQqLmFkbWluLmNoZWppamlhLmNvbYIUki5h
ZS5hbGlicWJhLWluYy5jb22CEyouYw0ZWN0LWRldmVsb3AuY26CEcouYwkuYwXp
YmFiYS5jb22CFsouYwLjBjB22CEyouYw0ZWN0LWRldmVsb3AuY26CEcouYwkuYwXp
b22CFcouYwLsYwJzLmFsaWJhYmEuY29tgiEqLmFsZ28tc2VydmlvYyBGVzcy5jYwlu
awFvLWluYy5jb22CEcouYwXpLWlyYw0aC5jb22CHcouYwXpY29tLW1jb25hbGlicW
JhLWluYy5jb22CGcouYwXpZxhwcmVzcy5hbGlicWJhLmNvbYIbKi5hbGloZWFs
dGguYwXpYmFiYS1pbmMuY29tggsqlmFsaWprLmNvbYIwKi5hbGltZWJvdC5hbGlicW
JhLmNvbYIdKi5hbGlib2RlLXByZS5hbGlicWJhLWluYy5jb22CGsouYwXpbm9k
ZS5hbGlicWJhLWluYy5jb22CFcouYwXpcGF5LmtlcnV5dW4uY29tghwqLmFsaXBz
cG9ydHMuYwXpYmFiYS1pbmMuY29tghcqlmFsaXNwb3J0cy5hbGlicWJhLmNvbYIV
Ki5hbGloYwXrLmFsaWJhYmEuY29tgg4qLmFsaXZlY2RuLmNvbYITKi5hbGlicWJhLmNv
bGlicWJhLmNvbYIRKi5hbGlicWJhLWluYy5jb22CEiouYwXzyYy5hbGlicWJhLmNv
bYINKi5hbHNjLmVsZS5tZiYQKi5hbHRhLmVsZW5ldC5tZiYISKi5hbHd4LmFsaWJh
YmEuY29tghYqLmFtYXAuYwXpYmFiYS1pbmMuY29tghAqLmFtcy50YW9iYW8ub3Jn
ghYqLmFuYw5c2lZLmFsaWJhYmEuY29tghQqLmFwb2xsby5hbGlicWJhLmNvbYIO

[... sortie tronquée pour lisibilité du rapport ...]

■ Résultats Nmap

Starting Nmap 7.95 (<https://nmap.org>) at 2026-07-16 16:22 CET
Nmap scan report for alibaba.com (47.246.136.52)
Host is up (0.21s latency).
Other addresses for alibaba.com (not scanned): 47.246.131.198 47.246.137.105 47.246.136.156
Skipping host alibaba.com (47.246.136.52) due to host timeout
Nmap done: 1 IP address (1 host up) scanned in 16.82 seconds

■ Résultats WhatWeb

- Alibaba-Aliyun
- Cookies (ali_apache_id, JSESSIONID, cna)
- Country (CANADA, UNITED STATES)
- HTTPServer (Tengine)
- IP (47.246.137.105, 184.25.54.189)
- PoweredBy (Tengine, AI)
- RedirectLocation (<https://www.alibaba.com/>)
- Strict-Transport-Security (max-age=31536000)
- Tengine-Web-Server
- Title (301 Moved Permanently, Alibaba.com: Manufacturers, Suppliers, Exporters & Importers from the world's largest online B2B marketplace)
- UncommonHeaders
 - (ups-target-key,x-protocol,eagleeye-traceid,s-brt,alt-svc,s-rt,timing-allow-origin,eagleid,server-timing, link,x-content-type-options,ups-target-key,x-protocol,eagleeye-traceid,s-brt,s-rt,timing-allow-origin,eagleid,server-timing,alt-svc,object-status,edge-type)
 - HTML5
 - HttpOnly (JSESSIONID)
 - Java
 - Open-Graph-Protocol (v=site)
 - Script (application/ld+json, text/javascript)
 - X-Frame-Options (DENY)

■ Résultats OWASP ZAP

ZAP désactivé

■ Résultats SSL Labs API

SSL Labs non inclus dans ce scan. Les résultats SSL Labs apparaîtront ici lorsqu'ils seront présents dans `resultats_ssl["ssllabs"]`.

■ Résultats NVD API

Statut NVD : Erreur

Nombre de CVE NVD : 40

Erreurs : Limite NVD publique atteinte; configurez `NVD_API_KEY` pour rechercher les autres technologies.

- CVE-1999-0241 – CVSS 10.0 (HIGH) – Guessable magic cookies in X Windows allows remote attackers to execute commands, e.g. through xterm.
- CVE-1999-0809 – CVSS 5.0 (MEDIUM) – Netscape Communicator 4.x with Javascript enabled does not warn a user of cookie settings, even if they have selected the option to "Only accept cookies originating from the same server as the page being viewed".
- CVE-2000-0439 – CVSS 2.6 (LOW) – Internet Explorer 4.0 and 5.0 allows a malicious web site to obtain client cookies from another domain by including that domain name and escaped characters in a URL, aka the "Unauthorized Cookie Access".
- CVE-2001-1086 – CVSS 7.5 (HIGH) – XDM in XFree86 3.3 and 3.3.3 generates easily guessable cookies using `gettimeofday()` when compiled with the `HasXdmAuth` option, which allows remote attackers to gain unauthorized access to the X display.
- CVE-2001-0972 – CVSS 10.0 (HIGH) – Surf-Net ASP Forum before 2.30 uses easily guessable cookies based on the UserID, which allows remote attackers to gain administrative privileges by calculating the value of the admin cookie (UserID 1).
- CVE-2001-0962 – CVSS 7.5 (HIGH) – IBM WebSphere Application Server 3.02 through 3.53 uses predictable session IDs for cookies, which allows remote attackers to gain privileges of WebSphere users via brute force guessing.
- CVE-2001-0658 – CVSS 7.5 (HIGH) – Cross-site scripting (CSS) vulnerability in Microsoft Internet Security and Acceleration (ISA) Server 2000 allows remote attackers to cause other clients to execute certain script or read cookies via a crafted URL.
- CVE-2001-0723 – CVSS 6.4 (MEDIUM) – Internet Explorer 5.5 and 6.0 allows remote attackers to read and modify user cookies via Javascript, aka the "Second Cookie Handling Vulnerability".
- CVE-2001-0897 – CVSS 5.0 (MEDIUM) – Cross-site scripting vulnerability in Infopop Ultimate Bulletin Board (UBB) before 5.47e allows remote attackers to steal user cookies via an `[IMG]` tag that references an about: URL with an onerror event handler.
- CVE-2001-0898 – CVSS 5.0 (MEDIUM) – Opera 6.0 and earlier allows remote attackers to access sensitive information such as cookies and links for other domains via Javascript that uses `setTimeout` to (1) access data after a new window is opened.
- CVE-2003-1268 – CVSS 7.5 (HIGH) – Multiple SQL injection vulnerabilities in (1) `addcustomer.asp`, (2) `addprod.asp`, and (3) `process.asp` in aShopKart 2.0.3 allow remote attackers to execute arbitrary SQL and obtain sensitive information.
- CVE-2004-1926 – CVSS 7.5 (HIGH) – Tiki CMS/Groupware (TikiWiki) 1.8.1 and earlier allows remote attackers to inject arbitrary code via the (1) Theme, (2) Country, (3) Real Name, or (4) Displayed time zone fields in a User Profile, or
- CVE-2004-0866 – CVSS 7.5 (HIGH) – Internet Explorer 6.0 allows web sites to set cookies for country-specific top-level domains, such as `.ltd.uk`, `.plc.uk`, and `.sch.uk`, which could allow remote attackers to perform a session fixation attack.
- CVE-2004-0746 – CVSS 7.5 (HIGH) – Konqueror in KDE 3.2.3 and earlier allows web sites to set cookies for country-specific top-level domains, such as `.ltd.uk`, `.plc.uk` and `.firm.in`, which could allow remote attackers to perform a session fixation attack.
- CVE-2004-0867 – CVSS 7.5 (HIGH) – Mozilla Firefox 0.9.2 allows web sites to set cookies for country-specific top-level domains, such as `.ltd.uk`, `.plc.uk`, and `.sch.uk`, which could allow remote attackers to perform a session fixation attack.

[... sortie tronquée pour lisibilité du rapport ...]

■ Liste des CVE et scores CVSS

CVE	Score CVSS	Description
CVE-2014-3566	7.5	Protocole TLSv1.0 obsolète détecté, vulnérable aux attaques POODLE.
CVE-1999-0241	10.0	Guessable magic cookies in X Windows allows remote attackers to execute commands, e.g. through xterm.
CVE-1999-0809	5.0	Netscape Communicator 4.x with Javascript enabled does not warn a user of cookie settings, even if they have selected the option to "Only accept cookies originating from the same server as the page being viewed".

CVE-2000-0439	2.6	Internet Explorer 4.0 and 5.0 allows a malicious web site to obtain client cookies from another domain by including that domain name and escaped characters in a URL, aka the "Unauthorized Cookie Access" vulnerability.
CVE-2001-1086	7.5	XDM in XFree86 3.3 and 3.3.3 generates easily guessable cookies using gettimeofday() when compiled with the HasXdmXauth option, which allows remote attackers to gain unauthorized access to the X display via a brute force attack.
CVE-2001-0972	10.0	Surf-Net ASP Forum before 2.30 uses easily guessable cookies based on the UserID, which allows remote attackers to gain administrative privileges by calculating the value of the admin cookie (UserID 1), i.e. "0888888."
CVE-2001-0962	7.5	IBM WebSphere Application Server 3.02 through 3.53 uses predictable session IDs for cookies, which allows remote attackers to gain privileges of WebSphere users via brute force guessing.
CVE-2001-0658	7.5	Cross-site scripting (CSS) vulnerability in Microsoft Internet Security and Acceleration (ISA) Server 2000 allows remote attackers to cause other clients to execute certain script or read cookies via malicious script in an invalid URL that is not properly quoted in an error message.
CVE-2001-0723	6.4	Internet Explorer 5.5 and 6.0 allows remote attackers to read and modify user cookies via Javascript, aka the "Second Cookie Handling Vulnerability."
CVE-2001-0897	5.0	Cross-site scripting vulnerability in Infopop Ultimate Bulletin Board (UBB) before 5.47e allows remote attackers to steal user cookies via an [IMG] tag that references an about: URL with an onerror field.
CVE-2001-0898	5.0	Opera 6.0 and earlier allows remote attackers to access sensitive information such as cookies and links for other domains via Javascript that uses setTimeout to (1) access data after a new window to the domain has been opened or (2) access data via about:cache.
CVE-2003-1268	7.5	Multiple SQL injection vulnerabilities in (1) addcustomer.asp, (2) addprod.asp, and (3) process.asp in a.shopKart 2.0.3 allow remote attackers to execute arbitrary SQL and obtain sensitive information via the zip, state, country, phone, and fax parameters.
CVE-2004-1926	7.5	Tiki CMS/Groupware (TikiWiki) 1.8.1 and earlier allows remote attackers to inject arbitrary code via the (1) Theme, (2) Country, (3) Real Name, or (4) Displayed time zone fields in a User Profile, or the (5) Name, (6) Description, (7) URL, or (8) Country fields in a Directory/Add Site operation.
CVE-2004-0866	7.5	Internet Explorer 6.0 allows web sites to set cookies for country-specific top-level domains, such as .ltd.uk, .plc.uk, and .sch.uk, which could allow remote attackers to perform a session fixation attack and hijack a user's HTTP session.
CVE-2004-0746	7.5	Konqueror in KDE 3.2.3 and earlier allows web sites to set cookies for country-specific top-level domains, such as .ltd.uk, .plc.uk and .firm.in, which could allow remote attackers to perform a session fixation attack and hijack a user's HTTP session.
CVE-2004-0867	7.5	Mozilla Firefox 0.9.2 allows web sites to set cookies for country-specific top-level domains, such as .ltd.uk, .plc.uk, and .sch.uk, which could allow remote attackers to perform a session fixation attack and hijack a user's HTTP session. NOTE: it was later reported that 2.x is also affected.
CVE-2004-2180	4.3	Multiple cross-site scripting (XSS) vulnerabilities in WowBB Forum 1.61 allow remote attackers to inject arbitrary web script or HTML via the (1) country parameter to view_user.php, (2) show parameter to view_forum.php, (3) letter parameter to view_user.php, (4) highlight parameter to view_topic.php, (5) show parameter to index.php, (6) q parameter to search.php, (7) Referer header to admin.php, o
CVE-2004-2511	4.3	Multiple cross-site scripting (XSS) vulnerabilities in DCP-Portal 5.3.2 and earlier allow remote attackers to inject arbitrary web script or HTML via (1) the year, (2) month, and (3) day parameters in calendar.php; (4) the cid and (5) url parameters in index.php; (6) the cid parameter in annoucement.php; (7) the cid parameter in news.php; (8) the cid parameter in contents.php; (9) the q parameter

CVE-2005-0995	4.3	Multiple cross-site scripting (XSS) vulnerabilities in ProductCart 2.7 allow remote attackers to inject arbitrary web script or HTML via (1) the keyword parameter to advSearch_h.asp, (2) the redirectUrl parameter to NewCust.asp, (3) the country parameter to storelocator_submit.asp, or (4) the error parameter to techErr.asp. NOTE: it has been reported that storelocator_submit.asp does not exist in
CVE-2005-2985	7.5	SQL injection vulnerability in search_result.php in AEwebworks aeDating Script 4.0 and earlier allows remote attackers to execute arbitrary SQL statements via the Country parameter.
CVE-2005-4576	4.3	Multiple cross-site scripting (XSS) vulnerabilities in the UpdateEngine program in Fatwire UpdateEngine 6.2 and earlier allow remote attackers to inject arbitrary web script or HTML via the (1) COUNTRYNAME, (2) EMAIL, and (3) FUELAP_TEMPLATENAME parameters.
CVE-2007-1939	6.8	Cross-site scripting (XSS) vulnerability in the embedded webserver in Daniel Naber LanguageTool before 0.8.9 allows remote attackers to inject arbitrary web script or HTML via unspecified vectors involving an error message, possibly the demultiplex method in HTTPServer.java.
CVE-2017-7504	9.8	HTTPServerILServlet.java in JMS over HTTP Invocation Layer of the JbossMQ implementation, which is enabled by default in Red Hat Jboss Application Server <= Jboss 4.X does not restrict the classes for which it performs deserialization, which allows remote attackers to execute arbitrary code via crafted serialized data.
CVE-2018-12537	5.3	In Eclipse Vert.x version 3.0 to 3.5.1, the HttpServer response headers and HttpClient request headers do not filter carriage return and line feed characters from the header value. This allow unfiltered values to inject a new header in the client request or server response.
CVE-2019-3888	9.8	A vulnerability was found in Undertow web server before 2.0.21. An information exposure of plain text credentials through log files because Connectors.executeRootHandler:402 logs the HttpServerExchange object at ERROR level using UndertowLogger.REQUEST_LOGGER.undertowRequestFailed(t, exchange)
CVE-2020-5403	7.5	Reactor Netty HttpServer, versions 0.9.3 and 0.9.4, is exposed to a URISyntaxException that causes the connection to be closed prematurely instead of producing a 400 response.
CVE-2022-35252	3.7	When curl is used to retrieve and parse cookies from a HTTP(S) server, it accepts cookies using control codes that when later are sent back to a HTTPserver might make the server return 400 responses. Effectively allowing a "sister site" to deny service to all siblings.
CVE-2019-25087	5.3	A vulnerability was found in RamseyK httpserver. It has been rated as critical. This issue affects the function ResourceHost::getResource of the file src/ResourceHost.cpp of the component URI Handler. The manipulation of the argument uri leads to path traversal: '../filedir'. The attack may be initiated remotely. The name of the patch is 1a0de56e4daff9c2f9c8f6b130a764f7a50df52. It is recommended
CVE-2026-35392	9.8	goshs is a SimpleHTTPServer written in Go. Prior to 2.0.0-beta.3, PUT upload in httpserver/updown.go has no path sanitization. This vulnerability is fixed in 2.0.0-beta.3.
CVE-2026-44895	0.0	GitLab MCP Server lets an AI agent talk directly to GitLab. Prior to 0.6.0, the HTTP transport in src/transport.ts ships with no authentication layer at all and a wildcard Access-Control-Allow-Origin: * on every response. The structural defect is that the SSE server stands up a stateful, mutation-capable RPC endpoint that is backed by the operator's GITLAB_PERSONAL_ACCESS_TOKEN without any inbound

CVE-2026-49855	7.5	Tornado is a Python web framework and asynchronous networking library. Prior to 6.5.6, Tornado gzip decompression routines processed limited-size chunks but did not enforce an overall limit on accumulated decompressed chunks, allowing a malicious server accessed by SimpleAsyncHTTPClient or an HTTPServer configured with decompress_request=True to consume effectively unlimited memory. This issue is
CVE-1999-1306	7.5	Cisco IOS 9.1 and earlier does not properly handle extended IP access lists when the IP route cache is enabled and the "established" keyword is set, which could allow attackers to bypass filters.
CVE-1999-1466	7.5	Vulnerability in Cisco routers versions 8.2 through 9.1 allows remote attackers to bypass access control lists when extended IP access lists are used on certain interfaces, the IP route cache is enabled, and the access list uses the "established" keyword.
CVE-1999-1216	7.5	Cisco routers 9.17 and earlier allow remote attackers to bypass security restrictions via certain IP source routed packets that should normally be denied using the "no ip source-route" command.
CVE-1999-0161	7.5	In Cisco IOS 10.3, with the tacacs-ds or tacacs keyword, an extended IP access control list could bypass filtering.
CVE-1999-0511	9.1	IP forwarding is enabled on a machine which is not a router or firewall.
CVE-1999-0525	0.0	IP traceroute is allowed from arbitrary hosts.
CVE-1999-0195	5.0	Denial of service in RPC portmapper allows attackers to register or unregister RPC services or spoof RPC services using a spoofed source IP address such as 127.0.0.1.
CVE-1999-1463	5.0	Windows NT 4.0 before SP3 allows remote attackers to bypass firewall restrictions or cause a denial of service (crash) by sending improperly fragmented IP packets without the first fragment, which the TCP/IP stack incorrectly reassembles into a valid session.
CVE-1999-0667	10.0	The ARP protocol allows any host to spoof ARP replies and poison the ARP cache to conduct IP address spoofing or a denial of service.
CVE-1999-1061	7.5	HP Laserjet printers with JetDirect cards, when configured with TCP/IP, can be configured without a password, which allows remote attackers to connect to the printer and change its IP address or disable logging.

Score CVSS moyen : 6.5/10 — Nombre de CVE : 41

■ Recommandations

1. [CVE-2022-35252] to deny service to all siblings.
2. Désactiver TLSv1.0/TLSv1.1 et n'autoriser que TLSv1.2 et TLSv1.3.

■ Conclusion

L'audit du domaine alibaba.com révèle un niveau de risque critique. Des actions correctives immédiates sont nécessaires pour réduire l'exposition (score sécurité 2.0/10). Priorisez les CVE à CVSS élevé et les alertes ZAP à risque High.

Document généré automatiquement par CyberScan le 16/07/2026 à 18:09 UTC. Usage strictement confidentiel.