

Let's Get Random – Entropy and Cryptocurrencies



A Little About Me...

- Software Engineer @ Microsoft in Pittsburgh
- Tech Educator @ chaintuts
- Love to build free and open source technical education!
- Interested in cryptocurrencies, computer science, security topics




Why Talk About Entropy?

- Entropy (randomness) is critical to applied cryptography/cryptocurrencies
- Broken randomness breaks cryptographic systems
- It's interesting!



Entropy (In CS)

- Different (but similar) to entropy in physics – the degree of disorder in a system
- Randomness collected by a computer system for use in things like key generation, nonces, etc.
- There's different “levels” of randomness for our purposes



Types of Entropy

- True random sources
- Non-cryptographic pseudorandom numbers
- Cryptographically-secure pseudorandom numbers



True Random Sources

- There are a few sources of true randomness in the universe
- One of them is radioactive decay
- This entropy is possible to record, but impractical
- We can't easily carry around radioactive isotopes, nor expect the systems not to break




Pseudorandomness

- Instead of relying on physical TRNGs, let's use computer algorithms instead
- Problem: computers are very predictable
- There's different algorithms for getting random bits
- Two types: PRNG, CS-PRNG




PRNG vs. CS-PRNG



Non-CS PRNG – Mersenne Twister

vs.



CS-PRNG – OS source via Python
`os.urandom()`



Histogram showing the distribution of random numbers generated... what's the actual difference?

PRNG vs. CS-PRNG

- It's not just about *uniform distribution*.
- It's about *predictability* of new random bits
- Given 624 numbers, you can predict next numbers from Mersenne Twister
- Cannot predict output of CS-PRNG function given previous bits



PRNG vs. CS-PRNG

- Why do we care?
- It's critically important for many cryptographic uses of RNGs that the numbers be unpredictable
- Ex: key generation for a crypto exchange
- Imagine an attacker gets hold of 650 keys in a leak, and then can predict new keys!




CS-PRNGs

- **Seed -> Feed**
- Use relatively unpredictable environmental sources
 - Mouse movement, key press timings, accelerometer, temperature, etc.
 - Can even be manually generated, like dice rolls
- Feed those sources to a cryptographic function
 - SHA hashing algorithm, AES block cipher in CTR mode
 - Production algorithm: Fortuna
- Get unpredictable random bits out the other end




Demos:



Entropal: Diceware password generator showing bits of entropy

<https://github.com/chaintuts>



EntropyCollector: Generates passwords from accelerometer entropy



Uses of Cryptographic Randomness in Cryptocurrencies

- Key generation
- Signatures
- Proof-of-Work
- Proof-of-Stake
- and what happens when these things break...



Key Generation

- Private keys are the core of cryptocurrency ownership – your keys, your coins. Not your keys, not your coins!
- Key *must* be random – keys themselves are 256 bits, but often start from 128 bit seed which is key stretched
- 256 bit keys give so many possibilities, collisions are near impossible *if the keys are random*
 - 2^{256} is around 10^{64} , on the order of the number of atoms in the observable universe



Key Generation - Breakage

- What happens if keys aren't random enough?
- Pretty much worst-case scenario for crypto – the coins are stolen and moved to an attacker wallet.
- Practical example: *Brainwallets*
 - SHA-256 hash of a user-generated passphrase like “Interior Crocodile Alligator” -> used as 256 bit private key
 - Ryan Castellucci did a DEFCON topic and they released a tool called brainflayer
 - They note that brainwallets are often drained in minutes to hours, even with seemingly strong passphrases
 - *Humans are bad at entropy*



Signatures/Nonces

- Signature algorithms such as secp256k1 (elliptic curve used in Ethereum and Bitcoin) require a nonce when signing messages (like transactions)
- Nonce *must* be one time use
- Nonce reuse can easily reveal *private key*
- Ex: <https://github.com/chaintuts> - NotOKReuse
- Sloppy wallet programming can lead to theft



Some Less Obvious Uses...

- Proof-of-Work and Proof-of-Stake!
- We have to make it difficult for an attacker to change the state of the blockchain, and to *sustain* an attack
- In other words, we need the block “winner” to be *chosen at random*
- **But**, we also want to reward those that invest more in mining/staking with a higher *probability* of being selected



Proof-of-Work

- PoW uses the pseudo-random property of cryptographic hash functions like SHA-256
- Require a block with a certain number of leading zero bits (ex: 4, real difficulty much higher)
 - block + 0 -> 1aef0...
 - block + 1 -> ed032...
 - block + 2 -> 123ac8... ..
 - block + 4000 -> 0000a2
- Difficulty: the more 0 bits, more guesses on average it takes to find a block
- The mechanism is simple: more hashpower, higher chance of being the first to guess correctly




Proof-of-Stake

- PoS again uses the pseudo-random property of hashes like SHA with a *commit-reveal* scheme for RNGs on the blockchain
- Validator generates a random number from its CS source, hashes, *commits* to blockchain
- Later, the number is *revealed*. The number can be hashed by other nodes to verify it's the same hash that was committed
- Numbers XORed for a random validator selection
- It's impractical for nodes to game the system in their favor, since they can't easily change number after the commit (by finding a hash collision)



Let's Get Random

- There's different types of RNGs – and the ones we need are *cryptographically secure sources*
 - Use proven systems – like your OS's random source
 - Ex: Python `os.urandom()` NOT the `random` module
- Random numbers are critical for obvious things like key generation/nonces
- But they're also critical for things like PoW and PoS algorithms that secure these networks
- Getting random *wrong* has serious consequences, like coin theft



Questions?

