

Platypus 7 API Help

Table of Contents

Getting Started.....	1
Platypus API.....	1
Overview	1
Connecting to the API	1
Samples	1
XML Format.....	1
Methods.....	5
Platypus	5
AddNote	5
AddRate.....	7
Address / Phone Manager.....	9
AddService	11
AddToPlat	13
AuthCard	16
AuthorizeCard	18
ChangeCompany	20
ChangeNotes	21
ChangePassword	22
ChangeRate	23
ChangeStatus	24
ChargeAll	25
ChargeCard.....	27
CheckExpire	29

CheckFormat	30
Chk_Multi_Sec.....	32
Chk_Sec.....	33
ClockIn	34
ClockOut	35
CloseOut.....	36
CreateBonus	37
CreateExpiration.....	39
CreateInvoice.....	41
CreateMultiLineInvoice	43
DeleteRate	45
DeleteService.....	46
Email_Account.....	47
FakePost	49
FormatCCNumber	50
FormatPhone	51
GetAddress	52
GetAvailableCountries	53
GetAvailableRates.....	54
GetAvailableWebRates	55
GetCCInfo	57
GetChildren	58
GetCommissions	59
GetCustomer.....	61

GetECheckInfo	63
GetEmailDomains	64
GetInvoiceDetails	65
GetInvoices.....	66
GetOptions.....	68
GetPaths.....	70
GetPaymentDetails	71
GetPayments.....	72
GetPaymentTypes	74
GetPhone	75
GetPlatOption.....	77
GetPreviousUsage	78
GetRates	80
GetRatingInfo	81
GetReferrals.....	82
GetReportCategories	84
GetReportDetails	85
GetReports.....	86
GetReportFile	88
GetServiceDefs.....	89
GetServiceDetail	90
GetServiceInfo.....	91
GetStaffNotes	92
GetStores	94

GetTimeClockStatus	95
GetUsage	96
GetUsageByTerm.....	98
GetUsageDay.....	100
GetWebOption.....	102
IsChild	103
IsDupCCNumber.....	104
IsGuarantor	105
LaunchUM.....	106
ListServiceInstances	107
ListServiceInstances	109
ListServices2	111
LogChange	112
Login	114
OpenSRSGenProfile.....	115
OpenSRSGetProfile.....	116
OpenSRSSetProfile	117
Post	118
PostPayment	119
SearchCustomer.....	121
SearchServices.....	123
SendMail	125
SetAddress.....	126
SetPhone.....	128

Sql.....	129
Transaction_Auth	130
Transaction_Commit.....	131
Transaction_Refund	132
Transaction_GetPrice	133
Update	135
UpdateCCInfo	136
UpdateCustomer.....	137
UpdateRate	139
UpdateService	141
VerifyInfo.....	143
Welcome_Email	146
Wombat	147
attachment_Delete.....	147
attachment_Load	148
attachment_Save.....	149
call_Delete.....	150
call_New.....	151
call_Save	152
check_Security	153
customer_Search	154
email_Cancel	155
email_Delete.....	156
email_Get_Attachments	157

email_Load.....	158
email_New.....	160
email_Save	162
email_Send	163
get_Option.....	164
KB_Get_Article.....	165
KB_Get_Attachment	166
KB_Get_Issue	167
KB_Get_Titles.....	168
KB_Get_Tree	169
KB_Search.....	170
Login	171
note_Delete.....	172
note_Load.....	173
note_Save	175
sql_Execute	176
ticket_Change_Status	177
ticket_Delete.....	178
ticket_Get_Access_Settings	179
ticket_Get_Attachments	180
ticket_Get_Calls	181
ticket_Get_Category_List.....	182
ticket_Get_Customer_Info	183
ticket_Get_Emails	184

ticket_Get_History	185
ticket_Get_Notes	186
ticket_Get_Priority_List	188
ticket_get_Security_Settings	189
ticket_Get_Status_List	190
ticket_Get_Status_Progression_List	191
ticket_get_Ticket_Info	192
ticket_Get_Type_List	193
ticket_Load	194
ticket_Reassign	196
ticket_Save	197
ticket_Steal	199
ticketTree_Get_Filters	200
ticketTree_Get_Group_List	201
ticketTree_Get_Ticket_List	202
ticketTree_Get_Viewable	204
ticketTree_Get_View_List	205
Properties	207
Platypus	207
CustAdded	207
ChargeGood	209
LastError	210
Guarantor	211
PayError	212

XML Examples	213
Platypus	213
AddNote XML Example	213
AddRate XML Example.....	215
AddService XML Example	217
AddToPlat XML Example	220
AuthCard XML Example	222
AuthorizeCard XML Example	224
ChangeCompany XML Example	226
ChangeNotes XML Example	227
ChangePassword XML Example	228
ChangeRate XML Example	230
ChangeStatus XML Example.....	231
ChargeAll XML Example	232
ChargeCard XML Example.....	234
CheckExpire XML Example	237
CheckFormat XML Example	238
Chk_sec XML Example	241
Chk_Multi_Sec XML Example.....	243
Clockin XML Example	245
Clockout XML Example	246
Closeout XML Example.....	247
Createbonus XML Example.....	249
CreateExpiration XML Example.....	250

Createinvoice XML Example.....	252
CreateMultiLineInvoice XML Example	254
DeleteRate XML Example	256
Deleteservice XML Example	257
Email_account XML Example	258
Fakepost XML Example.....	259
Formatccnumber XML Example.....	261
Formatphone XML Example.....	264
GetAddress XML Example	266
Getavailablecountries XML Example	268
Getavailablerates XML Example	270
Getavailablewebrates XML Example.....	272
Getccinfo XML Example	274
GetChildren XML Example	276
Getcommissions XML Example	279
Getcustomer XML Example.....	281
GetECheckInfo XML Example	287
Getemaildomains XML Example.....	289
Getinvoicedetails XML Example	291
Getinvoices XML Example.....	293
Getoptions XML Example	297
GetPaths XML Example.....	299
Getpaymentdetails XML Example	301
Getpayments XML Example.....	303

Getpaymenttypes XML Example	309
GetPhone XML Example	312
GetPlatOption XML Example	314
Getprevioususage XML Example	315
Getrates XML Example.....	317
Getratinginfo XML Example	319
Getreferrals XML Example.....	321
Getreportcategories XML Example	324
Getreports XML Example	326
Getreportdetails XML Example	328
Getreportfile XML Example	330
Getservicedefs XML Example	361
Getservicedetail XML Example	363
Getserviceinfo XML Example	364
Getstaffnotes XML Example.....	368
Getstores XML Example.....	370
Gettimeclockstatus XML Example	372
Getusge XML Example.....	376
Getusagebyterm XML Example.....	378
Getusageday XML Example	380
Getweboption XML Example	381
Ischild XML Example	384
Isdupccnumber XML Example	386
Isguarantor XML Example.....	388

Launchum XML Example	390
ListServiceInstances XML Example	391
ListServiceITree XML Example	393
Listservices2 XML Example	395
Logchange XML Example	397
Login XML Example	399
OpenSRSGenProfile XML Example	402
OpenSRSGetProfile XML Example	403
OpenSRSSetProfile XML Example	404
Post XML Example	405
Postpayment XML Example	406
Searchcustomer XML Example	409
Searchservices XML Example	413
Sendmail XML Example	415
Setaddress XML Example	417
Setphone XML Example	420
SQL XML Example	422
Transaction_Auth XML Example	425
Transaction_Commit XML Example	427
Transaction_Refund XML Example	428
Transaction_GetPrice XML Example	429
Update XML Example	431
Updateccinfo XML Example	433
Updatecustomer XML Example	435

Updaterate XML Example	436
Updateservice XML Example	437
Verifyinfo XML Example	439
Welcome_email XML Example	442
Wombat	443
attachment_Delete XML Example	443
attachment_Load XML Example	445
attachment_Save XML Example	447
call_Delete XML Example	449
call_New XML Example	450
call_Save XML Example	452
check_Security XML Example	454
customer_Search XML Example	455
email_Cancel XML Example	457
email_Delete XML Example	459
email_Get_Attachments XML Example	460
email_Load XML Example	461
email_New XML Example	463
email_Save XML Example	466
email_Send XML Example	468
get_Option XML Example	470
KB_Get_Article XML Example	471
KB_Get_Attachment XML Example	473
KB_Get_Issue XML Example	475

KB_Get_Titles XML Example.....	477
KB_Get_Tree XML Example	480
KB_Search XML Example.....	482
Login XML Example	484
note_Delete XML Example.....	485
note_Load XML Example	487
note_Save XML Example	489
sql_Execute XML Example	491
ticket_Change_Status XML Example	494
ticket_Delete XML Example.....	496
ticket_Get_Access_Settings XML Example	497
ticket_Get_Attachments XML Example	500
ticket_Get_Calls XML Example	501
ticket_Get_Category_List XML Example.....	503
ticket_Get_Customer_Info XML Example	505
ticket_Get_Emails XML Example	507
ticket_Get_History XML Example	509
ticket_Get_Notes XML Example	512
ticket_Get_Priority_List XML Example	517
ticket_get_Security_Settings XML Example	519
ticket_Get_Status_List XML Example	522
ticket_Get_Status_Progression_List XML Example.....	524
ticket_get_Ticket_Info XML Example	526
ticket_Get_Type_List XML Example.....	528

ticket_Load XML Example.....	529
ticket_Reassign XML Example.....	531
ticket_Save XML Example	532
ticket_Steal XML Example	533
tickettree_Get_Filters XML Example	534
ticketTree_Get_Group_List XML Example.....	535
tickettree_Get_Ticket_List XML Example.....	537
tickettree_Get_Viewable XML Example	539
tickettree_Get_View_List XML Example.....	542
Advanced Topics.....	545
Adding Custom Fields to the Signup Pages	545
Commonly Used Signup Methods.....	547
Creating Bonuses/Commissions from the Web.....	548
Removing Default Fields from the Signup Pages	550
Running SQL Statements against the Database	552
Web Transactions	554
Index.....	559

Getting Started

Platypus API

Overview

The Platypus API is a windows service that accepts HTTPS requests containing XML. This provides platform independence, allowing access to any programming language - that can talk to a web server - to make Platypus API requests.

Connecting to the API

To connect to the API, an HTTPS request must be sent to the port used by the Platypus API. By default, this is port 5566, meaning the following URL should be used, where <server> should be replaced with the DNS name of the server.

```
https://<server>:5566
```

Samples

[VB.NET](#)

[C#](#)

[PHP](#)

XML Format

The specific XML request and response formats are documented under each method entry in this documentation.

Example Request

```
<?xml version="1.0"?>
<PLATXML>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AddRate</action>
      <logintype>staff</logintype>
      <username>Admin</username>
      <password></password>
      <parameters>
        <rate>1</rate>
        <noconn type="boolean">false</noconn>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

```

        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Request Values

Node	Description
<object>	The API object to use in the API call. This can be addusr - for Platypus API calls - or wombat - for Helpdesk API calls. If excluded from the XML, the object will default to addusr.
<action>	The name of the API call to execute
<logintype>	The type of user making the API call. This can be staff or customer. If excluded from the XML, the logintype will default to staff.
<username>	The username of the staff or customer making the API call.
<password>	The password of the staff or customer making the API call.
<parameters>	The list of parameters to pass into the API call. Parameters must be in a specified order. If a method does not require any parameters or properties, the <parameters> node can be left empty.
<properties>	The list of properties to set on the API object. Properties do not have to be in a particular order. If a method does not require any parameters or properties, the <properties> node can be left empty.

Data Types

Within each parameter or property, the data type can be specified. This is optional, except when the data type is "xml".

```
<value type="int">12345</value>
```

- string - This is the default data type, if a data type is not specified in the XML.
- bool - A logical value. Can be true or false. Can also be 1 (true) or 0 (false).
- int - A whole number.
- float - A floating point number.
- date - A date, stored in ISO-8601 format. For example, 2000-12-31 represents December 31st, 2000.
- datetime - A date/time, stored in ISO-8601 format. For example, 2000-12-31T23:01:59 represents December 31st, 2000 12:01:59pm.
- currency - A currency amount.
- xml - The node in the XML API request will be passed in directly to the API call.

Example Response

```

<PLAT_XML>
<body>
  <data_block>
    <object>addusr</object>
    <action>Reply</action>
  </data_block>
</body>
</PLAT_XML>

```

```

    <response_text>Rate 1 was successfully added to customer
1012</response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
        <data_block>
            <crid>883</crid>
        </data_block>
    </attributes>
</data_block>
</body>
</PLAT_XML>

```

Response Values

Node	Description
<object>	The API object to use in the API call. This can be addusr - for Platypus API calls - or wombat - for Helpdesk API calls. If excluded from the XML, the object will default to addusr.
<action>	In XML responses, this will always be Reply.
<response_text>	A user friendly description of the result of the API call.
<response_code>	A status code, categorizing the result of the API call. This can be one of several codes and are listed below. If the API succeeded, the code will always be SUCCESS. If the API failed, for whatever reason, the code will end in ERROR.
<is_success>	Whether the API call succeeded or failed. Will be 1 for success and 0 for failure.
<attributes>	Additional information returned by the API call.

Response Codes

Code	Description
SUCCESS	Represents a successful API call.
DATA_ERROR	Represents a failed API call. This is a generic response code used by the majority of API call failures.
PARAM_ERROR	The API call failed because of problems with a property or parameter.
KEY_ERROR	The API call failed because of a license key error.
ODBC_ERROR	The API call failed because of a connection problem between the Platypus API and Microsoft SQL Server.
XML_PARSE_ERROR	The API call failed because the XML request was not formatted properly.
XML_ERROR	The API call failed because the XML request was not formatted properly.
LOGIN_ERROR	The API call failed because the authentication information passed in the XML failed.
PERMIT_ERROR	The API call failed because of a permission or security error.

Response Attributes

The attributes returned by an API call contain values specific to an API call. Different API calls will return different attributes. In the addrate example, specified earlier, the API call returned a single block of values with a single value named `crid` within that block.

```
<attributes>
  <data_block>
    <crid>883</crid>
  </data_block>
</attributes>
```

If an API call returns multiple rows of data, a separate block of values will be returned for each row.

```
<attributes>
  <data_block>
    <rg_id>1</rg_id>
    <rg_name>First Rate Group</rg_name>
  </data_block>
  <data_block>
    <rg_id>2</rg_id>
    <rg_name>Second Rate Group</rg_name>
  </data_block>
</attributes>
```

Methods

Platypus

AddNote

Description

Adds a note to a customers account.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Staffid	String	Required. The id number of the staff member creating the note.
NoteType	String	Required. The type of note being entered. Possible values are "Complete", "Incomplete", and "Waiting".
NoteText	String	Required. The actual text message of the note.
NoteTo	String	Required. The id number of the staff member to which the note is assigned.
NotePriority	String	Required. The priority level of the note.
SendEmail	String	Required. Whether or not to email this task to the assigned staff member. The value should be "1" to send email or "0" not to send email. This property defaults to "0".
Custid	String	Required. The id number of the customer the note is created for.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a text message indicating success or failure.

Syntax

Object.AddNote(Datatype)

Examples

Stateful Interface

```
ox.staffid = "1"  
ox.notetype = "Complete"
```

Platypus 7 API Help

```
ox.notetext = "Customer could not get a dial tone. I had him plug the phone line in the wall and it fixed it."  
ox.noteto = "3"  
ox.notepriority = "1"  
ox.custid = "1001"  
ox.sendemail = "1"  
retvalue = ox.addnote()
```

Stateless Interface

[AddNote XML Example](#)

AddRate

Description

Adds a rate group to a customer configuring setup fees, bonuses, and expirations appropriately.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.
Guarantor	String	Required. The customer id of the guarantor of the customer if the guarantor will be paying for the charges created from this rate group. If this value is not set to zero, the rate groups charges will be billed to the guarantor account of the customer. Defaults to "0".
BonusType	String	Required. Should be set to "G" to check global bonus rules, "M" to manually specify bonus rules, or "B" to do both. Defaults to "G".
Salesid	String	Required. Staff id of the salesperson who should receive any commissions for signing up this customer.
Refid	String	Required. Customer id of the customer who should receive any referral bonuses for referring this customer.
BillToGuar	String	Required. "Y" or "N" value that determines whether or not the guarantor specified with the Guarantor property should be billed for this rate group. To bill the rate to the guarantor, the Guarantor property must be set to a value other than zero and the BillToGuar property must be set to "Y".

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CurrentRate	String	Required. The rate group id to be added.
NoConn	Boolean	Optional. Should be set to true if this method should not create a new connection to the database or false if the method should create its own new connection to the database. Defaults to false.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Frequency	String	Required. The billing frequency of the rate
Quantity	String	Optional. The quantity of the rate

Return Values

This method returns the crid (unique id of the customer rate assignment) as a string if successful or "0" if an error occurs.

Stateless Interface

[AddRate XML Example](#)

Address / Phone Manager**Description**

This method is an interface to the internal Address and Phone Manager classes. These classes can be used to retrieve and update customer address and phone information. They are only available through the stateful interface.

Before using the methods of the Address/Phone Manager class, the idnum property must be set to appropriate customer id number and the connhandle property must be set to a valid connection handle. See the example for the correct syntax to do this. The following methods of the Address/Phone Manager class are then available:

Load: This method loads the address or phone information for the specified customer into a collection

Save: This method saves the address or phone information to the database

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
idnum	String	Required. The id number of the customer.
connhandle	String	Required. A connection handle.

Return Values

This method returns an HTML table of the customers usage date..

Syntax

Object.addrmgr.idnum()

Example*Stateful Interface*

```

ox.addrmgr.idnum=CLng(ox.custid)
myconn=ox.sqlconnect()
if myconn<>0 then
ox.addrmgr.connhandle=myconn
end if
ox.addrmgr.load()
for i=1 to ox.addrmgr.collection.itemcount
response.write(ox.addrmgr.collection.items(i).addr1)
Next
if myconn>0 then
ox.sqldisconnect(myconn)
end if
ox.addrmgr.connhandle=0

```

Stateless Interface

A stateless interface does not exist for this method.

AddService

Description

This method adds a service to a customer rate group assignment. All of the column names associated with the service including standard and custom fields are included in the Column_Array parameter along with the values to insert, the data control being used and the display name for each column.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Svc_ID	String	Required. The unique id of the service type being added.
Crid	String	Required. The unique id of the customer rate group assignment that the service is being added to.
Column_Array	Array	Required. An array containing the information about the service being added. The column array is described in detail below.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Column_Array

All service tables include 3 columns by default (crid, d_active, and d_custid) that must be included in this array. Any custom fields that are marked as required must also be included. Any other custom fields that are not included in the array will have the null value inserted for them.

<u>Array Position</u>	<u>Type</u>	<u>Description</u>
0	String	The column name from the service table.
1	String	The value to insert into this column.
2	String	The current value of the column. This should always be the empty string when adding a service.
3	String	The data control used by the column. This is the value of the ctrl column from the user_field table entry for this column. Possible values include "txt_text", "dropdown", "dropword", etc.
4	String	The display name of the column. This is used in error messages to tell the customer which field the error occurred in.

Return Values

This method returns the unique data id of the service that was added for success or zero for failure. When an error occurs, the [LastError](#) property can be used to check the error message.

Syntax

Object.AddService(Svc_ID, Crid, Column_Array,Datatype)

Example

Stateful Interface

This is an example of adding an email service that has custom fields named Username and Password.

```
dim column_array()
redim column_array(3,5)
column_array(0,0) = "crid"
column_array(0,1) = "12"
column_array(0,2) = ""
column_array(0,3) = "txt_text"
column_array(0,4) = "Crid"
column_array(1,0) = "d_active"
column_array(1,1) = "Y"
column_array(1,2) = ""
column_array(1,3) = "txt_text"
column_array(1,4) = "Active"
column_array(2,0) = "d_custid"
column_array(2,1) = "1234"
column_array(2,2) = ""
column_array(2,3) = "txt_text"
column_array(2,4) = "Customer ID"
column_array(3,0) = "username"
column_array(3,1) = "testguy"
column_array(3,2) = ""
column_array(3,3) = "txt_text"
column_array(3,4) = "Username"
column_array(4,0) = "password"
column_array(4,1) = "mypassword"
column_array(4,2) = ""
column_array(4,3) = "txt_text"
column_array(4,4) = "Password"
ret = ox.addservice("1", "12", column_array)
```

Stateless Interface

[AddService XML Example](#)

AddToPlat

Description

Adds a new customer to the Platypus database. This method handles inserting all of their customer information including addresses, phone numbers, and rate groups.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Required for All		
BillingMeth	String	The billing method of the customer signing up. This value can be "check" for check customers or "ccard" for credit card customers.
Phone	String	The phone number of the customer.
Username	String	The username of the customer.
Password	String	The password of the customer.
Name2	String	The full name of the customer.
Address	String	The first line of the address of the customer.
Address2	String	The second line of the address of the customer.
State	String	The state for the customer's address.
City	String	The city for the customer's address.
Zip	String	The postal code for the customer's address.
Fax	String	The fax number of the customer.
Required for Credit Card		
CCExpireM	String	The month part of the credit card expiration date.
CCExpireY	String	The year part of the credit card expiration date.
CCName	String	The cardholder's name on the credit card.
CCAddr	String	The first line of the cardholder's address on the credit card.
CCAddr2	String	The second line of the cardholder's address on the credit card.
CCCity	String	The city for the credit card address.
CCState	String	The state for the credit card address.
CCZip	String	The postal code for the credit card address.
CCNumber	String	The credit card number
CCType	String	The credit card type. "MASTERCARD", "VISA", etc.
Required for ACH		
BankNumber	String	Bank Account Number
RouteNumber	String	Bank Routing Number
Optional Properties		
<u>Guarantor</u>	String	The id number of the guarantor account for this customer. If this property is set, it will make the specified id the customer's

		guarantor and make all rate groups added to the customer be billed to the guarantor. Example: ox.guarantor = "1001"
Email	String	The email address of the customer. If this property is not specified, the email address will be set to the username that was specified at the default domain in your database.
BonusType	String	Flag indicating whether to give bonuses based on global bonus rules, to create manual bonus rules, or both. The value should be "G" to look at global bonus rules, "M" to create manual rules, or "B" to do both. See Creating Bonuses from the Web for detailed information on this topic. Defaults to give no bonuses.
Staffid	String	The id of the staff member who added the customer. Defaults to "1".
SelectPOP	String	The id number of the customer's POP location. Defaults to "1".
SelectRate	String	The rate group id number(s) to be added to the customer. If more than one rate is selected, the selectrate property should contain each rate group id seperated by commas. Example: selectrate = "2,6,12" If no rate groups should be added to the customer, this property can be set to "-1". Defaults to "-1".
SelectShell	String	The shell type id that was selected. This id must match the id found under Maintenance-Shells. Defaults to "1".
HTMLEmail	String	"Y" or "N" value indicating whether the customer should receive email correspondence in HTML format or plain text format. Should be set to "Y" for HTML or "N" for plain text. Defaults to "N".
Bank_Acct_Type	String	Indicates whether the bank account to be drafted is a checking account or a savings account. Value should be "1" for checking or "2" for savings. Defaults to "1".
Country	String	The country for the customer's address. Defaults to the empty string.
CCCountry	String	The country for the credit card address. Defaults to the empty string.
Storeid	String	The store id for the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
NoConn	Boolean	Optional. Determines whether or not a new SQL connection is made. Value should be False to create a new SQL connection or True to use an existing SQL connection. Defaults to False if not specified.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns "Success" for success or an error message for failure. You can check the [CustAdded](#) and [ChargeGood](#) variables to help determine why the signup attempt failed.

Syntax

Object.AddToPlat(NoConn,Datatype)

Example*Stateful Interface*

```

ox.selectrate = "3,8"
ox.billingmeth = "ccard"
ox.phone = "1234567890"
ox.username = "joetest"
ox.password = "joepwd"
ox.name2 = "Joe Test"
ox.address = "100 Main Street"
ox.address2 = "Suite 101"
ox.state = "MS"
ox.city = "Starkville"
ox.zip = "39759"
ox.fax = "1234567890"
ox.selectshell = "1"
ox.ccexpirem = "11"
ox.ccexpirey = "01"
ox.ccname = "Joe Test"
ox.ccaddr = "100 Main Street"
ox.ccaddr2 = "Suite 101"
ox.cccity = "Starkville"
ox.ccstate = "MS"
ox.cczip = "39759"
ox.setupfee = "Y"
retvalue = ox.addtoplat()

```

Stateless Interface

[AddTo Plat XML Example](#)

AuthCard

Description

This method allows you to authorize the credit card of an existing customer for a specified amount of money. The credit card is not actually charged, but it verifies that the credit card information is valid and a charge for the specified amount would be approved.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
CCV2	String	Optional unless required by the Payment Gateway. The credit card verification number from the back of the credit card.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CCType	String	Required. Credit Card Type. i.e. Visa, Mastercard etc.
CCDate	Date	Required. Credit Card Expiration Date
CCNum	String	Required. Credit Card Number
Custid	String	Required. Customer ID
CCName	String	Required. Name of the Credit Card
Tender	Money	Required. Amount to Authorize
Ignore	Boolean	False
TaxAmount	Money	Required. Amount of Tax included in Tender
Ignore	Boolean	False
Ignore	Boolean	False
Ignore	Boolean	False
Ignore	Boolean	False
Ignore	Boolean	False
ActiveConn	Boolean	Required. Active Connection Flag. False unless an SQL connection is open for the method in which case it is True.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string is a 0 for error or 1 for success. The 0 or 1 is followed by a comma and any error or success message. Example: "0, Credit Card Declined"

Syntax

Object.AuthCard(CCType, CCDate, CCNum, CustID, CCName, Tender, Noisy, TaxAmount, AVS, City, State, Zip, Country, ActiveConn, DataType)

Example

Stateful Interface

```
Object.CCV2 = "123"  
retval=ox.AuthCard("VISA", "5/31/2007", "4111111111111111", "1012", "Joe Test", 5.00, false, 0.00,  
"100 That Street", "Starkville", "MS", "39759", "US", false, ADO)
```

Stateless Interface

[AuthCard XML Example](#)

AuthorizeCard

Description

This method allows you to authorize the credit card of someone who is not an existing customer. This is useful during the signup process to verify that the credit card information provided by the customer is accurate and valid before actually creating their customer account. The credit card is not actually charged, but it verifies that the credit card information is valid and a charge for the specified amount would be approved.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
PaymentTypeID	String	Required. The id number of the payment type. A list of these can be found in the p_id column in the payment_types table.
CCExpireDate	String	Required. The credit card expiration date.
Amount	Currency	Required. The authorization amount.
Custid	String	Required. The id number of the customer.
PayNumber	String	Required. The credit card number.
StoreID	Integer	Required. The id number of the Company to use for options including credit card processor.
CCV	String	Optional if not required by credit card processor. The credit card verification number from the back of the credit card.
Ignore	Boolean	Optional. This should always be False. Defaults to False.
AddressLine1	String	Optional if AVS is not required. The first line of the credit card address.
AddressLine2	String	Optional if AVS is not required. The second line of the credit card address.
City	String	Optional if AVS is not required. The city from the credit card address.
State	String	Optional if AVS is not required. The state from the credit card address.
Zip	String	Optional if AVS is not required. The postal code from the credit card address.
Country	String	Optional if AVS is not required. The country from the credit card address.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space and any error or success message.

Syntax

```
Object.AuthorizeCard(PaymentTypeID, PayDate, Amount, Custid, PayNumber, StoreID, CCV, Noisy, AddressLine1, AddressLine2, City, State, Zip, Country, Datatype)
```

Example

Stateful Interface

```
retval=ox..AuthorizeCard("10", "5/31/2007", 5.00, "1012", "4111111111111111", "Joe Test", 1, "123",  
false, "100 That Street", "", "Starkville", "MS", "39759", "US", ADO)
```

Stateless Interface

[AuthorizeCard XML Example](#)

ChangeCompany

Description

Allows customers to be moved from one Virtual Company to another.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nCustomer	Integer	Required. The id number of the customer being moved.
nCompany	Integer	Required. The new company to which the customer is being moved.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

```
Object.ChangeCompany(nCustomer,nCompany,cDatatype)
```

Example

Stateful Interface

```
ret = ox.ChangeCompany(1006, 2, "ADO")
```

Stateless Interface

[ChangeCompany XML Example](#)

ChangeNotes

Description

Adds a resolution to a note.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Staffid	String	Required. The id number of the staff member creating the note.
NoteType	String	Required. The type of note being entered. Possible values are "Complete", "Incomplete", and "Waiting".
NoteText	String	Required. The actual text message of the note.
NoteNumber	String	Required. The id number of the note being updated.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a text message indicating errors or the empty string for success.

Syntax

Object.ChangeNotes(Datatype)

Example

Stateful Interface

```
ox.staffid = "1"
ox.notetype = "Complete"
ox.notetext = "Customer could not get a dial tone. I had him plug the phone line in the wall and it fixed it."
ox.notenumber = "312"
ox.custid = "1001"
ox.changenotes()
```

Stateless Interface

[ChangeNotes XML Example](#)

ChangePassword

Description

Changes the customer's password and fires the UM_Old Save action if the user manager is enabled.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer whose password is being changed.
Password	String	Required. The old password.
NewPassword	String	Required. The new password.
Password2	String	Required. The new password again for verification purposes.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a text message indicating success or failure.

Syntax

Object.ChangePassword(Datatype)

Example

Stateful Interface

```
ox.custid = "1001"  
ox.password = "help#me"  
ox.newpassword = "go5rock"  
ox.password2 = "go5rock"  
ox.changepassword()
```

Stateless Interface

[ChangePassword XML Example](#)

ChangeRate

Description

Changes the customer's rate group. This method **ONLY** updates the rate group id for the customer. It does **NOT** handle giving any refunds and it will not charge the setup fee for the new rate group.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer whose password is being changed.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CRID	String	Required. The unique ID associated with the assignment of the Rate ID to the customer.
NewRGID	String	Required. The ID number of the newly assigned rate group.
DataType	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Frequency	String	Required. The billing frequency of the rate.

Return Values

This method returns a message indicating success or failure.

Stateless Interface

[ChangeRate XML Example](#)

ChangeStatus

Description

Changes the customer's active status and fires the appropriate external manager command if enabled. When changing the status from inactive to active, the UM_Old Save command is fired. When changing the status from active to inactive, the UM_Deact Save command is fired. The external manager commands for any services assigned to the customer will be fired as well.

Properties

The following properties can be set on the object before this method is called.

Property	Type	Description
Custid	String	Required. The id number of the customer whose password is being change.
Parameters		
Parameter	Type	Description
NewStatus	String	Required. The customer's new active status. Value should be "Y" for active, "N" for inactive, "H" for hold, or "S" for suspended.
nReasonID	Integer	Required. The id number of the deactivation reason. This can be found in the rl_id column of the reason_list table.
cReasonNote	String	Required. A comment field for notes regarding the deactivation.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a message indicating success or failure.

Syntax

Object.ChangeStatus(NewStatus,nReasonID,cReasonNote,Datatype)

Example

[ChangeStatus XML Example](#)

ChargeAll**Description**

This method should only be used for new signup attempts.

This method determines the current unpaid balance on a customer's account and charges that amount to their credit card. If the credit card is declined, it checks the "Add customers if credit card is declined web page option" and deletes the customer if that option is set to "Y".

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer whose credit card is being charged.
CCNumber	String	Required. The credit card number to charge.
CCName	String	Required. The cardholder's name on the credit card.
CCExpireM	String	Required. The month part of the credit card expiration date.
CCExpireY	String	Required. The year part of the credit card expiration date.
Name2	String	Required. The name of the customer whom the invoices are billed to.
CCType	String	Required. The credit card type. "MASTERCARD", "VISA", etc.
Staffid	String	Optional. The id number of the staff member charging the card. Defaults to "1".
CCV2	String	Optional. The credit card security / verification code from the back of the credit card.
Cdid	String	Optional. The cash drawer id. Defaults to 1 if not specified.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CCAction	String/Boolean	Optional. This is used to override the web option and specify whether the credit card will be charged or authorized. Should be "1" to charge the card or "2" to authorize. If this parameter is omitted or passed in as a boolean False, this method will look up the value from the web options.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a message indicating success or failure..

Syntax

Object.ChargeAll(CCAction,Datatype)

Example

Stateful Interface

```
ox.custid = "1001"  
ox.ccnumber = "4005550000000019"  
ox.ccname = "Joe Test"  
ox.ccexpirem = "09"  
ox.ccexpirey = "99"  
ox.name2 = "Joe Test"  
ox.cctype = "VISA"  
ox.staffid = "1"  
ox.chargeall("24.95", "10123, 10231")
```

Stateless Interface

[ChargeAll XML Example](#)

ChargeCard

Description

Charges a customer's credit card a specified amount and applies the payment to the specified invoices.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer whose credit card is being charged.
CCNumber	String	Required. The credit card number to charge.
CCName	String	Required. The cardholder's name on the credit card.
CCExpireM	String	Required. The month part of the credit card expiration date.
CCExpireY	String	Required. The year part of the credit card expiration date.
Name2	String	Required. The name of the customer whom the invoices are billed to.
CCType	String	Required. The credit card type. "MASTERCARD", "VISA", etc.
Staffid	String	Optional. The id number of the staff member charging the card. Defaults to "1".
CCV2	String	Optional. The credit card security / verification code from the back of the credit card.
Cdid	String	Optional. The cash drawer id. Defaults to 1 if not specified.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Balance	String	Required. The amount of money to charge the credit card.
Invoices	String	Required. A comma separated list of invoices to apply the credit card payment to.
ActiveConn	String	Optional. Flag indicating whether there is already an active SQL connection or a new connection should be created. Value should be "true" to use existing connection or "false" to create a new connection. Defaults to "false".
CCAction	String/Boolean	Optional. This is used to override the web option and specify whether the credit card will be charged or authorized. Should be "1" to charge the card or "2" to authorize. If this parameter is omitted or passed in as a boolean False, this method will look up the value from the web options.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Address	String/Boolean	Optional. The customer's credit card address. If passed in as a boolean False, the parameter is populated by the credit card address on the customer account.
City	String/Boolean	Optional. The customer's credit card city. If passed in as a boolean False, the parameter is populated by the credit card city on the customer account.

State	String/Boolean	Optional. The customer's credit card state. If passed in as a boolean False, the parameter is populated by the credit card state on the customer account.
Zip	String/Boolean	Optional. The customer's credit card zip. If passed in as a boolean False, the parameter is populated by the credit card zip on the customer account.
Country	String/Boolean	Optional. The customer's credit card country. If passed in as a boolean False, the parameter is populated by the credit card country on the customer account.

Return Values

This method returns a message indicating success or failure.

Syntax

Object.ChargeCard(balance, invoices,activeconn,CCAction,Datatype,address,city,state,zip,country)

Example

Stateful Interface

```
ox.custid = "1001"  
ox.ccnumber = "4005550000000019"  
ox.ccname = "Joe Test"  
ox.ccexpirem = "09"  
ox.ccexpirey = "99"  
ox.name2 = "Joe Test"  
ox.cctype = "VISA"  
ox.staffid = "1"  
ox.chargecard("24.95", "10123, 10231")
```

Stateless Interface

[ChargeCard XML Example](#)

CheckExpire

Description

Creates rate expiration rules based on global expiration rules that have been setup for the specified rate group.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Rgid	String	Required. Rate group id. The id number of the rate group.
Crid	String	Required. The unique id number of the customer rate assignment from the custrate table.
Custid	String	Required. The id number of the customer.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns nothing.

Syntax

Object.CheckExpire(rgid, crid, custid,Datatype)

Example

Stateful Interface

```
ox.checkexpire("12","312","1001")
```

Stateless Interface

[CheckExpire XML Example](#)

CheckFormat

Description

Checks the specified username or password against the format options in Platypus for validity.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required for username checks but not for password checks. The id number of the customer. This is used to determine which domain to use when checking to see if the username is already in use by another customer in that same domain.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Value	String	Required. The username or password to be checked against the format options.
Formattype	String	Required. Should be set to the word "Username" to check against the username format options or the word "Password" to check against the password format options.
ErrorFile	String	Optional. The name of a text file that errors should be logged to. If not specified, errors are not logged to a file.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns true if the specified value is valid when compared to the format options or false if it is invalid.

Syntax

Object.CheckFormat(Value, Formattype,ErrorFile,Datatype)

Example

Stateful Interface

```
if Not ox.CheckFormat("newuser","Username") then
    response.write("The username is invalid.")
end if
```

Stateless Interface

[CheckFormat XML Example](#)

Chk_Multi_Sec

Description

This method checks an array of security tags to see if the staff member or customer that is currently logged in has security permission to access the specified tags.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
SecTagArray	Array	Required. An array of security tag names to check.
Datatype	String	Optional. Type of data returned from the method. This method returns XML data.

SecTagArray

Array Position	Type	Description
0	String	The name of the security tag to be checked. For rate, report, customer, and staff security checks, this will be the id number of the item to check.
1	Boolean/String	For normal security tags, this should be 'false'. For rate, report, customer, and staff security checks, this will be the appropriate string value from: "Rate", "Report", "Customer", "Staff".
2	Boolean	This should always be passed in as a boolean False. When the array is returned, this will contain a boolean 'true' if security access is allowed or 'false' if security access is denied.

Return Values

This method returns the array that was passed in with the third column updated to be true if the person logged in has access to the specified item or false if they do not have access.

Syntax

Object.Chk_Sec(SecTagArray, Datatype)

Example

Stateful Interface

This method does not have a Stateful Interface.

Stateless Interface

[Chk_Multi_Sec XML Example](#)

Chk_Sec

Description

This method checks a security tag to see if the staff member or customer that is currently logged in has security permission to access the specified tag.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Value	String	Required. The item that security is being checked for. This can be a security tag, a customer id number, a staff id number, a report name, or other items that have security.
Category	String	Optional. This parameter should only be specified when checking security on items other than security tags. It should be set to "Customer" when checking to make sure the person logged in has permission to access the specified customer record, "Staff" when checking to make sure the person logged in has permission to access the specified staff record, or "Report" when checking to make sure the person logged in has access to the specified report.
NoConn	Boolean	Optional. Defaults to False. Should be set to True if you do not want this method to create its own connection to the database and destroy it when it is finished.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns true if the person logged in has access to the specified item or false if they do not have access.

Syntax

Object.Chk_Sec(Value , Category, NoConn,Datatype)

Example

[Chk_sec XML Example](#)

ClockIn

Description

This method clocks in a staff member on the time clock.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
StaffID	String	Required. ID number of the staff member who is clocking in.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

Object.ClockIn(StaffID,Datatype)

Example

Stateful Interface

```
retvalue = ox.clockin("1")
```

Stateless Interface

[Clockin XML Example](#)

ClockOut

Description

This method clocks out a staff member on the time clock.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
StaffID	String	Required. ID number of the staff member who is clocking out.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

Object.ClockOut(StaffID,Datatype)

Example

Stateful Interface

```
retvalue = ox.clockout("1")
```

Stateless Interface

[Clockout XML Example](#)

CloseOut

Description

This method closes out a rate group that a customer is assigned by creating an invoice to bill for the rate through the current date and then removing the rate group assignment from the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. ID number of the customer.
Crid	String	Optional. ID number of the customer rate group assignment.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

Object.CloseOut(Custid,Crid,Closeout)

Example

Stateful Interface

```
ox.custid = "1001"  
retvalue = ox.datatype()
```

Stateless Interface

[Closeout XML Example](#)

CreateBonus

Description

Creates a bonus rule for a customer based on global bonus rules or manually creates bonus rules based on the global_bonus object properties. See [Creating Bonuses from the Web](#) for complete documentation of this topic.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Refid	String	Optional. The id number of the customer who is receiving the referral bonus.
Custid	String	Required. The id number of the customer.
Salesid	String	Optional. The id number of the salesperson who is receiving the commission.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Crid	String	Required. Custrate id value. Unique id value of the customer rate assignment for which the bonus/commission is being given.
DoSql	Boolean	Optional. Determines whether or not a new SQL connection is made. Value should be True to create a new SQL connection or False to use an existing SQL connection. Defaults to True if not specified.
GetDefaults	Boolean	Optional. Determines whether or not global bonus rule defaults should be loaded. Should be set to True to load default values from a global bonus rule or False when creating a manual bonus rule. Defaults to False.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a text message indicating success or failure.

Syntax

Object.CreateBonus(Crid, DoSql, GetDefaults, Datatype)

Example

Stateful Interface

```
ox.refid = "1001"
ox.salesid = "1"
retvalue = ox.createbonus("212")
```

Stateless Interface

[Createbonus XML Example](#)

CreateExpiration

Description

Creates a rate expiration rule for the specified customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nCustID	Integer	Required. Customer ID.
nCRID	Integer	Required. The unique id of the customer rate assignment that is to expire. This is the CRID column on the custrate table.
dExpDate	Date	Required. Date the specified rate assignment should expire. Defaults to current date.
nNewRGID	Integer	Required. Rate ID replacing the existing rate. The Rate ID will be 0 if the rate id is being removed instead of replaced.
cDeact	String	Required. Value is "F" if the customer active status is not being changed. Value is "H" to place the customer on hold. Value is "S" to suspend the customer. Value is "N" to deactivate the customer. Defaults to "F".
nReasonID	Integer	Required. Deactivation reason id. This is the rl_id column on the reason_list table. Value is 0 if no reason is selected. Defaults to 0 and is ignored if cDeact has a value of "F".
cReasonNote	String	Required. Deactivation reason note. Defaults to empty string and is ignored if cDeact is "F".
cPriceChange	String	Required. Value is "R" to remove price override, "N" to not change the existing price override, or "C" to change the existing price override. Defaults to "R".
nPrice	Numeric	Required. The price override to use if cPriceChange is "C". Defaults to 0.00 and is ignored if cPriceChange is not "C".
cCloseout	String	Required. Value is "Y" if a closeout invoice should be generated using the expiration date or "N" if an invoice should not be generated. Defaults to "N".
cUseExpireDate	String	Required. Value is "Y" if close out invoice should be generated using the expiration date or "N" if the invoice should not be generated. Defaults to "N" and is ignored if cCloseout is "N".
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

```
Object.CreateExpiration(nCustID,nCRID,dExpDate,nNewRGID,cDeact,nReasonID,cReasonNote,cPriceChange,nPrice,cCloseout,cUseExpireDate,Datatype)
```

Example

Stateful Interface

```
ox.custid = "1008"
```

```
retvalue = ox.CreateExpiration(1008,6121,cDate("6/3/2006"),0,"F",0,"","R",0.00,"Y","Y","ADO")
```

Stateless Interface

[CreateExpiration XML Example](#)

CreateInvoice

Description

This method creates an invoice for a customer. All of the invoice information is passed in as parameters to the method.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CustomerID	Integer	Required. Customer id number of the customer the invoice is being created for.
GuarantorID	Integer	Required. Customer id number of the customer the invoice should be billed to.
StaffID	Integer	Required. ID number of the staff member who is creating the invoice.
Comment	String	Required. Text message that should go in comment field of invoice. This can be set to the empty string ("") if no comment is needed.
ItemCode	String	Required. Item code that should appear on the line item for this invoice.
Description	String	Required. Description that should appear on the line item for this invoice.
Quantity	Integer	Required. Quantity of items that should appear on the line item for this invoice.
Price	Numeric	Required. Individual unit price of the item that will appear on the line item for this invoice.
TaxProfileID	Integer	Required. ID number of the tax profile that should apply to this invoice.
SDate	Date	Required. The starting date of the service period that the line item on this invoice covers. For example, if the invoice is for internet service for the month of June (June 1st to July 1st), the SDate would be June 1st. This date is mainly used in the calculation of deferred revenue.
EDate	Date	Required. The ending date of the service period that the line item on this invoice covers. For example, if the invoice is for internet service for the month of June (June 1st to July 1st), the EDate would be July 1st. This date is mainly used in the calculation of deferred revenue.
NoConn	Boolean	Optional. Determines whether or not a new SQL connection is made. Value should be "true" to create a new SQL connection or "false" to use an existing SQL connection. Defaults to "true" if not specified.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one if the invoice was created successfully or a zero if an error occurs. If an error occurs, the [LastError](#) property of the web object can be accessed to obtain the error message.

Syntax

Object.CreateInvoice(CustomerID, GuarantorID, StaffID, Comment, ItemCode, Description, Quantity, Price, TaxProfileID, SDate, EDate, NoConn,Datatype)

Example

Stateful Interface

```
retvalue = ox.CreateInvoice(1234, 1234, 1, "Comment on invoice.", "MISC", "56K Modem", 1, 29.95, 1,
"10/1/2000", "10/1/2000")
if retvalue = 0 then
    response.write(ox.lasterror)
end if
```

Stateless Interface

[Createinvoice XML Example](#)

CreateMultiLineInvoice

Description

This method allows you to create an invoice that contains one or more line item details. Any applicable taxes will be added to the invoice internally.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nCustomerID	Integer	Required. Customer id number of the customer the invoice is being created for. This parameter should be of type integer.
nGuarantorID	Integer	Required. Customer id number of the customer the invoice should be billed to. This parameter should be of type integer.
nStaffID	Integer	Required. ID number of the staff member who is creating the invoice. This parameter should be of type integer.
cComment		Required. Text message that should go in comment field of invoice. This can be set to the empty string ("") if no comment is needed.
altemArray	Array	Optional. An array of invoice line item information.
bNoConn	Boolean	Optional. Should be True if an external connection to the database has been made using the SQLConnect method. Otherwise, should be False. Defaults to False.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

altemArray

Array Position	Type	Description
0	String	The invoice item code.
1	String	The invoice item description.
2	Integer	The invoice item quantity.
3	Currency	The invoice item unit price.
4	Integer	The id number of the tax profile that applies to this invoice item.
5	Date	The service period start date of the item.
6	Date	The service period end date of the item.
7	Numeric	The unique id of the item from the item_instock table (column name ii_id). Optional.

Return Values

This method returns the invoice number of the created invoice for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.CreateMultiLineInvoice(nCustomerID, nGuarantorID, nStaffID, cComment, aItemArray, bNoConn, Datatype)

Example

Stateful Interface

```
dim item_array()  
redim item_array(2,10)  
item_array(0,0) = "MYITEM" ' Item Code  
item_array(0,1) = "My Description" ' Item Description  
item_array(0,2) = 1 ' Quantity  
item_array(0,3) = 3.00 ' Price  
item_array(0,4) = 1 ' Tax Profile ID  
item_array(0,5) = CDate("6/1/2005") ' Service Period Start Date  
item_array(0,6) = CDate("7/1/2005") ' Service Period End Date  
item_array(0,7) = 1005 ' Serial ID Number  
item_array(1,0) = "MISC" ' Item Code  
item_array(1,1) = "The Description" ' Item Description  
item_array(1,2) = 2 ' Quantity  
item_array(1,3) = 3.95 ' Price  
item_array(1,4) = 1 ' Tax Profile ID  
item_array(1,5) = CDate("6/1/2005") ' Service Period Start Date  
item_array(1,6) = CDate("6/1/2005") ' Service Period End Date  
item_array(1,7) = false ' Serial ID Number  
' Parameters are Customer ID, Guarantor ID, Staff ID, Comment, and Item Array  
ret = ox.CreateMultiLineInvoice(1008,1008,1,"This is the comment",item_array)
```

Stateless Interface

[CreateMultiLineInvoice XML Example](#)

DeleteRate

Description

This method deletes a single rate from a customer's account along with any bonus rules, expiration rules, and services that exist for the specified rate.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cCRID	String	Required. The unique id of the customer rate group assignment that is to be deleted. This is the CRID column on the custrate table
bNoCloseout	Boolean	Optional. If set to True, a closeout invoice will not be created. This is the same as answering No to the message box that is displayed inside Platypus. Defaults to False.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or zero for failure. When an error occurs, the [LastError](#) property can be used to check the error message.

Syntax

Object.DeleteRate(CRID,bNoCloseout,Datatype)

Example

Stateful Interface

```
ox.custid = "1008"
ret = ox.DeleteRate("6121","False", "ADO")
```

Stateless Interface[DeleteRate XML Example](#)

DeleteService

Description

This method deletes a service from a customer rate group assignment.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Svc_ID	String	Required. The unique id of the service type being added.
DataID	String	Required. The unique id of the instance of the service.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or zero for failure. When an error occurs, the [LastError](#) property can be used to check the error message.

Syntax

Object.DeleteService(Svc_ID, DataID,Datatype)

Example

Stateful Interface

```
ox.custid = "1234"  
ret = ox.deleteservice("1", "12")
```

Stateless Interface

[Deleteservice XML Example](#)

Email_Account

Description

This method is used to send email correspondence (statements, receipts, late notices, etc.) to an existing customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CorrespondenceType	String	Required. The type of email correspondence to send. The supported values for this parameter are: "STATEMENT" "RECEIPT" "LATE NOTICE" "CC CHARGE PENDING" "ECHECK CHARGE PENDING" "REFERRAL BONUS" "DEACTIVATION" "CLOSEOUT" "INVOICE"
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

Object.Email_Account(CorrespondenceType,Datatype)

Example

Stateful Interface

```
ox.custid = "1001"
retvalue = ox.email_account("LATE NOTICE")
```

Stateless Interface

[Email_account XML Example](#)

FakePost

Description

This method simulates the posting process for a single customer rate assignment over a specified date range. This is useful in determining the detailed usage charges for a customer over a previous date range. It can also be used to determine the usage charges currently accumulated during the current billable date range.

Return Values

This method returns an invoice object for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.FakePost()

Example*Stateful Interface*

```
ox.custid = "1704"
```

```
Set oInvoice = ox.fakepost(1247, false, CDate("1/1/2003"), CDate("3/1/2003"), "ADO")
```

Stateless Interface

[Fakepost XML Example](#)

FormatCCNumber

Description

This method formats a credit card number based on the Credit Card Mask option from the web pages or a specified mask.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CreditCardNumber	String	Required. The credit card number that is to be masked.
CreditCardMask	String	Optional. The mask to apply to the number. If not specified, the Credit Card Mask option from the web pages is looked up and used.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns the credit card number with the mask applied to it.

Syntax

Object.FormatCCNumber(CreditCardNumber, CreditCardMask,Datatype)

Example

Stateful Interface

```
NewCCNumber = ox.FormatCCNumber("4111111111111111")  
response.write(NewCCNumber)
```

Stateless Interface

[Formatccnumber XML Example](#)

FormatPhone

Description

This method formats the phone number to match the phone mask in Platypus.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Phone	String	Required. The phone number to be formatted.
Mask	String	Optional. The mask to apply to the phone number. Defaults to the Phone Mask option from Maintenance - Options in Platypus.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns the phone number with the phone mask applied to it.

Syntax

Object.FormatPhone(Phone, Mask,Datatype)

Example

Stateful Interface

```
retvalue = ox.formatphone("1234567890")
```

Stateless Interface

[Formatphone XML Example](#)

GetAddress

Description

This method returns an data set containing all of the address data for the specified customer. The data is accessed using the column names from the address and address_type tables.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
DataType	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing address data. The data in the recordset can be accessed using the column name from the address and address_type tables.

Syntax

```
Set RS = Object.GetAddress(DataType)
```

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetAddress("ADO")
response.write(RS("addr1"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[GetAddress XML Example](#)

GetAvailableCountries**Description**

This method returns all of the countries stored in the countries table/view.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a recordset containing all of the countries stored in the countries table/view for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.GetAvailableCountries(Datatype)

Example

Stateful Interface

Set RS = ox.getavailablecountries("ADO")

Stateless Interface

[Getavailablecountries XML Example](#)

GetAvailableRates

Description

This method returns all of the rate groups that the currently logged in staff member or customer has access to add to a customer account.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a recordset containing all of the rate groups that the currently logged in staff member or customer has access to add to a customer account for success or a 0 for error. The recordset includes the fields below. If a 0 is returned, the LastError property will contain the error message.

<u>Field</u>	<u>Type</u>	<u>Description</u>
ID	Integer	The rate group id number.
Name	String	The rate group name.
Sortorder	Integer	An id number representing the rate groups location in a sorted list of rates

Syntax

Object.GetAvailableRates(Datatype)

Example

Stateful Interface

Set RS = ox.getavailablerates("ADO")

Stateless Interface

[Getavailablerates XML Example](#)

GetAvailableWebRates**Description**

This method returns all rate groups marked as web accessible and available in the specified company.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	Integer	Required. The id of the customer to use when determining what rates are currently available. Allows for the display of Dependency Rate Groups if the customer has the appropriate Dependency Rate Groups. If not set or set to 0, returns rate groups for all customers--limited by the ICCS parameter.
Storeid	Integer	Required. The id number of the company to use when determining what rates are currently available. If not set or set to 0, returns rate groups for all companies--limited by the ICCS parameter.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
ICCS	Boolean	Optional. If set to true, returns Web Rates with a CCS Service set. If set to false or not set, returns Web Rates without a CCS Service set.

Return Values

This method returns a recordset containing all rate groups marked as web accessible and available in the specified company limited by the ICCS parameter for success or a 0 for error. The recordset contains the fields below. If a 0 is returned, the LastError property will contain the error message.

<u>Field</u>	<u>Type</u>	<u>Description</u>
ID	Integer	The rate group id number.
Name	String	The rate group name.
Rg_Description	String	The rate group description.
Sortorder	Integer	An id number representing the rate groups location in a sorted list of rates

Syntax

```
Object.GetAvailableWebRates(Datatype,ICCS)
```

Example*Stateful Interface*

```
Set RS = ox.getavailablewebrates("ADO",false)
```

Stateless Interface

[Getavailablewebrates XML Example](#)

GetCCInfo

Description

This method returns a data set containing credit card information for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the credit card type, number, expiration date, and address. The fields can be referenced by the names "cctype", "ccnumber", "ccdate", and all of the column names in the address table.

Syntax

Object.GetCCInfo(Datatype)

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetCCInfo()
response.write(RS("ccnumber"))
```

Stateless Interface

[Getccinfo XML Example](#)

GetChildren

Description

This method checks to see if the specified customer has any child accounts. If he does, it returns a data set containing all of the data from the customer table for each of those child accounts.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The customer id of the guarantor account.

Return Values

This method returns an ADO recordset containing all of the data from the customer table for all of the customers child accounts or a zero if the customer has not child accounts .

Syntax

Object.GetChildren()

Example

Stateful Interface

```
ox.custid="1234"  
retvalue = ox.getchildren()
```

Stateless Interface

[GetChildren XML Example](#)

GetCommissions

Description

This method returns a data set containing all of the commission data for the specified staff member. The data returned depends upon the value of the reftype parameter.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Staffid	String	Required. The id number of the staff member.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Reftype	String	Required. The type of commission information to retrieve. This parameter has three valid values: "I", "P", and "D". Pass an "I" to retrieve information for commissions that have been issued. Pass a "P" to retrieve information for commissions that are pending. Pass a "D" to retrieve details of the commissions paid with a certain payment id.
Payid	String	Required only if Reftype equals "D". The payment id number of the commission payment. This value is stored in the payid column of the bonus table.
Data Type	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing commission information. The field values in the recordset depend upon the setting of the Reftype parameter.

Reftype = "I"

<u>Field</u>	<u>Type</u>	<u>Description</u>
Total	Money	The total amount of commission paid for each payment id.
PaidDate	Date	The date each commission was paid.
Payid	Int	The payment id of the payment issued for the commission.

Reftype = "P"

The ADO recordset will contain all of the columns from the bonus_act table plus the following additional column.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Name	String	The name of the customer who signed up triggering the commission.

Reftype = "D"

The ADO recordset will contain all of the columns from the bonus table plus the following additional columns.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Name	String	The name of the customer who signed up triggering the commission.
InvoicePaid	Money	The paid amount on the invoice that triggered the commission.
InvoiceTotal	Money	The total on the invoice that triggered the commission.

Syntax

```
Set RS = Object.GetCustomer("ADO")
```

Example

Stateful Interface

```
ox.staffid = "2"  
Set RS = ox.GetCommissions("I",false,"ADO")  
response.write(RS("total"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getcommissions XML Example](#)

GetCustomer

Description

This method returns a data set containing all of the customer data for the specified customer. The data is accessed using the column names from the customer table.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Data Type	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing customer data. The data in the recordset can be accessed using the column name from the customer table. In addition to the columns from the customer table, the following four fields are available in the recordset:

Field	Type	Description
Balance	Money	The customers unpaid balance.
Credit	Money	The total amount of unapplied credit on the customers account.
CreditCardMasked	String	The customer's credit card number with the credit card mask applied to it.
PhoneMasked	String	The customer's default phone number with the phone mask applied to it.
FaxMasked	String	The customer's fax number with the phone mask applied to it.
ActiveStatus	String	The active status of the customer. Possible values are "Active", "Hold", "Suspend", and "Inactive".

Syntax

```
Set RS = Object.GetCustomer("ADO")
```

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetCustomer("ADO")
```

Platypus 7 API Help

```
response.write(RS("username"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getcustomer XML Example](#)

GetECheckInfo

Description

This method returns a data set containing ECheck direct debit information for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the bank account type, bank name, bank account number, routing number and credit card address. The fields can be referenced by the names "bank_acct_type", "bank_name", "ccnumber", "routenumber", and all of the column names in the address table.

Syntax

Object.GetECheckInfo(Datatype)

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetECheckInfo()
response.write(RS("ccnumber"))
```

Stateless Interface

[GetECheckInfo XML Example](#)

GetEmailDomains

Description

This method returns a data set containing all of the email domains available to the specified customer. It will include all global domains, all domains owned by the customer, and all domains owned by the customer's guarantor.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing email domain data. The data in the recordset can be accessed using the column name from the domain_item table.

Syntax

```
Set RS = Object.GetEmailDomains("ADO")
```

Example

Stateful Interface

```
ox.custid = "1001"  
Set RS = ox.GetEmailDomains("ADO")  
response.write(RS("domain"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getemaildomains XML Example](#)

GetInvoiceDetails

Description

This method returns a data set containing all of the invoice detail data for the specified invoice.

Properties

The following properties can be set before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Invoice	String	Required. The invoice number to retrieve details for.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing invoice detail data. The data in the recordset can be accessed using the column name from the idetail table. In addition to the columns from the idetail table, the following field is available in the recordset:

<u>Field</u>	<u>Type</u>	<u>Description</u>
Amount	Money	The total of the invoice specified calculated as the sum of quantity times price.

Syntax

```
Set RS = Object.GetInvoiceDetails(Invoice, Datatype)
```

Example

Stateful Interface

```
Set RS = ox.GetInvoiceDetails("ADO", "6231")
response.write(RS("price"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getinvoicedetails XML Example](#)

GetInvoices

Description

This method returns a data set containing invoice data for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.
InvoiceType	String	Optional. A text string indicating the type of invoices to return. Valid values are "PAID" and "UNPAID". If this property is not set or is set to any other value, all invoices will be returned.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
StartDate	String	Optional. If specified, only invoices created on or after this date will be returned.
EndDate	String	Optional. If specified, only invoices created on or before this date will be returned.
InvoiceOwner	String	Optional. This value indicates if invoices sold to the customer or billed to the customer should be returned. Valid values are "Guarantor" to retrieve invoices billed to the customer and "Customer" to retrieve invoices sold to the customer. Defaults to "Guarantor".
cInvoice	String	Optional. If specified, only the data for this invoice will be returned. If left blank or set to 0, then all invoices for the selected customer will be returned.

Return Values

This method returns an ADO recordset containing invoice data. The data in the recordset can be accessed using the column name from the iheader table. In addition to the columns from the iheader table, the following field is available in the recordset:

<u>Field</u>	<u>Type</u>	<u>Description</u>
Due	Money	The unpaid amount of each invoice.

Syntax

```
Set RS = Object.GetInvoices(Datatype, StartDate, EndDate, InvoiceOwner,cInvoice)
```

Example

Stateful Interface

```
ox.custid = "1001"  
ox.invoicetype="PAID"  
Set RS = ox.GetInvoices("ADO", "11/21/2001", "11/29/2001", "Guarantor","1101")  
response.write(RS("invoice"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getinvoices XML Example](#)

GetOptions

Description

This method returns a data set that contains all of the web page options and their current values.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Package	String	Optional. The web package to return options for. The valid values for this parameter are currently "signup" and "custinfo". If you pass this parameter in, only the options for the specified packages and the options that apply to all packages will be returned.
Category	String	Optional. The web package category to load return options for. The valid categories are the names displayed on the tabs on the showoptions.asp and shwsetup.asp pages.
Table Name	String	Optional. The table in the database to retrieve options from. This value defaults to "weboptions". This property allows you to have multiple sets of options for multiple copies of the web pages.

Return Values

This method returns an ADO recordset containing the web page options and their current values. The option values in the recordset can be accessed using the column names from the weboptions table.

Syntax

```
Set RS = Object.GetOptions("ADO")
```

Example

Stateful Interface

```
Set RS = ox.GetOptions("ADO")
response.write(RS("value"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getoptions XML Example](#)

GetPaths

Description

This method returns a list of upgrade or downgrade Rate Groups for a specific Rate Group.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Storeid	Integer	Required. The company id of the customer who has the Rate Group being evaluated for an upgrade or downgrade path assigned.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nRateGroupID	Integer	Required. The rate group for which the upgrade or downgrade rate group path will be returned.
nPathType	String	Required. If set to upgrade, returns upgrade path rate groups. If set to Downgrade, returns downgrade path rate groups.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing Rate Groups in the upgrade or downgrade path for a specific Rate Group.

Syntax

Set RS = Object.GetPaths(nRateGroupID,cPathType,nDatatype)

Example

Stateful Interface

Set RS = ox.getpaths(47,"UPGRADE","ADO")

Stateless Interface

[GetPaths XML Example](#)

GetPaymentDetails

Description

This method returns a data set containing all of the payment detail data for the specified payment.

Properties

The following properties can be set before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Payid	String	Required. The payment header id of the payment. This value is stored in the pmt_id column of the pheader table and the pd_hdr_id column of the pdetail table.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing payment detail data. The data in the recordset can be accessed using the column names from the pdetail table.

Syntax

```
Set RS = Object.GetPaymentDetails(Payid, Datatype)
```

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetPaymentDetails("2312","ADO")
response.write(RS("pd_amount"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getpaymentdetails XML Example](#)

GetPayments

Description

This method returns a data set containing payment data for the specified customer.

Properties

The following properties can be set before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
StartDate	String	Optional. If specified, only payments created on or after this date will be retrieved.
EndDate	String	Optional. If specified, only payments created on or before this date will be retrieved.
cPayID	String	Optional. If specified, only the data for this payment id will be returned. If left blank or set to 0, then all payments for the selected customer will be returned.

Return Values

This method returns an ADO recordset containing payment data. The data in the recordset can be accessed using the column name from the pheader and payment_types tables.

Syntax

Set RS = Object.GetPayments(Datatype, StartDate, EndDate,CPayID)

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetPayments("ADO","02/01/2006","02/28/2006","10")
response.write(RS("pmt_total"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getpayments XML Example](#)

GetPaymentTypes

Description

This method returns all of the payment types stored in the database. The payment types returned can be limited using the parameters of the method.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Active	String	Optional. Can be "Y" to limit the returned data set to only active payment types or "N" to limit the returned data set to only inactive payment types. Defaults to the empty string.
PaymentTypeID	Integer	Optional. If a payment type id number is specified, only data for that one payment type will be returned. Defaults to False.

Return Values

This method returns a recordset containing all of the payment types stored in the database for success or a 0 for error. All of the columns in the payment_types table are included in the recordset. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.GetPaymentTypes(Datatype, Active, PaymentTypeID)

Example

Stateful Interface

Stateless Interface

[Getpaymenttypes XML Example](#)

GetPhone

Description

This method returns a data set containing all of the phone data for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.
PhoneType	String	Optional. This property must be a valid name of a phone type from the Name column in the Phone_Type table. If it is specified, only the information for that one phone type will be retrieved. If it is not specified, all of the customers phone information will be retrieved.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing address data. The data in the recordset can be accessed using the column names from the phone and phone_type tables in addition to the field name below:

<u>Field</u>	<u>Type</u>	<u>Description</u>
PhoneMasked	String	The phone number with the mask from Maintenance-Options applied to it.

Syntax

```
Set RS = Object.GetPhone("ADO")
```

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetPhone("ADO")
response.write(RS("number"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[GetPhone XML Example](#)

GetPlatOption**Description**

This method returns the value of the specified Platypus option.

Parameters

Parameter	Type	Description
option	String	Required. The name of the Platypus option whose value should be retrieved.
reload	Boolean	Optional. True to force all Platypus options to be reloaded into memory, False to only reload all options into memory if an option value has been updated since they were previously loaded. Defaults to False.
company	Integer	Optional. For company specific options, this is the company id for which to pull the option.

Return Values

This method returns the value of the specified Platypus option for success, the empty string if the specified option is not found.

Example

[GetPlatOption XML Example](#)

GetPreviousUsage

Description

This method determines the billing cycle of a customer and returns a data set of beginning and ending dates that represent the customer's previous billing periods. The number of billing periods returned is determined by the Previous Months of Usage option on the showoptions.asp page.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.
Startday	String	Required. The day of the month the customer's billing period begins. This property is set to the appropriate value in the InitUsage method.
Endday	String	Required. The day of the month the customer's billing period ends. This property is set to the appropriate value in the InitUsage method.

Required Methods

The Object.InitUsage() method must be called before calling this method.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
DataType	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the following fields:

<u>Field</u>	<u>Type</u>	<u>Description</u>
BeginDate	String	The beginning date of the billing period in short date format using the Regional Settings format from Windows. Example: "11/1/2001"
EndDate	String	The ending date of the billing period in short date format using the Regional Settings format from Windows. Example: "11/30/2001"
BeginLong	String	The beginning date of the billing period in long date format with the name of the month spelled out.
EndLong	String	The ending date of the billing period in long date format with the name of the month spelled out.

out.

Syntax

Object.GetPreviousUsage(Datatype)

Example

Stateful Interface

```
ox.custid = "1234"  
ox.InitUsage()  
Set RS = ox.getprevioususage("ADO")  
response.write(RS("BeginDate"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getprevioususage XML Example](#)

GetRates

Description

This method returns a data set containing all of the data for the rate groups assigned to the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Data Type	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing data for the rate groups assigned the specified customer. The data in the recordset can be accessed using the column names from the custrate and rgheader tables.

Syntax

```
Set RS = Object.GetRates("ADO")
```

Example

Stateful Interface

```
ox.custid = "1001"  
Set RS = ox.GetRates("ADO")  
response.write(RS("rgid"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Getrates XML Example](#)

GetRatingInfo**Description**

This method returns service based billing details for the specified service based on the services billing class.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
SvcID	String	Required. The id number of the service. These can be found in the svc_id column of the svc_defs table.
DataID	String	Required. The data id of the customer service. This can be found in the data_id column of the service's data table.
LastBilled	String	Required. The start date of the service period to use in calculating usage.
NextBill	String	Required. The end date of the service period to use in calculating usage.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a recordset containing service based billing details for the specified service based on the services billing class for success or 0 for error. The fields in the recordset will vary based on the rating library. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.GetRatingInfo(SvcID, DataID, LastBilled, NextBill, Datatype)

Example

Stateful Interface

```
Set RS = ox.getratinginfo("2","91","8/19/2004","9/19/2004","ADO")
```

Stateless Interface

[Getratinginfo XML Example](#)

GetReferrals

Description

This method returns a data set containing all referral bonuses that have been given to the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
RefType	String	Required. This is the type of referrals to display. The value should be "I" for issued referrals, "P" for pending referrals, or "D" for details of issued referrals.
Payid	String	Optional. The payment id of the referrals to display. This parameter is only used if RefType is set to "D". To show details of pending referrals, either set Payid to "0" or don't pass in a value for Payid.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset. The contents of the recordset are as follows depending on the value of the RefType parameter.

Reftype = "I"

<u>Field</u>	<u>Type</u>	<u>Description</u>
Total	Money	The total amount of the bonus
PaidDate	Date	The date the bonus was issued
Payid	Int	Unique id indicating which payment this bonus was applied to.

Reftype = "P"

The ADO recordset will contain all of the columns from the bonus_act table plus the following additional column.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Name	String	The name of the customer.

Reftype = "D"

The ADO recordset will contain all of the columns from the bonus table plus the following additional columns.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Name	String	The name of the customer.
InvoicePaid	Money	The paid amount on the invoice.
InvoiceTotal	Money	The total on the invoice.

Syntax

Object.GetReferrals(RefType, Payid, Datatype)

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetReferrals("I")
response.write(RS("Total"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getreferrals XML Example](#)

GetReportCategories

Description

This method returns a data set of Report Wizard categories that the currently logged in user has security permission to access.

Parameter

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a data set of Report Wizard categories that the currently logged in user has security permission to access. If an error occurs, zero is returned and the error message can be accessed by using the [LastError](#) property of the web object.

Syntax

Object.GetReportCategories(Datatype)

Example

Stateful Interface

```
Set RS = ox.getreportcategories()
if RS = 0 then
    response.write(ox.lasterror)
else
    response.write(RS("category"))
end if
```

Stateless Interface

[Getreportcategories XML Example](#)

GetReportDetails**Description**

This method returns information about a specific report that is necessary to run that report. The returned data set contains all of the columns from the reports table which includes such things as the selection formulas, the selection criteria, and the report file name.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
ReportID	String	Required. The id number of the report. This can be found in the id column of the reports table.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc.

Return Values

This method returns a recordset containing information about a specific report that is necessary to run that report for success or a 0 for error. The recordset contains all of the columns from the reports table. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.GetReportDetails(ReportID, Datatype)

Example

Stateful Interface

```
Set RS = ox.getreportdetails("16","ADO")
```

Stateless Interface

[Getreportdetails XML Example](#)

GetReports

Description

This method returns a data set of reports that the logged in user has permission to access.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
ReportCategory	String	Optional. The Report Wizard category from which to select reports. If not specified, reports will be selected from all categories.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a data set containing all reports in the specified category that the currently logged in user has permission to access. The data in the recordset can be accessed using the following field names.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Name	String	The displayed name of the report such as "Aged Accounts Receivable".
Description	String	The description of the report. This can be seen in the gray box on the Report Wizard in Platypus.
FileName	String	The physical file name of the report files such as agedar.rpt.
ListOrder	Int	The integer value that represents where in the list of reports this report appears in the Report Wizard.

Syntax

```
Set RS = Object.GetReports(ReportCategory, Datatype)
```

Example

Stateful Interface

```
Set RS = ox.GetReports("Customer", "ADO")
response.write(RS("name"))
RS.Close
Set RS = Nothing
```

Stateful Interface

[Getreports XML Example](#)

GetReportFile

Description

This method generates a report and returns it in binary format.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
ReportID	String	Required. The id number of the report. This can be found in the id column of the reports table.
StartDate	String	Required. The start date of the date range.
EndDate	String	Required. The end date of the date range.
StartID	String	Required. The smallest id in the id range.
EndID	String	Required. The largest id in the id range.
StoreID	String	Required. The company id.
Datatype	String	Optional. Type of data returned from the method. This method returns XML data.

Return Values

Syntax

Object.GetReportFile(ReportID, StartDate, EndDate, StartID, EndID, StoreID,Datatype)

Example

Stateful Interface

This method does not have a Stateful Interface.

Stateless Interface

[GetReportFile XML Example](#)

GetServiceDefs**Description**

This method returns the service definition information from the svc_defs table for all services or the service specified by the cServiceID parameter.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
ServiceID	String	Optional. If set to a valid service id number, the data set is limited to only that service. Service ids can be found in the svc_id column of the svc_defs table.

Return Values

This method returns a recordset containing service definition information for success or a 0 for error. All of the columns from svc_defs table are included in the recordset. If a 0 is returned, the LastError property will contain the error message

Syntax

Object.GetServiceDefs(Datatype, ServiceID)

Example

Stateful Interface

```
Set RS = ox.getservicedefs("ADO","1")
```

Stateless Interface

[GetServiceDefs XML Example](#)

GetServiceDetail

Description

This method returns a data set containing all of the data from the service data table for the specified service instance.

Properties

The following properties must be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
SvcID	String	Required. The id number of the service type.
DataID	String	Required. The unique id of the instance of the service.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing all of the data from the service data table for the specified service instance. The data can be referenced by the column names from the service data table..

Syntax

Object.GetServiceDetail(SvcID, DataID, Datatype)

Example

Stateful Interface

```
ox.custid = "1001"  
Set RS = ox.GetServiceDetail("1", "123")  
response.write(RS("d_custid"))
```

Stateless Interface

[Getservicedetail XML Example](#)

GetServiceInfo

Description

This method returns a data set containing information on the custom fields associated with a service. This includes the column name, the display name, the type of control used to display it (txt_text, dropdown, dropword), the readonly flag, the required flag, etc.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nServiceTypeID	Integer	Required. The id number of the service type.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
nRGID	Integer	Optional. Rate group id used to determine Service Template defaults.
nCRID	Integer	Optional. Assigned Rate Group ID used to determine Service Template defaults.

Return Values

This method returns different values based on the parameters that are passed to it.

If nRGID and nCRID are not passed in, are invalid, or are 0 (zero), then the default values for all Custom Fields on the Service Type will be returned.

If nRGID is passed in, then the default values for the Service Template set on the Rate Group will be returned. Any Custom Fields not included in the Service Template will use the default values for the Custom Fields.

If nCRID is passed in, then the default values for the Rate Group on the Assigned Rate Group is retrieved. Then the default values for the Service Template on the Rate Group will be returned. Any Custom Fields not included in the Service Template will use the default values for the Custom Fields. This parameter is ignored if nRGID contains a valid Rate Group ID.

Syntax

```
Object.GetServiceInfo(nServiceTypeID,cDatatype,nRGID,nCRID)
```

Example

Stateful Interface

```
Set RS = ox.GetServiceInfo("1")
response.write(RS("datacol"))
```

Stateless Interface

[GetServiceInfo XML Example](#)

GetStaffNotes

Description

This method returns a data set containing all of the notes data for the specified customer or staff member.

Properties

One of the following properties can be set on the object before this method is called. If the Custid property is specified, it will retrieve all notes from that customers record. If the Custid property is not specified, the Staffid property is required and it will retrieve all notes that have been assigned to that staff member.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer. If this property is specified, the Staffid property is ignored. This can be set to the Customer's ID or the ID number of any child account. Otherwise, this is ignored. If left blank, it will only return Tasks/Notes for the logged in Customer.
Staffid	String	Required. The id number of the staff member. Required if Custid property is not specified or ignored otherwise.
NoteNumber	String	Optional. The id number of a specific note to retrieve. This value is from the id column in the custmsg table. Can be set to any valid Task/Note ID, which will return a single Task/Note
NoteIDType	String	Optional. Can be set to one of 3 things: STAFF, CUSTOMER or a blank string (""). When set to CUSTOMER, the property CUSTID will be used to filter the results based on Customer ID. If the CUSTID property is left blank or set to 0 (zero), Tasks/Notes which are not attached to a Customer will be returned. When set to STAFF or a blank string, the property STAFFID will be used to filter the results based on Staff Assigned to the Tasks/Notes. If the STAFFID property is set to 0 (zero) or left blank, the NOTEIDTYPE and STAFFID properties will be ignored
NoteType	String	Optional. The type of notes to retrieve. This parameter has four valid values: "INCOMPLETE" to retrieve only incomplete notes, "COMPLETE" to retrieve only complete notes, and "WAITING" to retrieve only waiting notes, ""(blank string). When set to a blank string, the results will not be filtered by the Status. If this property is not specified or is set to any other value, this property will be ignored. When set to a valid value, it will only return Tasks/Notes that have the input Status.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing notes data. The data in the recordset can be accessed using the column name from the custmsg and the following field:

<u>Field</u>	<u>Type</u>	<u>Description</u>
Username	String	The username of the customer on whose record the note appears.

Different Methods of Calling when logged in as a Staff Member

When logged in as a Staff Member, any combination of Notetype, NoteIDTYPE, and NOTENUMBER can be used.

Different Methods of Calling when logged in as a Customer

When logged in as a Customer, any combination of Notetype, NteIDTYPE, and CustID can be used.

Syntax

```
Set RS = Object.GetStaffNotes("ADO")
```

Example

Stateful Interface

```
ox.custid = "1001"
Set RS = ox.GetStaffNotes("ADO")
response.write(RS("message"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getstaffnotes XML Example](#)

GetStores

Description

This method returns a recordset of all the stores currently loaded in memory.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the stores name and id. The fields can be referenced by the names "storeid" and "name".

Syntax

Object.GetStores(Datatype)

Example

Stateful Interface

```
Set RS = ox.GetStores("ADO")  
response.write(RS("name"))
```

Stateless Interface

[Getstores XML Example](#)

GetTimeClockStatus**Description**

This method returns the last clock in and clock out times for all staff members or the staff member(s) specified by the staffIDList parameter. For staff members who are currently clocked in, the last clock out time will be returned as NULL.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
StaffIDList	String	Optional. A comma separated list of staff member ids that limits the returned data set to only those staff members.

Return Values

This method returns a recordset of data for success or a 0 for error. The recordset includes the fields below. If a 0 is returned, the LastError property will contain the error message.

<u>Field</u>	<u>Type</u>	<u>Description</u>
Tc_staffid	Integer	The id number of the staff member.
LastClockIn	Date	The date and time this staff member last clocked in.
LastClockOut	Date	The date and time this staff member last clocked out. If the staff member is currently clocked in, this value will be NULL.

Syntax

Object.GetTimeClockStatus(Datatype, StaffIDList)

Example

Stateful Interface

```
Set RS = ox.gettimeclockstatus("ADO", "")
```

Stateless Interface

[Gettimeclockstatus XML Example](#)

GetUsage

Description

This method returns a data set containing usage information for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
BeginDate	String	Optional. The beginning date of the date range to calculate usage for. Defaults to customers current billing cycle.
EndDate	String	Optional. The ending date of the date range to calculate usage for. Defaults to customers current billing cycle.
Username	String	Required. The customer's username.

Required Methods

The following method must be called before the GetUsage method can be called.

Object.InitUsage()

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset that contains usage information for the specified customer. The fields in the recordset are listed below. This method also sets a property that contains the total amount of time the customer was online between the dates specified. The property can be referenced as:

Object.TotalTime		
<u>Field Name</u>	<u>Type</u>	<u>Description</u>
LinkDate	String	The date in short date format. The GetUsageDay method requires the date to be in this format. Example: "05/10/00"
DispDate	String	The date in long date format. It is displayed on the web pages so there will be no confusion about whether the date is in MM/DD or DD/MM format. Example: "May 10, 2000"
Calls	String	The total number of calls received on the specific date.
AvgLen	String	The average call length for the specific date.

TtlTime	String	The total time the customer was online for the specific date.
OrderDate	Date	The date that is used to order the usage information regardless of the date format chosen in Regional Settings. If it is displayed, it will be interpreted based on date options under Regional Settings.
Total_In	Int	The total number of bytes downloaded by the customer on the specific date.
Total_Out	Int	The total number of bytes uploaded by the customer on the specific date.
Total_InOut	Int	The total number of bytes transferred (uploaded and downloaded) by the customer on the specific date.

Syntax

Object.GetUsage("ADO")

Example

Stateful Interface

```

ox.custid = "1001"
ox.Begin = "01/01/2000"
ox.End = "12/31/2000"
retval = ox.InitUsage()
Set RS = ox.GetUsage("ADO")
response.write(RS("LinkDate"))
RS.Close
Set RS = Nothing

```

Stateless Interface

[Getusage XML Example](#)

GetUsageByTerm

Description

This method returns a data set that includes a customers usage for the current billing period grouped together by which terminal servers he connected to.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Username	String	Required. The customer's username.
Begin	String	Optional. The beginning date of the date range to calculate usage for. Defaults to customers current billing cycle.
End	String	Optional. The ending date of the date range to calculate usage for. Defaults to customers current billing cycle.

Required Methods

The Object.InitUsage() method must be called before calling this method.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the following fields:

<u>Field</u>	<u>Type</u>	<u>Description</u>
TermName	String	The name of the terminal server that was connected to.
OldestCall	String	The oldest call dialed into the terminal server during the billing period.
LatestCall	String	The most recent call dialed into the terminal server during the billing period.
Calls	String	The total number of calls connected to the terminal server during the billing period.
TtlTime	String	The total time of all calls connected to the terminal server during the billing period. This value is expressed in hours, minutes, and seconds.
Total_In	Int	Optional. If the web pages are configured to display data transferred in, this value will be the total bytes, kilobytes, or megabytes transferred in

		during the billing period depending upon the setting of the Data In Units option on the showoptions.asp page. If the Data In Units option is set to "Not Displayed", this field will not exist in the recordset.
Total_Out	Int	Optional. If the web pages are configured to display data transferred out, this value will be the total bytes, kilobytes, or megabytes transferred out during the billing period depending upon the setting of the Data Out Units option on the showoptions.asp page. If the Data Out Units option is set to "Not Displayed", this field will not exist in the recordset.
Total_InOut	Int	Optional. If the web pages are configured to display total data transferred, this value will be the total bytes, kilobytes, or megabtes transferred during the billing period depending on the setting of the Data In/Out Units option on the showoptions.asp page. If the Data In/Out Units option is set to "Not Displayed", this field will not exist in the recordset.

Syntax

Object.GetUsageByTerm(Datatype)

Example*Stateful Interface*

```

ox.username = "joeuser"
retvalue = ox.initusage()
Set RS = ox.getusagebyterm("ADO")
response.write(RS("TermName"))
RS.Close
Set RS = Nothing

```

Stateless Interface

[Getusagebyterm XML Example](#)

GetUsageDay

Description

This method returns a data set containing a customer's usage for a single day.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Username	String	Required. The customer's username.
UsageDate	String	Required. The date for which usage should be determined. This value should be in valid short date format. Example: "11/25/2001"

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an ADO recordset containing the following fields:

<u>Field</u>	<u>Type</u>	<u>Description</u>
CallStart	Date	The date and time the call started.
CallEnd	Date	The date and time the call ended.
CallMin	String	The number of minutes that the call lasted.
TtlTime	String	The total time of the call expressed in hours, minutes, and seconds.
Total_In	Int	Optional. If the web pages are configured to display data transferred in, this value will be the total bytes, kilobytes, or megabytes transferred in during the call depending upon the setting of the Data In Units option on the showoptions.asp page. If the Data In Units option is set to "Not Displayed", this field will not exist in the recordset.
Total_Out	Int	Optional. If the web pages are configured to display data transferred out, this value will be the total bytes, kilobytes, or megabytes transferred out during the call depending upon the setting of the Data Out Units option on the showoptions.asp page. If the Data Out Units option is set to "Not Displayed", this field will not exist in the recordset.

Total_InOut	Int	Optional. If the web pages are configured to display total data transferred, this value will be the total bytes, kilobytes, or megabtes transferred during the call depending on the setting of the Data In/Out Units option on the showoptions.asp page. If the Data In/Out Units option is set to "Not Displayed", this field will not exist in the recordset.
-------------	-----	--

This method also populates the Object.TotalTime property with the total time of all calls received on this day expressed in hours, minutes, and seconds.

Syntax

Object.GetUsageDay(Datatype)

Example

Stateful Interface

```
ox.username = "joeuser"
ox.usagedate = "11/25/2001"
Set RS = ox.getusageday("ADO")
response.write(RS("CallStart"))
RS.Close
Set RS = Nothing
```

Stateless Interface

[Getusageday XML Example](#)

GetWebOption

Description

This method retrieves the value for a web package option. All web package options are stored in the weboptions table and are accessed from the web via the shwsetup.asp and showoptions.asp pages.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
OptionName	String	Required. The name of the option whose value is being retrieved. This name is stored in the name column of the weboptions table.
Store_Appended	Boolean	Optional. Flag indicating whether store id has already been appended to the option name or not. Value should be True if the store id has already been appended or False if it has not. Defaults to False.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string containing the value of the specified option.

Syntax

```
option_value = Object.GetWebOption(OptionName,Store_Appended,Datatype)
```

Example

Stateful Interface

```
option_value = ox.GetWebOption("enable_cc")
```

Stateless Interface

[Getweboption XML Example](#)

IsChild

Description

This method checks to see if the specified customer is a child account of the specified guarantor. It is used to allow guarantors to access their child accounts online without having access to other accounts.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
GuarantorID	String	Required. The id number of the guarantor account being checked.
ChildID	String	Required. The id number of the child account being checked.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns true if the ChildID is a child account of the GuarantorID or false if he is not.

Syntax

Object.IsChild(GuarantorID, ChildID,Datatype)

Example

Stateful Interface

```
retvalue = ox.ischild("1234", "5432")
```

Stateless Interface

[Ischild XML Example](#)

IsDupCCNumber

Description

This method checks the specified credit card number against the database to determine if the same number is already in use by another customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CCNumber	String	Required. Credit card number to check.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns the customer id of the customer who is already using the specified credit card number for success or 0 if no customer currently has that error. This method also returns a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.IsDupCCNumber(CCNumber, Datatype)

Example

Stateful Interface

```
ret = ox.isdupccnumber("4005550000000019","ADO")
```

Stateless Interface

[isdupccnumber XML Example](#)

IsGuarantor

Description

This method checks the specified customer to see if they have any child accounts in the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer who is being checked to see if he is a guarantor.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns true if the customer is a guarantor or false if he is not.

Syntax

Object.IsGuarantor(Custid,Datatype)

Example

Stateful Interface

```
retvalue = ox.isguarantor("1234")
```

Stateless Interface

[Isguarantor XML Example](#)

LaunchUM

Description

Fires the external manager action associated with the UM_ option specified.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	Integer	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Action	String	Required. The name of the UM_ action that should be fired. Example: UM_New Save
Dataid	String	Required for Email or Domain service commands. The unique data id of the email or domain service.
DoSql	String	Optional. Determines whether or not a new SQL connection is made. Value should be "1" to create a new SQL connection or "0" to use an existing SQL connection. Defaults to "1" if not specified.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns "true" for success or an error message.

Syntax

Object.LaunchUM(Action, Dataid, DoSQL,Datatype)

Example

Stateful Interface

```
ox.custid = "1001"
ox.launchum("UM_New Save")
```

For email/domain service commands:

```
ox.custid="1001"
ox.launchum("UM_New Save Email", "210")
```

Stateless Interface

[Launchum XML Example](#)

ListServiceInstances**Description**

This method returns an recordset containing information about all the service instances under a Customer. This can be filtered by Customer Rate, Service Definition and/or Service Instance.

Properties

The following properties can be set on the object before this method is called.

Property	Type	Description
Custid	String	Required. The id number of the customer.

Parameters

Both parameters are optional, but they must neither be passed in or both be passed in.

Parameter	Type	Description
SvcID	String	Optional. The unique identifier of the Service Definition. If used, only Service Instances of this Service Definition will be returned.
DataID	String	Optional. The unique identifier of the Service Instance to retrieve. If used, only the specific Service Instance specified will be returned.
Datatype	String	Optional. Type of data returned from the method. Defaults to XML.
CRID	String	Optional. The unique identifier of the Customer Rate. If used, only Service Instances under this Customer Rate will be returned.

Return Values

This method returns an recordset containing the following information.

Field	Type	Description
s_name	String	The descriptive name of the Service Instance
s_data	String	The friendly name of the Service Instance
s_num	Int	The unique identifier of the Service Instance
s_active	String	The active status of the Service Instance
s_svc_id	Int	The unique identifier of the Service Definition
s_customer_name	String	The name of the Customer, which owns the Service Instance
s_customer_id	Int	The unique identifier of the Customer
s_struct_id	Int	The branch in the Service Tree on the Rate Group
s_parent_id	Int	The parent Service Instance, if the Service Instance is a child of another.
s_parent_type	String	The parent Service Definition, if the Service Instance is a child of another.
s_custrate	Int	The unique identifier of the Customer Rate
s_svc_seq	Int	The sort order for the Service Definition

[ListServiceInstances XML Example](#)

ListServiceInstances**Description**

This method returns an recordset containing information about all allows Services under a Rate Group or a Customer.

Properties

The following properties can be set on the object before this method is called.

Property	Type	Description
Custid	String	*Required. The unique identifier of the customer.

Parameters

Both parameters are optional, but they must either be passed in or both be passed in.

Parameter	Type	Description
Datatype	String	Optional. Type of data returned from the method. Defaults to XML.
RGID	String	Required. The unique identifier of the Rate Group.

*Note: Either the custid property or the rgid parameter is required. If both included, only the custid will be used.

Return Values

This method returns an recordset containing the following information.

Field	Type	Description
rs_id	Int	The branch in the Service Tree on the Rate Group.
rs_parent_id	Int	The parent branch in the Service Tree on the Rate Group.
rs_rg_id	Int	The unique identifier of the Rate Group.
rs_cr_id	Int	The unique identifier of the Customer Rate.
rs_svc_id	Int	The unique identifier of the Service Definition.
rs_svc_qty	Int	The total number of allowed Service Instances for this Service Definition. If the Customer Rate has a quantity greater than one, then any Service Definitions in the root of the Service Tree will have the allowed multiplied by the quantity.
rs_base_qty	Int	The base number of allowed Service Instances for this Service Definition, as specified on the Rate Group.
rs_path	String	The friendly name of the Service Definition. For branches that are children of another branch it will take the format Parent->Child
rs_order	Int	The sort order of the branch within the Service Tree.
rs_parent_service	Int	The unique identifier of the Service Definition that is the parent of this branch.
rs_parent_instance	Int	The unique identifier of the Service Instance that is the parent

		of this branch.
rs_used	Int	The total number of used Service Instances for this branch.
rs_total	Int	The total number of used Service Instances for this branch.
rs_ccs_service	String	The OpenSRS service for this branch. This can be domain or none.
rs_hidden	String	(Y/N) Whether the branch is hidden from customers.

[ListServiceTree XML Example](#)

ListServices2**Description**

This method returns an recordset containing information about all the service instances under a Customer. This can be filtered by Customer Rate.

Properties

The following properties can be set on the object before this method is called.

Property	Type	Description
Custid	String	Required. The id number of the customer.

Parameters

Both parameters are optional, but they must either be passed in or both be passed in.

Parameter	Type	Description
CRID	String	Optional. The unique identifier for the Customer Rate
Datatype	String	Optional. Type of data returned from the method. Defaults to XML.

Return Values

This method returns an recordset containing the following information.

Field	Type	Description
s_name	String	The descriptive name of the Service Instance
s_data	String	The friendly name of the Service Instance
s_num	Int	The unique identifier of the Service Instance
s_active	String	The active status of the Service Instance
s_svc_id	Int	The unique identifier of the Service Definition
s_customer_name	String	The name of the Customer, which owns the Service Instance
s_customer_id	Int	The unique identifier of the Customer
s_struct_id	Int	The branch in the Service Tree on the Rate Group
s_parent_id	Int	The parent Service Instance, if the Service Instance is a child of another.
s_parent_type	String	The parent Service Definition, if the Service Instance is a child of another.
s_custrate	Int	The unique identifier of the Customer Rate
s_svc_seq	Int	The sort order for the Service Definition

Example

[ListServices2 XML Example](#)

LogChange

Description

This method is used to log changes to the Staff Log. A wide variety of changes are logged including updates to customer records, additions of addresses, phones, and rates to customers, changes made to option values, the creation of payments, the application of payments to invoices, etc.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Tagname	String	Required. Name of the logging option item.
KeyID	String	Required. Unique id of the item being logged. This can be a customer id when logging an update to a customer's account, a payment id when logging a payment being created or applied, an option id when logging a change to an option value, etc.
Comment	String	Required. Comment that describes what change took place.
OldValue	String	Required. When logging an update to a field, this is the previous value of the field that is being changed. Otherwise, it is left blank.
NewValue	String	Required. New value of the field being changed.
KeyType	String	Optional. Type of item being logged. Examples include "Customer", "Payment", "Option", "Email_data", etc. When this parameter is left off, it tries to determine the value based on the TagName. If it can't determine a value from the TagName, it uses "Web" as the value.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns "1" for success or "0" for failure. If an error occurs, the [LastError](#) property can be referenced to determine the error message.

Syntax

Object.LogChange(TagName, KeyID, Comment, OldValue, NewValue, KeyType, Datatype)

Example

Stateful Interface

```
retvalue = ox.LogChange("Customer Table Updated","1234","Customer.Statement Method Updated
from Customer Info web pages","PAPER","EMAIL")
```

Stateless Interface[Logchange XML Example](#)

Login

Description

This method is used to login as a customer or a staff member and determine if the specified username and password are valid.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
LoginType	String	Required. The type of login being attempted. Valid values are "Staff" and "Customer".
Username	String	Required. The username of the customer or staff member.
Password	String	Required. The password of the customer or staff member.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string containing the id number of the customer or staff member for successful logins or the string "0" if the login failed or an error occurred. If "0" is returned, the LastError property will contain the error message.

Syntax

Object.Login(LoginType, Username, Password, Datatype)

Example

Stateful Interface

```
ret = ox.login("Customer","mfdoomjr","danger","ADO")
```

Stateless Interface

[Login XML Example](#)

OpenSRSGenProfile**Description**

This method generates a random username and password for use as an OpenSRS Profile.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and the error message or the username and password for success.

Syntax

Object.OpenSRSGenProfile(Datatype)

Example

Stateful Interface

```
ret = ox.opensrsgenprofile("ADO")
```

Stateless Interface

[OpenSRSGenProfile XML Example](#)

OpenSRSGetProfile

Description

This method returns OpenSRS authentication information that is stored on the Platypus customer record.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nCustID	Integer	Required. The id number of the customer on which the OpenSRS profile is being retrieved.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

Object.OpenSRSGetProfile(nCustID,cDatatype)

Example

Stateful Interface

```
ret = ox.opensrsgetprofile("6842","ADO")
```

Stateless Interface

[OpenSRSGetProfile XML Example](#)

OpenSRSSetProfile**Description**

This method saves an OpenSRS profile to a Platypus customer record.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nCustID	Integer	Required. The id number of the customer on which the OpenSRS profile is being set.
cUsername	String	Required. The OpenSRS username.
cPassword	String	Required. The OpenSRS password.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

Object.OpenSRSSetProfile(nCustID,cUsername,cPassword,,cDatatype)

Example*Stateful Interface*

```
ret = ox.opensrssetprofile("1001","username","password","ADO")
```

Stateless Interface

[OpenSRSSetProfile XML Example](#)

Post

Description

Posts charges for a customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
NoConn	Boolean	Optional. Pass False to have the method create its own connection to the database or True to have the method use an existing connection.
Days	String	Optional. Days in advance to post. This allows you to override the "Days in Advance to Post" option setting on the shwsetup.asp page.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns nothing.

Syntax

Object.Post()

Example

Stateful Interface

```
ox.custid = "1001"  
ox.post()
```

Stateless Interface

[Post XML Example](#)

PostPayment

Description

This method creates a payment and applies it to the list of invoices that are passed in.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
CCV2	String	Optional unless required by the Payment Gateway. The credit card verification number from the back of the credit card.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Tender	Numeric	Required. The tendered amount of the payment. This is the total amount of the payment.
PayDate	String	Required. The date the payment was received.
Invoices	String	Required. A list of invoices to apply the payment to. This can be passed in as the empty string to create a credit.
PayTypeId	String	Required. This is the unique id value for the type of payment being entered.
Custid	String	Required. The id number of the customer who is making the payment.
PayNum	String	Required. The check/credit card number for the payment.
PayName	String	Required. The name of the person making the payment. This should be the name on the credit card for credit card payments.
ChargeCC	Numeric	Required. This is a flag that determines whether or not to charge credit cards in real time. The value should be 1 to charge the card in real time or 0 to enter the payment without charging the card.
Ignore	Boolean	Required. This parameter is no longer used in the method but is required as a placeholder. The value of this parameter should be False.
Ignore	Boolean	Required. This parameter is no longer used in the method but is required as a placeholder. The value of this parameter should be False.
CCExpire	String	Required only for credit card transactions. The expiration date of the credit card.
NoConn	Boolean	Optional. Flag indicating whether or not a SQL connection should be created and destroyed inside of the method. Value should be False to create and destroy a connection inside of the method or True if an existing SQL connection should be used. Defaults to False.
AuthOnly	Boolean	Optional. Flag indicating whether credit card should be charged or just authorized. Value should be False to charge the card or True to authorize it. Defaults to False.
RouteNumber	String	Required only for eCheck transactions. Bank routing number.
AcctType	String	Required only for eCheck transactions. Flag indicating whether

		the bank account to be debited is a checking or savings account. Value should be "CHECKING" for checking account or "SAVINGS" for savings account.
BankName	String	Optional. The name of the bank.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
Address	String/Boolean	Optional. The customer's credit card address. If passed in as a boolean False, the parameter is populated by the credit card address on the customer account.
City	String/Boolean	Optional. The customer's credit card city. If passed in as a boolean False, the parameter is populated by the credit card city on the customer account.
State	String/Boolean	Optional. The customer's credit card state. If passed in as a boolean False, the parameter is populated by the credit card state on the customer account.
Zip	String/Boolean	Optional. The customer's credit card zip. If passed in as a boolean False, the parameter is populated by the credit card zip on the customer account.
Country	String/Boolean	Optional. The customer's credit card country. If passed in as a boolean False, the parameter is populated by the credit card country on the customer account.

Return Values

This method returns a message indicating success or failure.

Syntax

Object.PostPayment(tender,paydate,invoices,paytypeid,custid,paynum,payname,useicverify,cdid,ignore,c
cexpire,NoConn,AuthOnly,RouteNumber,
AcctType,BankName,Datatype,Address,City,State,Zip,Country)

Example

Stateful Interface

```
retvalue = ox.PostPayment(20.00, "01/01/99", "2134, 2254, 3341", "10", "1001", "4005550000000019",  
"Joe Test", 1, "1", "0", "11/30/02")
```

Stateless Interface

[Postpayment XML Example](#)

SearchCustomer

Description

This method searches for customers that match a specified search criteria and returns an ADO recordset of customer data for customers that match that criteria. The customers' name, attention, phone number, customer id, and username is compared to the search string for matches.

Properties

The following properties can be set before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Search	String	Required. The string to search for. This search string is compared to the customers' name, attention, phone number, customer id, and username.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
DataType	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"
WhereClause	String	Optional. If specified, this where clause is appended to the existing where clause to limit the search. The WhereClause parameter should not include the word "where". It should be in the format similar to the example below: "customer.active = 'Y' and customer.date >= '01/01/2001'"
StoreList	String	Optional. Comma delimited list of store ids. If specified, only customers in these stores will be returned from the search.

Return Values

This method returns an ADO recordset containing customer data for customers that match the search criteria . The following fields are available for access in the recordset:

<u>Field</u>	<u>Type</u>	<u>Value</u>
Name	String	The name of the customer from the name column of the customer table.
Attn	String	The attention field from the default address of the customer. This comes from the attn column of the customer table.
ID	Int	The customer id number from the id column of the customer table.
Username	String	The username of the customer from the username column of the customer table.
Phone	String	The default phone number of the customer from the phone column of the customer table.
PhoneMasked	String	The customer's default phone number

Active	String	with the phone mask applied to it. The active status of the customer. Possible values are "Active", "Hold", "Suspend", and "Inactive".
--------	--------	---

Syntax

Set RS = Object.SearchCustomer(DataType, WhereClause,StoreList)

Example

Stateful Interface

```
ox.custid = "1001"  
Set RS = ox.SearchCustomer("ADO")  
response.write(RS("name"))  
RS.Close  
Set RS = Nothing
```

Stateless Interface

[Searchcustomer XML Example](#)

SearchServices

Description

This method allows you to search a specified service for a specified string value.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
ServiceID	Integer	Required. The id number of the service to search. Service ids can be found in the svc_id column of the svc_defs table.
SearchString	String	Required. The value to search for.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a recordset of data for success or a 0 for error. The recordset contains the fields below. If a 0 is returned, the LastError property will contain the error message.

<u>Field</u>	<u>Type</u>	<u>Description</u>
S_Name	String	The unique service code which consists of the string "SVC#" and the data id of the customer service.
S_Data	String	The value of the customer service data column. For example, the default data column for the Email service is the email address. Therefore, the email address value from this customer service would be returned in this field.
S_Num	String	The data id of the customer service.
Svc_Table	String	The name of the data table for this service.
S_Active	String	The active status of the customer service.
Svc_ID	Integer	The id number of the service. This comes from the svc_id column of the svc_defs table.
S_CustName	String	The name of the customer who owns this service.
S_CustID	Integer	The id number of the customer who owns this service.

Syntax

Object.SearchService(ServiceID, SearchString, Datatype)

Example

Stateful Interface

```
Set RS = ox.searchservices(1,"justin","ADO")
```

Stateless Interface

[Searchservices XML Example](#)

SendMail

Description

This method is used to send an email message to someone. The To and From addresses do not have to be valid customers or staff members in the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
ToAddress	String	Required. The email address the message will be delivered to.
FromAddress	String	Required. The email address of the person sending the email.
Subject	String	Required. The subject of the email message.
Body	String	Required. The text of the email message.
CCAddress	String	Optional. The carbon copy address. This is an email address that will receive a copy of the email. Defaults to the empty string.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a one for success or a zero for failure. If an error occurs, the [LastError](#) property of the web object can be accessed to obtain the error message.

Syntax

Object.SendMail(ToAddress, FromAddress, Subject, Body, CCAddress,Datatype)

Example

Stateful Interface

```
retvalue = ox.SendMail("support@microsoft.com", "platypus@boardtown.com", "Email Subject", "This is a test.", "platypus@tu cows.com", "ADO")
```

Stateless Interface

[Sendmail XML Example](#)

SetAddress

Description

This method allows you to save changes to the addresses of a customer or staff account. This method only supports the XML interface.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc.
AddressArray	Array	Required. An array containing the address values to use in updating the customer or staff account.
AddressType	Integer	Optional. The id number of the address type to update. These can be found in the id column of the address_types table.

AddressArray

<u>Array Position</u>	<u>Type</u>	<u>Description</u>
0	String	The name of the address property to update. These property names are the same as the column names in the address table.
1	Varies	The new value of the address property. The data type should match the data type of the column in the database.

Return Values

This method returns a 1 for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.SetAddress(Datatype, AddressArray, AddressType)

Example*Stateful Interface*

```
ret=ox.login("Customer","justint","abc123")
dim addrarray(1,1)
addrarray(0,0)="attn"
addrarray(0,1)="Justin Thornton"
addrarray(1,0)="addr1"
addrarray(1,1)="101 Main St"
ret = ox.setaddress("ADO",addrarray,1)
```

Stateless Interface[Setaddress XML Example](#)

SetPhone

Description

This method allows you to save changes to the phone numbers of a customer or staff account. This method only supports the XML interface.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc.
PhoneArray	Array	Required. An array containing the phone values to use in updating the customer or staff account.
PhoneType	Integer	Optional. The id number of the phone type to be updated. These can be found in the id column of the phone_types table.

PhoneArray

<u>Array Position</u>	<u>Type</u>	<u>Description</u>
0	String	The name of the phone property to update. These property names are the same as the column names in the phone table.
1	Varies	The new value of the phone property. The data type should match the data type of the column in the database.

Return Values

This method returns a 1 for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax**Example***Stateful Interface*

```
ret = ox.login("Customer","justint","abc123")
dim phonearray(0,1)
phonearray(0,0)="number"
phonearray(0,1)="1029384756"
ret = ox.setphone("ADO",phonearray,1)
```

Stateless Interface

[Setphone XML Example](#)

Sql

Description

This method can run any SQL statement against the Platypus database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
SQLQuery	String	Required. The SQL statement to run against the database.
NoConn	Boolean	Optional. Defaults to False. Should be set to True if you do not want this method to create its own connection to the database and destroy it when it is finished.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns false if an error occurs. The error can be accessed using the [LastError](#) property of the web object. If no error occurs, an ADO recordset is returned.

Syntax

Object.Sql(SQLQuery, NoConn,Datatype)

Example

Stateful Interface

This example would delete all customers from the state of Mississippi.

```
Set myvar = ox.Sql("delete from customer where state='MS'")
if Not myvar then
    response.write(ox.lasterror)
end if
```

Stateless Interface

[SQL XML Example](#)

Transaction_Auth

Description

This method generates a web transaction and authorizes payment information.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Authinput	XML	Required. Includes customer id, billing amount, service type, service name, transaction type, credit card information, and invoice information.
CreatePayment	Boolean	Optional. If true, a payment is generated on the customer during the Authorization Method. If false or not set, a payment is not generated until the Commit Method.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

Object.Transaction_Auth(Authinput,CreatePayment,Datatype)

Example

Stateful Interface

```
cXML = "<authinput
type='xml'><custid>1270</custid><amount>20.00</amount><ccinfo><ccnumber>4111111111111111<
/ccnumber><ccexpire>012007</ccexpire><ccname>John
Smith</ccname><cctype>Visa</cctype><cvv2>123</cvv2><ccaddress><addr1>10001 Blackberry
St</addr1><addr2></addr2><city>Some
City</city><state>MS</state><zip>12345</zip></ccaddress></ccinfo><invoice><details><item><code
>code#1</code><desc>my
description</desc><price>5.00</price><profile>1</profile></item><item><code>code#2</code><desc
>my
description</desc><price>15.00</price><profile>1</profile></item></details></invoice></authinput>"
```

```
ret = ox.transaction_auth(cXML,false,"ADO")
```

Stateless Interface

[Transaction_Auth XML Example](#)

Transaction_Commit**Description**

This method finalizes a web transaction.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
TransactionID	Integer	Required. The id number of the transaction.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

```
Object.Transaction_Commit(TransactionID,cDatatype)
```

Example

Stateful Interface

```
ret = ox.transaction_commit(1756,"ADO")
```

Stateless Interface

[Transaction_Commit XML Example](#)

Transaction_Refund

Description

This method cancels a web transaction.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
TransactionID	Integer	Required. The id number of the transaction.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a string. The first character in the string will be a 1 for success or a 0 for error. This is followed by a comma, a space, and any error or success message.

Syntax

Object.Transaction_Refund(TransactionID,cDatatype)

Example

Stateful Interface

```
ret = ox.transaction_refund(1758,"ADO")
```

Stateless Interface

[Transaction_Refund XML Example](#)

Transaction_GetPrice**Description**

This method contains pricing information for the web transaction.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cService	String	Optional. The name of the service. If cService is not set, all services will be returned.
cSubType	String	Optional. The subtype of the service ie Blogware, domain. If cSubType is not set, all subtypes will be returned.
cTransactionType	String	Optional. The type of transaction performed on the service i.e. register, renew, transfer, lock. If cTransactionType is not set, all transaction types will be returned.
nPeriod	Integer	Optional. The period of the service. If nPeriod is not set, then all periods will be returned.
cDatatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a recordset containing the following values.

<u>Field</u>	<u>Type</u>	<u>Description</u>
service_type	String	The billing transaction item service type.
service_subtype	String	The billing transaction item service subtype.
transaction_type	String	The billing transaction item service transaction type.
period	Integer	The billing transaction item billing period.
item	String	The billing transaction item's item code value.
desc	String	The billing transaction item description.
price	Currency	The billing transaction item price.
profile	Integer	The billing transaction item tax.

Syntax

Object.Transaction_GetPrice(cService,cSubType,cTransactionType,nPeriod,cDatatype)

Example*Stateful Interface*

```
Set RS = ox.transaction_getprice("domain","com","register",1,"ADO")
```

Stateless Interface[Transaction_GetPrice XML Example](#)

Update

Description

This method can update any column on any table in the Platypus database with any value.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Table	String	Required. The name of the table to be updated.
Column	String	Required. The name of the column to be updated.
Value	String	Required. The value to set the specified column to. The value must be enclosed in single and double quotes if it is character data. If it is numeric data, it should only be surrounded by double quotes.
WhereClause	String	Required. The where clause to use when updating. The word "where" should be included as part of this parameter.
NoConn	Boolean	Optional. Defaults to False. Should be set to True if you do not want this method to create its own connection to the database and destroy it when it is finished.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns true if the update is successful or false if it fails. If the update fails, you can access the LastError property of the web object to find out why it failed.

Syntax

Object.Update(Table, Column, Value, WhereClause, NoConn,Datatype)

Example

Stateful Interface

This example would set the active flag on the customer table to "Y" for all customers that have the active flag set to "N".

```
Set myvar = ox.Update("customer", "active", "Y", "active=N")
if myvar then
    response.write("Success")
else
    response.write(ox.lasterror)
end if
```

Stateless Interface

[Update XML Example](#)

UpdateCCInfo

Description

This method allows you to update the credit card information for the specified customer.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
CCType	String	Required. The credit card type such as "VISA", "MASTERCARD", etc.
CCMonth	String	Required. The month part of the expiration date.
CCYear	String	Required. The year part of the expiration date.
CCNumber	String	Required. The credit card number.
CCName	String	Required. The customer name on the credit card.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns a 1 for success or a 0 for error. If a 0 is returned, the LastError property will contain the error message.

Syntax

Object.UpdateCCInfo(CCType, CCMonth, CCYear, CCNumber, CCName, Datatype)

Example

Stateful Interface

```
ret = ox.login("Customer","justint","abc123")  
ret = ox.updateccinfo("VISA","7","2007","4111111111111111","Justin Thornton","ADO")
```

Stateless Interface

[Updateccinfo XML Example](#)

UpdateCustomer

Description

This method updates the customer table setting the specified column to the specified value. This allows you to set custom fields from the web pages or change the value of columns that are not specified on the web if you don't like the default value.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
FieldName	String	Required. The name of the column on the customer table that you are updating.
FieldValue	String	Required. The value to set the specified column (FieldName) to. If the column holds string values (such as a datatype of varchar) or dates, you must include a set of double quotes and single quotes around the FieldValue.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns an message indicating success or failure.

Syntax

```
Object.UpdateCustomer("FieldName", "FieldValue",Datatype)
```

Example

Stateful Interface

Here is an example of setting the customer's Day of Month for Bills to the value 1. Since this column contains numeric data, only the double quotes are required around the the FieldValue.

```
ox.custid = "1001"
retvalue = ox.updatecustomer("custbillday", "1")
```

Here is an example of setting the customer's email address to the value joetest@domain.com. Since this column contains a string, single quotes are required within the double quotes around the FieldValue.

```
ox.custid = "1001"
retvalue = ox.updatecustomer("email", "'joetest@domain.com'")
```

Platypus 7 API Help

Stateless Interface

[Updatecustomer XML Example](#)

UpdateRate

Description

This method updates rate group assignment information including the billing dates, pending setup fee flag, and bill to guarantor flag.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
LastBilledDate	String	Required. The date this rate group assignment last had an invoice created for it.
NextBillDate	String	Required. The next date this rate group assignment should be billed.
BillToGuarantor	String	Required. Flag indicating whether or not this rate group assignment is billed to the customer's guarantor account. This flag should be set to "X" if the rate is to be billed to the guarantor or the empty string "" if the rate is to be billed to the customer.
PendingSetupFee	String	Required. Flag indicating whether or not the setup fee for the rate group should be charged the next time the rate group is billed. This flag should be set to "Y" if the setup fee is pending or "N" if the setup fee has already been charged on a previous invoice.
CustrateID	String	Required. The unique customer rate group assignment id. This value is stored in the crid column of the custrate table.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns "1" if the update is successful or "0" if an error occurs. If an error occurs, the error message can be accessed using the LastError property of the web object.

Syntax

```
Object.UpdateRate(LastBilledDate, NextBillDate, BillToGuarantor,
PendingSetupFee,CustrateId,Datatype)
```

Example

Stateful Interface

```
myvar = ox.UpdateRate("12/01/2000", "01/01/2001", "", "Y", "1234")
if myvar = "0" then
    response.write(ox.lasterror)
end if
```

Stateless Interface

[Updaterate XML Example](#)

UpdateService

Description

This method updates a service on a customer rate group assignment.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Svc_ID	String	Required. The unique id of the service type being updated.
DataID	String	Required. The unique id of the instance of the service.
Column_Array	Array	Required. An array containing the information about the service being added. The column array is described in detail below.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Column_Array

Only the columns whose values are being changed are required to be included in the array, but including the ones that don't change won't cause any problems. If the current value and new values for the column are the same, the column is not updated.

<u>Array Position</u>	<u>Type</u>	<u>Description</u>
0	String	The column name from the service table.
1	String	The new value for the column.
2	String	The current value of the column.
3	String	The data control used by the column. This is the value of the ctrl column from the user_field table entry for this column. Possible values include "txt_text", "dropdown", "dropword", etc.
4	String	The display name of the column. This is used in error messages to tell the customer which field the error occurred in.

Return Values

This method returns a one for success or zero for failure. When an error occurs, the [LastError](#) property can be used to check the error message.

Syntax

```
Object.UpdateService(Svc_ID, DataID, Column_Array,Datatype)
```

Example

Stateful Interface

This is an example of updating the active status of an email service.

```
dim column_array()  
redim column_array(1,5)  
column_array(0,0) = "d_active"  
column_array(0,1) = "Y"  
column_array(0,2) = "Y"  
column_array(0,3) = "txt_text"  
column_array(0,4) = "Active"  
ret = ox.updateservice("1", "12", column_array)
```

Stateless Interface

[Updateservice XML Example](#)

VerifyInfo

Description

This method checks to make sure all the required information for a customer signup has been filled out and does some error checking.

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Name2	String	Required. The customers full name.
Phone	String	Required. The customers phone number.
Address	String	Required. The street address of the customers billing address.
City	String	Required. The city from the customers billing address.
State	String	Required. The state from the customers billing address.
Zip	String	Required. The postal code from the customers billing address.
Country	String	Can be Optional or Required depending on web option settings. The country part of the address.
Username	String	Required. The username the customer wishes to use.
Password	String	Required. The password the customer wishes to use.
Password2	String	Required. The password entered a second time for verification purposes.
BillingMeth	String	Required. The billing method the customer selected. This value should be set to "ccard" for credit card signups or "check" for check signups.
SelectRate	String	Required. The rate group id(s) that the customer selected. If multiple rate groups are to be assigned to the customer, this property should be a comma delimited list of the rate group ids like "2, 19, 4".
SelectPop	String	Required. The pop location id value selected by the customer. This is used by the Microsoft IEAK integration to determine which IEAK template file to use. This value can be hardcoded to "1" if you are not using IEAK.
If "ccard" BillingMethod		
CCName	String	Required. The name of the credit card holder as it appears on the credit card.
CCAddr	String	Required. The credit card address.
CCCity	String	Required. The city from the credit card address.
CCState	String	Required. The state from the credit card address.
CCZip	String	Required. The postal code from the credit card address.
CCNumber	String	Required. The credit card number.
CCExpireM	String	Required. The month part of the credit card expiration date.
CCExpireY	String	Required. The year part of the credit card expiration date.
CheckServices	String	Optional. This property is a flag that determines whether or not the

email address and username entered by the customer should be checked against the email services table for duplicate. This properties value should be set to "Y" to check the email services for duplicates or "N" not to check the email services for duplicates.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
DisplayRates	String	Optional. Flag indicating whether a rate group selection is required. If the value is "R", this method will check to make sure the SelectRate property is set to a valid rate group id.
DisplayBlockRates	String	Optional. Flag indicating whether a block time rate selection is required. If the value is "R", this method will check to make sure the SelectBlock parameter is set to a valid block time rate id.
SalesRequired	String	Optional. Flag indicating whether a salesperson is required to be selected. If the value is "Y" and the value of the ShowSales parameter is "Y", this method will check to make sure the SelectSales parameter is set to a valid salesperson id.
ShowSales	String	Optional. Flag indicating whether the customer was prompted to select a salesperson. If the value is "Y" and the value of the SalesRequired parameter is "Y", this method will check to make sure the SelectSales parameter is set to a valid salesperson id.
SelectSales	String	Optional. The id number of the salesperson selected.
SelectRef	String	Optional. The id number of the customer who referred the customer that is signing up.
SelectBlock	String	Optional. The id number of the block time rate that was selected.
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns the value of the VarGood property. It sets the VarGood property to true if everything is checked out successfully or sets it to false if any errors occurred. If errors occurred, they are stored in the LastError property.

Syntax

Object.VerifyInfo(DisplayRates, DisplayBlockRates, SalesRequired, ShowSales, SelectSales, SelectRef, SelectBlock,Datatype)

Example

Stateful Interface

```

ox.name2="Joe Test"
ox.phone="1234567890"
ox.address="110 That Street"
ox.city="Starkville"
ox.state="MS"
ox.zip="39759"
ox.username="joetest"
ox.password="apassword"

```



```
ox.password2="apassword"  
ox.billingmeth="check"  
ox.selectrate="7"  
ox.selectpop="1"  
ox.selectshell="1"  
ox.verifyinfo()
```

Stateless Interface

[Verifyinfo XML Example](#)

Welcome_Email

Description

This method sends a welcome email to the specified customer if the Auto Welcome Message option in Platypus is set to "Y".

Properties

The following properties can be set on the object before this method is called.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Custid	String	Required. The id number of the customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
Datatype	String	Optional. Type of data returned from the method. Can be "XML" to return XML data or "ADO" to return ADO recordsets, strings, numeric values, etc. Defaults to "ADO"

Return Values

This method returns nothing. If errors occur, the [LastError property](#) of the web object will be populated with an error message. If no errors occur, the [LastError](#) property of the web object will be equal to the empty string ("").

Syntax

Object.WelcomeEmail(Datatype)

Example

Stateful Interface

```
ox.custid = "1001"  
ox.email1 = "platypus@boardtown.com"  
retvalue = ox.welcomeemail()  
if ox.lasterror <> "" then  
    response.write(ox.lasterror)  
end if
```

Stateless Interface

[Welcomeemail XML Example](#)

Wombat**attachment_Delete****Description**

Deletes an attachment from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cID	String	Required. The id of the attachment to be deleted.
cType	String	Required. The type of the item that the contains the attachment. Currently "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attachment to be deleted, i.e. Ticket ID.

Return Values

Returns true if the attachment was successfully deleted. Returns false if the attachment was not successfully deleted.

Syntax

object.attachment_Delete(cID, CType, nTypeId)

Example

[attachment_Delete XML Example](#)

attachment_Load

Description

Loads an attachment from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cID	String	Required. The id of the attachment to be loaded.
cType	String	Required. The type of the item that contains the attachment. Currently "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attachment to be loaded, i.e. Ticket ID.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
at_id	Attachment id. This is the same as the c_id parameter.
at_idnum	Attachment item id. This is the same as the nTypeId parameter.
at_idtype	Attachment item. This is the same as the cType parameter.
at_description	Attachment description.
at_date	Date the item was added tot he database.
at_filename	Original filename.
at_file	File data. This is usually encoded and then zipped.
at_compressed	Flag showing if the file is zipped.
at_encodingtype	Encoded type used. Typically the type is mime64.

Syntax

object.attachment_Load(cID, CType, nTypeId)

Examples

[attachment_Load XML Example](#)

attachment_Save**Description**

Adds an attachment to the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cFile	String	Required. The filename of the attachment.
cDescription	String	Optional. The description of the attachment.
cType	String	Required. The type of the item on which the attachment will be added. Currently, "ticket" and "email" are the allowed values.
nTypeId	Long	Required. The id of the item that will contain the added attachment, i.e. Ticket ID or Email ID.
bReopen	Boolean	Optional. A flag that specifies whether or not the item should be reopened. Defaults to false if left blank.
cFileData	String	Required. The file that is added to the database. The string must be mime64 encoded.

Return Values

Returns true if the attachment was successfully saved. Returns false if the attachment was not successfully saved.

Syntax

```
object.attachment_Save(cFile,cDescription,cType,nId,bReopen,cFileData)
```

Example

[attachment_Save XML Example](#)

call_Delete

Description

Deletes a call from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cId	String	Required. The id of the call to be deleted.
cType	String	Required. The type of the item that contains the call to be deleted. Currently, "ticket" is the only allowed value.
NTypeId	Long	Required. The id of the item that contains the call to be deleted, i.e. Ticket ID.

Return Values

Returns true if the call was successfully deleted. Returns false if the call was not successfully deleted.

Syntax

object.call_Delete(cId,cType,NTypeId)

Example

[call_Delete XML Example](#)

call_New**Description**

Gets new call data from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cType	String	Required. The type of the item that contains the call to be added. Currently "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that will contain the received call, i.e. Ticket ID

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
Contact	Contact name.
Number	Contact phone number.

Syntax

object.call_New(CType, nTypeId)

Example

[call_New XML Example](#)

call_Save

Description

Saves a new call to the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cType	String	Required. The type of the item on which the call will be added. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that will contain the added call, i.e. Ticket ID.
cBody	String	Required. The call message.
nTime	Long	Required. Length of call in seconds.
cCallType	String	Required. Type of call, i.e incoming or outgoing. Allowed values are "I" and "O" respectfully.
cContractNumber	String	Required. The phone number contacted.
cContractName	String	Required. The name of the person contacted.
bReopen	Boolean	Optional. A flag that specifies whether or not the item should be reopened. Defaults to false if left blank.

Return Values

Returns true if the call was successfully saved. Returns false if the call was not successfully saved.

Syntax

```
object.call_Save(cType,nTypeId,cBody,nTime,cCallType,cContractNumber,cContractName,bReopen)
```

Example

[call_Save XML Example](#)

check_Security

Description

Retrieves a security setting.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cSecurityTag	String	Required. The security tag to check.

Return Values

Returns true if the person logged in has access to the security tag. Returns false if person does not have access to the security tag.

Syntax

object.check_Security(cSecurityTag)

Example

[check_Security XML Example](#)

customer_Search

Description

Searches the database for a customer.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cSearchstring	String	Required. Customer string to search.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
id	Customer ID.
name	Customer Name.
contact	Flag showing if the record is a customer or a contact record.
phone	Customer Phone
active	Customer Status.
attn	Attention Field.

Syntax

object.customer_Search(cSearchstring)

Example

[customer_Search XML Example](#)

email_Cancel**Description**

Cancels an email that has been started.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The original action that was taken when loading the email. Possible values include "REPLY", "RESEND", "FORWARD", and "NEW". All other values are ignored.
nEmail	Long	Required. The id of the email being canceled.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the email to be canceled., i.e. Ticket ID.

Return Values

Returns true if the email was successfully canceled. Returns false if the email was not successfully canceled.

Syntax

```
object.email_Cancel(cAction, nEmail,cType,nTypeId)
```

Example

[email_Cancel XML Example](#)

email_Delete

Description

Deletes an email from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cID	String	Required. The id of the email to be deleted.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the email to be deleted., i.e. Ticket ID.

Return Values

Returns true if the email was successfully deleted. Returns false if the email was not successfully deleted.

Syntax

object.email_Delete(cID, cType,nTypeId)

Example

[email_Delete XML Example](#)

email_Get_Attachments**Description**

Retrieves an array of attachments for an email.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The original action that was taken when loading the email. Possible values include "REPLY", "RESEND", "FORWARD", "NEW", "EDIT", "VIEW", and "CONTINUE".
nEmail	Long	Required. Email id for which attachments are retrieved.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attached email., i.e. Ticket ID.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
at_id	Attachment ID.
exp	Filename.
at_size	Size of the attachment in bytes.

Syntax

```
object.email_Get_Attachments(cAction, nEmail,cType,nTypeId)
```

Example

[email_Get_Attachments XML Example](#)

email_Load**Description**

Retrieves an email based on the email id that is passed to the method.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The action that will be taken when loading the email. Possible values include "EDIT", "VIEW", and "CONTINUE".
nEmail	Long	Required. Email id will be loaded.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attached email, i.e. Ticket ID.

Return Values

Returns a message object with the following properties.

<u>Field</u>	<u>Description</u>
connhandle	SQL connection handle.
em_attachments	Number of email attachments.
em_bcc	Bcc addresss.
em_body	Email body.
em_cc	CC address.
em_daterceived	Date the email was created in the database.
em_datesent	Date the email was sent.
em_from	From address.
em_from_default	?From address.
em_from_name	From title.
em_headers	??
em_id	Email id in the database.
em_idnum	ID of the item that contains the email.
em_idtype	The type of item that contains the email, i.e. Ticket.
em_rating	??
em_sent	Flag showing if the email has been sent.
em_subject	Subject field.
em_system	Flag showing if the email is a system email.
em_thread	??
em_timestamp	Timestamp.
em_to	To field.
em_type	Email type. Valid values include "I" for incoming and "O" for outgoing.
lasterror	The last error that occurred on the object.
mode	State of the email.

old_attachments	Backup value for the number of email attachments.
old_bcc	Backup value for the Bcc address.
old_body	Backup value for the email body.
old_cc	Backup value for the CC field.
old_datereceived	Backup value for the date the email was created in the database.
old_datesent	Backup value for the date the email was sent.
old_from	Backup value for the from address.
old_from_name	Backup value for the from title.
old_headers	Backup value for the ??.
old_id	Backup value for the email id in the database.
old_idnum	Backup value for the id of the item that contains the email.
old_idtype	Backup value for the type of item that contains the email, i.e. Ticket.
old_rating	Backup value for the ??.
old_sent	Backup value flag showing if the email was sent.
old_subject	Backup value for the subject field
old_system	Backup value flag showing if the email is a system email.
old_thread	Backup value for the ??.
old_to	Backup value for the to field.
old_type	Backup value for the email type. Valid values include "I" for incoming and "O" for outgoing.
regkey	???

Syntax

object.email_Load(cAction, nEmail,cType,nTypeId)

Example

[email_Load XML Example](#)

email_New**Description**

Creates a new email based on the action and email id passed into the method. The created email is returned.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The action that will be taken when creating the email. Possible values include "REPLY", "RESEND" "FORWARD", and "NEW".
nEmail	Long	Required. An existing email id used to generate the new email based on the action that is preformed (Reply, Resend, Forward, New). ID is 0 if the new action is preformed.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attached email., i.e. Ticket ID.

Return Values

Returns a message object with the following properties.

<u>Field</u>	<u>Description</u>
connhandle	SQL connection handle.
em_attachments	Number of email attachments.
em_bcc	Bcc addresss.
em_body	Email body.
em_cc	CC address.
em_daterceived	Date the email was created in the database.
em_datesent	Date the email was sent.
em_from	From address.
em_from_default	?From address.
em_from_name	From title.
em_headers	??
em_id	Email id in the database.
em_idnum	ID of the item that contains the email.
em_idtype	The type of item that contains the email, i.e. Ticket.
em_rating	??
em_sent	Flag showing if the email has been sent.
em_subject	Subject field.
em_system	Flag showing if the email is a system email.
em_thread	??
em_timestamp	Timestamp.
em_to	To field.
em_type	Email type. Valid values include "I" for incoming and "O"

	for outgoing.
lasterror	The last error that occurred on the object.
mode	State of the email.
old_attachments	Backup value for the number of email attachments.
old_bcc	Backup value for the Bcc address.
old_body	Backup value for the email body.
old_cc	Backup value for the CC field.
old_datereceived	Backup value for the date the email was created in the database.
old_datesent	Backup value for the date the email was sent.
old_from	Backup value for the from address.
old_from_name	Backup value for the from title.
old_headers	Backup value for the ??.
old_id	Backup value for the email id in the database.
old_idnum	Backup value for the id of the item that contains the email.
old_idtype	Backup value for the type of item that contains the email, i.e. Ticket.
old_rating	Backup value for the ??.
old_sent	Backup value flag showing if the email was sent.
old_subject	Backup value for the subject field.
old_system	Backup value flag showing if the email is a system email.
old_thread	Backup value for the ??.
old_to	Backup value for the to field.
old_type	Backup value for the email type. Valid values include "I" for incoming and "O" for outgoing.
regkey	???

Syntax

object.email_New(cAction, nEmail,cType,nTypeId)

Example

[email_New XML Example](#)

email_Save

Description

Saves an email to the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The original action that was taken when loading the email. Possible values include "REPLY", "RESEND", "FORWARD", "NEW", "EDIT", "VIEW", and "CONTINUE".
nEmail	Long	Required. Email ID to be saved.
cFrom	String	Required. From address of the email to be saved.
cTo	String	Required. To address of the email to be saved.
cCc	String	Optional. CC address of the email to be saved.
cBcc	String	Optional. BCC address of the email to be saved.
cSubject	String	Required. Subject of the email to be saved.
cBody	String	Required. The message of the email to be saved.
nAttachments	Long	Optional. The number of attachments on the email to be saved.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attached email., i.e. Ticket ID.

Return Values

Returns true if the email was successfully saved. Returns false if the email was not successfully saved.

Syntax

object.email_Save (cAction,
nEmail,cFrom,cTo,cCc,cBcc,cSubject,cBody,nAttachments,cType,nTypeId)

Example

[email_Save XML Example](#)

email_Send**Description**

Sends an email.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cAction	String	Required. The original action that was taken when loading the email. Possible values include "REPLY", "RESEND", "FORWARD", "NEW", "EDIT", "VIEW", and "CONTINUE".
nEmail	Long	Required. Email ID to be sent.
cFrom	String	Required. From address of the email to be sent.
cTo	String	Required. To address of the email to be sent.
cCc	String	Optional. CC address of the email to be sent.
cBcc	String	Optional. BCC address of the email to be sent.
cSubject	String	Required. Subject of the email to be sent.
cBody	String	Required. The message of the email to be sent.
nAttachments	Long	Optional. The number of attachments on the email to be sent.
cType	String	Required. The type of item that contains the attached email. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the attached email., i.e. Ticket ID.

Return Values

Returns true if the email was successfully sent. Returns false if the email was not successfully sent.

Syntax

```
object.email_Send (cAction,
nEmail,cFrom,cTo,cCc,cBcc,cSubject,cBody,nAttachments,cType,nTypeId)
```

Example

[email_Send XML Example](#)

get_Option

Description

Returns the value for an option.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cOptionName	String	Required. The option being looked up.

Return Values

Returns a string value for the requested option.

Syntax

```
object.get_Option(cOptionName)
```

Example

[get_Option XML Example](#)

KB_Get_Article**Description**

Retrieves article data.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nId	Long	Required. The article id to be retrieved.

Return Values

Returns an XML string.

Syntax

object.KB_Get_Article (nId)

Example

[KB_Get_Article XML Example](#)

KB_Get_Attachment

Description

Retrieves a file from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cId	String	Required. The attachment id to be retrieved.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
at_id	The attachment id.
at_idnum	The attachment item id.
at_idtype	The attachment item.
at_description	The description of the attachment.
at_date	The date the item was added to the database.
at_filename	The original filename.
at_file	The file data. The data is usually encoded and zipped.
at_compressed	A flag showing if the file is zipped.
at_encodingtype	The encoding type. Typically mime64 encoding is used.

Syntax

object.KB_Get_Attachment (cId)

Example

[KB_Get_Attachment XML Example](#)

KB_Get_Issue**Description**

Retrieves issue data from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nId	Long	Required. The issue id to be retrieved.

Return Values

Returns an XML string.

Syntax

object.KB_Get_Issue(nId)

Example

[KB_Get_Issue XML Example](#)

KB_Get_Titles

Description

Retrieves a list of article and issue titles.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
aList	Array	Required. An array of article and issue ids and there associated types.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
type	The type of item.
id	The item id.
title	The title of the item.

Syntax

object.KB_Get_Titles(aList)

Example

[KB_Get_Titles XML Example](#)

KB_Get_Tree

Description

Retrieves the Knowledgebase tree.

Return Values

Returns an XML string.

Syntax

object.KB_Get_Tree ()

Example

[KB_Get_Tree XML Example](#)

KB_Search

Description

Searches the database for articles and issues.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cQuery	String	Required. The search value.
bKeyword	Boolean	Optional. A flag that determines if keywords are searched. If left blank, defaults to false.
bTitle	Boolean	Optional. A flag that determines if titles are searched. If left blank, defaults to false.
bBody	Boolean	Optional. A flag that determines if the body of the article or issue is searched. If left blank, defaults to false.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
id	The id of the item.
title	The title of the item.
type	The type of item.

Syntax

object.KB_Search (cQuery,bKeyword,bTitle,bBody)

Example

[KB_Search XML Example](#)

Login**Description**

Logs a staff member or customer into Wombat.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cUsername	String	Required. The username of the person being logged in.
cPassword	String	Required. The password that corresponds to the username of the person being logged in.

Return Values

Returns the staff or customer id of the person logged into Wombat. A -1 represents a customer login.

Syntax

object.login (cUsername,cPassword)

Example

[Login XML Example](#)

note_Delete

Description

Deletes a note from the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cId	String	Required. The id of the note to be deleted.
cType	String	Required. The type of the item that contains the note to be deleted. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the note to be deleted, i.e. Ticket ID.

Return Values

Returns true if the note was successfully deleted. Returns false if the note was not successfully deleted.

Syntax

object.note_Delete (cId,Ctype,nTypeId)

Example

[note_Delete XML Example](#)

note_Load**Description**

Loads a note from a ticket based on the index of the note.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nIndex	Long	Required. The index of the note which is the order the note is displayed on the note tab of the ticket . The index begins with 1.
cType	String	Required. The type of the item that contains the note to be loaded. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the note to be loaded, i.e. Ticket ID.

Return Values

Returns a message object with the following properties.

<u>Field</u>	<u>Description</u>
connhandle	SQL connection handle.
existing	???
lasterror	The last error that occurred on the note.
mode	State of the note.
modified	Flag showing if the note has been modified.
note_body	The message of the note.
note_body_display	An overview of the note.
note_date_created	The date the note was created.
note_id	The note id.
note_idnum	The ID of the item that contains the note.
note_idtype	The type of item that contains the note, i.e. Ticket.
note_staff_id	The id of the staff member who created the note.
note_staff_name	The name of the staff member who created the note.
note_visible	A flag showing if the note is externally visible.
old_body	Old value of the note message.
old_date_created	Old value for the date the note was created.
old_id	Old value for the note id.
old_idnum	Old value for the ID of the item that contains the note.
old_idtype	Old value for the type of item that contains the note, i.e. Ticket
old_staff_id	Old value for the id of the staff member who created the note.
old_visible	Old value for the flag showing if a note is externally visible.
regkey	???

Syntax

object.note_Load (nIndex,cType,nTypeId)

Example

[note_Load XML Example](#)

note_Save**Description**

Saves a note to the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cBody	String	Required. The body of the note.
cVisible	String	Required. A flag that determines whether a note is externally visible. Allowed values are "Y" and "N".
bReopen	Boolean	Optional. A flag that specifies whether or not the item should be reopened. Defaults to false if left blank.
cType	String	Required. The type of item that contains the attached note. Currently, "ticket" is the only allowed value.
nTypeId	Long	Required. The id of the item that contains the note to be saved, i.e. Ticket ID.

Return Values

Returns true if the note was successfully saved. Returns false if the note was not successfully saved.

Syntax

object.note_Save (cBody,cVisible,bReopen,cType,nTypeId)

Example

[note_Save XML Example](#)

sql_Execute

Description

Executes the SQL statement passed to it.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cSQL	String	Required. A SQL statement.

Return Values

Returns a record set with the fields denoted by the SQL statement.

Syntax

object.sql_Execute (cSQL)

Example

[sql_Execute XML Example](#)

ticket_Change_Status**Description**

Changes the status of a ticket to a new status and executes any additional code related to the status change.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nProgression	Long	Required. The new status id.
nTicket	Long	Required. The id of the ticket whose status is to be changed.

Return Values

Returns true if the ticket status was successfully changed. Returns false if the ticket status was not successfully changed.

Syntax

object.ticket_Change_Status (nProgression,nTicket)

Example

[ticket_Change_Status XML Example](#)

ticket_Delete

Description

Changes the status of a ticket to a new status and executes any additional code related to the status change.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The id of the ticket whose status is to be changed.
bDeleteEmails	Boolean	Optional. Flag determining if all emails on the ticket are to be deleted. If false, emails will appear in Handle Emails. Defaults to false if left blank.

Return Values

Returns true if the ticket was successfully deleted. Returns false if the ticket was not successfully deleted.

Syntax

object.ticket_Delete (nProgression,nTicket)

Example

[ticket_Delete XML Example](#)

ticket_Get_Access_Settings**Description**

Retrieves a list of security tags and related values based on the loaded ticket and the person logged in and that person's security permissions. This is similar to the [ticket_Get_Security_Settings](#) API call. This API call should be called after [ticket_Get_Security_Settings](#) overriding any values returned there.

Parameters

Parameter	Type	Description
nTicket	Long	Optional. The ticket id.

Return Values

Returns a recordset with the following fields.

Field	Description
tag	The name of the security tag.
value	A flag showing if a user has access to the related tag. 1=True;0=false.

Example

[ticket_get_Access_Settings XML Example](#)

ticket_Get_Attachments

Description

Retrieves a list of attachments for a specified ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The id of the ticket that is to be checked for attachments.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
at_id	Attachment ID.
at_filename	Filename.
at_size	Size of the attachment in bytes.
at_date	Date the attachment was added to the database.
at_description	Description of the file.

Syntax

object.ticket_Get_Attachments (nTicket)

Example

[ticket_Get_Attachments XML Example](#)

ticket_Get_Calls**Description**

Retrieves a list of calls for a specified ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The id of the ticket that is to be checked for calls.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
call_id	Call ID.
call_date	Date the call was added to the database.
call_type	A flag showing if a call was incoming or outgoing. Valid values include "I" for incoming and "O" for outgoing.
call_number	The number for the contact.
call_contact_name	The name of the person called.
call_seconds	The call length in seconds.
call_staff_name	The name of the staff member making the call.
call_note	The message body of the note.

Syntax

object.ticket_Get_Calls (nTicket)

Example

[ticket_Get_Calls XML Example](#)

ticket_Get_Category_List

Description

Retrieves an array of categories and there associated values.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
bCreateableOnly	Boolean	Optional. A flag that specifies the retrieval of categories that are only defined as createable.
bCustomerVisible	Boolean	Optional. A flag that specifies the retrieval of categories that are viewable by the customer.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Category_List (bCreateableOnly, bCustomerVisible)

Example

[ticket_Get_Category_List XML Example](#)

ticket_Get_Customer_Info**Description**

Retrieves an array of customer data.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id used for retrieving customer data.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Customer_Info (nTicket)

Example

[ticket_Get_Customer_Info XML Example](#)

ticket_Get_Emails

Description

Retrieves a recordset of emails on a ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id used for retrieving emails.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
em_id	Email ID.
em_date	The date the email was created.
em_type	The email type. Valid values include "I" for incoming and "O" for outgoing.
em_sent	A flag showing if the email message was sent. Valid values include "Y" or "N".
em_subject	The email subject line.

Syntax

object.ticket_Get_Emails (nTicket)

Example

[ticket_Get_Emails XML Example](#)

ticket_Get_History**Description**

Retrieves a recordset of history data that is associated with a ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id used for retrieving history.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
hist_id	History ID.
hist_date	The date the history was created.
hist_staff_id	The ID of the staff member that created the history entry.
hist_staff_name	The name of the staff member that created the history entry.
hist_action	The description of the history entry.

Syntax

object.ticket_Get_History (nTicket)

Example

[ticket_Get_History XML Example](#)

ticket_Get_Notes**Description**

Retrieves a recordset of notes on a ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id used for retrieving notes.

Return Values

Returns a message object with the following properties.

<u>Field</u>	<u>Description</u>
connhandle	SQL connection handle.
existing	???
lasterror	The last error that occurred on the note.
mode	State of the note.
modified	Flag showing if the note has been modified.
note_body	The message of the note.
note_body_display	An overview of the note.
note_date_created	The date the note was created.
note_id	The note id.
note_idnum	The ID of the item that contains the note.
note_idtype	The type of item that contains the note, i.e. Ticket.
note_staff_id	The id of the staff member who created the note.
note_staff_name	The name of the staff member who created the note.
note_visible	A flag showing if the note is externally visible.
old_body	Old value of the note message.
old_date_created	Old value for the date the note was created.
old_id	Old value for the note id.
old_idnum	Old value for the ID of the item that contains the note.
old_idtype	Old value for the type of item that contains the note, i.e. Ticket
old_staff_id	Old value for the id of the staff member who created the note.
old_visible	Old value for the flag showing if a note is externally visible.
regkey	???

Syntax

object.ticket_Get_Notes (nTicket)

Example

[ticket_Get_Notes XML Example](#)

ticket_Get_Priority_List

Description

Retrieves an array of priorities and their associated values.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
bCreatableOnly	Boolean	Optional. A flag that specifies the retrieval of priorities that are only defined as creatable.
bCustomerVisible	Boolean	Optional. A flag that specifies the retrieval of priorities that are viewable by the customer.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Priority_List (bCreatableOnly,bCustomerVisible)

Example

[ticket_Get_Priority_List XML Example](#)

ticket_get_Security_Settings**Description**

Retrieves a list of security tags and related values based on the person logged in and that person's security permissions. This is similar to the [ticket_Get_Access_Settings](#) API call. This API call should be called before **ticket_Get_Access_Settings**. Any values returned by **ticket_Get_Access_Settings** should override values returned by this API call.

Return Values

Returns a recordset with the following fields.

Field	Description
tag	The name of the security tag.
value	A flag showing if a user has access to the related tag. 1=True;0=false.

Example

[ticket_get_Security_Settings XML Example](#)

ticket_Get_Status_List

Description

Retrieves an array of statuses and their ids.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
bCreatableOnly	Boolean	Optional. A flag that specifies the retrieval of statuses that are only defined as creatable.
bCustomerVisible	Boolean	Optional. A flag that specifies the retrieval of statuses that are viewable by the customer.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Status_List (bCreatableOnly,bCustomerVisible)

Example

[ticket_Get_Status_List XML Example](#)

ticket_Get_Status_Progression_List**Description**

Retrieves an array containing a progression of available statuses for the current status.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id used for retrieving the available statuses.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Status_Progression_List (nTicket)

Example

[ticket_Get_Status_Progression_List XML Example](#)

ticket_get_Ticket_Info

Description

Retrieves ticket information based on the type of data to be returned i.e. ticket manager, ticket queue, ticket search, project manager, and ticket picker.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The id of the ticket that is being retrieved.
nType	Long	Required. The type of data to be returned. Valid values include: 1=Ticket Manger, 2=Ticket Queue, 3=Ticket Search, 4=Project Manager, 5=Ticket Picker

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Example

[ticket_get_Ticket_Info XML Example](#)

ticket_Get_Type_List**Description**

Retrieves an array of types and their ids.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
bCreatableOnly	Boolean	Optional. A flag that specifies the retrieval of types that are only defined as creatable.
bCustomerVisible	Boolean	Optional. A flag that specifies the retrieval of types that are viewable by the customer.

Return Values

Returns an array of associated pairs. The pairs are contained in the following fields:

<u>Field</u>	<u>Description</u>
displayName	The name of the field label.
displayValue	The value of the field.

Syntax

object.ticket_Get_Type_List (bCreatableOnly,bCustomerVisible)

Example

[ticket_Get_Type_List XML Example](#)

ticket_Load

Description

Loads and retrieves the ticket object.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. Ticket id to be retrieved.
bLoadExtra	Boolean	Optional. A flag that determines if all the ticket information is to be loaded (i.e. notes). If left blank, defaults to true.

Return Values

Returns a ticket object with the following properties.

<u>Field</u>	<u>Description</u>
security_level	The security level on the ticket.
tkc_category	The category id of the ticket.
tkc_category_access	???
tkc_category_name	The category name of the ticket.
tkc_company_access	???
tkc_contact	A flag showing if the tkc_customer_id is a contact.
tkc_count_attachments	The number of attachments on a ticket.
tkc_count_calls	The number of calls on a ticket.
tkc_count_messages	The number of emails on the ticket.
tkc_created_by	The user id that created the ticket.
tkc_created_by_name	The name of the user that created the ticket.
tkc_customer_id	The id of the customer or contact associated with the ticket.
tkc_customer_name	The name of the customer or contact associated with the ticket.
tkc_date_entered	The date the ticket was created.
tkc_email	The email address on the ticket.
tkc_hidden	The flag stating if the ticket is externally visible.
tkc_id	The ticket id.
tkc_knowledgebase_id	The id of the related knowledge base item.
tkc_knowledgebase_type	The type of knowledge base item that is related to the ticket.
tkc_last_assigned	The date the ticket was assigned to the current staff member.
tkc_last_category_change	The date the category was set.
tkc_last_escalated	The date that the ticket was last escalated.
tkc_last_status_change	The date the ticket status was set.
tkc_last_type_change	The date the ticket type was set.

tkt_last_updated	The date the ticket was last updated.
tkt_last_updated_by	The id of the user to last update the ticket.
tkt_last_updated_by_name	The name of the user to last update the ticket.
tkt_modified	A flag showing if the ticket has been modified
tkt_priority	The priority ID.
tkt_priority_name	The priority name.
tkt_problem	The ticket problem.
tkt_project_access	???
tkt_project_admin	???
tkt_project_id	The project id of the ticket.
tkt_project_item_id	???
tkt_project_leader_assign	???
tkt_project_leader_notify	???
tkt_sent_survey	A flag showing if a survey has been sent for the ticket.
tkt_solution	The ticket solution.
tkt_staff_assigned	The id of the currently assigned staff member.
tkt_staff_assigned_name	The name of the currently assigned staff member.
tkt_status	The status id.
tkt_status_name	The status name.
tkt_status_progression	???
tkt_time_accessed	??
tkt_timestamp	The ticket timestamp.
tkt_total_time	The total time in seconds that the ticket has been worked on.
tkt_type	The type id.
tkt_type_name	The type name.
version	The ticket version.

Syntax

object.ticket_Load (nTicket,bLoadExtra)

Example

[ticket_Load XML Example](#)

ticket_Reassign

Description

Reassigns a ticket to a new staff member.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nStaffId	Long	Required. Staff id receiving the reassigned ticket.
nTicket	Long	Required. Ticket id being reassigned.

Return Values

Returns true if the ticket was successfully reassigned. Returns false if the ticket was not successfully reassigned.

Syntax

object.ticket_Reassign (nStaffId,nTicket)

Example

[ticket_Reassign XML Example](#)

ticket_Save**Description**

Saves a ticket to the database.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
bForceSave	Boolean	Optional. A flag that determines if the ticket will be forced to be saved. If left blank, defaults to false.
nTicket	Long	Optional. Ticket id to be saved. If blank or 0, the ticket is a new ticket.
nCategory	Long	Optional. Category id of the ticket.
cContact	Character	Optional. A flag that determines if a customer is a contact. Allowed values are "Y" for contact and "N" for not a contact.
nCustomer_Id	Long	Optional. Customer or Contact id that is on the ticket.
cEmail	String	Optional. The email address of the customer or contact.
cHidden	Character	Optional. A flag determining if a ticket is externally visible. Allowed values are "Y" for visible and "N" for not visible.
nKnowledgebase_id	Long	Optional. ID of the knowledgebase item related to the ticket.
cKnowledgebase_type	Character	Optional. A flag determining if the knowledgebase id is an article or an issue. Allowed values are "A" or "I".
nPriority	Long	Optional. The id of the priority of the ticket.
cProblem	String	Optional. The problem located on the ticket.
nProject_id	Long	Optional. The project id of the ticket.
cSolution	String	Optional. The ticket solution.
nStaff_assigned	Long	Optional. Staff id of the staff member assigned to the ticket.
nStatus	Long	Optional. The current status id of the ticket.
nStatus_progression	Long	Optional. The status id next in the progression list that the ticket will be moved to.
nType	Long	Optional. The type id of the ticket.
bReturnObject	Boolean	Optional. A flag that passes the ticket object back instead of true or false. If left blank, defaults to false.

Return Values

Returns true if the ticket was successfully saved. Returns false if the ticket was not successfully saved.

Syntax

object.ticket_Save (bForceSave,nTicket,nCategory,cContact,nCustomer_id, cEmail,cHidden,nKnowledgebase_id,cKnowledgebase_type,

nPriority,cProblem,nProject_id,cSolution,nStaff_assigned,
nStatus,nStatus_progression,nType,bReturnObject)

Example

[ticket_Save XML Example](#)

ticket_Steal**Description**

Assigns a ticket from one staff member to the staff member currently logged into Wombat..

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
nTicket	Long	Required. The ticket id being stolen.

Return Values

Returns true if the ticket was successfully stolen. Returns false if the ticket was not successfully stolen.

Syntax

object.ticket_Steal (nTicket)

Example

[ticket_Steal XML Example](#)

ticketTree_Get_Filters

Description

Returns an array of filters.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
cft_name	The category filter name.
cft_id	The category filter id.

Syntax

object.ticketTree_Get_Filters ()

Example

[ticketTree_Get_Filters XML Example](#)

ticketTree_Get_Group_List**Description**

Retrieves a list of tickets grouped by month and year.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cViewType	String	Required. The view type that is active. Allowed values include "status", "priority", "type", and "category".
nID	Long	Required. Staff ID associated with the ticket list.
nViewID	Long	Optional.. The view type id. View types include status, category, priority, and type.
cStatusViewable	String	Optional. A comma separated list of statuses.
cCategoryViewable	String	Optional. A comma separated list of categories.
cPriorityViewable	String	Optional. A comma separated list of priorities.
cTypeViewable	String	Optional. A comma separated list of types.
nCatFilter	Long	Optional. The category filter id.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
tkr_date_month	The month the ticket was created.
tkr_date_year	The year the ticket was created.
tkr_total_count	The number of tickets in the view type.
tkr_bold_count	The number of tickets that have not been viewed since they were last updated.

Syntax

```
object.ticketTree_Get_Group_List
(cViewType,nId,nViewId,cStatusViewable,cCategoryViewable,cPriorityViewble,cTypeViewable,nCatFilter)
```

Example

[ticketTree_Get_Group_List XML Example](#)

ticketTree_Get_Ticket_List**Description**

Retrieves an array of tickets and data for each ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cViewType	String	Required. The view type that is active. Allowed values include "status","priority","type", and "category".
nID	Long	Required. Staff ID or Customer ID associated with the ticket list.
nViewID	Long	Required. The view type id. View types include status, category, priority, and type.
nYear	Long	Optional. The year associated with the ticket list. Tickets with the same ticket creation month and year will appear in this list.
nMonth	Int	Optional. The month associated with the ticket list. Tickets with the same ticket creation month and year will appear in this list.
cStatusViewable	String	Optional. A comma separated list of statuses.
cCategoryViewable	String	Optional. A comma separated list of categories.
cPriorityViewable	String	Optional. A comma separated list of priorities.
cTypeViewable	String	Optional. A comma separated list of types.
nCatFilter	Long	Optional. The category filter id.
bCustomer	Boolean	Optional. A flag determining if the list is for a customer or a staff. If true, list is for a customer. If false, list is for a staff. If left blank, defaults to false.
cContact	Character	Optional. A flag determining if the customer is a contact. Allowed values are "Y" and "N". If the bCustomer flag is false, this parameter is ignored.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
ticket_id	The ticket id.
customer_id	The customer id on the ticket.
ticket_problem	The ticket problem.
date_entered	The ticket creation date.
staff_assigned	The staff name currently assigned to the ticket.
modified	A flag showing if the ticket has been viewed since it was last modified.
customer_name	The customer name on the ticket.
staff_assigned_id	The staff ID currently assigned to the ticket.
priority	The ticket priority.

Syntax

```
object.ticketTree_Get_Ticket_List  
(cViewType,nID,nViewID,nYear,nMonth,cStatusViewable,cCategoryViewable,cPriorityViewable,  
cTypeViewable,nCatFilter,bCustomer,cContact)
```

Example

[ticketTree_Get_Ticket_List XML Example](#)

ticketTree_Get_Viewable

Description

Returns a recordset of available views for the ticket tree. Allowable values include "status", "category", "priority", and "type".

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
view	The name of the view currently referenced.
id	The id of the sub view.
shown	A flag showing if the sub view is visible by default
name	The name of the sub view..

Syntax

object.ticketTree_Get_Viewable ()

Example

[ticketTree_Get_Viewable XML Example](#)

ticketTree_Get_View_List**Description**

Retrieves an array of tickets and data for each ticket.

Parameters

<u>Parameter</u>	<u>Type</u>	<u>Description</u>
cViewType	String	Required. The view type that is active. Allowed values include "status","priority","type", and "category".
nID	Long	Required. Staff ID or Customer ID associated with the ticket list.
cStatusViewable	String	Optional. A comma separated list of statuses.
cCategoryViewable	String	Optional. A comma separated list of categories.
cPriorityViewable	String	Optional. A comma separated list of priorities.
cTypeViewable	String	Optional. A comma separated list of types.
nCatFilter	Long	Optional. The category filter id.
bCustomer	Boolean	Optional. A flag determining if the list is for a customer or a staff. If true, list is for a customer. If false, list is for a staff. If left blank, defaults to false.
cContact	Character	Optional. A flag determining if the customer is a contact. Allowed values are "Y" and "N". If the bCustomer flag is false, this parameter is ignored.

Return Values

Returns a recordset with the following fields.

<u>Field</u>	<u>Description</u>
<X>t_id	View Type id. <X> will be the first letter of the cViewType parameter. For example, if status is passed in as the view type, this field will become the st_id. If priority is pass in as the view type, this field will become pt_id. If category is passed in as the view type, this field will become the ct_id. If type is passed in as the view type, this field will become the tt_id.
<X>t_name	Name of the view type. <X> will be the first letter of the cViewType parameter. For example, if status is passed in as the view type, this field will become the st_name. If priority is pass in as the view type, this field will become pt_name. If category is passed in as the view type, this field will become the ct_name. If type is passed in as the view type, this field will become the tt_name.
tket_total_count	The number of tickets for a view type.
tket_bold_count	The number of tickets that have not been viewed since their last update.

Syntax

object.ticketTree_Get_View_List (cViewType,nID,cStatusViewable,cCategoryViewable,
cPriorityViewable,cTypeViewable,nCatFilter,bCustomer,cContact)

Example

[ticketTree_Get_View_List XML Example](#)

Properties

Platypus

CustAdded

Description

This property is set during customer signups. The value of the property indicates whether a new customer was successfully added to the database or what error occurred if they were not successfully added.

Data Type

Numeric

Possible Values

This property can have the following possible values after a signup attempt.

<u>Value</u>	<u>Description</u>
0	The signup was successful.
1	The username is already taken by another customer.
2	An ODBC error occurred when attempting to connect to the database.
3	The insert statement failed. This could be because some of the required information wasn't specified or some of the data was invalid. This error is usually a result of removing a property from the signup.asp and not hard coding the value of the property on the adduser.asp page.

Methods That Set This Property

Method Name

[AddToPlat](#)

[AddRate](#)

[ChargeCard](#)

[CheckFormat](#)

[Post](#)

ShowCustInfo

[VerifyInfo](#)

Example

```
retvalue = ox.addtoplat()  
if ox.custadded <> 0 then  
    response.write("Error creating your customer account.")  
else
```

```
    response.write("Successful signup attempt.")  
end if
```


ChargeGood

Description

The value of this property indicates whether or not a credit card was successfully charged.

Data Type

Numeric

Possible Values

This property can have the following possible values.

<u>Value</u>	<u>Description</u>
0	The credit card was declined.
1	The credit card was approved.
2	No credit card charge was attempted. Either the billing method in a signup attempt was not "ccard" or the realtime credit card processing option is not enabled.
3	The credit card was approved but an error occurred creating the payment in the database. You can check the PayError property to see what error occurred.

Methods That Set This Property

Method Name

AddUser

[ChargeCard](#)

Example

```
retvalue = ox.addtoplat()
if ox.chargegood=0 then
  response.write("The credit card was declined")
end if
```

LastError

Description

This property is set by several methods of the web object when an error occurs.. The value of this property will be a text error message if an error occurred.

Example

```
retvalue = ox.sql("update customer set name='Justin Thornton' where id=1008")
if retvalue=false then
    response.write(ox.lasterror)
end if
```

Guarantor

Description

This is an optional property that can be used with the [AddToPlat](#) and AddUser methods. To assign a guarantor to a customer when adding them, this property should be set to the customer id of the account which will serve as the guarantor. The new customer being added will be setup as a child account of this guarantor and his rate groups will be billed to the guarantor.

This property's value should be specified as a string.

Example

```
retvalue = ox.setproperty("guarantor", "1001")
```

PayError

Description

This property is set in the [ChargeCard](#) method if an error inserting a payment occurs. The value of this property will be a text error message if an error occurred.

Example

```
retvalue = ox.chargecard()  
if ox.chargegood="3" then  
  response.write(ox.payerror)  
end if
```

XML Examples

Platypus

AddNote XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AddNote</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
        <staffid>1</staffid>
        <notetype>Complete</notetype>
        <notetext>This is my note.</notetext>
        <noteto>47</noteto>
        <notepriority>1</notepriority>
        <sendemail>1</sendemail>
        <emailsubject>My Subject</emailsubject>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The note was added successfully.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
```

```
</body>  
</PLAT_XML>
```

Method:

[AddNote](#)

-

AddRate XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AddRate</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <rate>1</rate>
        <noconn type="boolean">>false</noconn>
        <datatype>XML</datatype>
        <frequency>12</frequency>
        <quantity>1</quantity>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Rate 1 was successfully added to customer 1012</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <crid>883</crid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[AddRate](#)

AddService XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AddService</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <serviceid>1</serviceid>
        <crid>7</crid>
        <columnarray type="array">
          <row>
            <column_name>crid</column_name>
            <newvalue>7</newvalue>
            <oldvalue />
            <control>txt_text</control>
            <display>CRID</display>
          </row>
          <row>
            <column_name>d_custid</column_name>
            <newvalue>1012</newvalue>
            <oldvalue />
            <control>txt_text</control>
            <display>Customer ID</display>
          </row>
          <row>
            <column_name>d_active</column_name>
            <newvalue>Y</newvalue>
            <oldvalue />
            <control>txt_text</control>
            <display>Active</display>
          </row>
          <row>
            <column_name>username</column_name>
            <newvalue>newemail123</newvalue>
            <oldvalue />
            <control>txt_service_username_with_domain</control>
            <display>Username</display>
          </row>
          <row>
            <column_name>password</column_name>
            <newvalue>1234</newvalue>

```

```

        <oldvalue />
        <control>txt_password</control>
        <display>Password</display>
    </row>
    <row>
        <column_name>emailaddr</column_name>
        <newvalue>newemail123@justin.com</newvalue>
        <oldvalue />
        <control>txt_service_email</control>
        <display>Email Address</display>
    </row>
    <row>
        <column_name>domain</column_name>
        <newvalue>justin.com</newvalue>
        <oldvalue />
        <control>cmb_service_domain</control>
        <display>Domain</display>
    </row>
</columnarray>
<datatype>XML</datatype>
</parameters>
<properties>
    <custid>1012</custid>
</properties>
</data_block>
</body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Service successfully added.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <dataid>91</dataid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[AddService](#)

AddToPlat XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AddToPlat</action>
      <username>admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <activeconn type="boolean">>false</activeconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <billingmeth>check</billingmeth>
        <phone>6623245816</phone>
        <fax>1234567890</fax>
        <username>jameernelson</username>
        <password>a</password>
        <name2>Justin Thornton</name2>
        <address>110 That Street</address>
        <address2/>
        <city>Starkville</city>
        <state>MS</state>
        <zip>39759</zip>
        <country>US</country>
        <guarantor type="boolean">>false</guarantor>
        <email type="boolean">>false</email>
        <bonustype>F</bonustype>
        <staffid>1</staffid>
        <storeid type="integer">1</storeid>
        <selectpop>1</selectpop>
        <selectrate>4</selectrate>
        <selectshell>1</selectshell>
        <htmlemail>Y</htmlemail>
        <ccname>Justin Thornton</ccname>
        <ccaddr>110 That Street</ccaddr>
        <ccaddr2/>
        <ccccity>Starkville</ccccity>
        <ccstate>MS</ccstate>
        <cczip>39759</cczip>
        <ccccountry>US</ccccountry>
        <cctype>VISA</cctype>
        <ccnumber>4005550000000019</ccnumber>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

```

        <ccexpirem>4</ccexpirem>
        <ccexpirey>2005</ccexpirey>
        <banknumber>98765</banknumber>
        <routenumber>1234</routenumber>
        <bank_acct_type>1</bank_acct_type>
    </properties>
</data_block>
</body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The customer was successfully added.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <custid>1531</custid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[AddToPlat](#)

AuthCard XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AuthCard</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <cctype>VISA</cctype>
        <ccdate type="date">5/31/2007</ccdate>
        <ccnumber>4005550000000019</ccnumber>
        <custid>1012</custid>
        <ccname>Justin Thornton</ccname>
        <amount type="currency">5.00</amount>
        <ignored type="boolean">>false</ignored>
        <taxamount type="currency">0.00</taxamount>
        <addr>100 That Street</addr>
        <city>Starkville</city>
        <state>MS</state>
        <zip>39759</zip>
        <country>US</country>
        <activeconn type="boolean">>false</activeconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The card could not be authorized for the following reason:
|The Nova bank number or terminal ID is incorrect. Call Merchant Service Provider.|
```

```
AVS - |B|</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[AuthCard](#)

AuthorizeCard XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>AuthorizeCard</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <cctypeid>10</cctypeid>
        <ccdate>5/31/2007</ccdate>
        <amount type="currency">5.00</amount>
        <custid>0</custid>
        <ccnumber>4005550000000019</ccnumber>
        <ccname>Justin Thornton</ccname>
        <storeid type="integer">1</storeid>
        <ccv>123</ccv>
        <ignored type="boolean">false</ignored>
        <addr>100 That Street</addr>
        <addr2></addr2>
        <city>Starkville</city>
        <state>MS</state>
        <zip>39759</zip>
        <country>US</country>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>0,The card could not be authorized for the following reason:
```


|The Nova bank number or terminal ID is incorrect. Call Merchant Service Provider.|

AVS - |B|

CSC - ||</response_text>

<response_code>DATA_ERROR</response_code>

<is_success>0</is_success>

</data_block>

</body>

</PLAT_XML>

Method:

[AuthorizeCard](#)

ChangeCompany XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChangeCompany</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <nCustomer type="int">1011</nCustomer>
        <nCompany type="int">2</nCompany>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The Company was successfully changed.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ChangeCompany](#)

ChangeNotes XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChangeNotes</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <notenumber>1</notenumber>
        <notetext>This is a test</notetext>
        <notetype>Complete</notetype>
        <staffid>1</staffid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>A complete task cannot be updated.</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[ChangeNotes](#)

ChangePassword XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChangePassword</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1007</custid>
        <password>99</password>
        <newpassword>1234</newpassword>
        <password2>1234</password2>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Your password was successfully changed</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ChangePassword](#)

ChangeRate XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChangeRate</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <Crid type="int">20</Crid>
        <NewRGID type="int">3</NewRGID>
        <Datatype>XML</Datatype>
        <Frequecny>12</Frequecny>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
<header></header>
<body>
<data_block>
  <object>addusr</object>
  <protocol>TPP</protocol>
  <action>Reply</action>
  <response_text>The Rate Group was successfully changed.</response_text>
  <response_code>SUCCESS</response_code>
  <is_success>1</is_success>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ChangeRate](#)

ChangeStatus XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChangeStatus</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <newstatus>H</newstatus>
        <reasonid>2</reasonid>
        <reasonnote>Cause he wants to</reasonnote>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1007</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Customer placed on Hold</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[ChangeStatus](#)

ChargeAll XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChargeAll</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <ccaction type="boolean">false</ccaction>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <cctype>VISA</cctype>
        <ccexpirem>1</ccexpirem>
        <ccexpirey>2005</ccexpirey>
        <ccnumber>4005550000000019</ccnumber>
        <name2>Justin Thornton</name2>
        <ccv2>101</ccv2>
        <staffid>1</staffid>
        <custid>1007</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Cannot charge $0.00 to credit card.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```


Method:

[ChargeAll](#)

ChargeCard XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ChargeCard</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <balance type="currency">10.00</balance>
        <invoicelist>1135,3533</invoicelist>
        <activeconn type="boolean">>false</activeconn>
        <ccaction type="boolean">>false</ccaction>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <cctype>VISA</cctype>
        <ccexpirem>1</ccexpirem>
        <ccexpirey>2005</ccexpirey>
        <ccnumber>4005550000000019</ccnumber>
        <name2>Justin Thornton</name2>
        <ccv2>101</ccv2>
        <staffid>1</staffid>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The card could not be authorized for the following reason:
|The credit card has expired.|
AVS - |P|
CSC - ||</response_text>
```

```

        <response_code>DATA_ERROR</response_code>
        <is_success>0</is_success>
    </data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
    <header></header>
    <body>
        <data_block>
            <protocol>Plat</protocol>
            <object>addusr</object>
            <action>ChargeCard</action>
            <username>Admin</username>
            <password>admin</password>
            <logintype>staff</logintype>
            <parameters>
                <balance type="currency">10.00</balance>
                <invoicelist>18923,18924</invoicelist>
                <activeconn type="boolean">>false</activeconn>
                <ccaction type="boolean">>false</ccaction>
                <datatype>XML</datatype>
                <address>123 Main Street</address>
                <city>Starkville</city>
                <state>MS</state>
                <zip>39759</zip>
                <country>US</country>
            </parameters>
            <properties>
                <cctype>VISA</cctype>
                <ccexpirem>1</ccexpirem>
                <ccexpirey>2007</ccexpirey>
                <ccnumber>4005550000000019</ccnumber>
                <name2>Justin Thornton</name2>
                <ccv2>101</ccv2>
                <staffid>1</staffid>
                <custid>6985</custid>
            </properties>
        </data_block>
    </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
    <header></header>
    <body>

```

```
<data_block>
  <object>addusr</object>
  <protocol>TPP</protocol>
  <action>Reply</action>
  <response_text></response_text>
  <response_code>SUCCESS</response_code>
  <is_success>1</is_success>
  <attributes>
    <data_block>
      <fraudstatus>"</fraudstatus>
    </data_block>
  </attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ChargeCard](#)

CheckExpire XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CheckExpire</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <rateid>41</rateid>
        <crid>7</crid>
        <custid>1012</custid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[CheckExpire](#)

CheckFormat XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CheckFormat</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <value>jet75</value>
        <formattype>username</formattype>
        <errorfile>c:\error.txt</errorfile>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Failed: jet75. There must be at least 4 alpha characters in the
      Username.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>>false</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CheckFormat</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <value>justin75</value>
        <formattype>username</formattype>
        <errorfile>c:\error.txt</errorfile>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>true</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[CheckFormat](#)

Chk_sec XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Chk_Sec</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <securitytag>Field Level-Credit Card Number</securitytag>
        <category type="boolean">false</category>
        <noconn type="boolean">false</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <return_value>true</return_value>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Chk_Sec</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <securitytag>42</securitytag>
        <category>Rate</category>
        <noconn type="boolean">>false</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <return_value>>false</return_value>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[Chk_Sec](#)

Chk_Multi_Sec XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>chk_multi_sec</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <myarray type="array">
          <row>
            <sectag>Web Action Customer-Address-Change Addr</sectag>
            <category type="boolean">>false</category>
          </row>
          <row>
            <sectag>Web Tab-Staff</sectag>
            <category type="boolean">>false</category>
          </row>
        </myarray>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>

```

```
<data_block_item>
  <item_0>Web Action Customer-Address-Change Addr</item_0>
  <item_1>True</item_1>
</data_block_item>
<data_block_item>
  <item_0>Web Tab-Staff</item_0>
  <item_1>True</item_1>
</data_block_item>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Clockin XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ClockIn</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <staffid>2</staffid>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>1</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[ClockIn](#)

Clockout XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>ClockOut</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <staffid>2</staffid>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>1</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ClockOut](#)

Closeout XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CloseOut</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <custid>1012</custid>
        <crid>7</crid>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>1</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[CloseOut](#)

Createbonus XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CreateBonus</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <crid type="int">4</crid>
        <doconn type="boolean">True</doconn>
        <getdefaults type="boolean">True</getdefaults>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <refid type="int">1007</refid>
        <salesid type="int">1</salesid>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Bonus(es) created successfully.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[CreateBonus](#)

CreateExpiration XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CreateExpiration</action>
      <username>Admin</username>
      <password>Admin</password>
      <logintype>staff</logintype>
      <parameters>
        <nCustID type="int">1015</nCustID>
        <nCRID type="int">6644</nCRID>
        <dExpDate type="date">6/3/2006</dExpDate>
        <nNewRGID type="int">0</nNewRGID>
        <cDeact>F</cDeact>
        <nReasonID type="int">0</nReasonID>
        <cReasonNote></cReasonNote>
        <cPriceChange>R</cPriceChange>
        <nPrice type="currency">0.00</nPrice>
        <cCloseout>Y</cCloseout>
        <cUseExpireDate>Y</cUseExpireDate>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1015</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
```

```
    </data_block>  
  </body>  
</PLAT_XML>
```

Createinvoice XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CreateInvoice</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <custid type="int">1012</custid>
        <guarid type="int">1012</guarid>
        <staffid type="int">2</staffid>
        <comment>This is the comment</comment>
        <item>MISC77</item>
        <description>This is the description</description>
        <quantity type="numeric">3</quantity>
        <price type="currency">5.95</price>
        <profileid type="int">1</profileid>
        <startdate type="date">6/1/2004</startdate>
        <enddate type="date">7/1/2004</enddate>
        <noconn>False</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Invoice 5665 created successfully.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
```

```
        <data_block>
          <invoice>5665</invoice>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[CreateInvoice](#)

CreateMultiLineInvoice XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>CreateMultiLineInvoice</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <custid type="int">1012</custid>
        <guarid type="int">1012</guarid>
        <staffid type="int">2</staffid>
        <comment>This is the comment</comment>
        <item_array type="array">
          <row>
            <item>MISC</item>
            <description>This is the description</description>
            <quantity type="numeric">3</quantity>
            <price type="currency">5.95</price>
            <profileid type="int">1</profileid>
            <startdate type="date">6/1/2005</startdate>
            <enddate type="date">7/1/2005</enddate>
          </row>
          <row>
            <item>MISC2</item>
            <description>This is the description</description>
            <quantity type="numeric">1</quantity>
            <price type="currency">3.95</price>
            <profileid type="int">1</profileid>
            <startdate type="date">6/1/2005</startdate>
            <enddate type="date">6/1/2005</enddate>
          </row>
        </item_array>
        <noconn>False</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Invoice 5691 created successfully.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <invoice>5691</invoice>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[CreateMultiLineInvoice](#)

DeleteRate XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>DeleteRate</action>
      <username>Admin</username>
      <password>Admin</password>
      <logintype>staff</logintype>
      <parameters>
        <cCRID>6644</cCRID>
        <bNoCloseout type="boolean">False</bNoCloseout>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1015</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```


Deleteservice XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>DeleteService</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <svcid>1</svcid>
        <dataid>89</dataid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[DeleteService](#)

Email_account XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Email_Account</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <corr_type>STATEMENT</corr_type>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[Email_Account](#)

Fakepost XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>FakePost</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <crid type="integer">2</crid>
        <activeconn type="boolean">>false</activeconn>
        <lastbilled>7/19/2004</lastbilled>
        <nextbill>8/19/2004</nextbill>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
    <data_block>
      <basequotenumber>0</basequotenumber>
      <batchexclude>0</batchexclude>
      <batchid>0</batchid>
      <connhandle>2</connhandle>
      <curname>cur_invoice</curname>
      <customer>0</customer>
      <date>2005-05-11T14:17:38</date>
    </data_block>
  </body>
</PLAT_XML>

```

```

        <detailcount>0</detailcount>
        <details>
            <itemcount>0</itemcount>
            <items>
                <items_item>False</items_item>
            </items>
        </details>
        <discountobject>0</discountobject>
        <guarantor>0</guarantor>
        <icomment></icomment>
        <ih_storeid>1</ih_storeid>
        <invoice>0</invoice>
        <isvoidwriteoff>0</isvoidwriteoff>
        <lasterror></lasterror>
        <mmtable>iheader</mmtable>
        <obj_name>invoice</obj_name>
        <old_total>0</old_total>
        <paid>0</paid>
        <phone></phone>
        <qh_new_invoice>0</qh_new_invoice>
        <regkey>invoice_object</regkey>
        <shipaddr1></shipaddr1>
        <shipaddr2></shipaddr2>
        <shipcity></shipcity>
        <shipcountry></shipcountry>
        <shipname></shipname>
        <shipstate></shipstate>
        <shipzip></shipzip>
        <staffnum>0</staffnum>
        <stmtdate>NULL</stmtdate>
        <storewhere> ih_storeid in (1, 2, 7)</storewhere>
        <subtotal>0</subtotal>
        <taxobj>0</taxobj>
        <taxtotal>0</taxtotal>
        <total>0</total>
    </data_block>
</data_block>
</body>
</PLAT_XML>

```

Method:

[FakePost](#)

Formatccnumber XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>FormatCCNumber</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <ccnumber>4005550000000019</ccnumber>
        <ccmask type="boolean">false</ccmask>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <logintype>Customer</logintype>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ccnumber>*****0019</ccnumber>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>FormatCCNumber</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <ccnumber>4005550000000019</ccnumber>
        <ccmask type="boolean">false</ccmask>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <loginid>1</loginid>
        <logintype>Staff</logintype>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ccnumber>4005550000000019</ccnumber>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[FormatCCNumber](#)

Formatphone XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>FormatPhone</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <phonenum>6623245816</phonenum>
        <phonemask type="boolean">false</phonemask>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <phone>(662)324-5816</phone>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[FormatPhone](#)

GetAddress XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetAddress</action>
      <username>Admin</username>
      <password></password>
      <logintype>Staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <addr1>100 that street</addr1>
          <addr2></addr2>
          <attn></attn>
          <city>Starkville</city>
          <connhandle>1</connhandle>
          <country>US</country>
          <datatable>address</datatable>
          <deflt>Y</deflt>
          <idnum>1012</idnum>
          <idtype>Customer</idtype>
```

```

    <modified>0</modified>
    <oldaddress>|100 that street||starkville|ms|39759|US|Y|N</oldaddress>
    <oldstore>0</oldstore>
    <regkey>address_object</regkey>
    <state>MS</state>
    <status>L</status>
    <store>0</store>
    <syncfield>Sync_Pri</syncfield>
    <syncpri>N</syncpri>
    <type>3</type>
    <typename>Billing</typename>
    <zip>39759</zip>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetAddress](#)

Getavailablecountries XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetAvailableCountries</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
<header></header>
<body>
  <data_block>
    <object>addusr</object>
    <protocol>TPP</protocol>
    <action>Reply</action>
    <response_text></response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <country_id>4</country_id>
        <country_name>Afghanistan</country_name>
        <country_a2>AF</country_a2>
        <country_a3>AFG</country_a3>
      </data_block>
      <data_block>
        <country_id>8</country_id>
        <country_name>Albania</country_name>
        <country_a2>AL</country_a2>
        <country_a3>ALB</country_a3>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>
```

```
<data_block>
  <country_id>12</country_id>
  <country_name>Algeria</country_name>
  <country_a2>DZ</country_a2>
  <country_a3>DZA</country_a3>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetAvailableCountries](#)

Getavailablerates XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetAvailableRates</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1</id>
          <name>Internet Access 3 Month Plan</name>
          <sortorder>2</sortorder>
        </data_block>
        <data_block>
          <id>5</id>
          <name>Internet Access 6 Month Plan</name>
          <sortorder>3</sortorder>
        </data_block>
        <data_block>
          <id>51</id>
```

```
        <name>Blogware Super Happy 1</name>
        <sortorder>193</sortorder>
    </data_block>
    <data_block>
        <id>52</id>
        <name>Blogware Super Happy 2</name>
        <sortorder>194</sortorder>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetAvailableRates](#)

Getavailablewebrates XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetAvailableWebRates</action>
      <username>Admin</username>
      <password></password>
      <logintype>Staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <ICCS type="boolean">>false</ICCS>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1</id>
          <name>Internet Access 3 Month Plan</name>
          <sortorder>2</sortorder>
        </data_block>
        <data_block>
          <id>5</id>
          <name>Internet Access 6 Month Plan</name>
          <sortorder>3</sortorder>
        </data_block>
        <data_block>

```



```
        <id>9</id>
        <name>Internet Access 12 Month Plan</name>
        <sortorder>4</sortorder>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetAvailableWebRates](#)

Getccinfo XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetCCInfo</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <cctype>BANKCARD</cctype>
          <ccnumber>400555000000019</ccnumber>
          <ccdate>2003-03-31T00:00:00</ccdate>
          <creditcardmasked>400555000000019</creditcardmasked>
          <type>5</type>
          <idnum>1012</idnum>
          <idtype>Customer</idtype>
          <attn>justn</attn>
          <addr1>100 that street</addr1>
          <addr2/>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

```
        <city>starkville</city>
        <zip>39759</zip>
        <deflt>N</deflt>
        <state>ms</state>
        <country>US</country>
        <sync_pri>NULL</sync_pri>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetCCInfo](#)

GetChildren XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetChildren</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1011</id>
          <name>Justin Thornton</name>
          <guarantor>1012</guarantor>
          <date>2003-02-21T00:00:00</date>
          <active>Y</active>
          <taxid>NULL</taxid>
          <staffnum>1</staffnum>
          <timestamp/>
          <attn/>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

```

<addr1>100 That Street</addr1>
<addr2/>
<city>Starkville</city>
<state>MS</state>
<country>US</country>
<zip>39759</zip>
<phone>1234567890</phone>
<fax/>
<username>justint3</username>
<password>a</password>
<email>justint3@yourdomain.com</email>
<stmtmethod>EMAIL</stmtmethod>
<laststmt>2003-02-21T00:00:00</laststmt>
<nextstmt>2003-02-21T00:00:00</nextstmt>
<custbillday>21</custbillday>
<nostatement>N</nostatement>
<nolatenotice>N</nolatenotice>
<nodeactivate>N</nodeactivate>
<nocloseout>NULL</nocloseout>
<noreceipt>Y</noreceipt>
<latedate>NULL</latedate>
<deactivatedate>NULL</deactivatedate>
<referralid>0</referralid>
<referral>NULL</referral>
<comment>NULL</comment>
<cctype>NULL</cctype>
<ccnumber>NULL</ccnumber>
<ccdate>NULL</ccdate>
<cuskey>NULL</cuskey>
<timeleft>360000</timeleft>
<blockuser>Y</blockuser>
<blocktype>1</blocktype>
<shellid>1</shellid>
<websignup>Y</websignup>
<ponumber>NULL</ponumber>
<routenumber>NULL</routenumber>
<damount>NULL</damount>
<dtype>NULL</dtype>
<salesid>1</salesid>
<lastusername>NULL</lastusername>
<latefeetype>NULL</latefeetype>
<latefeeamt>NULL</latefeeamt>
<lastlatefee>NULL</lastlatefee>
<c_pop_id>1</c_pop_id>
<lastrcpt>NULL</lastrcpt>
<bank_acct_type>NULL</bank_acct_type>
<bank_name>NULL</bank_name>
<storeid>1</storeid>
<blacklist>NULL</blacklist>
<gracedate>NULL</gracedate>
<htmlemail>N</htmlemail>

```

```
<closeoutdate>NULL</closeoutdate>
<reg_code_number>NULL</reg_code_number>
<account_type>1011</account_type>
<cc_type>NULL</cc_type>
<issuenum>NULL</issuenum>
<startdate>NULL</startdate>
<gift>No</gift>
<stmtamnt>NULL</stmtamnt>
<osrsusername>NULL</osrsusername>
<osrspassword>NULL</osrspassword>
<cpeid>NULL</cpeid>
<c_creditlimit_amount>NULL</c_creditlimit_amount>
<c_creditlimit_type>NULL</c_creditlimit_type>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetChildren](#)

Getcommissions XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetCommissions</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <reftype>I</reftype>
        <payid type="int">0</payid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <staffid>1</staffid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <total>37.6500</total>
          <paidddate>NULL</paidddate>
          <payid>NULL</payid>
        </data_block>
        <data_block>
          <total>10.0000</total>
          <paidddate>2004-08-30T14:55:58</paidddate>
          <payid>5</payid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[GetCommissions](#)

Getcustomer XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetCustomer</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1012</id>
          <name>justn</name>
          <guarantor>0</guarantor>
          <date>2003-03-07T00:00:00</date>
          <active>Y</active>
          <taxid>NULL</taxid>
          <staffnum>1</staffnum>
          <timestamp/>
          <attn/>
          <addr1>100 that street</addr1>

```

```

<addr2/>
<city>starkville</city>
<state>ms</state>
<country>US</country>
<zip>39759</zip>
<phone>1235678904</phone>
<fax/>
<username>justn</username>
<password>a</password>
<email>jthornton@tucows.com</email>
<stmtmethod>CREDIT CARD</stmtmethod>
<laststmt>2003-03-07T00:00:00</laststmt>
<nextstmt>2003-03-07T00:00:00</nextstmt>
<custbillday>7</custbillday>
<nostatement>N</nostatement>
<nolatenotice>N</nolatenotice>
<nodeactivate>N</nodeactivate>
<nocloseout>NULL</nocloseout>
<noreceipt>Y</noreceipt>
<latedate>NULL</latedate>
<deactivatedate>NULL</deactivatedate>
<referralid>0</referralid>
<referral>NULL</referral>
<comment>NULL</comment>
<cctype>BANKCARD</cctype>
<ccnumber>4005550000000019</ccnumber>
<ccdate>2003-03-31T00:00:00</ccdate>
<cuskey>NULL</cuskey>
<timeleft>360000</timeleft>
<blockuser>Y</blockuser>
<blocktype>1</blocktype>
<shellid>1</shellid>
<websignup>Y</websignup>
<ponumber>NULL</ponumber>
<routenumber>NULL</routenumber>
<damount>NULL</damount>
<dtype>NULL</dtype>
<salesid>1</salesid>
<lastusername>NULL</lastusername>
<latefeetype>NULL</latefeetype>
<latefeeamt>NULL</latefeeamt>
<lastlatefee>NULL</lastlatefee>
<c_pop_id>3</c_pop_id>
<lastrcpt>NULL</lastrcpt>
<bank_acct_type>NULL</bank_acct_type>
<bank_name>NULL</bank_name>
<storeid>1</storeid>
<blacklist>NULL</blacklist>
<gracedate>NULL</gracedate>
<htmlemail>N</htmlemail>
<closeoutdate>NULL</closeoutdate>

```

```

        <reg_code_number>NULL</reg_code_number>
        <account_type>PPP</account_type>
        <cc_type>NULL</cc_type>
        <issuenum>NULL</issuenum>
        <startdate>NULL</startdate>
        <gift>No</gift>
        <stmtamnt>NULL</stmtamnt>
        <osrsusername>NULL</osrsusername>
        <osrspassword>NULL</osrspassword>
        <cpeid>NULL</cpeid>
        <c_creditlimit_amount>NULL</c_creditlimit_amount>
        <c_creditlimit_type>NULL</c_creditlimit_type>
        <balance>541.54</balance>
        <credit>17.71</credit>
        <creditcardmasked>4005550000000019</creditcardmasked>
        <phonemasked>(123)567-8904</phonemasked>
        <faxmasked/>
        <activestatus>Active</activestatus>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetCustomer</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
/PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>

```

```

<body>
  <data_block>
    <object>addusr</object>
    <protocol>TPP</protocol>
    <action>Reply</action>
    <response_text></response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <id>1012</id>
        <name>justn</name>
        <guarantor>0</guarantor>
        <date>2003-03-07T00:00:00</date>
        <active>Y</active>
        <taxid>NULL</taxid>
        <staffnum>1</staffnum>
        <timestamp/>
        <attn/>
        <addr1>100 that street</addr1>
        <addr2/>
        <city>starkville</city>
        <state>ms</state>
        <country>US</country>
        <zip>39759</zip>
        <phone>1235678904</phone>
        <fax/>
        <username>justn</username>
        <password>a</password>
        <email>jthornton@tucows.com</email>
        <stmtmethod>CREDIT CARD</stmtmethod>
        <laststmt>2003-03-07T00:00:00</laststmt>
        <nextstmt>2003-03-07T00:00:00</nextstmt>
        <custbillday>7</custbillday>
        <nostatement>N</nostatement>
        <noatenotice>N</noatenotice>
        <nodeactivate>N</nodeactivate>
        <nocloseout>NULL</nocloseout>
        <noreceipt>Y</noreceipt>
        <latedate>NULL</latedate>
        <deactivatedate>NULL</deactivatedate>
        <referralid>0</referralid>
        <referral>NULL</referral>
        <comment>NULL</comment>
        <cctype>BANKCARD</cctype>
        <ccnumber>4005550000000019</ccnumber>
        <ccdate>2003-03-31T00:00:00</ccdate>
        <cuskey>NULL</cuskey>
        <timeleft>360000</timeleft>
        <blockuser>Y</blockuser>
        <blocktype>1</blocktype>

```

```

    <shellid>1</shellid>
    <websignup>Y</websignup>
    <ponumber>NULL</ponumber>
    <routenumber>NULL</routenumber>
    <damount>NULL</damount>
    <dtype>NULL</dtype>
    <salesid>1</salesid>
    <lastusername>NULL</lastusername>
    <latefeetype>NULL</latefeetype>
    <latefeeamt>NULL</latefeeamt>
    <lastlatefee>NULL</lastlatefee>
    <c_pop_id>3</c_pop_id>
    <lastrcpt>NULL</lastrcpt>
    <bank_acct_type>NULL</bank_acct_type>
    <bank_name>NULL</bank_name>
    <storeid>1</storeid>
    <blacklist>NULL</blacklist>
    <gracedate>NULL</gracedate>
    <htmlemail>N</htmlemail>
    <closeoutdate>NULL</closeoutdate>
    <reg_code_number>NULL</reg_code_number>
    <account_type>PPP</account_type>
    <cc_type>NULL</cc_type>
    <issuenum>NULL</issuenum>
    <startdate>NULL</startdate>
    <gift>No</gift>
    <stmtamnt>NULL</stmtamnt>
    <osrsusername>NULL</osrsusername>
    <osrspassword>NULL</osrspassword>
    <cpeid>NULL</cpeid>
    <c_creditlimit_amount>NULL</c_creditlimit_amount>
    <c_creditlimit_type>NULL</c_creditlimit_type>
    <balance>541.54</balance>
    <credit>17.71</credit>
    <creditcardmasked>*****0019</creditcardmasked>
    <phonemasked>(123)567-8904</phonemasked>
    <faxmasked/>
    <activestatus>Active</activestatus>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetCustomer](#)

GetECheckInfo XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetECheckInfo</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <bank_acct_type>1</bank_acct_type>
          <bank_name/>
          <ccnumber>4005550000000019</ccnumber>
          <routenumber/>
          <type>5</type>
          <idnum>1012</idnum>
          <idtype>Customer</idtype>
          <attn>justn</attn>
          <addr1>100 that street</addr1>
          <addr2/>

```

```
        <city>starkville</city>
        <zip>39759</zip>
        <deflt>N</deflt>
        <state>ms</state>
        <country>US</country>
        <sync_pri>NULL</sync_pri>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetECheckInfo](#)

Getemaildomains XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetEmailDomains</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <data_id>4</data_id>
          <crld>0</crld>
          <d_custid>0</d_custid>
          <gid>0</gid>
          <d_active>Y</d_active>
          <domain>bigfatdomain.com</domain>
          <timestamp></timestamp>
          <email_address>NULL</email_address>
          <password>tryme</password>
          <package>NULL</package>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

    </data_block>
    <data_block>
      <data_id>6</data_id>
      <crid>0</crid>
      <d_custid>0</d_custid>
      <gid>0</gid>
      <d_active>Y</d_active>
      <domain>newone.com</domain>
      <timestamp/>
      <email_address>NULL</email_address>
      <password>tryme</password>
      <package>NULL</package>
    </data_block>
  </attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetEmailDomains](#)

Getinvoicedetails XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetInvoiceDetails</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <invoice>1261</invoice>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <invoice>1261</invoice>
          <item>SVC#41</item>
          <descriptio>12/7/2003 to 1/7/2004 -- Fixed Monthly 0.00
hrs</descriptio>
          <qty>1</qty>
          <price>19.9500</price>
          <date>2004-01-22T18:06:51</date>
          <customer>1012</customer>
          <sdate>2003-12-07T00:00:00</sdate>

```

```
<edate>2004-01-07T00:00:00</edate>
<timestamp/>
<profileid>0</profileid>
<id_item_code>7</id_item_code>
<id_taxable_amt>0.0000</id_taxable_amt>
<id_item_instock>NULL</id_item_instock>
<amount>19.9500</amount>
</data_block>
<data_block>
  <invoice>1261</invoice>
  <item>SVC#41</item>
  <descriptio>11/7/2003 to 12/7/2003 -- Usage 0.00
hrs@1.0000/hr</descriptio>
  <qty>1</qty>
  <price>0.0000</price>
  <date>2004-01-22T18:06:51</date>
  <customer>1012</customer>
  <sdate>2003-11-07T00:00:00</sdate>
  <edate>2003-12-07T00:00:00</edate>
  <timestamp/>
  <profileid>0</profileid>
  <id_item_code>7</id_item_code>
  <id_taxable_amt>0.0000</id_taxable_amt>
  <id_item_instock>NULL</id_item_instock>
  <amount>0.0000</amount>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetInvoiceDetails](#)

Getinvoices XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetInvoices</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <startdate type="boolean">>false</startdate>
        <enddate type="boolean">>false</enddate>
        <invoiceowner>Customer</invoiceowner>
        <invoice>5665</invoice>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <invoice>5665</invoice>
          <customer>1012</customer>
          <shipname>justn</shipname>
          <shipaddr1>100 that street</shipaddr1>
          <shipaddr2/>
          <shipcity>starkville</shipcity>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

        <shipstate>ms</shipstate>
        <shipcountry>US</shipcountry>
        <shipzip>39759</shipzip>
        <phone>1235678904</phone>
        <total>18.7400</total>
        <date>2005-05-11T14:17:37</date>
        <subtotal>17.8500</subtotal>
        <guarantor>1012</guarantor>
        <paid>0.0000</paid>
        <timestamp/>
        <comment>This is the comment</comment>
        <staffnum>2</staffnum>
        <batchid>NULL</batchid>
        <stmtdate>NULL</stmtdate>
        <taxtotal>0.8900</taxtotal>
        <batchexclude>0</batchexclude>
        <ih_storeid>1</ih_storeid>
        <ih_locked>NULL</ih_locked>
        <due>18.7400</due>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetInvoices</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <startdate>5/1/2005</startdate>
        <enddate>6/1/2005</enddate>
        <invoiceowner>Customer</invoiceowner>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <invoice>5679</invoice>
          <customer>1012</customer>
          <shipname>justn</shipname>
          <shipaddr1>100 that street</shipaddr1>
          <shipaddr2/>
          <shipcity>starkville</shipcity>
          <shipstate>ms</shipstate>
          <shipcountry>US</shipcountry>
          <shipzip>39759</shipzip>
          <phone>123654789012</phone>
          <total>19.9500</total>
          <date>2005-05-11T15:07:52</date>
          <subtotal>19.9500</subtotal>
          <guarantor>1012</guarantor>
          <paid>0.0000</paid>
          <timestamp/>
          <comment/>
          <staffnum>1</staffnum>
          <batchid>NULL</batchid>
          <stmtdate>NULL</stmtdate>
          <taxtotal>0.0000</taxtotal>
          <batchexclude>0</batchexclude>
          <ih_storeid>1</ih_storeid>
          <ih_locked>NULL</ih_locked>
          <due>19.9500</due>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetInvoices](#)

Getoptions XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetOptions</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <package>custinfo</package>
        <category>general</category>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>28</id>
          <name>cash_drawer</name>
          <display>Cash Drawer</display>
          <value>1</value>
          <package>NULL</package>
          <category>General</category>
          <active>Y</active>
          <sortorder>10</sortorder>
          <input>select</input>
          <datatable>cash_drawers</datatable>
          <encrypted>N</encrypted>

```

```
        <regoption>X</regoption>
        <storeid>1</storeid>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetOptions](#)

GetPaths XML Example

Input:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetPaths</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <nRateGroup type="integer">47</nRateGroup>
        <cPathType>UPGRADE</cPathType>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>48</id>
          <name>Power Play Level 2</name>
          <rg_category/>
          <rg_subcategory/>
          <rg_description/>
          <sortorder>1</sortorder>
        </data_block>
        <data_block>
          <id>49</id>
          <name>Power Play Level 3</name>
          <rg_category/>

```

```
        <rg_subcategory/>
        <rg_description/>
        <sortorder>2</sortorder>
    </data_block>
    <data_block>
        <id>50</id>
        <name>Power Play Level 4</name>
        <rg_category/>
        <rg_subcategory/>
        <rg_description/>
        <sortorder>3</sortorder>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

[GetPaths](#)

Getpaymentdetails XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetPaymentDetails</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <payid>12</payid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <pd_hdr_id>12</pd_hdr_id>
          <pd_invoice>1012</pd_invoice>
          <pd_amount>19.9500</pd_amount>
          <pd_applied>2003-03-07T13:57:50</pd_applied>
          <pd_txnumber>13</pd_txnumber>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
</body>  
</PLAT_XML>
```

Method:

[GetPaymentDetails](#)

Getpayments XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
<header></header>
<body>
  <data_block>
    <protocol>Plat</protocol>
    <object>addusr</object>
    <action>GetPayments</action>
    <username>Admin</username>
    <password></password>
    <logintype>staff</logintype>
    <parameters>
      <datatype>XML</datatype>
      <sdate />
      <edate />
      <paymentid>808</paymentid>
    </parameters>
    <properties>
      <custid>1012</custid>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
<header></header>
<body>
  <data_block>
    <object>addusr</object>
    <protocol>TPP</protocol>
    <action>Reply</action>
    <response_text></response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <pmt_id>808</pmt_id>
        <pmt_name>REFUND--Unused SVC#41</pmt_name>
        <pmt_type>15</pmt_type>
        <pmt_total>0.0000</pmt_total>
        <pmt_applied>-17.7100</pmt_applied>
        <pmt_date>2005-05-11T00:00:00</pmt_date>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>

```

```

    <pmt_authorize/>
    <pmt_number/>
    <pmt_custid>1012</pmt_custid>
    <pmt_depositid>NULL</pmt_depositid>
    <pmt_postdate>2005-05-11T14:17:36</pmt_postdate>
    <pmt_staffid>1</pmt_staffid>
    <pmt_bounceid>NULL</pmt_bounceid>
    <pmt_ccbatchnum>NULL</pmt_ccbatchnum>
    <pmt_cdid>1</pmt_cdid>
    <pmt_batchexclude>NULL</pmt_batchexclude>
    <pmt_storeid>1</pmt_storeid>
    <pmt_transid>NULL</pmt_transid>
    <pmt_locked>NULL</pmt_locked>
    <p_id>15</p_id>
    <p_type>REFUND</p_type>
    <p_name>REFUND</p_name>
    <p_active>N</p_active>
    <p_sortorder>0</p_sortorder>
    <p_required>0</p_required>
    <p_available>0</p_available>
    <p_depositttype>NA</p_depositttype>
    <p_secure>0</p_secure>
    <p_carddigit/>
    <p_opendrawer>NULL</p_opendrawer>
    <p_bouncefee>0</p_bouncefee>
    <p_default>N</p_default>
    <p_allowchange>1</p_allowchange>
    <pmt_number_masked/>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetPayments</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```



```

        <custid>1008</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <pmt_id>808</pmt_id>
          <pmt_name>REFUND--Unused SVC#41</pmt_name>
          <pmt_type>15</pmt_type>
          <pmt_total>0.0000</pmt_total>
          <pmt_applied>-17.7100</pmt_applied>
          <pmt_date>2005-05-11T00:00:00</pmt_date>
          <pmt_authorize/>
          <pmt_number/>
          <pmt_custid>1012</pmt_custid>
          <pmt_depositid>NULL</pmt_depositid>
          <pmt_postdate>2005-05-11T14:17:36</pmt_postdate>
          <pmt_staffid>1</pmt_staffid>
          <pmt_bounceid>NULL</pmt_bounceid>
          <pmt_ccbatchnum>NULL</pmt_ccbatchnum>
          <pmt_cdid>1</pmt_cdid>
          <pmt_batchexclude>NULL</pmt_batchexclude>
          <pmt_storeid>1</pmt_storeid>
          <pmt_transid>NULL</pmt_transid>
          <pmt_locked>NULL</pmt_locked>
          <p_id>15</p_id>
          <p_type>REFUND</p_type>
          <p_name>REFUND</p_name>
          <p_active>N</p_active>
          <p_sortorder>0</p_sortorder>
          <p_required>0</p_required>
          <p_available>0</p_available>
          <p_deposittype>NA</p_deposittype>
          <p_secure>0</p_secure>
          <p_carddigit/>
          <p_opendrawer>NULL</p_opendrawer>
          <p_bouncefee>0</p_bouncefee>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

    <p_default>N</p_default>
    <p_allowchange>1</p_allowchange>
    <pmt_number_masked/>
</data_block>
<data_block>
  <pmt_id>109</pmt_id>
  <pmt_name/>
  <pmt_type>14</pmt_type>
  <pmt_total>9.9500</pmt_total>
  <pmt_applied>9.9500</pmt_applied>
  <pmt_date>2003-11-26T00:00:00</pmt_date>
  <pmt_authorize/>
  <pmt_number/>
  <pmt_custid>1012</pmt_custid>
  <pmt_depositid>NULL</pmt_depositid>
  <pmt_postdate>2003-11-26T10:01:55</pmt_postdate>
  <pmt_staffid>1</pmt_staffid>
  <pmt_bounceid>NULL</pmt_bounceid>
  <pmt_ccbatchnum>NULL</pmt_ccbatchnum>
  <pmt_cdid>1</pmt_cdid>
  <pmt_batchexclude>NULL</pmt_batchexclude>
  <pmt_storeid>1</pmt_storeid>
  <pmt_transid>NULL</pmt_transid>
  <pmt_locked>2004-06-04T11:14:03</pmt_locked>
  <p_id>14</p_id>
  <p_type>ACH</p_type>
  <p_name>ACH</p_name>
  <p_active>Y</p_active>
  <p_sortorder>0</p_sortorder>
  <p_required>0</p_required>
  <p_available>0</p_available>
  <p_deposittype>BANK</p_deposittype>
  <p_secure>0</p_secure>
  <p_carddigit/>
  <p_opendrawer>N</p_opendrawer>
  <p_bouncefee>0</p_bouncefee>
  <p_default>N</p_default>
  <p_allowchange>0</p_allowchange>
  <pmt_number_masked/>
</data_block>
<data_block>
  <pmt_id>105</pmt_id>
  <pmt_name/>
  <pmt_type>14</pmt_type>
  <pmt_total>9.9500</pmt_total>
  <pmt_applied>9.9500</pmt_applied>
  <pmt_date>2003-11-26T00:00:00</pmt_date>
  <pmt_authorize/>
  <pmt_number/>
  <pmt_custid>1012</pmt_custid>
  <pmt_depositid>NULL</pmt_depositid>

```

```

    <pmt_postdate>2003-11-26T10:01:55</pmt_postdate>
    <pmt_staffid>1</pmt_staffid>
    <pmt_bounceid>NULL</pmt_bounceid>
    <pmt_ccbatchnum>NULL</pmt_ccbatchnum>
    <pmt_cdid>1</pmt_cdid>
    <pmt_batchexclude>NULL</pmt_batchexclude>
    <pmt_storeid>1</pmt_storeid>
    <pmt_transid>NULL</pmt_transid>
    <pmt_locked>2004-06-04T11:14:03</pmt_locked>
    <p_id>14</p_id>
    <p_type>ACH</p_type>
    <p_name>ACH</p_name>
    <p_active>Y</p_active>
    <p_sortorder>0</p_sortorder>
    <p_required>0</p_required>
    <p_available>0</p_available>
    <p_depositttype>BANK</p_depositttype>
    <p_secure>0</p_secure>
    <p_carddigit/>
    <p_opendrawer>N</p_opendrawer>
    <p_bouncefee>0</p_bouncefee>
    <p_default>N</p_default>
    <p_allowchange>0</p_allowchange>
    <pmt_number_masked/>
  </data_block>
  <data_block>
    <pmt_id>12</pmt_id>
    <pmt_name>justn</pmt_name>
    <pmt_type>7</pmt_type>
    <pmt_total>19.9500</pmt_total>
    <pmt_applied>19.9500</pmt_applied>
    <pmt_date>2003-03-07T00:00:00</pmt_date>
    <pmt_authorize>000000</pmt_authorize>
    <pmt_number>4005550000000019</pmt_number>
    <pmt_custid>1012</pmt_custid>
    <pmt_depositid>NULL</pmt_depositid>
    <pmt_postdate>2003-03-07T13:57:50</pmt_postdate>
    <pmt_staffid>1</pmt_staffid>
    <pmt_bounceid>NULL</pmt_bounceid>
    <pmt_ccbatchnum>NULL</pmt_ccbatchnum>
    <pmt_cdid>1</pmt_cdid>
    <pmt_batchexclude>NULL</pmt_batchexclude>
    <pmt_storeid>1</pmt_storeid>
    <pmt_transid>NULL</pmt_transid>
    <pmt_locked>2004-06-04T11:14:03</pmt_locked>
    <p_id>7</p_id>
    <p_type>DEBITCARD</p_type>
    <p_name>BANKCARD</p_name>
    <p_active>Y</p_active>
    <p_sortorder>7</p_sortorder>
    <p_required>7</p_required>

```

```
<p_available>39</p_available>
<p_deposittype>ELECTRONIC</p_deposittype>
<p_secure>0</p_secure>
<p_carddigit/>
<p_opendrawer>N</p_opendrawer>
<p_bouncefee>0</p_bouncefee>
<p_default>N</p_default>
<p_allowchange>0</p_allowchange>
<pmt_number_masked>4005550000000019</pmt_number_masked>
</data_block>
</attributes>
</data_block>
</body>
</PLATXML>
```

Method:

[GetPayments](#)

Getpaymenttypes XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>getpaymenttypes</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <p_id>10</p_id>
          <p_type>CREDITCARD</p_type>
          <p_name>VISA</p_name>
          <p_active>Y</p_active>
          <p_sortorder>3</p_sortorder>
          <p_required>7</p_required>
          <p_available>62</p_available>
          <p_depositttype>ELECTRONIC</p_depositttype>
          <p_secure>0</p_secure>
          <p_carddigit>4</p_carddigit>

```

```

        <p_opendrawer>NULL</p_opendrawer>
        <p_bouncefee>0</p_bouncefee>
        <p_default>N</p_default>
        <p_allowchange>0</p_allowchange>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>getpaymenttypes</action>
      <username>admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <p_id>1</p_id>
          <p_type>VOID</p_type>
          <p_name>VOID</p_name>
          <p_active>N</p_active>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

    <p_sortorder>0</p_sortorder>
    <p_required>0</p_required>
    <p_available>0</p_available>
    <p_depositttype>NA</p_depositttype>
    <p_secure>0</p_secure>
    <p_carddigit/>
    <p_opendrawer>NULL</p_opendrawer>
    <p_bouncefee>0</p_bouncefee>
    <p_default>N</p_default>
    <p_allowchange>1</p_allowchange>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetPaymentTypes](#)

GetPhone XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetPhone</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <connhandle>2</connhandle>
          <datatable>phone</datatable>
          <deflt>Y</deflt>
          <dftfaxcol>fax</dftfaxcol>
          <dftphonecol>phone</dftphonecol>
          <idnum>1012</idnum>
          <idtype>Customer</idtype>
          <modified>1</modified>
          <number>(123)567-8904</number>
          <oldphone>(123)567-8904|Y|N</oldphone>
          <ph_comment>NULL</ph_comment>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```



```

        <regkey>phone_object</regkey>
        <status>L</status>
        <store>0</store>
        <syncfield>Sync_Pri</syncfield>
        <syncpri>N</syncpri>
        <type>1</type>
        <typename>Home</typename>
        <usformat>Y</usformat>
    </data_block>
    <data_block>
        <connhandle>2</connhandle>
        <datatable>phone</datatable>
        <deflt>n</deflt>
        <dftfaxcol>fax</dftfaxcol>
        <dftphonecol>phone</dftphonecol>
        <idnum>1012</idnum>
        <idtype>Customer</idtype>
        <modified>1</modified>
        <number></number>
        <oldphone>0</oldphone>
        <ph_comment></ph_comment>
        <regkey>phone_object</regkey>
        <status>N</status>
        <store>0</store>
        <syncfield>Sync_Pri</syncfield>
        <syncpri>N</syncpri>
        <type>2</type>
        <typename>Work</typename>
        <usformat>y</usformat>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetPhone](#)

GetPlatOption XML Example

Input Example

```
<?xml version="1.0"?>
<PLATXML>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>getplatoption</action>
      <username>John Smith</username>
      <password>password</password>
      <logintype>staff</logintype>
      <parameters>
        <option>Area Code</option>
        <reload type="bool">>false</reload>
        <company>1</company>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example

```
<?xml version="1.0"?>
<PLAT_XML>
  <body>
    <data_block>
      <object>addusr</object>
      <version>7.0 Build 2299</version>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <value>601</value>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method

[GetPlatOption](#)

Getprevioususage XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetPreviousUsage</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <begindate>09/07/2004</begindate>
          <enddate>10/07/2004</enddate>
          <beginlong>Sep 7, 2004</beginlong>
          <endlong>Oct 7, 2004</endlong>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetPreviousUsage](#)

Getrates XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetRates</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>41</id>
          <name>Basic Dialup</name>
          <fixed/>
          <accumulate/>
          <billfreq>1</billfreq>
          <fee>25.0000</fee>
          <daily/>
          <sortorder>188</sortorder>
          <billoffset>0</billoffset>

```

```

        <addinfo/>
        <poverride/>
        <autopost>Y</autopost>
        <webrate>X</webrate>
        <rg_tp_id>0</rg_tp_id>
        <rg_category/>
        <rg_subcategory/>
        <rg_fee_category/>
        <rg_fee_subcategory/>
        <rg_description>Basic Dialup Rate</rg_description>
        <reactivationfee>2.0000</reactivationfee>
        <rg_bill_active/>
        <pkgid>NULL</pkgid>
        <rg_fee_tax_profile_id>0</rg_fee_tax_profile_id>
        <rg_fee_question>Y</rg_fee_question>
        <rg_bundle>N</rg_bundle>
        <rg_ccs_svc_id>NULL</rg_ccs_svc_id>
        <rg_dngrade_overload>NULL</rg_dngrade_overload>
        <rg_ccs_include_fee>NULL</rg_ccs_include_fee>
        <crd>7</crd>
        <custid>1012</custid>
        <rgid>41</rgid>
        <lastbilled>2005-05-11T00:00:00</lastbilled>
        <nextbill>2005-05-11T00:00:00</nextbill>
        <billguar/>
        <pendfee>N</pendfee>
        <setuptaxes>0</setuptaxes>
        <price>NULL</price>
        <dateadded>2003-03-07T13:57:46</dateadded>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetRates](#)

Getratinginfo XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetRatingInfo</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <svcid>2</svcid>
        <dataid>91</dataid>
        <lastbilled>8/19/2004</lastbilled>
        <nextbill>9/19/2004</nextbill>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <number>1</number>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetRatingInfo](#)

Getreferrals XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetReferrals</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <referralttype>I</referralttype>
        <payid type="int">0</payid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <total>5.0000</total>
          <paiddate>2004-08-11T08:44:48</paiddate>
          <payid>4</payid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetReferrals</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <referraltypes>D</referraltypes>
        <payid type="int">1</payid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>No referral bonuses found for customer1012</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 3:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
```

```

        <action>GetReferrals</action>
    <username>Admin</username>
    <password></password>
    <logintype>staff</logintype>
    <parameters>
        <referraltyp>P</referraltyp>
        <payid type="int">0</payid>
        <datatype>XML</datatype>
    </parameters>
    <properties>
        <custid>1012</custid>
    </properties>
</data_block>
</body>
</PLATXML>

```

Output Example 3:

```

<PLAT_XML>
    <header></header>
    <body>
        <data_block>
            <object>addusr</object>
            <protocol>TPP</protocol>
            <action>Reply</action>
            <response_text>No referral bonuses found for customer1012</response_text>
            <response_code>DATA_ERROR</response_code>
            <is_success>0</is_success>
        </data_block>
    </body>
</PLAT_XML>

```

Method:

[GetReferrals](#)

Getreportcategories XML Example

Input Example:

```
<?xml version="1.0"?>
PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetReportCategories</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <category>Aged Accounts Receivable</category>
        </data_block>
        <data_block>
          <category>Credit Card</category>
        </data_block>
        <data_block>
          <category>Customer</category>
        </data_block>
        <data_block>
          <category>Daily Sales</category>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

```

    <data_block>
      <category>Debit Card</category>
    </data_block>
    <data_block>
      <category>Echeck</category>
    </data_block>
    <data_block>
      <category>Inventory</category>
    </data_block>
    <data_block>
      <category>Other</category>
    </data_block>
    <data_block>
      <category>Sales</category>
    </data_block>
    <data_block>
      <category>Staff</category>
    </data_block>
    <data_block>
      <category>Wombat</category>
    </data_block>
  </attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetReportCategories](#)

Getreports XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetReports</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <reportcategory>Customer</reportcategory>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <name>Accounts with Credits</name>
          <descriptio>Lists customers which have credits on their
account.</descriptio>
          <id>305</id>
          <filename>unappmt2.rpt</filename>
          <listorder>1</listorder>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[GetReports](#)

Getreportdetails XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetReportDetails</action>
      <username>Admin</username>
      <password></password>
      <logintype>Staff</logintype>
      <parameters>
        <reportid>16</reportid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>16</id>
          <category>Sales</category>
          <name>Bounced Payments</name>
          <descriptio>Lists all payments that have been bounced.</descriptio>
          <filename>bounced.rpt</filename>
          <listorder>1</listorder>
          <criteria>A,B,C,D,E</criteria>
          <selection>{bounce.date}</selection>
          <selection2>{bounce.staffid}</selection2>
          <selection3/>
```



```
        <selection4>{pheader.pmt_storeid}</selection4>
        <idcaption>Staff ID</idcaption>
        <sec_level>NULL</sec_level>
        <r_title/>
        <r_param/>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>
```

Method:

[GetReportDetails](#)

Getreportfile XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>getreportfile</action>
      <username>admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <reportId type="int">317</reportId>
        <startdate type="date">12/25/2004</startdate>
        <enddate type="date">3/10/2005</enddate>
        <startid>1001</startid>
        <endid>1200</endid>
        <cStores>1,2,7</cStores>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0"?>
<PLAT_XML>
  <header/>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>
      </response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <reportfile>
JVBERi0xLjIgCiXi48/TIAoxIDAgb2JqIAo8PCAKL1R5cGUgL0NhdGFsb2cgCi9QYWdlcyAyIDAg
```

UiAKL1BhZ2VNb2RIIC9Vc2VOB25IIAovVmld2VyUHJlZmVyZW5jZXMgPDwgCi9GaXR
 XaW5kb3cg
 dHJlZSAKL1BhZ2VMYXlvdXQgL1NpbmdsZVBhZ2UgCi9Ob25GdWxsU2NyZWVuUGFn
 ZU1vZGUgL1Vz
 ZU5vbmUgCj4+IAo+PiAKZW5kb2JqIAo1IDAgb2JqIAo8PCAKL0xlbmd0aCAzNTggCi9Ga
 Wx0ZXIlg
 WyAvRmxhdGVEZWNvZGUgXSAKPj4gCnN0cmVhbQp4nH1RTU/DMAy951dk/Vg/1qR1
 mjTJ1q1lgJA4
 Qo+5IBBliF248PdxkgHSDihKHPvZfs8J0A4XAzy0FfT5RLQ+Xw7Xx7uiKD3uL8IGGqBC
 3oiyii0
 wfkjx7Q0vAhID3a6HnouBD4oRBi4EZRKbiHy4m0lkJP11dSrpI0y9dJ4UpX1UmRp/6S1ehv8i
 Zl
 Na/o8k4YDJprRZkxvFN0efEdNLcq9GiztANXCizqQ7pU3CIvppVSDazGpqssTXQAoeu4VGf
 YWLbd
 pSGuBFe/4W0KrM7HLM3ZzitiRRKShOCDoho4RBVP1PyoiJPEQTYN420bpQv11TAwvtI3
 X+XrDkTf
 uMpVMiH5EP17Y/FxIr92pRFZYV217V21s2sjXJXjHveHaTpM4zz66nFurqZmZvoYqXo/AV
 OAfBdP
 tK+zXZN1cZw9H5JzAX4mVgwSuLyc518qBfJPLFwXrppR4A2aAN8u5BuLOnnGZW5kc3R
 yZWftIapl
 bmRvYmogCjEzIDAgb2JqIAo8PCAKL0xlbmd0aCA0MTYgCi9GaWx0ZXIlgWyAvRmxhdG
 VEZWNvZGUg
 XSAKPj4gCnN0cmVhbQp4nHWTwWrbQBCG736KOaYkIFkjSzYYQetcfGga4vYB1rsjI4hW
 YiVT8vbV
 P6MGeqhBgv00M7v6/Cs7nZ/PsZspe02Dv8hMbRdDkmm4Jy90IVsXaVtQ6Py8rvTuezdStjRf
 PqZZ
 +nNsBzoeN9nb8nCa0wc9fNXf48+ul+lfir8NvYtP34b38IWyHyll6uKNHn6dLsv6ch/Hd+klzp
 RT
 01CQdpOdvrvxxfVC2X9HaeF2PdEQZBqdl+TiTehYbBs6cmhIYvj32aY4WMu1tbXV6i3Py7J
 ZQAFQ
 KKh2AAzACmqtKAFKq9gC7AB2Bg4AFUBlwAPUALUBnbEH2CsocoADwMHOwQAOW
 Nm2BcAV4GoVewAP
 4K1CWwJasF1aAAEQq9CDtQCtzcBQzqEqtxbMYHVnPirswlDB5qPEDIYKNh+FtkAFm48
 Sxhgq2HzU
 OgMq2HzUeFuGCjYf7ACggs1HCacMFWw+qgAAfbz60F2ggs1HJQBQwasPHRRWHCxt1
 hf4vD3f0cy
 kOPPpPI7SksINeyaPwSsi/L5PYzDiDzh2vwBBJrWZmVuZHN0cmVhbSAAKZW5kb2JqIAoxN
 iAwIG9i
 aiAKPDwgCi9MZW5ndGggMTYyMDkgCi9MZW5ndGgxIDIyNzIwIAovRmlsdGVyIFsgL0Z
 sYXRIRGVj
 b2RIIF0gCj4+IApzdHJlYW0KeJzFvHlgVNx9OHrOuXPv7DN39i0zd2buzCSZyWSSyWQlZ
 G5WAjEQ
 FDFBImGLbEiCiILwQ3FBarWvZVat6rfMkwUA9SaVqu1tYWuYrWCLW3VGqEtaqsk8/uc
 O8Ni2/d7
 7/3+eO8O53zO8jn753y2ewPCCCE9GkEM6plzUSJ5y4mBDoTwP6F09tRfFg8h3cl1kH4XQtnS
 TRv9
 Azd8cBwhcgdCKtXg0OVXZDuvSCKkuRch9sjlazYPotGtP0NIfBWh1OkVyxcvW1b02U+hv
 3FoX7MC
 CiwK3Q5o3wn50IorNI59/Z+V34B6FeSvXrNu6eJXTr1wGvIjkG+6YvHVQ6oeSxvgr4G8f+3i
 K5Z/

WI3fQijYCDjbh9Zt2JgLoVcQ4uX6ofXLh1bvmnsI8jA/UwbKMKyLPjqkQH6ACvjBik9Oz+U
 gDuRy
 xmM0jxBXj4vY15GHuRPNic+giAKhhaQeRSHEFBugDHCgfi7Ud3FQxnjRXMCZBcHEzof8
 nWg24HVA
 eSmUIUAZhQkoK4b+9kBbnnsGXQD5tIx3J7IBziy6L2gK/5y0MeOKhYp32WPsMe4Z5bWq
 LRqV5iPt
 B7pj+l2GV40NfInJaf615bdWu/Vj+9WOq53fc51yXy+vENE13vvsD65bZGz8VOVSyQt+7I/V
 HRTu
 /80LM7+8bfIOHqmqAVedXy19mFXke4iFVT3EVke34TxkdqNBYsYsISpGybKEUaB/e7rXr
 V2H/CeD
 J6ezq6c6cJUygA/m56EMTLWjS3j05W1TER6dG6nw+OQSH/o7akTrEIcI4IECXQztsNZMYi
 wdyGB
 vUAORcy9yINQ7n0IQG+5D6Zm5U6zq5E4tSp3jLFA56F8KDxhdBMKoQ/Qfchl1I9+ShjUjst
 RL1Jg
 J3IhgutRF+aRA7FYg0qQiLpQD7LB7v8J69EeVik+wh1oGw6jOegRFESzkr01o6+h3XhG7k
 O0Df0K
 r0TPQuunsYSK0QW4M3cUzUU9uRdhDISmofvRQ9iABKjRYDH3HvSwAW1HB9BvUQ4t
 QA+wu6GXHnQh
 Wpt7ES1Ev8AL8KW5IjQTrUXXowfQt9BL6Di+FY8r2NwAqkZL0HqsxBZcwtyQexrVsUfU
 L+RezR2G
 3VoLuAfQxySm6Mh9giT0gQLnVsDOWVAV/Naix9A+9C524mqmFRlQCSbqR9eiPUwJzLE
 T3QZrO4Cv
 wXsYQ+5xWE0tWoq2omP4ajxOAuwR9mRuCzLD+Ilw0x3ocfQDuFl/hd468Dzmiql0bjacnwr
 FUDuM
 dBO6BX0Xdu6H8HsVG3EAz4Sef4Dfw+8za5k/Q89PoQn0GfonLSer8fUkTW5gk5Pbci+gCK
 xQgi5m
 okvQGvQcjmAJXwptHyFXkevJVmYf866iRHEiV5d7BWgkAbg3oGdgXT9Hv0JvwXl14G78
 W3I9M8re
 krsG5ptAK2AVN6En0H70KWaxGuuwFftxFa6FIV2Dx/H7xEtE0sssYfawd+Q25+5EAaCVfr
 QcWq5C
 N6Kb0YvoEPoD+iuawG5omYCWadyD78Q78avkEHMJ5C5TyEp7lM8q/ih4jRrYn849YupY
 7DrtJ8K
 1A2/fjSItsBej8HvFfQ7zGAP9kFP0/Es6GkRHsTX4l346/jb+Em8D7+OD+MP8Qn8L+Ikd5B7
 yUHy
 I3KIHGa8TJRpYx5l3lQEFL9TfKlcPomdenqRE6bi+Wqcrtyj+TeyU3Ip1AEFJ9GrUBdq4F3
 34R2
 oa+jb8CeP49+hn4DdHdU/h1HJ+EMvsQcUJMLZhTEli7GZbC6S3AvvgrvwPfgx/Fr+H18HJ8
 miOhI
 EH5RUkNmKYYXkBvIxOc1oGJFpZq5m7md+yXyh2Mwm4fcs+wJ7kjuuDKvePP3w5HtTaGrl
 1H1TD+eq
 gRY5oDwL3LkUagGamwWnvAwNw2892oSugj3aAjv+CFDOHpRFB9GP0Zuw94fQOyBh6
 Hzp70M4iVNo
 ErgigfNksQp++blXwMm0ArUM4OVwtvnfnfgGfBt+AH4P42/ib8H+/gL/Ev8KH8V/xJ/CmhC
 Jk2Yy
 A1bUQy4l/fBbRJaSbeR28jz8fk5+S94hfyBfMDxjYgSmmGlnLmduZXYwGeZ55tfMbxQRRb
 OiU7Fa
 8briF7DyTnYmu4hdyt7Ofov9NvtD9ifscTbH3cM9xo1xHyg1yhplj3Ke8jbld5QHle8qc6pioKdu
 mH3peXzwHnypIkF24RwZg3V/n2xkfkruxc+ezyrZHTCDZWgRGWNeIt+4dhfzB+Y5cgOIrza
 5ejpw
 sTfR99Cb7K8UNvYD9Dpxo0+AH97LLCbFjW8SJ65hpiluVrwJXGczPPb5ChRkj2A8Vc4jU
 XoYuxC

flfMRydg/w+xO2BPO8h7+FnyGpkFIHwEPU4OogfRbrQc18LslqEX0Bfoa3g/48f7gO62osPo
 Y3Ts
 3GwVickWkuacZBPXACe0H8/NvU5Kc3+FW/8+vhm9w3wBtD8fz8YJ9CT6I5z6b3AKC4op
 hQf9Ajif
 Dz0MVPsXNAp38CeKENygT9F+JoUWKI7BmScm35hqYzcyN+LPSDMcp0Pm3HMoNwYe
 /ADwKspHDWgP
 UAJwEfIG/xX9DAdhF3/F/Q49hHaiA4wNhZknyAjJMT9W+Nhd6BhzAYx6HfCnIpyCnq5A
 K2Ed/tyf
 px6HHlahOlSHl+AFqA1qOpEvdwXM/EngRVJuYe5Bto+NoZ/jC7ANvQzcywm7eB+rnpoAz
 OfhHr6D
 OvHtaHRqGRoHueLEYZwEappgN7G72GfY59nvsz/jKtHVcGsflhP8AzoFUsOP18JeflQ+B1p
 vgdT
 BvenGWbRCTJsDeljXkKt2I2GgAeWAN9ugT1YACe5AXq5Ad0B9+kJkCE/Rycxjxei76Mjc
 HMccM+X
 wvgq6KcLpOwiwH4SuOONeBRKloEcjsI+fYENuI5shPEon70P+Ow4zOld9GfgHDl5XmV4G
 m6D01uK
 Pqd3GUaoQT14L8jkfageJGUb8yb6EwqBdG2BO/o4tBsA2jAgL6pn/4gJKpuanasjK5mXsB2k
 oQGo
 ah5I9ul4GGZhhHVMlhueg6qnZkBvzwIv62GfkJrnSemm6Y3TGurraqtTVcnKikR5vCwWLS0
 pjoRD
 YjDgF3zeIo/b5XTYbVaL2cQbDXqdVqNWKTIWwRCMytrFjgF/JjKQUUTEzs44zYuLoWDx
 eQUDGT8U
 dXwVJ+MfkNH8X8WUAHPw3zCIPKZ0FhPz/kbUGC/zt4v+zM/aRP8YXjC3F9J3tol9/syEnO
 6W07vk
 tB7SgQA08Lc7V7T5M3jA357p2LRiR/tAG3S3V6tpFVuXa+JlaK9GC0ktpDIOcWgvdjRhOU
 Ec7Q17
 CVLpYVIZt9jWnnGJbXQGGsbcvnhZpmdub3ubJxDoi5dlcOtScUkGiS0ZY0xGQa3yMBmuN
 aOUh/Gv
 pKtBt/v3lo3vuGOMR0sGYrpl4rLFC3szzOI+OoYpBuO2ZRxbjvPZaFzc2vv9vNrPcyOdudKP
 83u
 2LHdn9k9t/f82gCN+/qgD2hLwh0DOzpg6Dtge7su8sNo5Oa+3gy+GYb005XQVeXXt1xspyU
 Dq/wZ
 tdgirtixagCOxr0jgy7cHMi63dL+3DHkbfvmNcrBjJp9i3uK1orXtuHDzqEvvy75aEy/by5vy
 G7vXYCwkPrZE8vP1skpGZ2mui48u7OYzkicCQSR8S/1w0x6RVhTHY2W16EdS+sADZ4+
 DK0yy+BE
 VmbUrQM7+AZaTtn2DAv+nd8ioACxImPv1qyuFDChflPEU1SOjlLalB/Jp2JxTLRKCURZS
 ucKeyx
 Sc5Xx8s2jZFHxSHeDwC2D/XA3i7ua0jA9gcC9IBvH5PQEshkRub25vN+tMSTRVli1pchA7
 Rm/EyN
 7WJaM3Km5mzzAREo+XIzybdIVJGz/4y83dK+oiGD7f+b6uX5+q6LxK65C3r97TsGCnvbNe
 8ruXx9
 3dm6Qipjae1lPKSQIh5GrgWiXHgWmWZ6dRIFGP5xMIEvG1OqgCrlEuzvyPADnfm4TxMI/
 D9sNJY7
 SVvJ4FyzwjQzDbGv5qd9Jf+V6el2MDBhRYR0zVuwY4fmK3UdwIF27OgQ/R07BnYsHsuN
 LBH9vLhj
 P6grxTuG2gfOnOhY7sDtnkzHHX2wiBW4AaiVoJa9Ir517l4J33rRgt79YJb5b53XmyWYtA60
 9O0N
 QV3vfrCMJbmUnC2lOT/NgeEEI4lKrnKs19CaESuVcgFcn7pGEZymepMGUZLx0i+jJfL4lk
 XbHGU
 C1Cb/T+fA2heblzBjLa3J6UxgLFyGWZLSp7aUXWXZR8Cdj7g2CkCFCAs3aPXIOyLS2FR
 EldPjEa

jSePNmvAej0BgYDdj0F0yq1GS8qTJ1+GPGamkBFjWsqcHuWtMBozOWq0JKVmnvkX6oF
AUIbZi8Yh
ELSO+RRthUAAfU82XkkHYvaMagxJHvBPID+EEQgM2g0xlVMSBIp/YtRip93/JWs0ye2OZ
itS+cQo
70z2NFuZd2E+bcC/BONUAHXvlyCgBeZ1gF6ArzE/Rnp5no+PGvncCIz3bUD/NrMZIUL1E
8wWlAT4
NHM9yFaK9nbWkB/n7WxJNNmsYZ5irpVRNjDDoFoIzBpmdTYp+A8yj8NMJebjUbWWzu/
jLG9LvsR8
yKxGVsA6DlGOWfgSsxYIINCvjI2q9cldzTpmDJY5BtsiwBwxelSOJeaXWegIxsOMwJGtM
AcYraB
uiYwzzA3ZG3C+EHmcxntM9oLjPdYVlVFwajekBxvVjOPQW2G+Tvs+N/I0U6NRuqSqDnC
3IEqIBDY
1D9C6o/UecB8AqlP4Jg+gaP5BI7mE5jFJ2CAIGY CaiYAJ8G8h4aYd9AuCI9CWgFdbS7CDu
6XE6GS
5H7mOuZa2An+IOwdhtLrR9UGOrNrs2aLjHbtqM6QTL/EvIXmQCAw+SOjDmdy3UHmLnk
pu0adHtrg
11m1DrbumvxZQMMt9AxeYkaYG+Sd2CbvQOb7kMXIyNwoN86N6kzJrXD68yC7DuKdEA
5DOAFBAWjz
YA3z0CIIDKD3jBqMSeNBZoHceGbWUCW8xHTC0jvl3erM2oLynGeMQmLuQaYLiGQO
Mzu7TIAJzs1C
Y1o7e7SuIVlxkJktL3h2VhDzxVmLS050ZNV54mkd1ZjocG0yYiyrMsjFscK9Y6KjVkdSAGJ
skJdU
RZk7UwtnVAv7XwuXoUre8eQobwYSX8Yk5Wkn0QCE3RAyEBRwkElAT8JBjkEvT8rLro
E11aAcBAYO
sAadhECgvBKlleyE8DKEYxBYuXQAAoHyChhhAOJdEAj0mIA8D7EEYQDCCITdEMYhn
ISgRIeYOIwT
B+wKiEcZCAchaCAaymDeZRBnZnxo0kVQgLaSh6UGvBWtBVvJVuZrYqt7FZ+q0kIVYf
LktIqGpXT
qASi2gH1kHpEzVS0JXWPmuHVfjUZy41nlQ1VACQz11D1u+6Pur/oZsy1u7hdSnKoWYdN
6CiEExAY
dAi06qMQTmBe2s4cajradKKJOdR9tPtEN3PovaPvnXiPORQ/Gj8RZ6RuT0OydhFeh7finVgh
4AQY
+XOWYhGzjtnK7GQUApNg0kALigHtkHZEy1RoJW2PluG1fi3Zpd2tzWjHtYe1bIYb5w5zx7i
THNvD
DXBD3Ai3i9vNcYIyoUwrJU5xsrmVvAOuhviDASCRiDeJad4uWYc4sNyfpecH4B4SM5LE
PflKRHi
CpqCIEJfvwO8EYh3QaB4NC9CXEHZEERg4W9D2RDEuyAQ8rZUFKwISSHCh/whAvbHy
RA+HDoWIpnQ
eIiMNzeQI/Isj8Asj8izPAItj8hjH4F+IQVBhNm+JeO9BXhvyXhvAR5N/beyAYiH5JQEcY+cE
iGu
oCnyVlasNTY7yMPQ4yKIH4VwFAKDEhCnlayTcwLFIA9DLJGHRovLkiNj5KFBBghgGA
e+PKgSAaj
LndyUbORPARdPgRdPgSd0JwAIU1zuXHyYLaN4j6YnZ4HDVVHm2tBVNkpPIj2QCBoDs
SPyqkExGk5
tUfGMZ7NZyA+JqeGIN59tt0iOSVAfKYtQx6C34OQMpItULpF0hJkt4MgN5tU5jFyILvSLIy
R57MI
PIDRPMhS0GwhDOy9Hn8ix9+V40fl+F45vkSOjZJW1P9L1P9I1D8l6ps1ZBYKQffJOf5Qjld
JhpD+
g5D+tZD+2yH9YyH9QfxHFISKgOQO6v8U1P8+qH8xqH8mqL8nqF8Y1M8N6i8I0q5KkB/pi
ZfG+DI5

LpIcfv1pv/59v/6nfv2P/fpv+fV9fn2DH9Dx30Fo6vEjcnY/HFe/mNILKb03pT9AgDPhS7NGpD
 5I
 CL4U6RlNNtokjDFqGZBAAtjsMoCjb3QzAk+2+EIA7270egCXbfY/QrCZGvBc0EoEY8F4Vh
 bpsdBtU
 a/NAIY1eBoDNRuuFMTyVjYoAvswOegF8kR30AfgsO5gC8CkF38P/QINgBQv4b9nBb0L3+
 CNUQrvF
 f0ER8izAsWx3GrBfzI+On0dNOAzFoPDTWeDnslGYHH46Gy0B8FQ2GgLwZB58OxsVAH
 wrO1gO4JvZ
 wXsAfCM7eBzAQ9mSNbS/B1GJ3M8DKCLDDdluD1QPZ7tpD0PZ7gSAddnuagCrs00/A7A
 y23ScNr0c
 78VA2XgQReWZLs4ORqF6UWEh/ahErl6IquWeZ2S76ZZ00E6a9bi9sJA23EoVO9yC98q9S
 NloBaA1
 ZaMRANPzO9eYHYwBqMuWwB7j2mzJN2HnagoDINLz+R4OwTRoR2I2+iwgCdnBUgC+7
 GA7AA9tCZOy
 FEY1oyZ5UqZslGLx2ahf+D7WokG5Rw2K4If2CZPQ75dNY3h+VvhCGlPhrPB5CYB9wsfd
 S4S/do+B
 Wit8BFf42X3CUUB9rwmSkIz4N3pceGcwKPwkChiSR3gjWi68EtksjJUcFEa7fcJemFhmcIm
 wZ1Du
 4bsRaJYVni4ZIxha7x68QHggGhPuj4zROdwNyNvpGNDRzdHNwg2RbcKVQAobu28TNkS9
 wIDJZcKq
 EjqQQ1gZvVBYAQu5HNosH7xcWBy9Rxiolmd8WfRnwKXV8hq6BuUVzWySKzoHLxQ6Y
 AZQkaYVMINp
 QJdJaFpfeZDuEYrj1tGfCRfXfo+AFMYjENZL5cqXlNcrlyjnKVtA3hQrw8qA0qe0qswqXmV
 Q6VQa
 lUrFqRQqoklqRKxjuWNSjL5nsnLy6yZOQWOFnOYJjUn+xRTBkoJmoYyF6Sjdf7VkamNd
 Y8rchZm6
 WfDg2XNp716M7+rDXZnxpahriT/z2UXiGNaAfcaKLThj7kjd81qcgJwht4KhM693DOdoi5s
 91Omx
 H2FcdvOdHgo7br6zrw/ZN6WdaXOTqb6j7b9EA4W4vS127nHGYl/JeTP3dV3Um3nG25dJ0k
 TO29eV
 KaWOklf1kDVnV3rafrKagr3c/XkHWtF9Iy/GKtj5AmyajoSayGtBQNwWARhaiJooG5QvPQ8
 N7obht
 b1NTHmkO3kuR4NLMkZEW5JFaz0dibsetMIrc7uM9M38gFGYBwwUQBo7BoUIQeMsmt
 kNCdF2xuJ
 QE+DEYqyNxBhL2RpFw991x1Sb76f/LV/0OrxzA+V18dyc+2BEXkESKkBHBi/z8+y1v+D
 xrh0emb
 1vZSh9aA2L4cwkDm9k0rnJmRjX7/3rWbCp6uyMCSpSsoXLw8s0lc3pZZK7b5907v/S/VvbR
 6uti2
 F/W2z+vd2ystb8tOl6a3i4vb+kZnb6sb/spYt50dq27bf+lsG+2sjo41e/i/VA/T6tl0rGE61jAd
 a7Y0Wx6r68IW3NXTu1eFWvpaF+bhKNFq4LYMeAJ9LXZ+qEm+OtMCzus9BxQIP420sb6
 MTmzJ6CHQ
 qnhzvJIWwZWmVQbqtCxUOa+fFvAcwE8XqngoNoktaKOzfWUb/NsAz8aNV8IDe7xhQ36v
 nfmKjbf2
 uR4QNkJqo/wAJqRp2CCXFuo3oivPPbFYHhdtiLX27u3ubneubPOAEj9K9e5Y3wYUi+UHj
 MUQjAmr
 lhV9u6zoazl71W+6/9T9aTczLmv4hyEckzX8cdDuD0M4Bhq+jxlvOtx0rIkZ7z7cfQxw3zv83r
 H3
 mPH44fixOFNbmAEdqg/DDM/9roxtuJIWx7C8WnndkN0Y2xCjSz6zB5CL0VK6K/Dky+V2
 MegldrZt
 7FxiQ77ySrlJvnTDOQIG5qpCg4X3/AxyoTPv/BWQdhXSHKSS1POjoN8eJFFXIU2QAV1XS
 DNQfnsh

rYD0S4U0B+kTzflTm7fyiuUbZi+/6sJ1VyxeW9aybs2y//cVqPm8XwzNQyvRFWg52oBmQ3
 wVuhCt
 g/xitBaVoRZlr0HLoGw5uhxdCenFaP3/Qfv/L1qAfCtCiC1i6SkoUcvzBL/CKccYIWRBrOIVB
 mmU
 ilcwcqk49hXCfA83IzUO4/nIGeM/a5xsnM2faueybERpSPOnIaqsCJgCpjBEuEiBTvuZ8dMSi7
 5E
 fsU4jEW/y2CH2QsAxrBWWugeUWtSIo14GsVodLllhfPy8EOIYyXs5aaVkLnf9ID9cQu31K
 D0e1Ew
 qPJ7DUGxqNxoIMFqjwepzPEio1fwEm+TqkKJe5RYeV3Z9BecMZhb/zDMrr+xm2/tlXgU4S
 Mk0o2s
 vLXCylhrPuvv/rDfsy/SXWHFcm6iD9bBT6QbJ2KxyoquizbvUzVulmaJcZ4t9lishCupLi0OFr
 M
 cOdyhLPbHDanzWVTcKFwjI+EcZRGohuiYksRjWJQFgvgbmEU4xvhlH6j9Jn2zbUj/tptqq6
 KIIT
 W1NtSkUioldgSDrsZpvVQJScyJisdoe9KllbY+KLI8URT3xa2qi2t9bHyaJ/3PvCwYV3v7xj+o
 0L
 elun6qneqy9sHuwMh/22lcy1K1LF4Za5U2OHdv7tG4vcOkXuy/fmRTTG9Q+Bhss+sqVMoN
 ZZ7jjT
 z7yCbMiPq6Veztxl7beus66wLXdutirDmqfla+QN0y/IL5gj+iO2fzD/1Gu22nBQsthS851BZl3w
 KmZr8EbmFsNH+g9s6qgqZ8cqtTqGQOnyqxhVP+u3I9xhH8Mlz3siFiUL6u+oTqu2y6wt6Urb
 JVcw
 ZV+JIL8Pska45pQzag0pCiWnqRq5E8F0cFHwRFAR9JcasYAJTvIUCfBl6DPnYaQiRaGk0xl
 Sh3nM
 uwJld+WpgO4w0MHx2Xz/Z7HYcKwbDhhodi9cQrIthEwjnP+jeHKCjhtn8nnDTsdLgfhisyC
 D7mt
 dh/2mTw+7LBBhOTzi8a2wbmh4X48jAPy6dTUOjhODBZHqlPmqRdmYKTEoNKzmZj+id
 z6gXtixuX
 1AUvGNt8ePX8yWfu+sUnYtgmpgLT8KcH1lzUeon94W27t738EbZ9+Ni3rhbMVX0PizJHjO
 T+Qe5T
 TAIffEAy7NTu1BE50uqQawzvklxYYbUythsJ5vxa6pZhtOvVywlawoxhg+Rlft0bg9WKJCR
 FVjC
 Ri1222ar1SLprGkL3SreG0wlLOOWwxG4nLPvvjMdsGNodXIw82B3ZnNf9Y9AVmUnjze
 T++5vGON
 sGGVFXgYDWNTIU0EGqUk6oAtgIVXm8TqmpaPPbee8YI39zgm7uv7xqTZsvlelsUk1PP
 LJ18eW7C
 u9Q+vnR68D78L7Hv1c2UNyzM/YN5D2ixEjWSWZKN4/l6hZ+vT0qNbanbq+9RPlzNNNFJ
 L+6q3leP
 r1c+GX+u8cX4a/EjgbfiR6r/HFdXK9uVsyyzHDOrex2Dqq+jh6ufwPvwPpWuCoyEpgcVD8Uf
 qVSg
 pp6mpfaBpvWO+2x78BMNL+NjTRqVvadp4zSmU0VsZhuZRkd51VF/YhpOVqnUKmWsrC
 RWFo6VITZW
 PVt1sIpRVE2v6q66rurOqker/qfqaqfV/2+aqJKO1SFq6ZZVQHvctWVKgVRTVNdoNqiuk31
 qOpJ
 1Y9Vb6vUWpVHNaRirGYV49RHhBj0WDqYmNZJkvej/kSCOKXSWMroFJyLnOucjzr3OF
 92Ko86P3ae
 djJOp2TgU04iKInWWCaUJcrSZYqyttJWY1gIk/BHCCXUafVW9ctqhR8AQWpeTdRj+KDE
 S00jTURq
 GmgiTU/bsI2qHlJJT0k658GeGKrla0ltkpXEcGode5IIFazE9rADrIJ1Ta+72DmGK2/Oc1K4Nc
 On
 hmM/6Of7h0/196+n9PHZ8X6UTpvrYwmop2QxwU/wk6eO8xMmR33/8HozjUz19dhkrq/n31
 DxjYbG

RtQfw+v3cqR1Xu/zOqfXSVB/n3z1knUNRaKGZxTGsDcSCGsj9REDXEek86t9OCg2MLU+
 xBfpfVgT
 hKhOMc2HZM1F5qrysw0evH64H62nVxMuKJSFKU1Wp2rC1ZS30itppW/+C6U1cFkhe5Z+
 ZQI2cXms
 qiSZ+eytPavGcLVDKmmOuosiM6elL17/5tqbH3YYNFa92+Nlrm7rWaDZPK044Iond9y/cs7
 qZ++6
 bFVtqdfstAmxksr2C6o6b+wYboneP/V1KcCHnbNau76O62fMraktFz2U7qMQiWDyaFEReke
 y+0ZM
 jrTRhMyoSDDxZr6Ic4QE8xj+5PmgPiSYaEJ0hoSig7IHjIPDNKVqUns4zEkI64o4s0mjpkdCB
 KV5
 KpCYUp3OqBf0RB91OiTo3kE1zIZqCkb9YkqGFocMpUS8IpVx4J0OjBy8gziukXw9PiL4Bn
 y7fRmf
 IuFL+3ZCYtx3zMd5Z4+DIgBn/Fl//7B8Ao3ANIAMgDmmG+E3IfNe3A+sIoaT57bdQoWaL
 VBdkHnF
 lTjSvOBSSVqw4M3y1illk89a3sKukQsk6dKpaZOepbWKUIgEHUtJEJh4I2gQ5IQ6BI8gsWa
 6a4N
 mMHkxkYWID9eYHngIJw2JHDy3uGQwMp7pwsJPCQkuwgtOVaD8jllqtPSndHmd4aC0Xgq
 pS3sEIWS
 CFuU0eKdWoy0vJZorxHMu80ZM5Mwp807zePmY2bWTPeRuykK98XLUyZ5g2Kx/uGv7J
 C8OWc2BsrX
 f2zH6LltuODLTWcXz/x4CV18dU1edivaYf0+FMdbJPEB/dP6/foX7QqzuVaFfLyPOIS4WuV
 8TPD9
 SDQqgXEo6frxY5wAiUtfVMVu0ulUWuofklyOzYGIVQldISq6iSqKnLyTOKOYrttAJTOeg0
 kGY+xO
 0B3qqqZgdNr0FIWSFURuT+JwggwldidIJoqgiCTLYhttyuMKXuJ7+MO8gneV121znmUo/S
 CR18M+
 fJbPTeR3ZuLUBNXD+E8nTuNP+2OMgW+Eh+4VMImSYFRvCYXFMOHmkbwGZggHLZ
 FiFNVDfDYFinGx
 MVaM8pIaRDWoWaD+JYb0Q5ah4FA0kxhPcEOGreZNj3iUOk18VscO+IP6O+3P1z2pP3Z
 sgNlhhHj
 bSZChXs/NUH3owSs1BVIyyt2+mWYdQhp2nsfKHAM4BRwemz1GQUgz1RMqWLgN9UW
 mecAO8krccwv
 OVW8burKGes6RlfMW/HCitYV09S6ipbts1aHneFEKu4o6Z0NR/7mFdaAXxHovnd+0+4bXr
 r/xJZU
 M3avtnuLopO33GUVHvnW3mcilh0NRXAP5ubeZy9hV6MQ9u5H9tzIKCjRRWN5yBWgHq
 DUBwmdW+2p
 sXS7b7Hf7t7pua1It dq02rzZtNl8m+kp7mn9E47XHT/1aDg7irTam4tG7Dc7bvHcVPSi4qBPk4i
 s
 EK7iNuk3eW6xHDAqaw0mc8iLFhAvxmPYKkEy8B2T2cCu8jKGVTY1XpQwYZN7CGjBH
 F67HycRPXc4
 CbVRI2ilptvIOkUV8NF8aqKPamf93cdlvQxkxsenJjAPpICookGV8SRVxkP2Ik6vizjCKrVST
 ThP
 RG/XhBFXBJHwaQgjtZsN4zMnD/IAbhfqH5ZVbmwsqQCQebtZVtIs9MRCBFS2UFUyr8W
 xlxSXnXxg
 668r0wtffWtkN5vWf/7E21N7Xvwp7vvhzkcXuvwJJbt6Kjr26t2b7t+/b+o3Dw7dduVVq7+LO
 8Z+
 iBeON4USVYil38p3gTm1FnSZUlwSabQRbb3WquNl5jIaDFFu8pdRj5CKFbgFwJGsUC1nvb
 58sZGX
 oVRstaf4GL5PuytGtC69KWX0wjUtFby8jy/lm3ucKAg3HGZyTleE7wykxNDQillcl5RkzRK
 vsa0

USqqTRsvZxmFEpVyPq/G2I80B/AipMCLXtylPKw8pmSALRyQtKjU6BCA70fFYP6mUzBa
 kUrJ0OOX
 oQQ7mBoP4qEgRkE+SIK/i1LtkT/D5YDjNTrVPzHBH8/LgUZqU8G/mFK+zPQugwVY4lix
 GL2rNvna
 5CVEXnem2rMjf7mANVLOCDCeOMb/Xc017U211fPVmr0XnepzY+VukTdlHJ6TKWJVD
 BP/fpri9rT
 rbPaFJw9mF585Vt19bzHxYRCbP0WwvbYi4BG8vKDswL/bMVpydwaFFHAz/u9qmDQKZ
 mlaafM+WqL
 0pQT7nYyfr/XOUbefjGY9HujwWADrbYAXoMEOMYGoWFPA9Pi9zYAzr6gkvagPNuDKlf
 uVjLY71XS
 HkST3+sliqVneiiVeygVSveUMqLfWwo40mVild9bHxSDgZJWZEQCSIPzPFpa6nQ6SEN9v
 UqlVImo
 hW8hLU1JYxWGf4tA+7wOtQ+0E6m9p313e6Zd0e7Py7YmE+Ix/OsBq+i6tumbCgx4fcE4ps
 KpkKEG
 MPzysbl+fQL0fSqM8lI89pUkw7PUFgCTH8vqUxWcEjVTzzNjbYVjNAX+o+TfW5AKB5i0k
 9Pi00Ju
 g1Y2b39E00YtPmpvqy8jr5Y1ipCj6cnGfJrcMbWQWrlhmyHoHMxbvPn01AgeOZc7fdO5NH
 4cyTzz
 OPk13M8k2S4t1FbY+LSC15daeW+pgrPara+FX4u8zX/E/4tXlvLhaB1fE92u/br49dB3tN8Wx
 7TP
 i1pWx+pVpTbdDG2XjpO0ko6YkwJ6mAgYgzRMY0lrTj+KKWdslyzoYXMCCIKJf8Scguthj
 +B2U/0A
 UHa5sXsMr5ZE18P2f5jNbCSmNPsiZq05f3CS2ZbCl5pRgA+QgGwza42pfC5ooPlykK+CAR
 vcxhRO
 pOakFqXWpbam9qS4lNmoEkCQS9Agnwq6S0vOmNklmCYINYjtEldV3bBMENQwPg4K2z
 AlvrDufg+f
 VIEkBzRQSDzAWtVoEyGyhyELU8/fXMq1hz9bT6V3vmHAD8sP0NcraughcBm0pjMfhQ5k
 CH3IELqh
 MHu2p1jfcbbkHMGqIEifsYJEJlt4DkcEBkd6eR+wDAUEH8vl8xrRvLPeHUbBmZQgYFGYB
 XUaU8fYj
 NveCZAZc1geIrA+wWOsZFP5jqqsW5MzH1PcqGROSxpROgJiCCNZC0ShSHouOHI7D1IC
 HHx7NQ1iq
 y5gOxx0GmvuVpIZEOG7Xp8Njub+NgqYA8PiLoDnoikCNQGd9oH1oGNgg1TP6gRla8tKJ2
 h0KygZl
 ZQJui8hUUdukppq6FGT14oysIvcag9NvbC5tsPpxpH/2XfNbh3zagD3AB+Pf6KiY3rjiwXjL1+
 +8
 YIbHZLY7mR9M/eCuFbUhj6v09dvnz76vJ6pN4p6bbpoWreiYsaruwqVr9oSNRhH0ylm548y
 LcDf0
 KIDnSc7X3bhYh82XqAwRPUZKR0SpVmm9kuKMZqiQImC0KrDCLblhQxm5EFaBqP101
 MUSqGSWGpc
 PCwSJErigeiTYHk+KhLRaBbMxCwd1mJtwbcjQ+iawn1AqFpXEPoYeb64mtKrTLCgV+d1y
 OH18oZ+
 BvKkewJRaUODrC+2YTC6SFjw+X2Es1psFsJxEU+Ru8hVxHBGvbkYVun1Ybva7ENOpbc
 Ym3SGYuxj
 DD5s0Th8qlh1FMtHlnfbxaJUrQAtprIE1+OZeCa/WccOcVt1W/kh1wi3U7eTH3H9mLwmaL
 YqQeM0
 bnXuVI7oR4w7nSrcD5pIH4bzTtrhgJVwwFT1cAQ5+dDteU5I1f8IntryyyuWb3nrV8c/PFQ102
 HQ
 dpbHfcV6ayTsZl65/oMdr9/yGC555Q0cm9H9x5+s7p8xyxWcvggHntnqtaHWhcDfTFMdzATz
 FErg

pS/Ilp+Okul3LbYmBbbiWWiWvtPd517g6S1f5V7IWVF+m2fM82OPocRSYq1Dde4O1KG/n
 Ltcebn
 gcTT6Gn3Wy49cE19Qq9LGDidUuBsLrtg4+lf2CgEuE0WwRq1FZeEYoZEosPtsrrdLp1e74Sr
 pr8M
 YSvSGxDGgYTbZdDrkNJWnEAhmsQs6w59FNvIM4Y+8tmsQPMs50bagcpjlScrmUpKMXp
 rSarS4XAb
 bQkbsY1hRnKwpaX+4lRxWzFT/EYghtjDLGFdFZVQNxr4wcWUNE71d5+a7D/OT/bPbl/e9
 ufYelkJ
 oSKtmwflcsJkdtSbzNQR4ag3129Xlcdihuv4V7cbyp1yAuUr652IBx10PB/3n59RqvhGFZV8/W
 Dp
 9rOY6iUBm3yQFot8VeWsElMPbjB/acEAyPtxa/Hfp37Z1lyO/1ZZktx9xbTKJlxf3tA29enyyv
 YV
 F10+I5WcjrFKZXR6Smoi5IVvdBrCYRJ0Roam7sae+6eFy0g4zE7fO9k1dbpx3qLWhguk1oh
 W643e
 h6xUTQC9hjXIPvYQqsQXS197wIHNYz2byKaKp5xg4PgOIL2pfDf+r4SmBNfhTjzTczHp8y
 wnt5Cb
 Kp7Gr5f9uuzPvg+Cn/n+GfxnhalTFQkXhULFBr9XHQwa/V5rUKwI+5gQKvdXVEZR2BcqQ
 khtLSoP
 h9XWULnNZiXRcpVKrUKgTRH/e65vmBXuqlClsVgoJsVxo8GVrBrDitHA9F75qBrzjtnPult
 796Fy
 vpyUU6NgbzkYBMB1Cw55Ho6sPjHhojEEc+H06uH8oBMLb2ikagh1IcXiAdHuZJWOcBCM
 BC5SFhbt
 /gQO0iimLE/ggDNEIxxHKxDgbTaDznPjNXEjUK09FgXILxYdxEimLVdQH+8puKfutrNV1
 OijTiO4
 woFAdBKmoO9UB+R7zbG0BAqUJpSShm1nGN2/mD20DX3Tx2bnHNZq8fT1k92fPjDobs
 m379re+eM
 m+7GtTU92zt7HyKH4tKlX3tw2eawWLeWGVpbHwx9ET/kgfN0sYFCzY04slHprqB9c/Yft
 Gi+xtR
 K/14cjbw60XAr0X0N+mKTzkcUuM+9ZO+H5EfiUfwR/gPRKIR4TISV4iDKovFzapN2nW+
 +63PGd5
 zjpGDlj3+Q6IP/IdCpsQtlkQYyg6jI6BFDiMj2FCmQXBAYvN6XKeBGvur86IVhnoVGiNoHP
 EcIFT
 y04CjxpME4x34wy0cO8JnwCmaywSikhRUlnAo3AfSIDDsqw8o34oXaGClz7WHyt4BKg3A
 FSR9bII
 ODHMN4I1aKrvH64flm+s7Hjup3Jz/XBY9tgBG60933gouN7zJncNIwktP1p38NjgNUe+9mx7
 3bRu
 NedwCBXB1LyZtV2VvX9zXrsZu197+Wt77l5Q3zZ7Wdrlqup+9Ka/TYuVIzhvjDoQUtTBfSr
 DR/cj
 Lncyq60vlx1lXdUptoOQnvLD5UTJspydi3AKox4FUZmg54N8GWfeY3jZQDwYWUKCYyY
 8I5mCxSEB
 lHp1SNCLYIFICIyR30lLxZKQUCaK2ANNkXNQoQwGAgaDXqMS1FgdtVqkQHPaIrXPSF
 mk6dUWqRVC
 fQNkKiohKi6BKBaHCEXli+QTIOJNqUMWbLRgv+WQhfAWbKGuYPN4ORbKM+UkUT4
 EF0lqqi6XpXND
 SobQmwyhQxlCTzIsK5ehZLDYUuUof6jRkmK5CCZ2shgniseLDwM/pti1DSkZJirzECYlo6q
 9gVSx
 Kz477/6hVw2OWTY6+MLVAzF+qv+MLI+d7yyTbRLgA0AicjFDb7x8R/ejAIwBVpSsHqtB
 XzNIeQUU
 jCtQwQwSKGMGCfQzgwT6KFWaswHrGZUz1pf3wK2HGw1GKDbJNqjsDj7PHSc7DaiX56
 suule6R9p7

rystmT4VSbrM5pin5IIyo2XaVGSay1TexF4w+ce5rcu27566Z3W1MhRSBtzL8bc2TgvUtk9pl
 7mC
 qlCI89tXM/tWpVRhux7orBQh8gn9G3a0Q4oHqFGo8XtJMOj2e83BoMfvBY6l9XtNQdFsIgS
 r3EaP
 4CGeJq1GflXWlIaaPaXCFRtIMacY1ikUQEY3LL++Ex+NNHQvgocB4gFQEpMCiwEggAxl
 OtgXplsv2
 YOyMDSg7J2PUaRv+3xh1lIQjn/w3kw1MufB/scpkO2x8FLhLCfCst9gV9C8O8DrpB1pW6/
 OwHp8C
 IzWxKZCasbJlZlIUSK3ktR6Nktc59Ure6DAoebPDwJksDgMDZ2QgNpdTT2xuj4bYijwaxup
 16hmr
 z6nnTIJHw5k0Hk8apBNIKL3TmXYyRa6HwWQ2+3yCABc2rVSqVFqtTmc08pxBr9do1lhR
 KIqKvF6L
 xZq22ex2l8vtJhIYch6wvB1IA1qKycRLRlfKyAt8gmf4KgPH0E+zpTlo9BNMqpBzj+MW/Z4
 0tcsC
 mls86ls8exLoBP3y12hOIZd/3W0Fjtc9cZynwg8Spybom7fGRjmm9F4g+4T8Ek7+TZ5JNJ5vp
 f9b
 1Xa2PEZ1GVBlABj/7aHE7rCI1VVyqGICEKpsohxES4CxBCyBBfNvfWza7z+/5KZeXDz/pt
 47nmh8
 /4v5N8+f+v2CjTjSMPW7Ivz0zTh0A947NYeGG6bevXmqFz891UviOJSnY8UXQMeVeLY0
 YVe41MRf
 VVE1VLWr6mnHW9a3HH92fO5Qb9ZstF1bfhtzt5W9TfMA84DmHtvTzNMazm9tt0lVPVW
 bGVbDaDSk
 it7mexWPqB9Xff9pJXVgQkyV6f7qcqrpB6ZYDA2t7Ly/TJvjJuL8U9ZLxfwe0uDluaQTqlH
 Nh6U
 RnvMarMzDqXDPmoud1aWlOJync5ZSpwqTmlUzlGSNEQ7lXuUh5RHlZxRuU5JlMmqPbG
 XYyQRS8fm
 xBbF1sW2xnbGHo2pYjfy9iH7Ljtjd0tVuArl36o0BfyuZOGTA/kKFVyz/cMm+Q1YolF+S5ag
 b8cm
 JhqpEKPaS79JVmSoYfKx4icL4ExWdq+AfQicabgfHvlnK4j+KpNYTvIvXOUsc94FIUufXF
 Hq6YQU
 Kfds28hHlrruwcWWVMPc7/8pGZ7+5Zr8fWU1nkhLXLEu4l05UPeQYmryyGPfnGzYeG/V1
 A1DSX/m
 +am5Zy7wQptoKQpPrbtNxGeG8wWViTkKtkUDeVXqKvY+KBB3Ed9AzE/5cIP+6or9DYzZ
 YBUiwlXk
 PsNDIW/go40qXsmreAfvVDgdKiXlyIKyR3lSySiVnCTVHQnzIRwKyS4RYzpUI3L0Oo1YX
 OmHag7U
 kPI4Tnh9gj7hNQj6BiOK4wajUq8SlC6vW3CF4mEhVNNQK9Qc4DCHWYFzGh2CUxSCgli
 dSAnV5T4D
 UnByLLoeTTyXIAsTdyS+l2AS3vuNzzV8r4FZ2HBHw+dG5hLjduOjDYy3w9hgNRob4gWt
 BeCPpVvM
 ttQf4/ii+Ej8ufiv4oo4NutLzNYUi204jNfjnzB7m/4V4XOBmSfcKNwjPC0ovq1/V/+ZnrkdP4g
 P
 YuZtYCGX6QWrXi80SGYxbCRGvTFhbFAIWNALCaFB0ZCIC16jHqu4sylvXTXVI5FxOJaf
 Z3TjeSBph
 Si8aTaIGMIjoHu3zGdOHYNUHMLWvfNnELu9L2Ifi5Co0DTWSjtHA36k9dGris0ngKnlbiKr
 UjdQh
 2yhToaN+eDi23dBdHqM0BhJZlqk4d2wUTgkUO4DxPLSW5KHRJ8OsriBF+4DNgbUUK60
 n6ELOIpnG
 qXp+vtV0foz7/69qKJ/qj+VfEEvA0DWGIJFGBhr5aCTb433U7wi357pEv7Ox8T24VfXXJvpj
 TkiC

VTaMZA3eXR1rj5FVaKX2et+q8qfwe8Jz/v3CT/Uf6jWYGuNgkmOL3XHGW5wqLpZFG71c
 Nqra19Yy
 edNOmX8j7HDUnmfdkbWPzav0JCY/n+71z21PcCpLoGzq7rbhNd3fmjO7gnCelIplXDMjPWI
 cd01f
 1UKmT735rZiDhEKs3VLU+MDydr0FiNUYCNu9uh5H725RhMPYDHKOvyZurVlbZvOyY
 PnNGKTfwhFU
 PDVLAeY/qJcJvFFymRMqI4eUyCRwcL1MnCUhIqwL0Zd7n0ha+r6T+5FYeGMsecT4TQ6l
 ycyZTVw4
 Img5pYEvxaWSx22uzHttKgvv82SruwI0vZ7Kw5WkolKq7KkcqlRUFjySUb1Z0uEKnaTr0Y3
 rDutY
 nati9rDs+R+WSUeXf1mmK7ws0xVeltEDA8xzRqrfyaiVedTKAmrleaifdcu2H9X5aExVvq+8B
 fRH
 ypw+VzgW8UaKw2XO0mIc8UEUdceLcUIR+OzbP9mga+2VpoWk9IyUSKOtqz2+rZGtZYq
 N1q2ule+1
 4lDx1tjN1jvE+6z3Ox/0PRh8OPSk9TvBZ0L7rN8LmdtsWPbQ0S8nw6YCXZzVAQO2mtq8xl
 jw1xXL
 Bj7QEbVA8B5HRcfkX+W3uPjWyqqZ8y//Tu+l/7OquzVZO39JjZiqj0jLmxdNPd6ZcsI5BxwD
 zDv0
 3fY1nf7EDX+66a6/XhN0P76lft7Hf++bdjcy+uhf3OT+gk8zP0Ra5EDJ/cgFZ+UyW1LcTKTUz
 TRr
 jcxMddnLNgxa0ZFDeS9/96nJ/KdO//EK/rw0nt++eHE7hLaOxUsoZH4oZyFMrl+STy1B8v+6h
 NgM
 6G0BFMIV0j1BXmtOD/Kb+KvE7fwt4jP6F3nlffpRPcEhkaCgKAY0Bq1X4wg4vQ4tmDJE5
 VXbTTav
 HYc0KGjflBp5v5j3Z4skEDfxVLkSiRggJQaj1WAwwk2gRGm2mHDAxBsVdjFgMoBR6hCN
 wVAJAp6H
 j/MSb2QcdjvobiqjHdsP4BuQiMsl0a9xVUSGiiOR3ZHDkWMRLsxH/BEp0gMluyKZiHLnFb
 BBw3z/
 KZe7exKozXlGqXLTD58mwdYoyGIHfT/I6nrgbzHVGS8RJPpfjcl26f/OSwQkqywIcRDjOFB
 gIjKz
 qcVVuMB5ztBMcTHDMPOmAvVF5Z5VU9NnXtaO/2TBH3bEg02TQ545fjtHilb95DC+4aa
 WWL2HV4XD
 2qUPKxq+fPqbpQJwCjvvM1vULf/Av5qKg5y+ACHuSuAXHWS2JMwg2GwWJI2vVmW0o
 EbUIVhgtR0c
 rql1hQTrGHnr+WA8JJRAQrIGm0NCoxg0hgSLKErFOBgSisflkRdFaRquDQnTIC1FxZaQ0C
 GKymC8
 JqDEC19jclDhG9RoFErUwTVOKym2WjSdEgiQTspRLvYFU6hzd2emc7xT0Qnyy2A0CkZij
 LpdYNK6
 qP36qOtl1yEXI7l2uojrw0AwWh6HqrhcFX85fijOSPgdCRL/EBlrhVpSG21ppj27vcHUQPOxZ
 rK7
 OdM83swkIDrezDS7ZnSOkYtGA9TgpC7BM+aN7F2A8y1AYEIULkJaFoyN8tvKbqqonVHT
 5Ndd+fde
 BbtTZkGhRKXHq9WzXEWkKFLJlvswp/Rq3T6s0ye4pA97dL7854J8Y/4DJdmzNHPeZsks+F
 Vqv8pX
 zArqQDHbYB1RKTEkPLFCZWYUGOo91Ek4X0qV0Uudvtewcdo5qtnqOdryTrSNzuDm6Lzg
 FJanh9fkP
 FDrp+xSvvNGjvC0NqsE/R0FtliGYxsCDT56FJn2+HKCcN2rzeWOhni+0A0jze7X1515YUIJZ
 KnV/5
 V7WO/3tjuYkUipS07N/s5ze6b5y9YEug556exRvixU1T3nqP2RrznxrkfzVFFx3GhNeEoCiW
 qo

88k2NfPUNfNa581f0NN3231T29akwIZmiz2L8d3XtQXS6SnNcneYficjVl6I794qhWxC15Rm
 aZqT
 Le01hKeWNtyLdO64ohL01yC+ez8KAQU92VXdEzocImqdRxfVzdQp6nUPFX2naKxIcUL5i
 YoEJa0+
 FaCRkUUWgeUtiqNKnFNi+kmRKOZviY+6dUSWYzWu5WqtRouCQavVwiEuWpCbPo76b
 zigaE5qhVDf
 AJmKSoiKSyAKhiACSueo/4aT/TccNnLYzx3iCOJ4jnDUG6MJUVdQSGqqDhU8N6GC5yZU
 8NRQmI3m
 q6HnUMGRQ6HkArE+HsJCKBMiidBQiIssAgiLqJG6RUahY0PBgWMoOHAM+c7kV40Wb
 yh10oAThnHD
 YQNjclmzz3II3tqZE/O+d6bf/PlwFWbOPd+uXEiLV+K/uH8x2Hyx7SgGpz5Ekr+EC9SkLK
 Fr/Nq
 auUs82bJ9KkbW2+5aM410eImfJ211BPyltRR8pgMUV/LdT0zF9/wGN5Az3ty27IGn8U9B5+i
 udw/
 C/68WuCLMaKg/rwPXtDWqzlM1X2pDighjlmW5cIc8zb5LfMbN2PjqtKowvwWH/UQs9EA
 oi8mGPgA
 H9tjNmwop4ia0gw5n17kZAQEIOakGCQfXt+6tuzicUhiQaS0O83Gg0a1yD9BMMzhheNHq
 avh3Mv
 SPOd1XgzKCycRvb22WxWesZWoBSjFfuth6zESknHCmRjpWRjlaprIIIzt1KKsVICslICslLas
 VLa
 4a3YSsnFKMQzcZKIDwHbBJqJF2hGhtBJvEA78QLtxAtEEy8QjbwnRiCaeBH9BoGgaHFx5
 KzbL4IT
 kXGQRuykQDWRAtVE8u6+UCriKjvn7pO9ffx57r4Y/Y70HH3I7Jgv+PtOxYYn8q/xZMb47z
 4/f97n
 5z/j8zNSL4H/jM/PSC1MI/X5GanPz/jvPj+Qx+vpI9tAbmj4zIcnjv/CyP6TZ73SedMFI15t5YEI
 FVc7eHPMPX9WcfVUcYE9bZ49Y3IX/WNT966RXX5h11K8e0Nj4Jop7co65VfYENCChDezo
 NcCHzCQq
 ac2IsTMfMl8yCv1Y7gNJLYZTjN/tpR9ufTDq81N4UupyeVINZBZZwWxlrtTtIHcw9+m/pN/
 kdzEd
 ujb9pcx83UHMj4yS8ND8St3fCUmoEmq/yW+er3tL9xfd5zqVlih0HmLVKQR2VYmOgJwmb
 nId2UFe
 ICzRY1Zn012pu1l3AJR7RsN0aDh9B9bkP8vKOy365e95PfuRGXa83qRJq9QmswmWoNObl
 +k36m/S
 36t/XP+8/jX9cTCB1frLCGMlhCGY0SO1zqolBsx0aNVjTETSazXIzJuJ2Yw1nJmWlOg7ENm
 HsMZK
 lQcElCxpDSkrqAxa1T61WnMpZq7Ulppj8h8I8NZ6JIEdnkY5RNbRvx4g4az+SvmNhEb+bBF
 jlwXu
 QtfZd4PDse5JmWmdoi63Rn5iNi8bxsNUAegGuf8JddX0842fyG+dcN5JQ98TlSfWy9SnByuY
 vtqk
 lJBWwQAPjIleLOdB/MrQKJcfyxosZz6U2H7dq7Qv/g3+DSTTILW28XqZexblmoGGaqMsdy
 W1qShN
 nBBBN5/sddTTj6RwrC8QqMYgYTmlaArYcN4B1Hr6l4Tct3heqkhkLFNEGn8mVmRn5ondS
 zHvOf38
 2ruRaylszSzQ3XXsBciPntuPgtTmcue/5ZrGmlP+oBTsCY4HFRWQIPj3SuVp4sVOv5cPBtV
 +rzEo
 Cr93u0/7vILSXYL8hDeq0JD8fUtUCqqMakFN1E0u3on9zh7nLif9PMC9gs9wlZhl6AQDuAo
 cpLv
 jgbW9lJbkf5hDsgKqn2dKjicJxvP+L/OOMDonxf0Fz7bo26t//hkSFYrRBOrc/Int0UWLXe0Ns
 Qn
 G/Ie6CW3NV3iiLAXTH1t67qA+cuPzjmhFfaGufdhoBXN/wI5qFQGZW5kc3RyZWFTlAplbm
 RvYmog

CjE5IDAgb2JqIAo8PCAKL0xlbmd0aCA0NTQgCi9GaWx0ZXIgwYAvRmxhdGVEZWNVZ
 GUgXSAKPj4g
 CnN0cmVhbQp4nG2TwY6bMBCG73kKH7fqAcIYk0gRUje95NBttWkfwMFDhLQYZliqffv6
 n6ErVWqk
 WPjD/GM+xsX58vUSh9UUP9LUXxk1/RBD4mV6pI7Nje9DNPvKhKFbt5mM3ehnU+SHr+/L
 LyuMl9pM5
 nXbFa765rOndPH3B7/nzz2Hk5YV/v06jj59M8T0FTkO8m6df52ueXx/z/MYjx9WUpm1N4H5
 XnL/5
 +cWPbIr/pcia/baPKfAy+46Tj3c2p2rfmpO1reEY/r23I6eP3Hqd61oZytJSm0EFUAloagACIAW
 y
 wgJYBRagBqgFuB7AATgFAaABaBRI6AHgoBkVwBHgKKAqATyA140dAW4ANwVStgPo
 BJAHCABBwQGA
 AViBlO0BegXI0DJfy5D3gbIEFaQ+3B4AKkh9OAaACtp8YGMEFaQ+agmFCtp8wBhBBam
 PpgGACIf
 tZSFCIfTkKhgtSHk1CoIPXhYIyggjYfslOooM2HhEIFbT4cAFSQ+qjiwoQgqaPOBUAsVVn0
 QQq30
 kvogvIuFCqs+LL6thQqrPhxeDp2nQwa5bO7Cv+2GhsSh+ejt7pFSbns5WdLx6Osh8sfhm6cZb
 Yz/
 7g8/ZequZW5kc3RyZWFTlAplbmRvYmogCjlyIDAgb2JqIAo8PCAKL0xlbmd0aCAyMTU1N
 SAKL0xl
 bmd0aDEgMjk4NTIgCi9GaWx0ZXIgwYAvRmxhdGVEZWNVZGUgXSAKPj4gCnN0cmVh
 bQp4nKy8CXxU
 ldkwfs65d+be2e/s+8ydzJ6ZZLISBiK5IQlbgkTZEmpM2EGwJGFRLEhcEVxIW+tSW8G2qN
 W2DGEEx
 gNboi9alVNpaq7ZW2IKrrWmpRV+tJvN/zpkJ4tt+3+/9/37f3JxznrMv9znPds4NwgghAxpAHG
 qf
 Nz9TddMfr5yMEJEH9dLIVy/tRfpzWwD+Lbj08i2b5H+m37wB8g8jJDy/qnfl1f/1sB9a0G5DS
 F25
 ev3WVavvSx1AKFSD0Pw1a1YuXfFXtbMOIfwu1J9EEyx/138V6vdCPLLm6k3X3j1ZHIV8E
 eJ3r9+w
 fOnN99/3LYiDQ21XL722V/0t6UdQ/m6Iy19eevVKy/TQGELBs1CmvXfDxk35CFqBkJsj+b3
 9K3vP
 Tr77exA/jZDJCmkY5kV/esQjOiceHhjvueZ8HvxQPm86Q+Mw+iz2qRahOTx0xvnRCpJFNoB
 b1Flk
 5u5EbeQxZCBQDsJq1U9QGPJzkL8N3DJwMo/yn0C52QDrmsjmgbxGVDWwG9EJVC+Ht
 KbodynCYB
 TPvqgHQOwjS4c+DmC35UAuEl0M886K4e/Yu08T9SvSIImi26Vfir9dcbJMNLRovJZ/qDtN7
 8C+tp
 +82Os85B14jnA+85f1vgaPD1kC90tGRTyY/C90TEyMexWKI/eZjNEtbC+9gnR7pN9R+Kbp
 EtzHf+
 6H+Whsd+dSTx6aaxOyQkGiGqKawK/XG1eBCpEFJ9U1UNCxothNw+tIpYsIoQNafiVYRO
 4ou/uRu+
 vAEp50Lnm1V3jM/A1UIIn2BvBAmh8Ra0WEKfbhqPSejznoq/KEuJog9g9luQgAiSUAYtghG
 8BO+U
 Q0R1F8BtKAjOx92NvAjlfw8OcCL/7vic/GeqdSg8fIX+DEcx4IdFR1u8B+1FEXQOV6Jn0Qia
 gx5G
 jagd3Y1molfQAWREW/HLgB9h1IweRVEchJ5nICdWofvRG+gK1I/+hM6gBGpFv8MwaKc
 F9SIHyubf
 A78V3ZY/BqW0qAn9CB3H6/F8GHMTmkXSOAU978mPICdK5E/lX4fYt9GfcCR/EM0C6B
 1kRnG0A30V

WdBV6KX8Z3RnoGXoEbwNv4dCqAfdztfwu/Pr0FR0BP0KtwI0F21Vva45gtZDre9iJx7Jv53/
M/ox
j9FKaOlGdBuMeAiNkHKuSbUP8D6GLkGXoqWQ+xX0BrbiSk7Jx/PT8/dD6iPoA5Iiz3MCj
COFZqNu
dCd6CFbjNXQWfYh1uBZ/Gz8Oz8/x31Svw9ha0WZ0HdCLb8PqPYJ+gI7hSlxJnMQJq+VES
bQQ8vag
/dD/IXQat+JOPIKf4farKsYb8ra8Pf9n2HmlqANGuBc9A32cxxVQBnrgSrhNfIDfpKoauwFmu
AJ9
C51GP4dx/A7W/UP0MS6F5/fkerIjvzj/aP5PMBYRBdFkdBlagjYApIyDvgNv9Vl0Ev0Df0o0U
PIV
/jnVdapz+a/B2sbQdBj7PCg9H9q+Hd7SEBqG5zWYpRnLMIvJ+FJ8OV6N9+B78DB+A79B1
CRE+shf
uBz3MvdbfpJKlZ8CLTIQAPoNo8VoDbyB62G1vwbfzRQ9h17EdhzDZTCj16D+R2QqaYbnu
+QV8jvu
Fm4P/5nq1vEz438d/zS/G/C6GfCuA1bzMViFv2MHjCGJr8Ib8R9h5IPkMGfkJC7M1XKN3A
Kuk7uN
u5t7gfsZ388/zr+pmq1aqnpcWDr+5fGf51vzN7N9pYZxxVEa1aA6wJ9VgE3rYHy98PSjbegGt
Bvd
BfjyNbQPPQ7zfhq9iH6F3kLvwxTAOARjXgu9Xw1Ydwu+C5778Q/wM/g5/CL+Pf6IPqQEng
SZRBpI
E5lBVpNb4LmbnCavkXc5H7ec28ENwPMgd5R7A8gsz+dVVfDMUt2uekT9spAQZgnLxJ9+
NjpWOtY5
9rtxNO4Z/9L4PePPjP85vyi/FcYfRWWoHEa6E0Z5P+DgfngA0w8ip5HP0W/ZmP9ABOsAo
x34TBg
QxreWgOeiWfDMxdfBs9CeBbjJfAsxcvwGnh24AF8I74J34zvxN9gz30wt/34+/goPE/g4/D8Cr
+N
38F/wR8QQGLCATZHSZxkSBZm2kRmknknknWkw3w9JJ+sgXe0CPkEDIGXuOsXJQr45Z
yfdz93I+4
Z7lXuU94wqf5DF/PL+JX8zfxr/A/51/nP1UFVS2qNaoHVC+qveoa9UL1Ver71AfU76o/E9RCu
7BM
2Ca8KuTFKFCm8C8j3yBjmbUr+CNKht/LXkb9oWL61XtxAthxdRkAbeeu4v7hWoVPsfJ+E
28m1vL
rct/l5tBPuY24EXkaVzCBVVtuFXoDpTHj5Pfk/Pkz7wdLyDv4QT/VfwE2cA1ETXtRPVL3s7
fpAJe
TX6NppDtelQ8x93E3ZR/Ck1RPYjfVj1Ifg6c7gyxordhV+8k90Kln5G15HbUwdeoPkVrYd2/r7
oW
1nsauQ2Xcq/yD6l/cWHyT3wO3wNU4xSew0fllSSLHweKO4YDaBT3oV78DaTgE/gtPIwwfp
R7BLcR
PbythdHgOmAFp7gQfpXTok46RhwdtxOzpGF3JPq08CbMFCJX6DrMIcrAHcmfuPoy7AD7
iZxoGkt
QE1+iauQC90L9P78+JOUYqteV90OePYQl0aXowrURV5GU2Bv/AmeDnQrqkLHAQdvQxX
kPrQtP4BX
AN2fC/SToGF8FcpgHVBLLJ4xtB/ALBykBWtgNvX4M9P8loPqt+G/oGizDzhpBCZ7m3MG3
AGXqAfp7
OzwrUBfEvoW+pj6i+iWah50gmMjjDwKW/xZdCTznj9C/B7jfV4GyPcSnYdQyUOY+qPGt8
VIIgedW
9DImaDuMeRrs83Z+FIDee/JXwQzXAo9qA574Ilqbvxclwbu7PH9T/nbUnX8ofwVajebnHwX
6uyU/
hCahnapOskiV4muAxxr6ITwI/+g2+Hej2LPQm0KModqG/wAPyF5qmOoF2878G2tmQvyP/K2
SH9SiB

FVoGXPQsuh9DdZtFjeCqscvJQfzM7he4FBvo8vyj+SDWlvW5NcD5X0S7RdUQHsGUEC1
 H3AXKdMX
 LIaapl1SP3VKdnLdpNqa6qrKikx5WTpVmkzEY9FIuCQkBwN+n9fjdkdNqvFLJmMBR1Oqx
 EFtYrn
 CEbplvCMHjkX68nxsfsCsWWU0HI4KCUsvSujJyZA044tlcnIPKyZ/saQCJVf9j5JKoaRyoSS
 W5HpU
 X5aWW8Jy7lRzWB7GSy7rAPjO5nCNNBtl8FwGDzLYAHAoBBXkFteaZjmHe+SW3Iwta3a3
 9DRDcwd1
 2qZw00ptWRod1OoA1AGUc4Z7D2LnNMwA4myZcpAg0QCDynnCzS05d7iZjiDHRVuWrsi
 1X9bR0uwN
 hTrL0jncDy8LIc03OmFCuCmlg3OXVTTmDdyGvpbNDt8sH0yO47hiW0rCelXxFesfSKjhy
 3tJP2
 YU5Bv80553VnXZ9HoXFLU8fOi3O93O4W11qZRnf3inn9l3WcXFuiPqdndBGjkRn9OyeA
 R3fAUvY
 Ol+GvsgtnR05fAt0KNN50DkVZrcy3EJTeq6Sc5rw9PCa3Vflwlvx7M6hy7eGhjwe5Vj+DPK0
 yLsX
 dIRDuQZvuHNps++gDe2+fOshtyK7v5hTlj4omQvLetBoKgJ6w8XAygt5DGLFKdR6+YV1x
 XRE4dmA
 Djl5uQwj6QjDnCZTb+VktHv5ZCgGv04MtXlr4H2szWmaenZLUyBdovVzqqgUlnD/iOD9h0f
 f/2LK
 0mKKOip9iChIseQCokH+BJxLpXKlpRRBhCZ4ozDGASeW5beMkxy4V5JhgCWD7XD2i7t
 nJKBxQ+F
 6Ou9fVhByyCSG7isoxCX0TLvEFlyqc4c6aE5IxM59oU0Z2Ai50L1njDgcUGfsOfE2IU/k+Sw
 tqyZ
 ksOO/0v2ykJ+6/xw62VLOuSW3T3FtW1d8IVYIX/yhbwihAsZsOA5PgorNTsMqHf5kg6aAH
 +q6lxw
 y9qeWbDVYIw5a1MH5yWdBYh4OdYU4O8VF1qmkQ49bYuPqhn+rxgWREBgloLIgTmPZ
 1bB79SGQv/L
 SsP5c7QWCz6vVpxTbkrqi/GpX4h/YXj63RwMmI+R1gVLdu/WfiFvBhCr3btNhOUZu3t2Lx3
 ODywL
 y1J49zGug+vY3dvSM/H6h/PHb/fmZtzRCZNYg6cAahM0/WAY33bZQQXfNn9JxzFQweTbF
 nQMEUya
 eqZ3HoxAXscx0JYVlkpoKk2kEZlGgL/BrhgiIivvPaYgNMByeZbA4suHmWJp4kQaRsuHSS
 FNmkgj
 kMYX0hSWRn+UUjQt6LgYB9jG6ixDBR2W/vlhqv/++84WpAf4X5/qKWlShmGMFXOwq
 FEsuoyzRjy
 +Kqe4n5PfgCichAS3h5yeFnO74amTy8CkyYXgEOlZVVvN2q536G/gyPc77i3ge2xWocS5VX
 nGg2Q
 gLnrkQmkkCDax72FcuAIUrg3D0ViVXuf5n4K+S9xL8JYabUXhwzmKmjwJ9wToEcEQVI+
 Usw5csho
 rkKNG7k7YZ1GwD8N7gy4c+B4tIF7BO0AtwfcAXA8MoEfBJcBN4+mcl9zj8M490N9E/gZc
 BvA7QHH
 owXcY5C+jvrco9xVwLqD3B2gOtshvJ37Ogu/B6EHwu9AOig43EMQp+HeYvwBCGn+N4vp
 90PcAeF9
 xfbESPdCeA9TyYPcN4rxLdxmVm9TMdzHbRwKBKXGAOTL4CrAcQDdDdDdsHR30lcM
 PgbRcz3r6SCE
 VRBeXQhhubYPhcLsHW0/5HRX7YMI3Q5Lvx1Wbjus3HbEQ9a2iTLbCmXKuG1QZhuU2Q
 ZltsGqVHAb
 ob+N8MIQ+BI4GRwH674R1p2m58AfAXeapd8M/iC4fTTGXQPrmIRR7eKuGkoEAclWH8o
 qVQ0nQNLG

0OyqQ25/1Z7PYxotRUQIjcXQRMuuZLkrD2n0NHXIIY+/EEKpdY1GbJn6CjiCbOBHwNWA
 awbHc8uH
 Ipngce5SdLWIFGNwB9nB7eB3qPiKZmx5mqtC7SICILRwZageCiSD3fW4rkfTqxnQcJJG1IR
 oFE27
 RrUBILY9HBfkMlwDN4/r5lTD+ZEhYUo1BMpM9ZTqQd0+XU43ojutU+XUI+rT6jPqc2qVr
 K5QK+p2
 dY+6Vz2gHITvU2sG1YMC6dH16gZ0nKSTdRU6RdeUwUFvK/xFm4Z5QfgS+B6wQ2C42
 GNuyFd5q4E
 1w1voxuW4kpIR+AjiEngTgN8BkIVxExQzgTITJBqglQTNUuBT3PawfWA6y3mqi/kTNSH5c
 /RHHBx
 yDVCqhHW9gz45ygEbg7EDBAzQMwApU6Tz2CEEvgyuHZwHEs7Aw6wBvyJvIpfifg84Ncs
 /x8pM5Cm0
 LvlMWRofSeJcEu9L4sEkVuobGquUEvAsFkt3uDvanejez28Ib4huSGzYz88Lz4vOS8zbzzeEG
 6IN
 iYb9fCaciWYSmfl8MByMBhPB/fyetzNtT7e90sZ3t21o29HG1cGrOzSUqqhiYUmUhkeG3J6
 qOlPj
 VHIAptMN/I5wb4PjUBD8DLgGcBvA8eQA+EHYQ0j9IaT+EM0D1w1OBTv+SMkL+MFiH
 k3fy/IoRPPJ
 F/I5mPgPhqZUZ2ucAyS3G9xecBy0/QPI/wErXYAOsPQc+GdY+rxI+X0sPQj+RB0OCNwSR
 uaWwPZb
 ghrAdYPrBadCr3CL0dvgoGXwg+B6wR0Ax3NL4FnMLSY/hOcH5AdcWjFU2oPI4QDGYT
 GLUqNE9IAD
 Bvwo8+9j/i7mNzA/ohjnGD6aY/jxHMOtcwxxAEgCtDMDvpv5IUXXaDjcaJjXaEg2GqA1Jwo
 hA7Ez
 X019/FfmX8r8tGILGT4JGf4ZMvwjZPh2yNAXMlwSovV8sHcNxmZ8HfVBfab+HObHFF3
 Q8HzQsDho
 qAsaGg34QQy9o+nMDzDfS338wWFTswlpTuAPUDO0hIfqk0HgwSzA+aH6RgjGh+pnQjA2
 VP8gBP8a
 qv968En8CWYsDX80FDkbbLTj83g2T+P/LIb/wLNBkQuCWj8bVMogfhjV4yiE3xuqv4GW/y
 7U/ybE
 v4NKRFR+IVBRabgXz2bp3y7W+9ZQehn0+sBQeiv0+k2UZr3eO5Q+C6lfH0rvguBrQ+n1EO
 wZitIB
 XjVUXxpsNOPVKEJo2eUoSuhI2oo9zoKW10M4s1C5ZShNazXTDoZx01C4EoI4HeWTOIza
 WXfBoTCb
 pB+FWRM+FGaD9qlOc43YxAZvQCUsFIcFN0Ar6sPRs8H/rj9BJ44+xKahB4N/fBLmtwiif8
 CzHx4P
 /vwYXa6h4CvpYRw9GvxZ+ETwucgwXjQUHEkPi5DxdHqY4CPBg7DIOSHL8NHggfTq4A/
 DLHd/GHLh
 Ve+tLws+EF4SvD8K8aHgDekn6TDQ1TDjRZDdmZ4WbKt/PDgiOowhW6mHzhRtcEq4P5iF
 5MnDePah
 x4OVkWE6lApo4/GjwVLoMRZmQ11Yd5zUIgFvVtLCJmGZsEi4TJgqVAtlgiz4BZ9gEy2iJB
 pFvagV
 RVEt8iIRkWgbzp9RUtTqaFMzE76apz7PYIIQnxSM/QSLBPZOzsQ1ktb503HO0opaF0zP1aV
 ah4X8
 5bnJqdac2P6ljoMY39UJsRy5DUTHBR2AoDTpFi9VOI8hjDO33Oml4bZb7uzsxK25keWodZ
 mc+2g+
 zEMLgrMqPN2FHFsaXA2WaebsjOb/4PUU/dTnPlfq4p/Ln7undX5H7jF/Z66KANl/Z2tuJIVVj
 5E+
 sqGl+RjppUFnxzF8HelruZym4+uaOy8UQyWkF4qhehrQYodQCS2GSvAhVqyNFQM0LWlp
 PlhSUij0

LJ5NCwH6PMsKrS60FYEuoK12GkAxEkAR1laEBGgxwIdCY6aLG9MjbGKNmfSINEajhQ5
 Go1AkHaVF
 DtZFocDBaB3Lfuzz7HC0MJxOFGX9RHEn6wffz8skCmUAC4pliAhlUv8vfyun//8ojA8t/e2K5
 dRg
 0BNuWQmuJ3f7ljWu3MAyWT644rdFS0KsZ9nyNTRcuJL32/DK5tyKcLN8cOny/5C9nGYv
 DTcfRMtb
 FnQcXK6sbB5aqixtCS9t7jz08I6m1i/0tetCX007/kNjO2hjTbSvh1v/Q3YrzX6Y9tVK+2qlfT2s
 PMz6ar18Om5t7zgoumdoHGy8BDRaWE/9HhDndMdUu80tjmmhlzXe4/zcNiWDR1fXh6z
 gCOZpU1
 ljXSLNidNMtITULFLNf1U0Pe4/jRYpYEyebwDJRCrpalzRf+Nm7cuIm6zZtT4G/a7GJpm2D
 Thua3
 5mZQBbY+V9+SU3qaOzF9HZuLv6YORXq6/pV6sqf+R/2e+r31B+pVmzd3QrLl6ZJXSkh3y
 YaSHSV7
 SvaWHChR04wrOo4q9XtL/l7CbQZswpvgl9LM+twMIfzR6KbNG+kPQQcbwRW6S21ONX
 U0lqDII0i
 kMzLkBVcGFw1uPngVOi/wP8luD+C+yc4Ht0E/tfBfRfcIZrCIXFILa61zbTHzhQlOi6u6lBFbd
 Xk
 YQiXriqE85cUwpZLC2F9Y5ULwqGGam2jCQRvjI6D/xK4N8H9Bdy/wKm4Kq6KNb65gLW
 dG9HGFibh
 I4hsot7G1CacAgDT5d60MZVC1FEEhzcARVP4i3iP8MbNCJYCXggEUilbqTVNtPw84Lsp
 GxV8ZyV
 QzY0cebKA2wrwmqAEIT14unZbwLVF2GCjKcJfMAO0vuLMA/wN4uwGuBnG+lvemrB2qt
 Xbrx05TWX
 b7h66Zf/t2kgPU08FAMXoLXoarQsBUXgn8NuhxtgPhS9GWAvoLgsBIY/FIYyf+21v/rcgRk
 BKTy
 Ue0DCWjuQYJpKB/DKgjK6SGk4ofJjw9zSCtQ4AhGblGtehryCeJwEmnwOnwlcqWkj+rH6i+
 VztfP
 HatHDQBLn4FXWREyh8xR8LCPR5/J3Mhnigp9imR+hL21Ofnfq0yqdSiCiTJdE8jgDMLwme
 A9pvsD
 3zV913LU9IRFJwaww4m3c1+xx+u4k9vt+DZ3j+cH3AlOo+eMPPHP4jo5VUaUzBEvGsaqI8
 SL8XE0
 zLUelb+pSvg4PEzePmJO5SQsDXONR/YY9hqIYZjLKBmbBqRvjHGV9IMDZhw0N5iJ2aPE
 cExTL7uw
 yRV0EZfeYCALXbOjK5a7UjC7VFf/3NFLpa6P+vvmjp7vG0UNY33nu86/0zD6/vlRLI2eH5V
 erKxo
 2qrIdq9aL0Q9MV3MEVV7NWVIbwdPdKvKsNZpKEPowga44Qbc14X6+7qwNRyLhUvUx
 G6zOKqrJtU5
 1XxYjsdqayyR6ionJNVNquN/HgxOe+ehnW9u3zJ6380vbQ2uGj93YvzAsd1HccNTX99TavH
 aPDrV
 uvHqV47uGn/17eHxDwb7HrUdefRfxz97GS84Meth9VawgydE8me5Me5uYHgVBwm1UCm
 OuGKxkIU
 FumssU500Kg8nP9M0ZlMAAVoOsTPKlZJAsjDCnosPlrOMpz/+DatBsC/DtMMAM4foQUt
 kePcH5CT
 +4NidEXVOtnoUvvTRp0gUmVOAwVELcq8lTrVMNpgyWYbpNH3cYYuzakUC0beSp2srE
 h5D6rZMBcL
 itgj9oqcqAXN3GWMRJ3QaqFJHRYlSb0Qa00m8OHtgS97eBrz8DTHo6VpHosoxmSRJstqmi
 DLMRjt
 B4dpEQA+OkyzKPAEzbVY4jGzJUsHY6Y+eNlpiDBvBMGwG6RT0ikzHfxbXacqK7xKLY
 73GLomyfGe
 eG88F+drdHXBKfKs4CxZ5RGt8wKueDg0LxCNh8U4bhQCYrOsi/pFkPAVqxZFo243m49Rq
 9PqdCF5

GK9WjCiHQUbuBa3jFcwDWj+IRC1uT8RiabcOWskAeCCVIqtklQEYsZ62qq09sWd3MMTt
6uuvnyvB
rhzr6oN9WS/RTSqNgqPPKB35h6Of4Q9TKYa+ktdnMvtMHh+SzF7J70MpLNUdpqIu3JUCc
dVsc1B0
dKrCtWp1uCQWqzXXxGJCbQgyKOZCLF7LLTeFHMg4cfxvZVu2tcztS/vqZuHGzobU1a3Z
JdzdY7/a
O9NnDvc9OzC9844BfH9jIRdHxx4YaJ/URoRL6wi9N7Mif5b8ijuAKvmaIo7GqxWrlSysVnQ
6spBg
F0Uv7KJoh01ejxjX0/R4yAQC/WGaB8B5pYrmmyoFMW4K8ZaUCm9V4fUqrIpmYPuXCu5
rAnh5AAei
sgf3eHo9xGPRoYaTXV2jXV0ZCCHosjizDRQpT2VSp149Jb0KEKDkKBZysCpniIl/qCFjKVas
0Uig0
47a0qvA61VdURBUtFZoDeEVgU4AEohYdpiP8QPFQ7DKZqqs8opGCYtxCg3i8uorh26nUy
UJ4EpCs
q4s66eTJrgbpbCULGTAoimtJTdqdJhZLuaLLphO6rMvWqV8Se0C6O6LSCtqENtIT3Vs9UK
02VQ9j
WdkJaPmy4WXjycjJ6K/Dr0XeSL/DvxN+J/JeWmdpSHelv1y2Pb0H7yF7uAH7gGfAO+DbVb
an3GDC
JqIFoqv2adMvlLwYFn2cw2bxOfzupDd9v+Z+7QPy18Nfj+gsKUMiPSc9r7q7+trktelbjY+GD1
S/
y73j0yfFygB6igRwEGcwwcM4NYSeKh/GHsVc6gq4n/IGPEEPJjwyrBzNdD/loJklFkskbNDxp
jgL
VAH8E1SeKa0ElgWL6rketsowN0OxOTJ0YclPLRhXgm9Hfp7iAsNczZF12vCPaZe06CJM
w3jSYo7
7nGXB4HIpfFGMd2dA3FOjlfESfw4lIEVlg+2TmyZuaP959mWGetq6hjKh3BXZzYDkt1QHg
MI1H/0
7Hm6i0bpJjpLt5Ezi6kHYqE2Eg5HDDqbwaDbaSxPGbdLJztdSAI+0dXPOEUBZmABiQ6Xy
xpDDUp1
si3oSySDsmRWC0FzyIfVSdGHZCngQ0JC5cMF7nED/DCMTNF8KnwkfWT+NMF3deJ+1Id
oonsv3kv2
cnt13zQM2gc9g95B3/0l94b3lum7OrtSuA/1p0AqVHSZcCZye/qByANpVRcVWxVzQnZnNQ
l3Fiva
LAHnpVZUbdZDrahubbYcktLMabJ6KWBpMMrUG86fG/JmWeDORobz7w5Zs+FCoIfgqD
WbdlkLbVkk
bZks0IUUFurBk07KF1jmmnExQzJTIJAP0Y6ANnFMsbujHAGXAuczMof+7DgUCKeqidKrA
Ue02p8Pp
dNhtQKvikCCEzdWUgE2qrYIFKIOdVOCvk+rIYCh2zRUzFsnB7q+9/NTmBetDdqchFPI9uK
xl8dLx
35WVPfCVSXOrzZJFzx0Yf+HrV80pm5xlls9c/p3t9we0Hjzzjrsuy7ZcOTglu7jvPqfJ6KIWhfw
/
SD3/DPLisSINi/oVC9Awv0IJIE7votxTb7dilZWBViOlNYJdgrAecZOrXQt9LSOVSemTQ4b
P4y9
QwirUcOpsdOnMqMnC1wz9da19Hzmi/TJ7dRT1uZgvv0iGN7Hu4zreSYANwCKjUK9Oqwze
bF9rQ3P
tmHWnQKoCH3rvFhFaBEV46EqxmhVMC/sSboSBkHBeBfjINarX5fkYO+Be70Kco0x053
dY0A4zzZ
VVIREIbgtXqPIQMMoFGf7cbdhDT47zff737a/rRj2P2uW9jrx7s8eJ5+nqFb32340KVSu+yuult
z
2F1uD4epZ/Puw5y9ojharoIQRNbX0kE7XrG/bf+7nbOvtHl/inTD+H0lLeuxvjzjz/mJH2RBnldF
bO1WPGDFIJEW2OgZykh9j++iQi7lo2MFptl1vmtUGgU6Aax07CzlpIloZJ3FZmcWgbMAbU
YglfX1

g3THmGa1PVzkj9UTXDNC02kSSHV4zmuvVSdC08zx8EBzeUfpV+s2ljmT/DPjv5wx9qPOa
 cnEsuXV
 3cvJmpBj7azYSqS4QfpuAfntGPBGE/ITfRGzfDa9miKIXk8xR8+kV71EWaLew1M8opkUUK
 w0kWfF
 eGdU1EIReP3hnYwyHDpVEL+AuRTxR0PzaTkPrexIMhRvY6/dppfoq4YdChE9T5FUR0Ge
 D+jlwQB9
 61Rokqg4BwIT64RyrRbLgB0/4jjqeA6/qDnpf0OjtvxZi2dpWhyL7bfgOzS7TG94haBSVcsHm
 4Bl
 7Q3i5+0veogSxLPFidFYeEpHUhZdwzweKzw+Tfl2vofv5Qf5HK/m39crkKno9+qJvinQVKD
 s/am5
 wEj7+kHrT4DW337ZkoP6wOyDQX725Us6nkL6/Ag9caMnc5MnTwYV/0nkAZ0XtEuu6j3pP
 e9FUXjl
 ncUJAcmehP2WqDFGor6YNqqOmU02GfmXR8YODUAuASCrQZKxIwPPrnPKyK0Cr0ixJn
 434H7AmVSq
 D3dhoM/mzWSz+jrtdcbrLNc6Nrs2+0Qg30DggVBrfJI56wVnh0U/qGNEsRMQRyqROkbrgL
 RNcpao
 gQJaGLmLxwg6ff26La/seOW61dt/Or923fS9Ny69fu1M7sCDOw985bOB/bf/8PpPrmlseHDbC
 +O/
 2/df5+/oobqCGRTqCsC1xdwvi5jm7GS6QqdCUexpZoqAeWFbBUUyilQA/IVhG01RTJSiVa
 RYqVRl
 3YyJUjMmStEUJURLzWic2cjKNfK0RKNarwe/zUZ7a5uo10ZFdFqobaIBAP6luGnZNi1tpi3F
 qqdY
 9VQdw0qaUCfRahB/VdHRenVMd4H4X5QgLVPHWD6hbdSZWRtm1oZZpnSxoAdVFPWg
 ZwttYKVFPeIN
 RUeLyqSYD3oTbUd2uDNVLbOGQf+RZy5YqNAymYV43sINC3cs5BYuUs+sdEXTOqE+rS
 rswUwmA3pE
 V+qUNDZCf0W6TndQ6t9BqoSclE5SfeSkIGLh8xLTmC6Q/3poHlrXCSphwcJFgqtypmRb7
 PMICi5
 paZbOMXSUnWNLNbIYo1tMI+/PFHQkTrqKFOiyXUF7sSAD1huXV1HG6X/NLGN0n9aDI
 CPWW5bW2fH
 xRoU86n6xBxMAbE5nwJFCvYUoIocoXVBx9NoRv5dIHTvogy4ivy7Rzwut8vmlz4dQKBrx
 FOd/7d
 wQ0Aee2kClfKgAc7sSzKyYBrmHx2uKQuGagEQNGVtCUDM+eUmJMB5zBnPBxOJQMV
 w5zhcLgxGZgB
 gDltvDA+t3FBYGGzmKybq2STCREJ0ZmLFtMXE03rtTpBzauEmTMqK1xObafT6ZHMkV
 CFjHvlnExA
 R6tVTHXJ8IRkckUd7q3L1ZE6muaYu7gx0tYWnNs+lwzMHZxL0FxpLpkLhOuoZVEzt6ejc5
 gsORR6
 eIdrGK+4JZW69HzqgrZ2nrKbs4Wg/tKWlc3vgNpGfw3sb+4oVeGKUmcWFTU4+mP0yFYS
 0ZsM0XAs
 ogcR0mgqMUZ9mGlyzOrQj6gYSMUkYEEgATmcBd9hN4O85Ki2h2qZyWESKHdUallgp
 MpfBR9Xmy
 oBY+Ty0k0tR4tBq3r7CUraletM2++q7W2X0hh0E76ZLxeuvUkFPLe+OLate1EWKfMmO8si
 2rU4XS
 8ybVzi9zV7aOT22o8miEgMcXN2Fbiry/whQrXdF9bWvrwinbxrcskh3BSMQphc3teHdvuVI7
 S5ca
 b72yHBIjEfPlkFap+NN14/Ylk7yRiHfqQnzlvemQ2xShX+kQ1AZ8cz6XQZbk57YXqVICdNjs
 SG+C
 zYyMLDAy3mm0VygItIIEvwj0euy+ZHDVhuUonzHbDYDhHTeqFlAgiQQgWbT2hQ4QssJ
 wKBeYzUA

eOkJSif4Sh1ol6MpulNBo2ObAhRMxnjfSo1kTo18znb99gG0D+UQR4egUPMkHUSHr5F2ok
ToNpME
WcgJHBJ6hAFhn8ALX+O/ww/xHO1KgKlR4hnpjvNoWDMA8KQizhZ1KZwuB0UGTjMYCu
2Yy2khB8WSS
WhfowqkqNIYYKbNvuc3dri53D+qxvcap3LIv6wTnUHZZIB2VtmIOjcyYNo0eSiRqWPL80vI
ar9qt
6bBe6eh2LnF9ySngTqMWNKJeZZ+t3kXuUO/U75Zu8X+XPO46Yn2VvGF6UzpP/sLZLT1C
j9gLS9ul
eUZ4wXROEHksGG4mnOZ4/gxS588ocyZpZpCZmnnBBWSBZhnPj7usu9z3W7+n+Z52WD
yiyWl/Qv5M
zujPa23iaQEj4bRA+mhI124QFi0HeLydt6EKH5001Qradbd9h30viIy83e79JY/hDZ4esmX5gk4
D
wevKLEuWrvEVXkzfiPBT0ZHwZk0OvMGxw7HHwTnO22wDIq4QB0VSle4R3xY5SSwYr
3LiGVEtPma0
82gXxSsurVgqjIqx3cgho2SUjdw5IzbSkWhgLY0XZJdUX3//3LE+ppV2QTDa1ZeSqCbaT1Eq
1Q90
leqqG+ygoKaoqHqeSjogiuluNHkylUebOg6rESakr5NKGQWxu7+JHs8J0JsunNUrZVkdOGq
dG0pk
hUKgpoG3EPMW8ooxbSGmLcQ0LKYYNVm75M66ZXPWIDN9jZ0GfP4DQcWqdhbttCCr
kNoaEFec9mgo
xgiI+k28YsXOJbeUBe0v3bf/r/84+s3nx3biR1WSe/mk+TeRqT/dtGn5tbZdv8f4jb9i4eXHpnRE
Jis3gKxigE3+BMgqCXxkYneXMpuROug0xxlHj7uCuCiyXMzhgxPiRXBCvADgb4qZ8vggE
0CCTDUL
XrCIBrHEuRzuE9wfkAvFqH1zXnxDfEeciycEI54Dbn6KcvJR4OPUxDxBx6kKNCKdfJ4y7Ist
m2Ha
XAzqbtDs0BANNOBSw0jZfjUzTk3HSI2rajqlvzBmS4EnaF4wWJr8XMeC9lGm4dSpLuCqtG
+6aTcA
mzJVkSqTQhTTjbyglOLuUhwEVhlnfPHWcDwuN8YC8Wak1ZWabbKEedeABmuyEqhJnRx
QGOB83Wqs
qLG6PFiKS5E5EgwGZTwgD8oEyRJwwhH5tKySe5IPf/mLlsf+s339wL2ootQ/2mUu8Kwsk7
YHXF/
H1Pa7ZQLMV19grsUudEEMyryF9y2cWvdrJpIeLHDYi+rsBqmTtxtPzShxa1WGsCcY12I7d+
BnP2tK
xye12JJXjs9uiwM7iDgY31i+7xIfYwgYVQO+XEu/v0PPKBtCTCcPMak2pCRq3aGl5hWTxK
CXhEpc
Qa8lVOIOenEorAl6zaGwxQzKpehyM2nRLVKMcPO0qrtE0ysOwBbn8nT7t8OW57rFEfG0yI
kM40QP
LSZSKYrWBWBc8dOuxaVyb2ggdCbEVYTaqZ0hbiR0OkSW/hbWEIYS9j/8uvromo4BVM8
WtMDwqR8t
8mzGhYE5h2tDdrqGjKPDZiPXjp2oWBBzGbTBdEUFaamcH3MbtHKqIhqNVsrXcetXh9wW
F4M/u5vB
yFQF5CmMkGorrJEDhTCndOq8Ov+t0jekX0mqLdIW207pPuv99he9L/pflUSX2WLzBzjBjnd
6bguQ
hKgOelGoRAh6DaGwM+QOJoxGA3EnHA4k+urnWTCySBbZUmFRLCrLcP53R9nJwewwJ
SLTGmphT8hh
3BveFz4T5slhp5oul5PprU7Gop0wPWYUUbNENVtY9YMIS4snNrBIhaWaK1GV7yN2hDNh
/B41Z7NF
YcnnCZjsUtQWC5h8i7DHDp7fHFyEvVb3oonDGmoA78P9XX3Vn68yXWOZt9glQR2KAzl
DZglRC1P1
oojDF59bTRK4Al/yzA+eGd/8mx2L3sVV4z87t2RjtC60kVu/Q05Hd4//+Jfjf/rxq8t8eAZ2Yjdu

9qMI/VYzLz+LB0FO0SEnmn6Qc9N7MH7D6kmD7n1uolaQQFVbk2LnFE3NoH2fndifxFEgQ
 7/AiJ3H
 dZ0fZYyBKqcYJL2JPQUqofUiGIKfKxvLwaUzjdNpyOVYFNyYdXoBmk5PBrfl3+V2q9Yg
 N4qhanyd
 crwTY011sLo0vqH6upIB3YCeWotvjA7Edld/37Xf80j0kP6w54nYifhz2ud0vzY4BKTFagPxa
 OIO
 g9MTNUSNrfgOfJPhFuP3kXEqmoJbUSuenejGX4pfUX0VugqvJatjV8XXVH8Fb4tvSW+r3s
 PvUQ0I
 A+KN5hste2x7HPfx94h3m++xPOB4OPbD+A+rh/mj4nu6v+jfM74Xf68qKRg08SkoiydXqZp
 FpPfE
 eeZJThDV1UNqVRkNrAZ/owabkAYrzFUALOOfVioRqlVqi1PbU7qs9U8vXhp+EDA5PQ6X
 YpGgrnlpz
 0Mk53TXH8d/we6hA6ebS87+uvo9Gz54vLDyTzKmNHvCrKpUJIJgdvAgcThVehoKCfxlO20
 qXoXJL
 xTJcwsvLcEAE+UoW4YyZvAusgwwU29f6InhThWsFjSdyg4Lpg1IS06iVo0mcHT4bRSrd
 9R1Prx
 roe6fvr9772w/vFctu3Ng8+sX7QVV16rbFmlaqC2ctL89juvXn9jbCZ5/OZ9i25+eqi/7cF1t126
 qm/Py1uXblxy8LX12+etvWbLvJo1mfE/z9jfc8MD1y2elb0KaOcywAlKF0I4oDR9j8eWzsDaw
 A7V
 DvUO/x38nX6hltSGQMOVF4fW+baotvp2kt2e3b7vco9q6H42oTA2SWaL1e5wijYD4bhh7FP
 Mcsgm
 c7wc8nh9wAB5FaTuPSTLIetx/AlycVYF9j3+AyJ/CIUQj47DO/HimUeo4AsCOP5Q0QLNU
 MI9YRJ2
 DONPjkpkXwiHaCOKRlaktRKR3CXH8TeKr+1s11xQObuo+Q5eXdfoWVQw5TWMUnF3F
 Juz9C3uFMtT
 qu3AUmmkyK0N/bif9Ms34hvJjbIaWBfss76iaUa3jt9gWRHoVfX6VV2duAsLIYEvmGWE4s
 ZjqlbB
 Bg20GnNbLx1f04k1D9yy+ObLNm69bkN52BPPtM7dfPDB269+EvOqtseOxh+8bXjd0YF43f
 wqX0oK
 1Rzc8ZVfTSkTiInqNTJs0mOwP7UgAf1aSTgMgLAtBsXEKSZcqsd2ARM1SNsqNeb1OgPi9
 QZeDStJ
 l9wiiDZBEEWOB1oqqABG07gbyE10sGiGVRYrRHValHF6/X8CTwbaIEIO0Sn0Zg4vJc7w
 BFY3P9W
 XLgBMMKD6GnLPtMZE2dSKwIW3Mbj+C6MC1sEBFa6yPVzz1PZ9R2J3hVoyGYKh5DS
 WH89rDaTC3aW
 p3hYbgqaTKbKCTfhYF8Y3vYHDAHanE1BJg7dnT/2LNk85f3j0fw+bvGv4lXDXA3fnYHe
 WisGzYy
 IvIPxudwx0EWjKMskSlKg8mpTBqs0pbSQKumXEPsrqRzCWtTCi0yg5mtpk4x6aWHCYX
 ylSRMjCT
 D5dIWxi2jNxsK1zuV3IUeOkTrUQp4YeDVLowTbCIAO+laI2ndFMRhotkIRMQQgcGZGe
 BwEwUzhL
 LAqBx1BV/rMjVMKr0IKrIYuCWu3UKTA6JghamV3GKhdkVDUd1N8ULzPjyFAqoTbGEX
 YbYTA6Oho6
 AEqLGqSCHlgvaHiniypeioqG12unUnUtK82WviTtMvO3pvHUdMPU1vSX0leZr0pvFLeat6Z
 vFvcL
 74mfaAwVUzuqO2vW1/DKVJwRuUTSYpWTAfetJVYqS4ZRPDQvHkDNxJJKcHy5NAnTk
 RCBjsntMIZV
 BrWDWtKjHdAe0HLav8rESg+4vbLcHuoNkYEQRiEplAtR0UcV6pnybOuE6b1wgt1P+Tc9d
 B/tBzFy
 QoDkjBK1jBSuX2RqBYMYrYnpYxXRWqFKxhkDeNWaSTKu1JXL/+P6RT8lrKCRcNFq+y
 R2FmS3CYyo

xidMG9WoukkXZE9VQSSIIkDRBEKwJzZzz7zdV/Td1vvYnEmJKme2dVx218WtdikccEVxj
 cZ49fwV
 0y67QumoyES4bP9rW5euv/nV0Qd22E1l4+9dWR2IRrFDV7mCW9ZZ4TLuGH9sQ3hKx6Wr
 jv2i71KX
 he7v2flRbhfgchW6hJtdxGW5gUmqDQyj7V5YYJHa9aNMMooifTWze1LNpZqhNMR/x8yl1
 RST7RSn
 q1nZ6qzAQqGsnApesgaqlFejAJ9MV9ToFQ09QVD8fuqb6WkVtZ8GaCEgCTtc2MVSXayES
 4oGhPo0
 jzKAddTGUVBJUqcyYxT/Xk2dAvvwHDDADniL2i5fLZxVKRt0vt3VxDJ/ErbIwexAw6Oao
 1rOkrJs
 R9urb0W3626vVfstjilSw0ADr/G1qdrULXJLSdsUpWGXX9QaBRmVzMat2tm62bWtdU1TZI
 +yWLda
 d4vmZu3NOtMCx00OEmzobiA9YjWqqS9PltWcwF6kp/b+o5qsPqGj55QjimdkraRv1xMFvB
 49J7Ng
 i57X17uoyp/UZee5ul0bXFzGtcNFXNcHJUxnXFGv1BOYdm/ZQBkpq4V1o6fSZL5XPIKGy3
 qiqNqg
 19fUVFNqjdr9Ql66RtFaY/GLIoGowPRwSivRM9FyUAURyVaKHqCNCEB2UGvDmbtdJ
 MEvJlspaAY
 s7LQLgwInCTgcwJuh23eNK3pgsZFTzjOj6akMWpKTNWPPpQpHVvWwi4Dinh872yWN9sH
 2GevqS5mz
 XcwQkCnQnyFOj4GX0SshBbURttPM2qm+sMpaN3nSZAK8QCsSdahELiHqWl1WRma/1Yc
 sVIPQ4MMl
 4amqrA9NfntkXFujs/gkHzaWgDdFXe+j8gwMANyeeNQKWVpaSuWaftyH+mAX0mProQ
 YLpgyzYJM4
 XAkzBYw8MySx4KgxWyfD3KkJrk+DM4pOl3XJuqwTnI9iu0eX1cKrrEvQUAuhFkINhJp/O
 zSmZ8TR
 CX4M27uOCU+gLtltF3i0s2APLez2OjtNj5uhTkG2IjPvjEy6pPsrgTL7y+e3xCNkUwsmstn
 v
 e7S
 qT6L1mmS9Pb63lWVU/C96XnNiya33Xy12X3jVU2VzdcuiuxaVVKSnIJeVVO2aDAZnJ66Z
 fzFm6ba
 BEP95Huav4676t3pnuysblRbDVxVD7z9v2HvV5ML5y+17Pylgqk+lcw3iiZHmB5klNNY2B9
 Jioyd
 FTVOZuMQHRFazcG0Jlee0gTHhNXDMUEcHJSjxGhxB/Kzyn7WkJ814U+yU+okM4UkC0
 e+DDjHWklo
 2E6S9ERGS2skkY9EKhhXrGRcsbLK8GPgmxK4EnBRmhMxRaoET5qwExDGKt9/XwLO+
 W92k4tOPaj5
 ZMKG8vlhx5UZB907Fex8u5LBbACVhfZNEZHxUZHxUZGddYgOQpMcLMnBzrQdjtoa5G
 cl/SzBzzL9
 bKI0NTlxyJGkRyC0RDJZW3PRIfdIEaYjRZkMTGvCEkNZj1eZUquU1oq19NSiorYdNI3e2s
 FaVRmP
 FQYPQCxXq87Vnq4luVrcAwkjtZxfdCQDpmHOpJhLkslAZE6JmAwY54T9yUB4mDMq5eH
 KeGljRaCy
 2YfCVdVsxpFw2GQyap2OiDAo4pyITWKvuFd8ReRFeovMm6z2R0qDyfZkT7I3yQ8kB5O5
 JleSUplk
 mQHS5qhJ9tQ8vIny4VTxBHysEKLCDbIGegxx4QpZUaO2uNycmo+6OacPq9QulWfi8IHe
 WumDP9SF
 +6khEP/7sUPR0AO78eLEz20/1bj1oa+1rpedRl3l9PGpVqVayzfOvWaLzkiPD2wzKk3BidOD0
 Wdb
 F9VvG9+6OOj2RSLxmGkevmZ7343j/i6H3xuJzFyBF+yf5aHGINhn4zO489zdzqOqCtGjTaFKl
 HLo2

juN+i9rG7pvZAJWpmlhlopiBhIKFgFQOrADwI4nPDaGo09T48DZlTXUzw+9y0H9CkkN9mJ
 tdV4Spk
 USN1+Drah8lmq0aopr4bA7CY9fJBpDduk4zcQ2QJye1Luh4CnnzHyN3/hzy5M8d1ErF47D
 HNZJF
 12BMfSNJrDXlJhWTblLdoiYajcoiukWPJmXzxDQRS8QTS03Gkyy13pmWNZo12rXuVZ7l3j
 Xpa8Wt
 2q3uazybvNemd2l3ue9D92nu9dyTOoFO1/xJHdZoxFQqXVqqxSIJYKvbFrCidFUAWbTmgC
 Umym6P
 p6JUa4MC6VQqohFtsHJQpdSj4bViGkK3ViOKYavFAuqAOS6sxDDaeCac9ZtqnE6PexiLine
 PFr+tt
 PUfFw17t30E83N6gmafp1nCa7eIwNir+1GsmGZvkTKR93SncSbdkCZpd3XN9+kRGj0+6+q
 fe7ar
 7+zy+S5q+x4rHpvNHTubKiDrxCUqtqPRa1k7jeWuVFHZcCFpFEsj/+4Lklgv1lNLCu5LAeIC
 2lqp
 bY3eLbJamRwYo9Y2qt8JWH0R/6DIXIepjheL6/Hj9rKy0NunzIJYksKl0YRL4x6/fdKBy6a21
 VWE
 sglTYGakcfwJU8gtOau5u6Nxf7xlvAr/K5mwaHSGaJR3hYwNn335ltua06XVDtO0zr3kULA8r
 Jf0
 UTfg7zSE+ByzZf5DmbIELyFL/EsC6/A6ss6/LiBmQg2heaH7VPd6H1U97BUI9gccQa8UKtE
 EvaZQ
 WHCFUZBIJjE0TEYUqwankOI0NlhM0Fw7OgC69jBJKB5Rw2xwGmZu0zCpUVPidARTAf
 ZGaQ0UkALd
 gX0BPnCJJAJ/37hnLzIdaD1Q/KKLkZNUue76JcJARBwdLW0gSGdqQZoQuqsVM+sdufZ/T
 ak6GrB
 TWS9w8yeY0BKsPQivXGNQe2m16fpSwhTilFdfcESSjm6Wghb+YdMMZ01uHrB097YvMz
 YMxWLIo7v
 didq5ggxSdU2/uyCyJS6T89vD5ZGozVyP683WtdfgaehVCms64z8WW4O8N8Q/nBI5PGE9E
 08XzA9
 srVQO6ImjdBDFZkQOwWEtQr5QV5mp4AAvHSUsk9/JQcCMj0E7Go4Wbx0c5JSBwuzfG4
 sLatBYaqR
 OQ2LVcRnXcDPV81XLxA6vB0+YbVqi2oADYQOe5+TT8tn0J9Umjo8Ey9yLfR1h3tcPb4tr
 n7fbstd
 1kHzoOth/D1yIHwIP4N/IvzE/Z541vcX+Tx2qckcy2LL7cHb5YHwubBglvGT+TNIBhcEcQv5
 ERVf
 K6QQ7gkNhAhVyGRmkO4NDYb2FZWzM6FzIUNolf9tEzb9xBHVCDC914dsWRooky1Zm
 KQu9NOgHs/T
 79ETfUZip5g9qBcNohwaQWeQhiYQ9NhGz00e0u7Bez3YM4z1iuWcGmiEpC58mq1SN5U0
 HSNfLRgR
 6N37rv6+sb6us31UFYRVbBgd7WOC71lLkboxq5/uX+zf6ua/7QZrt6wS6CRQST2YGGtzP7j6
 Celkk
 F72ReO6oNauSpCymCCChRuXLkoJQtmt+AP/Xh4gkVmjiZAEQrKH5MDATJkJsTff2mb72L8
 eGdP6pM
 Tw2YdeHwtBWXXPbQrmWX1tXgK478F1a//To27pkby8TsW4KBOcse+t6nTeVb4zF6ZpU/q
 zoMfCfN
 nSrg1tFYKGA2kjQVmoXIe3OJfCIaVJvUIKs0gHwEeu/YafiNXMRTjqFY/l2lmQonLh8TcZjv
 YqqE
 WPBdMQ2PEqzxrWmcRptB1dBtTuCErtB6Ol0WCpWXXWA/8Otq6GL8h3Egas1k8hdgKlM
 VfQ21jrgs
 yeZoXC7vLl+r6S1/L/pe4uPoxwk9LTBkrWXlXvAGa0Ll5ckVk/xud9Ablsp5bcwfS8eysYXOR
 5yP

uB6JibpoXaQuPg+14bnCbHFmZEE8bmJu8jZhQBow3xm9LXFbcqD8m9LdtHD0hHQseizxd
PkL0RcS
b0TfSJwuDyIVDy+Ed2qiQlyTUCdrnU1Sk7lddbwmwyHV5cpduj3Sba5d7V/i26G2xgXLnTs2tz
p0x
zqDpxNdI15h54G/wVqNRLRaAv0lOc0CSw6GAjJLpADJpjQFT0B0IBIfztx4SE3FAku2K4op
GZFEQ
NUIkmbAlkwnAimi8QtTYRFHjsrv9og2atNqo+FIpMLltrlc7mQs7HY56b980sJ7OIHFzIK4
PcP
BbHJTGMsMuL3Fa3JJEEnBoCwjQhMxSkMR2BGuE/gqFEUiflgxJRQYbCSS0MmfVZq8T
A+eHgErUyG
KRe1K95Muxvvc+On3K+433Zz7q9FMq5h7H1CNkVBX8VRei6v09dET2AJxZAdVEu9os10
x7ASG4iR
2DB+/7BmezWjHgCdWcReRSujBB5InEuQBCVrUDWxT2Bmm/YkHkhiKi/KSQVEx5Hk6aS
Q7Cm7cGny
IN5ocXtGx86eH+3qc533jLrppzR9HkiAbNdZz6h0nrrRojjpYQbYenq9ckJxLcCjhTvWO1UXc
W6R
AqoJYCillfo/svL/zNapRFoQSFOgfQJxOBKTbPoGein5EIRWqoT6s86LAhsNzg05s1Ea2Fnso
D17
4SpfJxMR1AUJgbF/Kh8IFySGYhyHORzGgHkGPFABmp98rsYVd9Tjw7MCNvH0M7Z4Foc
WJ8d/lvzT
+IfR8Tf9k+tBLOADvmB67B/4hzvrnUYuGuWcUthmH/sAfzpJtgZINGpY+9lfeyxJzgyu9qA
KtuA
xpaAbJBiskEaX3sMlcOe/PqU2kz5Ztem7ybfkRv+Td8wlbXE5Hjid94f+N7M6J2x6XyRCwbz
can
JirKl8TXxnvLB8p1zyPs8SV9rb5fu3/jVT2awC9F3nC+GXkj/nrrixG1Twn7E6lx6BVDJTjoFUJ
h
U9BrD4WRX06X+hMN4XlhEg4L9tKEw2EnsHcsyCN5KjyKp9ej8swuL577oXKslOfKyd7yk
fLT5Vx5
GjOpAzNOixmnxSUmY0HxZYIGJl0YHywrH8bXHAAR8z96l+p/nv91zaUCR4wre8/LAnqBk
x1KU5LX
NQoitiU7ocH4IkmmzxVNxJLOWDWO+MCLu0uredQbrr7oTHD2gq2KFCgJBcNT+ZKAPB
WF5CDCFG1T
KFU4tumnt63oKdz/EE6KB4hVjuKBXHzWjplLvh7vtjcmrET1YuiNm98bjX+x9FfDP7mhcr+
xtrL
/WvunXXzgup28pXxzQPBdDQ6ObiJW0+h1qHrHj5tnKnVPjTQcW+rNRGCd1+PEBFUdyEd
KiFF2+Ex
FIGV9rPTVgNT7w0hpriE2Nc0IauL01Dlnsl69GsaJujR20xM7hvO/+woLa0xuKj9gJYC4A+sl
IsW
p6UAel19AOaSKSNzzgttCO0IcaGSDUDRetRYrTC5CV75E+yCRonaijINr6VSXacoxyktfgV
W8O19
iRS714gvqPoG2UK5Woj5tJ3Dra1FoLGxACjuujr1QoWKE/vUhHaKkBwqEax0eh8pPlpTo4m
EDUy9
NxCqyBuY2k9nVtDwXRNfhNEUdp/R5YqEL1LvC4Z0xG4wniqY05iW71XcgxHcE+mNDE
b2Rc5FVHKk
PUIU6kUoAa6qqmHh5CmFsKyIElajLFTK3Z4aVzJgnVNiSAYsc8KhuLtRDoSa9W69dRCm
kkWoRC9Y
LdpBekmDo+y2qZZj31Y01HLr9HqD2xBxKamsi1k2J02pGXTdhfucfW6Bl37XOdcKtdQeOi
7RUKd
SrEvWWDTjBauaALuyV70RUNRthAdQdCSS8aX3Sk/J/vAOJk6dSppaX1U693VzaONzWV
e9m9voQR

21R30Yz60tKp46ExeVEWIHNP/UK89Btpmd7V09cA3jbnz/IqwNsgKiOtRak7lmF3NJJqFxO3
 xYLo
 zcRwJPsdWqZj6NhRjZndy2VWLtIVPMn5WGHUQma4Lvvo+Y2fGoAh5g9aKJpKVkVjJAut
 NhQFkTad
 5pglm57iZMAVbVH0m0SJ2aIuOrtRLrdALSTrOI5W9fX6seLv8RN/UAFn6BwMrRzsIg+Mk
 H1jIbNv
 E2VSuGCbKU+yMmxygL/qTHnxjKaIbCOAbdRA9lZX16mGUfpR2lv0Ot4xlAGsmTmzJkPf
 8/RUeU1P
 Zhu/TbWbH8gcyIxxBCUzkCEo4yi1pxaqFooLUvcIwiwBy5k67UztIu19/COl+zLCSOZcioDM
 IYfo
 rTpd/ozSUi/Pk6+UV2nXy9fJe9Fe+THhmPB8qS4mWuP6RkvA2mz3xx2NvoC/OQjVdHzazl
 YtCLJl
 OsjpgkgX0rPPFy32HseA44CDCzoGHcTx12S7ml0NLK9h+39mrpqpvGLH8c7G3NGx/i76nSL
 8ABHp
 5baGC0c9xStDjEJ7YilejEdjYIJGKR68hBCVcakqfeGIh97ZoNYRRoZxf18XZczRooJuAQW9
 9oJN
 6aKvGs3l5IJ0T37SNDDnnjMf/9fWeSbZ5UkZsLnMFHJ4y3Tj58rV9cszHS1fyq3/0uoZl3z63H
 N4
 5tzvf3uWRwr3fvrWQ+z7xhfx68292XlrXnjp16eTiOQ/pd9tAE47UAT/ooDTBwMqiq4SRUm
 VTY9c
 DIld+uH8O4yy6umhAfuWY+IkUn/hJFKvdzkrTzRWirpmm6KBYjY78kY1ulBnwZrKcPcLB
 4/F74Mm
 0DYGTXDQBNSjdWjdgEoViyIXw0YXI410OB8zyycAf2M3zvT6WPSLF0ZPFfs7ZS5+m7h
 ViuHvqY+q
 jwh/CfKqGNVo5dhmbgt/K7eTf5h7XBRmCniKaIsbGq0BW7PLqUe814FA77wwksqgalBFelQ
 DqgMq
 TvVXvQMhV0Svlwzthl7DoIEfAC9n4JBBMsiGCgBHDKcNgoFiVX2toSf6bPHm5IWbaBNni
 KP01iSg
 1efolHDLnE6IyVxAxh6ty4fcLp3eJ0IsyIdk7NZ5fciv9jLkYscYxbvUgFld1CrUXzRmFo4PY/H
 P
 7ZVm8wRnp3iFp97yzTt/8Z3bH2/fvwhwyldqxNay6quzX/r2t1fU1ibIR8f+8fPz3xiYMoU78i2
 G
 TGOJsd9WVb/wdO4pr439B3mkyqnWIR8KEleRLlpwMEACfuQLwBiDOOAjth8XDqeRAE5
 LGbBIfAHO
 JPocfhTsxQOYYCyaiAiMiwo/p06fymToi5NGR//2Ps4UftL2nSdPSuDo6/SKRpPJIGkDmmB7
 SG03
 WSWP2eP1+lx+NbV2DEVraXCooqOGhUCIWHKykCzHCsmeQCHZyZKH7CxQ7pWsNQa
 TDhrPmuaYZkiz
 A/NCnabF0kJbR+Aq02ppTWCLNMDvNO427ZR2WnYFbgs+YHpAut/8QOCY6Zj0lOdY4G
 XTS9IL/pcC
 vzG9Lv3V9K70buAT08fSJ/5PAmmNqdVLggFMFwn5AwGfxqj1ahw+p9chAp6JdrPNa782YJ
 LoR5a+
 ErNkM/eaMf0HvcZh8qJiJgEbIYGgfz9ChYUbxkcUvSiZOLvDAcqe6BvG/1I0JqhD9hsV8zCp
 ODQv
 gAPD5H3FKNN7veeMnPERedluxmvdnrGuURfVc7omlJ4GeleXnnDTz0XpXZOdXVSZ2ana
 fvL/rMvs
 lLafrBfq4Y9dPrlwtIX7uzpxiBEwJzBl9o1ZNXyUItRaqSPc98f+eUXJ1GXjCxe6q6fht/6/tq4F
 qI3rXJ9zVlq90Gr1QLuLXiukFXoAWkDCFPfhjTHBwgT8xEahEJKpnaQpj9puSusBJ3ETx+
 mF69Zx
 nOQCt711m0fHD2xHJtOYdtK0btJrz20n0zRpTXtJxnkwN9NxnTg2pOesALszlx3tOfvSaP/zn//
 8

j+//CcA/pjo3zX+4IRX++gefWdfebi3xxXWSZOHI72vuvvHMExu0kqQp95d2QTMKzr9HYtK
ZL69Q
r2h3Yn4MgqlT9+hVZJVWW0gas7koBy2KzVAEQkoIKaHu0ERoJqQJWclppgv0giEwAiaAF
gjSFPQu
YUQ61QoL/dda5m5IVq2HwUCwOIhoBCmIaJ3kdnlcXhdF20MWyRTiBU5AtF9j7QE+uqgH
Ohjccxbg
XhCKPdBFYFU2trAHCEa8W0ZVRdVPNLrPnrCtUH21VgdSnTsr2LzftnoRR0ki/JmndnV0P/
+d5574
fc8v9z30+tpUf/Uub7kcTEVqGpJNCTR2BbZuXD3+q4XjnyycPfz+Lz5buHLY8D0DL8PUlee+
IftX
bVp4/roX02wbptlJTDMEhMFNJbrbsMf4TeYRwzvSh3hVouBealAz6NzPadL6MK2lAkJYoc
mxSw/1
ObjmrBjClqIFM9/3JnmGJeSetJghmIIKwVIpNlMRiCpRpES7oxPRmagmKuTxUfhSvjKAbFfs
o/YJ
u84uRG4R/WZny/zsItWvpgnd0yrYf25gyVm+mKJsol00UqFOeFRK3ZLB5sHyBtFWyRySDI
Ee6GNd
PcDP4F7QGOqBbpvYglVUsWdRYqpkV+sIYBWYkKF0t6RlSciasAWrq6DKtMvCkqaefuwn
P3owOPrv
B9/a8Z23Dt7z2iFo+fzB+bdsdzZWrWs/8MTeULt2p2Ru/eGvD9w7c+LFp168exJ6zsKmhW3z
DY9v
6v5rffy/nmnpC9HrI8V0vpxFtXjtpcBGxQC0b/p2VAMlC1SJYkYUnuAURSp8mUAO+hSHSM
lUN9VH
TVAzFE29Cn+G3tTkYO/Jy2QGz11VJ25dmvgi9qoRSIjNeFS7UNgGP9b+2xdbtS/iYSGeGw
Col/B4
e+FO5REdb0pxvHtVglfwTiA7i9fpjOjSunW6F3S0ImY1Hfos18E/qN9l3WV73vQzfFHry6aX
mQva
C9xv+He4d/gZ8brmOldYCD0aQesqFJwC5+F1Bs7EmzwJ4U7hADci6ngBla5IKBBBoMyUgLc
2rmBa7
xpzDP8NgUBwFdQTYnaOqlAJWWzQiwHHhuICEKaoKUJi7ICrwYi5TzID+W6u9y95rH7Jr
7DmoU+yK
CvMSFXFYpLrFCRGJwqvWQqapGSqKowv1oiE0gs6ji+gy+j+kR4LvNgRYZ8tsOj+/O1vUBF
qi3pGi
FHxz/Xkee2XEAM8bLhoQ8dvGZgnzYc1CBYsjdpEN9wrfEwgbMunHWSwfGWIUEhRPJ+
EwEIOUPwIA
nn10geolHtMhnR+bJyuol7puzsB7oDj29fvGQ5Jw8bkf/1nOHLteC3u+1t5YBLULNyRYD595
Yd+x
3f3n3vjD6l4dPzyz8OlKtoIUZPoUjyeNx9MJjigOhe/GZtQMrwG8wqM94LsAMavt8H64Ghjg
BCjG
tCR9Pe4HAICfAwu8HzjxGQD/rjAQq3IGBLUGfQGiMLd8hm9fp9gYxqJYk7JlyDJqmbBoL
AI3hYJw
dpGAxJMxN8vmod8qZZYzvypkdWLZ86oskfW1aNkY+xRm/Pb03Quoe6XTqJOKpHrNr//zx
uMDK4m/
CHkqBtF7P4iSaYLfcROWUVvxO1bC9eeA8cuZUwUpA1mi0wWp1Ya1xkZTc7HmogFGIisj
SqI7cTEx
k/jMqAMJuNowFBgsfzF4LjhVfqH8cuCy9G75R8UfSgXr9JEcfGoyHGZBDs1OXpKhNKMsz
ygt64TO
HBw/41Fi8YQHy7hJ1hwJvwp3AgewoP9VTG2Yz9CoymeYWydpFMCCHBzF5wnQZrRsog
yV4fNnunRD
BP+J3lMSgJOJKYTKIHnce0riv28HdmFKiLtriwzYR7s2dl/lexmWVXoxYid0anCPvP5vOVx
b8ho

0dDF/oA/6Jf8GlorMaGQES8ncU1ZD/RacM9vKumBRkM5LWPpZ/aQ9UXFuCyKukVhNwD
 6YzH7MrjM
 qTKkfzlluCTwSvIhLDJuqqa4s+bkYz9qr5/aO9x3aOHjA/fG/UKR9WFOin71SKDIF3v6LrF1v
 Glf
 93M7NZkDhx9o7fjBWMXZb5/Y99OGEk+pXltHm8a+1tq80hNe7TV+5bHWHUPHwHwaj28
 xAPTfteuB
 DC8oVyw8ZICeYwRz2BKxRDWyzrYKropv53vhTv6h+Lf4I/DZ+Jv8n/gr8GNslvLQyNFyo0
 xV89Xy
 nTzllEv4kEzRvFbmOCOGlvjoDlDDpfikkJTrKlsrd4JBsIf/lrBLfhIc4PfLR8ER+QVwTJ6oPFH
 5
 FneBn658D4u1S5Vz3Ef8R8JM5TXwBfeZLDXBdVxjvANu57bGH+AeFt7gfyW/zb8tv8+/Lz
 MWn8vg
 LxZ9riJ/cbnPFfYXI+JyDLA+lxOPIs9V4g9wPF8MoAPwAoACzxM9rlaOO2Sek+N8HMBxb8
 ciUuCQ
 Qa8HQJZLwno5ixcAIV5eLIq3Rblo/5hSCSshI19hZi2ixYq2WMYq1LQMbFmQolctbCcBtmK
 b1ZqK
 L5A0TXZJrcMbWUWXQcS45dXOYrXGvPsZ/4F+FTzsihPPM8zv2BTPW1M8a0sBPU98zJf
 OcClOdqTy
 ok79bCeua///41skIWkIb8sBue0ypBrnr7qkNnkhTEKhDqZ5E1ZsP4GzcDjeHnS6pbb4/LTcHn
 DO
 /0Oz++aepcAotacj7CmRbryrUQ9vPrl84ckbB0mewKqFRupd6ji4A6wD26kjiM2Z9uR0NFqC
 pSx
 WbQnumcTAIG6nN54UNTUrWjN9q7YHerLEmz/o9xj/EjyydpH1440f7f1MHeYP9qa05zTnu
 ZO8xcS
 F5qns5eyM9IPs64isbCKTTqqfVntT/SZ6joXcFLV/owLCGtu/U8Ng93uMOiHJWiTCLDJ5kBb
 1KAH
 pippFZPNVDcuHZfOS5SUG2NntsWGsdGJb1XM5F7buP+4/zypIZN/Rm3xI358r8KPZmCGr
 KEZU14g
 U0r8TJk2B3SQ2lu9Vw+HsL6GrXG0RZ+kj66Ba3JUhVIgZlxxAbYJw3id/Tn6H0ADA9UC0v
 iSkdYJ
 G+CG0lJLy2uUDGTgxfsUaKFkxcfKsFcekcldlSuZJbmke1yQnU+XU8Ga4mbyb2YK24M5vT
 7MOtfMX
 1Wu5mcDhjGYL7km+MCRhGwUzfGIkDFvDfeHp8KWwJsyQO8NLELAwQX7ZiFshvFvM
 ylkI04Fprs2q
 gT5TQSLlJdZdCBvVUGJjheiEFmef86KTcpJiRmqenLOAJMXma4s4CbrIfRQO1lXIVBuF2iis
 gbEE
 Lo5JKXgS1GIMilryIJPOK+Qdqfs7slPwYeCHxpMH8Cy5lk97GpgbmFc7c7GBWTbWf009iA
 2QzMdY
 Pzt7FR8OkEhRPiFy/gOSHlnHzpG8qU6szLLkfnxz55ptp0mJINS5PTZwdY6YTEsMdFnCZwb
 IfF3U
 OpY1jyUk5GBze83aYNLt4XioDUmVfVUViQqKXh1qDZVL0dBWabMbuu/AFnhzskUE9b
 BOBKu0dW7Q
 VtbiBhtjm0XYwDe64ZaSdjfc2u6pceHbXXeA9RUZETZnktUKWiMSHIcm7YZ3xTe4wabIB
 hGs5da4
 89kgKnDylu5fiyhG1TQRAqjsVAuPqBBKxVhOMEFJLEDKSYDKli8TsZREwuWhV3gxog
 OBxdg2ndfA
 ybasmxOAJN7Up2C+os5SagI9+xE+Tm7u+N3Eo92/jDFYT6IssW+ufP3HDXeW+vyyu++/V3
 X2PvD8
 jV/sbzZZk7quRCwFCzP3NSTa1vesrVr4PC7X3Pzf0y9VJZ79K7wr8v3tT7yuaGkDV2TU0k19
 w2cd

oZTDKu0oInZg7tvYf++h9spqnpfqDff6KnyBr6DH9wyOtdcPDI531N/cV7VNkoO1Q00Jp1N
DY5q2
YuE0qH0KxJB+qQ5PmepJLI0jEGUqktoVgyxDQz0TWSyCZ2MIotJGJjhjUwNM+WATTRz
HBupvilEf
lLwcAHjpJOV4bDTxpsxNs9N1v8N8mHcXTxOX2+vsG2T7F6ziOawPkmcAKVbjidBB/E36y
GLdOhWZ
CFXfm/oz/pivq8Ko5/Hxn1QfHMOUIS45h1XUoZr1uVRkpfageLTwaIhqoBoKmoT91P4C7b
MaGC8b
8pMK9+P6ccMYO2Y9UWZgaVaHuqJdMeTWM6e9+kPF8LRXl6P0ii/gHfee9yKvNShxMNB
GQlaORmxW
Wq8zsi7oysGNkyNlsCyHrp2C0VgOsoo5HIE2i5U9ZLHAIelinuzuTqhtTU2+ravLt8EKtVWcb
n9i
lIEk9bmL6WommUsMzQilU9jw0i3qbPlk5Za5NFbWCPuncfNB52w+UJFOzw9gE8Ka6owvo
Q+lEocZ
JBWGGJGfYDUocQYI+jOULH+TrLap17JaXRBK2CCSrSMGUvI6mVuhR6x7QhYVVhfCY
W6rdNP/nSLhe
OHVq25n++7fVJLxcVcbnC5Ur7k+o9fPHhotLg8FwQw/qaEofeG13Q9IKb9L/kN1esePt+ibwT
3be
GellbmRzdHJlYW0gCmVuZG9iaiAKMiAwIG9iaiAKPDwgCi9UeXBliC9QYWdlcyAKL0tp
ZHMgWyA4
IDAgUiBdIAovQ291bnQgMSAKL01lZGhhQm94IDMgMCBSIAovQ3JvcEJveCA0IDAgUiA
KPj4gCmVu
ZG9iaiAKMyAwIG9iaiAKWyAwIDAgNjEyIDc5MiBdIAplbmRvYmogCjQgMCBvYmogCl
s gMCAwIDYx
MiA3OTIgXSAKZW5kb2JqIAo2IDAgb2JqIAo8PCAKL1Byb2NTZXQgNyAwIFIgCi9Gb250
IDw8IAov
OSA5IDAgUiAgCi9hIDEwIDAgUiAgCj4+IAo+PiAKZW5kb2JqIAo3IDAgb2JqIApIC9QR
EYgLRl
eHQgIF0gCmVuZG9iaiAKOCAwIG9iaiAKPDwgCi9UeXBliC9QYWdlIAovUGFyZW50IDI
gMCBSIAov
UmVzb3VyY2VzIDYgMCBSIAovQ29udGVudHMgWyA1IDAgUiBdIAo+PiAKZW5kb2JqI
Ao5IDAgb2Jq
IAo8PCAKL1R5cGUgL0ZvbnQgCi9TdWJ0eXBliC9UcnVlVHlwZSAKL05hbWUgLzkgCi9
CYXNlRm9u
dCAxMiAwIFIgCi9GaXJzdENoYXlzMzMgCi9MYXN0Q2hhciA2MSAKL1dpZHRocyAxM
SAwIFIgCi9G
b250RGVzY3JpcHRvciAxNCwIFIgCi9Ub1VuaWNvZGUgMTMgMCBSIAo+PiAKZW5kb
2JqIAoxMCAw
IG9iaiAKPDwgCi9UeXBliC9Gb250IAovU3VidHlwZSAvVHJlZVR5cGUgCi9OYWw1IIC9hI
AovQmFz
ZUZvbnQgMTggMCBSIAovRmlyc3RDaGFyIDMzIAovTGfzdENoYXlzMjgCi9XaWR0aH
MgMTcgMCBS
IAovRm9udERlc2NyaXB0b3IgMjAgMCBSIAovVG9Vbmljb2RlIDE5IDAgUiAKPj4gCmVu
ZG9iaiAK
MTEgMCBvYmogClsgCjcyMiAKNDQ0IAozMzMgCjUwMCAKMjc4IAoyNzggCjU1NiAK
MjUwIAo3Mjlg
CjQ0NCAKNzc4IAozODkgCjUwMCAKNTAwIAo2NjcgCjQ0NCAKNTU2IAozODkgCjUw
MCAKNjY3IAo1
MDAgCjU1NiAKMzMzMjlgCjgzMyAKNTU2IAo1NTYgCjQ0NCAKNjY3IApdIAplbm
RvYmogCjEy

IDAgb2JqIAovQUFBQUFBK1RpbWVzTmV3Um9tYW4sQm9sZCAKZW5kb2JqIAoxNCAw
 IG9iaiAKPDwg
 Ci9UeXBIIc9Gb250RGVzY3JpcHRvciAKL0FzY2VudCA4OTEgCi9DYXBIZWlnaHQgNTA
 wIAovRGVz
 Y2VudCAzMjE2IAovRmxhZ3MgNSAKL0ZvbnRCQm94IDE1IDAgUiAKL0ZvbnROYW1lI
 DEyIDAgUiAK
 L0l0YWxpY0FuZ2xlIDAKL1N0ZW1WIDAgCi9TdGVtSCAwIAovQXZnV2lkdGggNDI3IAo
 vRm9udEZp
 bGUyIDE2IDAgUiAKL0xIYWRpbmcgMCAKL01heFdpZHRoIDI1NTggCi9NaXNzaW5nV2
 lkdGggNDI3
 IAovWEhlaWdodCAwIAo+PiAKZW5kb2JqIAoxNSAwIG9iaiAKWyAtNTU4IC0zMDcgMjA
 wMCAxMDI2
 IF0gCmVuZG9iaiAKMTcgMCBvYmogClsgCjY2NyAKNTAwIAozODkgCjI3OCAKNTAwI
 Ao3NzggCjQ0
 NCAKMzMzIAoyNTAgCjMzMzMyAKNzIyIAoyNzggCjUwMCAKNTAwIAo1MDAgCjUwMC
 AKNDQ0IAo1MDAg
 CjUwMCAKNjExIAo0NDQgCjcyMiAKNTU2IAoyNzggCjUwMCAKNTAwIAo3MjIgCjUw
 MCAKNTAwIAoy
 NzggCjUwMCAKNTAwIAo1MDAgCjg4OSAKNTAwIAozMzMgCl0gCmVuZG9iaiAKMTg
 gMCBvYmogCi9B
 QUFBQUlrfVGltZXNOZXdsb21hbiAKZW5kb2JqIAoyMCAwIG9iaiAKPDwgCi9UeXBIIc9
 Gb250RGVz
 Y3JpcHRvciAKL0FzY2VudCA4OTEgCi9DYXBIZWlnaHQgNTAwIAovRGVzY2VudCAzM
 jE2IAovRmxh
 Z3MgNSAKL0ZvbnRCQm94IDIXIDAgUiAKL0ZvbnROYW1lIIDE4IDAgUiAKL0l0YWxpY
 0FuZ2xlIDAK
 L1N0ZW1WIDAgCi9TdGVtSCAwIAovQXZnV2lkdGggNDAxIAovRm9udEZpbGUyIDYyID
 AgUiAKL0xl
 YWRpbmcgMCAKL01heFdpZHRoIDI1NjggCi9NaXNzaW5nV2lkdGggNDAxIAovWEhlaW
 dodCAwIAo+
 PiAKZW5kb2JqIAoyMSAwIG9iaiAKWyAtNTY4IC0zMDcgMjAwMCAxMDA3IF0gCmVu
 ZG9iaiAKMjMg
 MCBvYmogCihQb3dlcmVkieJ5IENyeXN0YWwpIAplbmRvYmogCjI0IDAgb2JqIAooQ3J5c
 3RhbCBS
 ZXBvcnRzKSAKZW5kb2JqIAoyNSAwIG9iaiAKKERldGFpbGVkiENyZWZpYXJkIE
 JhdGNoICkg
 CmVuZG9iaiAKMjYgMCBvYmogCjw8IAovUHJvZHVjZXIgaKFBvd2VyZWQgQnkgQ3J5c3
 RhbCkgIAov
 VG10bGUgKERldGFpbGVkiENyZWZpYXJkIEJhdGNoICkgIAovQ3JlYXRvciAoQ3J5c3
 RhbCBS
 ZXBvcnRzKSAgCj4+IAplbmRvYmogCnhyZWYgCjAgMjcgCjAwMDAwMDAwMDAgNjU
 1MzUgZiAKMDAw
 MDAwMDAxNyAwMDAwMCBUIAowMDAwMDM5NjM2IDAwMDAwIG4gCjAwMDAw
 Mzk3MzUgMDAwMDAgbiAK
 MDAwMDAzOTc2OSAwMDAwMCBUIAowMDAwMDAwMTk0IDAwMDAwIG4gCjAwM
 DAwMzk4MDMgMDAwMDAg
 biAKMDAwMDAzOTg4MSAwMDAwMCBUIAowMDAwMDM5OTE1IDAwMDAwIG4gCj
 AwMDAwNDAwMDcgMDAw
 MDAgbiAKMDAwMDA0MDE4MSAwMDAwMCBUIAowMDAwMDQwMzU2IDAwMDA
 wIG4gCjAwMDAwNDA1MjUg

MDAwMDAgiAKMDAwMDAwMDYzNCaAwMDAwMCBuIAowMDAwMDQwNTcxIDA
wMDAwIG4gCjAwMDAwNDA4
MzggMDAwMDAgiAKMDAwMDAwMTEzMyAwMDAwMCBuIAowMDAwMDQwODg
xIDAwmDAwIG4gCjAwMDAw
NDEwODUgMDAwMDAgiAKMDAwMDAxNzQ0MyAwMDAwMCBuIAowMDAwMDQ
xMTI2IDAwmDAwIG4gCjAw
MDAwNDEzOTMgMDAwMDAgiAKMDAwMDAxNzk4MCAwMDAwMCBuIAowMDA
wMDQxNDM2IDAwmDAwIG4g
CjAwMDAwNDE0NzYgMDAwMDAgiAKMDAwMDA0MTUxMyAwMDAwMCBuIAow
MDAwMDQxNTYyIDAwmDAw
IG4gCnRyYWlsZXIgcjw8IAovU2l6ZSAyNyAKL1Jvb3QgMSAwIFIgCi9JbmZvIDI2IDAgUi
AKPj4g
CnN0YXJ0eHJIZiAKNDE2ODkgCiUIRU9GIAo=
 </reportfile>
 </data_block>
 </attributes>
</data_block>
</body>
</PLAT_XML>

Method:

[GetReportFile](#)

Getservicedefs XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetServiceDefs</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
        <serviceid>1</serviceid>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <svc_id>1</svc_id>
          <svc_name>Email</svc_name>
          <svc_class>email_address</svc_class>
          <svc_table>email_data</svc_table>
          <svc_seq>0</svc_seq>
          <svc_showdetail>1</svc_showdetail>
          <svc_use_table/>
          <svc_reid>1</svc_reid>
          <svc_datacol/>
          <svc_icon/>

```

```
<svc_endcol/>
<svc_usage>0</svc_usage>
<svc_useusagedate>0</svc_useusagedate>
<svc_usagedate>2002-11-12T13:42:30</svc_usagedate>
<svc_accumulate>0</svc_accumulate>
<svc_pricecol/>
<svc_orderbycol/>
<svc_compare_email>Y</svc_compare_email>
<svc_web_only>N</svc_web_only>
<svc_ccs_service/>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[GetServiceDefs](#)

Getservicedetail XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetServiceDetail</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <svcid>1</svcid>
        <dataid>80</dataid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[GetServiceDetail](#)

GetServiceInfo XML Example

Input Example1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetServiceInfo</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <svcid>1</svcid>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>142</id>
          <tblname>email_data</tblname>
          <fmat>K</fmat>
          <readonly>N</readonly>
          <reqd>N</reqd>
          <mask>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</mask>
          <dflt/>
          <ctrl>txt_service_email</ctrl>
          <datacol>emailaddr</datacol>
          <datahdr>Email Address</datahdr>
          <seq>1</seq>
          <search>Y</search>
```

```

        <sctype>1</sctype>
        <schfld>emailaddr</schfld>
        <classlib>username</classlib>
        <uf_blacklisttype/>
        <uf_webdisplay>R</uf_webdisplay>
        <uf_template_field>NULL</uf_template_field>
    </data_block>
    <data_block>
        <id>145</id>
        <tblname>email_data</tblname>
        <fmat>K</fmat>
        <readonly>N</readonly>
        <reqd>N</reqd>
        <mask>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</mask>
        <dflt/>
        <ctrl>cmb_service_domain</ctrl>
        <datacol>domain</datacol>
        <datahdr>Domain</datahdr>
        <seq>2</seq>
        <search>N</search>
        <sctype>=</sctype>
        <schfld>domain</schfld>
        <classlib>username</classlib>
        <uf_blacklisttype/>
        <uf_webdisplay>R</uf_webdisplay>
        <uf_template_field>NULL</uf_template_field>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
    <header></header>
    <body>
        <data_block>
            <protocol>Plat</protocol>
            <object>addusr</object>
            <action>GetServiceInfo</action>
            <username>Admin</username>
            <password></password>
            <logintype>staff</logintype>
            <parameters>
                <svcid>17</svcid>
                <datatype>XML</datatype>
                <rgid type="integer">47</rgid>
                <crd type="integer">817</crd>
            </parameters>
        </data_block>
    </body>
</PLATXML>

```

```

</data_block>
</body>
</PLATXML>

```

Output Example 2:

```
<PLAT_XML>  
  <header></header>  
  <body>  
    <data_block>  
      <object>addusr</object>  
      <protocol>TPP</protocol>  
      <action>Reply</action>  
      <response_text></response_text>  
      <response_code>SUCCESS</response_code>  
      <is_success>1</is_success>  
      <attributes>  
        <data_block>  
          <id>150</id>  
          <tblname>registered_domain_data</tblname>  
          <fmat>K</fmat>  
          <readonly>N</readonly>  
          <reqd>Y</reqd>  
          <mask/>  
          <dflt>XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX</d  
flt>  
          <ctrl>txt_text</ctrl>  
          <datacol>domain</datacol>  
          <datahdr>Domain</datahdr>  
          <seq>1</seq>  
          <search>Y</search>  
          <schtyp>1</schtyp>  
          <schfld/>  
          <classlib>ssmsclas</classlib>  
          <uf_blacklisttype/>  
          <uf_webdisplay>R</uf_webdisplay>  
          <uf_template_field>NULL</uf_template_field>  
          <template_dflt>NULL</template_dflt>  
        </data_block>  
        <data_block>  
          <id>151</id>  
          <tblname>registered_domain_data</tblname>  
          <fmat>D</fmat>  
          <readonly>N</readonly>  
          <reqd>N</reqd>  
          <mask/>  
          <dflt/>  
          <ctrl>txt_date</ctrl>  
          <datacol>expire_date</datacol>  
          <datahdr>Expiration Date</datahdr>
```

```

        <seq>2</seq>
        <search>N</search>
        <schtyp>1</schtyp>
        <schfld/>
        <classlib>ssmsclas</classlib>
        <uf_blacklisttype/>
        <uf_webdisplay>R</uf_webdisplay>
        <uf_template_field>NULL</uf_template_field>
        <template_dflt>NULL</template_dflt>
    </data_block>
    <data_block>
        <id>152</id>
        <tblname>registered_domain_data</tblname>
        <fmat>D</fmat>
        <readonly>Y</readonly>
        <reqd>N</reqd>
        <mask>99</mask>
        <dflt>1</dflt>
        <ctrl>txt_date</ctrl>
        <datacol>register_period</datacol>
        <datahdr>Registration period</datahdr>
        <seq>3</seq>
        <search>N</search>
        <schtyp>1</schtyp>
        <schfld/>
        <classlib>ssmsclas</classlib>
        <uf_blacklisttype/>
        <uf_webdisplay>R</uf_webdisplay>
        <uf_template_field>NULL</uf_template_field>
        <template_dflt>1</template_dflt>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[GetServiceInfo](#)

Getstaffnotes XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetStaffNotes</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <staffid>1</staffid>
        <notetype>Complete</notetype>
        <notenumber>1</notenumber>
        <noteidtype>Staff</noteidtype>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Nothing found matching search criteria</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
```



```

<body>
  <data_block>
    <protocol>Plat</protocol>
    <object>addusr</object>
    <action>GetStaffNotes</action>
    <username>Admin</username>
    <password></password>
    <logintype>staff</logintype>
    <parameters>
      <datatype>XML</datatype>
    </parameters>
    <properties>
      <staffid>1</staffid>
      <noteidtype>Staff</noteidtype>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Nothing found matching search criteria</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetStaffNotes](#)

Getstores XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetStores</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <storeid>1</storeid>
          <name>Tucows</name>
        </data_block>
        <data_block>
          <storeid>2</storeid>
          <name>Vandilay Industries</name>
        </data_block>
        <data_block>
          <storeid>7</storeid>
          <name>New Store</name>
        </data_block>
      </attributes>
    </data_block>
```

```
</body>  
</PLAT_XML>
```

Method:

[GetStores](#)

Gettimeclockstatus XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetTimeClockStatus</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <staffidlist></staffidlist>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tc_staffid>1</tc_staffid>
          <lastclockin>2005-01-26T14:34:28</lastclockin>
          <lastclockout>2005-01-26T14:34:30</lastclockout>
        </data_block>
        <data_block>
          <tc_staffid>2</tc_staffid>
          <lastclockin>2005-05-11T14:17:35</lastclockin>
          <lastclockout>2005-05-11T14:17:35</lastclockout>
        </data_block>
      </attributes>
    </data_block>
```

```

        <tc_staffid>47</tc_staffid>
        <lastclockin>2004-07-20T15:16:31</lastclockin>
        <lastclockout>NULL</lastclockout>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetTimeClockStatus</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <staffidlist>1</staffidlist>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tc_staffid>1</tc_staffid>
          <lastclockin>2005-01-26T14:34:28</lastclockin>
          <lastclockout>2005-01-26T14:34:30</lastclockout>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

        </attributes>
    </data_block>
</body>
</PLAT_XML>

```

Input Example 3:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetTimeClockStatus</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <staffidlist>1,47</staffidlist>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 3:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tc_staffid>1</tc_staffid>
          <lastclockin>2005-01-26T14:34:28</lastclockin>
          <lastclockout>2005-01-26T14:34:30</lastclockout>
        </data_block>
        <data_block>
          <tc_staffid>47</tc_staffid>
          <lastclockin>2004-07-20T15:16:31</lastclockin>
          <lastclockout>NULL</lastclockout>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[GetTimeClockStatus](#)

Getusge XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetUsage</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Internal Error: Invalid at the top level of the
document.</response_text>
      <response_code>XML_PARSE_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
```



```

    <object>addusr</object>
    <action>GetUsage</action>
    <username>justn</username>
    <password>a</password>
    <logintype>customer</logintype>
    <parameters>
      <datatype>XML</datatype>
    </parameters>
    <properties>
      <begin>6/1/2000</begin>
      <end>12/1/2004</end>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <linkdate>11/30/04</linkdate>
          <dispdte>Nov 30, 2004</dispdte>
          <calls> 1</calls>
          <avglen> 1757</avglen>
          <ttltime>29:17:36</ttltime>
          <orderdate>2004-11-30T00:00:00</orderdate>
          <total_out>0</total_out>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetUsage](#)

Getusagebyterm XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetUsageByTerm</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>No usage data found for specified time period</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
```

```

    <action>GetUsageByTerm</action>
    <username>justn</username>
    <password>a</password>
    <logintype>customer</logintype>
    <parameters>
      <datatype>XML</datatype>
    </parameters>
    <properties>
      <begin>6/1/2000</begin>
      <end>6/1/2004</end>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>No usage data found for specified time period</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[GetUsageByTerm](#)

Getusageday XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetUsageDay</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <usagedate>10/30/2003</usagedate>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>No usage data found for specified time period</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[GetUsageDay](#)

Getweboption XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetWebOption</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <option_name>CCS_ViaKLIX_Pin</option_name>
        <storeappended type="boolean">>false</storeappended>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <CCS_ViaKLIX_Pin>dprwipoewgrnlwet</CCS_ViaKLIX_Pin>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>GetWebOption</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <optionname>umenable_2</optionname>
        <storeappended type="boolean">true</storeappended>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <umenable_2>N</umenable_2>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 3:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
```

```

        <action>GetWebOption</action>
    <username>Admin</username>
    <password></password>
    <logintype>staff</logintype>
    <parameters>
        <option_name>CCS_ViaKLIX_Pin</option_name>
        <storeappended type="boolean">false</storeappended>
        <datatype>XML</datatype>
    </parameters>
    <properties>
    </properties>
</data_block>
</body>
</PLATXML>

```

Output Example 3:

```

<PLAT_XML>
    <header></header>
    <body>
        <data_block>
            <object>addusr</object>
            <protocol>TPP</protocol>
            <action>Reply</action>
            <response_text></response_text>
            <response_code>SUCCESS</response_code>
            <is_success>1</is_success>
            <attributes>
                <data_block>
                    <CCS_ViaKLIX_Pin>dprwipoewgrnlwet</CCS_ViaKLIX_Pin>
                </data_block>
            </attributes>
        </data_block>
    </body>
</PLAT_XML>

```

Method:

[GetWebOption](#)

Ischild XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isChild</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <guarantor type="int">1059</guarantor>
        <customer>1060</customer>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ischild>true</ischild>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:


```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isChild</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <guarantor type="int">1012</guarantor>
        <customer>1011</customer>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ischild>true</ischild>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[IsChild](#)

Isdupccnumber XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isDupCCNumber</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <ccnumber>4005550000000019</ccnumber>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <dupcustomer>1012</dupcustomer>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isDupCCNumber</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <ccnumber>4222222222222222</ccnumber>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <dupcustomer>1356</dupcustomer>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[IsDupCCNumber](#)

Isguarantor XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isGuarantor</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <customer>1012</customer>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <isguarantor>true</isguarantor>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>isGuarantor</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <customer>1011</customer>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <isguarantor>>false</isguarantor>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[IsGuarantor](#)

Launchum XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>LaunchUM</action>
      <username>justn</username>
      <password>a</password>
      <logintype>staff</logintype>
      <parameters>
        <option>UM_Close</option>
        <dataid>7</dataid>
        <openconnection>1</openconnection>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1001</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[LaunchUM](#)

ListServiceInstances XML Example**Input Example**

```

<?xml version="1.0"?>
<PLATXML>
<header></header>
<body>
  <data_block>
    <protocol>Plat</protocol>
    <object>addusr</object>
    <action>ListServiceInstances</action>
    <username>John Smith</username>
    <password>password</password>
    <logintype>staff</logintype>
    <parameters>
      <service>0</service>
      <instance>0</instance>
      <datatype>XML</datatype>
      <crid>1234</crid>
    </parameters>
    <properties>
      <custid>1000</custid>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example

```

<?xml version="1.0"?>
<PLAT_XML>
<body>
  <data_block>
    <object>addusr</object>
    <action>Reply</action>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <s_name>Domain #2169</s_name>
        <s_data>aplus.com</s_data>
        <s_num>2169</s_num>
        <s_active>Y</s_active>
        <s_svc_id>2</s_svc_id>
        <s_customer_name>Test User</s_customer_name>
        <s_customer_id>1000</s_customer_id>
        <s_struct_id>12341</s_struct_id>
        <s_parent_id>0</s_parent_id>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>

```

```
<s_parent_type>0</s_parent_type>
<s_parent_struct>0</s_parent_struct>
<s_custrate>1234</s_custrate>
<s_svc_seq>4</s_svc_seq>
</data_block>
<data_block>
  <s_name>Email #83</s_name>
  <s_data>admin@aplus.com</s_data>
  <s_num>83</s_num>
  <s_active>Y</s_active>
  <s_svc_id>1</s_svc_id>
  <s_customer_name>Test User</s_customer_name>
  <s_customer_id>1000</s_customer_id>
  <s_struct_id>12342</s_struct_id>
  <s_parent_id>0</s_parent_id>
  <s_parent_type>0</s_parent_type>
  <s_parent_struct/>
  <s_custrate>1234</s_custrate>
  <s_svc_seq>1</s_svc_seq>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method

[ListServiceInstances](#)

ListServiceITree XML Example**Input Example**

```

<?xml version="1.0"?>
<PLATXML>
<header></header>
<body>
  <data_block>
    <protocol>Plat</protocol>
    <object>addusr</object>
    <action>ListServicesTree</action>
    <username>John Smith</username>
    <password>password</password>
    <logintype>staff</logintype>
    <parameters>
      <datatype>XML</datatype>
    </parameters>
    <properties>
      <custid>1000</custid>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example

```

<?xml version="1.0"?>
<PLAT_XML>
<body>
  <data_block>
    <object>addusr</object>
    <action>Reply</action>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <rs_id>12341</rs_id>
        <rs_parent_id>0</rs_parent_id>
        <rs_rg_id>1234</rs_rg_id>
        <rs_cr_id>1234</rs_cr_id>
        <rs_svc_id>2</rs_svc_id>
        <rs_svc_qty>1</rs_svc_qty>
        <rs_base_qty>1</rs_base_qty>
        <rs_path>Domain</rs_path>
        <rs_order>2</rs_order>
        <rs_parent_service>0</rs_parent_service>
        <rs_parent_instance>0</rs_parent_instance>
        <rs_used>1</rs_used>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>

```

```
<rs_total>1</rs_total>
<rs_ccs_service>none</rs_ccs_service>
<rs_hidden>N</rs_hidden>
</data_block>
<data_block>
  <rs_id>12342</rs_id>
  <rs_parent_id>0</rs_parent_id>
  <rs_rg_id>1234</rs_rg_id>
  <rs_cr_id>1234</rs_cr_id>
  <rs_svc_id>1</rs_svc_id>
  <rs_svc_qty>25</rs_svc_qty>
  <rs_base_qty>25</rs_base_qty>
  <rs_path>Email</rs_path>
  <rs_order>2</rs_order>
  <rs_parent_service>0</rs_parent_service>
  <rs_parent_instance>0</rs_parent_instance>
  <rs_used>0</rs_used>
  <rs_total>0</rs_total>
  <rs_ccs_service>none</rs_ccs_service>
  <rs_hidden>N</rs_hidden>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method

[ListServiceTree](#)

Listservices2 XML Example**Input Example**

```

<?xml version="1.0"?>
<PLATXML>
<header></header>
<body>
  <data_block>
    <protocol>Plat</protocol>
    <object>addusr</object>
    <action>ListServices2</action>
    <username>John Smith</username>
    <password>password</password>
    <logintype>staff</logintype>
    <parameters>
      <crid>1234</crid>
      <datatype>XML</datatype>
    </parameters>
    <properties>
      <custid>1000</custid>
    </properties>
  </data_block>
</body>
</PLATXML>

```

Output Example

```

<?xml version="1.0"?>
<PLAT_XML>
<body>
  <data_block>
    <object>addusr</object>
    <action>Reply</action>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <s_name>Domain #2169</s_name>
        <s_data>aplus.com</s_data>
        <s_num>2169</s_num>
        <s_active>Y</s_active>
        <s_svc_id>2</s_svc_id>
        <s_customer_name>Test User</s_customer_name>
        <s_customer_id>1000</s_customer_id>
        <s_struct_id>12341</s_struct_id>
        <s_parent_id>0</s_parent_id>
        <s_parent_type>0</s_parent_type>
        <s_parent_struct>0</s_parent_struct>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>

```

```
<s_custrate>1234</s_custrate>
<s_svc_seq>4</s_svc_seq>
</data_block>
<data_block>
  <s_name>Email #83</s_name>
  <s_data>admin@aplus.com</s_data>
  <s_num>83</s_num>
  <s_active>Y</s_active>
  <s_svc_id>1</s_svc_id>
  <s_customer_name>Test User</s_customer_name>
  <s_customer_id>1000</s_customer_id>
  <s_struct_id>12342</s_struct_id>
  <s_parent_id>0</s_parent_id>
  <s_parent_type>0</s_parent_type>
  <s_parent_struct/>
  <s_custrate>1234</s_custrate>
  <s_svc_seq>1</s_svc_seq>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method

[ListServices](#)

Logchange XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>LogChange</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <tag>Note Loaded</tag>
        <key>1001</key>
        <comment>Test</comment>
        <oldvalue>a</oldvalue>
        <newvalue>b</newvalue>
        <keytype>Customer</keytype>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <loginid>1</loginid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <success>1</success>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
</body>  
</PLAT_XML>
```

Method:

[LogChange](#)

Login XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Login</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <logintype>Customer</logintype>
        <username>justn</username>
        <password>a</password>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1012</id>
          <storeid>1</storeid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Login</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <logintype>Customer</logintype>
        <username>jthornton</username>
        <password>aa</password>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>Login Failed</response_text>
      <response_code>LOGIN_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Input Example 3:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
```



```

        <action>Login</action>
    <username>Admin</username>
    <password></password>
    <logintype>staff</logintype>
    <parameters>
        <logintype>Staff</logintype>
        <username>Admin</username>
        <password></password>
        <datatype>XML</datatype>
    </parameters>
    <properties>
    </properties>
    </data_block>
</body>
</PLATXML>

```

Output Example 3:

```

<PLAT_XML>
    <header></header>
    <body>
        <data_block>
            <object>addusr</object>
            <protocol>TPP</protocol>
            <action>Reply</action>
            <response_text></response_text>
            <response_code>SUCCESS</response_code>
            <is_success>1</is_success>
            <attributes>
                <data_block>
                    <id>1</id>
                    <storeid>1</storeid>
                </data_block>
            </attributes>
        </data_block>
    </body>
</PLAT_XML>

```

Method:

[Login](#)

OpenSRSGenProfile XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>OpenSRSGenProfile</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <profile><username>rq1bJJek0Xu608seo3f1</username><password>
>q50aIID30X7={s15310</password></profile>
          </data_block>
        </attributes>
      </data_block>
    </body>
  </PLAT_XML>
```

Method:

[OpenSRSGenProfile](#)

OpenSRSGetProfile XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>OpenSRSGetProfile</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <CustomerID type="integer">1001</CustomerID>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>No OpenSRS Profile currently exists on Customer
#1001</response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[OpenSRSGetProfile](#)

OpenSRSSetProfile XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>OpenSRSSetProfile</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <nCustid>1001</nCustid>
        <username>username</username>
        <password>password</password>
        <datatype>XML</datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The OpenSRS Profile was successfully saved to the Customer
Record.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[OpenSRSSetProfile_1](#)

Post XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Post</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <noconn type="boolean">>false</noconn>
        <days>10</days>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[Post](#)

Postpayment XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>PostPayment</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <tender type="currency">20.00</tender>
        <paydate>3/4/2005</paydate>
        <invoicelist>1135,3441,5230</invoicelist>
        <paymenttypeid>6</paymenttypeid>
        <custid>1012</custid>
        <paymentnumber>321</paymentnumber>
        <name>JuStIn tHoRnToN</name>
        <chargerealttime type="int">0</chargerealttime>
        <ignore type="boolean">>false</ignore>
        <noisy type="boolean">>false</noisy>
        <ccexpire>1/31/2006</ccexpire>
        <noconn type="boolean">>false</noconn>
        <authorizeonly type="boolean">>false</authorizeonly>
        <routenumber></routenumber>
        <accounttype></accounttype>
        <bankname></bankname>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
```

```

        <response_text></response_text>
        <response_code>SUCCESS</response_code>
        <is_success>1</is_success>
        <attributes>
            <data_block>
                <fraudstatus></fraudstatus>
            </data_block>
        </attributes>
    </data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
    <header></header>
    <body>
        <data_block>
            <protocol>Plat</protocol>
            <object>addusr</object>
            <action>PostPayment</action>
            <username>Admin</username>
            <password>admin</password>
            <logintype>staff</logintype>
            <parameters>
                <tender type="currency">1.00</tender>
                <paydate>3/4/2005</paydate>
                <invoicelist>18923,18924</invoicelist>
                <paymenttypeid>6</paymenttypeid>
                <custid>6985</custid>
                <paymentnumber>321</paymentnumber>
                <name>JuStIn tHoRnToN</name>
                <chargerealttime type="int">0</chargerealttime>
                <ignore type="boolean">>false</ignore>
                <noisy type="boolean">>false</noisy>
                <ccexpire>1/31/2006</ccexpire>
                <noconn type="boolean">>false</noconn>
                <authorizeonly type="boolean">>false</authorizeonly>
                <routenumber></routenumber>
                <accounttype></accounttype>
                <bankname></bankname>
                <datatype>XML</datatype>
                <address>123 Main Street</address>
                <city>Starkville</city>
                <state>MS</state>
                <zip>39759</zip>
                <country>US</country>
            </parameters>
            <properties>
            </properties>
        </data_block>
    </body>
</PLATXML>

```

```
        </data_block>
    </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <fraudstatus></fraudstatus>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[PostPayment](#)

Searchcustomer XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SearchCustomer</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <search>justin</search>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <name>Justin Thornton</name>
          <id>1011</id>
          <phone>1234567890</phone>
          <phonemasked>(123)456-7890</phonemasked>
          <username>justint3</username>
          <attn/>
          <active>Y</active>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
</body>
</PLAT_XML>
```

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SearchCustomer</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <whereclause>active='Y'</whereclause>
      </parameters>
      <properties>
        <search>justin</search>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <name>Justin Thornton</name>
          <id>1011</id>
          <phone>1234567890</phone>
          <phonemasked>(123)456-7890</phonemasked>
          <username>justint3</username>
          <attn/>
          <active>Y</active>
        </data_block>
      </attributes>
```

```

    </data_block>
  </body>
</PLAT_XML>

```

Input Example 3:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SearchCustomer</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <whereclause>active='Y'</whereclause>
        <storelist>2,3</storelist>
      </parameters>
      <properties>
        <search>justin</search>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 3:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <name>Justin Thornton</name>
          <id>1022</id>
          <phone>1234567890</phone>
          <phonemasked>(123)456-7890</phonemasked>
          <username>justint5</username>
          <attn/>
          <active>Y</active>

```

```

    </data_block>
    <data_block>
      <name>Justin Thornton</name>
      <id>1091</id>
      <phone>1234567890</phone>
      <phonemasked>(123)456-7890</phonemasked>
      <username>justint29</username>
      <attn/>
      <active>Y</active>
    </data_block>
    <data_block>
      <name>Justin Thornton</name>
      <id>1092</id>
      <phone>1234567890</phone>
      <phonemasked>(123)456-7890</phonemasked>
      <username>justint30</username>
      <attn/>
      <active>Y</active>
    </data_block>
  </attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[SearchCustomer](#)

Searchservices XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SearchServices</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <serviceid type="int">1</serviceid>
        <searchstring>justin</searchstring>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <s_name>Email #36</s_name>
          <s_data>justint26@yourdomain.com</s_data>
          <s_num>36</s_num>
          <exp>email_data</exp>
          <s_active>Y</s_active>
          <svc_id>1</svc_id>
          <scust_name>Justin Thornton</scust_name>
          <s_custid>1087</s_custid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
<data_block>
  <s_name>Email #37</s_name>
  <s_data>justint27@yourdomain.com</s_data>
  <s_num>37</s_num>
  <exp>email_data</exp>
  <s_active>Y</s_active>
  <svc_id>1</svc_id>
  <scust_name>Justin Thornton</scust_name>
  <s_custid>1088</s_custid>
</data_block>
<data_block>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[SearchCustomer](#)

Sendmail XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SendMail</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <toaddr>jet75@bellsouth.net</toaddr>
        <fromaddr>platypus@boardtown.com</fromaddr>
        <subject>My Subject</subject>
        <emailbody>My Body</emailbody>
        <ccaddr>jthornton@tucows.com</ccaddr>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[SendMail](#)

Setaddress XML Example**Input Example 1:**

```

<?xml version="1.0"?>
<PLATXML>
  <header>
</header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>setaddress</action>
      <username>admin</username>
      <password>password</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
        <addrarray type="array">
          <row>
            <col_name>attn</col_name>
            <col_value>John Smith</col_value>
          </row>
          <row>
            <col_name>addr1</col_name>
            <col_value>116 E Main St</col_value>
          </row>
        </addrarray>
        <addrtype type="integer">1</addrtype>
      </parameters>
      <properties>
        <custid>1000</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header>
</header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>

```

</PLAT_XML>

Input Example 2:

```
<?xml version="1.0"?>
<PLATXML>
  <header>
</header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>setaddress</action>
      <username>admin</username>
      <password>password</password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <addrarray type="array">
          <row>
            <col_name>attn</col_name>
            <col_value>Justin E. Thornton</col_value>
          </row>
          <row>
            <col_name>addr1</col_name>
            <col_value>116 E Main St</col_value>
          </row>
        </addrarray>
        <addrtype type="integer">1</addrtype>
      </parameters>
      <properties>
        <custid>1000</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 2:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[SetAddress](#)

Setphone XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SetPhone</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <datatype>XML</datatype>
        <phonearray
type="array"><row><col_name>Number</col_name><col_value>123654789012</col_value>
</row></phonearray>
          <phonetype type="integer">1</phonetype>
        </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[SetPhone](#)

SQL XML Example

Input Example 1:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>SQL</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <query>select id,name,username,password from customer where
active='N'</query>
        <noconn type="boolean">>false</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example 1:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1048</id>
          <name>Test Setup</name>
          <username>tests</username>
          <password>a</password>
        </data_block>
        <data_block>
          <id>1115</id>
          <name>Test Dude</name>
```

```

        <username>testdude1</username>
        <password>a</password>
    </data_block>
    <data_block>
        <id>1119</id>
        <name>Another Store2</name>
        <username>astore22</username>
        <password>a</password>
    </data_block>
    <data_block>
        <id>1123</id>
        <name>Test IUG</name>
        <username>testiug0</username>
        <password>a</password>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
    <header></header>
    <body>
        <data_block>
            <protocol>Plat</protocol>
            <object>addusr</object>
            <action>sql</action>
            <username>admin</username>
            <password></password>
            <logintype>staff</logintype>
            <parameters>
                <sql>select * from abba</sql>
                <blah type="boolean">false</blah>
                <datatype>XML</datatype>
            </parameters>
            <properties>
            </properties>
        </data_block>
    </body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
    <header></header>
    <body>
        <data_block>

```

```
<object>addusr</object>
<protocol>TPP</protocol>
<action>Reply</action>
<response_text>Error running SQL query</response_text>
<response_code>DATA_ERROR</response_code>
<is_success>0</is_success>
</data_block>
</body>
</PLAT_XML>
```

Method:

[Sql](#)

Transaction_Auth XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header>
</header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Transaction_Auth</action>
      <username>Admin</username>
      <password>password</password>
      <logintype>staff</logintype>
      <parameters>
        <authinput type="xml">
          <custid>1234</custid>
          <amount>20.00</amount>
          <ccinfo>
            <ccnumber>4111111111111111</ccnumber>
            <ccexpire>012005</ccexpire>
            <ccname>John Smith</ccname>
            <cctype>Visa</cctype>
            <cvv2>123</cvv2>
            <ccaddress>
              <addr1>10001 Blackberry St</addr1>
              <addr2>
</addr2>
              <city>Some City</city>
              <state>MS</state>
              <zip>12345</zip>
            </ccaddress>
          </ccinfo>
          <invoice>
            <details>
              <item>
                <code>code#1</code>
                <desc>my description</desc>
                <price>5.00</price>
                <profile>1</profile>
              </item>
              <item>
                <code>code#2</code>
                <desc>my description</desc>
                <price>15.00</price>
                <profile>1</profile>
              </item>
            </details>
          </invoice>
        </parameters>
      </data_block>
    </body>
  </PLATXML>

```

```
</authinput>
<lChargeNow type="boolean">false</lChargeNow>
<Datatype>XML</Datatype>
</parameters>
</data_block>
</body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header>
</header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The customer was successfully authorized.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <transaction>
            <transid>99999</transid>
            <total>$20.00</total>
          </transaction>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[Transaction Auth](#)

Transaction_Commit XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Transaction_Commit</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <TransactionID type="integer">1497</TransactionID>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The transaction was successful.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <transid>1512</transid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[Transaction_Commit](#)

Transaction_Refund XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Transaction_Refund</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <TransactionID type="integer">1001</TransactionID>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>The transaction was successful.</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <transid>1512</transid>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[Transaction_Refund](#)

Transaction_GetPrice XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Transaction_GetPrice</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <Service>domain</Service>
        <SubType>com</SubType>
        <TransactionType>register</TransactionType>
        <Period type="integer">1</Period>
        <Datatype>XML</Datatype>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <service_type>Domain</service_type>
          <service_subtype>COM</service_subtype>
          <transaction_type>Register</transaction_type>
          <period>1</period>
          <item>Reg1COM</item>
          <desc>Domain Registration - TLD COM 1 Year</desc>
          <price>15.0000</price>
          <profile>0</profile>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
        </attributes>
      </data_block>
    </body>
  </PLAT_XML>
```

Method:

[Transaction_GetPrice](#)

Update XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Update</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <table>custrate</table>
        <column>pendfee</column>
        <value>'N'</value>
        <whereclause>pendfee='n'</whereclause>
        <noconn type="boolean">>false</noconn>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[Update](#)

Updateccinfo XML Example

Input Example:

```

<?xml version="1.0" encoding="UTF-8"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>UpdateCCInfo</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <cctype>VISA</cctype>
        <ccmonth>7</ccmonth>
        <ccyear>2007</ccyear>
        <ccnumber>4111111111111111</ccnumber>
        <ccname>Joe Blow</ccname>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[UpdateCCInfo](#)

Updatecustomer XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>UpdateCustomer</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <column>attn</column>
        <value>'justin'</value>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text>attn was set to justin for customer 1012</response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[UpdateCustomer](#)

Updaterate XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>UpdateRate</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <lastbilled>6/1/2004</lastbilled>
        <nextbill>7/1/2004</nextbill>
        <billguar></billguar>
        <pendfee>n</pendfee>
        <crid>7</crid>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[UpdateRate](#)

Updateservice XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>UpdateService</action>
      <username>Admin</username>
      <password></password>
      <logintype>staff</logintype>
      <parameters>
        <serviceid>1</serviceid>
        <dataid>90</dataid>
        <column_array type="array">
          <row>
            <columnname>d_active</columnname>
            <newvalue>Y</newvalue>
            <currentvalue>N</currentvalue>
            <control>txt_text</control>
            <displayname>Active</displayname>
          </row>
        </column_array>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <custid>1012</custid>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

```
</body>  
</PLAT_XML>
```

Method:

[UpdateService](#)

Verifyinfo XML Example

Input Example 1:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>VerifyInfo</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <display_rates>R</display_rates>
        <display_block_rates>N</display_block_rates>
        <sales_required>N</sales_required>
        <show_sales>N</show_sales>
        <selectsales>1</selectsales>
        <selectref>1</selectref>
        <selectblock></selectblock>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <name2>Justin Thornton</name2>
        <phone>6623245816</phone>
        <address>116 E Main Street</address>
        <city>Starkville</city>
        <state>MS</state>
        <zip>39759</zip>
        <country>US</country>
        <username>jet88</username>
        <password>a</password>
        <password2>a</password2>
        <billingmeth>check</billingmeth>
        <selectpop>1</selectpop>
        <selectrate>1</selectrate>
        <selectblock></selectblock>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example 1:

```

<PLAT_XML>
  <header></header>

```

```

<body>
  <data_block>
    <object>addusr</object>
    <protocol>TPP</protocol>
    <action>Reply</action>
    <response_text></response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <vargood>true</vargood>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>

```

Input Example 2:

```

<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>VerifyInfo</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <display_rates>R</display_rates>
        <display_block_rates>N</display_block_rates>
        <sales_required>N</sales_required>
        <show_sales>N</show_sales>
        <selectsales>1</selectsales>
        <selectref>1</selectref>
        <selectblock></selectblock>
        <datatype>XML</datatype>
      </parameters>
      <properties>
        <name2>Justin Thornton</name2>
        <phone>6623245816</phone>
        <address>116 E Main Street</address>
        <city>Starkville</city>
        <state>MS</state>
        <zip>39759</zip>
        <country>US</country>
        <username>jet88</username>
        <password>ab</password>
        <password2>a</password2>
      </properties>
    </data_block>
  </body>
</PLATXML>

```



```

        <billingmeth>check</billingmeth>
        <selectpop>1</selectpop>
        <selectrate>1</selectrate>
        <selectblock></selectblock>
    </properties>
</data_block>
</body>
</PLATXML>

```

Output Example 2:

```

<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text><PRE>Your passwords don't match.</PRE></response_text>
      <response_code>DATA_ERROR</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[VerifyInfo](#)

Welcome_email XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header></header>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>addusr</object>
      <action>Welcome_Email</action>
      <username>justn</username>
      <password>a</password>
      <logintype>customer</logintype>
      <parameters>
        <datatype>XML</datatype>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>addusr</object>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[WelcomeEmail](#)

Wombat**attachment_Delete XML Example**

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>attachment_Delete</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cID type='string'>218</cID>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <attachment_Delete>true</attachment_Delete>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[attachment_Delete](#)

attachment_Load XML Example**Input Example:**

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>attachment_Load</action>
      <username>Admin</username>
      <password>password</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cID>1234</cID>
        <cType>ticket</cType>
        <nTypeId type='int'>99999</nTypeId>
        <cType type='string'>ticket</cType>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0"?>
<PLAT_XML>
  <header/>
  <body>
    <data_block>
      <object>addusr</object>
      <version>7.1.2238</version>
      <protocol>TPP</protocol>
      <action>Reply</action>
      <response_text/>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <at_id>1234</at_id>
          <at_idnum>99999</at_idnum>
          <at_idtype>Ticket</at_idtype>
          <at_description>helpdesk</at_description>
          <at_date xmlns:dt="urn:schemas-microsoft-com:datatypes"
dt:dt="dateTime.tz">2010-06-14T13:58:02.000</at_date>
          <at_filename>example.txt</at_filename>
          <at_file>

```

Content-Type: application/octet-stream;

```
name="tmpzip.zip"
Content-Transfer-Encoding: base64
Content-Disposition: attachment;
  filename="tmpzip.zip"
UEsDBBQAAAAIAEFvzjzJ/06HJgAAACoAAAAALAEQAZXhhbXBsZS50eHQAACAAAA
AAAAAAAAAAAA
UZWayQvLAQBRIzrJC8sBAFGVmSkLywFOVRwATIVDWAsAZQB4AGEAbQBwAGwA
ZQAuAHQAeAB0
ACvJyCxWAKJEhZLU4hKFtMycVIXyzJIMCDczLy2/KDexJDM/Tw8AUesBAhQAFAAAA
AgAQW/O
PMn/TocmAAAAKgAAAAsAIgAAAAAAAAAAgIAAAAAAAAAAGV4YW1wbGUudHh0TIUe
AE5VQ1gIAAAA
ZQB4AGEAbQBwAGwAZQAuAHQAeAB0AFBLBQYAAAAAAQABAFsAAACTAAAA
AA=
  </at_file>
  <at_compressed>Y</at_compressed>
  <at_encodingtype/>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[attachment_Load](#)

attachment_Save XML Example**Input Example:**

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>attachment_Save</action>
      <username>Admin</username>
      <password>password</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cFile type='string'>example.txt</cFile>
        <cFileData type='string'>
          dGhpcyBpcyBhIHRlc3QgZmlsZSB3aXRoIHRlc3QgaW5mb3JtYXRpb24u
        </cFileData>
        <nTypeId type='int'>99999</nTypeId>
        <cType type='string'>ticket</cType>
      </parameters>
      <properties>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <version>7.1.2238</version>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <attachment_Save>true</attachment_Save>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[attachment_Save](#)

call_Delete XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>call_Delete</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cID type='string'>1040</cID>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <call_Delete>true</call_Delete>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[call_Delete](#)

call_New XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>call_New</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <contact>Mickey Melchiondo</contact>
          <number>6629997777</number>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[call_New](#)

call_Save XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>call_Save</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
        <cBody type='string'>called to chit chat</cBody>
        <nTime type='int'>20</nTime>
        <cCallType type='string'>I</cCallType>
        <cContactNumber type='string'>6629997777</cContactNumber>
        <cContactName type='string'>Mickey Melchiondo</cContactName>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <call_Save>true</call_Save>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[call_Save](#)

check_Security XML Example

Input Example:

```
<?xml version="1.0" ?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>webticket</object>
      <action>Check_Security</action>
      <username>admin</username>
      <password>admin</password>
      <logintype type="string">staff</logintype>
      <parameters>
        <cSecurityTag type="string">Form Email-Edit</cSecurityTag>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>webticket</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <Check_Security>true</Check_Security>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[check_Security](#)

customer_Search XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>customer_Search</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cSearchString type='string'>1542</cSearchString>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1542</id>
          <name>Edgar Potter</name>
          <contact>n</contact>
          <phone>323828829393</phone>
          <username>edgar</username>
          <active>H</active>
          <attn/>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
</body>  
</PLAT_XML>
```

Method:

[customer_Search](#)

email_Cancel XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Cancel</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cAction type='string'>edit</cAction>
        <nEmail type='int'>130</nEmail>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <email_Cancel>true</email_Cancel>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[email_Cancel](#)

email_Delete XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Delete</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cID type='string'>116</cID>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <email_Delete>true</email_Delete>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[email_Delete](#)

email_Get_Attachments XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Get_Attachments</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1015</nTypeId>
        <cAction type='string'>view</cAction>
        <nEmail type='int'>122</nEmail>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text>ADODB.RecordSet is empty.</response_text>
      <response_code>0</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[email_Get_Attachments](#)

email_Load XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Load</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1015</nTypeId>
        <cAction type='string'>view</cAction>
        <nEmail type='int'>122</nEmail>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <connhandle>1</connhandle>
          <em_attachments>0</em_attachments>
          <em_bcc></em_bcc>
          <em_body>tggtg\erfg
ergeg</em_body>
          <em_cc></em_cc>
          <em_datereceived>2006-04-21T14:36:16</em_datereceived>
          <em_datesent>2006-04-21T14:36:16</em_datesent>
          <em_from>gtgt</em_from>

```

```

    <em_from_default></em_from_default>
    <em_from_name></em_from_name>
    <em_headers></em_headers>
    <em_id>122</em_id>
    <em_idnum>1015</em_idnum>
    <em_idtype>Ticket</em_idtype>
    <em_rating>0</em_rating>
    <em_sent>N</em_sent>
    <em_subject>[#1015-1093#]</em_subject>
    <em_system>N</em_system>
    <em_thread>0</em_thread>
    <em_timestamp>196902</em_timestamp>
    <em_to>ray@boardtown.com</em_to>
    <em_type>O</em_type>
    <lasterror></lasterror>
    <mode>loaded</mode>
    <old_attachments>0</old_attachments>
    <old_bcc></old_bcc>
    <old_body>tggtg\erfg
ergeg</old_body>
    <old_cc></old_cc>
    <old_datereceived>2006-04-21T14:36:16</old_datereceived>
    <old_datesent>2006-04-21T14:36:16</old_datesent>
    <old_from>gtgt</old_from>
    <old_from_name></old_from_name>
    <old_headers></old_headers>
    <old_id>122</old_id>
    <old_idnum>1015</old_idnum>
    <old_idtype>Ticket</old_idtype>
    <old_rating>0</old_rating>
    <old_sent>N</old_sent>
    <old_subject>[#1015-1093#]</old_subject>
    <old_system>N</old_system>
    <old_thread>0</old_thread>
    <old_to>ray@boardtown.com</old_to>
    <old_type>0</old_type>
    <regkey>ticket_message_object</regkey>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[email_Load XML Example](#)

email_New XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_New</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
        <cAction type='string'>forward</cAction>
        <nEmail type='int'>130</nEmail>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <connhandle>1</connhandle>
          <em_attachments>0</em_attachments>
          <em_bcc></em_bcc>
          <em_body>
            -----Original Message-----
            To: jreinert@tu cows.com
            From: jreinert@tu cows.com
            CC: jreinert@tu cows.com
            Date: 6/16/2006 1:09:53 PM
          </em_body>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Subject: hbr6hy5r6 [#1031-1093#]

-----Original Message-----

To: mills@tucows.com

From: sffsdfsdf

CC:

Date: 6/16/2006 9:28:31 AM

Subject: hbr6hy5r6 [#1031-1093#]

sdfsfergegrsrgerg</em_body>

<em_cc></em_cc>

<em_datereceived>2006-06-28T09:55:21</em_datereceived>

<em_datesent>2006-06-28T09:55:21</em_datesent>

<em_from></em_from>

<em_from_default></em_from_default>

<em_from_name></em_from_name>

<em_headers></em_headers>

<em_id>131</em_id>

<em_idnum>1031</em_idnum>

<em_idtype>Ticket</em_idtype>

<em_rating>0</em_rating>

<em_sent>N</em_sent>

<em_subject>hbr6hy5r6 [#1031-1093#]</em_subject>

<em_system>N</em_system>

<em_thread>0</em_thread>

<em_timestamp>207761</em_timestamp>

<em_to>mils@tucows.com</em_to>

<em_type>O</em_type>

<lasterror></lasterror>

<mode>loaded</mode>

<old_attachments>0</old_attachments>

<old_bcc></old_bcc>

<old_body>

-----Original Message-----

To: jreinert@tucows.com

From: jreinert@tucows.com

CC: jreinert@tucows.com

Date: 6/16/2006 1:09:53 PM

Subject: hbr6hy5r6 [#1031-1093#]

-----Original Message-----

To: mills@tucows.com

From: sffsdfsdf

CC:

Date: 6/16/2006 9:28:31 AM

Subject: hbr6hy5r6 [#1031-1093#]

sdfsfergegrsrgerg</old_body>

<old_cc></old_cc>

<old_datereceived>2006-06-28T09:55:21</old_datereceived>

<old_datesent>2006-06-28T09:55:21</old_datesent>

<old_from></old_from>

<old_from_name></old_from_name>

<old_headers></old_headers>

<old_id>131</old_id>


```
<old_idnum>1031</old_idnum>
<old_idtype>Ticket</old_idtype>
<old_rating>0</old_rating>
<old_sent>N</old_sent>
<old_subject>hbr6hy5r6 [#1031-1093#]</old_subject>
<old_system>N</old_system>
<old_thread>0</old_thread>
<old_to>mils@tucows.com</old_to>
<old_type>0</old_type>
<regkey>ticket_message_object</regkey>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[email_New](#)

email_Save XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Save</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cFrom type='string'>reinert@tucows.com</cFrom>
        <cTo type='string'>reinert@tucows.com</cTo>
        <cCc/>
        <cBcc/>
        <cSubject type='string'>hbr6hy5r6 [#1031-1093#]</cSubject>
        <cBody type='string'>Yup yup</cBody>
        <cAction type='string'>edit</cAction>
        <nEmail type='int'>130</nEmail>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <email_Save>true</email_Save>
        </data_block>
      </attributes>
```

```
</data_block>  
</body>  
</PLAT_XML>
```

Method:

[email_Save](#)

email_Send XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>email_Send</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cFrom type='string'>reinert@tu cows.com</cFrom>
        <cTo type='string'>reinert@tu cows.com</cTo>
        <cCc/>
        <cBcc/>
        <cSubject type='string'>hbr6hy5r6 [#1031-1093#]</cSubject>
        <cBody type='string'>More stuff in this email
```

-----Original Message-----

To: reinert@tu cows.com
From: reinert@tu cows.com
CC: reinert@tu cows.com
Date: 6/16/2006 1:09:53 PM
Subject: hbr6hy5r6 [#1031-1093#]

-----Original Message-----

To: mills@tu cows.com
From: sffsdfsdf
CC:
Date: 6/16/2006 9:28:31 AM
Subject: hbr6hy5r6 [#1031-1093#]

```
sdfsfergegrsrgerg</cBody>
  <cAction type='string'>continue</cAction>
  <nEmail type='int'>131</nEmail>
  <cType type='string'>ticket</cType>
  <nTypeId type='int'>1031</nTypeId>
</parameters>
</data_block>
</body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
```

```
<body>
  <data_block>
    <object>wombat</object>
    <protocol>TPP</protocol>
    <action>REPLY</action>
    <response_text></response_text>
    <response_code>SUCCESS</response_code>
    <is_success>1</is_success>
    <attributes>
      <data_block>
        <email_Send>true</email_Send>
      </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>
```

Method:

[email_Send](#)

get_Option XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>get_Option</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cOptionName type='string'>Ticket Creation-Default Assigned</cOptionName>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <get_Option>2</get_Option>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[get_Option](#)

KB_Get_Article XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Get_Article</action>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nId type='int'>1004</nId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <KB_Get_Article>&lt;?xml version = "1.0" encoding="Windows-1252"
            standalone="yes"?&gt;&lt;VFPData&gt;
            &lt;title&gt;
            &lt;kba_title&gt;art&lt;/kba_title&gt;
            &lt;/title&gt;
            &lt;section&gt;
            &lt;kbsec_section_name&gt;Summary&lt;/kbsec_section_name&gt;
            &lt;kbsec_body&gt;art&lt;/kbsec_body&gt;
            &lt;/section&gt;
            &lt;section&gt;
            &lt;kbsec_section_name&gt;Body&lt;/kbsec_section_name&gt;
            &lt;kbsec_body&gt;art&lt;/kbsec_body&gt;
            &lt;/section&gt;
            &lt;keyword&gt;

```

```
<kbkey_word>art</kbkey_word>
</keyword>
<attachment/>
<issue>
<kb_id>1006</kb_id>
<kb_title>fifth</kb_title>
</issue>
<VFPDData></KB_Get_Article>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[KB_Get_Article](#)

KB_Get_Attachment XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Get_Attachment</action>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cId type='string'>129</cId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <at_id>129</at_id>
          <at_idnum>1001</at_idnum>
          <at_idtype>KB-Issue</at_idtype>
          <at_description>dfd</at_description>
          <at_date>2005-03-07T10:26:14</at_date>
          <at_filename>base.ico</at_filename>
          <at_file><![CDATA[Content-Type: application/octet-stream;
name="tmpzip.zip"
Content-Transfer-Encoding: base64
Content-Disposition: attachment;
filename="tmpzip.zip"
UESDBAoAAAAAAC1TZzIAAAAAAAAAAAAAAAAAAXAFwAUHJvZ3JhbSBGaWxlcY9Qb
GF0eXB1cy8KACAAAAAAAAAAAAAAAAAbzn6/yLFAQBvOfr/IsUBgCG7Fa6MxAFOVTQA
TIVDWBcAUABYAG8AZwByAGEAbQAgAEYAaQBsAGUAcwBcAFaAbABhAHQAeQB

```

```
wAHUAcwBcAFBLAwQUAAACACjeaEoRORiiEUBAAD+AgAACAA+AGJhc2UuaWNv
CgAgAAAAAAAAAAAAAAAAAC1pwH+zvwGAoRxiswPFAQBsGBuujMQBTIUWAE5VQ1gIA
GIAYQBzAGUALgBpAGMAbwB1krFqwzAQhs91QwvBJKW0W3HGjgXjKRT3EbwICiHP
Ei95n8LR6RY/gj14MgcZO2b0EKyeJDURaznp9+k7SaeTEUAghbVagrG/O4BX8e+ilehLFM
A9XNtyQoXtUBTOmSaDsizFm4i2HbR2zjQTMh+A+Y9LknxYNyeyPiS0ASKaKaWqligZO
BXetoRoGGntGNHOzzH55EapZ3T7Q0RmCbygywsRW35SQ/ER7Q0vz1dC3HKTD+XYE7
+5CenCyWyvNoTn/aRq4d984DbIolcbHrnZcq3U2y0Gc7pScuSYkGV+xmN9NiALYMr5hXl
NmPpMhP581Mov85mFwefWTw9QcVX5LBVOOOLJcllwxuEU4RFuWL87ZV3WxUeAxag
OIBZlvTyRHgJ5JaMMw86XNirkKZWh1ocH8YPM+LBwOsZOXab1SdRrJ7F/UEsBAhQAC
gAAAAAALVNnMgAAAAAAAAAAAAAAAAABcAOgAAAAAAAAAAQAAAAAAAAAFBy
b2dyYW0gRmlsZXNmUGxhdHlwdXMvTIU2AE5VQ1gXAAAAUABYAG8AZwByAGEAb
QAgAEYAaQBsAGUAcwBcAFAAABABhAHQAeQBwAHUAcwBcAFBLAQIUABQAAAAI
AKN5oShE6uKIRQEAAAP4CAAAIABwAAAAAAAAAAIAAAAJEAAABiYXNlmljb05VG
ABOVUNYCAAAAGIAAYQBzAGUALgBpAGMAbwBQSwUGAAAAAAIAAgDRAAAAO
gIAAAAA]]></at_file>
<at_compressed>Y</at_compressed>
<at_encodingtype>NULL</at_encodingtype>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[KB_Get_Attachment](#)

KB_Get_Issue XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Get_Issue</action>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nId type='int'>1001</nId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <KB_Get_Issue>&lt;?xml version = "1.0" encoding="Windows-1252"
standalone="yes"?&gt;
&lt;VFPData&gt;
&lt;title&gt;
&lt;kbi_title&gt;first no results will be found in here&lt;/kbi_title&gt;
&lt;/title&gt;
&lt;section&gt;
&lt;kbsec_section_name&gt;Summary&lt;/kbsec_section_name&gt;
&lt;kbsec_body&gt;first no results will be found in here&lt;/kbsec_body&gt;
&lt;/section&gt;
&lt;section&gt;
&lt;kbsec_section_name&gt;Body&lt;/kbsec_section_name&gt;
&lt;kbsec_body&gt;first no results will be found in here&lt;/kbsec_body&gt;
&lt;/section&gt;

```

```
<keyword>
<kbkey_word>results</kbkey_word>
</keyword>
<attachment>
<at_id>129</at_id>
<at_description>dfd</at_description>
<at_filename>base.ico</at_filename>
</attachment>
<attachment>
<at_id>130</at_id>
<at_description>log</at_description>
<at_filename>authnet30.log</at_filename>
</attachment>
<article/>
</VFPData></KB_Get_Issue>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[KB_Get_Issue](#)

KB_Get_Titles XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Get_Titles</action>
      <logintype type='string'>staff</logintype>
      <parameters>
        <aList type='array'>
          <row>
            <type type='string'>issue</type>
            <id type='string'>1006</id>
          </row>
          <row>
            <type type='string'>article</type>
            <id type='string'>1005</id>
          </row>
          <row>
            <type type='string'>issue</type>
            <id type='string'>1005</id>
          </row>
          <row>
            <type type='string'>article</type>
            <id type='string'>1004</id>
          </row>
          <row>
            <type type='string'>issue</type>
            <id type='string'>1001</id>
          </row>
          <row>
            <type type='string'>issue</type>
            <id type='string'>1002</id>
          </row>
          <row>
            <type type='string'>issue</type>
            <id type='string'>1004</id>
          </row>
          <row>
            <type type='string'>article</type>
            <id type='string'>1073</id>
          </row>
          <row>
            <type type='string'>article</type>
            <id type='string'>1074</id>
          </row>
        </aList>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

```

        </row>
        <row>
            <type type='string'>issue</type>
            <id type='string'>1125</id>
        </row>
    </aList>
</parameters>
</data_block>
</body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <type>issue</type>
          <id>1006</id>
          <title>fifth</title>
        </data_block>
        <data_block>
          <type>issue</type>
          <id>1005</id>
          <title>Fourth</title>
        </data_block>
        <data_block>
          <type>article</type>
          <id>1004</id>
          <title>art</title>
        </data_block>
        <data_block>
          <type>issue</type>
          <id>1001</id>
          <title>first no results will be found in here</title>
        </data_block>
        <data_block>
          <type>issue</type>
          <id>1002</id>
          <title>second</title>
        </data_block>
        <data_block>

```

```
        <type>issue</type>
        <id>1004</id>
        <title>Third</title>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[KB_Get Titles](#)

KB_Get_Tree XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Get_Tree</action>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>  
<PLAT_XML>  
  <header></header>  
  <body>  
    <data_block>  
      <object>wombat</object>  
      <protocol>TPP</protocol>  
      <action>REPLY</action>  
      <response_text></response_text>  
      <response_code>SUCCESS</response_code>  
      <is_success>1</is_success>  
      <attributes>  
        <data_block>  
          <KB_Get_Tree>&lt;kbtree&gt;&lt;kbnode&gt;&lt;id&gt;1001&lt;/id&gt;&lt;title  
&gt;&first no results will be found in  
here&lt;/title&gt;&lt;type&gt;issue&lt;/type&gt;&lt;kbchildren/&gt;&lt;kbnode&gt;&lt;kbnod  
e&gt;&lt;id&gt;1001&lt;/id&gt;&lt;title&gt;First&lt;/title&gt;&lt;type&gt;folder&lt;/type&gt;  
&lt;kbchildren&gt;&lt;kbnode&gt;&lt;id&gt;1002&lt;/id&gt;&lt;title&gt;Second&lt;/title&gt;  
&lt;type&gt;folder&lt;/type&gt;&lt;kbchildren&gt;&lt;kbnode&gt;&lt;id&gt;1002&lt;/id&gt;  
&lt;title&gt;second&lt;/title&gt;&lt;type&gt;issue&lt;/type&gt;&lt;kbchildren/&gt;&lt;kbnod  
e&gt;&lt;kbnode&gt;&lt;id&gt;1006&lt;/id&gt;&lt;title&gt;Third&lt;/title&gt;&lt;type&gt;fol  
der&lt;/type&gt;&lt;kbchildren&gt;&lt;kbnode&gt;&lt;id&gt;1004&lt;/id&gt;&lt;title&gt;Thir  
d&lt;/title&gt;&lt;type&gt;issue&lt;/type&gt;&lt;kbchildren/&gt;&lt;kbnode&gt;&lt;kbchildr  
en&gt;&lt;kbnode&gt;&lt;kbnode&gt;&lt;id&gt;1008&lt;/id&gt;&lt;title&gt;Fourth&lt;/title&  
gt;&lt;type&gt;folder&lt;/type&gt;&lt;kbchildren&gt;&lt;kbnode&gt;&lt;id&gt;1005&lt;/id&g  
t;&lt;title&gt;Fourth&lt;/title&gt;&lt;type&gt;issue&lt;/type&gt;&lt;kbchildren/&gt;&lt;kno  
de&gt;&lt;kbnode&gt;&lt;id&gt;1006&lt;/id&gt;&lt;title&gt;fifth&lt;/title&gt;&lt;type&gt;iss  
ue&lt;/type&gt;&lt;kbchildren&gt;&lt;kbnode&gt;&lt;id&gt;1004&lt;/id&gt;&lt;title&gt;art&l  
t;/title&gt;&lt;type&gt;article&lt;/type&gt;&lt;kbnode&gt;&lt;kbchildren&gt;&lt;kbnode&gt;  
&lt;kbchildren&gt;&lt;kbnode&gt;&lt;kbchildren&gt;&lt;kbnode&gt;&lt;kbchildren&gt;&
```



```
lt;/kbnode>&lt;/kbtree>&lt;
</KB_Get_Tree>
  </data_block>
    </attributes>
  </data_block>
</body>
</PLAT_XML>
```

Method:

[KB_Get_Tree](#)

KB_Search XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>KB_Search</action>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cQuery type='string'>%</cQuery>
        <bKeyword type='boolean'>true</bKeyword>
        <bTitle type='boolean'>true</bTitle>
        <bBody type='boolean'>true</bBody>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1001</id>
          <title>first no results will be found in here</title>
          <type>issue</type>
        </data_block>
        <data_block>
          <id>1002</id>
          <title>second</title>
          <type>issue</type>
        </data_block>
        <data_block>
          <id>1004</id>
```

```
        <title>Third</title>
        <type>issue</type>
    </data_block>
    <data_block>
        <id>1005</id>
        <title>Fourth</title>
        <type>issue</type>
    </data_block>
    <data_block>
        <id>1006</id>
        <title>fifth</title>
        <type>issue</type>
    </data_block>
    <data_block>
        <id>1004</id>
        <title>art</title>
        <type>article</type>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[KB Search](#)

Login XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>Login</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cUsername type='string'>Admin</cUsername>
        <cPassword type='string'>admin</cPassword>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <Login>1</Login>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[Login](#)

note_Delete XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>note_Delete</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cID type='string'>1120</cID>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <note_Delete>true</note_Delete>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[note_Delete](#)

note_Load XML Example

Input Example:

```

<?xml version="1.0" ?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>webticket</object>
      <action>note_Load</action>
      <username>admin</username>
      <password>admin</password>
      <logintype type="string">staff</logintype>
      <parameters>
        <nIndex type="int">1</nIndex>
        <cType type="string">ticket</cType>
        <nTypeId type="int">1007</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>webticket</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <connhandle>2</connhandle>
          <existing>0</existing>
          <lasterror></lasterror>
          <mode>loaded</mode>
          <modified>0</modified>
          <note_body>the note message</note_body>
          <note_body_display>the note message</note_body_display>
          <note_date_created>2006-06-20T15:05:38</note_date_created>
          <note_id>1118</note_id>
          <note_idnum>1007</note_idnum>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
<note_idtype>TICKET</note_idtype>
<note_staff_id>1</note_staff_id>
<note_staff_name>Admin</note_staff_name>
<note_visible>Y</note_visible>
<old_body>the note message</old_body>
<old_date_created>2006-06-20T15:05:38</old_date_created>
<old_id>1118</old_id>
<old_idnum>1007</old_idnum>
<old_idtype>TICKET</old_idtype>
<old_staff_id>1</old_staff_id>
<old_visible>Y</old_visible>
<regkey>ticket_note_object</regkey>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[note_Load](#)

note_Save XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>note_Save</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cBody type='string'>customer will never see this message</cBody>
        <cVisible type='string'>N</cVisible>
        <cType type='string'>ticket</cType>
        <nTypeId type='int'>1031</nTypeId>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <note_Save>true</note_Save>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[note_Save](#)

sql_Execute XML Example

Input Example:

```

<?xml version="1.0" ?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>webticket</object>
      <action>sql_Execute</action>
      <username>admin</username>
      <password>admin</password>
      <logintype type="string">staff</logintype>
      <parameters>
        <cSQL type="string">select * from customer where id = 1479</cSQL>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>webticket</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <id>1479</id>
          <name>Ween O'Reilley</name>
          <guarantor>0</guarantor>
          <date>2005-05-02T00:00:00</date>
          <active>Y</active>
          <taxid>NULL</taxid>
          <staffnum>1</staffnum>
          <attn>Mickey Melchiondo</attn>
          <addr1>109 Captain Fantasy Drive</addr1>
          <addr2>Suite "P"</addr2>
          <city>New Hope</city>
          <state>PA</state>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

<country>US</country>
<zip>543219876</zip>
<phone>6629997777</phone>
<fax>9499599999</fax>
<username>dude1</username>
<password>dude1</password>
<email>pmills@tucows.com</email>
<stmtmethod>CREDIT CARD</stmtmethod>
<laststmt>2005-05-02T00:00:00</laststmt>
<nextstmt>2005-05-02T00:00:00</nextstmt>
<custbillday>2</custbillday>
<nostatement>N</nostatement>
<nolatenotice>N</nolatenotice>
<nodeactivate>N</nodeactivate>
<nocloseout>N</nocloseout>
<noreceipt>Y</noreceipt>
<latedate>NULL</latedate>
<deactivatedate>NULL</deactivatedate>
<referralid>1711</referralid>
<referral>NULL</referral>
<comment>jablonski</comment>
<cctype>DISCOVER</cctype>
<ccnumber>ntanasaeokkkddssrikiotwdpengniw</ccnumber>
<ccdate>2010-12-31T00:00:00</ccdate>
<cuskey>NULL</cuskey>
<timeleft>2520000</timeleft>
<blockuser>Y</blockuser>
<blocktype>1</blocktype>
<shellid>1</shellid>
<websignup>Y</websignup>
<ponumber>NULL</ponumber>
<routenumber>NULL</routenumber>
<damount>NULL</damount>
<dtype>NULL</dtype>
<salesid>NULL</salesid>
<lastusername>NULL</lastusername>
<latefeetype>N</latefeetype>
<latefeeamt>0</latefeeamt>
<lastlatefee>NULL</lastlatefee>
<c_pop_id>1</c_pop_id>
<lastrcpt>2005-09-21T16:26:15</lastrcpt>
<bank_acct_type>NULL</bank_acct_type>
<bank_name>NULL</bank_name>
<storeid>1</storeid>
<blacklist>N</blacklist>
<gracedate>NULL</gracedate>
<htmlemail>Y</htmlemail>
<closeoutdate>2005-09-14T14:37:09</closeoutdate>
<reg_code_number>NULL</reg_code_number>
<account_type>PPP</account_type>
<cc_type>NULL</cc_type>

```

```

    <issuenum>NULL</issuenum>
    <startdate>NULL</startdate>
    <gift>NULL</gift>
    <stmtamnt>NULL</stmtamnt>
    <osrsusername>urkolastdsukepsr</osrsusername>
    <osrspassword>dgdfltnunraedtn</osrspassword>
    <cpeid>NULL</cpeid>
    <c_creditlimit_amount>NULL</c_creditlimit_amount>
    <c_creditlimit_type>NULL</c_creditlimit_type>
    <locked>N</locked>
    <failures>0</failures>
    <jobtitle>NULL</jobtitle>
    <collection>NULL</collection>
    <freeradius_group>NULL</freeradius_group>
    <freeradius_staticip>NULL</freeradius_staticip>
    <oldccnumber>4111111111111111</oldccnumber>
    <rockettype>NULL</rockettype>
    <acctnumber>NULL</acctnumber>
    <npo>NULL</npo>
    <promocode>NULL</promocode>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[sql_Execute](#)

ticket_Change_Status XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Change_Status</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
        <nProgression type='int'>1002</nProgression>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ticket_Change_Status>true</ticket_Change_Status>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ticket_Change_Status](#)

ticket_Delete XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Delete</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
        <bDeleteEmails type='boolean'>true</bDeleteEmails>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ticket_Delete>true</ticket_Delete>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ticket_Delete](#)

ticket_Get_Access_Settings XML Example**Input Example**

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_get_Access_Settings</action>
      <username>John Smith</username>
      <password>b</password>
      <logintype>staff</logintype>
      <parameters>
        <nTicket type='int'>25971</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tag>Menu Helpdesk-Ticket-New</tag>
          <value>1</value>
        </data_block>
        <data_block>
          <tag>Menu Helpdesk-Calls-Handle Call / Action</tag>
          <value>1</value>
        </data_block>
        <data_block>
          <tag>Menu Helpdesk-Ticket-View</tag>
          <value>1</value>
        </data_block>
      </data_block>
    </body>
  </PLAT_XML>

```

```

    <tag>Menu Helpdesk-Ticket-Edit</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Tree-Reassign All Button</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Tree-Delete Button</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Tree-Reassign Button</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Tree-Stafflist</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Hidden</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Change Status</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Change Category</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Change Priority</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Change Type</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Steal Button</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Ticket Manager-Reassign Button</tag>
    <value>1</value>
</data_block>
<data_block>
    <tag>Form Email-Edit</tag>
    <value>1</value>
</data_block>

```

```

<data_block>
  <tag>Form Ticket Manager-Delete Email</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Delete Call</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Delete Attachment</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Progression Buttons</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Problem</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Solution</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Email Controls</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Delete Note</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Reply-To</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Set Customer</tag>
  <value>1</value>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method

[ticket_get_Access_Settings](#)

ticket_Get_Attachments XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Attachments</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text>ADODB.RecordSet is empty.</response_text>
      <response_code>0</response_code>
      <is_success>0</is_success>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ticket_Get_Atatchments](#)

ticket_Get_Calls XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Calls</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <call_id>1060</call_id>
          <call_date>2006-06-28T10:03:36</call_date>
          <call_type>I</call_type>
          <call_number>6629997777</call_number>
          <call_contact_name>Mickey Melchiondo</call_contact_name>
          <call_seconds>00:00:20</call_seconds>
          <call_staff_name>Admin</call_staff_name>
          <call_note>called to chit chat</call_note>
        </data_block>
        <data_block>
          <call_id>1056</call_id>
          <call_date>2006-06-16T09:14:49</call_date>

```

```
<call_type>I</call_type>
<call_number>6629997777</call_number>
<call_contact_name>Mickey Melchiondo</call_contact_name>
<call_seconds>00:00:09</call_seconds>
<call_staff_name>Admin</call_staff_name>
<call_note>small message</call_note>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticket_Get_Calls](#)

ticket_Get_Category_List XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Category_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>Support Question</displayname>
              <displayvalue>1006</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Business Sales</displayname>
              <displayvalue>1003</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>General</displayname>
              <displayvalue>1002</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Sales</displayname>

```

```
        <displayvalue>1004</displayvalue>
      </display_fields_item>
    <display_fields_item>
      <displayname>Feature Request</displayname>
      <displayvalue>1005</displayvalue>
    </display_fields_item>
    <display_fields_item>
      <displayname>Other</displayname>
      <displayvalue>1001</displayvalue>
    </display_fields_item>
  </display_fields>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticket_Get_Category_List](#)

ticket_Get_Customer_Info XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Customer_Info</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
      </parameters>
      <properties>
        <tkr_id type='int'>1015</tkr_id>
      </properties>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>Customer ID</displayname>
              <displayvalue>1479</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Customer Name</displayname>
              <displayvalue>Ween O'Reilley</displayvalue>
            </display_fields_item>
          </display_fields>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

        <display_fields_item>
          <displayname>Attn</displayname>
          <displayvalue>Mickey Melchiondo</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Addr1</displayname>
          <displayvalue>109 Captain Fantasy Drive</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Addr2</displayname>
          <displayvalue>Suite "P"</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>City</displayname>
          <displayvalue>New Hope</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>State</displayname>
          <displayvalue>PA</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Zip</displayname>
          <displayvalue>543-219</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Phone</displayname>
          <displayvalue>(662)999-7777</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Fax</displayname>
          <displayvalue>(949)959-9999</displayvalue>
        </display_fields_item>
        <display_fields_item>
          <displayname>Email</displayname>
          <displayvalue>pmills@tucows.com</displayvalue>
        </display_fields_item>
      </display_fields>
    </data_block>
  </attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[ticket_Get_Customer_Info](#)

ticket_Get_Emails XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Emails</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <em_id>122</em_id>
          <em_date>2006-04-21T14:36:16</em_date>
          <em_type>O</em_type>
          <em_sent>N</em_sent>
          <em_subject>[#1015-1093#]</em_subject>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:

[ticket_Get_Emails](#)

ticket_Get_History XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_History</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <hist_id>1968</hist_id>
          <hist_date>2006-06-26T11:14:13</hist_date>
          <hist_staff_id>1</hist_staff_id>
          <hist_staff_name>Admin</hist_staff_name>
          <hist_action>Ticket Stolen from Justin Thornton</hist_action>
        </data_block>
        <data_block>
          <hist_id>1967</hist_id>
          <hist_date>2006-06-26T11:14:12</hist_date>
          <hist_staff_id>1</hist_staff_id>
          <hist_staff_name>Admin</hist_staff_name>
          <hist_action>Reassigned from Justin Thornton (Staff #47) to Admin (Staff

```

```

#1)</hist_action>
</data_block>
<data_block>
  <hist_id>1838</hist_id>
  <hist_date>2006-04-26T12:17:01</hist_date>
  <hist_staff_id>-1</hist_staff_id>
  <hist_staff_name>Customer</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1837</hist_id>
  <hist_date>2006-04-26T11:03:33</hist_date>
  <hist_staff_id>-1</hist_staff_id>
  <hist_staff_name>Customer</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1836</hist_id>
  <hist_date>2006-04-26T11:01:53</hist_date>
  <hist_staff_id>-1</hist_staff_id>
  <hist_staff_name>Customer</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1835</hist_id>
  <hist_date>2006-04-26T11:00:42</hist_date>
  <hist_staff_id>-1</hist_staff_id>
  <hist_staff_name>Customer</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1834</hist_id>
  <hist_date>2006-04-26T10:59:31</hist_date>
  <hist_staff_id>-1</hist_staff_id>
  <hist_staff_name>Customer</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1830</hist_id>
  <hist_date>2006-04-25T16:00:02</hist_date>
  <hist_staff_id>1</hist_staff_id>
  <hist_staff_name>Admin</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>
<data_block>
  <hist_id>1829</hist_id>
  <hist_date>2006-04-25T15:59:54</hist_date>
  <hist_staff_id>1</hist_staff_id>
  <hist_staff_name>Admin</hist_staff_name>
  <hist_action>Note Created</hist_action>
</data_block>

```

```
<data_block>
  <hist_id>1828</hist_id>
  <hist_date>2006-04-25T15:59:29</hist_date>
  <hist_staff_id>1</hist_staff_id>
  <hist_staff_name>Admin</hist_staff_name>
  <hist_action>Call / Action Created</hist_action>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticket_Get_History](#)

ticket_Get_Notes XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Notes</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <itemcount>8</itemcount>
          <items>
            <items_item>
              <connhandle>1</connhandle>
              <existing>0</existing>
              <lasterror></lasterror>
              <mode>loaded</mode>
              <modified>0</modified>
              <note_body>customer will never see this message</note_body>
              <note_body_display>customer will never see this
message</note_body_display>
              <note_date_created>2006-06-28T10:04:32</note_date_created>
```



```

<note_id>1122</note_id>
<note_idnum>1031</note_idnum>
<note_idtype>TICKET</note_idtype>
<note_staff_id>1</note_staff_id>
<note_staff_name>Admin</note_staff_name>
<note_visible>N</note_visible>
<old_body>customer will never see this message</old_body>
<old_date_created>2006-06-28T10:04:32</old_date_created>
<old_id>1122</old_id>
<old_idnum>1031</old_idnum>
<old_idtype>TICKET</old_idtype>
<old_staff_id>1</old_staff_id>
<old_visible>N</old_visible>
<regkey>ticket_note_object</regkey>
</items_item>
<items_item>
  <connhandle>1</connhandle>
  <existing>0</existing>
  <lasterror></lasterror>
  <mode>loaded</mode>
  <modified>0</modified>
  <note_body>sssfsf</note_body>
  <note_body_display>sssfsf</note_body_display>
  <note_date_created>2006-06-21T13:12:25</note_date_created>
  <note_id>1119</note_id>
  <note_idnum>1031</note_idnum>
  <note_idtype>TICKET</note_idtype>
  <note_staff_id>-1</note_staff_id>
  <note_staff_name>Customer</note_staff_name>
  <note_visible>Y</note_visible>
  <old_body>sssfsf</old_body>
  <old_date_created>2006-06-21T13:12:25</old_date_created>
  <old_id>1119</old_id>
  <old_idnum>1031</old_idnum>
  <old_idtype>TICKET</old_idtype>
  <old_staff_id>-1</old_staff_id>
  <old_visible>Y</old_visible>
  <regkey>ticket_note_object</regkey>
</items_item>
<items_item>
  <connhandle>1</connhandle>
  <existing>0</existing>
  <lasterror></lasterror>
  <mode>loaded</mode>
  <modified>0</modified>
  <note_body>lil' note</note_body>
  <note_body_display>lil' note</note_body_display>
  <note_date_created>2006-06-16T09:30:48</note_date_created>
  <note_id>1117</note_id>
  <note_idnum>1031</note_idnum>
  <note_idtype>TICKET</note_idtype>

```

```

    <note_staff_id>-1</note_staff_id>
    <note_staff_name>Customer</note_staff_name>
    <note_visible>Y</note_visible>
    <old_body>lil' note</old_body>
    <old_date_created>2006-06-16T09:30:48</old_date_created>
    <old_id>1117</old_id>
    <old_idnum>1031</old_idnum>
    <old_idtype>TICKET</old_idtype>
    <old_staff_id>-1</old_staff_id>
    <old_visible>Y</old_visible>
    <regkey>ticket_note_object</regkey>
</items_item>
<items_item>
    <connhandle>1</connhandle>
    <existing>0</existing>
    <lasterror></lasterror>
    <mode>loaded</mode>
    <modified>0</modified>
    <note_body>big Note</note_body>
    <note_body_display>big Note</note_body_display>
    <note_date_created>2006-06-16T09:22:18</note_date_created>
    <note_id>1116</note_id>
    <note_idnum>1031</note_idnum>
    <note_idtype>TICKET</note_idtype>
    <note_staff_id>1</note_staff_id>
    <note_staff_name>Admin</note_staff_name>
    <note_visible>Y</note_visible>
    <old_body>big Note</old_body>
    <old_date_created>2006-06-16T09:22:18</old_date_created>
    <old_id>1116</old_id>
    <old_idnum>1031</old_idnum>
    <old_idtype>TICKET</old_idtype>
    <old_staff_id>1</old_staff_id>
    <old_visible>Y</old_visible>
    <regkey>ticket_note_object</regkey>
</items_item>
<items_item>
    <connhandle>1</connhandle>
    <existing>0</existing>
    <lasterror></lasterror>
    <mode>loaded</mode>
    <modified>0</modified>
    <note_body>huh???</note_body>
    <note_body_display>huh???</note_body_display>
    <note_date_created>2006-04-26T10:54:26</note_date_created>
    <note_id>1103</note_id>
    <note_idnum>1031</note_idnum>
    <note_idtype>TICKET</note_idtype>
    <note_staff_id>-1</note_staff_id>
    <note_staff_name>Customer</note_staff_name>
    <note_visible>N</note_visible>

```

```

<old_body>huh???
```

`</old_body>
<old_date_created>2006-04-26T10:54:26</old_date_created>
<old_id>1103</old_id>
<old_idnum>1031</old_idnum>
<old_idtype>TICKET</old_idtype>
<old_staff_id>-1</old_staff_id>
<old_visible>N</old_visible>
<regkey>ticket_note_object</regkey>
</items_item>
<items_item>
 <connhandle>1</connhandle>
 <existing>0</existing>
 <lasterror></lasterror>
 <mode>loaded</mode>
 <modified>0</modified>
 <note_body>check</note_body>
 <note_body_display>check</note_body_display>
 <note_date_created>2006-04-26T10:54:11</note_date_created>
 <note_id>1102</note_id>
 <note_idnum>1031</note_idnum>
 <note_idtype>TICKET</note_idtype>
 <note_staff_id>-1</note_staff_id>
 <note_staff_name>Customer</note_staff_name>
 <note_visible>N</note_visible>
 <old_body>check</old_body>
 <old_date_created>2006-04-26T10:54:11</old_date_created>
 <old_id>1102</old_id>
 <old_idnum>1031</old_idnum>
 <old_idtype>TICKET</old_idtype>
 <old_staff_id>-1</old_staff_id>
 <old_visible>N</old_visible>
 <regkey>ticket_note_object</regkey>
</items_item>
<items_item>
 <connhandle>1</connhandle>
 <existing>0</existing>
 <lasterror></lasterror>
 <mode>loaded</mode>
 <modified>0</modified>
 <note_body>Why is everything in bold? :)</note_body>
 <note_body_display>Why is everything in bold? :)</note_body_display>
<note_date_created>2006-04-11T14:10:25</note_date_created>
 <note_id>1098</note_id>
 <note_idnum>1031</note_idnum>
 <note_idtype>TICKET</note_idtype>
 <note_staff_id>1</note_staff_id>
 <note_staff_name>Admin</note_staff_name>
 <note_visible>N</note_visible>
 <old_body>Why is everything in bold? :)</old_body>
 <old_date_created>2006-04-11T14:10:25</old_date_created>
 <old_id>1098</old_id>`

```

        <old_idnum>1031</old_idnum>
        <old_idtype>TICKET</old_idtype>
        <old_staff_id>1</old_staff_id>
        <old_visible>N</old_visible>
        <regkey>ticket_note_object</regkey>
    </items_item>
    <items_item>
        <connhandle>1</connhandle>
        <existing>0</existing>
        <lasterror></lasterror>
        <mode>loaded</mode>
        <modified>0</modified>
        <note_body>This is a test note.</note_body>
        <note_body_display>This is a test note.</note_body_display>
        <note_date_created>2005-10-28T16:39:05</note_date_created>
        <note_id>1087</note_id>
        <note_idnum>1031</note_idnum>
        <note_idtype>TICKET</note_idtype>
        <note_staff_id>-1</note_staff_id>
        <note_staff_name>Customer</note_staff_name>
        <note_visible>Y</note_visible>
        <old_body>This is a test note.</old_body>
        <old_date_created>2005-10-28T16:39:05</old_date_created>
        <old_id>1087</old_id>
        <old_idnum>1031</old_idnum>
        <old_idtype>TICKET</old_idtype>
        <old_staff_id>-1</old_staff_id>
        <old_visible>Y</old_visible>
        <regkey>ticket_note_object</regkey>
    </items_item>
</items>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[ticket_Get_Notes](#)

ticket_Get_Priority_List XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Priority_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>Low</displayname>
              <displayvalue>1001</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Normal</displayname>
              <displayvalue>1004</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>High</displayname>
              <displayvalue>1003</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Urgent</displayname>

```

```
        <displayvalue>1002</displayvalue>
      </display_fields_item>
    </display_fields>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticket_Get_Priority_List](#)

ticket_get_Security_Settings XML Example**Input Example**

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_get_Security_Settings</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters></parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tag>Menu Helpdesk-Ticket-New</tag>
          <value>1</value>
        </data_block>
        <data_block>
          <tag>Menu Helpdesk-Calls-Handle Call / Action</tag>
          <value>1</value>
        </data_block>
        <data_block>
          <tag>Menu Helpdesk-Ticket-View</tag>
          <value>1</value>
        </data_block>
        <data_block>
          <tag>Menu Helpdesk-Ticket-Edit</tag>
          <value>1</value>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

</data_block>
<data_block>
  <tag>Form Ticket Tree-Reassign All Button</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Tree-Delete Button</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Tree-Reassign Button</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Tree-Stafflist</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Hidden</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Change Status</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Change Category</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Change Priority</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Change Type</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Steal Button</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Reassign Button</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Email-Edit</tag>
  <value>1</value>
</data_block>
<data_block>
  <tag>Form Ticket Manager-Delete Email</tag>

```



```

        <value>1</value>
    </data_block>
    <data_block>
        <tag>Form Ticket Manager-Delete Call</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Form Ticket Manager-Delete Attachment</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Progression Buttons</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Problem</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Solution</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Email Controls</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Delete Note</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Reply-To</tag>
        <value>1</value>
    </data_block>
    <data_block>
        <tag>Set Customer</tag>
        <value>1</value>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method

[ticket_get_Security_Settings](#)

ticket_Get_Status_List XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Status_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>New</displayname>
              <displayvalue>1004</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Open</displayname>
              <displayvalue>1003</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Suspended</displayname>
              <displayvalue>1002</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Closed</displayname>
```

```
        <displayvalue>1001</displayvalue>
      </display_fields_item>
    </display_fields>
  </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticket_Get_Status_List](#)

ticket_Get_Status_Progression_List XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Status_Progression_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>Close</displayname>
              <displayvalue>1001</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Suspend</displayname>
              <displayvalue>1004</displayvalue>
            </display_fields_item>
          </display_fields>
        </data_block>
      </attributes>
```

```
</data_block>  
</body>  
</PLAT_XML>
```

Method:

[ticket_Get_Status_Progression_List](#)

ticket_get_Ticket_Info XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_get_Ticket_Info</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
        <nType type='int'>1</nType>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>Assigned Staff</displayname>
              <displayvalue>Admin</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Created by</displayname>
              <displayvalue>Admin</displayvalue>
            </display_fields_item>
            <display_fields_item>
              <displayname>Knowledge Base ID</displayname>
```

```

        <displayvalue>0</displayvalue>
    </display_fields_item>
    <display_fields_item>
        <displayname>Last Updated By</displayname>
        <displayvalue>Admin</displayvalue>
    </display_fields_item>
    <display_fields_item>
        <displayname>Last Accessed</displayname>
        <displayvalue>6/28/2006 10:42:25 AM</displayvalue>
    </display_fields_item>
</display_fields>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[ticket_get_Ticket_Info](#)

ticket_Get_Type_List XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Get_Type_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <display_fields>
            <display_fields_item>
              <displayname>External</displayname>
              <displayvalue>1002</displayvalue>
            </display_fields_item>
          </display_fields>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ticket_Get_Type_List](#)

ticket_Load XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Load</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1015</nTicket>
        <bLoadExtra type='boolean'>true</bLoadExtra>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <security_level>edit</security_level>
          <tkc_category>1003</tkc_category>
          <tkc_category_access>1</tkc_category_access>
          <tkc_category_name>Business Sales</tkc_category_name>
          <tkc_company_access>1</tkc_company_access>
          <tkc_contact>N</tkc_contact>
          <tkc_count_attachments>0</tkc_count_attachments>
          <tkc_count_calls>2</tkc_count_calls>
          <tkc_count_messages>1</tkc_count_messages>
          <tkc_created_by>1</tkc_created_by>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```

<ticket_created_by_name>Admin</ticket_created_by_name>
<ticket_customer_id>1479</ticket_customer_id>
<ticket_customer_name>Ween O'Reilley</ticket_customer_name>
<ticket_date_entered>2005-02-09T12:48:04</ticket_date_entered>
<ticket_email>ray@boardtown.com</ticket_email>
<ticket_hidden>N</ticket_hidden>
<ticket_id>1015</ticket_id>
<ticket_knowledgebase_id>0</ticket_knowledgebase_id>
<ticket_knowledgebase_type></ticket_knowledgebase_type>
<ticket_last_assigned>2006-06-26T11:14:12</ticket_last_assigned>
<ticket_last_category_change>2005-02-09T12:48:04</ticket_last_category_change>
<ticket_last_escalated>2005-02-09T12:48:04</ticket_last_escalated>
<ticket_last_status_change>2005-02-09T12:48:04</ticket_last_status_change>
<ticket_last_type_change>2005-02-09T12:48:04</ticket_last_type_change>
<ticket_last_updated>2006-06-26T11:14:12</ticket_last_updated>
<ticket_last_updated_by>1</ticket_last_updated_by>
<ticket_last_updated_by_name>Admin</ticket_last_updated_by_name>
<ticket_modified>N</ticket_modified>
<ticket_priority>1004</ticket_priority>
<ticket_priority_name>Normal</ticket_priority_name>
<ticket_problem>ahhhhhhhh</ticket_problem>
<ticket_project_access>0</ticket_project_access>
<ticket_project_admin>0</ticket_project_admin>
<ticket_project_id>0</ticket_project_id>
<ticket_project_item_id>0</ticket_project_item_id>
<ticket_project_leader_assign>0</ticket_project_leader_assign>
<ticket_project_leader_notify>0</ticket_project_leader_notify>
<ticket_sent_survey>N</ticket_sent_survey>
<ticket_solution></ticket_solution>
<ticket_staff_assigned>1</ticket_staff_assigned>
<ticket_staff_assigned_name>Admin</ticket_staff_assigned_name>
<ticket_status>1003</ticket_status>
<ticket_status_name>Open</ticket_status_name>
<ticket_status_progression>0</ticket_status_progression>
<ticket_timestamp>208008</ticket_timestamp>
<ticket_time_accessed>NULL</ticket_time_accessed>
<ticket_total_time>0</ticket_total_time>
<ticket_type>1002</ticket_type>
<ticket_type_name>External</ticket_type_name>
<version>2.0.7 Web Ticket</version>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[ticket_Load](#)

ticket_Reassign XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Reassign</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
        <nStaffID type='int'>47</nStaffID>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ticket_Reassign>true</ticket_Reassign>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[ticket_Reassign](#)

ticket_Save XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Save</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
        <cProblem type='string'>Test Machine is not working</cProblem>
        <cSolution type='string'>Flux compasitor was empty</cSolution>
      </parameters>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ticket_Save>true</ticket_Save>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[ticket_Save](#)

ticket_Steal XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticket_Steal</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <nTicket type='int'>1031</nTicket>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <ticket_Steal>true</ticket_Steal>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

Method:[ticket_Steal](#)

tickettree_Get_Filters XML Example

Input Example:

```
<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticketTree_Get_Filters</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>
```

Output Example:

```
<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <cft_name>asfsdf</cft_name>
          <cft_id>1002</cft_id>
        </data_block>
        <data_block>
          <cft_name>sdfdsf</cft_name>
          <cft_id>1003</cft_id>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>
```

Method:

[tickettree_Get_Filters](#)

ticketTree_Get_Group_List XML Example**Input Example:**

```

<?xml version="1.0" ?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>webticket</object>
      <action>ticketTree_Get_Group_List</action>
      <username>admin</username>
      <password>admin</password>
      <logintype type="string">staff</logintype>
      <parameters>
        <cViewType type="string">status</cViewType>
        <nId type="int">1</nId>
        <nViewID type="int">1003</nViewID>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>webticket</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tkr_date_month>6</tkr_date_month>
          <tkr_date_year>2006</tkr_date_year>
          <tkr_total_count>2</tkr_total_count>
          <tkr_bold_count>1</tkr_bold_count>
        </data_block>
        <data_block>
          <tkr_date_month>2</tkr_date_month>
          <tkr_date_year>2005</tkr_date_year>
          <tkr_total_count>1</tkr_total_count>
          <tkr_bold_count>0</tkr_bold_count>
        </data_block>
      </attributes>
    </data_block>
  </body>

```

```
</data_block>
<data_block>
  <tkr_date_month>1</tkr_date_month>
  <tkr_date_year>2005</tkr_date_year>
  <tkr_total_count>2</tkr_total_count>
  <tkr_bold_count>0</tkr_bold_count>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[ticketTree Get_Group_List](#)

tickettree_Get_Ticket_List XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticketTree_Get_Ticket_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cViewType type='string'>status</cViewType>
        <nID type='int'>0</nID>
        <nViewID type='int'>1002</nViewID>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <tkc_id>1006</tkc_id>
          <tkc_customer_id>1479</tkc_customer_id>
          <tkc_problem><![CDATA[some errorweird]]></tkc_problem>
          <tkc_date_entered>2005-01-14T15:32:12</tkc_date_entered>
          <tkc_staff_assigned>1</tkc_staff_assigned>
          <tkc_modified>N</tkc_modified>
          <tkc_customer_name>Ween O'Reilley</tkc_customer_name>
          <tkc_staff_assigned1>1</tkc_staff_assigned1>
          <tkc_priority>1004</tkc_priority>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
<data_block>
  <tkc_id>1005</tkc_id>
  <tkc_customer_id>1119</tkc_customer_id>
  <tkc_problem>hmmmmmmmm</tkc_problem>
  <tkc_date_entered>2005-01-14T11:01:24</tkc_date_entered>
  <tkc_staff_assigned>1</tkc_staff_assigned>
  <tkc_modified>N</tkc_modified>
  <tkc_customer_name>Another Store2</tkc_customer_name>
  <tkc_staff_assigned1>1</tkc_staff_assigned1>
  <tkc_priority>1004</tkc_priority>
</data_block>
<data_block>
  <tkc_id>1003</tkc_id>
  <tkc_customer_id>1479</tkc_customer_id>
  <tkc_problem>merging a ticket into itself makes it implode</tkc_problem>
  <tkc_date_entered>2005-01-13T07:47:08</tkc_date_entered>
  <tkc_staff_assigned>1</tkc_staff_assigned>
  <tkc_modified>Y</tkc_modified>
  <tkc_customer_name>Ween O'Reilley</tkc_customer_name>
  <tkc_staff_assigned1>1</tkc_staff_assigned1>
  <tkc_priority>1004</tkc_priority>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[tickettree_Get_Ticket_List](#)

tickettree_Get_Viewable XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticketTree_Get_Viewable</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <view>category</view>
          <id>1001</id>
          <shown>Y</shown>
          <name>Other</name>
        </data_block>
        <data_block>
          <view>category</view>
          <id>1002</id>
          <shown>Y</shown>
          <name>General</name>
        </data_block>
        <data_block>
          <view>category</view>
          <id>1003</id>
          <shown>Y</shown>

```

```

    <name>Business Sales</name>
  </data_block>
  <data_block>
    <view>category</view>
    <id>1004</id>
    <shown>Y</shown>
    <name>Sales</name>
  </data_block>
  <data_block>
    <view>category</view>
    <id>1005</id>
    <shown>Y</shown>
    <name>Feature Request</name>
  </data_block>
  <data_block>
    <view>category</view>
    <id>1006</id>
    <shown>Y</shown>
    <name>Support Question</name>
  </data_block>
  <data_block>
    <view>priority</view>
    <id>1001</id>
    <shown>Y</shown>
    <name>Low</name>
  </data_block>
  <data_block>
    <view>priority</view>
    <id>1002</id>
    <shown>Y</shown>
    <name>Urgent</name>
  </data_block>
  <data_block>
    <view>priority</view>
    <id>1003</id>
    <shown>Y</shown>
    <name>High</name>
  </data_block>
  <data_block>
    <view>priority</view>
    <id>1004</id>
    <shown>Y</shown>
    <name>Normal</name>
  </data_block>
  <data_block>
    <view>status</view>
    <id>1001</id>
    <shown>N</shown>
    <name>Closed</name>
  </data_block>
  <data_block>

```

```

        <view>status</view>
        <id>1002</id>
        <shown>Y</shown>
        <name>Suspended</name>
    </data_block>
    <data_block>
        <view>status</view>
        <id>1003</id>
        <shown>Y</shown>
        <name>Open</name>
    </data_block>
    <data_block>
        <view>status</view>
        <id>1004</id>
        <shown>N</shown>
        <name>New</name>
    </data_block>
    <data_block>
        <view>type</view>
        <id>1002</id>
        <shown>Y</shown>
        <name>External</name>
    </data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>

```

Method:

[tickettree_Get_Viewable](#)

tickettree_Get_View_List XML Example

Input Example:

```

<?xml version="1.0"?>
<PLATXML>
  <header/>
  <body>
    <data_block>
      <protocol>Plat</protocol>
      <object>wombat</object>
      <action>ticketTree_Get_View_List</action>
      <username>Admin</username>
      <password>admin</password>
      <logintype type='string'>staff</logintype>
      <parameters>
        <cViewType type='string'>status</cViewType>
        <cCategoryViewable
type='string'>1001,1002,1003,1004,1005,1006</cCategoryViewable>
        <cPriorityViewable type='string'>1001,1002,1003,1004</cPriorityViewable>
        <cStatusViewable type='string'>1002,1003</cStatusViewable>
        <cTypeViewable type='string'>1002</cTypeViewable>
        <nCatFilter type='int'>0</nCatFilter>
        <nID type='int'>0</nID>
      </parameters>
    </data_block>
  </body>
</PLATXML>

```

Output Example:

```

<?xml version="1.0" ?>
<PLAT_XML>
  <header></header>
  <body>
    <data_block>
      <object>wombat</object>
      <protocol>TPP</protocol>
      <action>REPLY</action>
      <response_text></response_text>
      <response_code>SUCCESS</response_code>
      <is_success>1</is_success>
      <attributes>
        <data_block>
          <st_id>1003</st_id>
          <st_name>Open</st_name>
          <tkr_total_count>4</tkr_total_count>
          <tkr_bold_count>1</tkr_bold_count>
        </data_block>
      </attributes>
    </data_block>
  </body>
</PLAT_XML>

```

```
<data_block>
  <st_id>1002</st_id>
  <st_name>Suspended</st_name>
  <tkr_total_count>3</tkr_total_count>
  <tkr_bolc_count>1</tkr_bolc_count>
</data_block>
</attributes>
</data_block>
</body>
</PLAT_XML>
```

Method:

[tickettree_Get_View_List](#)

Advanced Topics

Adding Custom Fields to the Signup Pages

Overview

To add an additional field to the Signup Server pages for customers to fill out requires modifying both the signup.asp and the signup.inc files. The signup.asp file must be modified to allow the customer to enter the additional information and the signup.inc file must be modified to update the Platypus database with this additional information.

Signup.asp File Modifications

The signup.asp page is written mostly in basic HTML. You can add any text boxes, radio buttons, drop down lists, or any other HTML data entry control that you wish to the page. As long as your data entry control is added between the <FORM> and </FORM> tags, the data will be passed to the adduser.asp page and can be referenced by the name you gave the data entry control. To add a drop down list that is populated with values from the Platypus database would be a slightly more involved procedure but it is not that difficult.

Populating a Drop Down List from the Platypus Database

To add a drop down list that is populated with data from the Platypus database, you would first need to select that data from the database. On the signup.asp page, there is a section of code that selects out the data used to populate the rate group, shell type, and staff member drop downs that come by default with the Signup package. You can add your SQL statement to select out the data you wish to display right below this code as shown in [blue](#) between the comments below:

```
<%  
  
SQLStmt = "SELECT id, name from rgheader where webrate='X'"  
Set RS = Connection.Execute(SQLStmt)  
SQLStmt2 = "Select id,name from um_shell "  
Set RS2 = Connection.Execute(SQLStmt2)  
SQLStmt3 = "Select num,name from staff where active='y'"  
Set RS3 = Connection.Execute(SQLStmt3)  
  
' Your SQL Statement Goes Here  
  
CustomSQLStmt = "Select column1, column2 from tablename"  
Set CustomRS = Connection.Execute(CustomSQLStmt)  
  
' End of added code  
  
%>
```

You can then display this data anywhere on the signup.asp page by looping through the data that is returned into the CustomRS recordset. Here is an example of what the code should look like:

```
<font color="#FF0000">Select a XXXXX:<br>  
<select name="customfield1" size="1">
```

```
<option selected value="0">Please Select a XXXXX
<%
CurrentRecord = 0
Do While Not CustomRS.EOF
%>
</option><option value="<%= CustomRS("column1") %>"> <%= CustomRS("column2")
%>
<%
CustomRS.MoveNext
CurrentRecord = CurrentRecord + 1
Loop
CustomRS.Close
Set CustomRS = Nothing
%>
</option></select></font>
```

This example would display the value from column2 in the drop down list and pass the value of column1 to the adduser.asp page as a variable called customfield1.

Signup.inc File Modifications

After you get the signup.asp page passing the data correctly to the adduser.asp page, you then need to modify the signup.inc file to update the Platypus database with the data. This can be done by adding a single line of code to the signup.inc file.

Updating Data in the Customer Table

You can update any column in the customer table using the [UpdateCustomer](#) method of the web object. You just pass the column name you wish to update and the value to this method and it updates it for you. See [UpdateCustomer](#) for documentation of this method.

Updating Data in Another Table

To update a column in another table, you can use either the [Update](#) method or the [Sql](#) method of the web object. The [Update](#) method takes the name of the table, the column to update, the value to set the column to, and a where clause to limit which record is to be updated as parameters. The [Sql](#) method allows you to run any SQL statement against the database. Its parameter must be a syntactically correct SQL update statement. See [Update](#) or [Sql](#) for documentation of these methods.

Commonly Used Signup Methods

Below is a list of commonly used signup methods:

1. AddBlockTime
2. AddtoPlat
3. ChargeAll
4. CheckFormat
5. CreateBonus
6. CreatINSFile
7. GetCustomer
8. GetWebOption
9. LaunchUM
10. Post
11. PostPayment
12. SQL
13. UpdateCustomer
14. VerifyInfo
15. WelcomeEmail

Creating Bonuses/Commissions from the Web

Overview

There are two ways to create commissions and referral bonuses from the web. One is to setup global bonus rules in Platypus and let the Signup Server pages check to see if the current customer signup fits any of those global rules, and the other is to hard code the global bonus object properties on the web page to manually create a bonus rule. You can use either of these methods or both on the adduser.asp page to give out commissions and/or referral bonuses.

Commissions versus Referral Bonuses

The first thing that needs to be setup is whether to give commissions, referral bonuses, or both. This is determined based on the value of the two properties Refid and Salesid. The Refid property should be set when giving referral bonuses and the Salesid property should be set when giving commissions. If both are set to a valid id value, both a commission and a referral bonus will be generated.

<u>Property</u>	<u>Type</u>	<u>Description</u>
Refid	String	This property should be set to the customer id number of the customer who is to receive the referral bonus. If you do not wish to give referral bonuses, simply do not reference the Refid property or set it to false.
Salesid	String	This property should be set to the id number of the staff member who is to receive the commission. If you do not wish to give a commission, simply do not reference the Salesid property or set it to false.

Global Bonus Rules versus Manual Bonus Rule Creation

The BonusType property determines whether global bonus rules are referenced, a bonus rule is created manually based on the hard coded property values, or both. The three values to assign the BonusType property are:

ox.BonusType = "G" to look at global bonus rules

ox.BonusType = "M" to create a manual bonus rule

or ox.BonusType = "B" to both look at global bonus rules and create a manual bonus rule

For the global bonus rule method to actually create a bonus rule, there must be a global bonus rule defined in Platypus for the rate group that is specified. The [CreateBonus](#) method determines the rate group based on the crid that is passed into that method. The [AddToPlat](#) method determines the rate group based on the SelectRate property that it requires.

Manual Bonus Rule Creation Properties

If the BonusType property is set to "M" or "B" so that a manual bonus rule is to be created, the following properties of the global bonus object must be set:

<u>Property</u>	<u>Type</u>	<u>Description</u>
FeeType	String	Required. This property should be set to "F" for a bonus rule of a Fixed amount or "P" for a bonus rule of a Percentage based amount.

Amount	String	Required. The amount of the bonus. Should be in the format of "3.00" which would be 3 dollars for a Fixed bonus or "0.10" which would be 10 percent for a Percentage based bonus.
OneTime	String	Required. Should be set to true for one time bonuses or false for recurring bonuses.
StartDate	String	Required. The earliest possible date that a bonus should be generated.
EndDate	String	Required for recurring bonuses. The date the recurring bonus rule should expire and stop creating bonuses.

All of these global bonus object properties must be referenced as:

```
ox.globalbonus1.FeeType
```

where ox is the name of the web object instance.

Creating the Bonus Rule

There are two methods which can be used to create a bonus rule. The first is [CreateBonus](#). The second is [AddToPlat](#).

The [AddToPlat](#) method, which is used in the signup process, automatically calls [CreateBonus](#) if the required properties have been set before the [AddToPlat](#) method is called. If you set the required properties before calling [AddToPlat](#), you do NOT need to call the [CreateBonus](#) method separately. If you do, you will end up with duplicates of all the bonus rules that are created.

You can find the requirements for each of these functions by navigating to their specific help topics using the links above.

Example

Here is an example of creating bonus rules using both global bonus rules and creating a manual bonus rule.

Stateful Example:

```
ox.Custid = "1012"
ox.Refid = "1234"
ox.Salesid = "2"
ox.globalbonus1.BonusType = "B"
ox.globalbonus1.FeeType = "F"
ox.globalbonus1.Amount = "3.00"
ox.globalbonus1.OneTime = false
ox.globalbonus1.StartDate = "11/01/99"
ox.globalbonus1.EndDate = "01/01/00"
ox.CreateBonus("212")
```

Stateless Example:

[Bonus/Commissions XML Example](#)

Removing Default Fields from the Signup Pages

Overview

All of the fields included on the signup.asp page by default are required to be set or the signup process will fail. If you wish to remove one of these fields, you must remove it from the signup.asp page and hard code the value of that property in the platypus.inc file.

Detailed Instructions

Here are step by step instructions on removing the shell type drop down. The same steps can be applied to any other field.

1. Comment out or delete the code from the signup.asp page that displays the data entry control in question.

```
<!-- hide shell option
<p><br><table><tr><td>
<font color="#FF0000">Select a Shell Type:<br>
<select name="selectshell" size="1">
<%
    CurrentRecord = 0
    Do While CheckRS(RS2)%></option>
<option value="<%= CheckRequest(RS2, "id") %"> <%= CheckRequest(RS2, "name")
%>
<%
    RS2.MoveNext
    CurrentRecord = CurrentRecord + 1
Loop
%>
</option>
</select></td><td></td>
// end hiding shell option -->
```

2. Find the variable name for the data that is being removed. For the shell type drop down list, you can see that the variable name is "selectshell".

```
<select name="selectshell"
```

3. Modify the platypus.inc file to hard code a value for the variable that has been removed. Most of the variables pass the data that you actually see on the signup.asp page to the adduser.asp page which is a string in most cases, but the shell type and the pop location drop downs both pass an id number that corresponds to the value you select. Therefore, the selectshell value must be hard coded to a number. Find the place in the platypus.inc file that requests the variable name.

```
shelltype = Request("selectshell")
```

And then modify that line of code to hard code an appropriate value to the property.

```
shelltype = "1"
```


Running SQL Statements against the Database

Overview

There are three methods in the web object that can be used to run SQL statements against the database. They are [UpdateCustomer](#), [Update](#), and [SQL](#). They were each added in different versions with each one being more powerful and potentially more destructive than the previous. Below is a description of each detailing what it is capable of and when it should be used.

UpdateCustomer

The [UpdateCustomer](#) method has been around since the earliest versions of the web object. It allows you to update any field on the customer table for the current customer which specified by setting the Custid property to the customer id number of the customer. It is the simplest of the three methods as you only need to pass it the column name to update and the value to update it to. The most common problem with using this method is that when updating character data, you must enclose the value in both double and single quotes so the method knows that it is a string. When updating numeric data, only double quotes are required.

String Data Example

```
ret = ox.UpdateCustomer("active", "Y")
```

Numeric Data Example

```
ret = ox.UpdateCustomer("guarantor", "1234")
```

The [UpdateCustomer](#) method returns 1 to indicate success or 0 to indicate failure as numeric values. If the method fails, an error message is stored in the LastError property. Very little damage can be done when using this method since it can only update one column of one row in the customer table.

Update

The second method that was added to the web object is [Update](#). It came about as customers requested the ability to update data in tables other than the customer table. It has four required parameters which are the table to update, the column to update, the value to update the column to, and the SQL where clause to use when updating. Just like in the [UpdateCustomer](#) method, if you are updating character data you must enclose the value in both double and single quotes while numeric data only requires the double quotes.

Since this method allows you specify the where clause, you can update multiple rows in the table at once. Some times this is very useful, but it also means that mistakes made in specifying the where clause parameter could cause all rows in the table to be updated. Obviously this would be a major problem if the username or active status or pretty much any other column was updated in this way. Only people with a reasonable knowledge of SQL query syntax should use this method, and even then you need to be careful and double check your syntax to make sure no mistakes were made.

The [Update](#) method returns true if for success or false for failure. If the update statement run by the method fails, an error message is stored in the LastError property.

SQL

The method that was added most recently is [SQL](#). This method was making additional data appear on the web pages would not require all of the code that goes along with creating an ADO connection to the

database. When writing ADO code, it is very easy to forget to close and/or destroy connections and record sets causing performance problems on the SQL Server. The [SQL](#) method takes care of all of this for you.

Any valid SQL statement can be run using the [SQL](#) method since it simply runs the exact SQL statement passed in without modifying it in any way. This makes the method very powerful, but at the same time very dangerous. Data can be updated and deleted from the database or entire tables can be renamed and dropped using this method if the author knows the correct SQL syntax to do that. This method is very useful and easy to use, but only people with a good knowledge of SQL query syntax should use it.

The [SQL](#) method returns false if an error occurs or a record set of data if a select statement is run.

Web Transactions

Overview

Transactions will add a whole new level of usability to the Platypus Billing System. By adding a transaction system, other systems can use Platypus as an API to handle billing transactions. In addition, by putting more emphasis on Platypus as an API, the client will no longer have to be the central point for Platypus owners. In the past, Platypus was the starting point for all interaction with external systems.

After adding transactions, Platypus will have the ability to function strictly as a billing system with the flexibility to generate billing transactions (invoices & payments) by calls from external systems.

Transaction Methods

Each of the methods listed below define the different steps within a transaction. These methods allow external systems to use this model to ensure a transaction is valid for the customer, to perform an external action, and to commit the transaction to the billing system. In addition, if the external action fails, the transaction can be "rolled back" to undo any information logged during the Authorization stage.

Method Names:

1. Transaction_Auth - Generate a transaction and authorize payment info
2. Transaction_Commit - Finalize a transaction
3. Transaction_Refund - Cancel a transaction

Authorization

The authorization method represents the beginning of a transaction and handles the bulk of data validation. All the information is passed into the method using three parameters, the first of which is in XML format.

Within this XML parameter, several pieces of information are input. Some information is required and some information is optional. Each piece of information is described below.

1. Customer ID (required) - the unique identifier for the customer.
2. Billing Amount (required) - the base amount (before taxes) that will be charged to the customer.
3. Service Type (optional) - the type of service which is being generated by the transaction process.
4. Service Name (optional) - the name of the service being generated. If the Service Type is set to domain, then a valid value for this node would be the domain name.
5. Transaction Type (optional) - the transaction being performed on the service. If the Service Type is set to domain, then a valid value for this node would be transfer, register, or renew.
6. CC Info block (optional) - this block in the XML contains all the credit card information necessary to generate a payment on the customer, which must include the CC Number, the expiration date, the name on the card, and the type of credit card. The CVV2 code on the back of the credit card is optional. In addition, the billing address for the credit card is optional only if a credit card address does not already exist on the customer record. Even though this block in the XML is optional, if one of the required fields in this block is missing, an error will occur.
7. Invoice / Line Item block (required) - this block in the XML contains all the line items that will be used to generate an invoice on the customer. Each line item must include a description and price. The line item can include code, quantity, and profile as well. The code is the SKU which

defaults to MISC. The quantity is the number of the items being sold. The quantity defaults to 1 (one). The profile is the Tax Profile ID from the client. If the profile node is excluded the item is considered non-taxable.

Here is an example of the XML for the Authorization method for the first parameter with all nodes both required and optional.

```
<authinput>
  <custid>1270</custid>
  <amount>20.00</amount>
  <servicetype>domain</servicetype>
  <servicename>mydomain.com</servicename>
  <transactiontype>transfer</transactiontype>
  <ccinfo>
    <ccnumber>4111111111111111</ccnumber>
    <ccexpire>012005</ccexpire>
    <ccname>John Smith</ccname>
    <cctype>Visa</cctype>
    <cvv2>123</cvv2>
    <ccaddress>
      <addr1>10001 Blackberry St</addr1>
      <addr2></addr2>
      <city>Some City</city>
      <state>MS</state>
      <zip>12345</zip>
      <country>Some Country</country>
    </ccaddress>
  </ccinfo>
  <invoice>
    <details>
      <item>
        <code>code#1</code>
        <desc>my description</desc>
        <price>15.00</price>
        <quantity>1</quantity>
        <profile>1</profile>
      </item>
      <item>
        <code>code#2</code>
        <desc>my description</desc>
        <price>5.00</price>
        <quantity>1</quantity>
        <profile>1</profile>
      </item>
    </details>
  </invoice>
</authinput>
```

The second parameter for the method is a boolean value which determines when a payment should be created on the customer's account. If True is passed in to this parameter, then a payment is generated on the customer's account during the Authorization method. If the transaction fails, the Refund method must refund the payment. If False is passed in, then a payment is not generated until the Commit method is called.

The third parameter for the method is the datatype which determines the output for the parameter. Valid values for this parameter are XML and ADO.

Once the Authorization Method is called, all the input data is validated. The customer record is validated to ensure that it exists and is active. The line items are validated to ensure that all required fields are included and the sum of all line items equals the billing amount for the transaction. If credit card information is included it is validated to ensure all required information is available.

After validation occurs, any payment related to functionality is handled. This functionality comes in two different forms.

1. Credit Card Auth is an authorization charge against the input credit card information. When Commit is called, this authorization is “captured” and turned into a payment in the client.
2. Credit Card Auth/Capture is a charge against the input credit card information. A payment is created on the customer record instead of waiting until Commit.

If the payment info is handled without errors, then the line items and payment information are cached to the database and any relevant transaction information is saved to the database. Any line items which are considered tax items are not cached in the database because they will be recalculated during invoice generation.

If the Authorization method fails to validate any of the information or fails to log appropriate information, the transaction is considered unsuccessful (or aborted).

If the Authorization method succeeds, the transaction is saved to the database as pending (waiting for commit or refund) and returns a success along with the updated Billing Amount (after taxes) and the transaction id. The transaction id will be used to commit or refund the transaction.

Commit

The Commit method represents the end of a successful transaction. After the external system calling the WOW finishes performing any external actions and considers those actions successful, a call to the commit method will finalize the transaction in the database.

This method accepts a single parameter which is the transaction id. Since all the relevant information about the transaction was cached during the Authorization method, the only parameter needed is a reference to that transaction.

Once called, the method ensures that the transaction is still pending. If the transaction is not still pending, an error is returned to the external system. If the transaction is still pending, any payment information is committed. For Credit Card Auth charges, the authorization is captured and a payment is generated. If the capture fails, the failure is logged to the database, but the method continues without any errors. For Credit Card Auth/Capture charges, no payment is generated.

Next, any line items associated with the transaction are converted into an invoice on the customer. Any payments created in the Commit or the Authorization methods are applied to the invoice. Finally, the line items and cached payment information are removed from the database.

Any errors occurring during the Commit method are logged to the database.

Refund

The Refund method represents the end of an unsuccessful transaction. After the external system calling the WOW finishes performing any external actions and considers those actions unsuccessful, a call to the Refund method will undo the transaction in the database.

This method accepts a single parameter which is the transaction id. Since all the relevant information about the transaction was cached during the Authorization method, the only parameter needed is a reference to that transaction.

Once called, the method ensures that the transaction is still pending. If the transaction is not still pending, an error is returned to the external system. If the transaction is still pending, any payment information is voided or refunded.

For Credit Card Auth charges, the authorization is voided. For Credit Card Auth/Capture charges, there are several steps that need to occur. To keep a valid paper trail, any payments generated during the Authorization method should not be deleted. To properly refund the credit card, the original payment must first be reduced to zero. This is handled by creating a non-taxable invoice for the total amount of the payment which is applied to the original payment. Next, a negative version of this invoice needs to be created. It must contain the same item code (SKU), description, etc., but the total for it must be the negative value for the original invoice. Finally, a negative charge must occur against the credit card.

Since the fields used to create the original payment should still be cached from the Authorization method, all relevant information should be available to refund the card. This negative charge should be applied to the negative invoice to finish the process.

Any line items/pending fees for the transaction are removed from the database. Finally, the transaction is marked as closed and a success is returned.

Any errors occurring during this method are logged to the database. However, the Refund method always returns a success.

Index

A

Addresses.....9, 52, 53, 125

B

Bonuses37, 59, 82, 548

C

Commissions37, 59, 548

Credit Cards 16, 18, 25, 27, 50, 57, 104, 118,
135, 209

Customers.....13, 20, 23, 24, 57, 58, 61, 63,
103, 104, 105, 120, 135, 136, 142, 211,
550

E

Echeck63, 118

Email47, 124

Expirations.....29, 39

I

Invoices36, 41, 43, 65, 66, 117, 129, 130,
131, 132, 554

K

Knowledge Base.....164, 165, 166, 167, 168,
169

L

Logging In113, 170

N

Notes.....5, 21, 92

O

OpenSRS114, 115, 116

Options68, 77, 102, 163

P

Passwords22, 30

Payments.....16, 18, 25, 27, 71, 72, 74, 118,
129, 130, 131, 209, 554

Phone Numbers.....9, 51, 75, 127

R

Rate Groups7, 23, 36, 45, 54, 55, 70, 80,
138

Referrals.....37, 82, 548

Reports.....84, 85, 86, 88

S

Security32, 33, 188

Services.....11, 46, 64, 89, 90, 91, 107, 108,
110, 122, 140

Signup.....13, 25, 142, 550

T

Ticket Attachments.....146, 147, 148, 179

Ticket Calls.....149, 150, 151, 180

Ticket Emails..154, 155, 156, 157, 159, 161,
162, 183

Ticket Notes.....171, 172, 174, 185

Ticket Queue 199, 200, 201, 203, 204

Tickets 176, 177, 178, 181, 182, 184, 187,
188, 189, 190, 191, 192, 193, 195, 196,
198

Time Clock 34, 35, 95

U

Usage 49, 78, 81, 96, 98, 100

User Manager 106

Username 30