

Notes:

1.- Engrave "TSH-GD-74.0002 Pos ... Rev ..." Rev. number according to Pos. Revision column of the table. Pos. Revision is independant from drawing revision.

> 8 2

ATP is 106.921, was 85.291. T or ØT is 262.323, was 262.338.

STP is 99.0, was 77.4. SL is 217, was 195. SS is 151.112, was 128.482,16-May-14 N.CROWLEY Added column Pos. Revision. Updated notes 1, 10 and gauge name.

05-May-14 N.CROWLEY DATE APPROVED

DESCRIPTION First issued.

REVISIONS

- Engrave Thread and Seal. Words shall be 0.8mm deep.
- 3.- Material: Thyrodur 2990.

Heat treatment:

- a) Stress Relief at 650°CX 2 hours, as an intermediate step between machining and grinding. b) Vacuum quenching from an austenitising temperature of 1070 1080°C to room temperature.
- c) Cooling: Subzero up to -80°C and then tempered twice at 520°C. Hardness required 58-60 HRC.
- 4.- Serial Number (according to vendor's identification).
- Taper surfaces for thread and seal axis shall be perpendicular to the reference surface.
- 6.- Dimensions S, SAP, T, ATP, SS; Angle A and Angle B shall be certified.
- 7.- Corrosion protection and packaging shall be according to TenarisConnections specification.
- 8.- Certificate shall be according TenarisConnections specification.
- 9.- Mark seal setting point on both seal pads.
- 10.- Setting standard Pos. 1 IAW PREN drawings PREN-PC-TBL-K-10750 Rev. 04
- 11.- Face to shoulder gage contact tip diameter shall be 0.096"

1 02	Position Pos. Revisi
10 3/4"	on Diameter
92.434	Α
106.921	ATP (ref.)
262.323	T or ØT
94.764	В
2.292	SAP (ref.)
257.989	S or ØS
99.0	STP
217	SL
77	SR
267	R or ØR
387	SW
151.112	SS

NOTICE PROPRIETARY RIGHTS INVOLVED THIS DOCUMENT AS WELL AS THE INFORMATION OR DATA CONTAINED HEREIN ARE CONFIDENTIAL AND SHALL NOT BE COPIED, RECOPIED, REPRODUCED, TRANSMITTED, DISCLOSED OR DISTRIBUTED TO OTHERS OR OTHERWISE USED FOR ANY PURPOSE WITHOUT THE EXPRESS, PRIOR AND WRITTEN PERMISSION OF TENARIS CONNECTIONS AG AND/OR HYDRIL COMPANY AND/OR ITS AFFILIATED COMPANIES ("TENARIS"). THIS DOCUMENT AS VELL AS THE INFORMATION OR DATA CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF TENARIS, AND ARE TO BE RETURNED UPON REQUEST THEREFOR. ALL RIGHTS IN PROPRIETARY AND NOVEL FEATURES OF THE SUBJECT MATTER ARE EXPRESSLY RESERVED BY TENARIS. RECIPIENT'S AGREEMENT TO THE FOREGOING IS INDICATED BY ACCEPTANCE OF THIS DOCUMENT. COPYRIGHTED 2010 AS UNPUBLISHED WORK, ALL RIGHTS RESERVED.									
RELEASED	APPROVED	APPROVED	QA	MFG		ENGINEER	CHECKED	PREPARED	
		N.CROWLEY					CHECKED S.NEVLUD 05-May-14	PREPARED A.OGGERO 15-Apr-14	
		05-May-14					05-May-14	15-Apr-14	
SCALE	Α4	SIZE		<u>П</u> Вс	77				
		APPROVED N.CROWLEY 05-May-14 SIZE CODE IDENT NO.		x Internal	Ten				
WT.		埬		Sea	arist		Ú		
SHEET 2 OF 2	TSH-GD-74,0002	DRAWING NO.		Box Internal Seal and Thread Standard	TenarisHydril Blue /K				
2 田 2	02	REVISION	1	ndard I	1.1	ı			