

Ant Colony Optimization

Application : Traveling Sales Man Problem

```
import numpy as np
import random

# Function to calculate the total distance of a given path
def calculate_total_distance(distance_matrix, path):
    total_distance = 0
    for i in range(len(path) - 1):
        total_distance += distance_matrix[path[i]][path[i + 1]]
    total_distance += distance_matrix[path[-1]][path[0]] # Returning to the origin city
    return total_distance

# Function to perform the Ant Colony Optimization
def ant_colony_optimization(distance_matrix, num_ants, num_iterations, alpha, beta, rho,
    pheromone_initial):
    num_cities = len(distance_matrix)

    # Initialize pheromone matrix with the initial pheromone value
    pheromone = np.ones((num_cities, num_cities)) * pheromone_initial

    # Initialize the best solution
    best_solution = None
    best_distance = float('inf')

    # Main ACO loop
    for iteration in range(num_iterations):
        # Ants' paths and their corresponding distances
        paths = []
        distances = []

        # Generate solutions for each ant
        for ant in range(num_ants):
            path = generate_path(distance_matrix, pheromone, alpha, beta)
            total_distance = calculate_total_distance(distance_matrix, path)
            paths.append(path)
            distances.append(total_distance)
```

```

    # Update the best solution if a new better one is found
    if total_distance < best_distance:
        best_solution = path
        best_distance = total_distance

    # Update pheromones
    pheromone = update_pheromones(pheromone, paths, distances, rho, best_solution,
best_distance)

    return best_solution, best_distance

# Function to generate a solution (path) for an ant
def generate_path(distance_matrix, pheromone, alpha, beta):
    num_cities = len(distance_matrix)
    path = [random.randint(0, num_cities - 1)] # Start at a random city
    visited = set(path)

    while len(path) < num_cities:
        current_city = path[-1]
        probabilities = []

        # Calculate the probabilities for all unvisited cities
        for next_city in range(num_cities):
            if next_city not in visited:
                pheromone_strength = pheromone[current_city][next_city] ** alpha
                distance_heuristic = (1.0 / distance_matrix[current_city][next_city]) ** beta
                probabilities.append(pheromone_strength * distance_heuristic)
            else:
                probabilities.append(0)

        # Normalize the probabilities
        total_prob = sum(probabilities)
        probabilities = [p / total_prob for p in probabilities]

        # Choose the next city based on the calculated probabilities
        next_city = np.random.choice(range(num_cities), p=probabilities)
        path.append(next_city)
        visited.add(next_city)

```

```

return path

# Function to update the pheromone matrix after each iteration
def update_pheromones(pheromone, paths, distances, rho, best_solution, best_distance):
    num_cities = len(pheromone)

    # Apply pheromone evaporation
    pheromone *= (1 - rho)

    # Deposit pheromones based on the paths and their distances
    for path, dist in zip(paths, distances):
        for i in range(len(path) - 1):
            pheromone[path[i]][path[i + 1]] += 1.0 / dist
        pheromone[path[-1]][path[0]] += 1.0 / dist # Returning to the origin city

    # Deposit more pheromone on the best path found so far
    for i in range(len(best_solution) - 1):
        pheromone[best_solution[i]][best_solution[i + 1]] += 1.0 / best_distance
    pheromone[best_solution[-1]][best_solution[0]] += 1.0 / best_distance # Returning to the
    origin city

    return pheromone

# Input the distance matrix and parameters from the user
print("Ant Colony Application for Travelling Sales Man Problem")
num_cities = int(input("Enter the number of cities: "))
distance_matrix = []
print("Enter the distance matrix (row by row):")
for i in range(num_cities):
    row = list(map(int, input(f"Row {i+1}: ").split()))
    distance_matrix.append(row)

num_ants = int(input("Enter the number of ants: "))
num_iterations = int(input("Enter the number of iterations: "))
alpha = float(input("Enter the value of alpha (importance of pheromone): "))
beta = float(input("Enter the value of beta (importance of heuristic information): "))
rho = float(input("Enter the evaporation rate (rho): "))
pheromone_initial = float(input("Enter the initial pheromone value: "))

```

```

# Run the ACO algorithm
best_solution, best_distance = ant_colony_optimization(
    distance_matrix, num_ants, num_iterations, alpha, beta, rho, pheromone_initial
)

# Display the results
print("Best Solution (Path):", list(map(int, best_solution))) # Fix for clean output
print("Best Distance:", best_distance)

```

Output:

```

Ant Colony Application for Travelling Sales Man Problem
Enter the number of cities: 5
Enter the distance matrix (row by row):
Row 1: 0 5 10 15 20
Row 2: 10 0 15 20 30
Row 3: 5 20 0 15 20
Row 4: 30 15 5 0 30
Row 5: 20 5 10 15 20
Enter the number of ants: 10
Enter the number of iterations: 100
Enter the value of alpha (importance of pheromone): 1.0
Enter the value of beta (importance of heuristic information): 2.0
Enter the evaporation rate (rho): 0.5
Enter the initial pheromone value: 1.0
Best Solution (Path): [0, 4, 1, 3, 2]
Best Distance: 55

```