QUALITY ENGINEERING · TEST STRATEGY

Test Plan: VWO Login Dashboard

A risk-based plan for validating secure, accessible, responsive, and reliable access to the VWO platform.

Version 1.0 | Status: Draft for stakeholder review | Source: Product Requirements Document | Prepared: 20 October 2026

Document map

1. Overview
2. Scope
3. Test Strategy
4. Test Types and Levels
5. Entry and Exit Criteria
6. Test Environment
7. Test Data Requirements
8. Risk Analysis
9. Test Schedule and Estimation
10. Coverage Matrix
11. Deliverables
12. Roles and Responsibilities

1. Overview

This plan covers the VWO login experience at **app.vwo.com**, from initial page load through authentication, recovery, and transition to the authenticated dashboard. It is based on the supplied PRD, which describes email/password authentication, session management, optional multi-factor authentication (MFA), enterprise single sign-on (SSO), password recovery, accessibility, mobile behavior, security, performance, integrations, and success measures.

Product	VWO Login Dashboard
Primary objective	Enable secure, low-friction access while protecting accounts and meeting enterprise, usability, and compliance expectations.
Primary users	Digital marketers, product managers, UX designers, developers, enterprise teams, CRO specialists, and analysts.
Release approach	Phase 1 core authentication; Phase 2 enhanced UX and accessibility; Phase 3 enterprise features and analytics.
Plan owner	QA/Test Lead (to be assigned)

> **Scope caveat:** The PRD is a broad product vision and does not specify several implementation policies (for example, password rules, lockout thresholds, session duration, exact browser support, or SSO provider configuration). These are recorded as assumptions and must be confirmed before final test-case sign-off; tests must not invent product behavior.

Success measures from the PRD

- Authentication success rate target: **95% or higher** for eligible attempts.
- Login page load target: **under 2 seconds** on standard connections.
- User satisfaction target: **90% or higher**.
- Zero successful brute-force attacks or unauthorized access incidents.
- 100% adherence to applicable security audit requirements; reduce login-related support tickets by 20%.

2. Scope

In scope

- Login page rendering, branding, responsive layout, light/dark theme, auto-focus, clickable labels, and loading feedback.
- Email/password validation, authentication success/failure, actionable errors, remember-me behavior, session creation/timeout, and logout/session invalidation where supported.
- Password reset request, secure reset token lifecycle, recovery email, password policy, and post-reset login.
- Optional MFA enrollment/challenge/recovery and enterprise SSO paths (SAML/OAuth or the configured protocols), when enabled for the release.
- Rate limiting and account/session protection; secure transport, storage, token handling, and privacy/compliance checks.
- Transition to the VWO dashboard, preservation of appropriate navigation context, login analytics, and login assistance/support integration.
- Keyboard and screen reader accessibility, high contrast, WCAG 2.1 AA evaluation, cross-browser/device behavior, and performance/load/availability checks.

Out of scope for this release unless explicitly enabled

- Biometric and adaptive authentication, progressive web app behavior, personalized login content, and future A/B optimization features.
- Functional validation of the full VWO dashboard after login beyond verifying successful, authorized handoff and basic landing-page availability.
- Third-party identity-provider internals, marketing platform internals, or production penetration testing; integration contracts and safe test-environment behavior remain in scope.

3. Test Strategy

1. **Risk first:** Prioritize credential handling, unauthorized access, recovery-token abuse, session security, brute-force protections, and SSO/MFA before visual polish.
2. **Traceability:** Map every planned scenario to one or more requirement IDs in section 10. Link execution records and defects to the same IDs.
3. **Layered validation:** Validate business rules at unit/service level, authentication and integrations at API/contract level, then critical user journeys in browser E2E.
4. **Positive and negative coverage:** Include valid, invalid, boundary, expired, replayed, interrupted, and unavailable-service cases. At least 40% of detailed scenarios should exercise negative/error behavior.
5. **Privacy-safe testing:** Use synthetic accounts and data, redact credentials/tokens from logs, and verify that analytics and error responses do not expose secrets or personal data.

6. **Shift left and repeat:** Review requirements and security design early; run smoke checks per build, focused regression on changes, and full release regression before go-live.
7. **Release phasing:** Gate Phase 1 on core authentication/recovery; Phase 2 on responsive/accessibility; Phase 3 on SSO/MFA/enterprise controls and analytics where those features are part of the release.

Prioritization

Priority	Definition	Examples
P0 / Critical	Security or availability failure can expose accounts/data or prevent broad access.	Unauthorized login, token/session compromise, TLS bypass, authentication outage, severe brute-force weakness.
P1 / High	Core journey or mandated control fails for a material user segment.	Valid login blocked, reset unusable, MFA/SSO broken for configured tenant, keyboard access blocked.
P2 / Medium	Partial degradation with a viable workaround.	Theme inconsistency, noncritical browser layout issue, delayed analytics event.
P3 / Low	Cosmetic or low-impact issue with no meaningful workflow impact.	Minor spacing or copy issue.

Test design techniques

- Equivalence classes for email, password, account status, identity-provider responses, and recovery-token states.
- Boundary analysis for configured password limits, session expiry, token lifetime, rate-limit thresholds, viewport breakpoints, and performance targets.
- Decision tables for valid/invalid credentials × account state × MFA/SSO policy × rate-limit state.
- State-transition testing for login, MFA challenge, password reset, session renewal/expiry, logout, and retry/lockout workflows.
- Exploratory testing for usability, browser/device differences, localization readiness, and error recovery.

4. Test Types and Levels

Level/type	Coverage focus	Execution	Priority
Unit/component	Validation rules, password policy, state transitions, error mapping, token utilities, accessibility semantics.	Automated in CI; developer-owned with QA review.	P1
API/service	Authentication/reset endpoints, rate limiting, session lifecycle, authorization, error contracts, analytics events.	Automated on each build and in regression.	P0/P1
Integration/contract	Email delivery, MFA service, configured SSO providers, VWO dashboard handoff, support/analytics integrations.	Automated contract tests plus controlled end-to-end integration checks.	P0/P1
End-to-end/UI	Critical user journeys across login, remember me, reset, MFA/SSO, responsive interface, and error recovery.	Automated smoke/regression; manual exploratory testing.	P1
Security/privacy	Authentication and authorization controls, abuse resistance, secure transport/storage, session protections, data minimization, audit evidence.	Automated checks and approved security assessment in a non-production environment.	P0
Performance/reliability	Page load under 2 seconds, concurrent login attempts, graceful degradation, availability and regional behavior.	Baseline and load/stress/soak tests with agreed traffic model.	P1

Level/type	Coverage focus	Execution	Priority
Accessibility	Keyboard, screen reader, focus order, labels, validation announcements, contrast, WCAG 2.1 AA.	Automated checks plus manual assistive-technology evaluation.	P1
Compatibility/visual	Supported browsers, mobile/tablet/desktop sizes, light/dark theme, rendering and touch targets.	Automated browser matrix plus targeted visual/manual checks.	P2
Acceptance/UAT	Business acceptance of core and enterprise journeys, help paths, and success measures.	Product, support, security, and representative business users.	P1

Security testing is authorized only against designated test systems and accounts, with agreed scope, rate limits, monitoring, and rollback contacts.

5. Entry and Exit Criteria

Entry criteria

- PRD and acceptance criteria reviewed; open questions affecting test outcomes are resolved or explicitly accepted as release assumptions.
- Build deployed to a stable, isolated test environment; smoke test passes and test endpoints are identifiable.
- Authentication, password, session, rate-limit, MFA, and SSO policies/configurations are documented for the target release.
- Test accounts, synthetic data, mail capture, identity-provider sandbox, and monitoring/log access are available.
- Supported browser/device matrix, performance workload, data-retention rules, and security-test authorization are agreed.
- Test cases are reviewed and traceable; defect triage severity/priority rules and release contacts are defined.

Exit criteria

- 100% of P0 and P1 scenarios executed; at least 95% of all planned release scenarios executed, with remaining tests waived and risk-accepted.
- All P0/P1 tests pass; all failures are resolved or formally accepted with owner, mitigation, and expiry date.
- No open Critical/High security defects, unauthorized access paths, or unresolved compliance blockers.
- Core login, reset, and applicable MFA/SSO regression passes on the agreed supported browser/device matrix.
- Page-load target under 2 seconds is met under the agreed standard-connection measurement; agreed load and availability targets are met.
- WCAG 2.1 AA assessment has no unresolved critical/blocking violations; remaining exceptions are documented and approved.
- Authentication success rate, security monitoring, and analytics event correctness meet approved acceptance criteria; no secrets appear in client or server logs.
- Test summary, requirement traceability, defect disposition, residual risks, and stakeholder sign-offs are published.

6. Test Environment

Environment/component	Required configuration	Verification
Web application	Production-like, isolated VWO login and dashboard handoff; feature flags/configuration match release.	Build/version recorded; smoke login and route checks pass.

Environment/component	Required configuration	Verification
Transport/security	HTTPS/TLS enforced; test certificates and security headers configured consistently with intended deployment.	Redirect, certificate, protocol, cookie, and header checks.
Identity/authentication	Test authentication service, session store, rate limiting, MFA and SSO sandboxes as applicable.	Known test identities and deterministic provider outcomes available.
Email/recovery	Non-delivering mail sink or approved test mailbox; reset-link inspection without sending to real customers.	Delivery, content, expiry, single-use, and invalidation behavior verified.
Clients	Supported desktop browsers and mobile/tablet viewports; exact versions to be set by product support policy.	Matrix recorded with browser, OS, viewport, and device class.
Observability	Sanitized application/security logs, metrics, audit events, and analytics test stream.	Confirm event correlation and ensure passwords/tokens/secret values are redacted.
Load testing	Isolated load environment with production-like scaling and a representative, approved login workload.	Baseline latency, error rate, concurrency, and resource telemetry captured.

7. Test Data Requirements

- Create synthetic accounts for active, unverified (if applicable), disabled, locked/throttled, MFA-enabled, SSO-managed, and password-expired states.
- Use valid and invalid email classes: normal valid address, malformed syntax, empty, overlong, internationalized if supported, and duplicate/existing identity.
- Cover password inputs at policy boundaries (below/at/above each configured rule), incorrect/correct credentials, leading/trailing whitespace, Unicode, and maximum accepted length. Exact policy comes from product/security configuration.
- Prepare reset tokens that are valid, expired, already used, malformed, tampered, and invalidated after a subsequent reset; keep tokens out of screenshots and logs.
- Prepare MFA cases for valid/invalid/expired/replayed challenge, recovery path, clock drift where relevant, and unavailable provider; use sandbox secrets only.
- Prepare SSO scenarios for successful assertion, denied/cancelled login, invalid signature/state/nonce, expired assertion, unprovisioned user, and IdP outage, as applicable to configured protocols.
- Generate load-test identities with non-personal synthetic attributes; ensure data is reset or expired after each run.
- Use only authorized test accounts; never use real customer credentials or expose passwords, reset links, session cookies, or MFA secrets in reports.

8. Risk Analysis

Score = likelihood × impact. Likelihood uses 1 (Low), 2 (Medium), 3 (High); impact uses 1 (Low), 2 (Medium), 3 (High), 4 (Critical). Scores 6+ are high priority.

ID	Risk	Likelihood	Impact	Score	Mitigation / test response
R-01	Credential compromise, account enumeration, or weak abuse controls permit unauthorized access.	Medium	Critical	8 · High	Prioritize negative/auth-abuse checks, generic responses where required, throttling verification, security review, and alert validation.

ID	Risk	Likelihood	Impact	Score	Mitigation / test response
R-02	Session or reset-token flaws allow replay, fixation, theft, or access after expiry/logout.	Medium	Critical	8 · High	Test token lifecycle/state transitions, cookie attributes, invalidation, expiry, and authorized session handling.
R-03	Unspecified password, timeout, lockout, or rate-limit policies cause inconsistent behavior or gaps.	High	High	9 · High	Obtain approved configuration before sign-off; parameterize boundary tests and attach evidence to the version tested.
R-04	SSO/MFA provider failures or configuration mismatches block enterprise users or weaken controls.	Medium	High	6 · High	Contract tests, sandbox scenarios, outage/denial paths, and tenant-specific configuration validation.
R-05	Peak login demand or regional latency violates performance/availability goals.	Medium	High	6 · High	Agree workload/SLA; load, stress, soak, and regional checks with monitoring and recovery observations.
R-06	Keyboard, screen-reader, contrast, or mobile issues prevent users from accessing the service.	Medium	High	6 · High	Manual WCAG 2.1 AA evaluation, assistive technology checks, viewport/device matrix, and defect gate.
R-07	Analytics/logging captures credentials or sensitive recovery/session data.	Low	Critical	4 · Medium	Inspect payloads/logs, enforce redaction, and test privacy-safe failure/success events.
R-08	Recovery email or support integration failure leaves users unable to regain access.	Medium	Medium	4 · Medium	Test delivery, delay/bounce/provider failure, useful guidance, and support escalation path.

9. Test Schedule and Estimation

Planning estimate for one QA lead/tester, with part-time engineering, security, product, and infrastructure support. Estimates are in person-days and should be recalibrated against team velocity and the final feature scope.

Activity	Optimistic	Most likely	Pessimistic	PERT estimate
Requirements review, risk analysis, and traceability	1	2	3	2.0
Test design and stakeholder review	2	4	6	4.0
Environment, integrations, and test-data setup	2	3	5	3.2
Automation implementation/maintenance	4	7	11	7.2
Functional, API, integration, and cross-browser execution	3	5	8	5.2
Security, accessibility, and performance validation	3	5	8	5.2
Defect retest, regression, and release reporting	2	3	5	3.2
Total	**17**	**29**	**46**	**30.0 person-days**

PERT formula: (Optimistic + 4 × Most likely + Pessimistic) / 6. A 20% contingency yields approximately **36 person-days**. This estimate excludes product development, external certification, and unplanned provider onboarding.

Indicative window	Work	Exit checkpoint
Days 1–2	Requirement clarification, risk review, traceability, test design.	Policies and acceptance criteria agreed.
Days 3–5	Environment/test data setup; unit/API/contract automation begins.	Environment and integration smoke passed.

Indicative window	Work	Exit checkpoint
Days 6–10	Functional, integration, E2E, browser/device, and accessibility execution.	Core journey and regression evidence available.
Days 11–13	Security, load/performance, defect fixes and focused retest.	Risk and nonfunctional gates reviewed.
Days 14–15	Final regression, UAT support, residual-risk review, release report.	Exit criteria and stakeholder sign-offs recorded.

10. Coverage Matrix

Requirement catalogue

ID	Requirement	Priority	PRD source area
FR-01	Email/password authentication; reject invalid credentials and handle account state safely.	P0	Authentication system
FR-02	Real-time/blur validation for email and password; actionable authentication errors.	P1	User input validation
FR-03	Remember-me option and secure session creation, timeout, renewal, and invalidation.	P0	Session management/current interface
FR-04	Password reset/recovery with secure, time-limited token and configured password requirements.	P1	Password management
FR-05	Optional MFA challenge and recovery for accounts/tenants where enabled.	P0*	Authentication system
FR-06	Enterprise SSO using configured protocol/provider; secure handoff and failure handling.	P0*	Authentication/integrations
FR-07	Successful login transitions to authorized VWO dashboard and preserves permitted context.	P1	User journey/integration
FR-08	Responsive, branded login UI with loading states, auto-focus, clickable labels, theme options, and signup path.	P1	User experience/current state
FR-09	Keyboard navigation, screen-reader support, high contrast, and accessible validation feedback.	P1	Accessibility features
FR-10	Login success/failure analytics and login assistance/support integration without sensitive-data leakage.	P2	Integration requirements
NFR-01	Login page loads in under 2 seconds on standard connections.	P1	Performance requirements
NFR-02	Secure transmission, password storage, session/token handling, and brute-force rate limiting.	P0	Security specifications
NFR-03	GDPR/CCPA and enterprise security/audit requirements are met for login data handling.	P0	Compliance standards
NFR-04	99.9% availability target and support for thousands of concurrent login attempts.	P1	Scalability
NFR-05	WCAG 2.1 AA accessibility and agreed browser/device compatibility.	P1	Accessibility/compatibility

*Treat MFA/SSO as release-gating P0 when enabled or required by a tenant; otherwise record as not applicable for that release and retain coverage for the next applicable phase.

Requirements traceability

Req ID	Requirement summary	Planned cases	Test types	Status
FR-01	Primary authentication and account-state handling	TC-01–TC-06	Unit, API, E2E, security	Planned
FR-02	Input validation and error handling	TC-07–TC-10	Unit, UI, accessibility	Planned
FR-03	Remember me and session lifecycle	TC-11–TC-14	API, integration, E2E, security	Planned
FR-04	Password reset and policy	TC-15–TC-19	API, integration, E2E, security	Planned
FR-05	MFA challenge/recovery	TC-20–TC-22	Integration, E2E, security	Planned*
FR-06	Enterprise SSO	TC-23–TC-25	Contract, integration, E2E, security	Planned*
FR-07	Authorized dashboard handoff/context	TC-26–TC-27	Integration, E2E	Planned
FR-08	Responsive, branded UI and loading/theme/signup	TC-28–TC-31	UI, compatibility, visual	Planned
FR-09	Accessibility	TC-32–TC-34	Accessibility, manual, automated	Planned
FR-10	Analytics/support integrations and privacy	TC-35–TC-36	Integration, privacy	Planned
NFR-01	Page load performance	TC-37	Performance	Planned
NFR-02	Transport/storage/session security and rate limiting	TC-05, TC-12–TC-14, TC-18, TC-22, TC-24, TC-38–TC-40	Security, API, performance	Planned
NFR-03	Privacy, compliance, and auditability	TC-36, TC-40	Privacy, audit	Planned
NFR-04	Availability and concurrent scale	TC-41–TC-42	Load, stress, reliability	Planned
NFR-05	WCAG and browser/device compatibility	TC-29–TC-34	Accessibility, compatibility	Planned

Representative test case matrix

These are scenario-level tests, not step-by-step test scripts. Detailed steps, expected messages, and exact boundary values require the final product policies and UX copy.

ID	Scenario / expected result	Req ID	Type	Priority	Automation
TC-01	Submit valid active-user credentials; authentication succeeds and authorized dashboard is reached.	FR-01, FR-07	E2E	P1	Yes
TC-02	Submit incorrect password; access is denied and safe, actionable feedback is shown.	FR-01, FR-02	API/E2E	P0	Yes
TC-03	Submit unknown email; access is denied without disclosing whether an account exists, where policy requires.	FR-01, NFR-02	API/security	P0	Yes

ID	Scenario / expected result	Req ID	Type	Priority	Automation
TC-04	Submit empty email, empty password, and both empty; required-field validation is correct and accessible.	FR-02, FR-09	UI/unit	P1	Yes
TC-05	Repeat failed attempts at and beyond configured rate/lockout boundaries; control activates, responses remain safe, and monitoring records the event.	FR-01, NFR-02	API/security	P0	Yes
TC-06	Attempt login for disabled/locked account; access is denied and approved recovery/support guidance is provided.	FR-01, FR-10	API/E2E	P1	Yes
TC-07	Enter malformed email and leave field focus; field-level validation appears at the specified interaction point.	FR-02	UI	P1	Yes
TC-08	Exercise email boundaries (empty, malformed, valid, maximum configured length); reject invalid values without breaking the form.	FR-02	Unit/UI	P2	Yes
TC-09	Verify error response for service outage/timeout; user can retry without duplicate or ambiguous submission state.	FR-02, FR-08	Integration/E2E	P1	Yes
TC-10	Verify password strength/policy feedback at configured boundaries without exposing password value in errors or telemetry.	FR-02, FR-04, NFR-02	Unit/security	P1	Yes
TC-11	Use remember-me on and off; persistence matches approved policy and shared/public-device guidance is clear.	FR-03	E2E	P1	Yes
TC-12	Verify session timeout, renewal, logout, and post-logout access at configured boundaries; expired/revoked sessions cannot access protected content.	FR-03, NFR-02	API/E2E/security	P0	Yes
TC-13	Inspect session cookies/tokens for approved secure attributes, rotation, and non-exposure to client-readable storage as required by design.	FR-03, NFR-02	Security	P0	Partial
TC-14	Attempt session fixation/reuse across authentication state changes; session identifiers rotate and stale sessions are rejected.	FR-03, NFR-02	Security	P0	Partial
TC-15	Request password reset for eligible account; generic safe response is returned and reset message reaches test mailbox.	FR-04	Integration/E2E	P1	Yes
TC-16	Request reset for unknown account; response avoids account enumeration and does not reveal identity state.	FR-04, NFR-02	API/security	P0	Yes
TC-17	Use valid reset token once; password changes and new credentials work according to policy.	FR-04	E2E	P1	Yes
TC-18	Use expired, replayed, malformed, tampered, or superseded reset token; reset is denied and token cannot be reused.	FR-04, NFR-02	API/security	P0	Yes
TC-19	Submit new password just below/at/above each configured policy boundary; accept/reject exactly as documented.	FR-04	Unit/API	P1	Yes
TC-20	For MFA-enabled account, valid challenge succeeds; invalid/expired/replayed challenge is rejected with safe retry/recovery handling.	FR-05, NFR-02	Integration/E2E	P0*	Yes
TC-21	MFA provider unavailable or user cancels challenge; no authenticated session is granted and a recoverable message is shown.	FR-05	Integration/E2E	P1*	Yes
TC-22	Verify MFA recovery path, attempt throttling, and recovery-code single-use behavior if supported.	FR-05, NFR-02	Security	P0*	Partial

ID	Scenario / expected result	Req ID	Type	Priority	Automation
TC-23	Configured enterprise SSO happy path validates response and returns user to permitted destination.	FR-06, FR-07	Contract/E2E	P0*	Yes
TC-24	Reject invalid signature/state/nonce, expired assertion, and unauthorized redirect; no session is created.	FR-06, NFR-02	Security/integration	P0*	Yes
TC-25	Handle IdP denial, cancellation, unprovisioned identity, or outage with safe error and no partial session.	FR-06	Integration/E2E	P1*	Yes
TC-26	After login, verify dashboard destination is authorized and any return URL is validated against open-redirect abuse.	FR-07, NFR-02	E2E/security	P0	Yes
TC-27	Verify permitted session context/recent activity behavior across return login without exposing another user's data.	FR-07	Integration/E2E	P1	Yes
TC-28	Verify loading/disabled-submit states prevent duplicate submissions and recover after success, failure, or timeout.	FR-08	UI/E2E	P1	Yes
TC-29	Verify responsive layout and touch targets at supported mobile, tablet, and desktop viewport breakpoints.	FR-08, NFR-05	Compatibility	P1	Partial
TC-30	Verify light/dark theme, branding, readable contrast, and theme consistency across supported browsers.	FR-08, NFR-05	Visual/compatibility	P2	Partial
TC-31	Verify auto-focus, clickable labels, registration link, and mobile email keyboard behavior without stealing focus unexpectedly.	FR-08, FR-09	UI/accessibility	P2	Partial
TC-32	Complete all login and reset flows using keyboard only; focus order, visible focus, and error recovery are usable.	FR-09, NFR-05	Accessibility	P1	Partial
TC-33	Validate accessible names, labels, instructions, live error announcements, and status/loading feedback with screen readers.	FR-09, FR-08	Accessibility	P1	Partial
TC-34	Evaluate contrast, zoom/reflow, semantics, and keyboard interaction against WCAG 2.1 AA; document exceptions.	FR-09, NFR-05	Accessibility	P1	Partial
TC-35	Verify success/failure analytics and support actions fire once with correct non-sensitive metadata and no credentials/tokens.	FR-10, NFR-03	Integration/privacy	P1	Yes
TC-36	Inspect client/server logs, audit records, and analytics payloads; sensitive authentication/recovery values are absent or redacted.	FR-10, NFR-03	Privacy/security	P0	Partial
TC-37	Measure login page load on agreed standard connections; meet the under-2-second target at the agreed percentile and measurement point.	NFR-01	Performance	P1	Yes
TC-38	Verify HTTP redirects to HTTPS and TLS/security configuration meets approved baseline; credentials never travel over plaintext.	NFR-02	Security	P0	Yes
TC-39	Verify password storage uses approved salted, industry-standard one-way hashing; plaintext/password-equivalent data is not stored.	NFR-02	Security	P0	Partial
TC-40	Review consent, retention, deletion, audit, and access controls for login-related personal data against approved GDPR/CCPA/enterprise requirements.	NFR-03	Privacy/compliance	P0	Manual
TC-41	Run representative concurrent login workload at agreed expected/peak levels; verify latency, error rate, and recovery objectives.	NFR-04	Load	P1	Yes
TC-42	Run approved stress/soak and regional availability checks; observe graceful degradation, alerting, and recovery toward 99.9% service target.	NFR-04	Reliability	P1	Yes

11. Deliverables

- This approved test plan, requirement catalogue, risk register, and traceability matrix.
- Detailed manual test cases and automated unit/API/contract/E2E checks linked to FR/NFR IDs.
- Environment and synthetic-data setup records, browser/device matrix, and run configuration.
- Execution evidence, performance/accessibility/security results, and defect reports with severity and reproduction evidence.
- Release test summary: execution/pass/fail/blocked counts, requirement coverage, open defects, residual risks, waivers, and recommendation.
- Stakeholder acceptance and security/privacy/compliance sign-offs where required.

12. Roles and Responsibilities

Role	Responsibilities
Product Manager / Product Owner	Clarify scope, policies, acceptance criteria, success measures, release priorities, and approve residual product risks.
QA / Test Lead	Own this plan, test design/traceability, risk-based execution, defect triage, evidence, and release test recommendation.
Developers	Provide unit/component coverage, testability, fixes, technical policy details, and support root-cause analysis.
Security / Privacy	Approve authorized security scope, authentication/session controls, threat coverage, privacy handling, and compliance evidence.
Platform / SRE / Operations	Provision environments, observability, rate limits, load-test support, availability targets, and incident/recovery contacts.
Identity / Integration owners	Provide SSO/MFA/email sandbox configuration, contract expectations, provider failure scenarios, and integration support.
Accessibility specialist	Review WCAG 2.1 AA coverage and perform assistive-technology evaluation.
Support / UAT representatives	Validate recovery guidance, support pathways, and representative business-user acceptance journeys.

Assumptions and open questions for approval

1. What exact password complexity/length policy, history/reuse rules, and password-expiry behavior apply?
2. What are the session idle/absolute timeouts, remember-me duration, cookie/token requirements, and logout/revocation semantics?
3. What are the login/reset/MFA attempt thresholds, throttling response, lockout duration, and account recovery rules?
4. Which MFA methods, enrollment rules, fallback/recovery mechanisms, and tenant policies are in this release?
5. Which SSO providers/protocols and identity provisioning policies are supported; is social login in scope?
6. Which browsers/versions, operating systems, mobile devices, regions, and locales are officially supported?
7. For the under-2-second load metric, what percentile, network profile, geographic location, and measurement boundary define acceptance?
8. What peak concurrent-user model, availability measurement window, recovery objective, and planned maintenance exclusions apply to the 99.9% target?

9. Which analytics events, consent requirements, retention periods, and GDPR/CCPA/enterprise audit controls are mandatory?
10. Are the theme options, signup path, analytics/support links, and recent-activity context included in the release under test?

> **Approval gate:** Resolve or formally accept these questions before finalizing detailed expected results and release exit status. Any unimplemented optional feature should be marked not applicable with a product-approved rationale, not counted as a passing test.

Prepared from the supplied “Product Requirements Document: VWO Login Dashboard.” This is a planning baseline, not a substitute for approved security policy, detailed acceptance criteria, or release-specific configuration.