

# CSS Briefing

Total points 0/0

Lets explore CSS

Email \*

845819369@qq.com

✓ What is the main difference between inline styles and the **<style>** tag? \*

- ☐ Inline styles allow you to write CSS in a separate file, whereas the **<style>** tag embeds CSS directly within HTML opening tags.
- ☐ There is no difference between inline styles and the **<style>** tag.
- ☐ The **<style>** tag allow you to write CSS in a separate file, whereas inline styles embed CSS directly within HTML opening tags.
- ☒ Inline styles directly modify individual HTML elements using a style attribute, whereas the **<style>** tag allows you to write CSS in a dedicated section of the HTML file. ✓

**Feedback***Correct*

✓ The **font-weight** property will adjust which of the following? \*

- ☐ The spacing between letters.
- ☐ How transparent text appears.
- ☒ How thin or thick text appears.
- ☐ How small or large text appears.

#### Feedback



Correct! *font-weight* sets the thickness of letters in text.

✓ What is the purpose of the HTML **<link>** tag when it comes to styling a page? \*

- ☒ To link a specific stylesheet file to an HTML file so that the styles get applied on the page.
- ☐ To make sure that all links are styled correctly on the page.
- ☐ To make sure that your inline styles are applied correctly.
- ☐ To determine the specificity of CSS rules.

#### Feedback



Correct! *<link>* is used to connect stylesheets to HTML files.



✓ The following HTML code attempts to use inline styling to change the color of the paragraph text, but fails to do so. Why? \*

`<p color="red;">I am learning to code!</p>`

- ☐ The value of the color attribute must be changed to style: red;.
- ☐ The color red should be set to Red instead.
- ☐ A `<style>` tag must be used to add styles to HTML.
- ☒ The color attribute is invalid. It should be changed to style and then set equal to color: red;: `<p style="color:red;">`.

#### Feedback



Correct! The style attribute is used to add inline styles to HTML elements.

✓ Which of the following is a correct CSS declaration? \*

- ☐ "color": green
- ☒ color: green;
- ☐ color = green;
- ☐ font green

#### Feedback



Correct! Properties and values are separated by a colon (:), and declarations should end with a semicolon (;).

✓ The following code attempts to style a paragraph using the `<style>` tag, but fails to do so. Why?

```
<head>
```

```
  <style>
```

```
    <p style="color:red;">I'm learning to code!</p>
```

```
  </style>
```

```
</head>
```

☐ The style attribute of the `<p>` element can be removed because the `<style>` tag replaces it.

☐ The color attribute must be changed to color-style.

☐ You must use either inline styles or the `<style>` tag but not both.

☒ The contents of the `<style>` tag must be CSS code, not HTML code. The `<p>` will not appear at all.

Feedback

Correct



✓ Separating HTML and CSS into their own files helps accomplish which of the following?

- ☐ More specific CSS selectors.
- ☒ Separating HTML structure from CSS style makes the code in both languages easier to read and maintain.
- ☐ Enhances webpage load time.
- ☐ Better-looking CSS styles.

Feedback

 Correct!



✓

What will the color of the links be after applying the CSS below? \*

✓

```
body {  
  color: green;  
}
```

```
.main-content a {  
  color: blue;  
}
```

```
a {  
  color: red !important;  
}
```

☐ Black

☐ Blue

☐ Green

☒ Red

Feedback

👏  
Correct! The !important rule will override the other color declarations.

✓ What does the **font-family** property control? \*

- ☐ It defines and creates a new font.
- ☒ The typeface used by the element.
- ☐ It allows you to group all the fonts you use in your stylesheet into a family.

Feedback



*font-family allows you to apply a typeface to a particular selector.*

✓ What does the **<style>** HTML tag allow? \*

- ☒ Writing one or more CSS rules in CSS syntax inside an HTML file.
- ☐ It links external CSS files to the HTML document.
- ☐ It is the only way to apply styles inside an HTML file.
- ☐ It automatically adds common styles to your webpage.

Feedback

*Correct*

✓ What does the **font-family** property control? \*

- ☐ It defines and creates a new font.
- ☒ The typeface used by the element.
- ☐ It allows you to group all the fonts you use in your stylesheet into a family.

#### Feedback



*font-family allows you to apply a typeface to a particular selector.*





✓

What will the color of the links be after applying the CSS below? \*

✓

```
body {  
  color: green;  
}
```

```
.main-content a {  
  color: blue;  
}
```

```
a {  
  color: red !important;  
}
```

☐ Black

☐ Blue

☐ Green

☒ Red

Feedback

👍  
Correct! The !important rule will override the other color declarations.

✓ What is the most specific selector in the code below? \*

```
p {
```

```
}
```

```
#side-bar {
```

```
}
```

```
.main-content {
```

```
}
```

```
.main-content p {
```

```
}
```

- ☐ .main-content
- ☒ #side-bar
- ☐ .main-content p
- ☐ p

### Feedback



Correct! ID selectors with # are more specific than any selector only using element type and/or class selectors.



✓ Which of the following is a correct CSS declaration? \*

- ☐ "color": green
- ☒ color: green;
- ☐ color = green;
- ☐ font green

#### Feedback



Correct! Properties and values are separated by a colon (:), and declarations should end with a semicolon (;).

✓ The following HTML code attempts to use inline styling to change the color of the paragraph text, but fails to do so. Why?  
<p color="red;">I am learning to code!</p>

- ☐ The value of the color attribute must be changed to style: red;.
- ☐ The color red should be set to Red instead.
- ☐ A <style> tag must be used to add styles to HTML.
- ☒ The color attribute is invalid. It should be changed to style and then set equal to color: red;: <p style="color:red;">.

#### Feedback



Correct! The style attribute is used to add inline styles to HTML elements.



✓ The following code attempts to style a paragraph using the `<style>` tag, but fails to do so. Why? \*

```
<head>
```

```
  <style>
```

```
    <p style="color:red;">I'm learning to code!</p>
```

```
  </style>
```

```
</head>
```

- ☐ The style attribute of the `<p>` element can be removed because the `<style>` tag replaces it.
- ☐ The color attribute must be changed to color-style.
- ☐ You must use either inline styles or the `<style>` tag but not both.
- ☒ The contents of the `<style>` tag must be CSS code, not HTML code. The `<p>` will not appear at all.

Feedback

Correct

✓ What is the purpose of the HTML `<link>` tag when it comes to styling a page? \*

- ☒ To link a specific stylesheet file to an HTML file so that the styles get applied on the page.
- ☐ To make sure that all links are styled correctly on the page.
- ☐ To make sure that your inline styles are applied correctly.
- ☐ To determine the specificity of CSS rules.

Feedback



Correct! `<link>` is used to connect stylesheets to HTML files.

✓ Which of the following will set an element's background to an image? \*

- ☒ background-image: url("image.jpg");
- ☐ background-image: url = "image.jpg";
- ☐ background-image: "image.jpg";
- ☐ background.image = url("image.jpg");

#### Feedback



Correct! The background-image takes a url() with an image path.



✓ What is the most specific selector in the code below? \*

```
p {
```

```
}
```

```
#side-bar {
```

```
}
```

```
.main-content {
```

```
}
```

```
.main-content p {
```

```
}
```

- ☐ .main-content
- ☒ #side-bar
- ☐ .main-content p
- ☐ p

### Feedback



Correct! ID selectors with # are more specific than any selector only using element type and/or class selectors.



✓ What does the **<style>** HTML tag allow? \*

- ☒ Writing one or more CSS rules in CSS syntax inside an HTML file.
- ☐ It links external CSS files to the HTML document.
- ☐ It is the only way to apply styles inside an HTML file.
- ☐ It automatically adds common styles to your webpage.

Feedback

Correct

✓ The **font-weight** property will adjust which of the following? \*

- ☐ The spacing between letters.
- ☐ How transparent text appears.
- ☒ How thin or thick text appears.
- ☐ How small or large text appears.

Feedback



Correct! *font-weight* sets the thickness of letters in text.

✓ Separating HTML and CSS into their own files helps accomplish which of the following? \*

- ☐ More specific CSS selectors.
- ☒ Separating HTML structure from CSS style makes the code in both languages easier to read and maintain.
- ☐ Enhances webpage load time.
- ☐ Better-looking CSS styles.

Feedback



Correct!

✓ Which of the following will set an element's background to an image? \*

- ☒ `background-image: url("image.jpg");`
- ☐ `background-image: url = "image.jpg";`
- ☐ `background-image: "image.jpg";`
- ☐ `background.image = url("image.jpg");`

Feedback



Correct! The `background-image` takes a `url()` with an image path.



✓ What is the main difference between inline styles and the <style> tag? \*

- ☐ Inline styles allow you to write CSS in a separate file, whereas the <style> tag embeds CSS directly within HTML opening tags.
- ☐ There is no difference between inline styles and the <style> tag.
- ☐ The <style> tag allow you to write CSS in a separate file, whereas inline styles embed CSS directly within HTML opening tags.
- ☒ Inline styles directly modify individual HTML elements using a style attribute, whereas the <style> tag allows you to write CSS in a dedicated section of the HTML file.

Feedback

Correct

This form was created inside Sacred Heart International College.

Google Forms









