PILLAI COLLEGE OF ENGINEERING
(Autonomous)

A+
NAAC

Implementation of Smart Agriculture for Efficient Cultivation in Hilly Regions

***644 -** Jay Padwal* ***645 -** Jyotiraditya Wakale*

***647 -** Yash Deokar* ***648 -** Chaitanya R Patil*

***Guide :** Dr. Aboli Khedkar*

***Institution :** Pillai College Of Engineering*



Introduction

The Challenge

Agriculture in hilly regions faces challenges such as uneven terrain, water scarcity, and difficulty in monitoring crops.

The Solution

Smart agriculture uses IoT and sensor technology to monitor environmental conditions and automate irrigation.

This Project

This project uses a ESP32 with sensors to improve farming efficiency and reduce manual effort.



Problem Statement

> ***Farmers in hilly regions face difficulties in managing irrigation and monitoring crop conditions. Traditional irrigation methods waste water and require continuous manual effort. There is a need for an automated system that monitors soil and environmental conditions to optimise irrigation and improve crop productivity.***

🌄 *Hilly Terrain*

Uneven land makes irrigation management extremely difficult for farmers.

💧 *Water Wastage*

Traditional irrigation methods waste water without precision control.

👨‍🌾 *Manual Effort*

Continuous manual monitoring is required, increasing labour burden.

📉 *Low Productivity*

Lack of monitoring leads to suboptimal crop productivity outcomes.

Why We Chose This Problem



Agricultural Need

Relieve repetitive manual effort and eliminate the guesswork involved in crop-specific watering to prevent both over-irrigation and severe drought stress.



Engineering Opportunity

Leveraging modern IoT capabilities (like the ESP32) allows us to replace complex mechanical systems with smart, sensor-driven embedded control logic.



Low-Cost Solution

Provide profound, automated agricultural assistance while strictly maintaining affordability and simplicity for small farmers operating in remote locations.

Existing System Architecture
(Traditional Agriculture)

1. Field / Environment (No Sensors)



Farm condition, soil moisture, temperature, humidity, etc. (checked manually)

2. Manual Observation



Farmer visits the field and checks crop and soil conditions manually.

3. Decision Making



Decisions are taken based on experience and estimation.

4. Manual Action (Irrigation, Fertilization etc.)



Manual irrigation, fertilization and other activities are performed.

5. Result (Low Efficiency)



Lower productivity, high resource wastage, and more manual effort.

Process Repeats Periodically (No Real-time Feedback)

Limitations of Existing System

- No real-time monitoring of parameters
- High dependency on manual labor
- Inefficient use of water and fertilizers
- Lower productivity due to inaccurate decisions
- Difficult to manage in remote / hilly areas
- No data storage or analysis for improvement

EXISTING IRRIGATION METHODS

Manual / Traditional Method

Low Initial Cost
Minimal equipment required at startup.

Labor Intensive
Requires constant, exhausting human presence.

Inefficient Water Use
Prone to severe overwatering and underwatering.

Poor Yield Optimization
Lacks crucial data on exact soil moisture and weather.

Commercial Smart Systems

High Precision
Excellent real-time monitoring and automation capabilities.

Extremely Expensive
Capital and setup costs are completely out of reach.

High Complexity
Requires highly specialized installation and maintenance.

Terrain Inflexible
Rigidly designed only for large, flat agricultural tracts.

OBJECTIVES OF THE PROJECT

01 Monitor soil moisture, temperature, and environmental conditions.

02 Automate irrigation based on soil moisture level.

03 Reduce water wastage and manual effort.

04 Improve crop productivity in hilly regions.

05 Enable remote monitoring of agricultural fields.

SYSTEM ARCHITECTURE

Closed-Loop Processing


Our proposed architecture is built on a direct feedback loop to ensure complete automation and reliability.

01 Data Acquisition
Multiple sensors capture real-time soil and ambient conditions.

02 Central Processing
The ESP32 evaluates incoming data against thresholds.

03 Actuation
Relay-controlled pump provides precise water delivery.

04 Monitoring
Dual feedback via local LCD and remote Web Dashboard.



HARDWARE SELECTION



ESP32 Controller

Chosen for its built-in Wi-Fi, abundant 12-bit ADC pins (eliminating the need for external ICs), dual-core processing, and low power consumption profile.



Environmental Sensors

Utilizing a Capacitive Soil Moisture Sensor (corrosion-resistant), DHT22 (temp/humidity), LDR (light), and a dedicated analog Water Level Sensor.



Actuation & Display

A 5V Single-Channel Relay securely isolates the 12V DC water pump circuit, while a 16x2 I2C LCD provides immediate, on-site system status.

HARDWARE CIRCUIT DESIGN

The circuit design prioritizes component safety, isolated power stages, and precise analog readings.

ADC Inputs

Sensors map directly to GPIO 32, 34, and 35, eliminating the need for external MCP conversion chips.


I2C Bus Integration

The 16x2 LCD is cleanly connected via standard hardware SDA (GPIO 21) and SCL (GPIO 22) lines.

Power Isolation

The ESP32 3.3V logic safely triggers the 5V relay. The relay acts strictly as an isolated switch, protecting the control board from the high-draw 12V pump power supply.

HARDWARE SYSTEM SCHEMATIC




Proposed Methodology

Install Sensors

Process Data

ESP32 analyzes readings



Collect Data

Measure moisture, temperature, light

Activate Pump

SYSTEM ALGORITHM

Continuous Autonomous Loop

The firmware is structured without blocking delays, utilizing a continuous execution cycle.

1. Initialize

Hardware setup and establish Wi-Fi connection.

2. Read


Poll all analog and digital sensors simultaneously.

3. Decide

Execute the cascading logic gates (Water Level → Soil Moisture).

4. Actuate & Post

Trigger relay, update local LCD, push to cloud.



IOT WEB DASHBOARD

Local Web Server Architecture

Real-Time Monitoring


Displays soil moisture, temperature, humidity, light intensity, water level, and pump status.

Wi-Fi-Based Remote Access

The ESP32 hosts the web dashboard, which can be accessed through a web browser on a laptop, PC, or smartphone using the ESP32 IP address.

Smart Irrigation Control

Provides automatic/manual water pump control based on soil moisture and water-level conditions.



IOT WEB DASHBOARD



DEVELOPMENT METHODOLOGY

System Implementation Pipeline — ESP32 Central Controller

STAGE 01
System Planning

Establish agricultural requirements and define target thresholds for soil moisture, humidity, temperature, and water level.

STAGE 02
Hardware Integration

Interface ESP32 DevKit V1 with DHT11/22, LDR, soil moisture, and water-level sensors, 16×2 I2C LCD, and relay module.

STAGE 03
Sensor Data Acquisition

Continuously scan, read, and collect environmental and soil metrics from the physical sensor array.

STAGE 04 [CORE]
Data Processing

The ESP32 microcontroller processes incoming readings and calculates irrigation decisions in real-time.

STAGE 05
Irrigation Control

Trigger water pump relay as determined by ESP32 logic. Output system status and sensor telemetry onto local 16×2 LCD.

STAGE 06
Wi-Fi Dashboard

ESP32 serves local web panel. Read live data, monitor parameters, and trigger manual/auto pump override via IP address.

TESTING & EVALUATION PLAN

1. Sensor Testing

Verify readings from soil moisture, DHT11/22, LDR, and water-level sensors under ambient conditions.

2. Hardware & ESP32

Validate ESP32 controller operations, 16×2 I2C LCD logs, relays, and proper power distribution.

3. Auto Irrigation

Test pump triggering logic; turning ON below soil dryness threshold and staying OFF when moisture is optimal.

4. Web Dashboard

Verify local Wi-Fi AP hosting, browser client response, live sensor feeds, and manual pump override actions.

5. Evaluation

Analyze overall hardware response, telemetry accuracy, fail-safe water level actions, and endurance run reliability.

EXPECTED OUTCOMES & KEY GOALS

- Accurate Data
- Reliable Control
- Proper Irrigation
- Real-Time Monitoring
- Stable Operation

BENEFITS & FUTURE SCOPE

Implementation of Smart Agriculture for Efficient Cultivation in Hilly Regions

PROJECT BENEFITS

Efficient Water Management

Automatic irrigation based on soil moisture drastically minimizes unnecessary water consumption.

Real-Time Monitoring

Instant updates on soil moisture, temperature, humidity, light, water level, and pump status.

Reduced Manual Effort

Automated sensing and precise **Smart Irrigation** control eliminate the need for continuous labor.

Suitable for Hilly Regions

Custom-tailored for sloped terrains with limited water resources where conventional, manual gravity feeding methods often fail.

FUTURE SCOPE

AI Crop Prediction

ML models to recommend ideal crops based on historical terrain telemetry.

Weather Integration

Incorporate real-time rain forecasting to dynamically adjust active watering schedules.

Solar-Powered System

Transition to complete off-grid solar harvesting for remote and rugged operations.


Advanced IoT Analytics

Long-term cloud-free data storage and advanced on-device predictive analytics.

Multi-Zone Smart Irrigation Expansion

Developing localized solenoid valve routing networks to allow the central controller to isolate and manage up to 8 distinct micro-climate farming zones independently from a single source node.

SYSTEM DATA PIPELINE



THANK YOU

A practical approach toward affordable agricultural automation.

ESP32 CONTROLLER • IOT CLOUD • EFFICIENT IRRIGATION