CHAPTER 2

LITERATURE SURVEY

2.1 Overview of AI-Based Chatbot Systems

Research on conversational intelligence originates from the foundational work of Turing, who reframed intelligence as the ability of a machine to exhibit human-like conversational behavior rather than internal reasoning processes [1]. This perspective continues to influence the evaluation of modern conversational systems, particularly in service-oriented domains such as tourism, where user interaction and communication quality are critical.

Early conversational systems such as ELIZA demonstrated that users could easily attribute intelligence and agency to machines based on simple rule-based text responses [2]. Despite lacking memory, contextual understanding, or reasoning capability, ELIZA revealed the psychological effectiveness of conversational interfaces. However, its limitations emphasized the gap between symbolic rule-based systems and the data-driven approaches used in contemporary chatbot applications.

PARRY extended this line of research by incorporating emotional modelling through handcrafted rules, simulating paranoid behaviour and enabling limited affective interaction [3]. This work laid early foundations for sentiment-aware systems, which remain relevant in modern tourism chatbots where user satisfaction and emotional context play important roles.



Figure 3 Evolution of Conversational Agents

2.2 Rule-Based and Hybrid Chatbot Architectures

The ALICE chatbot popularized the Artificial Intelligence Markup Language (AIML), enabling developers to design deterministic and predictable conversational behaviour [4]. Rule-based frameworks such as AIML proved effective in enterprise environments requiring controlled responses, compliance, and consistency. Even though neural models offer greater flexibility, rule-based systems continue to be useful in tourism and booking applications where accuracy and reliability are prioritized.

Survey studies indicate that chatbot architecture selection depends heavily on task complexity, domain specificity, and data availability [5]. In tourism-related platforms, hybrid chatbot architectures are commonly adopted, combining rule-based logic for structured tasks such as reservations and cancellations with natural language understanding components for open-ended user queries. Classification frameworks introduced in later studies further distinguish chatbots based on interaction strategy, domain scope, and functional capabilities, allowing clearer comparison across applications [6].



Figure 4 Taxonomy of Chatbot Types

2.3 Neural and Transformer-Based Dialogue Systems

Advancements in machine learning have shifted chatbot research away from traditional slot-filling approaches toward neural dialogue systems capable of handling noisy, ambiguous, and multilingual inputs [7]. These capabilities are particularly important in tourism environments that serve diverse international visitors with varying linguistic backgrounds.

Transformer-based language models further enhanced conversational systems by enabling long-context reasoning, semantic generalization, and zero-shot learning [8]. While these models significantly improve conversational fluency and coverage, researchers caution against challenges such as hallucinated responses, cultural bias, and



Figure 2.2: Research Gaps in Existing Museum Chatbot Systems

misinformation, which can negatively impact trust in tourism-related recommendations.

2.4 Chatbots in Tourism and Smart Destination Ecosystems

Recent literature increasingly positions chatbots as integral components of broader digital tourism ecosystems rather than isolated applications [9]. These systems are often integrated with mobile applications, booking platforms, Internet of Things (IoT) devices, and smart city infrastructures to provide seamless visitor experiences.

Comparative studies of chatbot development platforms highlight variations in customization, scalability, privacy guarantees, and NLP capabilities, emphasizing the risk of vendor lock-in when relying on proprietary cloud-based services [10]. To address this, modular chatbot architectures have been proposed, allowing independent evolution of language understanding, response generation, and backend integration components [11].

Such modularity supports adaptation to seasonal trends, policy updates, and regulatory requirements common in tourism management.

Human feedback mechanisms have also gained importance in aligning chatbot behaviour with ethical, commercial, and operational constraints, thereby improving user trust and reducing deployment risk [12].

2.5 Smart Tourism Frameworks and Research Gaps

Within destination marketing research, the 6A framework has been widely used to assess tourism competitiveness across dimensions such as attractions, accessibility, amenities, and activities [13]. Conversational agents can support these dimensions by offering personalized, context-aware information and real-time logistical assistance.

Smart tourism studies further identify chatbots as primary digital touchpoints for personalization, analytics, and visitor engagement [14]. More recent research explores the use of large language models in multilingual search, itinerary planning, and recommendation systems while simultaneously raising concerns regarding privacy, transparency, and explainability [15].

Despite these advancements, existing research reveals gaps in fully integrated systems that combine conversational intelligence with operational functionalities such as ticket booking, cancellation, and exhibit navigation using privacy-conscious architectures. These limitations motivate the development of the proposed MuseumBot system, which integrates hybrid chatbot mechanisms with local AI deployment and structured backend services.

REFERENCES:

1. A. M. Turing, “Computing machinery and intelligence,” Mind, vol. 59, no. 236, pp. 433–460, 1950.

2. J. Weizenbaum, “ELIZA—A computer program for the study of natural language communication between man and machine,” Communications of the ACM, vol. 9, no. 1, pp. 36–45, 1966.

3. K. M. Colby, S. Weber, and F. D. Hilf, “Artificial paranoia,” Artificial Intelligence, vol. 2, no. 1, pp. 1–25, 1971.

4. R. S. Wallace, “The anatomy of ALICE,” in Parsing the Turing Test, Springer, Berlin, Heidelberg, 2009, pp. 181–210.

5. S. Hussain, O. A. Sianaki, and N. Ababneh, “A survey on conversational agents,” in Proceedings of the International Conference on Advanced Information Networking and Applications Workshops (WAINA), Springer, 2019, pp. 946–956.

6. D. Braun and F. Matthes, “Towards a framework for classifying chatbots,” in Proceedings of the 21st International Conference on Enterprise Information Systems (ICEIS), 2019, pp. 572–579.

7. R. Sarikaya, “The technology behind personal digital assistants: An overview,” IEEE Signal Processing Magazine, vol. 34, no. 1, pp. 67–81, Jan. 2017.

8. G. Caldarini, S. Jaf, and K. McGarry, “A literature survey of recent advances in chatbots,” Information, vol. 13, no. 1, p. 41, 2022.

9. E. Adamopoulou and L. Moussiades, “Chatbots: History, technology, and applications,” Machine Learning with Applications, vol. 2, pp. 1–20, 2020.

10. S. Perez-Soler, E. Guerra, J. de Lara, and A. Gonzalez-Perez, “Choosing a chatbot

development tool," IEEE Software, vol. 38, no. 4, pp. 94–103, Jul.–Aug. 2021.

11. S. Srivastava and T. V. Prabhakar, "A reference architecture for applications with conversational components," in Proceedings of the IEEE International Conference on Software Engineering and Service Science (ICSESS), 2019, pp. 1–6.

12. L. Ouyang et al., "Training language models to follow instructions with human feedback," arXiv preprint arXiv:2203.02155, 2022.

13. D. Buhalis, "Marketing the competitive destination of the future," Tourism Management, vol. 21, no. 1, pp. 97–116, 2000.

14. D. Buhalis and A. Amaranggana, "Smart tourism destinations enhancing tourism experience through personalisation of services," in Proceedings of the ENTER Conference, Springer, 2015, pp. 377–389.

15. I. Carvalho and S. Ivanov, "ChatGPT for tourism: Applications, benefits, and risks," *T ourism Review*, vol. 79, no. 2, pp. 290–303,2024.

16. P. Lewis et al., "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, pp. 9459–9474, 2020.

17. T. B. Brown et al., "Language models are few-shot learners," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 33, pp. 1877–1901, 2020.

18. A. Vaswani et al., "Attention is all you need," in *Advances in Neural Information Processing Systems (NIPS)*, vol. 30, pp. 5998–6008, 2017.

19. J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of deep bidirectional transformers for language understanding," in *Proceedings of NAACL-HLT*, 2019, pp. 4171–4186.

20. S. Varitimiadis, K. Kotis, D. Spiliotopoulos, and C. Vassilakis, "'Talking' triples to

museum chatbots," in *Proceedings of the International Workshop on Chatbots at CONVERSATIONS*, 2020, pp. 1–10.

21. K. Zhou, Z. Sinha, and Y. Liu, "An AI chatbot based on user interaction over a knowledge base," in *Proceedings of the IEEE International Conference on Big Data (BigData)*, 2020, pp. 4133–4138.

22. M. Galvagno and G. Raciti, "Chatbots and service: A systematic literature review," *Journal of Service Theory and Practice*, vol. 31, no. 3, pp. 346–378, 2021.

23. A. Chou, C.-H. Tsai, and Y.-C. Chen, "Leveraging retrieval-augmented generation for culturally inclusive chatbots: Design insights and user perceptions," in *Proceedings of the IEEE International Symposium on Robot and Human Interactive Communication (RASSE)*, 2024.

24. F. Bertacchini, E. Bilotta, and P. Pantano, "Shopping with a robotic companion," *Computers in Human Behavior*, vol. 77, pp. 382–395, 2017.

25. M. Niculescu, B. van Dijk, A. Nijholt, H. Li, and S. L. See, "Making social robots more attractive: The effects of voice pitch, humor and empathy," *International Journal of Social Robotics*, vol. 5, no. 2, pp. 171–186, 2013.

26. R. Dale, "The return of the chatbots," *Natural Language Engineering*, vol. 22, no. 5, pp. 811–817, 2016.